

SARL DPR AXXAM

Registre de Fabrication

Imprimé le 06/09/2026 à 15:15

D a t e	H e u r e	R é f.	P r o d u i t f i n i	Q t é p r o d u i t e	Matières consommées	C o û t t o t a l (D A)	C o û t u n i t a i r e (D A)	S a i s i p a r	O b s e r v a t i o n s
2026-09-06	14:03	DPR	CONCEPTION	239	AILE PLASTIQUE x1 @ 2 447,60 = 2 447,60 ; AIR INTAKE MOUNTING x4 @ 344,25 = 1 377,00 ; ANTICHOC RESSORT x1 @ 2 597,36 = 2 597,36 ; ASSIETTE DE SELLETTE (AXE SELLETTE) x4 @ 2 189,76 = 8 759,04 ; AXE DE FREIN x4 @ 815,94 = 3 263,76 ; BAGUE RESSORT x4 @ 1 098,27 = 4 393,08 ; BAGUE SUSPENSION x4 @ 3 166,90 = 12 667,60 ; BARE DE SUSPENSION x1 @ 5 006,99 = 5 006,99 ; BARRE DE DIRECTION x1 @ 5 158,86 = 5 158,86 ; BARRE STABILISATRICE x1 @ 5 335,19 = 5 335,19 ; BOLT x1 @ 1 283,67 = 1 283,67 ; BOUCHON VASE DE FREIN x3 @ 817,43 = 2 452,29 ; BOULON x1 @ 2 321,72 = 2 321,72 ; BRAKE CHAMBER T24 M16*1.5 PORT x1 @ 1 075,38 = 1 075,38 ; BRAKE DRUM x1 @ 11 600,53 = 11 600,53 ; BRAKE DRUM (TAMBOUR DE FREIN) x1 @ 12 198,92 = 12 198,92 ; BRIDE DE RESSORT x2 @ 1 315,84 = 2 631,68 ; CACHE MOYEU x1 @ 13 903,19 = 13 903,19 ; CALE x3 @ 9 149,30 = 27 447,90 ; CALLE BALANCIER x2 @ 1 599,10 = 3 198,20 ; CAMSHAFT REPAR KIT x1 @ 593,18 = 593,18 ; CAPTEUR x4 @ 1 628,38 = 6 513,52 ; CLUTCH SERVO x1 @ 7 153,27 = 7 153,27 ; COFFRE A EXTINCTEUR EN PLASTIQUE 9KG x1 @ 2 263,76 = 2 263,76 ; CONTAINER LOCK x1 @ 2 635,88 = 2 635,88 ; CORNIERE x1 @ 153,97 = 153,97 ; CORNIERE 24*24*1.8MM x2 @ 123,16 = 246,32 ; COUSSIN SUSPENSION D'ESSIEU x2 @ 3 754,76 = 7 509,52 ; CRIC HYDRAULIQUE x2 @ 11 239,49 = 22 478,98 ; DISQUE DE FREIN x3 @ 9 196,45 = 27 589,35 ; ECROU x2 @ 2 055,73 = 4 111,46 ; ELECTRODE x1 @ 1 250,00 = 1 250,00 ; ENSEMBLE SILEN BLOC POUR SRB 52 ENS= 16 PCS x1 @ 1 850,47 = 1 850,47 ; ENSEMBLE SILEN BLOC POUR SRB 52 ENS= 6 PCS x1 @ 2 463,84 = 2 463,84 ; EQUALIZER x2 @ 3 296,77 = 6 593,54 ; EQUALIZER BUSH x2 @ 1 201,37 = 2 402,74 ; EQUALIZER BUSH (SILENBLOC) x1 @ 750,93 = 750,93 ; FER CARRE 11 x6 @ 92,65 = 555,90 ; FEU DE POSITION x3 @ 1 108,67 = 3 326,01 ; FLEXIBLE D'AIR ROUGE ID : 80MM 22TURNS M16 FITTING x1 @ 376,16 = 376,16 ; FLIXIBLE x3 @ 2 156,62 = 6 469,86 ; GARDE DE BOUE x4 @ 2 561,06 = 10 244,24 ; GARNITURE x1 @ 19 211,61 = 19 211,61 ; GARNITURE DE FREIN x1 @ 2 657,70 = 2 657,70 ; HEA 120 PERCEE ET COUPEE x2 @ 143,39 = 286,78 ; HUB CAP x4 @ 353,03 = 1 412,12 ; IPE 120 x0,5 @ 154,90 = 77,45 ; IPE 80 x1 @ 155,37 = 155,37 ; JOINT DE REPARATION x2 @ 3 210,44 = 6 420,88 ; JOINT ETANCHEITE x2 @ 1 243,63 = 2 487,26 ; JOINT SPI GUIDE x2 @ 664,71 = 1 329,42 ; KIT DE REPARATION x2 @ 1 011,72 = 2 023,44 ; LAME 2 x2 @ 13 218,91 = 26 437,82 ; LAME MT1602200 x2 @ 1 920,40 = 3 840,80 ; LEAF SPRING x2 @ 14 050,40 = 28 100,80 ; LETTER D x2 @ 584,22 = 1 168,44 ; LEVIER ETRIER x1 @ 2 854,54 = 2 854,54 ; MANUAL SLACK ADJUSTER -5HOLE 37 TEETH x2 @ 1 165,00 = 2 330,00 ; PIENTURE INDUSTRIEL x1 @ 1 203,00 = 1 203,00 ; PIPE DE CONNEXION x2 @ 1 886,01 = 3 772,02 ; POIGNEE x1 @ 1 392,73 = 1 392,73 ; RACCORT D 17 x1 @ 262,77 = 262,77 ; REGLEURE DE FREIN x1 @ 2 043,56 = 2 043,56 ; REGULEUR DE FREIN x1 @ 309,90 = 309,90 ; RESSORT x4 @ 29 977,47 = 119 909,88 ; RESSORT DE MACHOIRE DE FREIN x1 @ 96,89 = 96,89 ; RESSORT ELE x2 @ 33,11 = 66,22 ; ROLLER BRAKE SHOE x2 @ 99,66 = 199,32 ; ROULEMENT x3 @ 1 896,90 = 5 690,70 ; SEAL (JOINT SPIE) x2 @ 529,14 = 1 058,28 ; SILENBLOC SUSPENSION x1 @ 693,30 = 693,30 ; SOLENBLOC x2 @ 131,41 = 262,82 ; SPRING (RESSORT DE RAPPEL) x2 @ 121,03 = 242,06 ; SPRING BRAKE CHAMBER x1 @ 2 616,76 = 2 616,76 ; SPRING EE BUSH x1 @ 612,55 = 612,55 ; SPRING EYE BUSH x1 @ 658,34 = 658,34 ; STRUCTURE METALLIQUE IPE x3 @ 151,26 = 453,78 ; SUPPORT x2 @ 3 063,82 = 6 127,64 ; SUPPORT FIXATION x1 @ 1 635,96 = 1 635,96 ; SUPPORT RESSORT x1 @ 1 613,53 = 1 613,53 ; SUPPORT SUSPENSION x3 @ 1 337,26 = 4 011,78 ; THRUST WASHER x1 @ 491,32 = 491,32 ; TOLE NOIRE LAC x5 @ 118,07 = 590,35 ; TORQUE ROAD x3 @ 7 851,89 = 23 555,67	52708,42	22051,0	Ahcene	
TO				23		52			

T A U X				9			7 0 1 8 , 4 2			
------------------	--	--	--	---	--	--	---------------------------------	--	--	--