
```

% Part 1
%Generating a filled Julia set

fixpt1 = (1 + sqrt(6))/2; %First fixed point
fixpt2 = (1 - sqrt(6))/2; %Second fixed point

colormap([1 0 0; 1 1 1]); %Points numbered 1 (inside) will be colored
red;
                                % those numbered 2 (outside) will be white.
M = 2*ones(141,361); %Initialize array of point colors to 2 (white).

for j=1:141                                %Try initial values with imaginary parts
    between
        y = -.7 + (j-1)*.01;                % -0.7 and -.7
        for i=1:361                        %and with real parts between
            x = -1.8 + (i-1)*.01; % -1.8 and 1.8
            z = x +1i*y;                    %1i is the MATLAB symbol for sqrt(-1)
            phi = @(z) z^2 - 1.25; %using handle function is much faster
            than inline of original code
            zk = z;
            iflag1 = 0; %iflag1 and iflag2 count the number of iterations
            iflag2 = 0; % when a root is within 1.e-6 of a fixed pt
            kount = 0; %kount is the total number of iterations

            while kount < 100 && abs(zk) < 2 && iflag1 < 5 && iflag2 < 5
                kount = kount+1;
                zk = phi(zk); %This is the fixed pt iteration.


                err1 = abs(zk-fixpt1); %Test for convergence to fixpt1.
                if err1 < 1.e-6, iflag1 = iflag1 + 1; else iflag1 = 0; end

                err2 = abs(zk-fixpt2); %Test for convergence to fixpt2.
                if err2 < 1.e-6, iflag2 = iflag2 + 1; else iflag2 = 0; end

            end
            if iflag1 >= 5 || iflag2 >= 5 || kount >= 100 %If orbit is
            bounded, set
                M(j,i) = 1;
            end
        end
    end
end

image([-1.8 1.8],[-.7 .7],M), %This plots the results.
axis xy %If you don't do this, vertical axis is inverted

```



Published with MATLAB® R2019b