MATPOWER Interior Point Solver MIPS 1.3.1 User's Manual

Ray D. Zimmerman Hongye Wang June 20, 2019

Contents

1	Intr	roduction	5
	1.1	Background	5
	1.2	License and Terms of Use	6
	1.3	Citing MIPS	7
	1.4	MIPS Development	7
2	Get	ting Started	8
	2.1	System Requirements	8
	2.2	Installation	8
	2.3	Documentation	9
3	MI	PS – MATPOWER Interior Point Solver	10
	3.1	Example 1	12
	3.2	Example 2	14
	3.3	Quadratic Programming Solver	16
	3.4	Primal-Dual Interior Point Algorithm	17
		3.4.1 Notation	17
		3.4.2 Problem Formulation and Lagrangian	18
		3.4.3 First Order Optimality Conditions	19
		3.4.4 Newton Step	20
A	ppen	dix A MIPS Files and Functions	23
\mathbf{A}		dix B PARDISO – Parallel Sparse Direct and Multi-Recursive rative Linear Solvers	24
\mathbf{A}	ppen	dix C Release History	25
	C.1	Version 1.0 – released Feb 7, 2011	25
	C.2	Version 1.0.1 – released Apr 30, 2012	25
	C.3	Version 1.0.2 – released Nov 5, 2013	25
		Version 1.1 – released Dec 17, 2014	26
	C.5	Version 1.2 – released Mar 20, 2015	26
	C.6	Version 1.2.1 – released Jun 1, 2016	27
	C.7	Version 1.2.2 – released Dec 16, 2016	27
		Version 1.3 – released Oct 30, 2018	28
		Version 1.3.1 – released Jun 20, 2019	29

References 30

List of Tables

3-1	Input Arguments for mips		11
3-2	Output Arguments for mips		12
3-3	Options for mips		13
A-1	MIPS Files and Functions		23

1 Introduction

1.1 Background

MATPOWER Interior Point Solver (MIPS) is a package of MATLAB language M-files¹ for solving non-linear programming problems (NLPs) using a primal dual interior point method. The MIPS project page can be found at:

https://github.com/MATPOWER/mips

MIPS is based on code written in C language [1] by Hongye Wang as a graduate student at Cornell University for optimal power flow applications [2, 3]. It was later ported to the MATLAB language by Ray D. Zimmerman of PSERC² at Cornell University for use in MATPOWER [4, 5].

Up until version 6 of MATPOWER, MIPS was distributed only as an integrated part of MATPOWER. After the release of MATPOWER 6, MIPS was split out into a separate project, though it is still included with MATPOWER as its default AC optimal power flow solver.

¹Also compatible with GNU Octave [7].

²http://pserc.org/

1.2 License and Terms of Use

The code in MIPS is distributed under the 3-clause BSD license³ [8]. The full text of the license can be found in the LICENSE file at the top level of the distribution or at https://github.com/MATPOWER/mips/blob/master/LICENSE and reads as follows.

Copyright (c) 1996-2016, Power Systems Engineering Research Center (PSERC) and individual contributors (see AUTHORS file for details). All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

³Versions 1.0 through 1.1 of MIPS were distributed under version 3.0 of the GNU General Public License (GPL) [9] with an exception added to clarify our intention to allow MIPS to interface with MATLAB as well as any other MATLAB code or MEX-files a user may have installed, regardless of their licensing terms. The full text of the GPL can be found at https://www.gnu.org/licenses/gpl-3.0.txt.

1.3 Citing MIPS

We request that publications derived from the use of MIPS explicitly acknowledge that fact by citing the following 2007 paper [2].

```
H. Wang, C. E. Murillo-Sánchez, R. D. Zimmerman, and R. J. Thomas, "On Computational Issues of Market-Based Optimal Power Flow," Power Systems, IEEE Transactions on, vol. 22, no. 3, pp. 1185–1193, August 2007. doi: 10.1109/TPWRS.2010.2051168
```

The MATPOWER Interior Point Solver (MIPS) User's Manual [6] should also be cited explicitly in work that refers to or is derived from its content. The citation and DOI can be version-specific or general, as appropriate. For version 1.3.1, use:

```
R. D. Zimmerman, H. Wang. MATPOWER Interior Point Solver (MIPS) User's Manual, Verision 1.3.1. 2018. [Online]. Available: https://matpower.org/docs/MIPS-manual-1.3.1.pdf doi: 10.5281/zenodo.3251014
```

For a version non-specific citation, use the following citation and DOI, with $\langle YEAR \rangle$ replaced by the year of the most recent release:

```
R. D. Zimmerman, H. Wang. MATPOWER Interior Point Solver (MIPS) User's Manual. <\(YEAR\)>. [Online]. Available: https://matpower.org/docs/MIPS-manual.pdf
doi: 10.5281/zenodo.3236506
```

A list of versions of the User's Manual with release dates and version-specific DOI's can be found via the general DOI at https://doi.org/10.5281/zenodo.3236506.

1.4 MIPS Development

Following the release of MIPS 1.2.2 (with MATPOWER 6.0), the MIPS project moved to an open development paradigm, hosted on the MIPS GitHub project page:

```
https://github.com/MATPOWER/mips
```

The MIPS GitHub project hosts the public Git code repository as well as a public issue tracker for handling bug reports, patches, and other issues and contributions. There are separate GitHub hosted repositories and issue trackers for MATPOWER, MOST, MIPS and the testing framework used by all of them, MP-Test, all available from https://github.com/MATPOWER/.

2 Getting Started

2.1 System Requirements

To use MIPS 1.3.1 you will need:

- Matlab[®] version 7 (R14) or later⁴, or
- GNU Octave version 3.4 or later⁵
- MP-Test, for running the MIPS test suite.⁶

For the hardware requirements, please refer to the system requirements for the version of Matlab⁷ or Octave that you are using.

In this manual, references to MATLAB usually apply to Octave as well.

2.2 Installation

Installation and use of MIPS requires familiarity with the basic operation of MATLAB or Octave, including setting up your MATLAB path.

Step 1: Clone the repository or download and extract the zip file of the MIPS distribution from the MIPS project page⁸ to the location of your choice. The files in the resulting mips or mipsXXX directory, where XXX depends on the version of MIPS, should not need to be modified, so it is recommended that they be kept separate from your own code. We will use <MIPS> to denote the path to this directory.

Step 2: Add the following directories to your MATLAB or Octave path:

- <MIPS>/lib core MIPS functions
- <MIPS>/lib/t test scripts for MIPS

⁴Matlab is available from The MathWorks, Inc. (https://www.mathworks.com/). Matlab is a registered trademark of The MathWorks, Inc.

⁵GNU Octave [7] is free software, available online at https://www.gnu.org/software/octave/. MIPS 1.3.1 may work on earlier versions of Octave, but it has not been tested on versions prior to 3.4.

⁶MP-Test is available at https://github.com/MATPOWER/mptest.

⁷https://www.mathworks.com/support/sysreq/previous_releases.html

⁸https://github.com/MATPOWER/mips

Step 3: At the MATLAB prompt, type test_mips to run the test suite and verify that MIPS is properly installed and functioning. The result should resemble the following:

```
>> test_mips
t_mplinsolve.....ok (6 of 44 skipped)
t_mips......ok
t_mips_pardiso....ok (60 of 60 skipped)
t_qps_mips.....ok
All tests successful (170 passed, 66 skipped of 236)
Elapsed time 0.09 seconds.
```

2.3 Documentation

And second is the built-in help command. As with the built-in functions and toolbox routines in MATLAB and Octave, you can type help followed by the name of a command or M-file to get help on that particular function. All of the M-files in MIPS have such documentation and this should be considered the main reference for the calling options for each function. See Appendix A for a list of MIPS functions.

⁹The tests require a functioning installation of MP-Test.

3 MIPS – MATPOWER Interior Point Solver

MIPS, that is, the MATPOWER Interior Point Solver, is a primal-dual interior point solver implemented in pure MATLAB code, derived from the MEX implementation of the algorithms included in TSPOPF [1] and described in [2,3].

This solver has application to general nonlinear optimization problems of the following form:

$$\min_{x} f(x) \tag{3.1}$$

subject to

$$g(x) = 0 (3.2)$$

$$h(x) \le 0 \tag{3.3}$$

$$l < Ax < u \tag{3.4}$$

$$x_{\min} \le x \le x_{\max} \tag{3.5}$$

where $f: \mathbb{R}^n \to \mathbb{R}$, $g: \mathbb{R}^n \to \mathbb{R}^m$ and $h: \mathbb{R}^n \to \mathbb{R}^p$.

The solver is implemented by the mips function, which can be called as follows,

```
[x, f, exitflag, output, lambda] = ...
mips(f_fcn, x0, A, l, u, xmin, xmax, gh_fcn, hess_fcn, opt);
```

where the input and output arguments are described in Tables 3-1 and 3-2, respectively. Alternatively, the input arguments can be packaged as fields in a problem struct and passed in as a single argument, where all fields except f_fcn and x0 are optional.

```
[x, f, exitflag, output, lambda] = mips(problem);
```

The calling syntax is nearly identical to that used by fmincon from MATLAB's Optimization Toolbox. The primary difference is that the linear constraints are specified in terms of a single doubly-bounded linear function ($l \le Ax \le u$) as opposed to separate equality constrained ($A_{eq}x = b_{eq}$) and upper bounded ($Ax \le b$) functions. Internally, equality constraints are handled explicitly and determined at run-time based on the values of l and u.

The user-defined functions for evaluating the objective function, constraints and Hessian are identical to those required by fmincon, with one exception described below for the Hessian evaluation function. Specifically, f-fcn should return f as the scalar objective function value f(x), df as an $n \times 1$ vector equal to ∇f and, unless

Table 3-1: Input Arguments for mips[†]

-	
name	description
f_fcn	Handle to a function that evaluates the objective function, its gradients and Hessian [‡] for a given value of x . Calling syntax for this function: [f, df, d2f] = f_fcn(x)
x0	Starting value of optimization vector x .
A, 1, u	Define the optional linear constraints $l \leq Ax \leq u$. Default values for the elements of 1 and u are -Inf and Inf, respectively.
xmin, xmax	Optional lower and upper bounds on the x variables, defaults are -Inf and Inf, respectively.
${ t gh_fcn}$	Handle to function that evaluates the optional nonlinear constraints and their gradients for a given value of x . Calling syntax for this function is: $[h, g, dh, dg] = gh_f cn(x)$
hess_fcn	Handle to function that computes the Hessian [‡] of the Lagrangian for given values of x , λ and μ , where λ and μ are the multipliers on the equality and inequality constraints, g and h , respectively. The calling syntax for this function is: Lxx = hess_fcn(x, lam, cost_mult), where $\lambda = \text{lam.eqnonlin}$, $\mu = \text{lam.ineqnonlin}$ and cost_mult is a parameter used
	to scale the objective function
opt	Optional options structure with fields, all of which are also optional, described in Table 3-3.
problem	Alternative, single argument input struct with fields corresponding to arguments above.

 $^{^{\}dagger}$ All inputs are optional except f_fcn and x0.

gh_fcn is provided and the Hessian is computed by hess_fcn, d2f as an $n \times n$ matrix equal to the Hessian $\frac{\partial^2 f}{\partial x^2}$. Similarly, the constraint evaluation function gh_fcn must return the $m \times 1$ vector of nonlinear equality constraint violations g(x), the $p \times 1$ vector of nonlinear inequality constraint violations h(x) along with their gradients in dg and dh. Here dg is an $n \times m$ matrix whose j^{th} column is ∇g_j and dh is $n \times p$, with j^{th} column equal to ∇h_j . Finally, for cases with nonlinear constraints, hess_fcn returns the $n \times n$ Hessian $\frac{\partial^2 \mathcal{L}}{\partial x^2}$ of the Lagrangian function

$$\mathcal{L}(x,\lambda,\mu,\sigma) = \sigma f(x) + \lambda^{\mathsf{T}} g(x) + \mu^{\mathsf{T}} h(x)$$
(3.6)

for given values of the multipliers λ and μ , where σ is the cost_mult scale factor for the objective function. Unlike fmincon, mips passes this scale factor to the Hessian evaluation function in the 3rd argument.

The use of nargout in f_fcn and gh_fcn is recommended so that the gradients and Hessian are only computed when required.

[‡] If gh_fcn is provided then hess_fcn is also required. Specifically, if there are nonlinear constraints, the Hessian information must provided by the hess_fcn function and it need not be computed in f_fcn.

Table 3-2: Output Arguments for mips

name	description				
х	solution vector				
f	final objective function value				
exitflag	exit flag				
	1 - first orde	er optimality conditions satisfied			
	0 – maximur	m number of iterations reached			
	-1 – numerica	eally failed			
output	output struct	with fields			
	iterations	number of iterations performed			
	hist	struct array with trajectories of the following: feascond,			
		gradcond, compcond, costcond, gamma, stepsize, obj, alphap,			
		alphad			
	message	exit message			
lambda	struct contain	ing the Langrange and Kuhn-Tucker multipliers on the con-			
	straints, with f	fields:			
	eqnonlin	nonlinear equality constraints			
	ineqnonlin	nonlinear inequality constraints			
	$\mathtt{mu_l}$	lower (left-hand) limit on linear constraints			
	$\mathtt{mu}_{-\mathtt{u}}$	upper (right-hand) limit on linear constraints			
	lower	lower bound on optimization variables			
	upper upper bound on optimization variables				

3.1 Example 1

The following code, included as mips_example1.m in <MIPS>lib/t, shows a simple example of using mips to solve a 2-dimensional unconstrained optimization of Rosenbrock's "banana" function¹⁰

$$f(x) = 100(x_2 - x_1^2)^2 + (1 - x_1)^2. (3.7)$$

First, create a MATLAB function that will evaluate the objective function, its gradients and Hessian, for a given value of x. In this case, the coefficient of the first term is defined as a paramter a.

¹⁰https://en.wikipedia.org/wiki/Rosenbrock_function

Table 3-3: Options for \mathtt{mips}^\dagger

name	default	description
opt.verbose	0	controls level of progress output displayed
		0 – print no progress info
		1 – print a little progress info
		2 – print a lot of progress info
		3 – print all progress info
opt.feastol	10^{-6}	termination tolerance for feasibility condition
opt.gradtol	10^{-6}	termination tolerance for gradient condition
opt.comptol	10^{-6}	termination tolerance for complementarity condition
opt.costtol	10^{-6}	termination tolerance for cost condition
opt.max_it	150	maximum number of iterations
opt.step_control	0	set to 1 to enable step-size control
opt.sc.red_it	20	max number of step-size reductions if step-control is on
opt.cost_mult	1	cost multiplier used to scale the objective function for improved
		conditioning. Note: This value is also passed as the 3 rd argument to the Hessian evaluation function so that it can appro-
		priately scale the objective function term in the Hessian of the
		Lagrangian.
opt.xi	0.99995	ξ constant used in α updates in (3.46) and (3.47)
opt.sigma	0.33333	centering parameter σ used in γ update in (3.52)
opt.z0	1	used to initialize elements of slack variable Z
opt.alpha_min	10^{-8}	algorithm returns "Numerically Failed" if the α_p or α_d from
ори.атрпаштп	10	(3.46) and (3.47) become smaller than this value
opt.rho_min	0.95	lower bound on ρ_t corresponding to $1 - \eta$ in Fig. 5 in [2]
opt.rho_max	1.05	upper bound on ρ_t corresponding to $1 + \eta$ in Fig. 5 in [2]
opt.mu_threshold	10^{-5}	Kuhn-Tucker multipliers smaller than this value for non-binding
opo.ma_oniconota	10	constraints are forced to zero
opt.max_stepsize	10^{10}	algorithm returns "Numerically Failed" if the 2-norm of the New-
1	-	ton step $\begin{bmatrix} \Delta X \\ \Delta \lambda \end{bmatrix}$ from (3.45) exceeds this value

Then, create a handle to the function, defining the value of the paramter a to be 100, set up the starting value of x, and call the mips function to solve it.

```
>> f_fcn = @(x)banana(x, 100);
>> x0 = [-1.9; 2];
>> [x, f] = mips(f_fcn, x0)
     1
     0
```

3.2 Example 2

The second example¹¹ solves the following 3-dimensional constrained optimization, printing the details of the solver's progress:

$$\min_{x} f(x) = -x_1 x_2 - x_2 x_3 \tag{3.8}$$

subject to

$$x_1^2 - x_2^2 + x_3^2 - 2 \le 0$$
 (3.9)
 $x_1^2 + x_2^2 + x_3^2 - 10 \le 0.$ (3.10)

$$x_1^2 + x_2^2 + x_3^2 - 10 \le 0. (3.10)$$

First, create a MATLAB function to evaluate the objective function and its gradients, 12

¹¹From https://en.wikipedia.org/wiki/Nonlinear_programming#3-dimensional_example.

¹²Since the problem has nonlinear constraints and the Hessian is provided by hess_fcn, this function will never be called with three output arguments, so the code to compute d2f is actually not necessary.

one to evaluate the constraints, in this case inequalities only, and their gradients,

```
function [h, g, dh, dg] = gh2(x)

h = [ 1 -1 1; 1 1 1] * x.^2 + [-2; -10];

dh = 2 * [x(1) x(1); -x(2) x(2); x(3) x(3)];

g = []; dg = [];
```

and another to evaluate the Hessian of the Lagrangian.

Then create a problem struct with handles to these functions, a starting value for x and an option to print the solver's progress. Finally, pass this struct to mips to solve the problem and print some of the return values to get the output below.

```
function mips_example2
problem = struct( ...
    'f_fcn',
                0(x)f2(x), ...
                0(x)gh2(x), ...
    'gh_fcn',
    'hess_fcn', @(x, lam, cost_mult)hess2(x, lam, cost_mult), ...
               [1; 1; 0], ...
    'opt',
               struct('verbose', 2) ...
[x, f, exitflag, output, lambda] = mips(problem);
fprintf('\nf = %g exitflag = %d\n', f, exitflag);
fprintf('\nx = \n');
fprintf('
           %g\n', x);
fprintf('\nlambda.ineqnonlin =\n');
            %g\n', lambda.ineqnonlin);
```

>> mips_example2 MATPOWER Interior Point Solver MIPS, Version 1.3.1, 20-Jun-2019 (using built-in linear solver)							
it	~			gradcond	compcond	costcond	
0	-1		0	1.5	5	0	
1	-5.3250167	1.6875	0	0.894235	0.850653	2.16251	
2	-7.4708991	0.97413	0.129183	0.00936418	0.117278	0.339269	
3	-7.0553031	0.10406	0	0.00174933	0.0196518	0.0490616	
4	-7.0686267	0.034574	0	0.00041301	0.0030084	0.00165402	
5	-7.0706104	0.0065191	0	1.53531e-05	0.000337971	0.000245844	
6	-7.0710134	0.00062152	0	1.22094e-07	3.41308e-05	4.99387e-05	
7	-7.0710623	5.7217e-05	0	9.84879e-10	3.41587e-06	6.05875e-06	
8	-7.0710673	5.6761e-06	0	9.73527e-12	3.41615e-07	6.15483e-07	
Conve	rged!						
f = -	f = -7.07107 exitflag = 1						
x =							
1.	1.58114						
2.23607							
1.	58114						
lambd	lambda.ineqnonlin =						
0	0						
0.	707107						

This example can be found in mips_example2.m. More example problems for mips can be found in t_mips.m, both in <MIPS>lib/t.

3.3 Quadratic Programming Solver

A convenience wrapper function called qps_mips is provided to make it trivial to set up and solve linear programming (LP) and quadratic programming (QP) problems of the following form:

$$\min_{x} \frac{1}{2} x^{\mathsf{T}} H x + c^{\mathsf{T}} x \tag{3.11}$$

subject to

$$l \le Ax \le u \tag{3.12}$$

$$x_{\min} \le x \le x_{\max}. \tag{3.13}$$

Instead of a function handle, the objective function is specified in terms of the paramters H and c of quadratic cost coefficients. Internally, qps_mips passes mips the handle of a function that uses these paramters to evaluate the objective function, gradients and Hessian.

The calling syntax for qps_mips is similar to that used by quadprog from the MATLAB Optimization Toolbox.

```
[x, f, exitflag, output, lambda] = qps_mips(H, c, A, 1, u, xmin, xmax, x0, opt);
```

Alternatively, the input arguments can be packaged as fields in a problem struct and passed in as a single argument, where all fields except H, c, A and 1 are optional.

```
[x, f, exitflag, output, lambda] = qps_mips(problem);
```

Aside from H and c, all input and output arguments correspond exactly to the same arguments for mips as described in Tables 3-1 and 3-2.

As with mips and fmincon, the primary difference between the calling syntax for qps_mips and quadprog is that the linear constraints are specified in terms of a single doubly-bounded linear function $(l \le Ax \le u)$ as opposed to separate equality constrained $(A_{eq}x = b_{eq})$ and upper bounded $(Ax \le b)$ functions.

MIPS also includes another wrapper function qps_matpower that provides a consistent interface for all of the QP and LP solvers it has available. This interface is identical to that used by qps_mips with the exception of the structure of the opt input argument. The solver is chosen according to the value of opt.alg. See the help for qps_matpower for details.

Several examples of using qps_matpower to solve LP and QP problems can be found in t_qps_matpower.m.

3.4 Primal-Dual Interior Point Algorithm

This section provides some details on the primal-dual interior point algorithm used by MIPS and described in [2, 3].

3.4.1 Notation

For a scalar function $f: \mathbb{R}^n \to \mathbb{R}$ of a real vector $X = \begin{bmatrix} x_1 & x_2 & \cdots & x_n \end{bmatrix}^\mathsf{T}$, we use the following notation for the first derivatives (transpose of the gradient):

$$f_X = \frac{\partial f}{\partial X} = \begin{bmatrix} \frac{\partial f}{\partial x_1} & \frac{\partial f}{\partial x_2} & \cdots & \frac{\partial f}{\partial x_n} \end{bmatrix}.$$
 (3.14)

The matrix of second partial derivatives, the Hessian of f, is:

$$f_{XX} = \frac{\partial^2 f}{\partial X^2} = \frac{\partial}{\partial X} \left(\frac{\partial f}{\partial X} \right)^{\mathsf{T}} = \begin{bmatrix} \frac{\partial^2 f}{\partial x_1^2} & \cdots & \frac{\partial^2 f}{\partial x_1 \partial x_n} \\ \vdots & \ddots & \vdots \\ \frac{\partial^2 f}{\partial x_n \partial x_1} & \cdots & \frac{\partial^2 f}{\partial x_n^2} \end{bmatrix}. \tag{3.15}$$

For a vector function $F: \mathbb{R}^n \to \mathbb{R}^m$ of a vector X, where

$$F(X) = \begin{bmatrix} f_1(X) & f_2(X) & \cdots & f_m(X) \end{bmatrix}^\mathsf{T}$$
 (3.16)

the first derivatives form the Jacobian matrix, where row i is the transpose of the gradient of f_i

$$F_X = \frac{\partial F}{\partial X} = \begin{bmatrix} \frac{\partial f_1}{\partial x_1} & \cdots & \frac{\partial f_1}{\partial x_n} \\ \vdots & \ddots & \vdots \\ \frac{\partial f_m}{\partial x_1} & \cdots & \frac{\partial f_m}{\partial x_n} \end{bmatrix}. \tag{3.17}$$

In these derivations, the full 3-dimensional set of second partial derivatives of F will not be computed. Instead a matrix of partial derivatives will be formed by computing the Jacobian of the vector function obtained by multiplying the transpose of the Jacobian of F by a vector λ , using the following notation

$$F_{XX}(\lambda) = \frac{\partial}{\partial X} \left(F_X^{\mathsf{T}} \lambda \right). \tag{3.18}$$

Please note also that [A] is used to denote a diagonal matrix with vector A on the diagonal and e is a vector of all ones.

3.4.2 Problem Formulation and Lagrangian

The primal-dual interior point method used by MIPS solves a problem of the form:

$$\min_{X} f(X) \tag{3.19}$$

subject to

$$G(X) = 0 (3.20)$$

$$H(X) \le 0 \tag{3.21}$$

where the linear constraints and variable bounds from (3.4) and (3.5) have been incorporated into G(X) and H(X). The approach taken involves converting the n_i

inequality constraints into equality constraints using a barrier function and vector of positive slack variables Z.

$$\min_{X} \left[f(X) - \gamma \sum_{m=1}^{n_i} \ln(Z_m) \right] \tag{3.22}$$

subject to

$$G(X) = 0 (3.23)$$

$$H(X) + Z = 0 \tag{3.24}$$

$$Z > 0 \tag{3.25}$$

As the parameter of perturbation γ approaches zero, the solution to this problem approaches that of the original problem.

For a given value of γ , the Lagrangian for this equality constrained problem is

$$\mathcal{L}^{\gamma}(X, Z, \lambda, \mu) = f(X) + \lambda^{\mathsf{T}} G(X) + \mu^{\mathsf{T}} (H(X) + Z) - \gamma \sum_{m=1}^{n_i} \ln(Z_m).$$
 (3.26)

Taking the partial derivatives with respect to each of the variables yields:

$$\mathcal{L}_{X}^{\gamma}(X, Z, \lambda, \mu) = f_{X} + \lambda^{\mathsf{T}} G_{X} + \mu^{\mathsf{T}} H_{X}$$
(3.27)

$$\mathcal{L}_{Z}^{\gamma}(X, Z, \lambda, \mu) = \mu^{\mathsf{T}} - \gamma e^{\mathsf{T}} [Z]^{-1}$$
(3.28)

$$\mathcal{L}_{\lambda}^{\gamma}(X, Z, \lambda, \mu) = G^{\mathsf{T}}(X) \tag{3.29}$$

$$\mathcal{L}_{\mu}^{\gamma}(X, Z, \lambda, \mu) = H^{\mathsf{T}}(X) + Z^{\mathsf{T}}. \tag{3.30}$$

And the Hessian of the Lagrangian with respect to X is given by

$$\mathcal{L}_{XX}^{\gamma}(X,Z,\lambda,\mu) = f_{XX} + G_{XX}(\lambda) + H_{XX}(\mu). \tag{3.31}$$

3.4.3 First Order Optimality Conditions

The first order optimality (Karush-Kuhn-Tucker) conditions for this problem are satisfied when the partial derivatives of the Lagrangian above are all set to zero:

$$F(X, Z, \lambda, \mu) = 0 \tag{3.32}$$

$$Z > 0 \tag{3.33}$$

$$\mu > 0 \tag{3.34}$$

where

$$F(X, Z, \lambda, \mu) = \begin{bmatrix} \mathcal{L}_X^{\gamma \mathsf{T}} \\ [\mu] Z - \gamma e \\ G(X) \\ H(X) + Z \end{bmatrix} = \begin{bmatrix} f_X^{\mathsf{T}} + G_X^{\mathsf{T}} \lambda + H_X^{\mathsf{T}} \mu \\ [\mu] Z - \gamma e \\ G(X) \\ H(X) + Z \end{bmatrix}. \tag{3.35}$$

3.4.4 Newton Step

The first order optimality conditions are solved using Newton's method. The Newton update step can be written as follows:

$$\begin{bmatrix} F_X & F_Z & F_{\lambda} & F_{\mu} \end{bmatrix} \begin{bmatrix} \Delta X \\ \Delta Z \\ \Delta \lambda \\ \Delta \mu \end{bmatrix} = -F(X, Z, \lambda, \mu)$$
 (3.36)

$$\begin{bmatrix} \mathcal{L}_{XX}^{\gamma} & 0 & G_{X}^{\mathsf{T}} & H_{X}^{\mathsf{T}} \\ 0 & [\mu] & 0 & [Z] \\ G_{X} & 0 & 0 & 0 \\ H_{X} & I & 0 & 0 \end{bmatrix} \begin{bmatrix} \Delta X \\ \Delta Z \\ \Delta \lambda \\ \Delta \mu \end{bmatrix} = - \begin{bmatrix} \mathcal{L}_{X}^{\gamma \mathsf{T}} \\ [\mu] Z - \gamma e \\ G(X) \\ H(X) + Z \end{bmatrix}.$$
(3.37)

This set of equations can be simplified and reduced to a smaller set of equations by solving explicitly for $\Delta \mu$ in terms of ΔZ and for ΔZ in terms of ΔX . Taking the 2^{nd} row of (3.37) and solving for $\Delta \mu$ we get

$$[\mu] \Delta Z + [Z] \Delta \mu = -[\mu] Z + \gamma e$$

$$[Z] \Delta \mu = -[Z] \mu + \gamma e - [\mu] \Delta Z$$

$$\Delta \mu = -\mu + [Z]^{-1} (\gamma e - [\mu] \Delta Z). \tag{3.38}$$

Solving the 4th row of (3.37) for ΔZ yields

$$H_X \Delta X + \Delta Z = -H(X) - Z$$

$$\Delta Z = -H(X) - Z - H_X \Delta X. \tag{3.39}$$

Then, substituting (3.38) and (3.39) into the 1st row of (3.37) results in

$$\mathcal{L}_{XX}^{\gamma} \Delta X + G_{X}^{\mathsf{T}} \Delta \lambda + H_{X}^{\mathsf{T}} \Delta \mu = -\mathcal{L}_{X}^{\gamma\mathsf{T}} \\
\mathcal{L}_{XX}^{\gamma} \Delta X + G_{X}^{\mathsf{T}} \Delta \lambda + H_{X}^{\mathsf{T}} (-\mu + [Z]^{-1} (\gamma e - [\mu] \Delta Z)) = -\mathcal{L}_{X}^{\gamma\mathsf{T}} \\
\mathcal{L}_{XX}^{\gamma} \Delta X + G_{X}^{\mathsf{T}} \Delta \lambda \\
+ H_{X}^{\mathsf{T}} (-\mu + [Z]^{-1} (\gamma e - [\mu] (-H(X) - Z - H_{X} \Delta X))) = -\mathcal{L}_{X}^{\gamma\mathsf{T}} \\
\mathcal{L}_{XX}^{\gamma} \Delta X + G_{X}^{\mathsf{T}} \Delta \lambda - H_{X}^{\mathsf{T}} \mu + H_{X}^{\mathsf{T}} [Z]^{-1} \gamma e \\
+ H_{X}^{\mathsf{T}} [Z]^{-1} [\mu] H(X) + H_{X}^{\mathsf{T}} [Z]^{-1} [Z] \mu + H_{X}^{\mathsf{T}} [Z]^{-1} [\mu] H_{X} \Delta X = -\mathcal{L}_{X}^{\gamma\mathsf{T}} \\
(\mathcal{L}_{XX}^{\gamma} + H_{X}^{\mathsf{T}} [Z]^{-1} [\mu] H_{X}) \Delta X + G_{X}^{\mathsf{T}} \Delta \lambda \\
+ H_{X}^{\mathsf{T}} [Z]^{-1} (\gamma e + [\mu] H(X)) = -\mathcal{L}_{X}^{\gamma\mathsf{T}} \\
M \Delta X + G_{X}^{\mathsf{T}} \Delta \lambda = -N \quad (3.40)$$

where

$$M \equiv \mathcal{L}_{XX}^{\gamma} + H_X^{\mathsf{T}} [Z]^{-1} [\mu] H_X \tag{3.41}$$

$$= f_{XX} + G_{XX}(\lambda) + H_{XX}(\mu) + H_X^{\mathsf{T}}[Z]^{-1}[\mu] H_X$$
 (3.42)

and

$$N \equiv \mathcal{L}_X^{\gamma \mathsf{T}} + H_X^{\mathsf{T}} [Z]^{-1} (\gamma e + [\mu] H(X))$$
(3.43)

$$= f_X^{\mathsf{T}} + G_X^{\mathsf{T}} \lambda + H_X^{\mathsf{T}} \mu + H_X^{\mathsf{T}} [Z]^{-1} (\gamma e + [\mu] H(X)). \tag{3.44}$$

Combining (3.40) and the 3^{rd} row of (3.37) results in a system of equations of reduced size:

$$\begin{bmatrix} M & G_X^{\mathsf{T}} \\ G_X & 0 \end{bmatrix} \begin{bmatrix} \Delta X \\ \Delta \lambda \end{bmatrix} = \begin{bmatrix} -N \\ -G(X) \end{bmatrix}. \tag{3.45}$$

The Newton update can then be computed in the following 3 steps:

- 1. Compute ΔX and $\Delta \lambda$ from (3.45).
- 2. Compute ΔZ from (3.39).
- 3. Compute $\Delta \mu$ from (3.38).

In order to maintain strict feasibility of the trial solution, the algorithm truncates the Newton step by scaling the primal and dual variables by α_p and α_d , respectively,

where these scale factors are computed as follows:

$$\alpha_p = \min\left(\xi \min_{\Delta Z_m < 0} \left(-\frac{Z_m}{\Delta Z_m}\right), 1\right) \tag{3.46}$$

$$\alpha_d = \min\left(\xi \min_{\Delta \mu_m < 0} \left(-\frac{\mu_m}{\Delta \mu_m} \right), 1 \right) \tag{3.47}$$

resulting in the variable updates below.

$$X \leftarrow X + \alpha_p \Delta X \tag{3.48}$$

$$Z \leftarrow Z + \alpha_p \Delta Z \tag{3.49}$$

$$\lambda \leftarrow \lambda + \alpha_d \Delta \lambda \tag{3.50}$$

$$\mu \leftarrow \mu + \alpha_d \Delta \mu \tag{3.51}$$

The parameter ξ is a constant scalar with a value slightly less than one. In MIPS, ξ is set to 0.99995.

In this method, during the Newton-like iterations, the perturbation parameter γ must converge to zero in order to satisfy the first order optimality conditions of the original problem. MIPS uses the following rule to update γ at each iteration, after updating Z and μ :

$$\gamma \leftarrow \sigma \frac{Z^{\mathsf{T}} \mu}{n_i} \tag{3.52}$$

where σ is a scalar constant between 0 and 1. In MIPS, σ is set to 0.1.

Appendix A MIPS Files and Functions

This appendix lists all of the files and functions that MIPS provides. In most cases, the function is found in a MATLAB M-file in the lib directory of the distribution, where the .m extension is omitted from this listing. For more information on each, at the MATLAB prompt, simply type help followed by the name of the function. For documentation and other files, the filename extensions are included.

Table A-1: MIPS Files and Functions

name	description		
AUTHORS	list of authors and contributors		
CHANGES	MIPS change history		
CONTRIBUTING.md	notes on how to contribute to the MIPS project		
LICENSE	MIPS license (3-clause BSD license)		
README.md	basic introduction to MIPS		
docs/			
MIPS-manual.pdf	MIPS User's Manual		
MIPS-manual.tex	LaTeX source for MIPS User's Manual		
lib/			
mips	Matpower Interior Point Solver – primal/dual interior point solver for NLP		
mipsver	prints version information for MIPS		
mplinsolve	common linear system solver interface, used by MIPS		
qps_mips	common QP/LP solver interface to MIPS-based solver		
t/			
${\tt mips_example1}$	implements example 1 from MIPS User's Manual		
${\tt mips_example2}$	implements example 2 from MIPS User's Manual		
test_mips	runs full MIPS test suite		
${ t t}$ mips	runs tests for MIPS NLP solver		
${ t t_mips_pardiso}$	runs tests for MIPS NLP solver, using PARDISO as linear solver		
${ t t}$ mplinsolve	tests for mplinsolve		
t_qps_mips	runs tests for qps_mips		

Appendix B PARDISO – Parallel Sparse Direct and Multi-Recursive Iterative Linear Solvers

The PARDISO package is a thread-safe, high-performance, robust, memory efficient and easy to use software for solving large sparse symmetric and non-symmetric linear systems of equations on shared-memory and distributed-memory multiprocessor systems [10,11]. More information is available at https://pardiso-project.org.

When the Matlab interface to PARDISO is installed, PARDISO's solvers can be used to replace the built-in \backslash operator for solving for the Newton update step in MIPS by setting the linsolver option equal to 'PARDISO'. The mplinsolve function can also be called directly to solve Ax = b problems via PARDISO or the built-in solver, depending on the arguments supplied. This interface also gives access to the full range of PARDISO's options. For details, see help mplinsolve and the PARDISO User's Manual at https://pardiso-project.org/manual/manual.pdf.

Appendix C Release History

The full release history can be found in CHANGES.md or online at https://github.com/MATPOWER/mips/blob/master/CHANGES.md.

C.1 Version 1.0 – released Feb 7, 2011

Documentation found in Appendix A of the MATPOWER 4.0 User's Manual, available online.¹³

Changes

- Licensed under the GNU General Public License (GPL).
- Added compatibility with GNU Octave, a free, open-source Matlab clone.
- MIPS (MATPOWER Interior Point Solver), a new a pure-MATLAB implementation of the primal-dual interior point methods from the optional package TSPOPF.

C.2 Version 1.0.1 – released Apr 30, 2012

Documentation found in Appendix A of the MATPOWER 4.0 User's Manual, available online. 14

Bug Fixed

• Fixed fatal bug in MIPS for unconstrained, scalar problems. *Thanks to Han Na Gwon*.

C.3 Version 1.0.2 – released Nov 5, 2013

Documentation found in Appendix A of the MATPOWER 4.0 User's Manual, available online. ¹⁵

¹³https://matpower.org/docs/MATPOWER-manual-4.0.pdf

¹⁴https://matpower.org/docs/MATPOWER-manual-4.0.pdf

¹⁵https://matpower.org/docs/MATPOWER-manual-4.0.pdf

Bug Fixed

• Fixed a bug in MIPS where a near-singular matrix could produce an extremely large Newton step, resulting in incorrectly satisfying the relative feasibility criterion for successful termination.

C.4 Version 1.1 – released Dec 17, 2014

Documentation found in Appendix A of the MATPOWER 5.0 User's Manual, available online. ¹⁶

New Features

• Many new user-settable options.

Incompatible Changes

• The name of the mips() option used to specify the maximum number of stepsize reductions with step_control on was changed from max_red to sc.red_it for consistency with other MATPOWER options.

C.5 Version 1.2 – released Mar 20, 2015

Documentation found in Appendix A of the MATPOWER 5.1 User's Manual, available online.¹⁷

New License

• Switched to the more permissive 3-clause BSD license from the previously used GNU General Public License (GPL) v3.0.

New Documentation

• Added an online function reference to the MATPOWER website at http://www.pserc.cornell.edu/matpower/docs/ref/.

¹⁶https://matpower.org/docs/MATPOWER-manual-5.0.pdf

¹⁷https://matpower.org/docs/MATPOWER-manual-5.1.pdf

New Features

- Added support for using PARDISO (https://pardiso-project.org/) as linear solver for computing interior-point update steps in MIPS, resulting in dramatic improvements in computation time and memory use for very large-scale problems.
- New functions:
 - mplinsolve() provides unified interface for linear system solvers, including PARDISO and built-in backslash operator

C.6 Version 1.2.1 – released Jun 1, 2016

Documentation found in Appendix A of the MATPOWER 6.0b1 User's Manual, available online. 18

Bug Fixed

• Fixed issue where default value of 'feastol' option was not being set correctly in mips() when called directly (or via qps_mips()) with 'feastol' = 0.

C.7 Version 1.2.2 – released Dec 16, 2016

Documentation found in the MIPS 1.2.2 User's Manual¹⁹ or in Appendix A of the MATPOWER 6.0 User's Manual, available online.²⁰

New Open Development Model

- MIPS development has moved to GitHub! The code repository is now publicly available to clone and submit pull requests.²¹
- Public issue tracker for reporting bugs, submitting patches, etc.²²

¹⁸https://matpower.org/docs/MATPOWER-manual-6.0b1.pdf

¹⁹https://matpower.org/docs/MIPS-manual-1.2.2.pdf

²⁰https://matpower.org/docs/MATPOWER-manual-6.0.pdf

²¹https://github.com/MATPOWER/mips

²²https://github.com/MATPOWER/mips/issues

Other Changes

- Renamed from Matlab Interior Point Solver to Matpower Interior Point Solver.
- Remove dependence of t_mpsolve() on presence of have_fcn() (from MAT-POWER) to detect PARDISO installation.

C.8 Version 1.3 – released Oct 30, 2018

The MIPS 1.3 User's Manual is available online.²³

New Features

- Support for PARDISO 6.x.
- New mplinsolve solver option 'LU' for explicit LU decomposition with back substitution, with options in opt.lu for specifying the number of output arguments in call to lu (opt.lu.nout), whether to use permutation vectors or matrices (opt.lu.vec) and pivot threshold options (opt.lu.thresh). The following values for the solver argument act as shortcuts for specifying various combinations of options: 'LU3', 'LU3a', 'LU4', 'LU5', 'LU3m', 'LU3am', 'LU4m', 'LU5m'. See help mplinsolve for details. Thanks to Jose Luis Marín.

Bugs Fixed

• Fix bug preventing pardiso.dparm options from being set.

Other Changes

- LATEX source code for MIPS User's Manual included in docs/src.
- Move mplinsolve PARDISO options to opt.pardiso in preparation for adding options for other solvers.

²³https://matpower.org/docs/MIPS-manual-1.3.pdf

C.9 Version 1.3.1 – released Jun 20, 2019

The MIPS 1.3.1 User's Manual is available online. 24

Changes

- Add CITATION file.
- Other miscellaneous documentation updates, e.g. MATPOWER website links updated to https://matpower.org.

²⁴https://matpower.org/docs/MIPS-manual-1.3.1.pdf

References

- [1] TSPOPF. [Online]. Available: http://www.pserc.cornell.edu/tspopf/. 1.1,
- [2] H. Wang, C. E. Murillo-Sánchez, R. D. Zimmerman, and R. J. Thomas, "On Computational Issues of Market-Based Optimal Power Flow," *Power Systems, IEEE Transactions on*, vol. 22, no. 3, pp. 1185–1193, August 2007. doi: 10.1109/TPWRS.2010.2051168 1.1, 1.3, 3, 3-3, 3.4
- [3] H. Wang, On the Computation and Application of Multi-period Security-constrained Optimal Power Flow for Real-time Electricity Market Operations, Ph.D. thesis, Electrical and Computer Engineering, Cornell University, May 2007. 1.1, 3, 3.4
- [4] R. D. Zimmerman, C. E. Murillo-Sánchez, and R. J. Thomas, "MATPOWER: Steady-State Operations, Planning and Analysis Tools for Power Systems Research and Education," *Power Systems, IEEE Transactions on*, vol. 26, no. 1, pp. 12–19, Feb. 2011. doi: 10.1109/TPWRS.2010.2051168 1.1
- [5] R. D. Zimmerman, C. E. Murillo-Sánchez (2019). MATPOWER
 [Software]. Available: https://matpower.org
 doi: 10.5281/zenodo.3236535
 1.1
- [6] R. D. Zimmerman, H. Wang. MATPOWER Interior Point Solver (MIPS) User's Manual. 2019. [Online]. Available: https://matpower.org/docs/ MIPS-manual.pdf doi: 10.5281/zenodo.3236506 1.3
- [7] John W. Eaton, David Bateman, Søren Hauberg, Rik Wehbring (2015). GNU Octave version 4.0.0 manual: a high-level interactive language for numerical computations. Available: https://www.gnu.org/software/octave/doc/interpreter/. 1, 5
- [8] The BSD 3-Clause License. [Online]. Available: https://opensource.org/licenses/BSD-3-Clause. 1.2
- [9] GNU General Public License. [Online]. Available: https://www.gnu.org/licenses/. 3

- [10] O. Shenk and K. Gärtner, "Solving unsymmetric sparse systems of linear equations with PARDISO," *Journal of Future Generation Computer Systems*, 20(3):475–487, 2004. B
- [11] A. Kuzmin, M. Luisier and O. Shenk, "Fast methods for computing selected elements of the Greens function in massively parallel nanoelectronic device simulations," in F. Wolf, B. Mohr and D. Mey, editors, Euro-Par 2013 Parallel Processing, Vol. 8097, Lecture Notes in Computer Science, pp. 533–544, Springer Berlin Heidelberg, 2013. B