

Title		
Size: Letter	Number	Revision
Date: 10/06/2022		Sheet of
File: C:\Users\..\Mainboard.SchDoc		Drawn By:


I2C
P1
U2
LM7805CT
C5
10uF
R1
10K
U1
ATMEGA328P-PU
P4
ENCODER
C3
1uF
P5
POWER
P3
BUTTON
P6
SW
C1
Y1
C4
10uF
P2
MOTOR
D1
C2


P1


ATMEGA

Comment	Description	Designator	Footprint	LibRef	Quantity
22pF	Cap Ceramic 22pF 50V C0G ±5% Radial 2.5mm +125°C Ammo Pack	C1, C2	FP-RCE0DB-MFG	CMP-06035-057691-1	2
1uF	Capacitor	C3	CAPR5-4X5	Cap2	1
10uF	Capacitor	C4, C5	CAPR5-4X5	Cap2	2
1N4007-E3/54	DIODE GEN PURP 1KV 1A DO204AL	D1	FP-1N4007-MFG	CMP-02540-000046-1	1
I2C	Header, 4-Pin	P1	HDR1X4	Header 4	1
MOTOR	Header, 6-Pin	P2	HDR1X6	Header 6	1
BUTTON	Header, 3-Pin	P3	HDR1X3	Header 3	1
ENCODER	Header, 5-Pin	P4	HDR1X5	Header 5	1
POWER	Header, 2-Pin	P5	HDR1X2	Header 2	1
SW	Header, 2-Pin	P6	HDR1X2	Header 2	1
10K	Resistor	R1	AXIAL-0.4	Res2	1
ATMEGA328P-PU	8-Bit Microcontroller with 32 KBytes In-System Programmable Flash, 23 I/Os, -40 to 85 degC, 28-Pin PDIP (28P3), RoHS, Tube	U1	ATML-28P3	CMP-020-00004-3	1
LM7805CT	Positive Voltage Regulator, 5 V, 1 A, -40 to 125 degC, 3-Pin TO-220, RoHS, Tube	U2	FAIR-TO-220-3	CMP-2000-04938-1	1
16MHz	Resistance Weld Thru-Hole Crystal, 16 MHz, -20 to 70 degC, 2-Pin THD, RoHS, Bulk	Y1	FOX-FOXSLF160-20	CMP-1749-00003-1	1