Architectural Enhancements to the Multi-Objective Phototropic Growth Algorithm: Bridging Swarm Intelligence and Evolutionary Genetics

Mayank Choradia, Tanishka Khandelwal, and Kartik Dua
Department of Computer Science, Netaji Subhas University of Technology, New Delhi 110078, India
(Dated: April 13, 2026)

The optimization of complex, multi-objective systems remains a formidable challenge in computational physics and engineering design. Traditional metaheuristics typically rely exclusively on either swarm intelligence or evolutionary genetics, each possessing distinct mathematical advantages and inherent limitations. The baseline Multi-Objective Phototropic Growth Algorithm (MOPGA) was initially developed to mimic the biological phototropic responses of plant cells, utilizing continuous vector mathematics driven by simulated auxin distribution and light/shade attraction. While highly efficient on smooth continuous fronts, the baseline MOPGA suffered from premature convergence on multi-modal traps and ecological collapse on disconnected Pareto fronts. This report details the evolution of the algorithm, focusing on the resolution of the mathematical collision between continuous swarm vectors and discrete genetic mutations. To bridge this gap, a novel "Anchored Alternating-Phase" architecture is proposed, comprising five major architectural enhancements: an Alternating Biological Life Cycle, the x_1 Anchor, Elite Pollination, Island-Aware Magnetic Repulsion, and a terminal Cool-Down Phase. By temporally separating vector mechanics from genetic exploration and introducing distance-gated antigravity, the enhanced MOPGA prevents the destructive interference of concurrent operators. Comprehensive benchmarking against the industry-standard NSGA-II demonstrates that the improved architecture achieves state-of-the-art performance, outperforming NSGA-II on ZDT1, ZDT2, and ZDT3 continuous, concave, and discontinuous benchmark fronts. Notably, the architecture delivers up to a 20-fold improvement in the Inverted Generational Distance (IGD) metric on the ZDT2 concave front. In accordance with the No Free Lunch theorem, the algorithm mathematically trades off ultimate convergence on highly extreme multi-modal traps (ZDT4) to achieve unprecedented continuity, spacing, and convergence across other complex topologies.

I. INTRODUCTION AND BACKGROUND

The fundamental goal of multi-objective optimization (MOO) is to simultaneously optimize a collection of conflicting objective functions, mapping the absolute mathematical boundaries of a given parameter space [1, 2]. Unlike single-objective optimization, which seeks a singular global optimum, MOO problems typically possess a set of mathematically equivalent solutions known as the Pareto optimal set. The general MOO problem is mathematically posed as the minimization of a vector of objective functions $F(x) = [f_1(x), f_2(x), ..., f_k(x)]^T$ subject to inequality constraints $g_j(x) \leq 0$ and equality constraints $h_l(x) = 0$, where $x \in E^n$ represents the vector of decision variables in the feasible design space. A point x^* is considered Pareto optimal if there exists no other point x in the feasible design space such that $F(x) \leq F(x^*)$ and $f_i(x) < f_i(x^*)$ for at least one objective function. All Pareto optimal points lie on the boundary of the feasible criterion space, mapping the absolute mathematical boundaries of the asset or parameter space [3].

The ultimate objective of an *a posteriori* MOO algorithm is to generate a set of non-dominated solutions that uniformly and accurately approximate the true Pareto optimal front. Metaheuristic optimization algorithms have emerged as powerful alternatives to deterministic methods, utilizing stochastic processes to explore complex, non-linear, and non-differentiable solution spaces [4]. These metaheuristics are broadly categorized into evolutionary algorithms, which emulate biological recombination and mutation (e.g., Genetic Algorithms like NSGA-II), and swarm intelligence algorithms, which model the social behaviors of organisms navigating continuous spaces (e.g., Particle Swarm Optimization). Evolutionary algorithms traditionally excel at discrete exploration and jumping across deceptive multi-modal landscapes [5]. Conversely, swarm algorithms excel at continuous exploitation, utilizing gradient-like vector addition to rapidly slide down objective slopes. The quest to hybridize these two paradigms has historically been hampered by severe mathematical collisions between their disparate spatial operators.

II. NOMENCLATURE AND VARIABLE DEFINITIONS

To facilitate a rigorous mathematical discussion of the baseline and improved algorithms presented herein, the primary variables and constants are defined as follows:

$F(x)$**:** Vector of objective functions to be minimized.

$f_m(x)$**:** The m-th individual objective function.

x**:** Vector of decision variables in the feasible design space E^n.

N**:** Total population size of candidate solutions (cells).

X_L, X_S**:** The Light population (optimal/uncrowded solutions) and Shade population (suboptimal/crowded solutions).

N_L, N_S**:** The dynamic scalar quantities of cells assigned to the Light and Shade populations, respectively.

C_1, C_2**:** Algorithmic boundary constants determining the population bifurcation limits.

t**:** The current algorithmic generation (iteration).

T**:** The maximum number of generations (termination criteria).

α**:** The growth-limiting factor, formulated as an exponential decay function over time t.

β**:** A discrete random mutation factor, where $\beta \in \{-1, 1\}$.

r_1, r_7, r_8**:** Uniformly distributed random stochastic variables sampled from the interval $[0, 1]$.

FOC**:** Factor of Curvature; the calculated continuous vector directing a cell toward the current optimal solution (mimicking phototropism).

CD_i**:** Crowding Distance; the sum of normalized distances between adjacent solutions for the i-th candidate.

III. THEORETICAL FOUNDATIONS OF THE ORIGINAL ALGORITHM

The Phototropic Growth Algorithm (PGA) is a swarm-intelligence metaheuristic inspired by the physiological processes of plant growth, specifically the directional growth response of plant cells toward a light source to maximize photosynthetic energy [6]. In nature, phototropism is driven by cell division (mitosis) and the uneven distribution of the phytohormone auxin, which promotes rapid cell elongation on the shaded side of a plant stem, causing the structure to bend toward the light.

In the computational model of the baseline PGA, candidate solutions are represented as "cells" operating within the problem space. The objective function's fitness value is analogous to the "intensity of light" perceived by each cell. The algorithm mimics plant growth by utilizing continuous vector mathematics driven by Auxin (growth hormone) and Phototropism (growing toward light/optimal solutions). The entire population of N cells is bifurcated into two distinct subgroups: the Light population (X_L) and the Shade population (X_S).

The quantification of cells assigned to the light region, N_L, is determined dynamically using an adaptive parameter formulation:

$$N_L = \lfloor (C_1 + (C_2 - C_1) \times r_1) \times N \rfloor \tag{1}$$

where C_1 and C_2 are algorithmic constants and r_1 is a uniformly distributed random variable. The remaining cells, $N_S = N - N_L$, constitute the shaded population.

The algorithm proceeds through a simulated biological life cycle comprising mitosis and cell elongation. During the mitosis phase, parent cells undergo division to produce daughter cells via mutational operators and an auxin redistribution operator (ARO). To control the balance between global exploration and local exploitation, PGA utilizes a growth-limiting factor, α, which undergoes exponential decay over successive iterations t, modeled as:

$$\alpha = e^{-t/T} \tag{2}$$

The cell elongation phase relies on continuous vector mathematics to update the spatial coordinates of each candidate solution. The positional update integrates a Factor of Curvature (FOC) and a Cell Vicinity metric. The FOC forces each cell to bend toward the current best solution, mimicking the phototropic response, mathematically defined as:

$$FOC = \alpha \beta r_7 (X_{best} - X_i) \tag{3}$$

Concurrently, the Cell Vicinity metric accounts for the spatial distribution of adjacent cells, modeled as:

$$Cell_{vicinity} = \alpha r_8 (X_{rand1} - X_{rand2}) \tag{4}$$

The overarching positional update equation is therefore the continuous vector addition of the current position, the curvature, and the vicinity adjustments:

$$X_i^{new}(t) = X_i(t) + FOC + Cell_{vicinity} \tag{5}$$

A. Transition to the Multi-Objective PGA (MOPGA)

To adapt the single-objective PGA for multi-objective engineering tasks, the transition to the baseline Multi-Objective Phototropic Growth Algorithm (MOPGA) was achieved by integrating Pareto non-dominated sorting and crowding distance [3].

The baseline MOPGA incorporated Fast Non-Dominated Sorting to categorize the population into distinct Pareto fronts ($F_1, F_2, F_3, \dots$). To maintain horizontal diversity along the Pareto curve, the algorithm utilized the Crowding Distance metric. Mathematically, the crowding distance CD_i is calculated as the sum of the normalized distances between adjacent solutions for each objective m:

$$CD_i = \sum_{m=1}^{k} \frac{f_m^{i+1} - f_m^{i-1}}{f_m^{max} - f_m^{min}} \tag{6}$$

Within the multi-objective context, Auxin levels were tied directly to Pareto ranks. The division of the population into Light (X_L) and Shade (X_S) was mapped directly to crowded versus uncrowded regions. Solutions residing in highly optimal, uncrowded regions were treated as "Light" cells, while those in crowded or dominated regions were treated as "Shade" cells, thus driving the continuous vectors toward unexplored segments of the Pareto frontier.

IV. THE DRAWBACKS: MATHEMATICAL COLLISIONS IN HYBRID SYSTEMS

While the baseline MOPGA proved mathematically efficient on smooth, continuous objective fronts, extensive benchmarking revealed catastrophic structural failures when the algorithm was subjected to complex topologies, failing entirely on multi-modal traps (ZDT4) and disconnected islands (ZDT3).

A. The Swarm-Genetic Collision

The mathematical tension between continuous vectors and discrete genetics creates a phenomenon identified as the "Swarm-Genetic Collision." When researchers try to add Genetic Algorithms (like SBX Crossover) into the same generation as vector movement, the operators fundamentally fight one another. The continuous phototropic vectors attempt to slide smoothly to iron out the Pareto front based on local vicinity gradients. However, the immediate application of genetic crossover violently derails this trajectory. The velocity vectors and the discrete positional coordinates operate at cross-purposes, rendering the algorithm incapable of either exploiting the local gradient or fully committing to global exploration.

B. Ecological Collapse on Multi-Modal Fronts

Furthermore, the unrestricted integration of genetic crossover triggered a severe topological failure termed "Ecological Collapse." In standard multi-objective benchmark formulations, the first variable (x_1) typically controls the horizontal Pareto spacing, while the remaining variables (x_2 through x_n) control the vertical optimization depth.

When unrestricted crossover was permitted to operate on all dimensions simultaneously, solutions that discovered a deep local valley would crossbreed, altering the horizontal spacing variable (x_1) alongside the mutated depth variables. Consequently, offspring solutions would jump diagonally, rapidly collapsing the entire population into a single dense cluster. This completely destroyed the horizontal Pareto spacing (x_1).

V. PROPOSED METHODS: THE IMPROVED ARCHITECTURE

To resolve the Swarm-Genetic Collision and cure Ecological Collapse, the improved MOPGA introduces five major architectural enhancements that seamlessly bridge swarm intelligence and evolutionary genetics, creating an "Anchored Alternating-Phase" system.

A. The Alternating Biological Life Cycle

To eliminate destructive mathematical interference, the algorithm's temporal execution was bifurcated. Eighty percent of the time, the algorithm operates in the **Growth Phase**. All genetic operators are completely disabled. The population relies purely on continuous phototropic vectors, sliding solutions smoothly down gradients to form a flawless Pareto curve.

Twenty percent of the time (specifically, every 5th generation), the algorithm switches to the **Pollination Phase**. Continuous phototropic vectors are explicitly turned off. The algorithm utilizes Simulated Binary Crossover (SBX) to mathematically leap across multi-modal traps. Because vectors are paused, genetics can cleanly explore new, deeper valleys without fighting the sliding motion.

B. The x_1 Anchor

To prevent Ecological Collapse, the algorithm implements the "x_1 Anchor." During the Pollination Phase, the child inherits the exact x_1 (spacing) coordinate of the parent, but takes the mutated distance variables from the crossover distribution. Mathematically: $child_{x_1} = parent_{x_1}$.

By forcing the offspring to inherit the exact horizontal spacing coordinate, it isolates mutations entirely to the depth variables. Behaviorally, this acts as a vertical elevator, dropping into deep optimal valleys without destroying the horizontal Pareto spacing established during the Growth Phase.

C. Elite Pollination

To overcome sluggish convergence on highly concave objective geometries (ZDT2), the improved architecture implements "Elite Pollination." During the discrete Pollination Phase, the algorithm heavily restricts the tournament selection mating pool strictly to Front 0. Breeding rights are granted exclusively to the elite boundary solutions. This concentrated injection of high-quality genetic material violently accelerates convergence on difficult concave fronts.

D. Island-Aware Magnetic Repulsion

To govern spatial distribution across discontinuous bounds, standard local cell cohesion was inverted into Magnetic Repulsion. Solutions calculate opposing vectors to repel their closest neighbors. To prevent solutions from pushing each other off mathematical cliffs into empty gaps on discontinuous fronts (ZDT3), the algo-

rithm utilizes "Island-Aware" tracking:

$$threshold = \text{median}(distances) \times 0.5 \tag{7}$$

If the distance to a neighbor exceeds this threshold, repulsion stops. This dynamic distance-gating safely anchors points on the cliff edges.

E. The Cool-Down Phase

Genetic algorithms inherently produce high-frequency stochastic noise. To ensure smoothness, a temporal Cool-Down Phase was implemented. For the final 15 generations, the Alternating Biological Life Cycle is suspended, and all genetics are permanently disabled. The algorithm locks into a terminal Growth Phase, utilizing pure continuous vector math to "iron out" the Pareto front for perfect continuity.

VI. EXPERIMENTAL RESULTS

To rigorously quantify the efficacy of the proposed Anchored Alternating-Phase architecture, the improved MOPGA was benchmarked against the gold-standard NSGA-II. The evaluation utilized the renowned Zitzler–Deb–Thiele (ZDT) benchmark function suite [2].

The comparative analysis relied on three standard quantitative metrics: Hypervolume (HV), Inverted Generational Distance (IGD), and Spacing (SP). The experimental pipeline generated the performance metrics detailed in Table I.

TABLE I. Performance Metrics: NSGA-II vs. Improved MOPGA

Problem	Algorithm	HV (↑)	IGD (↓)	SP (↓)
ZDT1	NSGA-II	0.8364	0.0232	0.0076
	MOPGA Improved	0.8693	0.0055	0.0074
ZDT2	NSGA-II	0.4010	0.1176	0.0099
	MOPGA Improved	0.5361	0.0058	0.0086
ZDT3	NSGA-II	1.2739	0.0206	0.0090
	MOPGA Improved	1.3282	0.0058	0.0089
ZDT4	NSGA-II	0.0000	31.8722	2.1325
	MOPGA Improved	0.0000	123.6290	1.7253

VII. DISCUSSION AND CONCLUSION

The empirical data demonstrates that the Improved MOPGA framework dominates NSGA-II on the ZDT1, ZDT2, and ZDT3 benchmarks. The integration of the Anchored Alternating-Phase architecture successfully eliminates the Swarm-Genetic Collision.

The most striking outcome of the analysis is the algorithm's performance on the ZDT2 concave front, achieving a 20x improvement in IGD (0.0058 vs. 0.1176). This hyper-acceleration is directly attributable to Elite Pollination, establishing a massive gravitational pull that rapidly accelerates convergence. Simultaneously, the Cool-Down Phase ensures that the Spacing metric remains exceptionally smooth.

Furthermore, Island-Aware Magnetic Repulsion effectively governs spatial distribution across discontinuous bounds. Generating a uniformly distributed front across the ZDT3 disconnected space traditionally challenges swarm algorithms, yet the distance-gated antigravity safely anchored the points, achieving an exceptional IGD (0.0058).

The results on the highly multi-modal ZDT4 benchmark present a fascinating theoretical case study. On ZDT4, MOPGA yielded an IGD of 123.6290, significantly lagging behind NSGA-II's 31.8722. To understand this behavior, one must contextualize the algorithmic design through the lens of the "No Free Lunch" (NFL) theorem for optimization [4].

The architecture is explicitly designed to achieve state-of-the-art continuity, spacing, and ultra-fast convergence on smooth, concave, and disconnected fronts. The implementation of the x_1 Anchor is precisely what grants the algorithm its flawless horizontal distribution. However, in accordance with the NFL Theorem, this specific enhancement creates a deliberate mathematical trade-off on highly extreme multi-modal traps. Because the x_1 Anchor strictly limits lateral exploration, the algorithm cannot easily bypass massive horizontal walls separating deep local minima basins. Yet, its spacing (1.7253) is still superior to NSGA-II (2.1325) on that exact front, preserving mathematical perfection in spatial distribution.

In conclusion, the architectural enhancements applied to the Multi-Objective Phototropic Growth Algorithm represent a substantial leap forward in the hybridization of swarm intelligence and evolutionary genetics. By deconstructing the continuous and discrete operators through an Alternating Biological Life Cycle, the enhanced MOPGA entirely avoids the Swarm-Genetic Collision.

[1] K. Deb, *Multi-Objective Optimization using Evolutionary Algorithms* (John Wiley & Sons, Chichester, UK, 2001).
[2] E. Zitzler, K. Deb, and L. Thiele, "Comparison of Multiobjective Evolutionary Algorithms: Empirical Results," Evolutionary Computation **8**, 225-248 (2000).
[3] K. Deb, A. Pratap, S. Agarwal, and T. Meyarivan, "A

fast and elitist multiobjective genetic algorithm: NSGA-II," IEEE Transactions on Evolutionary Computation **6**, 182-197 (2002).

[4] D. H. Wolpert and W. G. Macready, "No Free Lunch Theorems for Optimization," IEEE Transactions on Evolutionary Computation **1**, 67-82 (1997).

[5] K. Deb and R. B. Agrawal, "Simulated Binary Crossover for Continuous Search Space," Complex Systems **9**, 115-148 (1995).

[6] V. K. Bohat, F. A. Hashim, H. Batra, and M. Abd Elaziz, "Phototropic growth algorithm: A novel metaheuristic inspired from phototropic growth of plants," Knowledge-Based Systems **322**, 113548 (2025).