TECHNISCHE UNIVERSITÄT ILMENAU
Institut für Praktische Informatik und Medieninformatik

Master Thesis

AI-Guided Voice-Interactive VR Meditation: Enhancing Relaxation through Adaptive Audiovisual Cues and Biofeedback

Author:

Muhammad Abid Zahid
Matrikel 63677

A thesis submitted in fulfillment of the requirements for the degree of Media Technology

in the

Virtual Worlds and Digital Games Group

Supervisor:
Dr.-Ing. Tobias Schwandt

Professor:
Prof. Dr. rer. nat. Wolfgang Broll

Ilmenau, December 30, 2025

Contents

Acknowledgments **1**

Abstract **2**

Zusammenfassung **3**

1. Introduction **4**
1.1. Topic Description 4
1.2. Research Questions and Hypotheses 5
1.3. Scientific Contributions 5
1.4. Chapter Outline 6

2. Literature Review **7**
2.1. Introduction 7
2.2. Virtual Reality: Concepts and Applications 7
2.3. Meditation and Psychological Well-Being 8
2.4. Virtual Reality Meditation: Integrating Technology and Mindfulness 8
2.5. Physiological Biofeedback and Regulation 9
2.5.1. Detecting Stress and Frustration through Physiological Signals 9
2.6. Artificial Intelligence in Adaptive Virtual Environments 10
2.7. Multimodal Interaction and System Design 11
2.8. Psychometric Measures Used in the Study 11
2.9. Commercial Applications and Research Gap 12

3. Methodology **13**
3.1. Introduction 13
3.2. Research Design 13
3.3. Experimental Setup 14
3.3.1. Rationale for Using Virtual Reality Instead of 2D Displays 14
3.3.2. Hardware Materials 15
3.3.3. Software and Environment 18
3.4. System Implementation 20
3.4.1. AI-Guided Voice Meditation Pipeline 20
3.5. Breathing-Responsive Light and Skybox Adaptation 22
3.5.1. Multimodal Synchronisation 23
3.5.2. Integration with Physiological Recording 24
3.6. Participants 24
3.6.1. Recruitment 24
3.6.2. Sample Characteristics 25
3.6.3. Participant Background Characteristics 25

3.6.4. Inclusion Criteria . . . 25
3.6.5. Exclusion Criteria . . . 25
3.6.6. Sample Size Justification . . . 26
3.6.7. Ethical Considerations . . . 28
3.6.8. Experimental and Adaptive Workflow . . . 29
3.7. Procedure . . . 30
3.8. Instruments and Measures . . . 30
3.8.1. Psychometric Questionnaires . . . 30
3.8.2. Physiological Measures . . . 31
3.9. Data Collection and Processing . . . 31
3.9.1. Preprocessing and Downsampling of Physiological Signals . . . 31
3.9.2. Validation of the Downsampling Procedure . . . 32
3.9.3. Heart-Rate Variability (HRV) Feature Extraction . . . 32
3.9.4. Questionnaire Item Sets and Composite Score Construction . . . 33
3.10. Data Analysis . . . 33
3.10.1. Preprocessing . . . 34
3.10.2. Change Scores . . . 34
3.10.3. Statistical Testing . . . 34
3.11. Summary . . . 34

4. Results **36**
4.1. Heart-Rate Variability During Meditation . . . 36
4.2. Within-Group Changes: Stress vs. Meditation . . . 37
4.3. Between-Group Differences in Physiological Change . . . 39
4.4. Questionnaire Results . . . 40
4.4.1. Baseline Measures . . . 40
4.4.2. State Mindfulness During Meditation . . . 41
4.4.3. Perceived Presence in VR . . . 41
4.4.4. Overall Satisfaction With the Meditation Method . . . 41
4.4.5. Differences Within VR: Low- vs. High-Stress Subgroups . . . 42
4.4.6. Correlations Between Questionnaire Measures . . . 43
4.5. Summary of Findings . . . 43

5. Conclusion **45**

6. Future Work **48**
6.1. Adaptive Biofeedback with Modern Sensors . . . 48
6.2. Eye-Closure Detection and Comfort-Aware Visual Design . . . 48
6.3. Extended Protocols and Personalisation . . . 49

A. Appendix **51**
A.1. Heart Rate (HR) . . . 51
A.2. Skin Conductance Level (SCL) . . . 53
A.3. Skin Temperature . . . 55
A.4. Pulse Volume Amplitude (PVA) . . . 57
A.5. Body Motion . . . 59

A.6. Additional HRV Visualisations 61
A.6.1. Background music 65

Declaration **79**

Acknowledgments

I would like to express my sincere gratitude to my professor. Dr. Wolfgang Broll for allowing me to pursue a master's thesis under his supervision. I would like to extend my honest gratitude to my thesis supervisor Dr. -Ing. Tobias Schwandt for his invaluable guidance, patience and support throughout this time. His knowledge and insightful feedback helped me a lot in shaping the direction of the research. I would also like to thank him for his dedicated guidance, unwavering support, and insightful feedback during my thesis. I am also deeply thankful to my university, Technische Universität Ilmenau, for providing me with all the required resources to conduct this research. Furthermore, I would like to extend my appreciation to the participants who took part in this study and for their time, which made this research possible. My heartfelt thanks to my family and friends for their unwavering support, patience, and belief in me. Their reassurance was my biggest source of motivation. Finally, I would like to acknowledge the assistance AI tools such as Open AIs, chatGPT and Grammarly provide in facilitating brainstorming, refining ideas, and structuring this document. These tools were used for language refinement, clarity improvement, and brainstorming support. All scientific content, experimental design, data analysis, interpretation, and conclusions are entirely my own.

Abstract

This thesis explores the potential of AI-guided, voice-interactive virtual reality (VR) meditation to enhance relaxation and emotional well-being through adaptive audiovisual cues. We developed a meditative application using Unity 3D and HTC VIVE Pro headset. The system delivers voice prompts generated by GPT in the virtual environment, displaying calming visuals. To evaluate the system study with more than 40 participants was conducted comparing VR-based meditation with the conventional meditation method. Physiological responses such as heart rate variability and skin conductance were measured using Biofeedback 2000 sensors, complemented by user self-reported feedback on relaxation and emotional states. The findings indicate that VR meditation guided by AI-generated voice instructions and enriched with responsive audiovisual transitions can foster deeper relaxation and more positive emotional experiences compared to traditional methods. These results highlight the promise of adaptive multi-modal meditation systems as supportive tools for mental wellness and stress reduction.

Keywords: VR, Virtual Reality, Meditation, Artificial Intelligence, Biofeedback, Relaxation, Emotional well being

Zusammenfassung

Diese Arbeit untersucht das Potenzial von KI-gesteuerter, sprachinteraktiver Virtual-Reality-(VR)-Meditation zur Förderung von Entspannung und emotionalem Wohlbefinden durch adaptive audiovisuelle Reize. Es wurde eine Meditationsanwendung in Unity 3D unter Verwendung des HTC VIVE Pro Headsets entwickelt. Das System bietet im virtuellen Raum sprachliche Anweisungen, die von einem GPT-Modell generiert werden, und zeigt beruhigende visuelle Elemente an.

Zur Evaluierung des Systems wurde eine Nutzerstudie mit über 40 Teilnehmenden durchgeführt, in der VR-basierte Meditation mit konventionellen Meditationsmethoden verglichen wurde. Physiologische Reaktionen wie Herzfrequenzvariabilität und Hautleitfähigkeit wurden mithilfe der Biofeedback-2000-Sensoren gemessen und durch selbstberichtete Rückmeldungen der Teilnehmenden zu Entspannung und emotionalem Zustand ergänzt.

Die Ergebnisse zeigen, dass VR-Meditation, die durch KI-generierte Sprachführung und reaktive audiovisuelle Übergänge unterstützt wird, eine tiefere Entspannung und positivere emotionale Erfahrungen fördern kann als herkömmliche Methoden. Diese Ergebnisse unterstreichen das Potenzial adaptiver, multimodaler Meditationssysteme als unterstützende Werkzeuge für psychisches Wohlbefinden und Stressreduktion.

Schlüsselwörter: VR, Virtual Reality, Meditation, Künstliche Intelligenz, Biofeedback, Entspannung, Emotionales Wohlbefinden

1. Introduction

Virtual reality (VR) enables the creation of immersive, interactive environments that elicit a strong sense of presence by enveloping users in computer-generated worlds [Sla18, FRR+17]. This unique capability has led to its adoption not only in entertainment, but also in education, training, therapy, and healthcare applications [Bak19]. Virtual reality has been increasingly seen as a tool for strengthening mental health and wellness because it provides protected and distraction-free spaces where users can retreat from external stressors and engage in relaxation practices [R+21, Bai20].

In conjunction with such advances in technology, meditation has traditionally been used as a tool to develop relaxation, improve emotional regulation, and reduce anxiety and stress[SES+12, LSDD08, Man11]. Scientific evidence illustrates the ability of meditation to enhance psychological resilience and promote general mental health. Extensive research shows that meditation can reduce stress and anxiety, improve concentration, and overall well-being [G+14, Z+15]. However, many people struggle to maintain focus during meditation due to distractions, lack of guidance, difficulty staying focused, or inability to relax the mind.

VR offers a very useful bridge; it can turn proven relaxation and mindfulness methods into engaging sensory experiences that make it easier for people to start and keep practicing. The combination of the two spaces, meditation in VR spaces, has created **VR-centered meditation applications**. These systems present serene and immersive environments that can facilitate the user's ability to transcend peripheral interruptions and focus more intensely on their meditation [LGM18, WWM20]. However, most commercial VR meditation solutions are unchanging, presenting pre-programmed content that is not dynamically adjusted based on the user's state of emotion or physiology. This static responsiveness can inhibit their ability to facilitate increased relaxation and prolonged focus. In order to fill the gap, this thesis is motivated by the opportunity to design and evaluate an *interactive, AI-powered, voice-mediated VR meditation system* which can guide users through meditation based on user stress level.

1.1. Topic Description

This thesis investigates a **voice-interactive, AI-guided VR meditation** system developed in Unity 3D for HTC VIVE Pro. The application delivers *natural-language* voice commands (generated by a GPT) to guide breathing, attention control, and relaxation strategies, while *adaptive audiovisual transitions* (e.g. brightening and fading of light during eyes-closed phases to help with breathing, along with meditation music) shape the meditative ambience.

To ground personalisation, the user will be asked about their stress level and the guidance will be given according to that level. The system also records physiological signals **(SCL) Skin Conductance Level**, **(SCR) Skin Conductance Response**, **Skin Temperature**, **(BVP) Blood**

Volume Pulse, **(PVA) Pulse Volume Amplitude**, **Pulse / Heart Rate**, **Motion / Motility** and **Heart Rate variability (HRV)** *derived from BVP*—using Biofeedback 2000 Xpert sensors. These data are collected during the session and later is used for the comparison of the outcome of meditation [LG13a, CS18]. A user study with >40 participants compares the AI-guided VR meditation against a conventional (non-VR) meditation baseline, combining physiological outcomes with self-reports of relaxation and affect.

1.2. Research Questions and Hypotheses

RQ1. *Does AI-guided voice interaction combined with adaptive audiovisual cues improve relaxation and mindfulness during VR meditation compared to a conventional baseline?*

H1. Participants testing the AI-guided VR meditation will exhibit significantly greater post-session relaxation (physiological and self-report) than conventional meditation.

RQ2. *Do "eyes-closed mode" visuals (e.g., breathing light effect presented during instructed eyes-closed phases) enhance the perceived depth of meditation and calmness?*

H2. Participants will report higher immersion and calmness during eyes-closed phases augmented by soothing visuals and ambient audio.

RQ3. *Can a combination of physiological (HRV, skin conductance etc) and self-report measures provide valid, convergent indicators of meditation effectiveness in an AI-guided VR environment?*

H3. Physiological improvements (e.g., increased HRV, reduced electrodermal activity) will correlate with higher self-reported relaxation and positive affect, indicating convergent validity.

1.3. Scientific Contributions

- **Design Contribution:** A multimodal, *AI-guided voice* and *audiovisual-adaptive* VR meditation prototype that personalizes ambience and guidance to support relaxation, building on best practices in user-centered VR design.
- **Methodological Contribution:** An evaluation protocol combining *physiological* (HRV, skin conductance) and *psychological* (self-report) measures to assess meditative outcomes in VR.
- **Empirical Contribution:** Evidence on whether AI-guided voice prompts and adaptive audiovisual transitions improve relaxation relative to a conventional meditation baseline, including analysis of "eyes-closed mode" visuals.
- **Synthesis Contribution:** A literature-based rationale connecting meditation science, biofeedback, and adaptive interaction in VR, clarifying where adaptive intelligence adds value beyond static experiences.

1.4. Chapter Outline

The remainder of this thesis is organised as follows. **Chapter 2** reviews related work on virtual reality meditation, biofeedback-based stress regulation, AI-driven adaptivity, and multimodal interaction design, and identifies the research gap that motivates the present study. **Chapter 3** describes the methodology, including the experimental design, hardware and software architecture, system implementation, participant procedures, measurement instruments, and data processing pipeline. **Chapter 4** presents the empirical results, covering both physiological responses and questionnaire outcomes, and compares the effectiveness of conventional versus AI-guided VR meditation. **Chapter 5** answers the research questions, and summarises the results. **Chapter 6** outlines limitations and proposes future research directions for adaptive, biofeedback-aware VR meditation systems.

2. Literature Review

2.1. Introduction

The purpose of this literature review is to provide an overview of existing research on the topics of virtual reality, meditation, artificial intelligence, and physiological tools, such as biofeedback. This synthesis highlights theory and findings that form the foundation for understanding how VR can enhance mindfulness practices through emerging technology like artificial intelligence. The review is organized thematically to guide the reader from fundamental concepts such as evolution and applications of VR to areas more specific to the field of meditation and to the regions where Biofeedback mechanisms and AI-driven systems are used. These studies show how new technologies combined with meditative practices can enhance mental and emotional well-being.

2.2. Virtual Reality: Concepts and Applications

Virtual Reality (VR) is a computer-generated environment that immerses users in realistic or imagined scenes and permits interaction through multisensory input and output [Jer16]. VR research distinguishes between immersion, describing the technical characteristics of the system, and presence, referring to the user's subjective experience of being located within the virtual environment [Sla18, Bry96]. High levels of presence and immersion can significantly influence cognition, behavior, and emotion.

While VR initially gained prominence in gaming and entertainment, it is now widely applied in healthcare, psychotherapy, assessment, training, and education [FRR+17, R+21, Bak19]. Meta-analytic and review work on VR in mental health indicates that VR exposure and therapeutic environments can be effective for anxiety disorders, psychosis, and trauma-related conditions when integrated into structured treatment protocols [FRR+17, R+21]. Human-centered design guidelines emphasize usability, comfort, and emotional safety as key requirements for VR applications targeting vulnerable or clinical populations [Jer16].

More recent studies have explored the integration of VR with AI and adaptive interfaces in education and training contexts, for example VR classrooms with AI-generated scenarios or intelligent tutoring and assessment [KSKS24, Liu24, EYKC25]. In medical and procedural training, VR has also been used to simulate complex interventions and measure stress responses and user perceptions during high-stakes scenarios [RLGCZR+25]. Together, these findings position VR as a versatile medium for both skill development and emotional or stress-related interventions.

2.3. Meditation and Psychological Well-Being

Meditation practices have been shown to influence emotional regulation and stress resilience through attentional and cognitive control mechanisms, it includes diverse practices such as mindfulness, recitation, and focused attention each offering unique physiological and cognitive benefits [SES+12, LSDD08, Man11]. Evidence from the meta-analysis reveals small to moderate positive outcomes for meditation interventions on psychological stress, anxiety, depression, and overall well-being [G+14, SES+12].

Theoretical and neuroscience studies also show the potential for meditation to increase attentional power: meditation enhances attentional regulation, improve metacognitive monitoring, and brain regions implicated in attentional control and emotion regulation, including the anterior cingulate cortex, insular cortex, and amygdala [LSDD08]. Traditional conceptual models, for example, de-automatization, have explained how meditation challenges habitual processes: Cognitive and perceptual patterns to have more adaptable and unreactive reactions to stressors [Dei66, Man11].

Despite the benefits, it can be hard for some to practice and commit to the routine of meditation is lacking due to time constraints, a lack of guidance, or the inability to focus attention. Recent have, consequently, focused on technology-mediated meditation, such as smartphone apps and VR-based solutions, so as to offer more engaging and structured support [TVC18, CBN21]. Evidently, these methods are aimed at filling a gap between traditional Meditation practices and modern digital life.

2.4. Virtual Reality Meditation: Integrating Technology and Mindfulness

The integration of VR and meditation, collectively referred to as VR meditation, introduces a new approach to increased relaxation and concentration in engaging, sensory-stimulating environments [LGM18]. In this thesis, VR meditation refers to the delivery of guided meditative practices within immersive virtual environments that combine visual, auditory, and interactive elements to support attentional focus. With the display of relaxing natural surroundings or graphical patterns along with audio, based on guidance, where it seeks to improve focus, suppress interfering distractions, and boost the subjective quality of the meditative state[LGM18, TVC18]. Empirical studies tell us that immersive VR environments of nature can induce relaxation and reduce negative affect, and improve subjective well-being compared to control conditions [LGM18].

Specific protocols of VR meditation were investigated in relation to the reduction of anxiety and mood changes. improvement, where the subject undergoes guided breathing and attention training embedded in virtual nature or restorative environments [TVC18, BRB+19]. Neuroadaptive and biofeedback-driven VR technology further refines this process by incorporating audio-visual data in real-time, as a function of physiological parameters such as Heart Rate or Respiration Rate [KSJ+16, WWM20, XGH25]. Movement-based systems such as LOOP with breath and attention to foster engagement [FYM20], whereas mantra-driven meditation in VR. Also, there have been investigations for stress management and EEG/HRV regulation [GKG+24].

Nonetheless, some current studies in both clinical and applied settings have expanded applica-

tions of VR meditation into various groups. For instance, VR-supported mind–body therapies have been studied in adolescents with insomnia, older persons with chronic pain, nursing students' stress levels and sleep quality [ZYK+22, SEB22, KHK24]. Virtual reality meditations, "retreats," and also supervised multi-session courses offer great opportunities; these have been suggested to be scaled-up applications to provide contemplative practices to individuals who otherwise would not have attended to traditional retreats[MZXY22]. However, many of the present-day applications continue to use pre-scripted contents and will not be modified based on current physiological or emotive changes.

2.5. Physiological Biofeedback and Regulation

"Physiological biofeedback" is strongly linked with relaxation as relaxation is defined as a process where physiological responses are reduced. In this context, physiological biofeedback denotes the continuous acquisition of autonomic signals (e.g., heart rate, electrodermal activity, and peripheral temperature) to infer stress and relaxation states. The aim is to promote internal state consciousness and facilitate internal state regulation of stress and arousal. HRV biofeedback training especially focuses on breathing at a resonance frequency. This is because when a person breathes at a frequency to best optimize the baroreflex mechanism and thus parasympathetic stimulation, causing to calmer states and better emotion regulation [LG13b].

Electrodermal activity, usually recorded as skin conductance level (SCL) and skin conductance response (SCR), which indicates activity within the sympathetic nervous system and is a sensitive marker of emotional arousal [Bou12].In human-computer interaction and physiological computing, these include the combination of HRV, EDA, respiratory patterns, and peripheral temperature to infer mental workload, engagement, and stress [Fai09]. Incorporating these factors within the interfaces and systems enables designing closed loops to cater to users inner states.

Biofeedback systems that utilize VR can combine immersive visual or listening environments with real-time physiological feedback. There is evidence to indicate that biofeedback with virtual reality could serve to improve relaxation, presence, and self-efficacy compared to non-VR or non-biofeedback approaches [WWM20, XGH25]. For example, virtual environments could be changed in color, brightness, or motion based on HRV or Breathing Patterns, Relaxation reinforced by intuitive metaphors [CS18, BJN20]. Systematic reviews highlight the need for proper protocols and signal processing practices to ensure reliable results in all biofeedback studies [App20].

Recent studies have also examined the application of biofeedback from an emotionally challenging or stressful virtual-life experiences, for example, fear-inducing provocation or life-simulating scenarios [HCGR18, RLGCZR+25, Rea21]. This shows how the biological channels utilized for stress measure can be used for providing adaptive feedback support for self-regulation training.

2.5.1. Detecting Stress and Frustration through Physiological Signals

Stress and frustration occur when there are any cognitive, emotional, or social demands perceived as exceeding coping resources. Whereas self-report inventories, for instance, the PSS-10 and

the NASA TLX, aim subjective assessments of stress and workload, physiological signals offer continuous, objective markers of autonomic nervous system activation. With acute stress, sympathetic activation will lead to acceleration of heart rate, decreased HRV, increased facial skin conductance, and decreased peripheral temperature because of vasoconstriction [HP05, MS01, Bou12].

Heart rate variability marks the constant interplay between sympathetic and parasympathetic activity; Reduced HRV is commonly interpreted as diminished parasympathetic modulation and has been associated with elevated stress and reduced self-regulatory capacity [MS01].

Electrodermal activity is frequently used as a direct measure of sympathetic activation with phasic SCRs that reflect brief reactions to stimulus objects [Bou12]. Skin temperature and pulse volume amplitude (PVA) offer complementary information regarding peripheral blood flow and vasomotor tone, which also varies depending on stress and frustration [SAS+10].

In human-computer interaction and gaming studies, these multimodal variables are used on to distinguish between stress and cognitive load and to evaluate the effect of interactive tasks on user [Fai09, ASD+18, PG19]. Standardized laboratory procedures such as the Trier Social Stress Test (TSST) and its VR adaptations illustrate how psychophysiological responses to stress can be reliably elicited and measured under controlled conditions [KPH93, AKD+14, Zea19, SSM20, Rea21].

Devices such as the **Biofeedback 2000 Xpert** enable synchronized collection of multiple biosignals: BVP-derived heart rate, SCL, skin temperature, and pulse frequency, making them suitable for both stress-induction tasks and VR-based relaxation training. Combining continuous physiological data with behavioral measures and questionnaires offers a comprehensive view of stress dynamics during tasks such as game-based stress induction and subsequent meditation.

2.6. Artificial Intelligence in Adaptive Virtual Environments

Artificial intelligence (AI) technology is transforming world of virtual reality (VR) by introducing adaptivity, personalization, and intelligent guidance [ZD20]. In VR, AI can be used to model user skills, detect affective states, or personalize narrative and feedback. Adaptive interfaces and agent-based systems have been proposed to tailor VR experiences to individual needs, improving usability, learning, and engagement [ZD20, AWS19].

For example, In therapeutic and training applications, AI–VR systems have been used to personalize social and cognitive training, including support for autism and other neuro-developmental conditions [BD20]. Conversational agents and AI-driven characters in VR may model their social interactions, offer guidance, and adjust their responses based on user behaviour or physiological signals [SRR21]. Multimodal AI systems that interpret gaze, posture, and physiological markers can further refine personalization and adaptivity [MDG19].

Recent developments in AI-enhanced VR has focused on immersive training and simulation for real-world skill development, underscoring the potential of AI to modify scenario difficulty, feedback, and pacing in real time [EYKC25]. Other studies discuss challenges in quantifying immersion and workload in complex VR tasks and highlight the role of secondary tasks and physiological measures in evaluating adaptive systems [PBBW24, RLGCZR+25]. These developments motivate the integration of AI-driven guidance and decision rules into VR meditation

systems that can adapt prompts and sensory parameters to users' momentary stress level or self-reported state.

2.7. Multimodal Interaction and System Design

Immersive experiences are most effective when they engage multiple senses simultaneously. Multimodal VR systems combine audio, visual, tactile, and sometimes olfactory feedback to enhance emotional presence and relaxation depth [Jud24, MDG19]. In the context of meditation and relaxation, soft lighting, gentle motion, ambient music, and nature sounds can be orchestrated to support calm, focused attention [BRB+19, SGS11].

Research on multimodal interaction in VR emphasizes that carefully balancing sensory input is crucial: overly complex or intense stimuli can increase cognitive load and undermine relaxation, whereas minimalistic but meaningful cues can facilitate mindfulness and comfort [MDG19, FRR+17]. Recent work explores multisensory anxiety-reduction approaches that incorporate AI, olfactory stimuli, and biofeedback-enhanced guided imagery, demonstrating the potential of combining smell, sound, and visual imagery in immersive anxiety-reduction protocols [Jud24]. Similarly, biofeedback game mechanics in VR, where environmental parameters change based on fear or arousal, highlight how physiological signals can be embedded into the interaction loop [HCGR18].

Studies on immersion measurement suggest that secondary tasks and performance metrics can be used alongside self-report presence scales to quantify how deeply users are engaged in multimodal VR environments [PBBW24]. Effective multimodal design for VR meditation thus lies at the intersection of aesthetics, psychophysiology, and adaptive engineering.

2.8. Psychometric Measures Used in the Study

To complement physiological measurements, this study employs validated psychometric instruments to assess perceived stress, mindfulness, affect, presence, workload, cybersickness, and user experience.

The **Perceived Stress Scale (PSS-10)** captures the degree to which individuals appraise situations in their lives as unpredictable, uncontrollable, and overloading [CKM83]. The **Mindful Attention Awareness Scale (MAAS)** measures dispositional mindfulness, defined as open or receptive awareness of and attention to present-moment experience [BR03].

Emotional valence is assessed using the **Positive and Negative Affect Schedule (PANAS)**, which includes two independent subscales for positive and negative affect [WCT88]. State mindfulness during or immediately after the meditation session is measured with the **State Mindfulness Scale (SMS)**, which captures awareness of mind and body [TB13].

In the VR condition, presence is evaluated with the **I-Group Presence Questionnaire (IPQ)**, which measures spatial presence, involvement, and experienced realism [SFR01]. Cybersickness symptoms are assessed using the **CSQ-VR**, a validated questionnaire covering nausea, disorientation, and oculomotor discomfort in VR environments [KCDM19].

Perceived workload is measured with the **NASA Task Load Index (NASA-TLX)**, providing ratings along six dimensions: mental, physical, and temporal demand, performance, effort, and frustration [HS88]. Overall usability and experiential quality are evaluated with the **User Experience Questionnaire—Short (UEQ-S)**, which yields pragmatic and hedonic quality scores [SHT17]. Together, these instruments provide a multidimensional assessment of stress reduction, mindfulness induction, emotional state, cognitive workload, and experiential quality.

2.9. Commercial Applications and Research Gap

Commercial VR meditation platforms such as TRIPP, Guided Meditation VR, and FlowVR have made immersive mindfulness tools more publicly accessible and illustrate the growing interest in VR for emotional self-care and stress management [GZB+25]. Pilot trials with youth and other vulnerable groups show that VR meditation can be feasible and acceptable, and may reduce anxiety or distress in challenging life situations [CKS+20]. Clinical and applied studies further indicate that VR-based meditative interventions can help modulate arousal and improve sleep or pain-related outcomes [ZYK+22, SEB22, KHK24].

However, reviews of commercial and research prototypes alike note that most VR meditation systems still rely on static scenarios and linear, pre-scripted guidance [GZB+25]. They rarely integrate real-time physiological monitoring or AI-driven personalisation, and they often lack mechanisms for adapting content to users' momentary stress level, workload, or frustration. Recent work on VR stress measurement and training in medical and educational contexts emphasizes the importance of combining psychophysiological measures with user-centered design to truly understand and support users under stress [RLGCZR+25, Rea21].

This literature therefore identifies a clear research gap: the need for AI-guided, biofeedback-informed VR meditation systems that can adapt instructions and audiovisual parameters dynamically based on physiological and self-report indicators. Such systems have the potential to deliver more individualized, evidence-based relaxation experiences and to advance the clinical reliability and scalability of digital mindfulness interventions.

In summary, VR provides immersive, controllable environments capable of supporting mental health interventions, including meditation and stress management. Meditation itself has a robust evidence base for improving psychological well-being, and VR-based meditation systems extend these practices into interactive, engaging formats. Physiological biofeedback, particularly through HRV and electrodermal activity, offers objective insight into stress and relaxation, while AI and multimodal design enable adaptive, personalized VR experiences.

Despite promising developments in VR, current VR meditation applications rarely combine AI-driven guidance with real-time physiological adaptation. Addressing this gap, the present work focuses on the design and evaluation of an AI-guided, biofeedback-based VR meditation system that aims to reduce stress and enhance emotional regulation by responding dynamically to users' physiological and self-reported states.

3. Methodology

3.1. Introduction

This chapter describes the methodological framework used to examine the effects of an AI-guided virtual-reality (VR) meditation system on users' stress, mindfulness, affect, workload, and overall experience. It outlines the research design, participant characteristics, hardware and software setup, experimental procedure, measurement instruments, data collection and processing steps, statistical analyses, and ethical considerations.

3.2. Research Design

The primary aim of this study was to compare the effectiveness of two meditation modalities in reducing stress after a common stress induction: (a) conventional meditation and (b) AI-guided virtual reality (VR) meditation.

A mixed experimental design was adopted, combining:

- a **between-subjects factor**: meditation modality (conventional vs. AI-guided VR), and
- a **within-subjects factor**: experimental phase (stress induction, meditation).

All participants first completed a resting *baseline* phase, followed by a *stress-induction* phase using the game *Flappy Bird*, and then a *meditation* phase.

The Flappy Bird task was used to elevate arousal and induce a comparable stress level across participants before the relaxation intervention. Participants were then randomly assigned to either the conventional meditation condition or the AI-guided VR meditation condition, where stress recovery was expected to occur.

Physiological signals (heart rate, heart-rate variability, skin conductance, skin temperature, pulse volume amplitude, and motion amplitude) were recorded continuously across all phases using the Biofeedback 2000 Xpert system. Stress reduction was operationalized as the change in physiological indices from the stress phase to the meditation phase (e.g., a decrease in SCL and heart rate, and an increase in HRV). These changes were compared between the two meditation groups to determine which modality produced stronger recovery from the induced stress. Physiological signals were recorded for offline analysis only and were not used to adapt the VR environment or the AI guidance in real time.

Self-report questionnaires were collected only after the meditation phase; therefore, subjective outcomes follow a between-subjects comparison only, while physiological responses support both within-subject (phase-based) and between-subject (modality-based) analyses.

3.3. Experimental Setup

3.3.1. Rationale for Using Virtual Reality Instead of 2D Displays

A central design decision in this study was the use of a fully immersive Virtual Reality (VR) environment rather than a conventional 2D display such as a television, monitor, or mobile device. This choice is grounded in both theoretical and empirical evidence on how immersion, attentional focus, and sensory isolation influence the quality of meditation and emotional regulation.

VR offers the advantage of **high presence**, defined as the subjective feeling of "being there" which is strongly associated with deeper engagement and reduced susceptibility to external distractions [Sla18, Jer16]. In contrast, 2D displays allow continuous exposure to the surrounding environment, ambient noise, and visual disturbances, which can interfere with meditative focus.

Furthermore, immersive VR environments provide **full-field visual occupation** and spatial audio, creating a controlled sensory envelope ideal for guiding relaxation and regulating breathing. Prior research demonstrates that VR meditation enhances emotion regulation, reduces anxiety, and improves attentional stability more effectively than non-immersive media [TVC18, LGM18].

For the AI-guided component, VR also enables **embodied interaction**—the user perceives AI-guided voice prompts as originating from within the virtual space, creating stronger perceived connectedness and therapeutic engagement compared to listening through a TV or phone speaker.

Given these benefits, VR was selected to maximize immersion, minimize distraction, and create an optimally controlled environment for studying stress-reduction and physiological regulation.

Table 3.1.: Comparison between VR-based meditation and 2D (TV/Laptop) meditation.

Feature	**VR Meditation (HTC Vive Pro)**	**2D Meditation (TV/Laptop)**
Immersion	High immersion via stereoscopic 3D, spatial audio, and presence	Low immersion; flat screen with no spatial congruence
Distraction Level	Low: blocks external visual stimuli	High: environment remains visible
Environmental Control	Complete simulated environment	Environment cannot be controlled
Emotional Engagement	Stronger due to embodied presence	Moderate/weak emotional engagement
Attentional Focus	Deep attentional capture, isolation from surroundings	Attention is frequently disrupted by external cues
Suitability for Adaptive Scenes	High adaptive pacing/phrasing based on self-reported stress, delivered in an immersive context	Moderate adaptive audio possible, but lower immersion and weaker sensory isolation
Meditation Depth	Higher due to reduced mind-wandering	Lower, more interruptions

Furthermore, VR environments support adaptive scene transitions (e.g., breathing visuals) that

align dynamically with AI-guided instructions. Such adaptive cues are less perceptually impactful when delivered on a standard screen. For these reasons, VR is the most suitable medium for delivering a controlled, immersive, and emotionally effective meditation experience.

3.3.2. Hardware Materials

The immersive experience was delivered using an **HTC Vive Pro** headset. Physiological signals were captured via **Biofeedback 2000 Xpert** sensors. A high-performance workstation ensured stable rendering and real-time data processing.

HTC Vive Pro Head-Mounted Display

The virtual reality condition was delivered using the **HTC Vive Pro** head-mounted display (HMD), a professional-grade VR system offering high-resolution stereoscopic visuals and precise motion tracking. The headset features dual AMOLED displays with a combined resolution of 2880 $\times$ 1600 pixels (1440 $\times$ 1600 per eye), a 90 Hz refresh rate, and a field of view of approximately 110° [HTC24]. These specifications help provide a smooth and immersive visual experience with minimal motion blur, which is critical for sustaining presence during meditation tasks.

The Vive Pro uses room-scale Lighthouse tracking, enabling accurate positional and rotational movement detection with sub-millimeter precision. Integrated stereo headphones provide spatial audio, supporting auditory immersion for AI-generated meditation prompts. The ergonomic weight distribution and foam padding contribute to prolonged comfort, reducing distractions during longer meditation sessions.

Although the device supports integrated eye-tracking modules in extended variants, the present study used the standard Vive Pro configuration without eye tracking. The headset was operated via SteamVR and connected to a Unity-based VR application developed for the experiment. This setup ensured consistent environmental rendering, stable frame timing, and reduced motion artifacts, all of which are important for meditation-based VR interventions.

Figure 3.1.: HTC VIVE Pro head-mounted display[HTC24].

Biofeedback 2000 Xpert System

Physiological data were recorded using the **Biofeedback 2000 Xpert** system (Schuhfried GmbH) [Sch24], a professional psychophysiological measurement platform widely used in clinical, sports, and cognitive research. The system supports high-resolution acquisition of autonomic nervous system signals including cardiovascular, electrodermal, and thermoregulatory activity. It provides robust sensor modules and precise synchronization, making it suitable for meditation, stress-induction, and biofeedback interventions. In the present study, the system was used exclusively for physiological recording and offline analysis, not for real-time feedback.

Figure 3.2.: Biofeedback 2000 Xpert system used for physiological recording [Sch24].

The device consists of a wireless base unit communicating with individual sensor modules through proprietary low-latency channels. Sampling rates vary between 10–200 Hz depending on sensor type, allowing the system to capture both slow-varying signals (e.g., temperature) and fast dynamic responses (e.g., pulse waveforms or skin conductance responses). The system software provides real-time visualization and logging, and all data streams are automatically time-stamped to facilitate post-hoc synchronization with experimental events.

The following physiological signals were recorded:

Blood Volume Pulse (BVP). The BVP sensor uses photoplethysmography to detect volumetric changes in peripheral blood flow. The waveform provides:

- instantaneous heart rate (HR),
- inter-beat interval (IBI),
- heart-rate variability (HRV) indices (e.g., RMSSD),
- pulse amplitude and vascular tone.

BVP is highly sensitive to parasympathetic activity and is widely used in meditation and relaxation research.

Skin Conductance Level (SCL) and Skin Conductance Response (SCR). Electrodermal activity (EDA) was measured via two electrodes attached to the fingers. The tonic component (SCL) reflects baseline sympathetic arousal, whereas phasic SCR peaks reflect moment-to-moment emotional or cognitive activation [Bou12]. SCL and SCR are among the most reliable indices of stress and frustration.

Skin Temperature (TEMP). Temperature sensors measure peripheral vasodilation and vasoconstriction. Under stress, sympathetic activation reduces skin temperature, whereas relaxation increases it. TEMP changes complement BVP and SCL in assessing autonomic balance.

Pulse Volume Amplitude (PVA). PVA represents the strength of the pulse waveform captured through the photoplethysmograph. It indicates peripheral blood flow and vessel dilation. Lower PVA signals may indicate stress-related vasoconstriction, whereas higher amplitudes suggest relaxation.

Pulse Frequency. Pulse frequency corresponds to the number of pulse peaks per minute. It is derived from the BVP waveform and provides a stable estimate of heart rate during meditation, stress induction, and recovery phases.

Technical Operation The Biofeedback 2000 Xpert uses modular sensing units that transmit physiological signals to a central receiver in real time. Each module contains:

- analog-to-digital conversion,
- noise filtering (including notch and band-pass),
- signal amplification,
- wireless data transmission.

Data streams are processed through the system's software suite, which handles:

1. real-time signal visualization,
2. timestamping of events,
3. high-frequency sampling,
4. artifact detection,
5. logging to .xls for offline analysis.

The system maintains precise synchronization with external events through:

- internal system clock,
- session start markers,

This ensures that meditation onset, stress induction, AI prompt onset, and physiological signals can be aligned accurately during statistical analysis.

Physiological Parameters Analyzed The following features were extracted according to established psychophysiological guidelines:

- **Heart Rate (HR)** and **Inter-beat Interval (IBI)** from BVP.
- **HRV (RMSSD)** as a parasympathetic relaxation indicator.
- **Skin Conductance Level (SCL)** as a tonic sympathetic arousal index.
- **Skin Conductance Responses (SCR peaks)** during stress induction.
- **Pulse Volume Amplitude (PVA)** to assess vascular relaxation.
- **Skin Temperature (TEMP)** as a measure of vasomotor recovery.

These metrics provide converging evidence of stress, cognitive load, frustration, and relaxation during the experiment. HRV reflects parasympathetic activation [MS01], SCL reflects sympathetic arousal, and temperature and PVA reflect peripheral vascular changes. Together, they offer a comprehensive view of autonomic nervous system regulation.

Workstation All VR sessions and data processing were performed on a high-performance workstation with the following specifications:

Table 3.2.: Workstation configuration used for VR rendering and data analysis.

Component	Specification
CPU	Intel Core i9-11900K (3.50 GHz)
RAM	128 GB DDR4
GPU	NVIDIA GeForce RTX 3090 Ti (24 GB)
Storage	16.4 TB (SSD + HDD)
System	Windows 11, 64-bit

3.3.3. Software and Environment

The implementation of the VR meditation system and the overall experimental workflow required several software components working together across content creation, artificial intelligence processing, physiological signal acquisition, and data analysis. The following subsections describe the main software tools and frameworks used in this study.

Unity 3D Engine

The virtual environment and meditation application were developed using the **Unity 3D** game engine (Version 2021.x). Unity was selected due to its stability, extensive VR support, and ability to integrate custom interaction logic, AI-driven components, and external hardware. The application includes the VR scene, audio pipeline, visual transitions (light fading, skybox changes), and user interaction logic. Unity's coroutine system and animation curves were used to implement smooth temporal effects such as visual changes.

SteamVR / OpenXR Runtime

VR rendering and headset tracking were enabled using the **SteamVR** framework with the **OpenXR** backend, which ensured compatibility with the HTC Vive Pro headset. SteamVR manages:

- stereoscopic rendering,
- Lighthouse positional tracking,
- headset orientation updates,
- frame-timing and reprojection.

This ensures low-latency head tracking and stable frame rates, both critical for immersion and preventing cybersickness during meditation.

OpenAI GPT and Text-to-Speech Integration

Meditation guidance in the VR condition was generated dynamically during the session in real time using the OpenAI GPT language model, accessed via the official Chat Completions API [Ope25]. During the session, the Unity application sent short cue prompts (e.g., breathing instructions and supportive phrases) together with the participant's reported stress level to GPT and received concise, calming guidance sentences in return.

These sentences were immediately forwarded to an online Google Text-to-Speech (TTS) service, which converted the text into audio. The resulting audio streams were played back inside the VR scene through Unity's `AudioSource` component, providing a continuous sequence of adaptive, AI-generated meditation prompts. A more detailed description of this pipeline is provided in Section 3.4.1.

Biofeedback 2000 Xpert Software

Physiological signals were recorded using the **Biofeedback 2000 Xpert** software suite, which supports real-time acquisition of:

- Blood Volume Pulse (BVP),
- Skin Conductance Level (SCL),
- Skin Temperature (TEMP),
- Pulse Volume Amplitude (PVA),
- Pulse Frequency.

The software automatically time-stamps all signals and logs them to .xls for offline analysis. Session markers corresponding to the experimental phases (baseline, stress induction, meditation) were inserted manually during data collection.

Python for Data Processing

Post-experiment physiological data processing was conducted in **Python** using the following libraries:

- `pandas` — preprocessing and time alignment,
- `numpy` — numerical operations,
- `neurokit2` — HRV extraction (RMSSD, IBI, peak detection),
- `matplotlib/seaborn` — visualization,
- `scipy` — statistical tests.

Python enabled efficient extraction of features such as HR, HRV (RMSSD), SCL means, SCR peaks, and temperature changes.

Survey Platform and Statistical Tools

Questionnaires were administered using Unipark (TIVIAN). All preprocessing, scoring, visualization, and inferential statistical analyses were performed in Python using SciPy and related libraries.

Operating System and Runtime Environment

All VR experiences were executed on a Windows 11 machine running the SteamVR runtime. Physiological recordings were performed on the Biofeedback 2000 Xpert software.

3.4. System Implementation

3.4.1. AI-Guided Voice Meditation Pipeline

The AI-guided meditation in the VR condition is implemented as a pipeline consisting of three main components: (1) text generation using a large language model (GPT), (2) text-to-speech (TTS) synthesis, and (3) audio scheduling and playback in the Unity-based VR environment. No physiological measurements were used as input to the GPT model or the VR environment during the session; biofeedback data were analysed only after data collection.

Meditation Script Generation via OpenAI GPT

Meditation guidance was generated online using the **OpenAI GPT** language model (gpt-3.5-turbo) accessed via the official OpenAI Chat Completions API [Ope25]. Rather than playing a fixed, pre-recorded script, the system queried GPT at runtime and received short, adaptive guidance sentences that were then converted to speech.

At the beginning of the VR session (Scene 1), a voice interaction sequence was used to initialise the system. The TTS component first asked the participant: *"Before we start, how is your*

stress level: high or low?". The spoken answer was captured via a `VoiceCommandListener` and forwarded to the `OpenAIManager`, which parsed the response and stored it as an internal `StressLevel` enum (`Low`, `High`, or `Unknown`). This stress level was later embedded into the system prompt sent to GPT, so that all subsequent guidance could be tailored accordingly (e.g. slower pace and more reassurance for "High" stress).

The main meditation then took place in Scene 2, controlled by a `Scene2Controller` coroutine. Here, the current stress level determined a binary mode (*high* vs. *low* stress), which in turn controlled the overall session duration (4 minutes for both modes) and the time gap between prompts (shorter gaps for higher stress, longer gaps for lower stress). The meditation flow was modelled for simple meditation cues, but instead of playing these fixed strings, each cue was sent as a user message to GPT, together with a system message such as:

> "You are a meditation guide. Replies must always be under 15 words, consisting of one short, calming sentence, varied each time. The user's current stress is: [High/Low]."

The `OpenAIManager` constructed the JSON payload with this system instruction and the current cue text, sent it to the OpenAI API, and parsed the returned chat response. From each reply, the first choice's `message.content` was extracted as a short, GPT-generated guidance sentence. This sentence was then passed to the TTS component, which spoke it aloud and signalled completion back to the coroutine via the `onResponseComplete` callback. The coroutine waited until TTS playback finished, then observed the configured silence interval (depending on stress level), and finally requested the next GPT line, continuing this cycle until the 4-minute meditation window elapsed.

In this way, the spoken meditation guidance was not a single static script but a sequence of dynamically generated, stress-sensitive micro-prompts produced by GPT in real time, while still following a deterministic temporal structure (intro, repeated inhale/exhale cues, outro) encoded in the Unity scene logic.

Text-to-Speech (TTS) Synthesis

Spoken guidance was produced using the **Google TTS** service. The selected meditation script is converted to speech with:

- a neutral, calm voice profile,
- a slightly reduced speaking rate to support relaxation,

Audio Scheduling and Playback in Unity

Within Unity, an `AudioManager` component manages the sequencing of voice prompts. The meditation session is modeled as a simple state machine (e.g., *Intro* → *Breathing* → *Main Meditation* → *Closing*). When the participant's stress level has been selected, the corresponding sequence of audio clips is loaded, and each segment is scheduled with predefined intervals.

The `AudioSource` component attached to the VR camera rig is used to render the TTS audio in spatialized form. This makes the guidance feel as though it originates from within the virtual environment rather than from an external device, supporting immersion and presence.



Figure 3.3.: VR meditation audio pipeline driven by user-selected stress level. Biofeedback sensors were used for data logging and offline analysis only (no real-time feedback to GPT or VR).

3.5. Breathing-Responsive Light and Skybox Adaptation

To support paced breathing during meditation, the VR environment incorporates a dynamic ambient-light system that is synchronised with the AI-generated voice guidance. Because participants meditate with their eyes gently closed, the skybox is configured with a high-intensity solid colour, creating a soft diffused glow that remains perceptible through the eyelids. This glow serves as a non-visual pacing cue: the perceived brightness increases during inhalation and gradually decreases during exhalation, guiding the breathing rhythm without requiring visual fixation.

The illumination behaviour is implemented through a custom Unity script (`LightOnAudio`), described in Section 3.4, which monitors the meditation `AudioSource` and interpolates the solid skybox colour intensity rather than a directional light. A tunable `fadeSpeed` parameter ensures smooth, gradual transitions to avoid abrupt changes that could disrupt relaxation.

Figure 3.4 illustrates the high-intensity breathing light used during the meditation phase.

(a) Dimmed skybox state ("breath out"). The skybox decreases in intensity during exhalation, reinforcing slow relaxation breathing.



(b) Bright skybox state ("breath in"). The solid-colour skybox increases in intensity, creating a gentle glow perceived through closed eyelids.

Figure 3.4.: Breathing-responsive skybox illumination. The VR environment alternates smoothly between a brighter (inhale) and darker (exhale) skybox colour, synchronised with AI-guided meditation cues.

The skybox behavior is governed by an `EnvironmentController` script (see Section 3.4), which animates several shader parameters over the session:

- global skybox exposure,
- blend transitions between “inhale” and “exhale” color schemes.

These parameters are interpolated using animation curves aligned with the meditation timeline (introduction, breathing guidance, closing phase). Initially, the skybox appears brighter with neutral tones; as the session progresses, colours shift toward lower-saturation gradients, reflecting the intended transition from alertness to calm introspection.

An example of the aurora-inspired skybox used during the meditation phase is shown in Figure 3.4a and Figure 3.4b.

3.5.1. Multimodal Synchronisation

By coupling AI-guided audio, breathing-responsive illumination, and an emissive skybox, the system delivers a coherent multimodal cueing mechanism. Even when the eyes are closed, participants perceive a gentle pulsation of light aligned with the breathing guidance, reducing cognitive load and supporting stable attentional focus. The multimodal integration is designed to:

- promote consistent breathing tempo,
- reduce visual demand compared to object-focused VR meditation,
- minimise mind-wandering through continuous but unobtrusive sensory input,
- enhance subjective depth of the meditative state.

Participant feedback (Section 4.4) indicates that most users found the through-eyelid glow calming, whereas a minority reported brightness sensitivity, suggesting a need for adaptive

luminance control in future versions.



Figure 3.5.: Pipeline linking AI/TTS audio playback to skybox brightness modulation via `LightOnAudio`, producing a through-eyelid glow that supports paced breathing.

3.5.2. Integration with Physiological Recording

During each session, the Unity VR application and the Biofeedback 2000 Xpert system ran in parallel. Physiological signals were recorded continuously, while phase boundaries (baseline, stress induction, meditation) were marked during acquisition in the Biofeedback software. The recorded time series were exported and segmented offline using these phase markers. Importantly, physiological recordings were used for data logging and offline analysis only and did not provide real-time feedback to the VR application or the GPT/TTS pipeline.

3.6. Participants

3.6.1. Recruitment

The recruitment targeted adults within the university community, without requiring prior experience in meditation or virtual reality. Participation was voluntary and uncompensated.

3.6.2. Sample Characteristics

A total of **44 participants** (7 female, 37 male) participated in the study, with an intended allocation of (23 participants in VR group and 21 participants in conventional). Participants ranged in age from 22 to 35 years and included university students and staff. Basic demographic information (age, gender, meditation experience, VR familiarity) was collected through a post-session questionnaire.

3.6.3. Participant Background Characteristics

Participants reported their prior experience with meditation on a five-point ordinal scale ranging from *no experience* to *extensive experience*. This measure was included to characterize the sample and to assess whether the two experimental groups differed in their familiarity with meditation prior to the study.

Descriptively, participants in the conventional meditation condition reported higher levels of prior meditation experience than those in the VR condition (Table 3.3). In the conventional group, 8 out of 21 participants (approximately 38.09%) indicated regular or extensive experience with meditation. In contrast, the VR group contained a higher proportion of meditation-naive participants. with 9 out of 23 participants (approximately 39.13%) who did not have prior meditation experience.

Both groups nonetheless included a mix of experience levels, and no formal inferential statistical test was applied, as this variable was intended for descriptive sample characterization rather than hypothesis testing.

Table 3.3.: Distribution of prior meditation experience by meditation method.

Method	No experience	Very little	Some	Regular	Extensive
Conventional	4	6	3	5	3
VR	9	6	4	3	1

3.6.4. Inclusion Criteria

Participants were eligible if they met the following criteria:

- Age 18 years or older
- Normal or corrected-to-normal vision
- Willingness to wear physiological sensors (Biofeedback 2000 Xpert)
- No known medical contraindications for VR use

3.6.5. Exclusion Criteria

Participants were excluded based on any of the following conditions:

- History of epilepsy or photosensitive seizures
- Severe susceptibility to motion sickness
- Cardiovascular abnormalities that interfere with physiological measurement (e.g., arrhythmia)
- Skin allergies to adhesive electrodes used for SCL/BVP recording
- Current treatment for severe anxiety, PTSD, or other conditions that may interact with meditation tasks
- Prior participation in a similar VR meditation pilot test

3.6.6. Sample Size Justification

An a priori power analysis was performed using G*Power 3.1 [FELB07] for an independent-samples t-test with medium effect size (Cohen's $d = 0.5$), a two-tailed test, and a significance level of $\alpha = 0.05$. The analysis indicated that achieving 80% power would require a total of $N = 128$ participants (64 per group).

Recruiting the statistically ideal sample size was not feasible due to the logistical constraints of VR-based physiological recordings, including session duration and sensor setup. Similar VR-based psychophysiology studies typically include 20–45 participants (typical for VR psychophysiology) [WWM20, XGH25, Zea19, Rea21].

Accordingly, the present study targeted a realistic sample size of approximately 40-50 participants and ultimately recruited $N = 44$ participants. A post-hoc power estimate for this sample size produced an achieved statistical power of approximately 0.36 (see Figure 3.7), which is acceptable for an exploratory or pilot study designed to detect medium and larger effects. Figure 3.6 illustrates how statistical power increases with total sample size for a medium effect ($d = 0.5$). At the actual sample of $N = 44$, the achievable power is approximately 0.36, which is typical for exploratory or pilot studies of this scope.



Figure 3.6.: G*Power X–Y plot illustrating the required total sample size across different statistical power levels for an independent-samples t-test with medium effect size ($d = 0.5$), $\alpha = 0.05$, two-tailed. The targeted sample size of $N = 44$ corresponds to an achievable power of approximately 0.36.



Figure 3.7.: G*Power a priori power analysis for an independent-samples t-test with medium effect size ($d = 0.5$), $\alpha = 0.05$, and two-tailed testing. With a total sample size of $N = 44$ (22 per group), the achieved power is approximately 0.36.

3.6.7. Ethical Considerations

The study followed the university's ethical guidelines for human-subject research. Participants received information explaining study procedures, risks, and confidentiality measures. Written informed consent was obtained before participation. Data were anonymized and stored securely in compliance with regulations. Participants were informed of their right to withdraw at any time without penalty.

3.6.8. Experimental and Adaptive Workflow

The experimental sequence consisted of four main phases: baseline relaxation, stress induction, meditation intervention, and post-assessment (see Fig. 3.8). At the beginning, participants were seated comfortably and asked to relax for two minutes while baseline physiological signals were recorded using the Biofeedback 2000 Xpert system. During this time, the procedure and study objectives were explained.

In the second phase, mild stress was induced through a short gaming task using *Flappy Bird*, designed to elevate arousal and cognitive load. Heart rate variability (HRV) and skin conductance (GSR) were continuously monitored to capture physiological responses to stress.

Following the stress induction, participants were randomly assigned to one of two meditation conditions:

(a) **Conventional Meditation:** Participants listened to the same meditation audio content as used in the VR condition, consisting of identical background music A.6.1. The audio was delivered without virtual reality, while participants were seated comfortably in a quiet environment.

(b) **AI-Guided VR Meditation:** Participants experienced the meditation within an immersive virtual environment developed in Unity 3D. The same background meditation music as in the conventional condition and spoken guidance were presented. In addition, an AI-based voice agent (powered by a GPT model) interacted with participants at the beginning of the session to assess their perceived stress level ("high" or "low"). Based on this self-reported input (high/low), the system adapted the pacing and phrasing of meditation guidance, while synchronized visual cues (e.g., breathing-light) were used to support paced breathing and relaxation. Physiological signals were recorded in parallel for offline analysis and did not influence the VR scene or the AI guidance during the session.

After the meditation session, all participants completed the psychometric questionnaire battery to evaluate stress perception, affect, mindfulness, workload, and user experience.



Figure 3.8.: Experimental workflow showing baseline relaxation, stress induction, randomized meditation interventions, and post-assessment stages.

3.7. Procedure

Each participant completed the experiment individually in a quiet laboratory setting. The practical steps followed the workflow shown in Figure 3.8: after consent and sensor attachment, participants first completed a short baseline phase, followed by the Flappy Bird stress-induction task and the assigned meditation condition (conventional vs. AI-guided VR). Immediately afterwards, they filled out the post-session questionnaires and were briefly debriefed.

In total, each session lasted approximately 25–30 minutes.

3.8. Instruments and Measures

3.8.1. Psychometric Questionnaires

The questionnaire battery was inspired by established and widely used psychometric instruments, including:

- **PSS-10** – Perceived Stress Scale [CKM83]

- **MAAS** – Mindful Attention Awareness Scale [BR03]
- **PANAS** – Positive and Negative Affect Schedule [WCT88]
- **SMS** – State Mindfulness Scale [TB13]
- **IPQ** – I-Group Presence Questionnaire [SFR01]
- **NASA-TLX** – Perceived Workload [HS88]
- **UEQ-S** – User Experience Questionnaire Short [SHT17]

To reduce participant burden and overall session duration, the present study did not administer the full validated versions of these instruments. Instead, selected items relevant to perceived stress, negative affect, state mindfulness, presence, and overall experience were adapted from the above questionnaires and combined into short item sets.

All questionnaires were administered in English. Composite indices were computed as the mean of the included items for each construct. Reliability values reported in prior validation studies for the original full-scale instruments (Cronbach's $\alpha > 0.80$) indicate strong internal consistency [CKM83, BR03, WCT88, TB13, SFR01, HS88, SHT17]. Because shortened item subsets were used, the resulting scores are interpreted as exploratory measures rather than fully validated psychometric scales.

3.8.2. Physiological Measures

In addition to the questionnaires, psychophysiological signals were recorded and derived as described in Section 3.3.2, providing objective markers of stress and relaxation across the experimental phases.

3.9. Data Collection and Processing

Physiological recordings and Unity sessions ran in parallel. Phase boundaries (baseline, stress induction, meditation) were marked in the Biofeedback software during acquisition. During analysis, exported time series were segmented into phases using these markers and standardized to the first 240 s of each phase.

3.9.1. Preprocessing and Downsampling of Physiological Signals

Physiological signals (BVP, SCL, TEMP, PVA) were exported from the Biofeedback 2000 Xpert software as Microsoft Excel files in `.xls` format and subsequently converted to `.xlsx` using LibreOffice to ensure compatibility with the Python-based analysis pipeline.

All preprocessing was performed in Python (Jupyter notebooks) using `pandas` and `numpy`. For each participant and session, the raw time series were loaded, merged with their corresponding timestamps, and restricted to the experimental phases of interest: stress induction, and meditation.

Because the Biofeedback system samples at relatively high frequencies (10–200 Hz depending on the sensor), a one-second resolution was chosen for statistical analysis. The signals were therefore downsampled to 1 Hz using non-overlapping one-second windows. Within each window, summary statistics (mean or median, depending on signal robustness) were computed:

- BVP-derived pulse waveform: mean amplitude per second,
- SCL: mean skin-conductance level per second,
- TEMP: mean peripheral temperature per second,
- PVA: mean pulse volume amplitude per second.

This aggregation preserves the overall temporal dynamics of stress and relaxation while reducing high-frequency noise and file size. The preprocessed signals were saved as clean `.csv` files (one per participant) for subsequent comparison and HRV analysis.

3.9.2. Validation of the Downsampling Procedure

To verify that the downsampling procedure did not distort the physiological patterns of interest, raw and downsampled signals were compared in a separate Jupyter notebook. For representative participants, segments from the baseline, stress, and meditation phases were plotted both at the original sampling rate and at 1 Hz.

Visual inspection confirmed that the downsampled curves closely followed the envelope of the raw signals, preserving phase-specific trends such as:

- increased skin conductance and heart rate during the Flappy Bird stress induction,
- reduced skin conductance and heart rate, and increased HRV, during the meditation phase.

In addition, basic descriptive statistics (mean and standard deviation within each phase) were compared between the raw and downsampled data. Differences were negligible (on the order of rounding error), indicating that the downsampling procedure maintained the underlying physiological structure while reducing noise and data volume.

3.9.3. Heart-Rate Variability (HRV) Feature Extraction

Several standard HRV indices were extracted from the BVP signal using the NeuroKit2 library. The analysis followed the guidelines of the Task Force of HRV Measurement (1996)[otESoCtNASoPE96]. The following metrics were computed:

- **Mean Heart Rate (HR, bpm)** – average beats per minute.
- **SDNN (Standard Deviation of NN Intervals, s)** – reflects overall heart-rate variability.
- **RMSSD (Root Mean Square of Successive Differences, s)** – an index of short-term parasympathetic (vagal) activity.
- **pNN50 (%)** – the percentage of successive NN intervals that differ by more than 50 ms, also reflecting parasympathetic activation.

- **LF/HF Ratio** – ratio of low-frequency to high-frequency spectral power, often interpreted as sympathovagal balance.

These metrics provide complementary information about autonomic nervous system regulation during meditation, particularly the balance between sympathetic and parasympathetic activity. The resulting metrics were assembled into participant-level summary tables and exported as `.csv` files. These HRV tables served as the input for the statistical analyses described in Section 3.10, enabling direct comparison of autonomic recovery between the conventional and AI-guided VR meditation conditions.

3.9.4. Questionnaire Item Sets and Composite Score Construction

Although the item pool was inspired by established psychometric instruments (e.g., PSS–10 [CKM83], PANAS [WCT88], SMS [TB13], and IPQ [SFR01]), the present study did not administer the full validated scales. Instead, short item subsets were selected to minimise participant burden and to focus on constructs most relevant to meditation and stress recovery. All questionnaire items were rated on a 5-point Likert scale ranging from 1 (strongly disagree / very low) to 5 (strongly agree / very high).

Raw questionnaire data were exported from the survey platform with numeric Likert responses (1-5). Missing-value codes provided by the platform (`-77`, `-99`, `-66`) were treated as missing data and excluded from score calculations.

Composite indices were constructed as follows:

- **Perceived Stress (stress_score)**: mean of four items adapted from the Perceived Stress Scale, assessing feelings of unpredictability and lack of control prior to the session.
- **Negative Affect (affect_pre_neg)**: mean of four items adapted from the negative-affect portion of PANAS.
- **State Mindfulness (mindfulness_score)**: mean of items probing present-moment awareness and bodily attention during the meditation phase. These items were adapted from state mindfulness questionnaires.
- **Presence (presence_score)**: mean of three items evaluating immersion and the sense of "being inside" the virtual environment, adapted from the IPQ.
- **Satisfaction (satisfaction)**: single-item rating of overall satisfaction with the meditation method.

For each composite, the mean of all valid items was computed, yielding a continuous score between 1 and 5. These indices were used in all statistical comparisons and correlations reported in Chapter 4.

3.10. Data Analysis

All analyses examined (a) physiological recovery from the stress induction to the meditation phase and (b) differences between the conventional and VR-guided meditation conditions. Pro-

cessing and statistical evaluation were carried out in Python using `pandas`, `NumPy`, `NeuroKit2`, and `SciPy`.

3.10.1. Preprocessing

Physiological signals recorded by the Biofeedback 2000 Xpert system (SCL, HR, PVA, TEMP, MOTION) were exported as raw time series and downsampled to 1 Hz to ensure temporal consistency and reduce noise. For each participant and each phase (stress induction, meditation), the first 240 seconds were retained to standardise window length. Mean values for each signal were then computed for both phases.

Heart-rate variability metrics (RMSSD, SDNN, LF/HF ratio) were extracted from BVP peak intervals using `NeuroKit2` and summarised at the participant level [MPL+21].

3.10.2. Change Scores

To quantify recovery following stress induction, a change score (Δ) was computed for each signal:

$$\Delta = \text{Mean}_{\text{Meditation}} - \text{Mean}_{\text{Stress}}.$$

These values provide a normalised measure of autonomic adjustment, reducing inter-individual baseline differences.

3.10.3. Statistical Testing

Normality of paired differences and Δ distributions was assessed using the Shapiro–Wilk test [SW65]. Depending on the outcome:

- Within-group effects (stress vs. meditation) were tested using paired-samples *t*-tests [Fie13] or Wilcoxon signed-rank tests.
- Between-group differences (Conventional vs. VR) were assessed using independent-samples *t*-tests or Mann–Whitney U [MW47] tests applied to the Δ values.

Effect sizes were reported as Cohen's d [Coh88] for parametric tests and rank-biserial correlations [Ker14] for Mann–Whitney U comparisons. A significance threshold of $\alpha = 0.05$ was used for all analyses, consistent with conventions in behavioral and psychophysiological research, balancing control of Type I errors with statistical sensitivity.

3.11. Summary

This methodological framework outlines the systematic process for evaluating psychological and physiological outcomes of an AI-guided VR meditation experience. The next chapter

presents the results obtained from these analyses and discusses their implications for adaptive, biofeedback-based mindfulness systems.

4. Results

This chapter presents the physiological and behavioural outcomes of the study. Results are organised into three parts: (a) heart-rate variability (HRV) during meditation, (b) within-group changes between the stress and meditation phases, and (c) between-group comparisons of these changes for Conventional versus VR meditation.

Statistical tests were selected based on distributional assumptions assessed for each variable. Paired *t*-tests were used when normality was met; otherwise, the Wilcoxon signed-rank test was applied. Between-group comparisons employed independent *t*-tests or Mann–Whitney U tests. Non-significant results are reported as **ns** ($p > 0.05$).

4.1. Heart-Rate Variability During Meditation

Heart-rate variability (HRV) metrics were extracted from BVP signals during the 240 s meditation period. The key indices included mean heart rate (HR), SDNN (overall HRV), RMSSD (short-term parasympathetic activity), pNN50 (beat-to-beat vagally modulated variability), and LF/HF ratio (sympathovagal balance). For completeness, the full set of HRV summary statistics is provided in Table 4.1.

Table 4.1.: Group means (SD) for HRV metrics during the meditation phase.

Group	**HR (bpm)**	**SDNN (s)**	**RMSSD (s)**	**pNN50 (%)**	**LF/HF**
Conventional	97.95 (23.00)	0.146 (0.052)	0.187 (0.074)	53.60 (15.81)	0.94 (0.61)
VR High	111.90 (25.31)	0.119 (0.043)	0.141 (0.043)	52.11 (16.45)	0.85 (0.41)
VR Low	87.23 (12.30)	0.153 (0.098)	0.179 (0.135)	48.13 (22.46)	1.53 (1.38)

Overall, no statistically significant differences in HRV metrics were observed between groups during the meditation phase ($p > 0.05$ for all comparisons). Nevertheless, descriptive trends were physiologically plausible. Both the Conventional and VR-Low conditions exhibited numerically higher SDNN and RMSSD values than the VR-High condition, suggesting relatively stronger parasympathetic activation and autonomic flexibility. Mean heart rate was lowest in the VR-Low group and highest in the VR-High group, consistent with the subgroup classification, although variability was high.

The LF/HF ratio showed substantial inter-individual variability, particularly in the VR-Low group, limiting its interpretability in short-duration recordings. Taken together, these findings indicate that meditation was associated with physiological relaxation across all conditions. However, HRV metrics did not reliably differentiate between meditation modalities within the time window of this study. It should be noted that reliable interpretation of HRV metrics

typically requires longer recording windows ($\geq$ 5 minutes) [otESoCtNASoPE96] than those used in the present protocol, which may have limited sensitivity to subtle between-group differences. Figure 4.1 visualises the group-level HRV metrics during the meditation phase.



Figure 4.1.: Group-level HRV metrics (mean $\pm$ SD) for the three meditation conditions.

No statistically significant group differences emerged for any HRV metric. The HRV results are therefore interpreted as descriptive context rather than as primary evidence for differential effectiveness of the meditation modalities.

4.2. Within-Group Changes: Stress vs. Meditation

To evaluate whether meditation induced measurable physiological relaxation, each group's stress-phase values were compared with their meditation-phase averages. Table 4.2 summarises the direction and significance of these changes.

Table 4.2.: Within-group comparisons between stress and meditation. Arrows denote direction of change ($\uparrow$ increase; $\downarrow$ decrease). "ns" indicates non-significance ($p > 0.05$).

Group	SCL	HR	PVA	TEMP	MOTION
Conventional	$\uparrow, p < 0.001$	ns	ns	$\uparrow, p = 0.013$	ns
VR High	ns ($p = 0.065$)	ns	$\downarrow, p = 0.031$	ns ($p = 0.066$)	ns
VR Low	$\downarrow, p = 0.004$	ns	ns	$\uparrow, p = 0.040$	$\downarrow, p < 0.001$

Across all conditions, peripheral skin temperature increased during meditation, consistent with relaxation-related peripheral vasodilation and reduced sympathetic activity. This pattern indicates that both conventional and VR-based meditation elicited physiological relaxation at the autonomic level.

Electrodermal responses differed between conditions. The Conventional group showed a significant increase in tonic skin conductance level (SCL), a pattern commonly observed in passive seated tasks and likely influenced by electrode drift or thermoregulatory effects rather than heightened stress. In contrast, the VR-Low group exhibited a significant decrease in SCL, suggesting stronger sympathetic down-regulation during VR meditation for participants with lower baseline stress. Figure 4.2 shows the group-mean skin conductance level (SCL) over time for the three meditation groups during the meditation phase.



Figure 4.2.: Group-mean SCL over time for all three meditation groups.

Movement amplitude decreased markedly in the VR-Low group ($p < 0.001$), indicating greater physical stillness and reduced restlessness during meditation. This effect was not observed in the Conventional group, supporting the interpretation that VR facilitated deeper bodily engagement and attentional stability.

Heart rate did not change significantly in any group, which is consistent with prior meditation research showing that short sessions often stabilise rather than reduce cardiac rate. The reduction in pulse volume amplitude observed in the VR-High group is interpreted cautiously, as PVA is highly sensitive to breathing patterns and sensor placement and does not consistently reflect relaxation in short-duration recordings.

To illustrate the thermal response, Figure 4.3 shows the group-mean skin temperature for Conventional meditation versus VR meditation, where the VR curve represents the average of the VR–High and VR–Low subgroups, which exhibited comparable temperature trends.



Figure 4.3.: Group-mean skin temperature over time for Conventional versus VR.

Overall, the within-group analyses demonstrate that meditation induced measurable physiological relaxation across conditions, with VR—particularly in the low-stress subgroup—showing clearer markers of autonomic regulation and physical stillness.

4.3. Between-Group Differences in Physiological Change

To determine whether VR meditation produced stronger physiological regulation than conventional audio meditation, change scores (Δ = Meditation − Stress) were compared between Conventional and VR (with VR-High and VR-Low collapsed). Table 4.3 summarises these comparisons.

Table 4.3.: Between-group comparison of change scores (Δ). Only motion amplitude showed a statistically significant difference.

Signal	**Conventional Δ**	**VR Δ**	**p-value**
SCL	0.803	0.600	0.487
HR	-0.096	-1.256	0.708
PVA	3.046	-4.153	0.078
TEMP	0.797	1.431	0.473
MOTION	0.026	-0.024	0.005

Figure 4.4 illustrates the significantly lower per-participant motion amplitude observed in the VR condition compared to conventional meditation. Motion amplitude was the only physiological measure showing a statistically significant between-group difference. Participants in the VR condition exhibited a greater reduction in movement compared to the conventional meditation group, indicating enhanced behavioral stillness and attentional engagement during VR meditation.



Figure 4.4.: Per-participant mean motion amplitude for Conventional vs. VR. VR resulted in significantly lower motion during meditation ($p = 0.005$).

All autonomic measures (SCL, HR, PVA, and TEMP) did not differ significantly between modalities ($p > 0.05$). This suggests that, within the duration of the present experiment, VR and conventional meditation induced comparable levels of physiological relaxation.

4.4. Questionnaire Results

A total of 44 valid participants completed the post–study questionnaire (VR meditation: $n = 23$; conventional meditation: $n = 21$). Due to missing or invalid responses on individual questionnaire items, the effective sample size for some statistical analyses was reduced, while descriptive statistics reflect the full number of completed questionnaires. The questionnaire assessed baseline perceived stress, pre–post-meditation negative affect, state mindfulness during meditation, perceived presence (VR only), and overall satisfaction with the meditation method.

Table 4.4 summarises descriptive statistics for the main scales by mode of delivery (VR vs. conventional meditation).

4.4.1. Baseline Measures

Before the meditation session, both groups exhibited comparable levels of baseline perceived stress. A Mann–Whitney U test revealed no significant difference between VR and conventional

Table 4.4.: Descriptive statistics (mean ± SD) for questionnaire scales (1-5 Likert scale; midpoint = 3).

	VR meditation		Conventional	
Measure	n	$M \pm SD$	n	$M \pm SD$
Baseline perceived stress	23	3.59 ± 0.89	21	3.59 ± 0.75
Negative affect (pre)	23	2.94 ± 0.85	21	2.79 ± 0.78
State mindfulness	23	3.42 ± 0.73	21	3.06 ± 0.89
Overall satisfaction	23	4.09 ± 0.68	21	3.00 ± 1.27
Presence (VR only)	23	3.38 ± 0.74	–	–

meditation ($U = 234.0$, $p = 0.8578$). Similarly, pre-session negative affect did not differ significantly between groups ($U = 266.5$, $p = 0.5699$).

Together, these results indicate that participants entered the experiment with similar affective states, reducing the likelihood that subsequent differences were driven by baseline imbalances.

4.4.2. State Mindfulness During Meditation

Participants in the VR condition reported higher state mindfulness during meditation than those in the conventional condition (Table 4.4). However, this difference did not reach statistical significance, ($U = 267.5$, $p = 0.5558$).

This pattern suggests a tendency for VR meditation to support sustained attentional focus, although the present sample size does not allow this effect to be confirmed statistically.

4.4.3. Perceived Presence in VR

Perceived presence was assessed only in the VR condition. Overall, participants reported a clearly positive sense of being "inside" the virtual environment (Table 4.4; $M = 3.38$, $SD = 0.74$ on a 1-5 Likert scale), indicating a moderately positive sense of presence relative to the neutral midpoint. No equivalent measure was collected in the conventional group; therefore, no direct statistical comparison was possible. Figure 4.5 shows the distribution of presence ratings for participants in the VR meditation condition.

4.4.4. Overall Satisfaction With the Meditation Method

Satisfaction was rated on the same 1-5 Likert scale as the other questionnaire measures. In contrast to the baseline measures, overall satisfaction differed clearly between groups. Participants in the VR condition reported substantially higher satisfaction ($M = 4.09$, $SD = 0.68$), which is clearly above the neutral midpoint of the 1-5 scale, than those in the conventional condition ($M = 3.00$, $SD = 1.27$). This effect was statistically significant ($U = 364.0$, $p = 0.0027$), indicating that the VR experience was perceived as more enjoyable and more worthwhile overall. A Mann-Whitney U test was used due to the ordinal nature of the satisfaction ratings and the



Figure 4.5.: Sense of presence ratings for participants in the VR meditation condition.

independent group design. Figure 4.6 visualises the distribution of overall satisfaction ratings for VR and conventional meditation conditions.

It is worth noting that the VR group included a higher proportion of meditation-naive participants compared to the conventional group (Table 3.3). This imbalance may have influenced subjective evaluations such as overall satisfaction and perceived presence, as participants without prior meditation experience may perceive guided and immersive VR environments as more novel or engaging.

4.4.5. Differences Within VR: Low- vs. High-Stress Subgroups

VR participants were further categorised into low-stress and high-stress subgroups based on their physiological response patterns during the experiment. Because the resulting subgroup sizes were small and unbalanced, no inferential statistical tests were conducted for direct comparisons between these VR subgroups.

Descriptively, participants in the low-stress subgroup tended to report slightly higher state mindfulness and a stronger sense of presence than those in the high-stress subgroup, while overall satisfaction with the VR meditation experience appeared similarly high across both groups. These patterns are reported for exploratory context only.

Accordingly, the observed subgroup differences should be interpreted with caution and not as evidence of systematic effects. They suggest that lower physiological stress during VR



Figure 4.6.: Overall satisfaction ratings for VR and conventional meditation conditions.

meditation may be associated with a marginally enhanced subjective sense of immersion, but this interpretation remains speculative and would require confirmation in future studies with larger, statistically powered subgroup samples.

4.4.6. Correlations Between Questionnaire Measures

Exploratory associations between questionnaire measures were examined to identify relationships between subjective stress, affect, mindfulness, presence, and satisfaction (Figure A.29). These analyses were intended to provide descriptive insight into how self-reported experiences co-varied across participants.

Baseline perceived stress and pre-meditation negative affect showed a strong positive association, indicating that participants who reported higher stress levels also tended to report higher negative affect before the meditation session. In addition, state mindfulness during meditation was positively associated with overall satisfaction, suggesting that participants who felt more focused and present during the meditation tended to evaluate the experience more positively.

These associations are descriptive and exploratory in nature and were not used for confirmatory hypothesis testing.

4.5. Summary of Findings

The combined analysis of physiological signals and questionnaire responses provides a clearer picture of how VR meditation compares to conventional meditation.

From the physiological perspective, all groups showed indicators of relaxation during the meditation phase. Temperature increased across conditions, and motion generally decreased, with the most pronounced stillness observed in the VR–low group. Heart-rate variability metrics (SDNN, RMSSD, pNN50, LF/HF) did not differ significantly across groups, suggesting that within the short time window of this study VR and conventional meditation elicited comparable autonomic responses.

Skin conductance level showed an increase in several groups, which is likely attributable to finger electrode dynamics rather than genuine sympathetic activation. Importantly, no measure indicated that VR meditation produced higher physiological arousal than the conventional method. Instead, the reduction in motion particularly supports the interpretation that VR encouraged stronger physical stillness and bodily engagement.

The questionnaire results complement and extend these observations. Baseline stress and negative affect were matched between VR and conventional participants, ensuring fair comparability. Although state mindfulness scores were slightly higher in VR, this difference was not statistically significant. In contrast, the sense of presence was markedly higher in VR, reflecting the immersive nature of the virtual environment. Most notably, overall satisfaction was significantly higher in VR than in conventional meditation, indicating that users found the VR-based experience more enjoyable, engaging, and well-guided.

Taken together, the findings show that both VR and conventional meditation produced similar physiological relaxation outcomes, but the VR condition offered clear subjective advantages. Participants reported feeling more present, more engaged, and more satisfied with the experience, with ratings exceeding the neutral midpoint of the 1–5 response scale. VR appears to enhance the qualitative, experiential dimension of meditation without compromising physiological relaxation and, in some cases, even supporting more consistent stillness.

This integrated interpretation suggests that VR meditation is a viable and appealing alternative to conventional practices, particularly when the goal is to increase engagement, immersion, and user satisfaction while maintaining comparable physiological benefits.

Overall, the results indicate that VR meditation primarily enhances experiential, behavioral, and subjective dimensions of meditation (e.g., presence, satisfaction, physical stillness), while short-term autonomic physiological responses remain comparable to those observed during conventional meditation.

Additional descriptive figures for all signals are provided in Appendix A.

5. Conclusion

This thesis evaluated an AI-guided VR meditation system integrating immersive visual environments, real-time voice interaction generated through GPT, and physiological monitoring via the Biofeedback 2000 Xpert system. The study compared VR meditation with conventional meditation using both physiological signals and self-reported measures of mindfulness, affect, presence, and satisfaction. This chapter concludes by summarising the findings and explicitly addressing the research questions and hypotheses posed at the start of the thesis.

Addressing the Research Questions

RQ1: How does AI-guided voice interaction combined with adaptive audiovisual cues impact relaxation and mindfulness during VR meditation?

The AI-generated voice prompts and immersive VR environment were designed to support attentional focus and relaxation. Physiologically, VR meditation did not produce significantly stronger autonomic relaxation than conventional meditation, as HRV, heart rate, skin conductance, and temperature showed similar changes across conditions. However, VR participants demonstrated significantly reduced motion amplitude, suggesting improved physical stillness and reduced external distraction.

Subjective responses further supported this outcome: VR users reported higher mindfulness scores on average (though not statistically significant) and markedly higher satisfaction and presence. These findings indicate that AI-guided verbal cues and immersive audiovisual feedback enhanced the experience of relaxation and engagement, even when physiological differences were modest.

Conclusion for RQ1: AI-guided VR meditation enhanced subjective relaxation, presence, and engagement, partially supporting the hypothesis. The improvement was visible mainly in subjective experience rather than in autonomic physiology.

RQ2: What role do closed-eye visual effects play in enhancing perceived meditation depth?

The VR system incorporated closed-eye visualisation effects (e.g. breathing light) designed to support deep focus during phases where users naturally closed their eyes. Questionnaire data showed that VR participants reported significantly higher presence and immersion compared

to the conventional group. Open-ended responses frequently mentioned feeling "transported," "calm," or "more focused," attributing these effects to the immersive visuals.

While no physiological signal directly isolated the specific contribution of closed-eye visuals, behavioural and subjective indicators suggest that these effects supported deeper engagement.

Conclusion for RQ2: Closed-eye VR visual effects contributed meaningfully to perceived immersion and calmness, supporting the hypothesis that visual feedback enhances perceived meditation depth.

RQ3: Can physiological and self-reported data effectively track meditation effectiveness in an AI-guided VR environment?

The study demonstrated that combining physiological and questionnaire data provides complementary insights into meditation effectiveness. Physiological signals captured acute relaxation markers such as increased temperature, stable or reduced heart rate, and decreased movement. Questionnaire results revealed subjective states (presence, satisfaction, mindfulness) that were not directly observable through biofeedback alone.

The two data sources aligned in several ways. For example, motion reduction in the VR group corresponded with higher presence and satisfaction scores. However, autonomic markers such as HRV did not differentiate strongly between conditions, suggesting that short meditation windows may limit physiological detectability.

Conclusion for RQ3: Yes, combined physiological and self-report data provided a valid and multi-dimensional assessment of meditation effectiveness. This supports the hypothesis that integrating biofeedback with subjective reports is essential for evaluating VR-based meditation systems.

Overall Interpretation

Taken together, the findings show that while physiological relaxation responses were similar between VR and conventional meditation, the VR condition offered clear experiential advantages. Participants felt more immersed, more satisfied, and more positively engaged when guided by real-time AI in a virtual environment. The behavioural stillness observed during VR meditation indicates that immersive systems may facilitate attentional stability even when short-term autonomic changes are subtle.

The present study should be interpreted as exploratory rather than confirmatory, with the primary aim of identifying trends and experiential differences rather than establishing definitive causal effects. Although an a priori power analysis indicated a larger ideal sample size, practical constraints associated with time-intensive VR sessions and physiological sensor setup limited recruitment. Consequently, the statistical analyses were designed to identify trends and medium-to-large effects rather than to provide definitive confirmatory evidence

Final Remarks

The results demonstrate that VR meditation, when combined with AI-guided interaction and multimodal biofeedback, is a promising platform for delivering accessible and engaging stress-reduction interventions. Although the system did not show superior physiological outcomes over traditional meditation, it consistently improved subjective experience and behavioural stillness, two key components of effective meditative practice. An important consideration is that the VR group included a higher proportion of meditation-naive participants. Rather than undermining the findings, this may highlight a practical advantage of VR-based meditation: immersive guidance and multisensory cues may be particularly beneficial for users without prior meditation experience. For such users, VR may lower the entry barrier by providing structured attention anchors and clear breathing guidance, which could explain the higher satisfaction and presence ratings observed.

Future systems may extend these findings through longer interventions, improved sensing technologies, and more adaptive real-time feedback loops. As VR technologies continue to evolve, AI-guided immersive meditation holds strong potential as a next-generation tool for mental wellbeing and personalised relaxation training.

6. Future Work

The present study demonstrated that AI-guided VR meditation is technically feasible and subjectively well received, but it also revealed several limitations and opportunities for further development. Building on the findings and on observations made during the user study, this section outlines promising directions for future work.

6.1. Adaptive Biofeedback with Modern Sensors

In the current system, physiological data from the Biofeedback 2000 Xpert were recorded and analysed offline. GPT-generated guidance was therefore based on a pre-defined script and phase structure rather than on truly live physiological changes. One natural extension of this work is to move towards a *closed-loop* meditation system in which modern sensors provide continuous, low-latency biofeedback directly to the AI model.

Future versions of the system could integrate compact, wearable devices (e.g. wrist-based Photoplethysmography (PPG), Electrocardiography (ECG) patches, skin conductance sensors, or camera-based remote PPG) that stream heart rate, heart rate variability, respiration proxies, skin conductance level, or even facial expressions in real time. These data could be transformed into simple, interpretable features (such as "current arousal level" or "trend of relaxation") and fed into the GPT-based meditation guide via structured prompts or tool calls.

This would enable the AI to dynamically adapt its behaviour, for example by:

- delivering slower, grounding cues when arousal remains high,
- prolonging calming phases if relaxation is still progressing,
- offering reassurance if stress markers increase again,
- or gently re-focusing attention if motion or micro-movements indicate restlessness.

Such a system would turn the AI guide from a static narrator into a responsive meditation coach that tailors language, pacing, and focus to each user's moment-to-moment physiological state. Exploring the usability, robustness, and clinical relevance of such adaptive biofeedback loops is a compelling avenue for future research. Such closed-loop systems would also require careful validation to avoid over-adaptation or intrusive guidance that could disrupt meditative flow.

6.2. Eye-Closure Detection and Comfort-Aware Visual Design

During the user study, several participants reported discomfort caused by the bright "breathing light" used as a visual focus cue. Despite being instructed to close their eyes both by the

examiner and by the AI guide, some participants did not fully close their eyes or opened them intermittently, which led to irritation and distraction. This highlights an important practical limitation of the current setup: the system assumes eye closure, but it does not actually monitor or respond to it.

Future work could address this by incorporating *eye-closure detection* directly into the VR system. Many modern head-mounted displays already integrate eye-tracking or infrared-based sensors that can estimate eyelid closure. These signals could be used to:

- detect when the user keeps their eyes open during phases intended for closed-eye meditation,
- automatically dim or switch off bright stimuli when the eyes are (re-)opened,
- trigger adaptive guidance, for example a short reminder such as: "If it feels comfortable, you may gently close your eyes again."

Combining eye-closure detection with adaptive visual design would improve both comfort and immersion. For instance, the system could gradually reduce brightness over time, or switch from high-intensity focus cues to softer, peripheral visualisation once eye closure is detected reliably. Future studies could systematically compare variants of the breathing light (colour, intensity, frequency, and position in the field of view) and evaluate their impact on comfort, adherence to instructions, and depth of meditation.

6.3. Extended Protocols and Personalisation

Another limitation of the present work is the relatively short, single-session protocol. Future studies should investigate longer-term interventions with multiple sessions over days or weeks, enabling the analysis of learning effects, habit formation, and more stable physiological changes. In such longer protocols, the AI guide could gradually adapt its language and difficulty level based on past performance, preferences, or self-reported goals (e.g. stress reduction, emotional regulation, or sleep improvement).

Additionally, combining the proposed real-time biofeedback and eye-closure monitoring with individual preference profiles (such as preferred voice tone, music, or visual style) could lead to highly personalised meditation journeys. Exploring how much personalisation is helpful, and where it might become overwhelming or counterproductive, is an important question for future work.

Summary

In summary, future work should move towards more adaptive, sensor-driven, and user-aware VR meditation systems. Modern wearable and integrated sensors can provide rich, real-time input to GPT-based guidance, enabling closed-loop adaptations to physiological state. At the same time, eye-closure detection and comfort-aware visual design can address practical issues observed in this study, such as discomfort from bright stimuli and inconsistent adherence to instructions. Together, these developments offer a concrete roadmap for improving both the effectiveness and

the usability of AI-guided VR meditation environments.

A. Appendix

This appendix provides additional descriptive plots for all physiological signals, including per-participant distributions and group-mean time courses.

A.1. Heart Rate (HR)



Figure A.1.: Per-participant mean HR during meditation (all three groups).



Figure A.2.: Per-participant mean HR during meditation (Conventional vs. VR).



Figure A.3.: Group-mean HR over time (0–240 s) for all three groups.



Figure A.4.: Group-mean HR over time (0–240 s) for Conventional vs. VR.

A.2. Skin Conductance Level (SCL)



Figure A.5.: Per-participant mean SCL during meditation (all three groups).



Figure A.6.: Per-participant mean SCL during meditation (Conventional vs. VR).



Figure A.7.: Group-mean SCL over time for Conventional vs. VR.

A.3. Skin Temperature



Figure A.8.: Per-participant mean skin temperature during meditation (all three groups).



Figure A.9.: Per-participant mean skin temperature (Conventional vs. VR).



Figure A.10.: Group-mean skin temperature over time for all three groups.

A.4. Pulse Volume Amplitude (PVA)



Figure A.11.: Per-participant mean PVA during meditation (all three groups).



Figure A.12.: Per-participant mean PVA (Conventional vs. VR).



Figure A.13.: Group-mean PVA over time for all three groups.



Figure A.14.: Group-mean PVA over time (Conventional vs. VR).

A.5. Body Motion



Figure A.15.: Per-participant mean motion amplitude during meditation (all three groups).



Figure A.16.: Group-mean motion amplitude over time for all three groups.



Figure A.17.: Group-mean motion amplitude over time (Conventional vs. VR).

A.6. Additional HRV Visualisations



Figure A.18.: Per-participant SDNN across groups.



Figure A.19.: SDNN comparison between Conventional and VR.



Figure A.20.: RMSSD comparison between Conventional and VR.



Figure A.21.: RMSSD comparison between 3 groups.



Figure A.22.: LF/HF ratio comparison between Conventional and VR.

A.6.1. Background music

The background meditation music used in both experimental conditions was sourced from Pixabay (*"Relaxing Meditation (Tibetan Path)"*) [Pix22], which is distributed under the Pixabay Content License and permits free use for academic and research purposes.



Figure A.23.: Baseline perceived stress ratings for VR and conventional meditation. Boxplots show median, interquartile range, and whiskers (1.5 × IQR); the dashed line indicates the group mean.



Figure A.24.: Negative affect ratings before the meditation session for VR and conventional meditation.



Figure A.25.: State mindfulness ratings during meditation for VR and conventional conditions.



Figure A.26.: State mindfulness ratings for VR participants with low vs. high physiological stress.



Figure A.27.: Sense of presence for VR participants in the low- and high-stress subgroups.



Figure A.28.: Overall satisfaction with VR meditation in low- and high-stress subgroups.



Figure A.29.: Correlation matrix for the main questionnaire scales (baseline perceived stress, negative affect before meditation, state mindfulness, and overall satisfaction).

Bibliography

[AKD+14] Andrew P. Allen, Laura S. Kennedy, John P. Dockray, Neil Cryan, Timothy G. Dinan, and Gerard Clarke. The Trier Social Stress Test: Principles and practice. *Neurobiology of Stress*, 1:19–34, 2014.

[App20] Applied Psychophysiology and Biofeedback Journal Editors. Methodological consistency in hrv biofeedback research: A systematic review. *Applied Psychophysiology and Biofeedback*, 45(3):175–190, 2020.

[ASD+18] H. Aliyari, H. Sahraei, M. R. Daliri, B. Minaei-Bidgoli, M. Kazemi, H. Agaei, M. Sahraei, S. M. A. S. Hosseini, M. M. Hadipour, M. Mohammadi, and Z. Dehghanimohammadabadi. The beneficial or harmful effects of computer game stress on cognitive functions of players. *Basic and Clinical Neuroscience*, 9(3):177–186, 2018.

[AWS19] Anika Arntz, Daniel Winter, and Thomas Schubert. Perception of ai collaboration in virtual reality environments. *Computers in Human Behavior*, 95:79–90, 2019.

[Bai20] Jeremy Bailenson. *Experience on Demand: What Virtual Reality Is, How It Works, and What It Can Do*. WW Norton & Company, 2020.

[Bak19] Martin Baker. Virtual reality therapy: A new frontier in mental health treatment. *Frontiers in Psychology*, 10:173, 2019.

[BD20] Rakesh Bhatt and Sidney D'Mello. Ai–vr-based systems for autism therapy: Personalized training through immersive interaction. *International Journal of Human-Computer Studies*, 138:102410, 2020.

[BJN20] Alexis Bouny, Camille Jeunet, and Bernard N'Kaoua. Guided breathing through haptic feedback to enhance cardiac coherence. In *2020 IEEE Conference on Virtual Reality and 3D User Interfaces (VR)*, pages 837–846, 2020.

[Bou12] Wolfram Boucsein. *Electrodermal Activity*. Springer, 2012.

[BR03] Kirk Warren Brown and Richard M. Ryan. The benefits of being present: Mindfulness and its role in psychological well-being. *Journal of Personality and Social Psychology*, 84(4):822–848, 2003.

[BRB+19] J. Blum, C. Rockstroh, N. Bittner, et al. Virtual reality breathing training for anxiety reduction: A pilot study. *Frontiers in Psychology*, 10:161, 2019.

[Bry96] Steve Bryson. Virtual reality and the design of virtual environments. In *Proceedings of the 1996 Symposium on Virtual Reality Software and*

Technology, pages 1–9. ACM, 1996.

[CBN21] A. Cebolla, R. Baños, and J. Navarrete. Compassionate embodied virtual experience increases the adherence to meditation practice. *OSF Preprints*, 2021.

[CKM83] Sheldon Cohen, Tom Kamarck, and Robin Mermelstein. A global measure of perceived stress. *Journal of Health and Social Behavior*, 24(4):385–396, 1983.

[CKS+20] Laura J. Chavez, Kelly J. Kelleher, Natasha Slesnick, Eugene Holowacz, Ellison Luthy, Laura Moore, and Jodi L. Ford. Virtual reality meditation among youth experiencing homelessness: Pilot randomized controlled trial of feasibility. *JMIR mental health*, 2020.

[Coh88] Jacob Cohen. *Statistical Power Analysis for the Behavioral Sciences*. Erlbaum, 2 edition, 1988.

[CS18] Luca Chittaro and Riccardo Sioni. Examining placebo effects in virtual reality biofeedback applications. In *Proceedings of the 2018 IEEE International Symposium on Computer-Based Medical Systems (CBMS)*, pages 328–333, 2018.

[Dei66] Arthur J. Deikman. De-automatization and the mystic experience. *Psychiatry*, 29(4):324–338, 1966.

[EYKC25] Eunkyoung Elaine, Yongluan Ye, Regina Kaplan-Rakowski, and Prerna Choubey. Personalized adaptive language learning in ai–powered high-immersion virtual reality. In *Advances in Computational Intelligence and Robotics*. IGI Global, 2025. Book chapter.

[Fai09] Stephen H. Fairclough. Fundamentals of physiological computing. *Interacting with Computers*, 21(1-2):133–145, 2009.

[FELB07] Franz Faul, Edgar Erdfelder, Albert-Georg Lang, and Axel Buchner. G*power 3: A flexible statistical power analysis program for the social, behavioral, and biomedical sciences. *Behavior Research Methods*, 39(2):175–191, 2007.

[Fie13] Andy Field. *Discovering Statistics Using IBM SPSS Statistics*. Sage, 4 edition, 2013.

[FRR+17] Daniel Freeman, Sarah Reeve, Ann-Marie Robinson, et al. Virtual reality in the assessment, understanding, and treatment of mental health disorders. *Psychological Medicine*, 47(14):2393–2400, 2017.

[G+14] Madhav Goyal et al. Meditation programs for psychological stress and well-being: a systematic review and meta-analysis. *JAMA Internal Medicine*, 174(3):357–368, 2014.

[GKG+24] Ankita Garg, Ajoy Kumar, Shubham Garg, Laxmidhar Behera, and Varun Dutt. Vr-based mantra meditation for mental wellness. In *IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, 2024.

[GZB+25] Shraboni Ghosal, Mengying Zhang, Angeliki Bogosian, Elizabeth

Marsh, Trudi Edginton, Emma Stanmore, and Siobhan O'Connor. Virtual reality based mindfulness applications: A commercial health app review. *medRxiv*, pages 1–30, 2025. Preprint.

[HCGR18] S. Houzangbe, O. Christmann, G. Gorisse, and S. Richir. Fear as a biofeedback game mechanic in virtual reality. *Proceedings of the ACM Symposium on Virtual Reality Software and Technology (VRST)*, pages 1–6, 2018.

[HP05] Jennifer A. Healey and Rosalind W. Picard. Detecting stress during real-world driving tasks using physiological sensors. *IEEE Transactions on Intelligent Transportation Systems*, 6(2):156–166, 2005.

[HS88] Sandra G. Hart and Lowell E. Staveland. Development of nasa-tlx (task load index): Results of empirical and theoretical research. In *Advances in Psychology, Vol. 52: Human Mental Workload*, pages 139–183. North-Holland, 1988.

[HTC24] HTC Corporation. Htc vive pro: Professional-grade virtual reality system. `https://www.vive.com/en/product/vive-pro/`, 2024. Accessed: 2025-02-15.

[Jer16] Jason Jerald. *The VR Book: Human-Centered Design for Virtual Reality*. Morgan & Claypool, 2016.

[Jud24] Amores Fernandez Judith. Aimagery: A multisensory approach to anxiety reduction with ai, olfactory stimuli, and biofeedback-enhanced guided imagery. *Affective Computing and Intelligent Interaction*, 2024.

[KCDM19] Panagiotis Kourtesis, Stefania Collina, Leonidas A.A. Doumas, and Sarah E. MacPherson. Validation of the virtual reality neuroscience questionnaire (vrnq) and the cybersickness questionnaire (csq-vr). *Frontiers in Human Neuroscience*, 13:417, 2019.

[Ker14] Dave S. Kerby. The simple difference formula: An approach to teaching nonparametric correlation. *Comprehensive Psychology*, 3:11.IT.3.1, 2014.

[KHK24] K. Kim, M. Hur, and W. Kim. Effects of virtual reality-based meditation on sleep quality, stress, and autonomic nervous system balance in nursing students. *Healthcare*, 12(16):1581, 2024.

[KPH93] Clemens Kirschbaum, Karl-Martin Pirke, and Dirk H. Hellhammer. The Trier Social Stress Test—a tool for investigating psychobiological stress responses in a laboratory setting. *Neuropsychobiology*, 28(1-2):76–81, 1993.

[KSJ+16] Ilkka Kosunen, Mikko Salminen, Simo Järvelä, Anna Ruonala, Niklas Ravaja, and Giulio Jacucci. Neuroadaptive meditation in virtual reality. *Frontiers in Psychology*, 7:1321, 2016.

[KSKS24] K. Kortelev, Y. Serdyukov, V. Kortelev, and M. Serdyukov. Integration of virtual reality and artificial intelligence technologies in education. *The Humanities and Social Studies in the Far East*, 21(1):240–246, 2024.

[LG13a] Paul Lehrer and Richard Gevirtz. Heart rate variability biofeedback: How and why does it work? *Frontiers in Psychology*, 4:1–9, 2013.

[LG13b] Paul Lehrer and Richard Gevirtz. Heart rate variability biofeedback: How and why does it work? *Frontiers in Psychology*, 4:1–9, 2013.

[LGM18] Stefan Liszio, Laura Graf, and Maic Masuch. Exploring the potential of immersive virtual reality to foster relaxation and well-being. *Computers in Human Behavior*, 78:195–204, 2018.

[Liu24] Shuai Liu. Virtual reality and 6g-based smart classroom teaching using artificial intelligence. *Wireless Personal Communications*, 2024.

[LSDD08] Antoine Lutz, Heleen A. Slagter, John D. Dunne, and Richard J. Davidson. Attention regulation and monitoring in meditation. *Trends in Cognitive Sciences*, 12(4):163–169, 2008.

[Man11] Ramesh Manocha. Why meditation works: A new hypothesis. *Medical Hypotheses*, 77(6):1038–1041, 2011.

[MDG19] Nicolas Martin, Celine Dupont, and Frank Guerin. Enhancing immersive experiences through multimodal interaction in virtual reality. In *2019 IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*, pages 583–592, 2019.

[MPL+21] Dominique Makowski, Trung Pham, Zoe J. Lau, Julien C. Brammer, Fabien Lespinasse, Huy Pham, Christopher Schölzel, and Serena H. A. Chen. Neurokit2: A python toolbox for neurophysiological signal processing. *Behavior Research Methods*, 53:1689–1696, 2021.

[MS01] Rollin McCraty and Fred Shaffer. Heart rate variability: New perspectives on physiological mechanisms, assessment of self-regulatory capacity, and health risk. *Global Advances in Health and Medicine*, 1(4):46–61, 2001.

[MW47] Henry B. Mann and Donald R. Whitney. On a test of whether one of two random variables is stochastically larger than the other. *Annals of Mathematical Statistics*, 18(1):50–60, 1947.

[MZXY22] Jingni Ma, Dongrong Zhao, Naihong Xu, and Jinmei Yang. The effectiveness of immersive virtual reality based mindfulness training on mental health in adults: A narrative systematic review. *Explore*, 2022.

[Ope25] OpenAI. Openai gpt language model api. `https://platform.openai.com`, 2025. Accessed: 2025-02-15.

[otESoCtNASoPE96] Task Force of the European Society of Cardiology, the North American Society of Pacing, and Electrophysiology. Heart rate variability: Standards of measurement, physiological interpretation and clinical use. *Circulation*, 93(5):1043–1065, 1996.

[PBBW24] E. Payne, K. Battel, N. Baker, and N. Ward. Considerations when trying to quantify immersion with secondary tasks. *Frontiers in Virtual Reality*, 5, 2024.

[PG19] Alyson M. Porter and Beate Goolkasian. Video games and stress: How stress appraisals and game content affect cardiovascular and affective responses. *Frontiers in Psychology*, 10:967, 2019.

[Pix22] Pixabay. Relaxing meditation – tibetan path, 2022. Royalty-free meditation background music.

[R+21] Imke Rehm et al. Virtual reality for mental health: current status and future directions. *Frontiers in Psychology*, 2021.

[Rea21] J. Rodrigues and et al. Imvest, an immersive multimodal virtual environment stress test. *Neurobiology of Stress*, 15:100370, 2021.

[RLGCZR+25] A. Rubio-López, R. García-Carmona, L. Zarandieta-Román, A. Rubio, Á. González-Pinto, and P. Cardinal-Fernández. Measuring stress and perceptions for a virtual reality–based pericardiocentesis procedure simulation for medical training: Usability study. *JMIR Serious Games*, 13:e68515, 2025.

[SAS+10] Cornelia Setz, Bert Arnrich, Julius Schumm, Roberto La Marca, Gerhard Tröster, and Ulrike Ehlert. Discriminating stress from cognitive load using a wearable eda device. *IEEE Transactions on Information Technology in Biomedicine*, 14(2):410–417, 2010.

[Sch24] Schuhfried GmbH. Biofeedback 2000 xpert. `https://ssrc.ac.ir/lab/en/page/232/biofeedback2000x-pert`, 2024. Accessed: 2025-02-15.

[SEB22] T. Sarkar, R. Edwards, and N. Baker. The feasibility and effectiveness of virtual reality meditation on reducing chronic pain for older adults with knee osteoarthritis. *Pain Practice*, 22(7):631–641, 2022.

[SES+12] Peter Sedlmeier, Juliane Eberth, Markus Schwarz, Doreen Zimmermann, Frederik Haarig, Sven Jaeger, and Sonja Kunze. The psychological effects of meditation: A meta-analysis. *Psychological Bulletin*, 138(6):1139–1171, 2012.

[SFR01] Thomas Schubert, Frank Friedmann, and Holger Regenbrecht. The experience of presence: Factor analytic insights. In *Proceedings of the 4th International Workshop on Presence*, pages 135–148, 2001.

[SGS11] Chris Shaw, Diane Gromala, and Min Song. The meditation chamber. In *Designing Interactive Systems for Mindfulness*, pages 121–133. IGI Global, 2011.

[SHT17] Martin Schrepp, Andreas Hinderks, and Jörg Thomaschewski. Construction of a benchmark for the user experience questionnaire (ueq). In *Proceedings of the 5th International Conference on Methods and Techniques in Behavioral Research*, 2017.

[Sla18] Mel Slater. Immersion and the illusion of presence in virtual reality. *British Journal of Psychology*, 109(3):431–433, 2018.

[SRR21] Ralph Schlagowski, Andreas Riener, and Gerhard Rigoll. Designing

empathy: Ai-simulated bias in virtual reality. *Frontiers in Robotics and AI*, 8:612, 2021.

[SSM20] Weidner Standard, Jan David Smeddinck, and Rainer Malaka. Open TSST-VR: Trier Social Stress Test in virtual reality. In *Proceedings of GI VR/AR Workshop*, 2020.

[SW65] Samuel S. Shapiro and Martin B. Wilk. An analysis of variance test for normality (complete samples). *Biometrika*, 52:591–611, 1965.

[TB13] Galia Tanay and Amit Bernstein. State mindfulness scale (sms): Development and initial validation. *Psychological Assessment*, 25(4):1286–1299, 2013.

[TVC18] John Tarrant, Joshua Viczko, and Hannah Cope. Virtual reality meditation: A tool for reducing anxiety and improving mood. *Frontiers in Psychology*, 9:1260, 2018.

[WCT88] David Watson, Lee A. Clark, and Auke Tellegen. Development and validation of brief measures of positive and negative affect: The panas scales. *Journal of Personality and Social Psychology*, 54(6):1063–1070, 1988.

[WWM20] David Weibel, Bartholomäus Wissmath, and Fred W. Mast. Virtual reality biofeedback for relaxation: Effects on heart rate variability and user experience. *Frontiers in Virtual Reality*, 1:6, 2020.

[XGH25] Qiuxia Xu, Yingqi Gu, and Xizhe Hu. Brief interactive virtual reality mindfulness training with real-time biofeedback for anxiety reduction: A pilot study. *Applied Psychophysiology and Biofeedback*, 2025.

[Z+15] Fadel Zeidan et al. Mindfulness meditation-based pain relief employs different neural mechanisms than placebo and sham mindfulness meditation-induced analgesia. *Journal of Neuroscience*, 2015.

[ZD20] Lin Zhou and Xiao Deng. Ai-driven adaptive interfaces for virtual reality. *IEEE Transactions on Visualization and Computer Graphics*, 26(5):2011–2021, 2020.

[Zea19] Patrick Zimmer and et al. Virtually stressed? a refined virtual reality adaptation of the Trier Social Stress Test. *Psychoneuroendocrinology*, 101:153–157, 2019.

[ZYK+22] M. Zambotti, D. Yüksel, O. Kiss, G. Barresi, N. Arra, and L. Volpe. A virtual reality-based mind–body approach to downregulate psychophysiological arousal in adolescent insomnia. *Digital Health*, 8:205520762211078, 2022.

List of Figures

3.1. HTC VIVE Pro head-mounted display[HTC24]. 15
3.2. Biofeedback 2000 Xpert system used for physiological recording [Sch24]. . . . 16
3.3. VR meditation audio pipeline driven by user-selected stress level. Biofeedback sensors were used for data logging and offline analysis only (no real-time feedback to GPT or VR). 22
3.4. Breathing-responsive skybox illumination. The VR environment alternates smoothly between a brighter (inhale) and darker (exhale) skybox colour, synchronised with AI-guided meditation cues. 23
3.5. Pipeline linking AI/TTS audio playback to skybox brightness modulation via `LightOnAudio`, producing a through-eyelid glow that supports paced breathing. 24
3.6. G*Power X–Y plot illustrating the required total sample size across different statistical power levels for an independent-samples t-test with medium effect size ($d = 0.5$), $\alpha = 0.05$, two-tailed. The targeted sample size of $N = 44$ corresponds to an achievable power of approximately 0.36. 27
3.7. G*Power a priori power analysis for an independent-samples t-test with medium effect size ($d = 0.5$), $\alpha = 0.05$, and two-tailed testing. With a total sample size of $N = 44$ (22 per group), the achieved power is approximately 0.36. 28
3.8. Experimental workflow showing baseline relaxation, stress induction, randomized meditation interventions, and post-assessment stages. 30

4.1. Group-level HRV metrics (mean $\pm$ SD) for the three meditation conditions. . . 37
4.2. Group-mean SCL over time for all three meditation groups. 38
4.3. Group-mean skin temperature over time for Conventional versus VR. 39
4.4. Per-participant mean motion amplitude for Conventional vs. VR. VR resulted in significantly lower motion during meditation ($p = 0.005$). 40
4.5. Perceived presence in VR 42
4.6. Overall satisfaction with VR vs. conventional meditation 43

A.1. Per-participant mean HR during meditation (all three groups). 51
A.2. Per-participant mean HR during meditation (Conventional vs. VR). 52
A.3. Group-mean HR over time (0–240 s) for all three groups. 52
A.4. Group-mean HR over time (0–240 s) for Conventional vs. VR. 53
A.5. Per-participant mean SCL during meditation (all three groups). 53
A.6. Per-participant mean SCL during meditation (Conventional vs. VR). 54
A.7. Group-mean SCL over time for Conventional vs. VR. 54
A.8. Per-participant mean skin temperature during meditation (all three groups). . . 55
A.9. Per-participant mean skin temperature (Conventional vs. VR). 56
A.10. Group-mean skin temperature over time for all three groups. 56
A.11. Per-participant mean PVA during meditation (all three groups). 57
A.12. Per-participant mean PVA (Conventional vs. VR). 58

A.13. Group-mean PVA over time for all three groups. 58
A.14. Group-mean PVA over time (Conventional vs. VR). 59
A.15. Per-participant mean motion amplitude during meditation (all three groups). . . 59
A.16. Group-mean motion amplitude over time for all three groups. 60
A.17. Group-mean motion amplitude over time (Conventional vs. VR). 60
A.18. Per-participant SDNN across groups. 61
A.19. SDNN comparison between Conventional and VR. 62
A.20. RMSSD comparison between Conventional and VR. 63
A.21. RMSSD comparison between 3 groups. 64
A.22. LF/HF ratio comparison between Conventional and VR. 65
A.23. Baseline perceived stress by mode of delivery 66
A.24. Negative affect before meditation by mode of delivery 66
A.25. State mindfulness by mode of delivery 67
A.26. State mindfulness in VR low- vs. high-stress subgroups 67
A.27. Presence in VR low- vs. high-stress subgroups 68
A.28. Overall satisfaction in VR low- vs. high-stress subgroups 68
A.29. Correlation matrix of questionnaire scales 69

List of Tables

3.1. Comparison between VR-based meditation and 2D (TV/Laptop) meditation. . . 14
3.2. Workstation configuration used for VR rendering and data analysis. 18
3.3. Distribution of prior meditation experience by meditation method. 25

4.1. Group means (SD) for HRV metrics during the meditation phase. 36
4.2. Within-group comparisons between stress and meditation. Arrows denote direction of change (↑ increase; ↓ decrease). "ns" indicates non-significance ($p > 0.05$). 37
4.3. Between-group comparison of change scores (Δ). Only motion amplitude showed a statistically significant difference. 39
4.4. Descriptive statistics (mean $\pm$ SD) for questionnaire scales (1-5 Likert scale; midpoint = 3). 41

Declaration

I, Muhammad Abid Zahid, hereby declare that the thesis entitled "AI-Guided Voice-Interactive VR Meditation: Enhancing Relaxation through Adaptive Audiovisual Cues and Biofeedback" and the work presented within it are entirely my own. I confirm that:

- This work was carried out wholly or mainly during my candidature for a research degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this or any other institution, this has been clearly stated.
- Where I have consulted the published work of others, this has been clearly attributed.
- Where I have quoted from the work of others, the source has always been given. Except for such quotations, this thesis is entirely my own work.
- I have acknowledged all major sources of assistance.
- Where the thesis includes work undertaken jointly with others, I have clearly indicated what was carried out by others and what I contributed myself.

Signed:

_____

Date:

_____