



Safety Compliance Plan

**Custom Electric, Inc.
52 Main Street
Manchester CT 06042**

Last Revision: August 2026

Custom Electric Company Safety Plan
August 2026

Section	Topic	Page
1.0	Employee Hazard Awareness and Notification Plan	3
2.0	Custom Electric Company Safety Policy Statement	4
3.0	General Safety Compliance Requirements for Employees	5
4.0	Job Hazard Analysis Procedure	6
5.0	Protective Equipment (PPE) Basics	6-7
6.0	Emergency Situations	8-12
7.0	Accident Reporting and Investigation Plan	13-16
8.0	Bloodborne Pathogens	17-18
9.0	Confined Space Entry	20-25
9.12	Confined Space Entry Permit	27-29
10.0	Contractor Safety Plan	31-39
11.0	Electrical Safety & Lockout Tagout Plan	39-41
12.0	Ergonomic Injury Prevention Plan	42-44
13.0	Fall Protection Plan	45-54
14.0	Fire Prevention and Emergency Action Plan	55-59
15.0	Forklift Operation Plan	59-69
16.0	Flammable and Combustible Liquids Plan	70-72
17.0	Hand and Portable Power Tools	73-75
18.0	Hazard Communication Plan	76-78
19.0	Personal Protective Equipment Plan	79-85
20.0	Scaffold Use and Aerial Work Platforms	86-91
21.0	Trenching and Excavations	92-95
22.0	Vehicle/Fleet/Driver Safety	96-99
23.0A	Respirable Crystalline Silica Program	100-115
23.0B	Asbestos Safety Procedure	116-121
24.0	First Report of Accident	122
25.0	Accident Investigation Form	124-125
26.0	Job Hazard Analysis Form	126
27.0	Aerial-Scissor Lift Checklist	128
28.0	Daily Lull Checklist	130
29.0	Harness Inspection	132
30.0	Lanyard Inspection	134
31.0	Ladder Safety Inspection	136
32.0	SRL Inspection	138
33.0	Scaffold Inspection	140-145
34.0	Equipment Damage/Loss/Theft Report Form	146-147
35.0	Voluntary Respirator Use Form	148
36.0	GFI Test Log	149

1.1 Employee Hazard Awareness and Notification Plan

Purpose

Custom Electric is committed to eliminating worker injury at every project site and every workplace. All employees are obligated as follows:

- To conduct their work in a safe manner.
- To stop work immediately to correct any unsafe condition that is encountered.
- To take corrective action so that work may proceed in a safe manner.

It is the Company's expectation that no one will suffer an injury in the execution of our work.

Custom Electric will make every attempt to insure the continued safety and health of its employees. In return, employees are required to use good judgment and comply with company safety policies. Each person must accept responsibility for their own safety by working safely and insisting that their co-workers do the same.

1.2 Duties

Employee Specific duties include:

- Arrive at work alert and ready to focus on safely performing their job. The safety of each worker and those around the worker requires full attention.
- Following safety instructions given by your Forman or Supervisor.
- Be on guard for unsafe conditions or activities and take action to correct them. If the problem cannot be fixed, report it your direct your Forman or Supervisor.
- Use good judgment to provide for personal safety and for the safety of co-workers.
- Use the required safety equipment.
- Comply with all Custom Electric policies and with state and federal OSHA regulations and good safety practices.
- Wear proper clothing for the job.
- Attend Custom Electric-required safety training.

Report all injuries / near misses to your Foreman Supervisor immediately after occurrence. (See **Accident Reporting and Investigation Plan**)

2.0 Custom Electric Company Safety Policy Statement

It is the policy of Custom Electric Company, Inc. that accident prevention shall be considered of primary importance in all phases of operation and administration. It is the intention of Custom Electric Company, Inc.'s management to provide safe and healthy working conditions and to establish and insist upon safe practices at all times by all employees. To help enforce this, Custom Electric has appointed Adam Drummond of National Safety Services to be the company Safety Director. He will insure that the following policy is met or exceeded.

The prevention of accidents is an objective affecting all levels of our company and its operations. It is, therefore, a basic requirement that each supervisor make the safety of all employees an integral part of his or her regular management function. It is equally the duty of each employee to accept and follow established safety regulations and procedures.

In addition to the Safety Director, a secondary Safety Officer will be designated to every job site. Along with the Safety Director, it will be the Safety Officer's responsibility to conduct jobsite inspection during the first week of work, and every month ensuing. Inspections will be documented on a checklist form. In addition, the Safety Officer will provide knowledgeable insight and suggestions on how to make the workplace a safer and more efficient environment.

Every effort will be made to provide adequate training to employees. However, if an employee is ever in doubt about how to do a job or task safely, it is his or her duty to ask a qualified person for assistance. Employees are expected to assist management in accident prevention activities. Unsafe conditions must be reported immediately. Fellow employees that need help should be assisted. Everyone is responsible for the housekeeping duties that pertain to their jobs.

Every injury that occurs on the job, even a slight cut or strain, must be reported to management and/or the Safety Director as soon as possible.

Site employees will be responsible for reviewing and signing weekly Toolbox Talks forms during a weekly safety meeting. Employees are expected to assist management in accident prevention activities. Unsafe conditions must be reported immediately. Fellow employees that need help should be assisted. Everyone is responsible for the housekeeping duties that pertain to their jobs. Every injury that occurs on the job, even a slight cut or strain, must be reported to management and/or the Safety Director as soon as possible.

Under no circumstances, except emergency trips to the hospital, should an employee leave the work site without reporting an injury. When you have an accident, everyone is hurt.

Above all, please work safely. Safety is everyone's responsibility.

3.1 General Safety Compliance Requirements for Employees

3.2 Purpose

This written General Safety Compliance Requirements for Employees Plan is intended to ensure that all employees perform work tasks in a safe manner. Furthermore, it is our intent to comply with the requirements of OSHA 29CFR1926 Standards for Construction.

3.3 Administrative Duties

The Safety Director is responsible for developing and maintaining the written General Safety Compliance Requirements for Employees. The Safety Director is solely responsible for all facets of the plan and has full authority to make necessary decisions to ensure the success of this plan. The Safety Director is also qualified by appropriate training and experience that is commensurate with the complexity of the plan to administer or oversee our General Safety Compliance Requirements for Employees and conduct the required evaluations of plan effectiveness.

3.4 Affected Operations

All or part of this plan affects all operations within this company. Custom Electric is Electrical contractor that provides multiple associated services. This plan is designed and written to cover the broad scope of safety sensitive areas for all of these operations facilities and job sites. As such, this plan establishes safety policy and procedures that encompass the entire breadth of the activity performed by the various service functions. Many of the policies and procedures in this plan pertain to all personnel. However, every facet of this plan will affect not every service operation. The nature of the service provided by some operations does not include duties or place personnel in work areas in which certain job specific safety concerns exist. All personnel will be familiarized with the plan in its entirety. Specific training and procedures will be provided as needed and required base on specific work tasks, job requirements, site location, and work environment. This plan is a working plan that will be modified, updated and enhanced as required to provide safe working conditions for all personnel and to maintain compliance to OSHA 29CFR1926 Standards for Construction Industry. The Safety Director will serve to continually evaluate, determine needed changes and ensure all personnel are informed and trained in all areas inherent to their work tasks ad the general safety of others in their surrounding areas.

3.5 Hazard Evaluation

The Safety Director and their designate initially performed our company's hazard assessment in 2013. Our initial hazard assessment revealed our need to develop the following formal safety plans:

1. General Safety Compliance Requirements for current employees and new hires (i.e. compliance, training and accident reporting procedures and requirements)
2. Accident Investigations
3. Contractor Safety
4. Electrical Safety and Lockout Tagout

5. Emergency Action and Fire Prevention Plan
6. Forklift Operations (Powered Industrial Truck)
7. Fall Protection, Ladder Safety and Use
8. Fire Safety and Flammable Liquid Storage
9. Hazard Communications
10. Hand and Portable Power Tools
11. Personal Protection Equipment (PPE)
12. Scaffolding and Aerial Work Platform Operation
13. Trenching and Excavations
14. Vehicle Operations

We understand that after our initial hazard assessment, additional assessments may be necessary.

4.0 Custom Electric Job-Hazard Analysis Procedure

Custom Electric's company policy is to provide a "Job Hazard Analysis" (JHA) to the client (GC, CM, Owner and/or Owner's Representative) which identifies and outlines any hazardous condition that is created by a specific job task. Custom Electric shall submit this document to the client which clearly outlines the hazard, and also lists the steps of the task, hazards for each task, and the actions to be taken to ensure the safety for each task. JHA's shall be submitted for but not limited to: Installation, maintenance, or service of electrical systems, working at hazardous heights, specific tool use, confined space, rigging operations, excavations and any other task which creates a risk to personnel or jobsite conditions. JHA's shall be reviewed by the Safety Director prior to the submission to clients and/or owners. A copy of Custom Electric JHA is included in the Appendix.

5.1 Protective Equipment Basics

All protective equipment, including personal protective equipment (PPE), as required under OSHA's PPE standard, will be provided without cost to employees. Protective equipment will be chosen based on anticipated hazards.

Here is the protective equipment we generally require (not all inclusive):

- Safety glasses
- Gloves (work, chemical and voltage rated)
- Safety Shoes
- Full Body Harnesses
- Impact and Chemical Splash Goggles
- Face Shields
- Hard Hats
- Ear Protection

Foreman and/or Superintendents shall ensure that appropriate protective equipment in the appropriate sizes is readily accessible at the workplace or is issued without cost to employees.

In order to assure the continued reliability of protective equipment, it must be inspected

on a regular basis. The frequency of inspection is related to the frequency of use.

See section 19.0 for a more detailed PPE plan.

Employees are required to maintain all personally assigned PPE in clean working order. Protective equipment that fails an inspection or is otherwise found to be defective is removed from service, and is discarded, repaired or adjusted in accordance with the manufacturers instructions and/or the instructions received as part of the PPE training program. Custom Electric will replace this PPE at no cost to employees.

6.1 Emergency Situations

Our emergency/accident response procedures are found in the **Fire Prevention and Emergency Action Plan**

6.2 Inspections

The Safety Director is qualified to perform inspections for this General Safety Compliance Requirements for Employees on a regular basis. Inspections are conducted at minimum annually or sooner as required.

6.3 Training

Under no circumstances may an employee begin work at Custom Electric until he/she has successfully completed this company's training program under the General Safety Compliance Requirements for Employees. This includes all new employees, regardless of claimed previous experience.

The Safety Director will identify trainees in each set of new employees and make arrangements with department management to schedule training. The Safety Director will also identify those existing employees who need retraining. Training is done in-house. The company-training program includes:

- Aerial Work Platform Operations
- Hazard Communications
- Personal Protective Equipment
- Fire Prevention
- Ergonomics and Safe Lifting Techniques
- Powered Industrial Truck Operation
- Electrical Safety including Lock Out Tag Out and the NFPA70E Provisions
- Fall Protection
- Ladder Safety
- Flammable Material Storage and Handling
- Scaffolding and Aerial Work Platform Operation

Training Certification

After an employee has completed the training program, the instructor will determine whether the employee can safely perform the job.

The Safety Director is responsible for keeping records certifying each employee who has successfully completed training. Each certificate includes the name of the employee, the date(s) of the training, and the signature of the person who did the training and evaluation.

Each trained employee is evaluated to verify that the employee has retained and uses the knowledge and skills needed to operate safely. This evaluation is done by at the conclusion of the training program. If the evaluation shows that the employee is lacking the appropriate skills and knowledge, the employee is retrained by our instructor(s). When an employee has an accident or near miss or some unsafe operating procedure is identified, we do retraining.

6.4 Plan Evaluation

It is inherent that problems may occasionally arise in this General Safety Compliance Requirements for Employees. Although we may not be able to eliminate all problems, we try to eliminate as many problems as possible to improve employee protection and encourage employee safe practices. By having our plan administrator, The Safety Director, thoroughly evaluate and, as necessary, revise our General Safety Compliance Requirements for Employees, we can eliminate problems effectively.

6.5 General Safety/Housekeeping

- Do not take unnecessary risks or chances. Make safety an integral part of every job. Keep your eyes on your work and in your direction of travel.
- Always work on a stable surface so both feet are firmly planted. Do not begin a job until the necessary safety equipment is on site and ready for use.
- If you come in contact with a toxic or corrosive material or petroleum product check the Material Safety Data Sheet (SDS) to see if any other action may be necessary. Report the incident to the Job Supervisor/Foreman.
- Practice the following fundamentals for safe lifting:
 1. Keep lower back in normal curvature
 2. Bend your legs so you use the strongest muscles in your body to lift
 3. Keep your feet no further apart than the width of your shoulders
 4. Keep a firm and level footing to avoid slipping or twisting with the load
 5. Avoid sudden or jerky motions, never twist with a load
 6. Do not overextend yourself. Move, don't reach.
 7. If one person cannot safely lift the object, get assistance.
- If an object (such as a drum, pallet, bucket, tool, ladder, pipe, etc) starts to fall, don't try to catch it. Let it free fall.
- Proper work clothing must be worn at all times. Proper clothing is based on job location, job-specific tasks, and climate.
- Appropriate footwear is required. Soles should be notched or grooved to prevent slipping on oily or wet surfaces.
- Safety glasses are required in all designated work areas and job assignment areas. Hearing protection (disposable molded ear plugs or ear muffs) should be worn when working in noisy areas.

- Hard hats protect the head from impact and penetration by falling or flying objects, overhead spills, and electric shock. Hard hats also reduce the risk of hair becoming entangled in machinery. They must meet ANSI Requirements for Industrial Head Protection.
- Gloves shall be worn when hands are exposed to hazardous substances or to sharp, rough or hot objects. Voltage rated gloves are required when justified live energy work is performed.
- Wear and maintain the required personal protective equipment when the job operating procedure or SDS calls for it or when advised. Respiratory protection equipment shall be individually assigned. Personal protective equipment must be kept in clean usable condition. Employees are responsible for cleaning and storing any equipment that has been assigned to them. Replacement parts are available from the Facilities Manager.
- Never used compressed air to clean or dust off work clothing.

6.6 General Housekeeping

Housekeeping is perhaps the most important single item influencing the safety of a construction job. Good housekeeping should be planned at the beginning of the job and carried through to a final cleanup. It should be of prime interest to the Senior Construction Site Representative. Good housekeeping is not a burden if constantly maintained and not left to an occasional cleanup. Moreover, it always pays for itself in increased efficiency, employee morale and safety.

The following housekeeping requirements shall be followed at all times:

- All stairways, passageways and gangways shall be kept free from materials, supplies and obstructions of every kind.
- Materials and supplies shall be kept away from edges of hoist ways, stairways, floor openings, and when exterior walls are not built away from the perimeter of the building.
 - When protruding nails are found in reusable boards, planks and timbers, they shall be removed away from the perimeter of the building. Protruding nails in scrap lumber should be bent flush or hammered in.
 - Tools shall not be strewn about where they may cause tripping or other hazards and shall at the end of each work day be collected and stored in a tool shed or tool box.
- Debris and waste material shall not be permitted to accumulate in the work area.
- On larger jobs, and organized clean up crew should be formed whose primary duty is general clean up work. During some activities, such as concrete form stripping, dismantling old buildings or equipment or unpacking material, this crew should be supplemented with sufficient help to remove debris promptly.
- Non-flammable receptacles should be provided for waste paper and rubbish.

7.1 Accident Reporting and Investigation Plan

7.2 Purpose

This Accident Reporting and Investigation Plan prescribe methods and practices for reporting and investigating accidents. No matter how conscientious the safety effort at a company, accidents happen occasionally due to human or system error. Therefore, this written plan is intended to provide a means to deal with all workplace accidents in a standardized way and demonstrate our company's compliance with the reporting requirements of 29 CFR 1904. In addition, it is the policy of the company to comply with all workers' compensation laws and regulations.

7.3 Administrative Duties

Our Safety Director is responsible for developing and maintaining this written Accident Reporting and Investigation Plan. This person is solely responsible for all facets of the plan and has full authority to make necessary decisions to ensure the success of this plan. Our safety manager is also qualified, by appropriate training and experience that is commensurate with the complexity of the plan, to administer or oversee our Accident Reporting and Investigation Plan and conduct investigations.

7.4 Accident Reporting Procedures

Our accident reporting procedures include the following:

1. Employees injured on the job are to report the injury to their immediate supervisor/foreman as soon as possible after an incident/accident. "Near miss" accidents or incident should be reported as well, i.e., when an employee nearly has an accident but is able to avoid an injury or illness.
2. The supervisor/foreman is to immediately notify the safety director; complete the company Accident Report Form (see the Appendices for a sample form) with the employee, any witnesses, and/or other relevant people; and send a copy of the written Accident Report Form to the safety manager as soon as possible after the accident.
3. Any employee witnessing an accident at work is to call for emergency help or whatever assistance appears to be necessary. In addition, the employee is immediately to report the accident to their immediate supervisor and take part in answering questions related to the Accident Report Form and Accident Investigation Form.

A sample Accident Report Form is provided in the appendix.

7.5 Accident Investigation Procedures

Thorough accident investigations will help our company determine why accidents occur, where they happen, and any trends that might be developing. Such identification is critical to preventing and controlling hazards and potential accidents. For all accident investigations, the safety director will perform the following duties:

1. Conduct an accident investigation at the scene of the injury as soon after the injury as safely possible.
2. Ask the employee involved in the accident and any witnesses, in separate interviews, to tell him/her in their own words exactly what happened.
3. Repeat the employee's version of the event back to the employee or witness and allow him/her to make any corrections or additions.
4. After the employee or witness has given his/her description of the event, asks appropriate questions that focus on causes.
5. Remind the employee that the investigation was to determine the cause and possible corrective action that can eliminate the cause(s) of the accident.
6. Complete section "A" of the attached Accident Investigation Form with the employee, and review the data with the employee for accuracy.
7. Our company will use the Accident Investigation Form for:
 - Tracking and reporting injuries on a monthly basis;
 - Grouping injuries by type, cause, body part affected, time of day, and process involved;
 - Determining if any trends in injury occurrence exist and graphing those trends if possible;
 - Identifying any equipment, materials, or environmental factors that seem to be commonly involved in injury incidents;
 - Discussing with the company management and supervisors the possible solutions to the problems identified; and
 - Proceeding with improvements to reduce the likelihood of future injuries.

7.6 Recordkeeping

The Safety Director is responsible for maintaining the following records and documentation:

- Accident Report Forms.
- Accident Investigation Forms.
- OSHA 300 Form, Log of Work-Related Injuries and Illnesses. Injuries and illnesses at the company are recorded on this form within seven calendar days of receiving information that a recordable injury or illness has occurred.
- OSHA 301 Form, Injury and Illness Incident Report. Injuries and illnesses at the company are recorded on this form within seven calendar days of receiving information that a recordable injury or illness has occurred.

- OSHA 300-A Form, Summary of Work-Related Injuries and Illnesses. This form is completed by the end of the year, posted no later than July 1 of the year following the year covered by the form and kept posted in place until May 30.

7.7 Annual Summary Posting

At the end of each calendar year, the Safety Director performs the following annual summary posting duties:

1. Reviews the OSHA 300 Form to verify that the entries are complete and accurate,
2. Corrects any deficiencies identified in the entries,
3. Creates OSHA 300-A, an annual summary of injuries and illnesses recorded on the OSHA 300 Form,
4. Posts OSHA 300-A in the employee break room at the company headquarters from July 1 through May 30 of the year following the year covered by the form.

7.8 Reporting

OSHA requires direct notification of safety accidents/incidents under certain circumstances.

These include:

1. Any accident that results in the in-hospitalization of three (3) or more employees as a result of the same accident
2. Any accident that leads to the fatality of an employee

A telephone report to the nearest OSHA office is required under these conditions within 8 hours from the initial incident. All such reports are to be made following notification to the safety director. When contacting OSHA, ensure that you have noted the date, time, and name of the OSHA officer contacted.

7.9 Employee Involvement and Training

This plan is an internal document guiding the action and behaviors of employees, so they need to know about it. Monthly, Supervisors thoroughly explain to all employees why the Accident Reporting and Investigation Plan was prepared and how employees may be affected by it. Employees are informed in how to report an injury or illness.

Employees, and their representatives, are also provided limited access to our injury and illness records. Copies of relevant OSHA 300 form are provided by the next business day to all employees, former employees, and representatives that request them. Employees and former employees who request OSHA 301 form will also receive them by the end of the next business day. However, authorized employee representatives will only receive requested OSHA 301 form within seven calendar days, and all sections of the OSHA 301 form will be removed except the OSHA 301 Incident Report section titled

'Tell us about the case.' section. All initial copies are provided to requestors free of charge. Additional copies involve a reasonable charge.

Our company does not discriminate against employees for:

- Reporting a work-related fatality, injury, or illness;
- Filing a safety and health complaint;
- Asking for access to occupational injury and illness records; or
- Exercising any rights afforded by the Occupational Safety and Health Act.

Our company conducts weekly **Tool Box Talks** with all work crews. The crew supervisors who have successfully completed a Train the Trainer workshop conduct these training sessions. Supervisors are supplied with a variety of customized Tool Box Talk outlines from which to choose from. Upon completion of the Tool Box Talks, the supervisor will have all workers sign the attendance form. Questions or concerns not resolved during the course of the Tool Box Talks will be noted on the Tool Box Talk form, and brought to the direct attention of the safety manager.

7.10 Program Evaluation

The Accident Reporting and Investigation Plan is evaluated and updated by the Safety Director annually or sooner if circumstances require determining whether the plan is being followed and if further training may be necessary.

8.1 Bloodborne Pathogens

8.2 Scope

Custom Electric is dedicated to the protection of its employees from on-the-job injuries. All employees of Custom Electric have the responsibility to work safely on the job. The purpose of this plan is to ensure that our employees are aware of pathogenic microorganisms that are present in human blood and other body fluids that can cause disease such as HVB, hepatitis B virus or HIV, human immunodeficiency. Employees must be aware of how to handle possible exposure to these pathogens when encountered during the course of regular work activities.

8.3 Procedure

Should an accident or incident occur in which an employee sustains an injury, or happens upon a suspected bodily fluid spill during the normal course of their duties, universal precautions shall be observed to prevent contact with blood and other potentially infectious materials. (A universal precaution is an approach to infection control in which all body fluids shall be considered potentially infectious materials.) Disposable gloves shall be worn when making contact with blood, mucous membranes, other potentially infectious materials and non-intact skin.

Disposable gloves and protective eyewear are provided to our employees by Custom Electric and are stocked in the First Aid Kits, as well as in the PPE storage areas. This information is also found in the company PPE policy.

When feasible, such as when an employee cuts their finger and only requires a Band-Aid, that employee should be responsible for his or her cleaning up of any contaminated areas. Alternatively, a designated person who is trained to use the proper materials while decontaminating could do any clean up. If the bodily fluid spill is major, an outside qualified decontamination service may be utilized. Contaminated surfaces shall be cleaned with an appropriate disinfectant such as bleach, and shall be done immediately after any spill of blood or other potentially infectious materials on any surface.

All cleanup materials shall be disposed of properly in a plastic bag that can be sealed.

Handwashing facilities are typically available at our customer facilities however we also supply portable handwashing solutions (Purell) and hand washing towelettes in all company vehicles if the customer facilities are unavailable.

8.4 Training

Any Custom Electric employee who may be potentially "exposed" to a bodily fluid spill will receive initial training and any necessary retraining on Bloodborne Pathogens Safety including the safe, effective use of universal precautions.

"Exposure" means that an employee encounters a bodily fluid spill, or comes in contact with a sharp object that may be contaminated with a Bloodborne Pathogen, in the course of employment.

Our goal is to ensure employee comprehension and understanding of this important topic, including being aware that they may be exposed these hazardous substances during the normal course of their duties.

8.5 Training Content

Training content is organized so all Custom Electric employees receive the same level of training on Bloodborne Pathogens annually. In addition to this annual training, we conduct Tool Box Talks periodically as refresher level training. The training plan

emphasizes these elements:

- ☐ Summary of the standard and this written program, including what hazardous bodily fluids may be present at our client sites
- ☐ The potential consequences of accidental contamination with these types of bodily fluids The proper method to protect or safeguard from exposure to these bodily fluids.

Since all employees are required to wear Universal Precautions PPE when potentially exposed to Bloodborne Pathogens or Other Potentially Infected Materials (OPIM), they shall participate in initial Universal Precautions PPE training, which will cover the following topics, at minimum:

- ☐ When Universal Precautions PPE is necessary,
- ☐ What Universal Precautions PPE is necessary,
- ☐ How to properly put on, take off, adjust and wear Universal Precautions PPE,
- ☐ The limitations of the Universal Precautions PPE, and
- ☐ The proper care, maintenance, useful life and disposal of the Universal Precautions PPE.

8.6 Auditing

Custom Electric will conduct an annual audit of the company's Bloodborne Pathogens program. Program updates will be made consistent with the assessment findings, employee feedback, injuries and illnesses and regulatory requirements.

8.7 All Employees shall:

Use Universal Precautions PPE when required by regulation or this procedure, inspect Universal Precautions PPE prior to use, maintain PPE in a safe and clean working condition and replace PPE if necessary.

8.8 Enforcement

Constant awareness of and respect for hazardous materials, and compliance with all safety rules are considered conditions of employment. Custom Electric reserves the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

9.1 Confined Space Entry

9.2 General

The purpose of this program is to inform interested persons, including employees that Custom Electric is complying with the OSHA Confined Space Standard for General Industry, Title 29 Code of Federal Regulations 1910.146 and OSHA Confined Space Standard for Construction Industry, Title 29 Code of Federal Regulations 1926.1200 "Final Rule" in effect August 3, 2015. We have determined that the nature of our work performed onsite at our customer locations requires written procedures for the evaluation of confined spaces, and where permit- required spaces are identified, we have developed and implemented a permit-required confined space entry program. This program applies to all work operations where Custom electric employees must enter a permit-required confined space as part of their job duties.

Under this program, we identify permit-required spaces in which Custom Electric personnel may enter to perform work, and provide training for our employees according to their responsibilities in the permit space. These employees receive instructions for safe entry into our specific type of confined spaces, including testing and monitoring, appropriate personal protective equipment, rescue procedures, and attendant responsibilities.

Custom Electric will monitor the particular spaces its employees are working in on a job-to-job basis. Potential hazards will be identified and the conditions will be made as safe as possible.

This program is designed to ensure that safe work practices are utilized during all activities regarding the permit space to prevent personal injuries and illnesses that could occur.

9.3 Hazard Evaluation for Permit Spaces

To determine if there are permit-required confined spaces at our customer' facilities or job sites, we require that our customer's inform our personnel of the location and nature of permit required confined spaces found within their workplace. Custom Electric will obtain the host employer's information about the permit space hazards and previous entry operations and obtain all of the controlling contractor's information regarding permit space hazards and entry operations. Custom Electric will also inform the controlling contractor of the permit space program that our employees will follow, including any hazards likely to be confronted or created in each permit space. The controlling employer shall be responsible for coordinating all related activities by other employers located at this site that may have an impact on Custom Electrics permit entry operations.

9.4 Safe Permit Space Entry Procedures

The Custom Electric Entry Supervisor is responsible for authorizing entry and issuing entry permits for work in our permit spaces. The file of permits and related documents are kept in Custom Electric office. The procedures we follow for preparing, issuing, and canceling entry permits includes the following elements:

- (1) Before entry is authorized, our designated Competent Person shall document the completion of measures required by paragraph (d)(3) of this section by preparing an entry permit.
- (2) Before entry begins, the entry supervisor identified on the permit shall sign the entry permit to authorize entry.
- (3) The completed permit shall be made available at the time of entry to all authorized

entrants or their authorized representatives, by posting it at the entry portal or by any other equally effective means, so that the entrants can confirm that pre-entry preparations have been completed.

(4) The duration of the permit may not exceed the time required to complete the assigned task or job identified on the permit.

The entry supervisor shall terminate or suspend the entry permit when the entry operations covered by the entry permit have been completed or a condition that is not allowed under the entry permit arises in or near the permit space.

(5) Custom Electric shall retain each canceled entry permit for at least 1 year to facilitate the review of the permit-required confined space program.

Any problems encountered during an entry operation shall be noted on the pertinent permit so that appropriate revisions to the permit space program can be made.

9.5 Entry Permit

The entry permit that documents compliance with this section and authorizes entry to a permit space shall identify:

- (1) The permit space to be entered;
- (2) The purpose of the entry;
- (3) The date and the authorized duration of the entry permit;
- (4) The authorized entrants within the permit space, by name or by such other means (for example, through the use of rosters or tracking systems) as will enable the attendant to determine quickly and accurately, for the duration of the permit, which authorized entrants are inside the permit space; NOTE: This requirement may be met by inserting a reference on the entry permit as to the means used, such as a roster or tracking system, to keep track of the authorized entrants within the permit space.
- (5) The personnel, by name, currently serving as attendants;
- (6) The individual, by name, currently serving as entry supervisor, with a space for the signature or initials of the entry supervisor who originally authorized entry;
- (7) The personnel, by name, currently serving as designated rescuers;
- (8) The hazards of the permit space to be entered;
- (9) The measures used to isolate the permit space and to eliminate or control permit space hazards before entry; NOTE: Those measures can include the lockout or tagging of equipment and procedures for purging, inerting, ventilating, and flushing permit spaces.
- (10) The measures taken to evaluate and monitor for potential engulfment hazards;
- (11) The acceptable entry conditions;
- (12) The results of initial and periodic atmospheric tests performed, accompanied by the names or initials of the testers and by an indication of when the tests were performed;
- (13) The rescue and emergency services that can be summoned and the means (such as the equipment to use and the numbers to call) for summoning those services;
- (14) The communication procedures used by authorized entrants and attendants to maintain contact during the entry;
- (15) Equipment, such as personal protective equipment, testing equipment, communications equipment, alarm systems, and rescue equipment, to be provided for compliance with this section;
- (16) Any other information whose inclusion is necessary, given the circumstances of the particular confined space, in order to ensure employee safety; and
- (17) Any additional permits, such as for hot work, that have been issued to authorize work in the permit space.
- (18)

9.6 Pre-Entry Evaluation

To ensure the safety and health of our employees, before allowing authorized workers to enter a permit space, we evaluate conditions in that space to determine if the conditions are safe for entry. Any employee, who enters the space, or that employee's authorized representative, has the opportunity to observe the pre-entry and any subsequent testing. The authorized entrant or that employee's representative also has the option of requesting a reevaluation of the space if they feel that the evaluation was not adequate.

- (6)
- (7) Our company follows the procedures to evaluate each permit space before entry according to 1910.146(c)(5)(ii)(C). This includes testing the internal atmosphere with a

calibrated direct-reading instrument for oxygen content, flammable gases and vapors, and potential toxic air contaminants. We also continually test the atmosphere of the space to ensure that the continuous ventilation is preventing the accumulation of a hazardous atmosphere.

9.7 Certification

According to 1910.146(c)(5)(ii)(H) and 1926.1203(a), our company verifies that the space is safe for entry and that the pre-entry measures as required by the standards have been taken, through a written certification that contains the date, location of the space, and signature of the person providing the certification. At our company, the Safety Director is responsible for verifying these procedures. The certification is made before entry and is available to each employee entering the space.

Our company documents the basis for determining that all hazards in a permit space have been eliminated, through a certification that contains the date, location of the space, and signature of the person making the determination. At our company, The Entry Supervisor is responsible for documenting this information. The certification is available to each employee entering the space.

9.8 Equipment

To ensure the safety and health of our employees, Custom Electric provides appropriate equipment to all employees who work in or near our permit spaces. Accordingly, each authorized entrant will use a full body harness, with a retrieval line (if this does not create an additional hazard to the entrant) attached at the center of the entrant's back near shoulder level, above the entrant's head, or at another point which Custom Electric can establish presents a profile small enough for the successful removal of the entrant. Wristlets may be used instead of the full body harness if Custom Electric can demonstrate that the use of a full body harness is infeasible or creates a greater hazard and that the use of wristlets is the safest and most effective alternative.

All electrical lighting and extension cords shall be protected by ground fault circuit interrupters. We maintain all equipment in excellent working condition, train the entrants in the correct usage of this equipment, and ensure that all equipment, including that used for personal protection, is used properly.

Our entry supervisor has the responsibility of ensuring use of the appropriate equipment by all entrants to the confined space.

9.9 Duties: Authorized Entrants

Those persons who have completed the training and are authorized to enter our permit spaces (authorized entrants) are assigned specific duties and responsibilities which they must perform when they work in the permit space. Their duties and responsibilities

- (1) Know the hazards that may be faced during entry, including information on the mode, signs or symptoms, and consequences of the exposure;
- (2) Properly use equipment as required;
- (3) Communicate with the attendant as necessary to enable the attendant to monitor entrant status and to enable the attendant to alert entrants of the need to evacuate the space as required;

9.10 Duties: Attendants

Those persons who have completed the training and have been designated as permit space attendants are assigned specific duties and responsibilities which they must perform in permit space job duties. Their duties and responsibilities include:

- (1) Know the hazards that may be faced during entry, including information on the mode, signs or symptoms, and consequences of the exposure;
- (2) Be aware of possible behavioral effects of hazard exposure in authorized entrants;
- (3) Continuously maintain an accurate count of authorized entrants in the permit space
- (4) Remains outside the permit space during entry operations until relieved by another attendant;
- (5) Communicate with authorized entrants as necessary to monitor entrant status and to alert entrants of the need to evacuate the space;
- (6) Monitor activities inside and outside the space to determine if it is safe for entrants to remain in the space and orders the authorized entrants to evacuate the permit space immediately under any of the following conditions:
 - If the attendant detects a prohibited condition;
 - If the attendant detects the behavioral effects of hazard exposure in an authorized entrant;
 - If the attendant detects a situation outside the space that could endanger the authorized entrants;
 - If the attendant cannot effectively and safely perform all the duties required;
- (7) Summon rescue and other emergency services as soon as the attendant determines that authorized entrants may need assistance to escape from permit space hazards;
- (8) Take the following actions when unauthorized persons approach or enter a permit space while entry is underway:
 - Warn the unauthorized persons that they must stay away from the permit space;

- Advise the unauthorized persons that they must exit immediately if they have entered the permit space; and
- Inform the authorized entrants and the entry supervisor if unauthorized persons have entered the permit space;

(9) Perform non-entry rescues as specified by our rescue procedure; and

(10) Performs no duties that might interfere with the attendant's primary duty to monitor and protect the authorized entrants.

9.11 Duties: Entry Supervisors and Competent Persons

Those persons who have completed the training and have been designated as permit space entry supervisors and Competent Persons are assigned specific duties and responsibilities which they must perform in permit space job duties. Their duties and responsibilities include:

(1) Know the hazards that may be faced during entry, including information on the mode, signs or symptoms, and consequences of the exposure;

(2) Verify, by checking that the appropriate entries have been made on the permit, that all tests specified by the permit have been conducted and that all procedures and equipment specified by the permit are in place before endorsing the permit and allowing entry to begin;

(3) Terminate the entry and cancels the permit as required;

(4) Verify that rescue services are available and that the means for summoning them are operable;

(5) Remove unauthorized individuals who enter or who attempt to enter the permit space during entry operations; and

(6) Determine, whenever responsibility for a permit space entry operation is transferred and at intervals dictated by the hazards and operations performed within the space, that entry operations remain consistent with terms of the entry permit and that acceptable entry conditions are maintained.

9.12 Training Program

Every employee at Custom Electric who faces the risk of confined space entry is provided with training so that each designated employee acquires the understanding, knowledge and skills necessary for the safe performance of the duties assigned to them. All training related materials, documents, and signed certificates are kept in Custom Electric office.

In our company, all employees receive training for entry into permit spaces. When we conduct the training, we use classroom and hands on practical training. New employees are always trained before their initial assignment of duties. New employees must undergo the Custom Electric confined space entry training program prior to their first assignment to work in our permit required confined spaces.

When changes occur in permit-required confined space areas of our company, we will modify our training program. If we have reason to believe that an employee has deviated from a previously trained upon procedure or that their knowledge seems inadequate, we will retrain that employee prior to their next confined space entry assignment.

Upon successful completion of Custom Electric permit-required confined space training program, each participant receives a certificate which they sign verifying that they understand the material presented, and that they will follow all company policies and procedures regarding permit space entry.

9.13 Rescue and Emergency Services

Custom Electric utilizes trained company personnel as the first responders in the event of a required assisted rescue operation. This rescue would be limited to those circumstances where the company trained personnel would not be exposed to and uncontrollable risk during rescue (i.e. unsafe atmospheric conditions). Should situations warrant, local fire department or our customers designated onsite rescue team will be promptly summoned to perform rescue and emergency services in the event of a permit space incident.

9.14 Post-Operations Procedures

Upon completion of work in a permit space, the duration of the permit may not exceed the time required to complete the assigned task or job identified on the permit in accordance with the standard(s). Furthermore, permits are only issued for a duration of time not to exceed one working shift. The entry supervisor will terminate the permit upon the conclusion of the entry operation.

9.15 Review-Procedures

To ensure that all employees participating in entry operations are protected from permit space hazards, Custom Electric reviews the Permit-Required Confined Space Entry Program on a regular basis. We use the retained canceled permits from the past 12 months within one year after each entry and revise the program as necessary. Custom Electric performs a single annual review covering all entries performed during a 12 month period.

9.16 Enforcement

Constant awareness of and respect for permit-required confined space entry hazards, and compliance with all safety rules are considered conditions of employment. Custom Electric reserves the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this permit entry program.

Date:

Confined Space Entry PermitIn the Event of
Emergency Call 911

1. General Information:	Host Employer:
CONFINED SPACE LOCATION:	
REASON FOR PERMIT:	
All concerns associated with this Confined Space Entry have been appropriately addressed. Work is hereby authorized to begin	
ENTRY SUPERVISOR:	
DATE/TIME ISSUED:	DATE/TIME EXPIRED:

2. Entrants:	3. Attendants(s) & Shift Duration

4. Confined Space Pre-Entry List:

CHECKLIST INSTRUCTIONS: THE ENTRY SUPERVISOR SHALL ANSWER AND INITIAL EACH CHECKLIST ITEM AS IT IS COMPLETED. THE ENTRY SUPERVISOR SHALL AUTHORIZE WORK TO BEGIN BY SIGNING BELOW, ONLY AFTER ALL CHECKLIST ITEMS HAVE BEEN APPROPRIATELY ADDRESSED. THE ENTRY SUPERVISOR SHALL CANCEL THE PERMIT BY SIGNING BELOW AFTER WORK IS COMPLETED, OR IF CONDITIONS ARISE THAT ARE OUT OF COMPLIANCE WITH THE CHECKLIST.

	Yes	No	N/A	Initials
1. Have all personnel been appropriately trained and instructed in CSE procedures?	☐	☐	☐	
2. Have emergency communication and action procedures been identified and explained?	☐	☐	☐	
3. Have all hazardous sources of energy been locked/tagged out?	☐	☐	☐	
4. Is a Hot Work Permit required?	☐	☐	☐	
5. Are ventilators positioned and operating properly?	☐	☐	☐	
6. Are the ventilators in use sufficient to maintain an atmosphere free from contaminants?	☐	☐	☐	
7. Is the gas detector within calibration limits and operating properly?	☐	☐	☐	
8. Is the space and surrounding area free of harmful vapors and gases?	☐	☐	☐	
9. Is the appropriate fall protection/retrieval equipment been installed and inspected?	☐	☐	☐	
10. Has the body harness been donned and properly inspected?	☐	☐	☐	
11. Is a fire extinguisher available?	☐	☐	☐	

Custom Electric Company Safety Plan
August 2026

12.	Is explosion-proof equipment required (i.e. lighting, radios)	☐	☐	☐	
13.	Is an appropriately maintained First Aid Kit available?	☐	☐	☐	
14.	Is the entry area secured and marked with barriers?	☐	☐	☐	
15.	Is traffic control equipment in place?	☐	☐	☐	
16.	Is other safety equipment necessary (i.e. hard hat, SCBA, etc.)?				
17.	If applicable, is upstream storm water and weather monitored				

5. List of Potential Hazards of the Space:	6. List Safety Equipment Required:

7. Method of Attendant/Entrant Communication:	8. Method for Contacting Emergency Rescue Service:

9.	Atmosphere Readings	Note: Conduct 1st reading before ventilating space												
		Gas	1st	Time:	Time:	Time:	Time:	Time:	Time:	Time:	Time:	Time:	Time:	Time:
		Readings	reading:											
		O2												
	CO													

	H2S	
	LEL	
10.	Confined space work is complete. This permit is hereby canceled:	

Entry Supervisor's Signature

Date and Time

11.	Rescue Means: Site Specific Rescue Services			
Check box				
	Local Fire Department:	Has Local Fire Department been notified agreed to	Yes (name of officer)	No

		provide immediate rescue		
	Company Designated Recue Team	Has team been properly trained and equipped to perform rescue	Yes	No
	Company Contracted Recue Service	Name of Service		

10.0 Contractor Safety Policy

Good communication is a necessary element of maintaining safety at our job sites. Communication among our company and subcontractors must identify safety hazards and prevention practices that each brings to the worksite. Therefore, Custom Electric has implemented the following contractor safety program for our worksites so that on the job injuries are minimized and work practices may be standardized.

10.1 Purpose

A written contractor safety policy establishes guidelines to be followed for contractors working at our company. The rules established:

- * Provide a safe working environment.
- * Govern facility relationships with outside contractors.
- * Ensure that contractor employees and our employees are trained to protect themselves from all potential and existing hazards.

The effectiveness of the contractor safety program depends upon the active support and involvement of all employees. This plan is intended to implement a program to ensure that all contractor work practices are carried out safely to minimize the possibility of injury or harm to the contractors' employees or our own employees. It is intended to serve as an additional tool in safeguarding the health and safety of employees.

The contractor safety policy establishes uniform requirements designed to ensure that contractor safety orientation, coordination, and safety administration practices are communicated to and understood by employees.

This document is provided to ensure all corporate safety plans, policies and procedures are communicated to all participating contractors. It also provides an avenue for contractors to communicate their safety plans, policies and procedures to the company. This program aims to prevent personal injuries and illnesses.

10.2 Administrative Duties

The Safety Director is responsible for developing and maintaining the program. Employees may review a copy of the plan. It is located at our main office in Manchester Connecticut.

If after reading this program, you find that improvements can be made, please contact The Safety Director. We encourage all suggestions because we are committed to the success of our contractor safety program. We strive for clear understanding, safe behavior, and involvement from every level of our company.

10.3 Explanation Of Responsibilities

Company Responsibilities

This company has specific safety responsibilities when hiring contractors to come onto the worksite, onto the grounds, or into the buildings or facilities to perform work. Company responsibilities when hiring contractors include the following listed steps. The company will:

1. Take steps to protect contract workers who perform work on or near a potentially hazardous process.
2. Obtain and evaluate information regarding the contract employer's safety performance and programs.
3. Inform the contractor of known potential fire, explosion, or toxic release hazards related to the contractor's work and the process.
4. Explain the applicable provisions of the emergency action plan to the contractor, and require that the contractor disperse that information to all workers who will work at this site.
5. Develop and implement safe work practice procedures to control contract employee entry into hazardous work areas.
6. Maintain a contract employee injury and illness log.
7. Periodically evaluate the contract employer's fulfillment of his or her responsibilities under this policy.
8. Hire and use only contractors who meet Contractor Selection Criteria as listed in the next section of this policy.

Contractor Responsibilities

Contractor employees must perform their work safely. Considering that contractors often perform very specialized and potentially hazardous tasks, such as confined space entry activities and non-routine repair activities, their work must be controlled. Contractor responsibilities when accepting contracts with this company include the following listed steps. The contract employer will:

1. Assure that the contract employee is trained in the work practices necessary to safely perform his or her job.
2. Instruct the contract employee in the potential fire, explosion, or toxic release hazards related to his or her job and the process.
3. Assure that the contract employee knows the applicable provisions of the emergency action plan.
4. Document contract employee training.

5. Inform contract employees of and then enforce safety rules of the facility, particularly those implemented to control the hazards of the contracted process during operations.
6. Require that all subcontractors abide by the same rules to which this section binds the contractor.
7. Smoking is prohibited in all indoor areas at all jobsites. Smoking is allowed only in designated outdoor areas.
8. Therefore, permission must be requested before the contractor's employees are allowed to smoke in any area.

10.4 Guidelines For Contractor Safety

The following listed steps are the standard procedures for evaluating and choosing contractors who will work on-site at this company.

Obtain and evaluate information regarding a contractor employer's safety performance and programs when selecting a contractor to perform any type of contract work that might bring them into contact with any hazardous chemical or process on the premises of this company.

To determine that past safety performance, the group or individual selecting the contractor should consider the contractor's:

- * Employee injury records such as Experience Modification Rate (EMR or MOD) for workers' compensation for the past three years and the contractor's past safety record in performing jobs of a similar nature.
- * OSHA log, which includes the injury and illness rates (number of lost-time accident cases, number of recordable cases, number of restricted workday cases, number of fatalities) for the past three years.
- * Incidence rates for lost-time accidents and recordables for the past three years.
- * Written safety program and training system.

For contractors whose safety performance on the job is not known, obtain information on injury and illness rates and experience and obtain contractor references.

Contractor work methods and experience should be evaluated. Ensure that for the job in question the contractor and its employees have the appropriate:

- * Job skills.
- * Equipment.
- * Knowledge, experience, and expertise.
- * Any permits, licenses, certifications, or skilled trades' people necessary to be capable of performing the work in question.

The contractor must be willing and able to provide a current certificate of insurance for workers' compensation and general liability coverage with the contracting company.

Each contractor must be responsible for ensuring that its employees comply with all applicable local, state, and federal safety requirements, as well as with any safety rules and regulations set forth by this company, at which it is performing the contracted work.

Possible ways to determine past compliance with such safety regulations include:

- * Requesting copies of any citations for violations occurring within the last three years, to determine the frequency and type of safety laws violated.
- * Having all bidders on jobs describe in detail in writing any safety programs in place at the contractor, infractions, accidents, and workers' compensation claims within the last three years. This information will provide Custom Electric with a solid background on that contractor's safety performance and adherence to safety rules and regulations.

10.5 Guidelines For Information Exchange

Company Guidelines for Information Exchange

Before contract work begins, this company must:

1. Designate a representative to coordinate and communicate all safety and health issues and communicate with subcontractors. The designated representative will have a copy of the work document, be thoroughly familiar with its contents, and with the safety and health aspects of the work, or know whom to call to obtain this information. The designated representative is responsible for ensuring that all company responsibilities listed below are carried out.
2. Provide a copy of the job site written safety policies and procedures to the contractor.
3. Inform the contractor of any emergency signals and procedures that may be put into operation in areas where the contractor's employees are working. The contractor should be given the telephone numbers of the nearest hospital, ambulance service, and fire department.
4. Conduct an inspection of the proposed worksite area before the prestart-up meeting so any known information about on-site hazards, particularly non-obvious hazards, are documented and thoroughly communicated to the contractor.
5. Work directly with the contractor's designated representative, with whom all contacts should be made.
6. Conduct a pre-start up meeting (walk through) with the contractor's designated representative and a supervisor from each of the areas of the plant involved in the contractor's work.
7. Review all contract requirements related to safety and health with the contractor's designated representative, including, but not limited to, rules and procedures, personal protective equipment (PPE), and special work permits or specialized work procedures. Advise the contractor that the job site safety and health policies must be followed. A copy of the job site's safety plans must be furnished to the contractor.
8. Inform contractor's designated representative of the required response to employee

alarms and furnish the contractor with a demonstration or explanation of the alarms.

9. Communicate thoroughly with the contractor's designated representative any safety and health hazards (particularly non obvious hazards and hazard communication issues) known to be associated with the work, including those in areas adjacent to the worksite. Tell them it is the contractor's responsibility to convey this information to its employees.

10. Review preparation of worksite before contractor begins initial work.

11. Identify connect-points for all services, such as steam, gas, water, electricity, etc. Define any limitations of use of such services.

12. Ensure that all affected employees at this company receive training on all hazards to which a contractor will introduce them.

During the contract work, our company will:

1. Limit, as necessary, the entry of company employees into contractor work areas.

2. Monitor the contractor's compliance with the contract throughout the duration of the work. When checking contractor work during the project, note any negligent or unlawful act or condition in violation of safety standards or requirements. Any items noted should be brought immediately to the attention of the contractor's designated representative in writing, with a copy of the notice being sent to the contractor's home office concurrently. However, if an unsafe act or a condition is noted that creates an imminent danger of serious injury, immediate steps should be taken with the contractor's designated representative, or in his or her absence, the contractor's employees to stop the unsafe act or condition. Do not allow work that is in violation of a regulation to continue.

3. Document all discussions, including place, time, and names of contractor employees in attendance.

4. Approve the contractor beginning work each day, unless it is routine service or maintenance work or periodic outdoor service or maintenance work.

5. For work for which this company has developed specific and generally applicable procedures, make sure contractors and their subcontractors follow the same procedures.

6. Do not allow loaning of tools and equipment to outside contractors and their subcontractors. The contractor is required to provide the necessary tools and equipment.

7. Contact the nearest medical facilities, when available, in emergency situations where severity of the injury dictates immediate attention.

8. Obtain a copy of each OSHA recordable injury report from the contractor and subcontractor. Investigate and report to the facility manager all personal injuries to contractor and subcontractor employees.

9. Investigate and report any property losses. Maintain a contractor accident report file.

After conclusion of the contract work, the designated representative completes a post-project assessment of the contractor's safety performance for the facility manager to be used for future reference, with a recommendation on whether or not to re-hire the

Contractor Guidelines for Information Exchange

Before the contract work begins, the contractor must:

1. Designate a representative to coordinate all safety and health issues and communicate with this company's designated representative.
2. Provide documentation of any necessary safety training, as described in the Training Requirements section of this policy, to this company's designated representative.
3. Sign a confidentiality statement to protect this company's proprietary data.
4. Provide information to the designated representative on the safety and health hazards that may arise during the course of the contractor's work at this company and the means necessary to avoid danger from those hazards, including Hazard Communication and all other potential hazards.
5. Obtain from this company any safety rules and regulations in effect at the site or potential hazards present that may affect the contractor's work.
6. Be certain to be informed of any emergency signals and procedures that may be put into operation in areas where the contractor's employees are working. The contractor should be certain to have the telephone numbers of the nearest hospital, ambulance service, and fire department.
7. Advise and train its employees on hazards associated with the work to be performed, including any Hazard Communication or other hazard information provided the contractor by this company's designated representative.
8. Keep the designated representative of this company fully informed of any work that may affect the safety of this company's employees or property. This includes complying with the state and federal right-to-know legislation and providing the designated representative appropriate material safety data sheets (SDSs) or other required information about chemicals the contractor will bring onto the site.
9. Know who to call and what to do in emergencies, including where first aid and medical services are located and train employees on this.

During the contract work, the contractor will:

1. Have a designated site safety coordinator present and attentive to the work being carried out at all times that the contractors and/or subcontractors are working at the facility site.
2. Ensure that all subcontractors are abiding by the terms of this plan.
3. Perform its work while the plant is operating, if necessary, and establish necessary safe practices to permit work under operating conditions without endangering this company's associates and property. This includes but is not limited to barricading, sign-posting, and fire watches.

4. Make sure that any equipment, chemicals, or procedures used by the contractor to perform contracted work meet all OSHA requirements.
5. Be held responsible and accountable for any losses or damages suffered by this company and/or its employees as a result of contractor negligence.
6. Provide its employees with medical care and first-aid treatment. Plant first-aid facilities may be used only in case of emergencies.
7. Use only the job site entrance designated, and follow the job site access control practice.
8. Provide supervisors and employees who are competent and adequately trained, including training in all health and safety aspects of the work involved in the contract.
9. Provide all tools and equipment for the work, including personal protective equipment (PPE), and ensure the equipment is in proper working order and employees are instructed in its proper use.
10. Maintain good housekeeping in the workplace.
11. Follow specific instructions supplied by this company should emergency alarms be activated.
12. Notify the designated representative immediately of any OSHA recordable injury or illness to contractor employees or subcontractor employees occurring while on the site of this company. Provide a copy of each accident report to the designated representative.
13. Receive and use a copy of the job site's written safety policies and procedures.

After conclusion of the contract work, the contractor is responsible for cleaning all work areas and disposing of any discarded materials in a proper and legal manner.

10.6 Training Requirements

Company Requirements

Custom Electric makes sure that affected company employees receive training on all hazards to which a contractor will introduce them.

In addition, we emphasize to the contractor that it is the contractor's responsibility to convey to its employees any safety information provided by the company to the contractor.

Contractor Requirements

The contractor must:

1. Train all workers on all safety and health hazards and provisions applicable to the type of work being done, and provide documentation of such training to this company's designated representative.

2. Train employees on where to obtain first aid and medical services.

10.7 Recordkeeping Requirements

Company Requirements

The designated representative will:

1. Have a copy of the contract on file and be thoroughly familiar with its contents, and with the safety and health aspects of the work.
2. Keep records of all training done with company workers regarding hazards to be caused by the contracting company.
3. Keep copies on file of all forms or statements related to the contracts that are required by the company to be filled out before or during contract work.
4. Keep an OSHA recordable injury and illness log for the project, as well as copies of accident reports on all accidents that occur in the course of the project.
5. Keep a daily log regarding pre-work start-up inspection findings.
6. Keep records of all documentation of any sort given to you by the contractor, including records of training done, SDSs, accident reports, etc.
7. Keep records of all documentation of any sort you give to the contractor, including list of hazards to train their employees on, SDSs, etc.
8. Document all discussions, letters, memos, or other communications made to the contractor regarding safety issues, including place, time, names of people involved.

Contractor Requirements

The contractor will:

1. Keep records of all training done with contract workers and all documentation provided to the contracting company regarding such training.
2. Keep copies on file of all forms or statements related to the contracts that are required by the company to be filled out before or during contract work.
3. Have on file the telephone numbers of the nearest hospital, ambulance service, and fire department.
4. Have copies on-site of all material safety data sheets (SDSs) or other required information about chemicals relevant to the work on-site.
5. Keep an OSHA recordable injury and illness log for the project, as well as copies of accident reports on all accidents that occur in the course of the project.

10.8 Enforcement

Constant awareness of and respect for hazardous materials, and compliance with all safety rules are considered conditions of employment. Custom Electric reserves the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

11.1 Electrical Safety and Lockout/Tagout

11.2 General Company Policy

Custom Electric complies with the OSHA Electrical Safety Standard, Title 29 Code of Federal Regulations 1910.333 and 1926 Subpart K, by establishing the following written procedures for preventing electric shock or other injuries resulting from direct/indirect electrical contacts to employees working on or near energized or de-energized parts. This program applies to all work operations at Custom Electric where employees may be exposed to live parts and/or those parts that have been de-energized.

The Safety Director has overall responsibility for coordinating safety and health programs in this company. The Safety Director has overall responsibility for the Electrical Safety Program. The Safety Director will review and update the program, as necessary. Under this program, our employees receive instructions in the purpose and use of energy control procedures, as well as the other required elements of the Control of Hazardous Energy standard. This instruction includes the de-energizing of equipment, applying locks and tags, verifying de-energization, and equipment reenergizing.

Custom Electric's company policy is to adhere to or exceed the most stringent of policies, whether it be Custom Electric's or the facility or location of work being performed.

11.3 Hazard Analysis Report

To determine areas of Custom Electric facilities that need to be included in the Electrical Safety Program, the Safety Director will have a hazard analysis conducted of our work site. This analysis will provide us with information identifying which locations have equipment using electricity, various types of wiring installations, and the types of employee functions that must be covered by the Electrical Safety Program.

Electrically operated equipment that must be de-energized before work can be done on it and where it is located includes all electrically driven equipment utilized by Custom Electric.

Employees of our company must be qualified by the Safety Director to work on, near, or with energized electric circuits and equipment as per the requirements of NFPA70E.

11.4 Training Program

Every employee at Custom Electric who faces the risk of electric shock from working on or near energized or de-energized electrical sources receives training in electrical related safety work practices pertaining to the individual's job assignment.

The goal of our electrical safety training program is to ensure that all employees understand the hazards associated with electric energy and that they are capable of performing the necessary steps to protect themselves and their co workers.

Our electrical training program covers these basic elements:

- * Affected Employee level training on Lockout and tagging of conductors and parts of electrical equipment.
- * Safe procedures for de-energizing circuits and equipment.
- * Application of locks and tags.
- * Verification that the equipment has been de-energized.
- * Procedures for reenergizing the circuits or equipment.
- * Other electrically related information that is necessary for employee safety.

When changes involving electrical elements occur in our company, we provide additional employee training to ensure the safety of all affected workers.

The Safety Director conducts basic electrical safety training for all affected employees. Every employee who participates in the Electrical Safety Program receives a certificate which they sign verifying that they have completed the course, that they understand the information presented, and that they will follow all company policies and procedures regarding electrical safety. The Safety Director keeps these signed certificates of training, as well as all training materials and documentation.

11.5 Lockout/Tagout Program

It is a Custom Electric policy that circuits and equipment must be disconnected from all electric energy sources before work on them begins. We require the use of lockout and tagging devices to prevent the accidental re-energization of this equipment. These lockout and tagging procedures are the main component of our electrical safety program. The safety procedures that make up our lockout and tagging program include these elements:

- **De-energizing circuits and equipment.** The circuits and equipment to be worked on are disconnected from all electric energy sources and stored energy that could accidentally reenergize equipment is released.
- **Application of locks and tags.** Only authorized employees are allowed to place a lock and tag on each disconnecting means used to de-energize our circuits or equipment before work begins. Locks prevent unauthorized persons from reenergizing the equipment or circuits and the tags prohibit unauthorized operation of the disconnecting device.
- **Verification of de-energized condition of circuits and equipment.** Prior to work on the equipment, we require that a "qualified" person verify that the equipment is de-energized and cannot be restarted.
- **Reenergizing circuits and equipment.** Before circuits or equipment are reenergized, we require these steps be followed in this order:
 - A "qualified" person conducts tests and verifies that all tools and devices have been removed.
 - All exposed employees are warned to stay clear of circuits and equipment.
 - Authorized contractors remove their own locks and tags.
 - A visual inspection of the area to be sure all employees are clear of the circuits and equipment.

The Safety Director is responsible for the overall lockout and tagging procedures in our company.

Employees of our company are not permitted to work on, near, or with energized electric circuits and equipment unless they have been specifically qualified by management and have undergone comprehensive training on all aspects of NFPA70E.

11.1 Enforcement

Constant awareness of and respect for electrical hazards, and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

12.1 Ergonomic Injury Prevention Program

12.2 General Company Policy

The purpose of this program is to inform interested persons, including employees, that Custom Electric is committed to improve our employees' comfort and well being by identifying and correcting ergonomic risk factors on the job. This program applies to all work operations, both in our office areas as well as our jobsites.

Under this program, our Safety Director will evaluate jobs that have been identified as having "problem areas" and develop and implement solutions to reduce job-related worker injury and illness.

Our goal through this Ergonomics Program is to prevent the occurrence of work-related musculoskeletal disorders by controlling or eliminating the risk factors that cause them. This program ensures that all affected employees are aware of job-related risk factors and provides information and solutions to elevate them. Custom Electric promotes continuous improvement for the efficiency, comfort, and well being of all employees through a team effort of management and employee involvement.

The Director members have been trained to recognize problem jobs, identify risk factors, and develop solutions to reduce those factors. Elements of this training include the identification of workplace risk factors; job analysis methods, implementation and evaluation of control measures, and teamwork skills.

12.3 Injury/Medical Management

We encourage all employees to immediately report any symptoms of discomfort that may be associated with their job duties. In most cases, employees are to report to their immediate supervisor. Those supervisors are responsible to recommend alternative work or medical evaluation for injured or ill employees.

Supervisors record and file a written report from the first observation of illness or injury through all subsequent follow-up activities. They are also responsible to forward information about the worker injury or illness for recording on the Log of Work-Related Injuries and Illnesses.

Custom Electric's employees are its greatest asset. Accordingly, we are committed to providing a safe work environment for each employee. However, in the event that an injury is sustained on the job, you must take the following steps to ensure prompt medical treatment and compensation benefits:

1. Report all injuries to your supervisor IMMEDIATELY—no matter how minor
2. If medical attention is necessary, report to your supervisor prior to leaving the facility.
3. Any non-life threatening medical emergency will be treated at a company authorized medical services facility

Employees must submit all bills regarding the injury to Human Resources.

Remember, medical bills and benefits for work-related injuries may be covered under

the Workers' Compensation Act. Immediate notification is necessary for timely payments.

Every work procedure that causes a worker injury or illness will be investigated and reported. This documentation provides vital information for the identification of job related risk factors so that the problems can be corrected before other injuries occur.

After the health care provider has treated an injured employee, the following procedures are used to monitor the recovery process and their return to work.

Custom Electric is committed to providing a safe work environment for its employees. If an employee sustains an injury while employed by this company, every effort will be made to ensure the employee receives quality medical care and is returned to work environment as soon as he/she is physically able.

Employees who may be able to return to work in a limited capacity, but who are temporarily not capable of performing the full scope of their regular job duties, will receive a temporary job assignment through the Custom Electric. transitional, light duty, work program.

Job assignments will be based on specific medical restrictions established by a licensed physician. If work is available for the injured employee and the physical requirements of such work do not violate any of the medical restrictions, the employee will be required to perform the job assignment.

The Company has developed a list of light and restricted duty jobs that have low musculoskeletal risks. This list is a valuable resource for assigning duties to recovering employees until they can resume their normal job functions.

After verification of an employee's job-related injury or illness, our Safety Director will review this plan and re-evaluate the injured workers job function to determine if additional practices, procedures, or redesign of the station could be implemented to prevent similar injuries.

12.4 Identifying Problem Jobs

There are several methods used to identify problem jobs that are most likely to result in ergonomic disorders. The Safety Director initially reviewed and periodically monitors Custom Electric injury and illness records such as the Log of Work-Related Injuries and Illnesses and workers' compensation data to identify patterns of ergonomic-related injuries and illnesses.

In addition, jobs are evaluated for the following risk factors:

- Rate and number of repetitions: performance of the same motion or motion patterns every few seconds for more than two hours at a time.
- Postures and limb positions: fixed or awkward work postures such as overhead work, twisted or bent back, bent wrist, stooping, or squatting, for more than a total of two hours.
- Loads/lifted: lifting, lowering, or carrying of anything weighing more than 25 pounds (11.34 kg) more than once during the work shift.
- Loads/static: holding a fixed or awkward position with arms or neck for more than ten seconds.
- Muscle forces: continually pulling or pushing objects.

12.5 Solutions

When a job, process, or equipment has been evaluated, the Safety Director completes a risk factor checklist. Through this checklist, problems are identified for correction and supervisors and employees in the affected areas are notified. The Safety Director, in conjunction with those affected employees, will develop possible solutions, choose the most appropriate, implement the changes, and follow up to determine the effectiveness.

12.6 Employee Training

Custom Electric's management staff receives copies of this written ergonomics program and the company's policy statement regarding ergonomics in our workplace. We train each employee who works at a job with exposure to specific risk factors and each employee in a job where a work-related musculoskeletal disorder has been recorded.

These are the ergonomic elements we teach to all employees:

- How to recognize workplace risk factors associated with work-related musculoskeletal disorders and the ways to reduce exposure to those risk factors.
- The signs and symptoms of work related musculoskeletal disorders, the importance of early reporting, and medical management procedures.
- Reporting procedures and the person to whom the employee is to report workplace risk factors and work-related musculoskeletal disorders.
- The process Custom Electric is taking to address and control workplace risk factors, each employee's role in the process, and how to participate in the process.
- Opportunity to practice and demonstrate proper use of implemented control measures and safe work methods that apply to the job.

Each employee involved in job analysis will be trained in job analysis methods, especially as they relate to identifying workplace risk factors, and evaluation and implementation of control measures.

This company will not implement any policy or practice which discourages reporting or which results in discrimination or reprisal against any employee who makes a report.

12.7 Enforcement

Constant awareness of and respect for ergonomic hazards, and compliance with all safety rules are considered conditions of employment. Custom Electric reserves the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

13.1 Fall Protection Plan

13.2 Purpose

Written fall protection procedures establish guidelines to be followed whenever an employee works on ladders, at heights, or with fall protection at our company. The rules established are to be followed to:

- * Provide a safe working environment, and
- * Govern use of fall protection procedures and equipment.

The effectiveness of the written fall protection procedures depends upon the active support and involvement of all employees who work with procedures and jobs requiring it. This written plan is intended to be used in implementing procedures to ensure that work with fall protection is carried out safely to minimize the possibility of injury or harm to our employees.

These written fall protection procedures establish uniform requirements designed to ensure that fall protection training, operation, and practices are communicated to and understood by the affected employees. These requirements are also designed to ensure that procedures are in place to safeguard the health and safety of all employees.

It is the policy of Custom Electric to permit only employees trained in fall protection procedures to work in areas where fall hazards occur, to reduce likelihood of fall accidents and to help ensure a safe workplace.

13.3 Administrative Duties

The Safety Director is responsible for developing and maintaining this written Fall Protection Plan. The Safety Director is solely responsible for all facets of the plan and has full authority to make necessary decisions to ensure the success of this plan. Appropriate training and experience that is commensurate with the complexity of the plan, to administer and oversee our fall protection plan and conduct the required evaluations of plan effectiveness, also qualify the Safety Director.

13.4 Pre-Work Check

Prior to beginning work in any area or on any device where fall hazards exist, a pre-work check must be completed that includes the following items:

13.3a Stairs

- All required covers or guardrails must be in place.
- All handrails or guardrails are in place on stairways.
- All treads and risers on stairs are in good repair.
- Non-slip surfaces are in place on stairs.
- All stairs meet OSHA and ANSI specifications for design and safety.

13.3 b Ladders

Except where permanent stairways, temporary stairways, suitable ramps or runways are provided, ladders shall be provided to give access to all floors, scaffolds and platforms where work is being performed more than four feet above the ground or to a permanent or temporary floor. This requirement may be waived, where other acceptable means of access has been provided.

13.3c Care and Use

- Ladders shall be inspected prior to each daily use.
- When portable ladders are used, they should be inclined so that the horizontal distance from the foot of the ladder to a plumb line dropped from the upper point of support is approximately $\frac{1}{4}$ of the ladder length from the base to the upper support. In case of necessity, where a ladder is placed more nearly vertical, it shall be securely fastened to prevent tipping. If placed more nearly horizontal, it should be braced to prevent sagging.
- Portable ladders should be so placed that all side rails have secure footing. The top rest should be rigid and have ample strength to support the applied load and the top of the ladder shall be tied or otherwise securely fastened to prevent movement or held by someone at the bottom.
- Separate or double cleat ladders for ascending and descending should be provided where traffic warrants.
- Ladders with broken or missing rungs or steps, broken or split side rails, or other faulty or defective construction shall not be used. When ladders with such defects are discovered they shall be tagged, withdrawn from service, replaced or marked for repair or destruction. Limited repairs may be made with ladders in position.
- Single portable ladders over 30 feet in length shall not be used. If greater heights are to be reached, separate ladders shall be used and intermediate-landing platforms provided.
- Ladders made by fastening cleats across a single rail shall not be used.
- Single short ladders shall not be splice together to provide long sections.
- Ladders where used within shafts or hoist ways shall be protected from objects falling from operations at higher elevations in or adjoining the enclosure.
- Portable ladders, where used on smooth floors or other smooth surfaces, shall be equipped with non-slipping bases, or otherwise secured to prevent displacement.
- Ladders shall be of sufficient length to project at least 3 feet above the top landing, except where such extension would in itself constitute a hazard. Ladders should never be painted, to do so tends to hide or camouflage weaknesses, which would otherwise be seen.

- Ladders shall be equipped with safety feet.
- All employees are required to maintain 3 points of contact when using or accessing a ladder. This means that either two hands and one foot, or two feet and one hand must always been in secure contact with the ladder when in use.
- Do not permit more than one person at any time on a ladder.
- Ladders shall not me moved while loaded.

13.3d Platforms

- Guardrails are in place and securely attached.
- Toeboards are in place and secure.
- All platforms meet OSHA specifications for design and safety.

13.4 Work Procedures

If any one of the conditions described in Pre-Work Check is not met for the area or piece of equipment posing a potential fall hazard, then employees may not perform that work until the condition is met. If the condition cannot be remedied immediately, a supervisor or must be notified of the problem.

All employees are required to use personal fall protection when exposed to a potential fall of six feet or greater to the next lower surface if that exposure is not controlled by effective fall prevention, such as, but not limited to, guard rail systems. If the situation calls for use of fall protection devices, such as harnesses, or positioning or restraining devices, then the employee must don such protective equipment before beginning the work and use it as intended throughout the duration of the work. Only employees trained in such work are expected to perform it.

To prevent slipping, tripping, and falling, all places of employment, passageways, storerooms, and service rooms must be kept clean and orderly and in a sanitary condition. The floor of every workroom will be maintained in a clean and, so far as possible, dry condition. Where wet processes are used, drainage will be maintained, and false floors, platforms, mats, or other dry standing places are provided where practicable.

13.5 Rescue

In the event of a fall related incident, if an employee is unable to self-rescue, our employees are equipped with suspension trauma straps on their harnesses. These straps are included on all company harnesses. Our employees are trained on the use of trauma straps.

Job tasks will be reviewed for their fall hazard potential. Basic rescue plans will be communicated to all affected workers including the deployment of available mobile elevating work platforms to perform rescue. Should there be an obvious injury related to

the incident, local emergency services will be immediately contacted for assistance with the rescue and treatment of the worker.

13.6 Training Program

Under no circumstances will an employee work in areas of high fall hazards, do work requiring fall protection devices, or use fall protection devices until he/she has successfully completed this company's fall protection program. This includes all new employees, regardless of claimed previous experience.

The training program includes classroom instruction and operational training on each specific area of fall hazard involved in the work of the employee.

The Safety Director will identify all new employees in the Employee Orientation Program and make arrangements with department management to schedule the classroom instruction for those employees previously identified in this procedure.

Classroom training consists of:

- Review of these written procedures by employee.
- Review of fall protection training video.
- Successful completion of examination.

Operational training consists of:

- Pre-operational check.
- Operational review of use of lanyards and belts, accessing of areas with fall hazards.

13.7 Recordkeeping

The Safety Director maintains training records that include the following information:

- 13.7.1** The date the training was provided,
- 13.7.2** The specific area of fall hazard involved in the work of the employee, and
- 13.7.3** A certification signed by the employee receiving the training.

13.8 Disciplinary Procedures

Constant awareness of and respect for fall protection procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

13.9 Program Evaluation

Although we may not be able to eliminate all problems, we try to eliminate as many as possible to improve employee protection and encourage employee safe practices. Therefore, The Safety Director is responsible for evaluating and updating this written plan. The evaluation will include a review of reported accidents, as well as near misses, to identify areas where additional safety measures need to be taken.

The Safety Director will also conduct a periodic review to determine the effectiveness of the program. This review may include:

- 13.9.1** A walk-through of the facility, and
- 13.9.2** Interviews with employees to determine whether they are familiar with the requirements of this program and if safety measures are being practiced.

13.0B Scaffolding and Aerial Work Platform Safety

Purpose

It is Custom Electric ' purpose in issuing these procedures to further ensure a safe workplace based on the following formal, written procedures for scaffold work. These procedures will be reviewed and updated as needed to comply with new OSHA regulations, new best practices in scaffolding, and as business practices demand. This general scaffold plan applies to all work sites where our company may utilize scaffolding systems.

Capacity

Taking into account the OSHA rules we must apply and the engineering/manufacturing requirements of our scaffolds, the following rules apply. Each scaffold and scaffold component we use will support, without failure, its own weight and at least four times the maximum intended load applied or transmitted to it.

Platform Construction

This section documents the procedures and safety requirements we use to construct our fabricated frame supported scaffold platforms.

The following safety rules apply for this scaffold platform construction:

- Each scaffold plank or platform will be installed so that the space between adjacent planks and the space between the platform and uprights is no more than one inch wide.
- Except for outrigger scaffolds (3 inches) and plastering and lathing operations (18 inches), the front edge of all platforms will not be more than 14 inches from the face of the work, unless we have a guardrail or personal fall arrest system in place that meets regulations.
- Supported scaffolds with a height to base width ratio of more than four to one (4:1) must be restrained from tipping by guying, tying, bracing, or equivalent means.
- Supported scaffold poles, legs, posts, frames, and uprights will always bear on base plates and mud sills or other adequate firm foundations.
- We provide fall prevention or protection for any employee on a scaffold more than 10 feet above a lower level.

Gaining Access to Scaffolds

We know that getting to the working platform is critical to the safety of our employees. This section outlines the mechanical requirements for gaining access to scaffold platforms such as ladders, ramps and walkways, stair rails and direct access from another scaffold. This section is divided into two parts. The first part is for workers gaining access to scaffold platforms to do work; the second part is access for employees erecting and dismantling scaffolds.

Working Employees:

- Portable, hook-on, and attachable ladders will be positioned so as not to tip the scaffold. The top of the ladder will extend 36 inches beyond the work surface being accessed and the ladder will be secured in place.

- All stair rail systems and handrails will be surfaced to prevent injury to our employees from punctures or lacerations, and to prevent snagging of their clothes.

Erectors and Dismantlers:

Fall Protection Plan

Fall protection planning is critical to the safety and well being of our employees.

Our fall protection plan follows the OSHA requirements that are different depending on the type of scaffold we are using. In this plan we address fall protection for our self-contained adjustable scaffold supported by the frame structure. We provide fall prevention or protection for any employee erecting a scaffold more than 10 feet above a lower level if there is not an installed handrail as detailed below.

We also protect each employee on our self-contained, frame structure supported, adjustable scaffolds by a guardrail system. The guardrail system:

- Has a minimum 200 pound top rail capacity
- Will be installed before being released for use by our employees.

Falling Object Protection

All employees must wear hardhats when working on, assembling, or dismantling scaffolds. This is our primary protection from falling objects. Additionally, we will:

- Install all guardrail systems with openings small enough to prevent passage of potential falling objects.
- Prevent tools, materials, or equipment that inadvertently fell from our scaffolds from striking employees by barricading the area below the scaffold.

Using Scaffolds

Site preparation, scaffold erection, fall protection, and gaining access to the working platform are only part of the requirements for scaffold work. While this all takes concentration and safe work practices, the most dangerous time can be when employees are concentrating on their work and not particularly aware of the hazards of working from scaffolds. It is critical that employees who use scaffolds be trained, among other things, in the recognition of the hazards associated with the type of scaffold being used and to understand the procedures to control or minimize those hazards. Our competent person will inspect all scaffolds and scaffold components for visible defects before each work shift, and after any occurrence that could affect a scaffold's structural integrity. Scaffolds that fail inspection will be "tagged out of service" until proper repairs or modifications have been made. Our competent person completes a scaffold inspection form as part of this process. However, in addition to that, all users of scaffolds in this company will know and understand the following safety rules:

- Scaffolds and scaffold components will never be loaded in excess of their maximum intended loads or rated capacities.
- Debris must not be allowed to accumulate on platforms.

Prohibited Practices

The following practices will never be tolerated in this company:

- Scaffold components manufactured by different manufacturers will never be intermixed unless the components fit together without force and the scaffold's structural integrity is maintained.
- Unstable objects will never be used to support scaffolds or platform units. Footings must be level, sound, rigid, and capable of supporting the loaded scaffold without settling or displacement.

- Cross braces will never be used as a means of access.
- The use of shore or lean-to scaffolds is prohibited.

Aerial Lifts

Anytime aerial lifts, including:

- (1) Extensible boom platforms,
- (2) Aerial ladders,
- (3) Articulating boom platforms,
- (4) Vertical towers, or
- (5) A combination of any such devices, are used to elevate employees to job-sites above ground, the following safety rules will apply:

No aerial lift this company owns or uses will be 'field modified' for uses other than those intended by the manufacturer unless the manufacturer certifies the modification in writing, or any other equivalent entity, such as a nationally recognized testing lab, certifies the aerial lift modification conforms to all applicable provisions of ANSI A92.2-1969, and the OSHA rules at 1926.453. The lift must be at least as safe as the equipment was before modification.

Extensible and articulating boom platforms:

- We will test lift controls each day prior to use to determine they are in safe working condition.
- Only trained and authorized employees may operate an aerial lift.
- A full body harness must be worn and a lanyard attached to the boom or basket as specified by the equipment manufacturer when working from an aerial lift.

Duties of Competent and Qualified Persons

When working with scaffolds in this company there are some tasks that must be done by our competent or a qualified person. By definition they are:

- Competent Person-One who is capable of identifying existing and predictable hazards in the surroundings or working conditions which are unsanitary, hazardous, or dangerous to employees, and who has authorization to take prompt corrective measures to eliminate them.
- Qualified Person-One who, by possession of a recognized degree, certificate, or professional standing, or who by extensive knowledge, training and experience, has successfully demonstrated his/her ability to solve or resolve problems related to the subject matter, the work, or the project. The following tasks will only be done by the person we have deemed competent or qualified to perform.

Competent Person:

We will not intermix scaffold components manufactured by different manufacturers unless the components fit together without force and the scaffold's structural integrity is maintained. Scaffold components manufactured by different manufacturers will not be modified in order to intermix them unless our competent person determines the resulting scaffold is structurally sound.

- Prior to each work shift, at anytime during the work shift when the scaffold appears to have been moved or damaged, and after every weather event which could affect the scaffolds structural integrity, all scaffolds will be inspected by our competent person. If a scaffold is determined to be unsafe as a result of this inspection, the

scaffold will be removed from service immediately by the competent person until such time as it passes inspection.

- Scaffolds will be erected, moved, dismantled, or altered only under the supervision and direction of a competent person.

Training

Recognizing the need for training for employees who perform work while on scaffolds, are involved in erecting, disassembling, moving, operating, repairing, maintaining, or inspecting scaffolds, and have lost the requisite proficiency, the following training syllabus is a part of this written safety plan.

Employees Who Use Scaffolds:

Our employees who perform work on scaffolds will be trained by a qualified person to recognize the hazards associated with the type of scaffold being used and to understand the procedures to control or minimize those hazards. The training will include the following areas as applicable:

- The nature of and the correct procedures for dealing with electrical hazards.
- The nature of and the correct procedures for erecting, maintaining, and disassembling the fall protection and falling object protection systems used.
- The proper use of the scaffold, and the proper handling of materials on the scaffold.
- The maximum intended load and the load-carrying capacities of the scaffolds used.
- Any other pertinent requirements of the OSHA rules.

Employees Who Erect, Disassemble, Move, Operate, Repair, Maintain, or Inspect Scaffolds:

Our employees who erect, disassemble, move, operate, repair, maintain, or inspect scaffolds will be trained by our competent person to recognize the hazards associated with the work being done. The training will include the following topics as applicable:

- The nature of scaffold hazards.
- The correct procedures for erecting, disassembling, moving, operating, repairing, inspecting, and maintaining the type of scaffold in question.
- The design criteria, maximum intended load-carrying capacity, and intended use of the scaffold.
- Any other pertinent requirements of this subpart.

Employees Who Need Retraining:

When we have reason to believe that one of our employees lacks the skill or understanding needed for safe work involving the erection, use or dismantling of scaffolds, we will retrain the employee so that the requisite proficiency is regained. Retraining will be done in at least the following situations:

- Where changes at the worksite present a hazard about which the employee has not been previously trained.
- Where changes in the types of scaffolds, fall protection, falling object protection, or other equipment present a hazard about which an employee has not been previously trained.
- Where inadequacies in an affected employee's work involving scaffolds indicate that the employee has not retained the requisite proficiency.

Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Foremen, and the Safety Manager reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

14.1 Fire Prevention and Emergency Action Plan

14.2 Purpose

OSHA's requires Custom Electric to have a written Emergency Action Plan (EAP) and Fire Prevention Plan (FPP).

The EAP plan applies to all operations in our company where employees may encounter a fire, weather or medical emergency.

Under this plan, our employees will be informed of the plan's purpose, preferred means of reporting fires and other emergencies, types of evacuations to be used in various emergency situations, and the alarm system.

14.3 Plan Coordinator Responsibilities

The Safety Director is the Plan Coordinator has overall responsibility for the plan. The Safety Director will review and update the plan as necessary. The coordinator:

- Develops a written Emergency Response Plan for regular and after-hours work conditions.
- Insures that a procedure is in place to immediately notify the 911 emergency services, in the event of an emergency affecting the job site.
- Distributes procedures for reporting an emergencies, the location of fire exits, and exit routes to each employee.
- Conducts drills to acquaint the employees with evacuation procedures, and to judge their effectiveness.
- Insures that all local fire codes and regulations are satisfied as required.
- Trains designated employees in the use of fire extinguishers and the application of medical first-aid techniques.
- Keeps key management personnel home telephone numbers in a safe place in the facility for immediate use in the event of a fire. Distributes a copy of the list to key persons to be retained in their homes for use in communicating a fire occurring during non-work hours.
- Decides whether to have employees and non-employees remain in or evacuate the facility in the event of an emergency.

14.4 Emergency Reporting and Evacuation Procedure

Preparing for a disaster is a necessity for all companies. Our company philosophy is to provide a healthy and rewarding work environment. Life safety issues concentrate on getting everyone out of the building safely in a controlled manner. It is vital to the success of this plan that it be taken seriously and communicated to all employees.

There are two scenarios likely. One is that the disaster/emergency occurs during working hours when a job site is occupied. The second is that a disaster occurs after working hours when the building is unoccupied.

If the emergency occurs during working hours and an evacuation is deemed necessary, the Plan Coordinator ensures that:

- All employees are notified and evacuated and a head count is taken to confirm

total evacuation of all employees.

- When practical, equipment is placed and locked in storage rooms or desks for protection.

If the disaster/emergency should be after working hours it will be necessary to contact key personnel at their homes to begin communicating the recovery plan for the continuation of business.

14.5 Fire Prevention Plan (FPP)

This Fire Prevention Plan (FPP) is in place at this company to control and reduce the possibility of fire and to specify the type of equipment to use in case of fire. This plan addresses the following issues:

- Major workplace fire hazards and proper handling and storage procedures for hazardous materials.
- Potential ignition sources and their control.
- The type of fire protection equipment necessary to control each major hazard.
- Procedures to control accumulations of flammable and combustible waste materials.
- Procedures for regular maintenance of safeguards installed on heat-producing equipment to prevent the accidental ignition of combustible materials.
- The name of job title of employees responsible for maintaining equipment to prevent or control sources of ignition or fires.
- The name of job title of employees responsible for the control of fuel source hazards.

14.6 Fire Protection Equipment

Fire protection equipment, selected, purchased and in use by this company includes the following extinguishers:

Class A—This common fire involves ordinary materials like wood, paper, rubber, and plastics. The extinguishing agent is water or dry chemicals.

Class B—Flammable liquids, gases, and greases make up this class, and the extinguishing agent is carbon dioxide or dry chemicals.

Class C—This is an electrical fire. Carbon dioxide or dry chemicals extinguish this fire. If you use a fire extinguisher, be sure to use one only on fires for which that fire extinguisher is designed. Using the wrong agent on a fire may increase the intensity of the fire. Check the label on the fire extinguisher; it should list the fire classes it is meant to put out.

There are fire extinguishers located throughout our facilities and at our job sites. Each extinguisher is hung on a bracket and has an identifying sign above.

Instructions for fire extinguisher use:

- a) Hold upright and pull ring pin
- b) Start back 8 feet. Aim at base of fire.
- c) Squeeze lever. Sweep side to side

Fire protection equipment and systems are indicated on the building floor plan in the appendix.

14.7 Maintenance of Equipment/Systems

It is our intent to assure the reliability of fire protection equipment and equipment and systems installed on heat-producing equipment to prevent the accidental ignition of combustible materials. The Facility Manager is responsible for maintaining equipment and systems installed to prevent or control sources of ignition or fires.

Our fire extinguishers require maintenance, testing, and monthly visual inspections by a professional contractor.

14.8 Fire Hazard Prevention

Fire can be represented by a simple equation: Fire = Ignition Source + Fuel + Oxygen. Without any one of these three elements, a fire cannot start. Likewise, during a fire, if you take away any one of these three elements, you can successfully put out a fire. It is our company's intent to prevent these three elements from reacting to produce a fire.

Fuel is used throughout the facility as an energy source for various systems or equipment. This fuel can be a significant fire hazard and must be monitored and controlled. Fire prevention measures involving proper handling and storage of hazardous materials have been developed. These include the proper storage and handling procedures for hazardous materials. During storage, proper venting in the right vessels is of primary concern.

Here is some further storage guidance:

- Stack objects orderly and solidly, and don't overload floors or shelves.
- Keep stacks at or below the recommended distance below sprinklers.
- Store breakable and heavy things on low shelves, and don't place objects so they hang over shelves causing a falling object hazard.
- Don't block fire extinguishers, electrical panels, vents, or exits.
- Keep frequently used things within reach, and return extra stock material.
- Separate flammables and combustibles by their properties.
- Keep corrosives away from flammables.
- Store flammables in approved containers.
- Report leaks of flammables or combustibles.
- Don't eat or smoke around flammables and combustibles.
- PROPERLY dispose of unneeded flammables and combustibles.

14.9 Housekeeping Procedures

Our company controls accumulations of flammable and combustible waste materials and residues so that they do not contribute to a fire.

The following procedures have been developed to eliminate or minimize the risk of fire due to improperly stored or disposed of materials.

- Oil soaked rags must be treated differently than general paper trash and are disposed of in designated oily waste cans only
- House keeping procedures include, but are not limited to, keeping the floors free of paper or saw dust,
- Flammables are stored in approved fire cabinets when not in use.

14.10 Fire Protection Training

The Safety Director provides training for each employee who is required to use fire protection equipment. Employees shall not use fire protection equipment without appropriate training. Custom Electric has chosen to train employees through presentation followed by a periodic tool box talks.

Training, conducted on initial assignment, includes:

- Fire hazards to which an employee is exposed
- What to do if employee discovers a fire
- Demonstration of alarm, if more than one type exists
- How to recognize fire exits
- Types of fire prevention equipment
- Location of fire prevention equipment
- How to use fire prevention equipment
- Limitations of fire prevention equipment
- Proper care and maintenance of assigned fire prevention equipment
- Evacuation routes
- Assisting employees with disabilities
- Measures to contain fire (e.g., closing office doors, windows, etc. in immediate vicinity)
- Head count procedures return to building after the "all-clear" signal

Employees must demonstrate an understanding of the training and the ability to use the equipment properly before they are allowed to perform work requiring the use of the equipment.

14.10 In the Event of Fire

In the event of a fire emergency detected by smoke detectors or a drop in water pressure due to sprinkler activation during working hours the alarms will sound and the strobes will flash. At this time the **Evacuation Plan** will be activated. IT IS IMPERATIVE THAT THE JOBSITE BE EVACUATED IN AN ORDERLY MANNER EACH AND EVERY TIME THE HORNS SOUND AND THE STROBES FLASH. PROCEED TO THE DESIGNATED RALLY POINT AND REMAIN THERE UNTIL INSTRUCTED OTHERWISE.

14.11 Other Potential Emergencies

14.11 a In the Event of a Weather Emergency

The Safety Director has access to the local and National Weather Service. When a severe storm watch or tornado watch has been issued by the National Weather Service, the weather page will sound, followed by a weather bulletin with further information. At that point, the Operations Manager or his designee will determine if the warning affects our site location, and if so, warn employees of the weather emergency.

In the event of a tornado, it is corporate policy to provide emergency warning and

shelter. At the time the tornado warning, all employees are responsible for evacuating to their assigned shelters head counts once evacuation has been completed.

14.11 b In the Event of a Medical Emergency

Rescue and medical aid may be necessary during emergency situations.

If available, needed designated first aid responders are to provide medical assistance within their capabilities to employees requiring it during an emergency situation. Adequate first aid supplies shall be readily available.

Should it become necessary, outside medical help will be requested by calling 911. Professional emergency services responding in an emergency should be met upon their arrival on site and directed to the location of the emergency.

14.12 Enforcement

Constant awareness of and respect for hazardous materials, and compliance with all safety rules are considered conditions of employment. Custom Electric reserves the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

15.1 Forklift Operation Plan

This written Forklift Operation Program establishes guidelines to be followed whenever any of our employees work with powered industrial trucks at this company. The rules established are to be followed to:

- Provide a safe working environment,
- Govern operator use of powered industrial trucks, and
- Ensure proper care and maintenance of powered industrial trucks.

The procedures here establish uniform requirements designed to ensure that powered industrial truck safety training, operation, and maintenance practices are communicated to and understood by the affected employees. These requirements also are designed to ensure that procedures are in place to safeguard the health and safety of all employees.

It is our intent to comply with the requirements of OSHA's 29 CFR 1910.178 as well as 29CFR1926.602. These regulations have detailed requirements for powered industrial truck operator training and for powered industrial truck operations.

15.2 Training

The Safety Director will identify all new employees in the employee orientation program and make arrangements with department management to schedule training.

Before we begin training a new employee, our Safety Director, determines if the potential powered industrial truck operator is capable of performing the duties necessary to be a competent and safe driver. This is based upon his/her physical and mental abilities to perform job functions that are essential to the operation of the vehicle.

These capabilities include the level at which the operator must:

- See and hear within reasonably acceptable limits, (this includes the ability to see at a distance and peripherally, and in certain instances, it is also necessary for the driver to discern different colors, primarily red, yellow, and green);
- Endure the physical demands of the job; and
- Endure the environmental extremes of the job, such as the ability of the person to work in areas of excessive cold or heat. An operator must be able to climb onto and off of a truck, to sit in the vehicle for extended periods of time, and to turn his/her body to look in the direction of travel when driving in reverse.

Once our Safety Director determines that a potential operator is capable of performing powered industrial truck duties, the following initial training and evaluation: will be conducted.

Initial Training

During an operator's initial training, the instructor(s) combine(s) both classroom instruction and practical training. Our classroom instruction includes the following formats:

- Lecture, discussion, videos and written materials.
- Classroom instruction, itself, covers the following topics:

15.1 a TRUCK-RELATED:

- Operating instructions, warnings, and precautions for the types of trucks the operator will be authorized to operate;
- Differences between the truck and automobiles;
- Truck controls and instrumentation: where they are located, what they do, and how they work;
- Engine or motor operation;
- Steering and maneuvering;
- Visibility (including restrictions due to loading);
- Fork and attachment adaptation, operation, and use limitations;
- Vehicle capacity;
- Vehicle stability;
- Any vehicle inspection and maintenance that the operator will be required to perform;
- Refueling and/or charging and recharging of batteries;
- Operating limitations;
- Any other operating instructions, warnings, or precautions listed in the operator's manual for the types of vehicle that the employee is being trained to operate.

15.1 b WORKPLACE-RELATED:

- Surface conditions where the vehicle will be operated;
- Composition of loads to be carried and load stability;
- Load manipulation, stacking, and unstacking;
- Pedestrian traffic in areas where the vehicle will be operated;
- Narrow aisles and other restricted places where the vehicle will be operated;
- Hazardous locations where the vehicle will be operated;
- Ramps and other sloped surfaces that could affect the vehicle's stability.

- Closed environments and other areas where insufficient ventilation or poor vehicle maintenance could cause a buildup of carbon monoxide or diesel exhaust;
- Other unique or potentially hazardous environmental conditions in the workplace that could affect safe operation.

Our practical training includes an operator obstacle course requiring trainees demonstrate their skill and knowledge of the proper operation of the forklift that they anticipate operating in the future.

Each type of powered industrial truck has a different "feel" to it, and that makes operating it slightly different from operating other industrial trucks. The work areas where these trucks are being used also present particular hazards. For these reasons, it is impractical to develop a single "generic" training program that fits all of our powered industrial trucks. Accordingly, during training, Custom Electric covers the operational hazards of our powered industrial trucks, including:

- General hazards that apply to the operation of all or most powered industrial trucks;
- Hazards associated with the particular make and model of the truck;
- Hazards of the workplace in general; and
- Hazards of the particular workplace where the vehicle is operated.

If each potential operator has received training in any of the elements of our training program, and is evaluated to be competent, they need not be retrained in those elements before initial assignment in our workplace. The training must be specific for the types of trucks that employee will be authorized to operate and for the type of workplace in which the trucks will be operated.

Training Certification

After an employee has completed the training program, the instructor will determine whether the potential driver can safely perform the job. At this point, the trainee will take a performance test or practical exercise through which the instructor(s) will decide if the training has been adequate. All powered industrial truck trainees are tested on the equipment they will be driving.

Our Safety Director is responsible for keeping records certifying that each employee who has successfully completed operator training and testing. Each certificate includes the name of the driver, the date(s) of the training, and the name of the person who did the training and evaluation.

Performance Evaluation

Each certified powered industrial truck operator is evaluated at least once every 3 years to verify that the operator has retained and uses the knowledge and skills needed to drive safely. If the evaluation shows that the operator is lacking the appropriate skills and knowledge, the operator is retrained by our instructor(s).

15.2 Refresher Training

Refresher training is triggered by any of the following situations:

- If the operator is involved in an accident or a near-miss incident;
- If the operator has been observed driving the vehicle in an unsafe manner;
- When the operator is assigned to a different type of truck;
- If it has been determined during an evaluation that the operator needs additional training; or
- When there are changes in the workplace that could affect safe operation of the truck. This could include a different type of paving, reconfiguration of the storage racks, new construction leading to narrower aisles, or restricted visibility.

Current Certified Truck Operators

Under no circumstances shall an employee operate a powered industrial truck until he/she has successfully completed this company's powered industrial truck training program. Regardless of claimed previous experience, all new operators must at least undergo a performance evaluation.

Pre-Operational Inspection Procedures

The company requires operators to perform pre-operational equipment checks on powered industrial trucks prior to the beginning of each shift in which those trucks will be utilized to ensure the safe operating condition of the vehicle. The pre-operational check is performed by completing a daily truck inspection checklist.

No blank spaces are allowed on the form. If an item does not apply, we use the code N/A. We also require that operators fill out the comment section thoroughly and accurately if there are any operational or visual defects. That way our Maintenance Department can pinpoint and repair the problem before the truck becomes unsafe to operate.

Our pre-operational inspection procedures used by operators include:

If a completed checklist form is not present on the powered industrial truck, then the truck may not be operated until a checklist is completed.

If the powered industrial truck is safe to operate, the operator must:

1. Place the completed checklist form in the holder provided on the vehicle. The checklist must remain in the vehicle's holder for the duration of the shift. This serves as a visual notice to all area operators that this piece of equipment was inspected at the beginning of the shift and may be used during the shift without another inspection.
2. At the end of the shift, operators must turn the checklist in to the foreman or supervisor.

The manager or supervisor is responsible for reviewing the checklists for accuracy, completeness, and any noted defects.

If the powered industrial truck is unsafe to operate, the operator is to:

1. Remove the key from the powered industrial truck;
2. Place a DANGER DO NOT OPERATE tag on the steering wheel or control lever of the powered industrial truck;
3. Report the problem to his/her immediate supervisor;
4. Not use the truck until the problem has been identified and fixed.

No one else may use the truck until the problem has been identified and fixed.

Appropriate disciplinary action will be enforced for anyone violating this policy.

Periodic Inspection Procedures

Periodic inspections are in conjunction with the particular powered industrial truck's maintenance or service schedule. Maintenance schedules are normally expressed in days and operating or running hours.

The manufacturers' operator instruction manuals contain the recommended maintenance schedule. Authorized workshops and/or service technicians do inspections and maintenance or repair beyond the recommended service schedules.

See an attached sample of our periodic truck inspection checklist.

A supply of these forms is provided in each charging and parking area within user departments. Each department is responsible for retaining all periodic truck inspection checklist forms for each of their department's vehicles.

15.3 Operating Procedures

Powered industrial trucks can create certain hazards that only safe operation can prevent. That's why we have created sets of operating procedures.

Driving

It is our policy for all operators to follow these driving procedures:

- Use only powered industrial trucks approved for the location of use.
- Only start/operate a powered industrial truck from the designated operating location.
- Observe all traffic regulations, including plant speed limits and keeping to the right.
- Yield the right of way to pedestrians and emergency vehicles.
- Maintain safe distances from powered industrial trucks ahead (typically three truck lengths).
- Travel at speeds that will permit vehicles to stop safely at all times, under all road and weather conditions.
- Avoid quick starts/changes of direction.
- Turns must be negotiated by reducing speed and turning the steering wheel with a smooth, sweeping motion.
- Maintain forks in proper position.
- Drive properly in reverse.
- Do not engage in stunt driving and horseplay.
- Drive slowly over wet or slippery floors.
-
- When the forks are empty, travel with the forks at a negative pitch as low to the floor as practical. Adjust the height of the forks to a safe level when the operating terrain warrants.
- When operating a narrow aisle reach truck that is unloaded, do not travel until the forks are fully retracted and positioned at a negative pitch as low to the floor as practical.
- Direct motorized hand trucks into elevators with loads facing forward.
- Do not run over loose objects on roadway surfaces.
- Slow down and sound the horn and look at intersections, corners, and other locations where vision is obstructed.
- Do not pass other trucks traveling in the same direction at intersections, blind spots, or other dangerous locations.
- Maintain a clear view of the direction of travel at all times. Look in direction of travel.
- Keep unauthorized personnel from riding on powered trucks, and provide a safe place to ride where riding on trucks is authorized.
- Keep all body parts within truck.
- Do not allow anyone to place their arms or legs between the uprights of the mast or outside the running lines of the truck.
- Do not drive trucks up to anyone standing in front of a bench or other fixed object.
- A vehicle is considered "unattended" when an operator is 25 feet or more away from a vehicle which remains in view, or whenever an operator leaves a vehicle and it is not in view. Unattended trucks must be secured by: - Fully lowering forks or other attachments (when unloaded, tilt the forks forward first and then lower them to the ground until the tips of the forks come in contact with the ground; - Neutralizing controls; - Shutting off power; and - Setting brakes.
- Secure trucks when dismounted operators are within 25 feet of a vehicle still in

view by: - Fully lowering the load; - Neutralizing controls; and - Setting brakes.

- Be aware of headroom under overhead installations, lights, pipes, door beams, and sprinkler systems.
- Do not block access to fire or emergency exits, stairways, fire equipment, or electrical panels.
- Sound the horn or other audible warning device at all intersections and corners to warn pedestrians.
- Maintain safe distances from the edges of ramps or platforms while on any elevated dock, platform, or freight car.
- Dockboards and bridgeplates must be secured before vehicles cross over them. Be sure they do not exceed rated weight limits.
- When ascending or descending a grade or incline: - Proceed slowly and with caution; - Tilt or raise the forks and attachments only as far as necessary to clear the road surface; and - Sound the horn before ascending or descending.
- Do not park on inclines, ramps, or dock plates. If you must park on an incline, block the wheels.
- Do not use powered industrial trucks for any purpose other than what they were designed.
- Clean up all fluid leaks (oil, hydraulic, transmission, etc.) from the floor.
- Do not operate a powered industrial truck with a leak in the fuel system until the leak has been corrected.
- If the warning device (like a warning lamp or sound-producing device) comes on, stop the truck as soon as possible.
- Follow manufacturer's recommended emergency procedures for fire or tipover and be familiar with manufacturer's emergency equipment.
- Do not modify a powered industrial truck.
- Report all powered industrial truck accidents involving employees, building structures, and equipment to department management.

Load Lifting and Carrying

Powered industrial trucks can lift only so much. Each truck has its own load capacity, which is indicated on the rating plate or lifting chart. Powered industrial trucks also have three-point suspension that forms an imaginary triangle from the left front wheel to the right front wheel to the point between the two back wheels. The center of gravity for a powered industrial truck must lie somewhere within this triangle or else the truck will tip over. The load and its position on the forks, as well as traveling speed and slopes, all affect the center of gravity. Loads, themselves, have gravity with which to contend. Loads need special care so that they do not fall.

In order to prevent tipping and load falling hazards, we have established the following load lifting and carrying procedures:

- Handle loads only within the capacity rating of the truck.
- Use a forking system that suits the load.
- Do not allow anyone to stand or pass under the elevated portion of any truck whether empty or loaded.
- Do not start a powered industrial truck or operate any of its functions or attachments from any position other than from the designated operator's position. * Keep a clear view of the path of travel and look for other traffic, personnel and safe clearances. If the load being carried obstructs forward

view, travel with the load trailing.

- When traveling with a load on the forks, travel with the load as low to the floor as practical with the load tilted back slightly for improved stability.
- When ascending or descending a grade or incline: - Drive with the load positioned upgrade or uphill when the truck is loaded.
- When unloading or loading semi-trailers: - Engage dock lock mechanism and light before entering the trailer. - Check condition of dock leveler plate and trailer floor before entering. - Set the brakes of the semi-tractor. - Chock the rear wheels of the trailer prior to loading or unloading.
- When unloading or loading trailers: secure trailer wheel chocks before entering the trailer. - Check condition of dock leveler plate and trailer floor before entering. - Be sure the semi-tractor is coupled to the trailer, or the fixed jack on the front of the trailer is lowered to the ground to prevent these two trailers from tipping forward. - Set the brakes of the semi-tractor. - Chock the rear wheels of the trailer.
- Use the following backup procedure and sequence: - Pivot at the waist and inspect the area of operation in the rear of the fork truck, watching for obstructions and pedestrians. - Blow the horn to alert any pedestrians that may or may not be visible. - Engage the directional lever to the reverse position. - Concentrate on the removal of the forks from the load to avoid any load disturbance, as you back the fork truck out of the load. - Stop the fork truck 18" to 24" away from the load's resting location and lower the forks to the proper travel height and angle.
- During load placement: - Square the fork truck with the load resting location. - Stop the fork truck 18" to 24" away from the load resting location. - Raise the load to proper entry height. - Drive forward with the load and position the load over its resting location. - Lower the load to a height of 4" if possible. - Tilt the load forward to a level position. - Lower the load to its resting platform. - Back up the unit using proper back up procedures and sequence.
- Do not attempt to move loads with broken pallets.
- During load retrieving: - Tie together unstable loads. - Square the fork truck with the load resting location. - Stop the fork truck 18" to 24" away from the load resting location. - Raise the forks to eye level and level the forks to a horizontal position. - Raise the forks to the proper entry height. - Slide the forks into the load and maintain the clearance around the forks to avoid load disturbance. Be sure to place the heaviest part of the load closest to the backrest. - Raise the load so it is completely suspended from its resting platform. Be sure to support and center the load so that it will not fall forward or sideways. - Tilt the load back. - Visually inspect the rear area of the fork truck to ensure no pedestrians are behind or around the unit. - Back up the unit using proper back up procedures and sequence. - Back up the fork truck 18" to 24" and stop.
- Know the load limits of elevators.
- Whenever a truck is equipped with vertical only, or vertical and horizontal controls elevatable with the lifting carriage or forks for lifting personnel, use these precautions (note: these personnel lifting precautions are no longer required by OSHA, but recommended by ANSI B56.1-1969, American National Standard for Powered Industrial Trucks): - Use a safety platform that is firmly

secured to the lifting carriage and/or forks. - Provide a way for the person on the platform to shut off power to the truck. - Provide protection from falling objects

Fuel Handling and Storage

Some of our powered industrial trucks operate with highly flammable and combustible fuels.

The storage and handling of liquid fuels, including gasoline and diesel fuel are done in accordance with NFPA Flammable and Combustible Liquids Code (NFPA 30-1969). The storage and handling of liquefied petroleum gas fuel is done in accordance with NFPA Storage and Handling of Liquefied Petroleum Gases (NFPA 58-1969).

All employees who handle or use flammable liquids are instructed by our forklift instructors in their safe handling and use and made aware of the specific OSHA requirements for what they are doing with the liquids.

15.3 a More specifically, employees are instructed in the following procedures:

- Never smoke in fueling areas.
- Prevent open flames, sparks, or electric arcs while fueling.
- Never fuel a powered industrial truck while the engine is running.
- Keep solvent waste, oily rags, and flammable liquids (liquids having a flashpoint below 140 deg. F and capable of being easily ignited, burning intensely, or having a rapid rate of flame spread) in fire resistant covered containers until removed from the workplace.
- To change a liquid petroleum (LP) gas tank: - Put on leather work gloves and goggles. - Disconnect powered industrial truck valve from the empty LP cylinder. - Replace with full cylinder. NOTE: The pin on the lift truck must fit into the cut out hole(s) provided on the LP cylinder. This is required by law. - Strap in the cylinder and re-connect the truck valve securely to the cylinder outlet. - Open cylinder valve and listen for leaks. - If leaking, close cylinder valve and slowly uncouple the fuel valve. Try to re-connect. If still leaking, try a different cylinder and notify department management of faulty cylinder. - If no leaks are present, lift truck may be utilized.

Carbon Monoxide Awareness

Powered industrial trucks with internal combustion engines produce carbon monoxide (CO), an odorless, colorless, and deadly gas produced by the incomplete burning of any material that contains carbon. These materials include gasoline, natural gas, propane, coal, and wood. The most common source of CO is the internal combustion engine. Trucks, cars, forklifts, floor polishers, pressure washers, or any other machine powered by fossil fuels generates CO.

If inhaled, CO restricts the ability of your blood system to carry oxygen to the body tissues that need it. Overexposure combined with less oxygen results in carbon monoxide poisoning. Mild poisoning can result in headaches, tightness in the chest,

dizziness, drowsiness, inattention, fatigue, flushed face, or nausea. If you continue exposure lack of coordination, confusion, weakness, or loss of consciousness may result. A heart condition, smoking, taking drugs or alcohol, and pregnancy can aggravate CO poisoning. Physical activity, too, can make a situation worse. That's because your body needs more oxygen to exert itself. Severe poisoning can kill you within minutes, sometimes without warning symptoms. The more CO there is in the air and the longer the exposure, the greater the danger.

Personal Protective Equipment (PPE)

We have assessed our workplace and determined that the hazards which threaten our operators include:

- Injurious gases, vapors, and liquids;
- Dusts or powders, fumes, and mists;
- Flying objects or particles;
- Foot compression or puncture;
- Slipping;
- Extreme heat or cold;
- Hand cuts, punctures, abrasions, and crushing;
- Electricity;
- Materials handling;
- Falling objects;
- Bumping head or other body part against fixed object;
- Noise;
- Falling from an elevated platform attached to the powered industrial truck;
- Falling out of the powered industrial truck;
- Being crushed by a tipped over powered industrial truck.

For this reason, we require that our powered industrial truck operators wear the following PPE and equipment as applicable:

- Safety glasses;
- Goggles;
- Face shields;
- Safety shoes;
- Gloves;
- Protective helmets;
- Warm clothing or suits;
- Body harnesses.

Custom Electric forklift operators are required to use these seatbelts. In the event of an accident, seatbelts reduce the risk of entrapment of the head and torso between the truck and the ground.

15.3b All powered industrial truck operators must:

- Yield the right of way to pedestrians and emergency vehicles.
- Sound the horn or other audible warning device at all intersections and corners to warn pedestrians.
- When backing up pivot at the waist and inspect the area of operation to the

- rear of the powered industrial truck, watching for obstructions and pedestrians and blow the horn to alert any pedestrians that may or may not be visible.
- When retrieving a load and before backing up, visually inspect the rear area of the powered industrial truck to ensure no pedestrians are behind or around the unit.
- Never allow riders on any powered industrial truck.
- Never engage in horseplay.
- Do not allow pedestrians to walk under loads.
- Do not allow anyone to place their arms or legs between the uprights of the mast or outside the running lines of the truck.
- Do not drive trucks up to anyone standing in front of a bench or other fixed object.

15.3 c All pedestrians must:

- Use designated pedestrian walkways.
- Look out for powered industrial trucks and give them the right of way.
- Listen for horns and other warning devices.
- Use any provided mirrors to assist with vision around corners.
- Not walk in front of, behind, or beside a powered industrial truck.
- Never walk or stand under a raised load.
- Never hitch a ride on a powered industrial truck.

15.4 Maintenance

Investing time and effort into the proper upkeep of our equipment results in day-to-day reliability. Keeping up with the manufacturer's recommended maintenance and lubrication schedules, and completing the proper records, will also increase our trucks' longevity and enhance its resale value.

We follow the manufacturer's operator instruction manual for daily or weekly maintenance. Periodic maintenance (those completed monthly, every 6 months, or annually) is done by a factory-trained expert or a dealer.

15.5 Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

16.1 Flammable and Combustible Liquids Compliance Program

This Flammable & Combustible Liquids Compliance Program has been written to protect employees who handle, store, and use or work around flammable and combustible liquids subject to the OSHA Flammable & Combustible Liquids Standard, 29 CFR 1910.106. We intend for the information here to facilitate proper design, installation, storage, usage, and handling measures necessary to prevent fire and explosion.

16.2 Administrative Duties

Our company's Safety Director is responsible for developing and maintaining the written Flammable & Combustible Liquids Compliance Program. The Safety Director is responsible for all facets of the program and has full authority to make necessary decisions to ensure the program's success.

16.3 Control

Measures 16.2a

Work Practice

Controls

We require our employees to take the following work practice control measures to reduce employee injury and illness:

- Do not permit open flames and smoking in flammable or combustible liquid storage areas.
- Only dispense flammable and combustible liquids from containers over 30 gallons by approved pump or self-closing faucet.
- Use only approved containers and portable tanks. Metal containers and portable tanks meeting the requirements of and containing products authorized by Chapter I, Title 49 of the Code of Federal Regulations (regulations issued by the Hazardous Materials Regulations Board, Department of Transportation), shall be deemed to be acceptable.
- Take adequate precautions to prevent the ignition of flammable vapors. Sources of ignition include, but are not limited to: open flames; lightning; smoking; cutting and welding; hot surfaces; frictional heat; static, electrical, and mechanical sparks; spontaneous ignition, including heat-producing chemical reactions; and radiant heat.
- Keep aisles adequate and unobstructed so that personnel and fire protection equipment can reach flammable or combustible liquid use, handling, and storage areas.
- Provide means to dispose promptly and safely of leakage or spills where flammable or combustible liquids are used or handled, except in closed containers.
- Use class I liquids only where there are no open flames or other sources of ignition within the possible path of vapor travel.
- Do not dispense class I liquids into containers unless the nozzle and container are electrically interconnected.

16.2b Inside a building:

- Do not store flammable or combustible liquids, so as to limit use of exits, stairways, or areas used for egress of people.
- Do not store flammable or combustible liquids in office occupancies, except if required for maintenance and operation of a building and/or equipment. Such storage must be kept in

closed metal containers inside a storage cabinet or safety cans or in an inside storage room not having a door that opens into that portion of the building used by the public.

- Remove leaking containers from buildings and take them to a safe location outside the building and transfer the contents to an undamaged container.
- Store flammable or combustible liquids according to Table H-14 or H-15 in general purpose public warehouses or in portions of such buildings cut off by standard firewalls. Do not store material that creates a fire hazard to the flammable or combustible liquids in the same area.
- Arrange storage according to Table H-14 or H-15. The total quantity of liquids within a liquid storage building is not restricted, but must meet the arrangements of H-14 and H-15.
- Keep combustible waste material and residues in a building or unit operating area to a minimum. Store it in covered metal receptacles and dispose of daily.

16.2 c Inside storage rooms:

- Store flammable and combustible liquids according to Table H-13.
- Maintain one clear aisle at least 3 feet wide.
- Do not stack containers that are over 30 gallons capacity.

16.3 Protective Equipment

All protective equipment, including personal protective equipment (PPE), used at this facility will be provided without cost to employees. Protective equipment will be chosen based on anticipated hazards and will be provided to employees.

16.4 Storage Procedures

Maintenance Procedures

Our maintenance and operating procedures control leakage and prevent accidental escape of flammable or combustible liquids. Spills are cleaned up promptly.

We permit hot work, such as welding or cutting operations, use of spark-producing power tools, and chipping operations, only under supervision of an individual in responsible charge.

All plant fire protection facilities shall be adequately maintained to make sure they are always in satisfactory operating condition, and they will serve their purpose in time of emergency.

16.5 Emergency Situations

Please refer to the **Fire Prevention and Emergency Action Plan.**

16.6 Training

Under no circumstances may an employee use, handle, or store flammable or combustible liquids until he/she has successfully completed this company's training program under the Flammable & Combustible Liquids Compliance Program. This includes all new employees, regardless of claimed previous experience.

The Flammable & Combustible Liquids Compliance Program Administrator will identify new trainees and those existing employees who need retraining.

When an employee has an accident or near miss or some unsafe operating procedure is identified, we retrain that employee. In some cases, it may be necessary to take disciplinary action.

16.7 Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

17.1 Hand Tool and Portable Power Tools

17.2 General

Custom Electric shall ensure that all hand tools are used properly, safely and in accordance with all manufacturers' guidelines.

17.3 Responsibilities

Custom Electric Safety Director is responsible for:

- Assisting supervisors in identifying hazardous conditions in regards to hand/power tools;
- Inspecting areas to ensure that this policy is being adhered to; and
- Providing safety awareness training, as needed.

Supervisors are responsible for:

- Anticipating all work hazards;
- Ensuring that all safeguards are utilized;
- Replacing all damaged tools;
- Ensuring that tools are being properly maintained by instituting an inspection program; and
- Ensuring employees are trained to use tools properly and in accordance with the manufacturer's instructions;

Employees are responsible for:

- Anticipating all work hazards;
- Ensuring that all safeguards are utilized;
- Conducting routine inspections to ensure that tools are properly maintained;
- Reporting to their supervisor any tool that needs to be replaced;
- Following all safety guidelines for the use of hand/power tools and according to manufacturer's instructions;

Participating in training provided by the company

17.4 General Safety Precautions

Employees who use hand and power tools and who are exposed to the hazards of falling, flying, abrasive and splashing objects, or exposed to harmful dusts, fumes, mists, vapors, or gases must be provided with the appropriate equipment needed, including Personal Protective Equipment, to protect them from the hazard.

All hazards involved in the use of power tools can be prevented by following some basic safety rules:

- Keep all tools in good condition with regular maintenance;
- Use the right tool for the job;
- Examine each tool for damage before use;
- Operate according to the manufacturer's instructions;
- Utilize the proper protective equipment (refer to Personal Protective Equipment Policy)

17.5 Hand Tools

Hand tools are non-powered. They include anything from axes to wrenches. The greatest hazards posed by hand tools result from misuse and improper maintenance.

Some examples of misuse include the following:

- Turn off the power when not in use; and
- Never clamp a hand-held grinder in a vise.

17.6 Pneumatic Tools

Pneumatic tools are powered by compressed air and include chippers, drills, hammers, and sanders.

There are several dangers encountered in the use of pneumatic tools. The main one is the danger of getting hit by one of the tool's attachments or by some kind of fastener the worker is using with the tool.

Eye protection is required and face protection is recommended for employees working with pneumatic tools. When sanders are used, dust masks shall also be worn.

Noise is another hazard. Working with noisy tools (e.g. jackhammers) requires proper, effective use of hearing protection.

When using pneumatic tools, employees shall ensure they are fastened securely to the hose to prevent them from becoming disconnected. A short wire or positive locking device attaching the air hose to the tool will serve as an added safeguard.

A safety clip or retainer shall be installed to prevent attachments, such as chisels on a chipping hammer, from being unintentionally shot from the barrel.

Screens shall be set up to protect nearby workers from being struck by flying fragments around chippers, riveting guns, staplers or air drills.

Compressed air guns shall never be pointed toward anyone. Users shall never "dead-end" it against themselves or anyone else.

17.7 Powder-Actuated Tools

Powder-actuated tools operate like a loaded gun and shall be treated with the same respect and precautions. The use of powder-actuated tools is prohibited until approved by our Safety Director.

Safety precautions to remember include the following:

- These tools shall not be used in an explosive or flammable atmosphere;
- Before using the tool, the worker shall inspect it to determine that it is clean, all moving parts operate freely, and the barrel is free from obstructions;
- Employees shall not modify tools;
- The tool shall never be pointed at anybody;
- The tool shall not be loaded unless it is to be used immediately. A loaded tool shall not be left unattended, especially where it could be available to unauthorized persons;
- Hands shall be kept clear of the barrel end;
- To prevent the tool from firing accidentally, two separate motions are required for firing: one to bring the tool into position and another to pull the trigger;
- The tools shall not be able to operate until they are pressed against the work surface with a force of at least five pounds greater than the total weight of the tool;

- If a powder-actuated tool misfires, the employee shall wait at least 30 seconds, then try firing it again;
- If it still will not fire, the user shall wait another 30 seconds so that the faulty cartridge is less likely to explode then carefully remove the load. The bad cartridge shall be put in water;
- Suitable eye and face protection are essential when using a powder-actuated tool;
- The muzzle end of the tool shall have a protective shield or guard centered perpendicularly on the barrel to confine any flying fragments or particles that might otherwise create a hazard when the tool is fired. The tool shall be designed so that it will not fire unless it has this kind of safety device;

- All powder-actuated tools shall be designed for varying powder charges so that the user can select a powder level necessary to do the work without excessive force; and

If the tool develops a defect during use, it shall be tagged and taken out of service immediately until it is properly repaired.

17.8 Enforcement

Constant awareness of and respect for hazardous materials, and compliance with all safety rules are considered conditions of employment. Custom Electric reserves the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

18.1 Hazard Communication Program

18.2 Purpose

The purpose of this program is to inform interested persons, including employees, that Custom Electric is complying with the OSHA Hazard Communication Standard, Title 29 Code of Federal Regulations 1910.1200, by compiling a hazardous chemicals list, by using safety data sheets (SDS), by ensuring that containers are labeled, and by providing our employees with training and information availability.

This program applies to all work operations in our company where employees may be exposed to hazardous substances under normal working conditions or during an emergency situation.

Our Safety Director has overall responsibility for the program. He will review and update the program, as necessary.

All employees, or their designated representatives, can obtain further information on this written program, the hazard communication standard, applicable SDS, and chemical information lists from our Safety Director. Under this program, our employees will be informed of the contents of the Hazard Communication Standard, the hazardous properties of chemicals with which they work, safe handling procedures, and measures to take to protect themselves from these chemicals.

18.3 Hazard Evaluation Procedures

Our chemical inventory is a list of hazardous chemicals known to be present in our various workplaces. Anyone who comes into contact with the hazardous chemicals on the list needs to know what those chemicals are and how to protect him or herself. That is why it is so important that hazardous chemicals are identified, whether they are found in a container or generated in work operations (for example, welding fumes, dusts, and exhaust fumes). The hazardous chemicals on the list can cover a variety of physical forms including liquids, solids, gases, vapors, fumes, and mists. Sometimes hazardous chemicals can be identified using purchase orders.

Identification of others requires an actual inventory of the facility. After the chemical inventory is compiled, it serves as a list of every chemical for which an SDS must be maintained. The Safety Director updates the chemical inventory as necessary. Our company does not manufacture any chemicals and, therefore, does not make any hazard determinations.

18.4 Safety Data Sheets (SDS)

The SDS we use are fact sheets for chemicals that pose a physical or health hazard in the workplace. SDS provide our employees with specific information on the chemicals they use.

Our Safety Director is responsible for obtaining/maintaining the SDS for our facilities and worksites. He or She will contact the chemical manufacturer or vendor if additional research is necessary. A member of management must clear all new chemical procurements for the company.

The safety data sheets are kept at the Main office as well as at each of our jobsites.

18.5 Labels and Other Forms of Warning

All chemical product containers shall be appropriately labeled. Labels list at least the chemical identity, appropriate hazard warnings, and the name and address of the manufacturer, importer or other responsible party. The chemical identity is found on the label, the SDS, and the chemical inventory. Therefore, the chemical identity links these three sources of information. The chemical identity used by

the supplier may be a common or trade name, or a chemical name. The hazard warning is a brief statement of the hazardous effects of the chemical (i.e., "warning", danger") Labels frequently contain other information, such as pictograms (i.e., "flammable"), as well as additional information as provided by the product manufacturer. Our labels are legible and prominently displayed, though their sizes and colors can vary.

The Safety Director is responsible for ensuring that all hazardous chemicals are properly labeled and updated, as necessary. The Safety Director also ensures that newly purchased materials are checked for labels prior to use.

18.6 Training

Everyone who works with or is potentially "exposed" to hazardous chemicals will receive initial training and any necessary retraining on the Hazard Communication Standard and the safe use of those hazardous chemicals. "Exposure" means "an employee is subjected to a hazardous chemical in the course of employment through any route of entry (inhalation, ingestion, skin contact or absorption, etc.) and includes potential (e.g., accidental or possible) exposure." Whenever a new hazard is introduced or an old hazard changes, additional training is provided.

Information and training is a critical part of the hazard communication program. All employees receive training for hazard communication. We train our employees to read and understand the information on labels and SDS, determine how the information can be obtained and used in their own work areas, and understand the risks of exposure to the chemicals in their work areas as well as the ways to protect them.

Our goal is to ensure employee comprehension and understanding including being aware that they are exposed to hazardous chemicals, knowing how to read and use labels and SDS, and appropriately following the protective measures we have established. As part of the assessment of the training program, our trainer asks for input from employees regarding the training they have received, and their suggestions for improving it. In this way, we hope to reduce any incidence of chemical source illnesses and injuries.

Training Content

The training program emphasizes these elements:

- Summary of the standard and this written program, including what hazardous chemicals are present, the labeling system used, and access to SDS information and what it means.
- Chemical and physical properties of hazardous materials (e.g., flash point, reactivity) and methods that can be used to detect the presence or release of chemicals (including chemicals in unlabeled pipes).
- Physical hazards of chemicals (e.g., potential for fire, explosion, etc.).
- Health hazards, including signs and symptoms of exposure, associated with exposure to chemicals and any medical condition known to be aggravated by exposure to the chemical.
- Procedures to protect against hazards (e.g., engineering controls; work practices or methods to assure proper use and handling of chemicals; personal protective equipment required, and its proper use, and maintenance; and procedures for reporting chemical emergencies).

Certificates of completion are signed by employees upon completion of their training and are kept by the Safety Director.

18.7 Contractors

Each contractor bringing chemicals on-site must provide our Safety Director with the appropriate hazard information on these substances, including the SDS, the labels used and the precautionary measures to be taken in working with these chemicals.

18.8 Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

19.1 Personal Protective Equipment (PPE) Program

19.2 Purpose

While OSHA's Personal Protective Equipment regulation does not explicitly require a written Personal Protective Equipment (PPE) Program, Custom Electric has developed a written PPE program to document and specify all information relative to our PPE needs.

The Safety Director has overall responsibility for the program. The Safety Director will designate appropriate supervisors to assist in training employees and monitoring their use of PPE. This written plan is kept in at the main office. The Safety Director will review and update the program as necessary.

Here at Custom Electric we believe it is our obligation to provide a hazard free environment to our employees. Any employee encountering hazardous conditions must be protected against the potential hazards. The purpose of protective clothing and equipment (PPE) is to shield or isolate individuals from hazards that may be present in the workplace.

Establishing an overall written PPE program detailing how employees use PPE makes it easier to ensure that they use PPE properly in the workplace and document our PPE efforts in the event of an OSHA inspection.

Custom Electric's PPE program covers:

- Purpose
- Hazard assessment
- PPE selection
- Employee training
- Cleaning and maintenance of PPE
- PPE specific information

19.3 Purpose of Program

The basic element of any PPE program is an in depth evaluation of the equipment needed to protect against the hazards at the workplace; this is the initial hazard assessment for which written documentation is required. Two basic objectives of any PPE program should be to protect the wearer from incorrect use and/or malfunction of PPE. The purpose of this Personal Protective Equipment (PPE) Program is to document the hazard assessment, protective measures in place, and PPE in use at this company. PPE devices are not to be relied on as the only means to provide protection against hazards, but are used in conjunction with guards, engineering controls, and sound manufacturing practices. If possible, hazards will be abated first through engineering controls, with PPE to provide protection against hazards that cannot reasonably be abated otherwise.

19.4 Hazard Assessment

In order to assess the need for PPE the following steps are taken:

1. The Safety Director, with other appropriate employees, identifies job classifications where exposures occur or could occur. The Safety Director examines the following records to identify and rank jobs

according to exposure hazards:

- Injury/illness records
- First aid logs

2. The Safety Director periodically conducts a walk through survey of workplace areas where hazards exist or may exist to identify sources of hazards to employees. He considers these basic hazard categories:

- Impact
- Heat
- Electrical Contact
- Penetration
- Harmful dust
- Compression (roll over)
- Chemical

During the walk through survey the Safety Director observes and records the following hazards along with PPE currently in use:

- Sources of motion; i.e., machinery or processes where any movement of tools, machine elements or particles could exist, or movement of personnel that could result in collision with stationary objects
- Sources of falling objects or potential for dropping objects
- Sources of sharp objects that might pierce the feet or cut the hands
- Layout of workplace and location of co-workers:
- Electrical hazards.

3. Following the walk through survey, the Safety director organizes the data and information for use in the assessment of hazards to analyze the hazards and enable proper selection of protective equipment.

4. An estimate of the potential for injuries is now made. Each of the basic hazards is reviewed and a determination made as to the frequency, type, level of risk, and seriousness of potential injury from each of the hazards found. The existence of any situations where multiple exposures occur or could occur is considered.

5. The Safety Director documents the hazard assessment via a written certification that identifies the workplace evaluated, the person certifying that the evaluation has been performed, the date(s) of the hazard assessment, and that the document is a certification of hazard assessment.

19.5 Selection Guidelines

Once any hazards have been identified and evaluated through hazard assessment, the general procedure for selecting protective equipment is to:

1. Become familiar with the potential hazards and the type of protective equipment (PPE) that are available, and what they can do.
2. Compare types of equipment to the hazards associated with the environment.
3. Select the PPE that ensures a level of protection greater than the minimum required to protect employees from the hazards.
4. Fit the user with proper, comfortable, well fitting protection and instruct employees on care and use of the PPE. It is very important that the users are aware of all warning labels for and limitations of their PPE.

It is the responsibility of the Safety Director to reassess the workplace hazard situation as necessary, to identify and evaluate new equipment and processes, to review accident records, and reevaluate the suitability of previously selected PPE. This reassessment will take place as needed, but at least annually.

Elements that should be considered in the reassessment include:

- Adequacy of PPE program
- Accidents and illness experience
- Levels of exposure (this implies appropriate exposure monitoring)
- Adequacy of equipment selection
- Adequacy of training/fitting of PPE
- Program costs
- Adequacy of program records
- Recommendation for program improvement and modification
- Coordination with overall safety and health program

19.6 Employee Training

The Safety Director and supervisors provide training for each employee who is required to use personal protective equipment. Training includes:

- When PPE is necessary
- What PPE is necessary

- How to wear assigned PPE
- Limitations of PPE
- Proper care, maintenance, useful life, and disposal of assigned PPE

Employees must demonstrate an understanding of the training and the ability to use the PPE properly before they are allowed to perform work requiring the use of the equipment.

Employees are prohibited from performing work without donning appropriate PPE to protect them from the hazards they will encounter in the course of that work.

If the Safety Director has reason to believe an employee does not have the understanding or skill required, the employer must retrain. Since an employee's supervisor is in the best position to observe any problems with PPE use by individual employees, the Safety Director will seek this person's input when making this determination. Circumstances where retraining may be required include changes in the workplace or changes in the types of PPE to be used, which would render previous training obsolete. Also, inadequacies in an affected employee's knowledge or use of the assigned PPE, which indicates that the employee has not retained the necessary understanding or skills, would require retraining.

The Safety Director certifies in writing that the employee has received and understands the PPE training.

Because failure to comply with company policy concerning PPE can result in OSHA citations and fines as well as employee injury, an employee who does not comply with this program will be disciplined for noncompliance according to the following schedule:

1. Verbal warning for the first offense accompanied by retraining
2. Written reprimand for the second offense that goes in the employee's permanent record
3. Suspension without pay for a third offense and documentation in the permanent record
4. Dismissal as a last resort.

19.7 Cleaning and Maintenance

It is important that all PPE be kept clean and properly maintained by the employee to whom it is assigned. Cleaning is particularly important for eye and face protection where dirty or fogged lenses could impair vision. PPE is to be inspected, cleaned, and maintained by employees at regular intervals as part of their normal job duties so that the PPE provides the requisite protection. Supervisors are responsible for ensuring compliance with cleaning responsibilities by employees. If PPE is for general use, the Safety Director has responsibility for cleaning and maintenance. If a piece of PPE is in need of repair or replacement it is the responsibility of the employee to bring it to the immediate attention of his or her supervisor or the Safety Director. It is against work rules to use PPE that is in disrepair or not able to perform its intended function. Contaminated PPE that cannot be decontaminated is disposed of in a manner that protects employees from exposure to hazards.

19.8 PPE Specific

Information 19.7a Eye

and face protection

It is the policy of the company that as a condition of employment, all regular full time, part time, and temporary employees working in designated work areas and/or job assignments are required to wear ANSI approved eye/face protection to help prevent eye and face injuries, including those resulting from flying particles, liquid chemicals, acids or caustic liquids, chemical gases or vapors, for example.

Employees from contractors are required to wear eye/face protection if assigned to work in designated work areas.

All supervisors and foremen are responsible for ensuring employees under their charge are in compliance with this policy.

All employees who work in designated work areas and/or job assignments are responsible for wearing company provided eye/face protection to comply with this policy. Failure to comply will result in disciplinary action up to and including discharge.

All employees required to wear eye/face protection must routinely inspect and properly care for their goggles/face shields.

19.7b Foot Protection-Safety Shoes

It is the policy of the company that as a condition of employment, all regular full time, part time, and temporary employees working in designated work areas and/or job assignments are required to wear proper shoes to help prevent foot injuries, ankle injuries, slips, and falls.

Employees of contractors are required to wear proper shoes if assigned to work in the designated work areas. It is the responsibility of the contractor to ensure the employee reports to his/her assignment at this company wearing approved safety shoes.

The Human Resource Department is responsible for informing new employees who are assigned to the designated work areas of the safety shoe policy and the procedures for obtaining them. The new employee is responsible for reporting to his/her first day of work wearing approved safety shoes.

19.7c Hand Protection -- Gloves

It is the policy of the company that as a condition of employment, all regular full time, part time, and temporary employees working in designated work areas and/or job assignments are required to wear gloves to help prevent hand injuries, including cuts, burns, chemical exposure, for example.

Employees of contractors are required to wear protective gloves if assigned to work in the designated work areas.

All supervisors are responsible for ensuring employees under their charge are in compliance with this policy.

All employees who work in designated work areas and/or job assignments are responsible for wearing company provided gloves to comply with this policy. Failure to comply will result in disciplinary action up to and including discharge.

All employees required to wear protective gloves must routinely inspect and properly care for their assigned gloves (if the gloves are not disposable).

19.7d Head protection -- Hard hats

It is the policy of the company that as a condition of employment, all regular full time, part time, and temporary employees working in designated work areas and/or job assignments are required to wear ANSI approved hard hats to help prevent head injuries, including those resulting from falling objects, bumping the head against a fixed object, or electrical shock.

Employees of contractors are required to wear hard hats if assigned to work in the designated work areas. All supervisors are responsible for ensuring employees under their charge are in compliance with this policy.

All employees who work in designated work areas and/or job assignments are responsible for wearing company provided hard hats to comply with this policy. Failure to comply will result in disciplinary action up to and including discharge.

All employees required to wear hard hats must routinely inspect and properly care for their hard hats.

19.7e Ear protection

It is the policy of Custom Electric that as a condition of employment, all regular full time, part time, and temporary employees working in designated work areas and/or job assignments are required to wear ANSI approved hearing protective devices to help prevent hearing loss, including loss resulting from the use of loud (85dba+) power equipment. Hearing Protection is provided free of charge to all employees who work in areas where the noise levels exceed 85dba. Hearing Protection is evaluated for the specific area of exposure in which it will be used, and appropriate hearing protection will be provided as such.

Custom Electric will evaluate the noise levels emitted by the powered operating equipment used at our facility and at our customer locations. All reasonable efforts to minimize noise output will be taken. Noise levels that exceed the OSHA Permissible Exposure Limit (PEL) will require the implementation of a Hearing Conservation Program which will include annual Audiometric testing and the use of noise protection PPE by our employees. As required, a baseline audiogram will be established within the first 6 months of employment for affected employees. If the baseline test is necessary, we will ensure the affected employee is not exposed to the standard workplace noise levels for a minimum period of at least 14 hours. Employees are notified in writing within 21 days if audiograms indicate a standard threshold shift (STS). Should it become necessary as a result of a STS to re-evaluate an employees hearing protection, this will be undertaken promptly.

All records related to audiometric testing are maintained at the company headquarters for the duration of the employee's employment plus 30 years.

All employees will be trained prior to the distribution of noise protection PPE as to the proper use, maintenance and effectiveness of the hearing protection device

All supervisors and managers are responsible for ensuring employees under their charge are in compliance with this policy.

All employees shall receive annual training in the use and application of hearing protection. The retaining shall include the proper application of the hearing protectors, maintenance of the protectors, and the limitations of the protectors.

19.8 Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

20.1 Scaffolding Safety

20.2 Purpose

It is Custom Electric's purpose in issuing these procedures to further ensure a safe workplace based on the following formal, written procedures for scaffold work. These procedures will be reviewed and updated as needed to comply with new OSHA regulations, new best practices in scaffolding, and as business practices demand.

This general scaffold plan applies to all work sites where our company may utilize scaffolding systems.

20.3 Capacity

Taking into account the OSHA rules we must apply and the engineering/manufacturing requirements of our scaffolds, the following rules apply. Each scaffold and scaffold component we use will support, without failure, its own weight and at least four times the maximum intended load applied or transmitted to it.

20.4 Platform Construction

This section documents the procedures and safety requirements we use to construct our fabricated frame supported scaffold platforms.

The following safety rules apply for this scaffold platform construction:

- Each scaffold plank or platform will be installed so that the space between adjacent planks and the space between the platform and uprights is no more than one inch wide.
- Except for outrigger scaffolds (3 inches) and plastering and lathing operations (18 inches), the front edge of all platforms will not be more than 14 inches from the face of the work, unless we have a guardrail or personal fall arrest system in place that meets regulations.
- Supported scaffolds with a height to base width ratio of more than four to one (4:1) must be restrained from tipping by guying, tying, bracing, or equivalent means.
- Supported scaffold poles, legs, posts, frames, and uprights will always bear on base plates and mud sills or other adequate firm foundations.
- We provide fall prevention or protection for any employee on a scaffold more than 10 feet above a lower level.

20.5 Gaining Access to Scaffolds

We know that getting to the working platform is critical to the safety of our employees. This section outlines the mechanical requirements for gaining access to scaffold platforms such as ladders, ramps and walkways, stair rails and direct access from another scaffold. This section is divided into two parts. The first part is for workers gaining access to scaffold platforms to do work; the second part is access for employees erecting and dismantling scaffolds.

Working Employees:

- Portable, hook-on, and attachable ladders will be positioned so as not to tip the scaffold. The top

of the ladder will extend 36 inches beyond the work surface being accessed and the ladder will be secured in place.

- All stair rail systems and handrails will be surfaced to prevent injury to our employees from punctures or lacerations, and to prevent snagging of their clothes.

Erectors and Dismantlers:

20.6 Fall Protection Plan

Fall protection planning is critical to the safety and well being of our employees.

Our fall protection plan follows the OSHA requirements that are different depending on the type of scaffold we are using. In this plan we address fall protection for our self-contained adjustable scaffold supported by the frame structure. We provide fall prevention or protection for any employee erecting a scaffold more than 10 feet above a lower level if there is not an installed handrail as detailed below.

We also protect each employee on our self-contained, frame structure supported, adjustable scaffolds by a guardrail system. The guardrail system:

- Has a minimum 200 pound top rail capacity
- Will be installed before being released for use by our employees.

20.7 Falling Object Protection

All employees must wear hardhats when working on, assembling, or dismantling scaffolds. This is our primary protection from falling objects. Additionally, we will:

- Install all guardrail systems with openings small enough to prevent passage of potential falling objects.
- Prevent tools, materials, or equipment that inadvertently fell from our scaffolds from striking employees by barricading the area below the scaffold.

20.8 Using Scaffolds

Site preparation, scaffold erection, fall protection, and gaining access to the working platform are only part of the requirements for scaffold work. While this all takes concentration and safe work practices, the most dangerous time can be when employees are concentrating on their work and not particularly aware of the hazards of working from scaffolds. It is critical that employees who use scaffolds be trained, among other things, in the recognition of the hazards associated with the type of scaffold being used and to understand the procedures to control or minimize those hazards. Our competent person will inspect all scaffolds and scaffold components for visible defects before each work shift, and after any occurrence that could affect a scaffold's structural integrity. However, in addition to that, all users of scaffolds in this company will know and understand the following safety rules:

- Scaffolds and scaffold components will never be loaded in excess of their maximum intended loads or rated capacities.
- Debris must not be allowed to accumulate on platforms.

20.9 Prohibited Practices

The following practices will never be tolerated in this company:

- Scaffold components manufactured by different manufacturers will never be intermixed unless the components fit together without force and the scaffold's structural integrity is maintained.
- Unstable objects will never be used to support scaffolds or platform units. Footings must be level, sound, rigid, and capable of supporting the loaded scaffold without settling or displacement.
- Cross braces will never be used as a means of access.
- The use of shore or lean-to scaffolds is prohibited.

20.10 Aerial Lifts

Anytime aerial lifts, including:

- (1) Extensible boom platforms,
- (2) Aerial ladders,
- (3) Articulating boom platforms,
- (4) Vertical towers, or
- (5) A combination of any such devices, are used to elevate employees to job-sites above ground, the following safety rules will apply:

No aerial lift this company owns or uses will be 'field modified' for uses other than those intended by the manufacturer unless the manufacturer certifies the modification in writing, or any other equivalent entity, such as a nationally recognized testing lab, certifies the aerial lift modification conforms to all applicable provisions of ANSI A92.2-1969, and the OSHA rules at 1926.453. The lift must be at least as safe as the equipment was before modification.

20.11 Extensible and articulating boom platforms:

- We will test lift controls each day prior to use to determine they are in safe working condition.
- Only authorized employees can operate an aerial lift.
- A full body harness must be worn and a retractable lanyard attached to the boom or basket as specified by the equipment manufacturer when working from an aerial lift.

20.12 Duties of Competent and Qualified Persons

When working with scaffolds in this company there are some tasks that must be done by our competent or a qualified person. By definition they are:

- Competent Person-One who is capable of identifying existing and predictable hazards in the surroundings or working conditions which are unsanitary, hazardous, or dangerous to employees, and who has authorization to take prompt corrective measures to eliminate them.
- Qualified Person-One who, by possession of a recognized degree, certificate, or professional standing, or who by extensive knowledge, training and experience, has successfully demonstrated his/her ability to solve or resolve problems related to the subject matter, the work, or the project. The following tasks will only be done by the person we have deemed competent or qualified to perform.

Competent Person:

We will not intermix scaffold components manufactured by different manufacturers unless the components fit together without force and the scaffold's structural integrity is maintained. Scaffold components manufactured by different manufacturers will not be modified in order to intermix them unless our competent person determines the resulting scaffold is structurally sound.

- Prior to each work shift, at anytime during the work shift when the scaffold appears to have been moved or damaged, and after every weather event which could affect the scaffolds structural integrity, all scaffolds will be inspected by our competent person. If a scaffold is determined to be unsafe as a result of this inspection, the scaffold will be removed from service immediately by the competent person until such time as it passes inspection.
- Scaffolds will be erected, moved, dismantled, or altered only under the supervision and direction of a competent person.

20.13 Training

Recognizing the need for training for employees who perform work while on scaffolds, are involved in erecting, disassembling, moving, operating, repairing, maintaining, or inspecting scaffolds, and have lost the requisite proficiency, the following training syllabus is a part of this written safety plan.

Employees Who Use Scaffolds:

Our employees who perform work on scaffolds will be trained by a qualified person to recognize the hazards associated with the type of scaffold being used and to understand the procedures to control or minimize those hazards. The training will include the following areas as applicable:

- The nature of and the correct procedures for dealing with electrical hazards.
- The nature of and the correct procedures for erecting, maintaining, and disassembling the fall protection and falling object protection systems used.
- The proper use of the scaffold, and the proper handling of materials on the scaffold.
- The maximum intended load and the load-carrying capacities of the scaffolds used.
- Any other pertinent requirements of the OSHA rules.

Employees Who Erect, Disassemble, Move, Operate, Repair, Maintain, or Inspect Scaffolds:

Our employees who erect, disassemble, move, operate, repair, maintain, or inspect scaffolds will be trained by our competent person to recognize the hazards associated with the work being done. The training will include the following topics as applicable:

- The nature of scaffold hazards.
- The correct procedures for erecting, disassembling, moving, operating, repairing, inspecting, and maintaining the type of scaffold in question.
- The design criteria, maximum intended load-carrying capacity, and intended use of the scaffold.
- Any other pertinent requirements of this subpart.

Employees Who Need Retraining:

When we have reason to believe that one of our employees lacks the skill or understanding needed for safe work involving the erection, use or dismantling of scaffolds, we will retrain the employee so that the requisite proficiency is regained. Retraining will be done in at least the following situations:

- Where changes at the worksite present a hazard about which the employee has not been previously trained.
- Where changes in the types of scaffolds, fall protection, falling object protection, or other equipment present a hazard about which an employee has not been previously trained.
- Where inadequacies in an affected employee's work involving scaffolds indicate that the employee has not retained the requisite proficiency.

20.14 Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

21.1 Trenching and Excavations

21.2 Purpose

The purpose of this policy is to outline the procedures established in order to effectively administer Custom Electric guidelines regarding employee safety requirements when working in or around trenches and excavations. Custom Electric undertakes all practical steps to safeguard employees, contractors, and the general public from accidents and personal injuries related to these environments.

It is also Custom Electric's intention to comply with all applicable regulations including, but not limited to, OSHA's 29CFR Part 126, Subpart P, 650, .651 and .652, including appendices A, B, C, D

21.3 Responsibilities

Assigned company supervisors or foreman are responsible for insuring all employees under their direction receive the appropriate level of training for the trenching and excavation tasks they are expected to perform. All training sessions shall be documented.

Supervisors are responsible for insuring each employee receives the appropriate level of personal protection equipment prior to job assignment.

Supervisors shall enforce safe work practices and procedures, including the use of safety equipment as required.

Employees are required to utilize personal protective equipment and follow safe work practices when working in or around excavations, trenches, or with shoring protection systems.

Custom Electric shall ensure that any contractor hired to perform work at any of our job sites, which involves excavating or trenching shall comply with all applicable OSHA Regulations.

21.4 Employee Training

Custom Electric provides employees with the understanding, knowledge, and skills necessary for the safe performance of their assigned duties. Our training program is designed to ensure proficiency in the duties required by this procedure. These duties include but are not limited to:

- General Safety Requirements
- Mark-out Requirements
- Identifying and Recognizing Hazards
- Access and Egress
- Ladder Safety
- Protecting the Work Area
- Monitoring Atmospheres
- Soil Placement
- Competent Person Responsibilities
- Soil Classification
- Protective Systems
- Hazards with Water Accumulation
- Selection of Personal Protective Equipment
- Job Site Assessment/Securing the Jobsite Area

An employee's initial training is provided prior to assignment and whenever a new hazard is introduced.

21.5 Emergency Rescue Preparedness

Custom Electric will ensure that, if necessary, the means of contacting outside emergency services is available should a trench or excavation rescue be necessary.

21.6 General Requirements

All surface encumbrances that are located so as to create a hazard to employees shall be removed or supported, as necessary, to safeguard employees.

The estimated location of underground utilities or any other underground installations that reasonably may be expected to be encountered during excavation work shall be determined prior to opening an excavation.

The Call Before You Dig Center (CBYD) shall be contacted within established or customary response times, advised of the proposed work, and asked to notify all applicable utility underground owners, or others, of the proposed work. They will be asked to establish the location of the utility or facility prior to the start of actual excavation. When utility companies or other owners cannot respond to a request to locate their facilities within the required period by State Law, or cannot establish the exact location of these facilities, coordinated efforts should be established with the owner to proceed with the excavation provided work commences with caution using detection equipment or other acceptable means to locate the facility.

When excavation operations approach the established location of underground facilities, the exact location of the installation shall be determined by safe and acceptable hand digging practices.

While the excavation is open, underground facilities shall be protected, supported, or removed as necessary to safeguard employees.

21.7 Protective Systems

Protective systems, such as shoring or shielding (i.e. trench boxes), for the protection of employees from cave-ins or collapse shall be installed in all trenches exceeding five feet in depth. Under no circumstances are employees permitted to enter or work within trenches unless this condition is met.

21.8 Safe Access and Egress

A stairway, ladder, ramp, or other safe means of egress shall be located in trench excavations that are four feet (4') or more in depth so as to require no more than twenty-five feet (25') of lateral travel for employees' means of egress. Ladders must be secured and extend a minimum of thirty-six inches (36") above the landing or top of trench. Ladders containing metal should be used with caution, particularly when electric utilities are present.

A competent person shall design structural ramps that are used solely by employees, as a means of access or egress from excavations. Structural ramps used for access or egress of equipment shall be designed by a competent person qualified in structural design and shall be constructed in accordance with the design.

21.9 Atmospheric Testing

Under any circumstances where a competent person might reasonable anticipate that a trench may contain a hazardous atmosphere, the trench shall be tested for the presence of a hazardous atmosphere prior to and during the course of the entry activities. A Hazardous Atmosphere is an atmosphere that by reason of being explosive, flammable, poisonous, corrosive, oxidizing, irritating, oxygen-deficient, toxic, or otherwise harmful may cause death, illness or injury to persons exposed to

21.10 Exposure to Vehicle Traffic

Employees exposed to public vehicular traffic shall be provided with, and shall wear, warning vests or other suitable garments marked with or made of reflective or high-visibility material.

The work site area shall be evaluated identifying existing and predictable hazards on site. A designated, trained flag person, along with signs, signals, barricades, barriers, traffic cones, or other traffic control devices, shall be used as necessary to protect employees from vehicle traffic.

21.11 Exposure to Falling Loads

No employee shall be permitted underneath loads handled by lifting or digging equipment. Employees are required to stand away from any vehicle being loaded or unloaded to avoid being struck by any spillage or falling materials. Operators may remain in the cabs of the vehicles being loaded or unloaded when vehicles are equipped to provide adequate protection for the operator during loading and unloading operations.

21.12 Warning Systems for Mobile Equipment

When mobile equipment is operated adjacent to an excavation, or when such equipment is required to approach the edge of an excavation, and the operator does not have a clear and direct view of the edge of the excavation, a warning system shall be utilized such as barricades, hand or mechanical signals, or stop logs. If possible, the grade should be away from the excavation.

21.13 Protection for Water Accumulation

Employees shall not work in excavations in which there is accumulated water, or in excavations in which water is accumulating unless precautions have been taken to protect them against the hazards posed by the water accumulation. The precautions necessary for protection vary with each situation, but could include special support or shield systems to protect against cave-ins, water removal to control the level of accumulating water, or the use of a safety harness and life line.

If water is controlled or prevented from accumulating by the use of water removal equipment, a competent person shall monitor and ensure the proper operation the equipment and operations.

If excavation work interrupts the natural drainage of surface water, diversion ditches, dikes, or other suitable means shall be used to prevent surface water from entering the excavation and to provide adequate drainage of the area adjacent to the excavation. Excavations subject to runoff from heavy rains will require an inspection by a competent person prior to any employee entering the excavation.

21.14 Stability of Adjacent Structures

Where the stability of adjoining buildings, walls, or other structures is endangered by excavation operations, employees shall install support systems such as shoring, bracing or underpinning to ensure the stability of such structures for their protection.

Excavations below the level of the base or footing of any foundation or retaining wall that could be reasonably expected to pose a hazard to the employees shall not be permitted except when:

- A support system such as underpinning is provided to ensure safety of the employees and the stability of the structure;
- The excavation is in stable rock;
- A registered professional engineer has approved the determination that the structure is sufficiently removed from the excavation so as to be unaffected by the excavation activity; or
- A registered professional engineer has approved the determination that such excavation

work will not pose a hazard to employees.

Employees shall not undermine sidewalks, pavements, and structures unless a support system or another method of protection is provided to protect employees from the possible collapse of such structure.

21.15 Protection of Employees from Loose Rock or Soil

Adequate protection shall be provided to protect employees from loose rock or soil that could pose a hazard by falling or rolling from an excavation face. Such protection shall consist of employees scaling to remove loose material, installing protective barricades at intervals as necessary on the face to stop and contain falling material, or other means that provide adequate protection.

Employees shall be protected from excavated materials or equipment that could pose a hazard by falling or rolling into excavations. Protection shall be provided by employees placing and keeping such materials or equipment at least two feet (2') from the edge of excavations, or by the use of retaining devices that are sufficient to prevent materials or equipment from falling or rolling into excavations.

21.16 Fall Protection

Walkways shall be provided where employees or equipment are required or permitted to crossover excavations. OSHA-approved guardrails shall be used where walkways are six feet (6') or more above lower levels.

Adequate barrier physical protection shall be used to cover or barricade all remotely located excavations. Excavations shall be backfilled upon completion of work or as soon as practical.

21.17 Inspections

Daily inspections of excavations, the adjacent areas and protective systems shall be made by a competent person for evidence of a situation that could result in possible cave-ins, indications of failure of protective systems, hazardous atmospheres, or other hazardous conditions. The inspection shall be prior to the start of work and periodically throughout the shift. Inspections shall also be made after every rainstorm, or other hazard- increasing occurrence.

Where the competent person finds evidence of a situation that could result in a possible cave-in, indications of failure of protective systems, hazardous atmospheres, or other hazardous conditions, employees shall not enter the hazardous area until the necessary precautions have been taken to make the area safe.

21.18 Enforcement

Custom Electric excavations, trenching and shoring protection policy will be implemented, updated and supervised by Safety Director. Supervisors and foremen will be responsible for implementing all provisions of the excavations, trenching, and shoring protection policy and ensuring they are met at the jobsite. Any employee knowingly violating this safety procedure will be subject to disciplinary action.

22.1 Vehicle Fleet Safety Policy

22.2 Purpose

The purpose of this policy is to ensure the safety of those individuals who drive company vehicles. Vehicle accidents are costly to our company, but more importantly, they may result in injury to you or others. It is the driver's responsibility to operate the vehicle in a safe manner and to drive defensively to prevent injuries and property damage. As such, our company endorses all applicable state motor vehicle regulations relating to driver responsibility. Our company expects each driver to drive in a safe and courteous manner pursuant to the following safety rules. The attitude you take when behind the wheel is the single most important factor in driving safely.

22.1 a Driver Safety Rules

1. The use of a company vehicle while under the influence of intoxicants and other drugs are forbidden and are sufficient cause for discipline, including dismissal.
2. No driver shall operate a company vehicle when his/her ability to do so safely has been impaired by illness, fatigue, injury, or prescription medications.
3. All drivers and passengers operating or riding in company vehicles must wear seatbelts, even if air bags are available.
4. No unauthorized personnel (e.g. hitch-hikers) are allowed to ride in company vehicles.
5. Drivers are responsible for the security of company vehicles assigned to them
6. Headlights shall be used ½ hour before sunset and ½ hour after sunrise, or during inclement weather or at any time when a distance of 500 feet ahead of the vehicle cannot be seen clearly.
7. All other state laws, local laws, or D.O.T. Motor Carrier Safety Regulations, must be obeyed.
8. Personal cellular telephone use is prohibited while operating company vehicles. If a business call is necessary a wireless device must be used.

22.1 b Driver Eligibility

- Company vehicles are to be driven by authorized employees only, except in emergencies, or in case of repair testing by a mechanic. Spouses and other family members are not authorized to drive the Company vehicle.
- Company vehicles may be used only for company business purposes unless appropriate approvals have been received from management.
- Any employee who has a driver's license revoked or suspended shall immediately notify and discontinue operation of the company vehicle. Failure to do so may result in disciplinary action, including dismissal.
- All accidents, regardless of severity, must be reported to the office, which will notify the police. Failing to stop after an accident and/or failure to report an accident may result in disciplinary action, including dismissal.
- Drivers must immediately report all summonses received for moving violations during the operation of a company vehicle to the office.

- All CDL drivers must comply with all applicable D.O.T. regulations, including successful completion on all medical drug, and alcohol evaluations.
- Motor Vehicle Records will be reordered periodically to access employees' driving records. An unfavorable record will result in a loss of the privilege of driving a Company vehicle. The following system will be used to determine eligibility to operate a Company vehicle:
 - ALL TYPE "A" VIOLATIONS (as defined) WILL RESULT IN TERMINATION OF DRIVING PRIVILEGES FOR EMPLOYEES AND WILL DISQUALIFY ANY POTENTIAL EMPLOYEES.
 - ANY DRIVERS (EMPLOYEES OR APPLICANTS) SHOWING ONE OF THE FOLLOWING WILL BE RESTRICTED FROM DRIVING COMPANY VEHICLES:
 - One (1) or more type "A" Violations in the last 3 years.
 - Three (3) or more accidents (regardless of fault) in 3 years.
 - Four (4) or more type "B" Violations in the last 3 years.
 - Any combination of accidents and type "B" Violations that equal Four (4) or more in the last 3 years.

Type "A" Violations:

- Driving While Intoxicated
- Driving While Under the Influence of Drugs
- Negligent Homicide Involving a Motor Vehicle (gross negligence)
- Operating During a period of Suspension or Revocation
- Using a Motor Vehicle for the commission of a Felony
- Aggravated Assault with a Motor Vehicle
- Operating a Motor Vehicle Without the Owners Authority (grand theft)
- Permitting an Unlicensed Person to Drive
- Reckless Driving
- Speed Contest (racing)
- Hit and Run (Bodily Injury or Property Damage)

Type "B" Violations:

- All Moving Violations not listed as type "A" Violations

Tips For Defensive Driving

1. Drivers are required to maintain a safe following distance at all times. To estimate your following distance, pick a stationary object ahead of you. As the vehicle in front of you passes the object, begin counting 1001, 1002, 1003, etc. until you reach the same object. This counts the number of seconds between you and the vehicle ahead of you.
 - Drivers of passenger vehicles should keep a two-second interval between their vehicle and the vehicle immediately ahead. During slippery road conditions, the following distance should be increased to at least four seconds.
 - Drivers of heavy trucks should keep a minimum of a three-second interval when not carrying cargo, and at least four-seconds when fully loaded. Following distance should also be increased when adverse conditions exist.
2. Drivers must yield the right of way at all traffic control signals and signs requiring them to do so. Drivers should also be prepared to yield for safety's sake at any time. Pedestrians and bicycles in the roadways always have the right of way.

3. Avoid driving in other driver's blind spots. Attempt to maintain eye contact with the other driver, either directly or through mirrors.
4. Drivers must honor posted speed limits. In adverse driving conditions, reduce the speed to a safe operating speed that is consistent with the conditions of the road, weather, lighting, and volume of traffic. Tires can hydroplane on wet pavement at speeds as low as 40 mph.
5. Turn signals must be used to show where you are heading; while going into traffic and before every turn or lane change.
6. When passing or changing lanes, view the entire vehicle in your rear view mirror before pulling back into that lane.
7. Be alert of other vehicles, pedestrians, and bicyclists when approaching intersections. Never speed through an intersection on a caution light. Approach a stale green light with your foot poised over the brake to reduce your reaction time should it be necessary to stop. When the traffic light turns green, look both ways for oncoming traffic before proceeding.
8. When waiting to make left turns, keep your wheels facing straight ahead. If rear-ended, you will not be pushed into the lane of oncoming traffic.
9. When stopping behind another vehicle, leave enough space so you can see the rear wheels of the car in front. This allows room to go around the vehicle if necessary, and may prevent you from being pushed into the car in front of you if you are rear-ended.
10. Avoid backing where possible, but when necessary, keep the distance traveled to a minimum and be particularly careful.
 - Check behind your vehicle. Operators of heavy trucks should walk around their vehicle before backing and/or have someone guide one.
 - Back to the driver's side. Do not back around a corner or into an area of no visibility.

22.1 c Vehicle Inspection

Proper vehicle maintenance is a basic element of any fleet safety program, not only to ensure a safe, road worthy vehicle, but also to avoid costly repair expenses and unexpected breakdowns.

- Inspection is the responsibility of the assigned driver.
 - Drivers of D.O.T. regulated vehicles are required to inspect their vehicle prior to usage, documenting and notifying the office of deficiencies found.
 - In addition to inspections required by law for passenger vehicles, drivers of passenger vehicles must also complete routine inspections of critical items, such as brakes, lights, tires, wipers, etc.
- The vehicle should be cleaned (interior & exterior) monthly to help maintain its good appearance for you and the Company. A clean vehicle makes a good impression on customers. Employees shall be reimbursed once an expense report has been submitted, not to exceed \$12.00 per each cleaning.
- Notify the company when scheduled maintenance intervals are completed and turn in with mileage reports weekly.
- All major repairs (over \$200) require company approval.

22.1 d What to Do in the Event of an Accident

In an attempt to minimize the results of an accident, the driver must prevent further damages or injuries and obtain all pertinent information and report it accurately.

- Call for medical aid if necessary (911).
- Secure accident scene – pull onto shoulder or side of road, redirect traffic, set up road flares/reflectors, etc.
- Notify the office immediately.
- Record names and addresses of driver, witnesses, and occupants of the other vehicles and any medical personnel who may arrive at the scene.
- Complete the accident form located in the vehicle registration package. Pertinent information to obtain includes:
 - License number of other drivers
 - Insurance company names and policy numbers of other vehicles
 - Make, year, model of other vehicles
 - Date and time of accident
 - Overall road and weather conditions
 - Draw a diagram of the accident scene and not the street names and locations of traffic signs, signals, etc.

Do not discuss the accident with anyone at the scene except the police. Do NOT accept any responsibility for the accident. DON'T argue with anyone.

- Provide the other party with your name, address, phone number, driver's license number and insurance information.
- Cooperate fully with any follow-up from Claims personnel.

22.1 e Persons Driving Their Own Vehicles for Company Purposes

Persons driving their own vehicles for company use must provide proof of adequate insurance relating to the vehicle that will be used. A copy of the policy declaration page identifying the dates of coverage and the limits of liability must be provided to administration on an annual basis. Adequate insurance limits for potential bodily injury must be secured and maintained on each vehicle planned to be used by the vehicle custodian.

22.2 Disciplinary Procedures

Constant awareness of and respect for safety procedures and compliance with all safety rules are considered conditions of employment. Management, Supervisors, and the Safety Director reserve the right to issue disciplinary warnings to employees, up to and including termination, for failure to follow the guidelines of this program.

23.0A

Respirable Crystalline Silica Program

PURPOSE

This Respirable Crystalline Silica Program was developed to prevent employee exposure to hazardous levels of Respirable Crystalline Silica that could result through construction activities or nearby construction activities occurring on worksites. Respirable Crystalline Silica exposure at hazardous levels can lead to lung cancer, silicosis, chronic obstructive pulmonary disease, and kidney disease. It is intended to meet the requirements of the Respirable Crystalline Silica Construction Standard (29 CFR 1926.1153) established by the Occupational Safety and Health Administration (OSHA).

All work involving chipping, cutting, drilling, grinding, or similar activities on materials containing Crystalline Silica can lead to the release of respirable-sized particles of Crystalline Silica (i.e. Respirable Crystalline Silica). Crystalline Silica is a basic component of soil, sand, granite and many other minerals. Quartz is the most common form of Crystalline Silica. Many materials found on construction sites include Crystalline Silica; including but not limited to – cement, concrete, asphalt, pre-formed structures (inlets, pipe, etc.) and others. Consequently, this program has been developed to address and control these potential exposures to prevent our employees from experiencing the effects of occupational illnesses related to Respirable Crystalline Silica exposure.

SCOPE

This Respirable Crystalline Silica Program applies to all employees who have the potential to be exposed to Respirable Crystalline Silica when covered by the OSHA Standard. The OSHA Respirable Crystalline Silica Construction Standard applies to all occupational exposures to Respirable Crystalline Silica in construction work, except where employee exposure will remain below 25 micrograms of Respirable Crystalline Silica per cubic meter of air (25 $\mu\text{g}/\text{m}^3$) as an 8-hour time-weighted average (TWA) under any foreseeable conditions.

RESPONSIBILITIES

Custom Electric firmly believes protecting the health and safety of our employees is everyone's responsibility. This responsibility begins with upper management providing the necessary support to properly implement this program. However, all levels of the organization assume some level of responsibility for this program including the following positions.

Company Management

- Conduct job site assessments for Silica containing materials and perform employee Respirable Crystalline Silica hazard assessments in order to determine if an employee's exposure will be above 25 $\mu\text{g}/\text{m}^3$ as an 8-hour TWA under any foreseeable conditions
- Select and implement into the project's ECP the appropriate control measures in accordance with the Construction Tasks identified in OSHA's Construction Standard Table 1; and potentially including (but not limited to) - a written Exposure Control Plan (ECP), exposure monitoring, Hazard Communication training, medical surveillance, housekeeping and others.

NOTE: OSHA's Construction Standard Table 1 is a list of 18 common construction tasks along with acceptable exposure control methods and work practices that limit exposure for those tasks.

- Ensure that the materials, tools, equipment, personal protective equipment (PPE), and other resources (such as worker training) required to fully implement and maintain this Respirable Crystalline Silica Program are in place and readily available if needed.
- Ensure that Project Managers, Site Managers, Competent Persons, and employees are educated in the hazards of Silica exposure and trained to work safely with Silica in accordance with OSHA's Respirable Crystalline Silica Construction Standard and OSHA's Hazard Communication Standard. Managers and Competent Persons may receive more advanced training than other employees.
- Maintain written records of training (for example, proper use of respirators), ECPs, inspections (for equipment, PPE, and work methods/practices), medical surveillance (under lock and key), respirator medical clearances (under lock and key) and fit-test results.
- Conduct an annual review (or more often if conditions change) of the effectiveness of this program and any active project ECP's that extend beyond a year. This includes a review of available dust control technologies to ensure these are selected and used when practical.
- Coordinate work with other employers and contractors to ensure a safe work environment relative to Silica exposure.

Project Managers

- Ensure all applicable elements of this Respirable Crystalline Silica Program are implemented on the project including the selection of a Competent Person.
- Assist in conducting job site assessments for Silica containing materials and perform employee Respirable Crystalline Silica hazard assessments in order to determine if an ECP, exposure monitoring, and medical surveillance is necessary.
- Assist in the selection and implementation of the appropriate control measures in accordance with the Construction Tasks identified in OSHA's Construction Standard Table 1; and potentially including (but not limited to) - a written Exposure Control Plan (ECP), exposure monitoring, Hazard Communication training, medical surveillance, housekeeping and others.

- Ensure that employees using respirators have been properly trained, medically cleared, and fit-tested in accordance with the company's Respiratory Protection Program. This process will be documented.
- Ensure that work is conducted in a manner that minimizes and adequately controls the risk to workers and others. This includes ensuring that workers use appropriate engineering controls, work practices, and wear the necessary PPE.
- Where there is risk of exposure to Silica dust, verify employees are properly trained on the applicable contents of this program, the project-specific ECP, and the applicable OSHA Standards (such as Hazard Communication). Ensure employees are provided appropriate PPE when conducting such work.

Competent Person and/or Site Manager

- Make frequent and regular inspections of job sites, materials, and equipment to implement the written ECP.
- Identify existing and foreseeable Respirable Crystalline Silica hazards in the workplace and take prompt corrective measures to eliminate or minimize them.
- Notify the Project Manager of any deficiencies identified during inspections in order to coordinate and facilitate prompt corrective action.
- Assist the Project Manager in conducting job site assessments for Silica containing materials and perform employee Respirable Crystalline Silica hazard assessments in order to determine if an ECP, exposure monitoring, and medical surveillance is necessary.

Employees:

- Follow recognized work procedures (such as the Construction Tasks identified in OSHA's Construction Standard Table 1) as established in the project's ECP and this program.
- Use the assigned PPE in an effective and safe manner.
- Participate in Respirable Crystalline Silica exposure monitoring and the medical surveillance program.
- Report any unsafe conditions or acts to the Site Manager and/or Competent Person.
- Report any exposure incidents or any signs or symptoms of Silica illness.

DEFINITIONS

If a definition is not listed in this section, please contact your supervisor. If your supervisor is unaware of what the term means, please contact the Competent Person or your Safety Department.

- Action Level means a concentration of airborne Respirable Crystalline Silica of 25 $\mu\text{g}/\text{m}^3$, calculated as an 8-hour TWA.

- Competent Person means an individual who is capable of identifying existing and foreseeable Respirable Crystalline Silica hazards in the workplace and who has authorization to take prompt corrective measures to eliminate or minimize them.
- Employee Exposure means the exposure to airborne Respirable Crystalline Silica that would occur if the employee were not using a respirator.
- High-Efficiency Particulate Air (HEPA) Filter means a filter that is at least 99.97 percent efficient in removing monodispersed particles of 0.3 micrometers in diameter.
- Objective Data means information, such as air monitoring data from industry-wide surveys or calculations based on the composition of a substance, demonstrating employee exposure to Respirable Crystalline Silica associated with a particular product or material or a specific process, task, or activity. The data must reflect workplace conditions closely resembling or with a higher exposure potential than the processes, types of material, control methods, work practices, and environmental conditions in the employer's current operations.
- Permissible Exposure Limit (PEL) means the employer shall ensure that no employee is exposed to an airborne concentration of Respirable Crystalline Silica in excess of 50 µg/m³, calculated as an 8-hour TWA.
- Physician or Other Licensed Health Care Professional (PLHCP) means an individual whose legally permitted scope of practice (i.e., license, registration, or certification) allows him or her to independently provide or be delegated the responsibility to provide some or all of the particular health care services required by the Medical Surveillance Section of the OSHA Respirable Crystalline Silica Standard.
- Respirable Crystalline Silica means Quartz, Cristobalite, and/or Tridymite contained in airborne particles that are determined to be respirable by a sampling device designed to meet the characteristics for respirable-particle size- selective samplers specified in the International Organization for Standardization (ISO) 7708:1995: Air Quality-Particle Size Fraction Definitions for Health-Related Sampling.
- Specialist means an American Board Certified Specialist in Pulmonary Disease or an American Board Certified Specialist in Occupational Medicine.

REQUIREMENTS

Specified Exposure Control Methods

When possible and applicable, Custom Electric will conduct activities with potential Silica exposure to be consistent with OSHA's Construction Standard Table 1. Supervisors will ensure each employee under their supervision and engaged in a task identified on OSHA's Construction Standard Table 1 have fully and properly implemented the engineering controls, work practices, and respiratory protection specified for the task on Table 1 (unless Custom Electric has assessed and limited the exposure of the employee to Respirable Crystalline Silica in accordance with the Alternative Exposure Control Methods Section of this program).

The typical task(s) being performed by Custom Electric are identified on OSHA's Construction Standard **Table 1 #7**.

Table 1: Specified Exposure Control Methods When Working With Materials Containing Crystalline Silica

Construction Task or Equipment Operation		Engineering and Work Practice Control Methods	Required Respiratory Protection	
			≤ 4 hours/shift	>4 hours/shift
1	Stationary masonry saws	- Use saw equipped with integrated water delivery system that continuously feeds water to the blade. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	None
2a	Handheld power saws (any blade diameter) when used outdoors	- Use saw equipped with integrated water delivery system that continuously feeds water to the blade. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
2b	Handheld power saws (any blade diameter) when used indoors or in an enclosed area	- Use saw equipped with integrated water delivery system that continuously feeds water to the blade. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
3	Handheld power saws for cutting fiber-cement board (with blade diameter of 8 inches or less) for tasks performed outdoors only	- Use saw equipped with commercially available dust collection system. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency.	None	None
4a	Walk-behind saws when used outdoors	- Use saw equipped with integrated water delivery system that continuously feeds water to the blade. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	None
4b	Walk-behind saws when used indoors or in an enclosed area	- Use saw equipped with integrated water delivery system that continuously feeds water to the blade. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
5	Drivable saws for tasks performed outdoors only	- Use saw equipped with integrated water delivery system that continuously feeds water to the blade. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	None
6	Rig-mounted core saws or drills	- Use tool equipped with integrated water delivery system that supplies water to cutting surface. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	None
7	Handheld and stand-mounted drills	Use drill equipped with commercially available shroud or cowl with dust collection system.	None	None

Construction Task or Equipment Operation		Engineering and Work Practice Control Methods	Required Respiratory Protection	
			≤ 4 hours/shift	>4 hours/shift
	(including impact and rotary hammer drills)	- Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism. - Use a HEPA-filtered vacuum when cleaning holes.		
8	Dowel drilling rigs for concrete for tasks performed outdoors only	- Use shroud around drill bit with a dust collection system. - Dust collector must have a filter with 99% or greater efficiency and a filter cleaning mechanism. - Use a HEPA-filtered vacuum when cleaning holes.	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
9a	Vehicle-mounted drilling rigs for rock and concrete	Use dust collection system with close capture hood or shroud around drill bit with a low-flow water spray to wet the dust at the discharge point from the dust collector.	None	None
9b	Vehicle-mounted drilling rigs for rock and concrete	Operate from within an enclosed cab and use water for dust suppression on drill bit.	None	None
10a	Jackhammers and handheld powered chipping tools when used outdoors	Use tool with water delivery system that supplies a continuous stream or spray of water at the point of impact.	None	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
10b	Jackhammers and handheld powered chipping tools when used indoors or in an enclosed area	Use tool with water delivery system that supplies a continuous stream or spray of water at the point of impact.	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
10c	Jackhammers and handheld powered chipping tools when used outdoors	- Use tool equipped with commercially available shroud and dust collection system. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.	None	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
10d	Jackhammers and handheld powered chipping tools when used indoors or in an enclosed area	- Use tool equipped with commercially available shroud and dust collection system. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask

Construction Task or Equipment Operation		Engineering and Work Practice Control Methods	Required Respiratory Protection	
			≤ 4 hours/shift	>4 hours/shift
		Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.		
11	Handheld grinders for mortar removal (i.e., tuckpointing)	- Use grinder equipped with commercially available shroud and dust collection system. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask	Powered Air-Purifying Respirator (PAPR) with P100 Filters
12a	Handheld grinders for uses other than mortar removal for tasks performed outdoors only	- Use grinder equipped with integrated water delivery system that continuously feeds water to the grinding surface. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	None
12b	Handheld grinders for uses other than mortar removal when used outdoors	- Use grinder equipped with commercially available shroud and dust collection system. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.	None	None
12c	Handheld grinders for uses other than mortar removal when used indoors or in an enclosed area	- Use grinder equipped with commercially available shroud and dust collection system. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.	None	N95 (or Greater Efficiency) Filtering Facepiece or Half Mask
13a	Walk-behind milling machines and floor grinders	- Use machine equipped with integrated water delivery system that continuously feeds water to the cutting surface. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.	None	None

Construction Task or Equipment Operation		Engineering and Work Practice Control Methods	Required Respiratory Protection	
			≤ 4 hours/shift	>4 hours/shift
13b	Walk-behind milling machines and floor grinders	- Use machine equipped with dust collection system recommended by the manufacturer. - Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions. - Dust collector must provide the air flow recommended by the manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism. - When used indoors or in an enclosed area, use a HEPA-filtered vacuum to remove loose dust in between passes.	None	None
14	Small drivable milling machines (less than half-lane)	- Use a machine equipped with supplemental water sprays designed to suppress dust. - Water must be combined with a surfactant. - Operate and maintain machine to minimize dust emissions.	None	None
15a	Large drivable milling machines (half-lane and larger) for cuts of any depth on asphalt only	- Use machine equipped with exhaust ventilation on drum enclosure and supplemental water sprays designed to suppress dust. - Operate and maintain machine to minimize dust emissions.	None	None
15b	Large drivable milling machines (half-lane and larger) for cuts of four inches in depth or less on any substrate	- Use machine equipped with exhaust ventilation on drum enclosure and supplemental water sprays designed to suppress dust. - Operate and maintain machine to minimize dust emissions.	None	None
15c	Large drivable milling machines (half-lane and larger) for cuts of four inches in depth or less on any substrate	- Use a machine equipped with supplemental water spray designed to suppress dust. - Water must be combined with a surfactant. - Operate and maintain machine to minimize dust emissions.	None	None
16	Crushing machines	- Use equipment designed to deliver water spray or mist for dust suppression at crusher and other points where dust is generated (e.g., hoppers, conveyers, sieves/sizing or vibrating components, and discharge points). - Operate and maintain machine in accordance with manufacturer's instructions to minimize dust emissions. - Use a ventilated booth that provides fresh, climate-controlled air to the operator, or a remote control station.	None	None
17a	Heavy equipment and utility vehicles used to abrade or fracture silica-containing materials (e.g., hoe-ramming, rock ripping) or used	Operate equipment from within an enclosed cab.	None	None

Construction Task or Equipment Operation		Engineering and Work Practice Control Methods	Required Respiratory Protection	
			≤ 4 hours/shift	>4 hours/shift
	during demolition activities involving silica-containing materials			
17b	Heavy equipment and utility vehicles used to abrade or fracture silica-containing materials (e.g., hoe-ramming, rock ripping) or used during demolition activities involving silica-containing materials	When employees outside of the cab are engaged in the task, apply water and/or dust suppressants as necessary to minimize dust emissions.	None	None
18a	Heavy equipment and utility vehicles for tasks such as grading and excavating but not including demolishing, abrading, or fracturing silica-containing materials	Apply water and/or dust suppressants as necessary to minimize dust emissions.	None	None
18b	Heavy equipment and utility vehicles for tasks such as grading and excavating but not including demolishing, abrading, or fracturing silica-containing materials	When the equipment operator is the only employee engaged in the task, operate equipment from within an enclosed cab.	None	None

When implementing the control measures specified in Table 1, Custom Electric shall:

- For tasks performed indoors or in enclosed areas, provide a means of exhaust as needed to minimize the accumulation of visible airborne dust;
- For tasks performed using wet methods, apply water at flow rates sufficient to minimize release of visible dust;
- Where an employee performs more than one task included on OSHA's Construction Standard Table 1 during the course of a shift, and the total duration of all tasks combined is more than four hours, the required respiratory protection for each task is the respiratory protection specified for more than four hours per shift. If the total duration of all tasks on Table 1 combined is less than four hours, the required respiratory protection for each task is the respiratory protection specified for less than four hours per shift.

Alternative Exposure Control Methods

Alternative Exposure Control Methods apply for tasks not listed in OSHA's Construction Standard Table 1, or where Custom Electric cannot not fully and properly implement the engineering controls, work practices, and respiratory protection described in Table 1.

First, **if applicable**, Custom Electric will assess the exposure of each employee who is or may reasonably be expected to be exposed to Respirable Crystalline Silica at or above the Action Level in accordance with either the Performance Option or the Scheduled Monitoring Option.

- **Performance Option** – Custom Electric will assess the 8-hour TWA exposure for each employee on the basis of any combination of air monitoring data or objective data sufficient to accurately characterize employee exposures to Respirable Crystalline Silica.
- **Scheduled Monitoring Option:**
 - Custom Electric will perform initial monitoring to assess the 8-hour TWA exposure for each employee on the basis of one or more personal breathing zone air samples that reflect the exposures of employees on each shift, for each job classification, and in each work area. Where several employees perform the same tasks on the same shift and in the same work area, Custom Electric will plan to monitor a representative fraction of these employees. When using representative monitoring, Custom Electric will sample the employee(s) who are expected to have the highest exposure to Respirable Crystalline Silica.
 - If initial monitoring indicates that employee exposures are below the Action Level, Custom Electric will probably discontinue monitoring for those employees whose exposures are represented by such monitoring.
 - Where the most recent exposure monitoring indicates that employee exposures are at or above the Action Level but at or below the PEL, Custom Electric will repeat such monitoring within six months of the most recent monitoring.
 - Where the most recent exposure monitoring indicates that employee exposures are above the PEL, Custom Electric will repeat such monitoring within three months of the most recent monitoring.
 - Where the most recent (non-initial) exposure monitoring indicates that employee exposures are below the Action Level, Custom Electric will repeat such monitoring within six months of the most recent monitoring until two consecutive measurements, taken seven or more days apart, are below the Action Level, at which time Custom Electric will probably discontinue monitoring for those employees whose exposures are represented by such monitoring, except when a reassessment is required. Custom Electric will reassess exposures whenever a change in the production, process, control equipment, personnel, or work practices may reasonably be expected to result in new or additional exposures at or above the Action Level, or when Custom Electric has any reason to believe that new or additional exposures at or above the Action Level have occurred.

Custom Electric will ensure that all Respirable Crystalline Silica samples taken to satisfy the monitoring requirements of this program and OSHA are collected by a qualified individual (i.e. a Certified Industrial Hygienist) and the samples are evaluated by a qualified laboratory (i.e. accredited to ANSI/ISO/IEC Standard 17025:2005 with respect to Crystalline Silica analyses by a body that is compliant with ISO/IEC Standard 17011:2004 for implementation of quality assessment programs).

Within five working days after completing an exposure assessment, Custom Electric will individually notify each affected employee in writing of the results of that assessment or post the results in an appropriate location accessible to all affected employees.

Whenever an exposure assessment indicates that employee exposure is above the PEL, Custom Electric will describe in the written notification the corrective action being taken to reduce employee exposure to or below the PEL.

Where air monitoring is performed, Custom Electric will provide affected employees or their designated representatives an opportunity to observe any monitoring of employee exposure to Respirable Crystalline Silica. When observation of monitoring requires entry into an area where the use of protective clothing or equipment is required for any workplace hazard, Custom Electric will provide the observer with protective clothing and equipment at no cost and shall ensure that the observer uses such clothing and equipment.

Once air monitoring has been performed, Custom Electric will determine its method of compliance based on the monitoring data and the hierarchy of controls. Custom Electric will use engineering and work practice controls to reduce and maintain employee exposure to Respirable Crystalline Silica to or below the PEL, unless Custom Electric can demonstrate that such controls are not feasible. Wherever such feasible engineering and work practice controls are not sufficient to reduce employee exposure to or below the PEL, Custom Electric will nonetheless use them to reduce employee exposure to the lowest feasible level and shall supplement them with the use of respiratory protection.

Control Methods

Custom Electric will provide control methods that are either consistent with Table 1 or otherwise minimize worker exposures to Silica. These exposure control methods can include engineering controls, work practices, and respiratory protection. Listed below are control methods to be used when Table 1 is not followed:

List and discuss control methods

Respiratory Protection

Where respiratory protection is required by this program, Custom Electric will provide each employee an appropriate respirator that complies with the requirements of the company's Respiratory Protection Program and the OSHA Respiratory Protection Standard (29 CFR 1910.134).

Respiratory protection is required where specified by the OSHA Construction Standard Table 1, for tasks not listed in Table 1, or where the company has not fully and properly implemented the engineering controls, work practices, and respiratory protection described in Table 1. Situations requiring respiratory protection include:

- Where exposures exceed the PEL during periods necessary to install or implement feasible engineering and work practice controls;
- Where exposures exceed the PEL during tasks, such as certain maintenance and repair tasks, for which engineering and work practice controls are not feasible; and
- During tasks for which an employer has implemented all feasible engineering and work practice controls and such controls are not sufficient to reduce exposures to or below the PEL.

Housekeeping

Custom Electric does not allow dry sweeping or dry brushing where such activity could contribute to employee exposure to Respirable Crystalline Silica unless wet sweeping, HEPA-filtered vacuuming, or other methods that minimize the likelihood of exposure are not feasible.

Custom Electric does not allow compressed air to be used to clean clothing or surfaces where such activity could contribute to employee exposure to Respirable Crystalline Silica unless:

- The compressed air is used in conjunction with a ventilation system that effectively captures the dust cloud created by the compressed air; or
- No alternative method is feasible.

Written Exposure Control Plan

When employee exposure on a construction project is expected to be at or above the Action Level, a Written Exposure Control Plan (ECP) will be established and implemented. This ECP will contain at least the following elements:

- A description of the tasks in the workplace that involve exposure to Respirable Crystalline Silica;
- A description of the engineering controls, work practices, and respiratory protection used to limit employee exposure to Respirable Crystalline Silica for each task;
- A description of the housekeeping measures used to limit employee exposure to Respirable Crystalline Silica; and
- A description of the procedures used to restrict access to work areas, when necessary, to minimize the number of employees exposed to Respirable Crystalline Silica and their level of exposure, including exposures generated by other employers or sole proprietors.

The written ECP will designate a Competent Person to make frequent and regular inspections of job sites, materials, and equipment to ensure the ECP is implemented.

The written ECP will be reviewed at least annually to evaluate the effectiveness of it and update it as necessary. Having said this, ECP's are project specific and most project durations do not exceed a year. The written ECP will be readily available for examination and copying, upon request, to each employee covered by this program and/or ECP, their designated representatives, and OSHA.

Medical Surveillance

Medical surveillance will be made available for each employee who will be required to use a respirator for 30 or more days per year due to their Respirable Crystalline Silica exposure. Medical surveillance (i.e. medical examinations and procedures) will be performed by a PLHCP and provided at no cost to the employee at a reasonable time and place.

Custom Electric will make available an initial (baseline) medical examination within 30 days after initial assignment, unless the employee has received a medical examination that meets the requirements of the OSHA Respirable Crystalline Silica Construction Standard within the last three years. The examination

shall consist of:

- A medical and work history, with emphasis on past, present, and anticipated exposure to Respirable Crystalline Silica, dust, and other agents affecting the respiratory system in addition to any history of respiratory system dysfunction, including signs and symptoms of respiratory disease (e.g., shortness of breath, cough, wheezing), history of tuberculosis, and smoking status and history;
- A physical examination with special emphasis on the respiratory system;
- A chest X-ray (a single postero-anterior radiographic projection or radiograph of the chest at full inspiration recorded on either film [no less than 14 x 17 inches and no more than 16 x 17 inches] or digital radiography systems) interpreted and classified according to the International Labour Office (ILO) International Classification of Radiographs of Pneumoconiosis by a NIOSH-certified B Reader;
- A pulmonary function test to include forced vital capacity (FVC) and forced expiratory volume in one second (FEV1) and FEV1/FVC ratio, administered by a spirometry technician with a current certificate from a NIOSH-approved spirometry course;
- Testing for latent tuberculosis infection; and
- Any other tests deemed appropriate by the PLHCP.

Custom Electric will make available medical examinations that include the aforementioned procedures (except testing for latent tuberculosis infection) at least every three years. If recommended by the PLHCP, periodic examinations can be more frequently than every three years.

Custom Electric will ensure that the examining PLHCP has a copy of the OSHA Respirable Crystalline Silica Construction Standard, this program, and the following information:

- A description of the employee's former, current, and anticipated duties as they relate to the employee's occupational exposure to Respirable Crystalline Silica;
- The employee's former, current, and anticipated levels of occupational exposure to Respirable Crystalline Silica;
- A description of any personal protective equipment (PPE) used or to be used by the employee, including when and for how long the employee has used or will use that equipment; and
- Information from records of employment-related medical examinations previously provided to the employee and currently within the control of Custom Electric.

Custom Electric will ensure that the PLHCP explains to the employee the results of the medical examination and provides each employee with a written medical report within 30 days of each medical examination performed. The written report shall contain:

- A statement indicating the results of the medical examination, including any medical condition(s) that would place the employee at increased risk of material impairment to health from exposure to Respirable Crystalline Silica and any medical conditions that require further evaluation or treatment;

- Any recommended limitations on the employee's use of respirators;
- Any recommended limitations on the employee's exposure to Respirable Crystalline Silica; and;
- A statement that the employee should be examined by a Specialist if the chest X-ray is classified as 1/0 or higher by the B Reader, or if referral to a Specialist is otherwise deemed appropriate by the PLHCP.

Custom Electric will also obtain a written medical opinion from the PLHCP within 30 days of the medical examination. The written opinion shall contain only the following in order to protect the employee's privacy:

- The date of the examination;
- A statement that the examination has met the requirements of the OSHA Respirable Crystalline Silica Construction Standard; and
- Any recommended limitations on the employee's use of respirators.

If the employee provides written authorization, the written opinion shall also contain either or both of the following:

- Any recommended limitations on the employee's exposure to Respirable Crystalline Silica; and/or
- A statement that the employee should be examined by a Specialist if the chest X-ray is classified as 1/0 or higher by the B Reader, or if referral to a Specialist is otherwise deemed appropriate by the PLHCP.

If the PLHCP's written medical opinion indicates that an employee should be examined by a Specialist, Custom Electric will make available a medical examination by a Specialist within 30 days after receiving the PLHCP's written opinion. Custom Electric will ensure that the examining Specialist is provided with all of the information that the employer is obligated to provide to the PLHCP.

Custom Electric will ensure that the Specialist explains to the employee the results of the medical examination and provides each employee with a written medical report within 30 days of the examination. The written report will contain:

- A statement indicating the results of the medical examination, including any medical condition(s) that would place the employee at increased risk of material impairment to health from exposure to Respirable Crystalline Silica and any medical conditions that require further evaluation or treatment;
- Any recommended limitations on the employee's use of respirators; and
- Any recommended limitations on the employee's exposure to respirable crystalline Silica.

In addition, Custom Electric will obtain a written opinion from the Specialist within 30 days of the medical examination. The written opinion shall contain the following:

- The date of the examination;
- Any recommended limitations on the employee's use of respirators; and

- If the employee provides written authorization, the written opinion shall also contain any recommended limitations on the employee's exposure to Respirable Crystalline Silica.

Hazard Communication

Custom Electric will include Respirable Crystalline Silica in the company's Hazard Communication Program established to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Custom Electric will ensure that each employee has access to labels on containers of Crystalline Silica and those containers respective Safety Data Sheets (SDS's).

All employees will be trained in accordance with the provisions of the OSHA Hazard Communication Standard and the Training Section of this program. This training will cover concerns relating to cancer, lung effects, immune system effects, and kidney effects.

Custom Electric will ensure that each employee with the potential to be exposed at or above the Action Level for

Respirable Crystalline Silica can demonstrate knowledge and understanding of at least the following:

- The health hazards associated with exposure to Respirable Crystalline Silica;
- Specific tasks in the workplace that could result in exposure to Respirable Crystalline Silica;
- Specific measures Custom Electric has implemented to protect employees from exposure to Respirable Crystalline Silica, including engineering controls, work practices, and respirators to be used;
- The contents of the OSHA Respirable Crystalline Silica Construction Standard;
- The identity of the Competent Person designated by Custom Electric; and
- The purpose and a description of the company's Medical Surveillance Program.

Custom Electric will make a copy of the OSHA Respirable Crystalline Silica Construction Standard readily available without cost to any employee who requests it.

Recordkeeping

Custom Electric will make and maintain an accurate record of all exposure measurements taken to assess employee exposure to Respirable Crystalline Silica. This record will include at least the following information:

- The date of measurement for each sample taken;
- The task monitored;
- Sampling and analytical methods used;
- Number, duration, and results of samples taken;

- Identity of the laboratory that performed the analysis;
- Type of personal protective equipment (PPE), such as respirators, worn by the employees monitored; and
- Name, social security number, and job classification of all employees represented by the monitoring, indicating which employees were actually monitored.

Custom Electric will ensure that exposure records are maintained and made available in accordance with 29 CFR 1910.1020. Exposure records will be kept for at least 30 years.

The employer shall make and maintain an accurate record of all objective data relied upon to comply with the requirements of the OSHA Respirable Crystalline Silica Construction Standard. This record shall include at least the following information:

- The Crystalline Silica-containing material in question;
- The source of the objective data;
- The testing protocol and results of testing;
- A description of the process, task, or activity on which the objective data were based; and
- Other data relevant to the process, task, activity, material, or exposures on which the objective data were based.

Custom Electric will ensure that objective data are maintained and made available in accordance with 29 CFR 1910.1020. Objective data records will be kept for at least 30 years.

Custom Electric will make and maintain an accurate record for each employee enrolled in the Medical Surveillance portion of this program. The record shall include the following information about the employee:

- Name and social security number;
- A copy of the PLHCPs' and/or Specialists' written medical opinions; and
- A copy of the information provided to the PLHCPs and Specialists.

Custom Electric will ensure that medical records are maintained and made available in accordance with 29 CFR 1910.1020. Medical records will be kept under lock and key for at least the duration of employment plus 30 years. It is necessary to keep these records for extended periods because Silica-related diseases such as cancer often cannot be detected until several decades after exposure. However, if an employee works for an employer for less than one year, the employer does not have to keep the medical records after employment ends, as long as the employer gives those records to the employee.

PROGRAM EVALUATION

This program will be reviewed and evaluated on an annual basis by the Custom Electric Management unless changes to operations, the OSHA Respirable Crystalline Silica Construction Standard (29 CFR 1926.1153), or another applicable OSHA Standard require an immediate re-validation of this program.

23.0B

Custom Electric Asbestos Safety Procedure

PURPOSE

The purpose of this policy is to outline the procedures established in order to effectively administer the Company guidelines regarding employee safety protocols for asbestos located at Custom Electric customer premises.

The practice of the Custom Electric is to take all practical steps to safeguard employees, customers, sub-contractors, and the general public from accidents and personal injuries and enforce the national emission standards for hazardous air pollutants for asbestos.

REGULATIONS

It is the intent of the corporation to comply with all applicable regulations including, but not limited to the following:

- 29 CFR 1910.1001
- 29 CFR 1926.1101
- EPA National Emissions Standard for Hazardous Air Pollutants (NESHAP)
- 40 CFR Part 61, Subparts A (General Provisions) and M (National Emission Standard for Asbestos)
- RCSA Section 19a-332a-1 to 19a-332-16 for Asbestos Abatement

RESPONSIBILITIES

Each project manager or their designee will be responsible for insuring all employees under their direction will receive the appropriate level of training for the tasks they are expected to perform prior to job assignment.

Each project manager will be responsible for insuring each employee receives the appropriate level of personal protection equipment prior to job assignment.

Each project manager will be responsible for maintaining a department training file that identifies the location of asbestos containing material within their job site and the training records. The project manager must forward a copy of the training records to the company headquarters for file.

Employees are required to utilize personal protective equipment and follow safe work practices when working with asbestos containing materials or materials presumed to contain asbestos.

Each project manager utilizing a contractor to perform work on or near asbestos containing material must obtain proof from the contractor that the personnel performing the work are qualified and aware of safe work practices.

All employees are responsible for becoming familiar with the terms in the definition section of this policy. When friable asbestos is found on job sites the project manager, supervisor or a designee shall contact the controlling employer to remove or encapsulate the asbestos..

At no time will a Custom Electric employee handle friable asbestos.

PROCEDURES

Asbestos may be encountered on customer job sites and premises. An outside contractor will conduct any tasks requiring asbestos activities.

A. Asbestos/Suspected Asbestos on Customer Premises:

1. If an employee encounters asbestos at a customer's premises, he or she is to determine if the asbestos/suspected asbestos must be interfered with to perform his or her duties. If the asbestos/suspected asbestos must be interfered with, the employee is to contact his/her supervisor.
2. Upon supervisor concurrence, the employee and supervisor shall notify the customer of the requirement for asbestos removal before the job is completed.

B. Permissible Exposure to Airborne Concentrations of Asbestos Fibers - The eight (8) hour time-

weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed 0.1 fibers, longer than five (5) micrometers, per cubic centimeter of air.

C. Ceiling Concentration Excursion Limit - No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of one fiber, longer than five (5) micrometers, per cubic centimeter of air over a sampling period of thirty (30) minutes.

D. Methods of Compliance - Engineering controls, such as, but not limited to, isolation, enclosed, exhaust ventilation, wet methods, and dust collection are used to meet the exposure limits.

E. Environmental Monitoring:

a. When samples are collected by customers at our jobsites by a designated testing laboratory from areas of the work environment the results of that testing will be shared with all affected Customer Electric workers.

b. Employee Observation of Monitoring - Affected employees are given a reasonable opportunity to observe any monitoring required and are able to have access to the records.

F. Caution Signs and Labels - The project managers are responsible for ensuring that signs and labels regarding asbestos locations within the jobsite are prominently posted.

EMPLOYEE INFORMATION AND REQUIRED TRAINING

A. Personal Protective Equipment Where Asbestos is present or suspected:

1. It is employee's responsibility to properly utilize personal protective equipment where asbestos is suspected or present, and to ensure the issued protective equipment is functional and stocked in assigned vehicles or locations.

2. Air Purifying Respirators - A reusable air purifying respirator is used when the ceiling or the eight (8) hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to be exceeded.

a. Employees are instructed on how to use the respirators in accordance with the requirements of the American National Standards Practices for Respiratory Protection, ANSI Z88.2-1969 (refer to Section VI.B.3).

b. No employee is assigned to tasks requiring the use of respirators if, based upon medical examination it is determined the employee is unable to function normally wearing a respirator, or that the safety or health of the employee will be impaired by his or her use of a respirator. (Reference Policy No. 478.02)

3. Protective Clothing - Disposable coveralls or similar whole body clothing, head coverings, gloves, and foot coverings are provided by contractors to employees who will be exposed to asbestos. Contaminated clothing is transported by the contractor to an approved hazardous waste dumpsite in sealed impermeable bags, or other closed impermeable containers, and labeled in accordance with EPA hazardous waste regulations pertaining to asbestos.

B. Any employee of Custom Electric would require training if they work on or around:

1. Asbestos insulated equipment at any customer job site.

2. Asbestos insulated equipment at customers' facilities or at some part of the conduit system.

3. Pumps/machinery that may cause exposure to disintegrating asbestos gaskets.

4. Vehicle maintenance

C. This training session must cover the following areas:

1. Description of Asbestos:

a. Appearance and properties

b. Identification of locations in the power plant

c. Interpreting sample results

2. Health Effects of Asbestos:

a. Description of respiration

b. Routes of asbestos exposure

c. Possible health effects of asbestos exposure including the synergistic effects of smoking

d. Latency period of diseases

3. Worker Protection:
 - a. Protective clothing purpose, use and limitations (including demonstration of how to suit up properly)
 - b. Respirators:
 1. Comparison of various types
 2. Positive vs. negative pressure
 3. Inspection of respirators: cleaning and storage
 4. Respirator fitting
4. Legal Aspects:
 - a. OSHA Standards
 - b. Worker compensation and access to medical and air-sampling data
 - c. Right-to-know law
5. Procedures for discovering, handling, removing, and disposing of asbestos at the work site, including engineering and work practices.
6. Initial Training

An employee's initial training must be provided prior to assignment in an area that would have asbestos exposure or whenever a change in procedures or equipment would cause exposure. The responsibility for providing this training lies with each department supervisor or their designee for the department concerned. The responsible department must maintain records and instructor notes for each training session. A training file will be maintained at Custom Electric headquarters.

ENFORCEMENT

Custom Electric's Asbestos Program will be implemented, updated and supervised by the Company President. Project Managers and supervisors will be responsible for implementing all provisions of the Asbestos Program and ensuring they are met within each project team. Affected project teams will be audited by our safety manager to determine its compliance with the Law and with existing Custom Electric policies. Any employee knowingly violating any safety procedure will be subject to disciplinary action under the Custom Electric Discipline Policy.

DEFINITIONS

Aggressive method means removal or disturbance of building material by sanding, abrading, grinding or other method that breaks, crumbles, or disintegrates intact ACM.

Amended water means water to which surfactant (wetting agent) has been added to increase the ability of the liquid to penetrate ACM.

Asbestos includes chrysotile, amosite, crocidolite, tremolite asbestos, anthophyllite asbestos, actinolite asbestos, and any of these minerals that has been chemically treated and/or altered. For purposes of this standard, "asbestos" includes PACM, as defined below.

Asbestos-containing material (ACM), means any material containing more than one percent asbestos.

Assistant Secretary means the Assistant Secretary of Labor for Occupational Safety and Health, U.S. Department of Labor, or designee.

Authorized person means any person authorized by the employer and required by work duties to be present in regulated areas.

Building/facility owner is the legal entity, including a lessee, which exercises control over management and record keeping functions relating to a building and/or facility in which activities covered by this standard take place.

Certified Industrial Hygienist (CIH) means one certified in the practice of industrial hygiene by the American Board of Industrial Hygiene.

Class I asbestos work means activities involving the removal of TSI and surfacing ACM and PACM.

Class II asbestos work means activities involving the removal of ACM which is not thermal system insulation or surfacing material. This includes, but is not limited to, the removal of asbestos-containing wallboard, floor tile and sheeting, roofing and siding shingles, and construction mastics.

Class III asbestos work means repair and maintenance operations, where "ACM", including TSI and surfacing ACM and PACM, is likely to be disturbed.

Class IV asbestos work means maintenance and custodial activities during which employees contact but do not disturb ACM or PACM and activities to clean up dust, waste and debris resulting from Class I, II,

and III activities.

Clean room means an uncontaminated room having facilities for the storage of employees' street clothing and uncontaminated materials and equipment.

Closely resemble means that the major workplace conditions which have contributed to the levels of historic asbestos exposure, are no more protective than conditions of the current workplace.

DEFINITIONS (cont.)

Competent person means, in addition to the definition in 29 CFR §1926.32 (f), one who is capable of identifying existing asbestos hazards in the workplace and selecting the appropriate control strategy for asbestos exposure, who has the authority to take prompt corrective measures to eliminate them, as specified in 29 CFR §1926.32(f): in addition, for Class I and Class II work who is specially trained in a training course which meets the criteria of EPA's Model Accreditation Plan (40 CFR 763) for supervisor, or its equivalent and, for Class III and Class IV work, who is trained in a manner consistent with EPA requirements for training of local education agency maintenance and custodial staff as set forth at 40 CFR 763.92 (a)(2).

Critical barrier means one or more layers of plastic sealed over all openings into a work area or any other similarly placed physical barrier sufficient to prevent airborne asbestos in a work area from migrating to an adjacent area.

Decontamination area means an enclosed area adjacent and connected to the regulated area and consisting of an equipment room, shower area, and clean room, which is used for the decontamination of workers, materials, and equipment that are contaminated with asbestos.

Demolition means the wrecking or taking out of any load-supporting structural member and any related razing, removing, or stripping of asbestos products.

Director means the Director, National Institute for Occupational Safety and Health, U.S. Department of Health and Human Services, or designee.

Disturbance means activities that disrupt the matrix of ACM or PACM, crumble or pulverize ACM or PACM, or generate visible debris from ACM or PACM. Disturbance includes cutting away small amounts of ACM and PACM, no greater than the amount which can be contained in one standard sized glove bag or waste bag in order to access a building component. In no event shall the amount of ACM or PACM so disturbed exceed that which can be contained in one glove bag or waste bag which shall not exceed 60 inches in length and width.

Employee exposure means that exposure to airborne asbestos that would occur if the employee were not using respiratory protective equipment.

Equipment room (change room) means a contaminated room located within the decontamination area that is supplied with impermeable bags or containers for the disposal of contaminated protective clothing and equipment.

Fiber means a particulate form of asbestos, 5 micrometers or longer, with a length-to-diameter ratio of at least 3 to 1.

Glovebag means not more than a 60 × 60 inch impervious plastic bag-like enclosure affixed around an asbestos-containing material, with glove-like appendages through which material and tools may be handled.

High-efficiency particulate air (HEPA) filter means a filter capable of trapping and retaining at least 99.97 percent of all mono-dispersed particles of 0.3 micrometers in diameter.

Homogeneous area means an area of surfacing material or thermal system insulation that is uniform in color and texture.

Industrial hygienist means a professional qualified by education, training, and experience to anticipate, recognize, evaluate and develop controls for occupational health hazards.

Intact means that the ACM has not crumbled, been pulverized, or otherwise deteriorated so that the asbestos is no longer likely to be bound with its matrix.

Modification for purposes of paragraph (g)(6)(ii), means a changed or altered procedure, material or component of a control system, which replaces a procedure, material or component of a required system. Omitting a procedure or component, or reducing or diminishing the stringency or strength of a material or component of the control system is not a modification for purposes of paragraph (g)(6) of this section.

Negative Initial Exposure Assessment means a demonstration by the employer, which complies with the criteria in paragraph (f)(2)(iii) of this section, that employee exposure during an operation is expected to be consistently below the PELs.

PACM means "presumed asbestos containing material".

Presumed Asbestos Containing Material means thermal system insulation and surfacing material found in buildings constructed no later than 1980. The designation of a material as "PACM" may be rebutted pursuant to paragraph (k)(5) of this section.

Project Designer means a person who has successfully completed the training requirements for an abatement project designer established by 40 U.S.C. Sec. 763.90(g).

Regulated area means: an area established by the employer to demarcate areas where Class I, II, and III asbestos work is conducted, and any adjoining area where debris and waste from such asbestos work accumulate; and a work area within which airborne concentrations of asbestos, exceed or there is a reasonable possibility they may exceed the permissible exposure limit. Requirements for regulated areas are set out in paragraph (e) of this section.

Removal means all operations where ACM and/or PACM is taken out or stripped from structures or substrates, and includes demolition operations.

Renovation means the modifying of any existing structure, or portion thereof.

Repair means overhauling, rebuilding, reconstructing, or reconditioning of structures or substrates, including encapsulation or other repair of ACM or PACM attached to structures or substrates.

Surfacing material means material that is sprayed, troweled-on or otherwise applied to surfaces (such as acoustical plaster on ceilings and fireproofing materials on structural members, or other materials on surfaces for acoustical, fireproofing, and other purposes).

Surfacing ACM means surfacing material that contains more than 1% asbestos.

Thermal system insulation (TSI) means ACM applied to pipes, fittings, boilers, breeching, tanks, ducts or other structural components to prevent heat loss or gain.

Thermal system insulation ACM is thermal system insulation, which contains more than 1% asbestos.

Departmental Safety Training Record
(Filed as Required by Policy)

Date of Training _____ Time _____ Instructor _____
Topic _____ Location _____
Content of Session _____ Tape ☐ Pamphlets _____ Other ☐
Explanation _____
Attendees _____

Print Name	Signature	Employee No.
1. _____		
2. _____		
3. _____		
4. _____		
5. _____		
6. _____		
7. _____		
8. _____		
9. _____		
10. _____		
11. _____		
12. _____		
13. _____		
14. _____		
15. _____		

Appendix

24.0

Accident 1st Report Form

Note: The immediate supervisor of the employee involved in the accident must fill out this accident report as soon as possible after the occurrence of the accident. Fax/Email this form to Custom Electric's main office.

Employee Name:		Date & Time of Accident:	
Employee Telephone:		Date of Birth:	
Employee Address:			
Department:	Job Title:	☐ Temp Hire	
Location of Accident:			
Description of Accident:			
Did outside agencies respond to the scene ☐ Yes ☐ No	Did you take pictures ☐ Yes (include with report) ☐ No	☐ Fire ☐ EMS ☐ Police ☐ OSHA Name of OSHA Officer:	
Was the employee transported to hospital ☐ Yes How: _____ ☐ No		Medical Treatment for Employee: (answer none if none)	
Clinic/Hospital/Physician (name/address/phone)			
Did Injury Cause Lost Work Time? ☐ Yes ☐ No	First Lost Day:	Date Returned:	
Report completed by:			
Signature:			

24.0			
Accident Investigation Form			
Date of Incident		Time of Incident AM/PM	
Employee Name		Employee Address	
Employee Phone		Supervisor	Department
Job performing at time of Incident			
TREATMENT			
Date/Time of Treatment		Treatment Provided By	
Treatment Facility Name/Address			
☐ Near Miss ☐ Injury	☐ Recordable ☐ Reportable	☐ First Aid ☐ Illness ☐ Fatality ☐ Workers' Comp	☐ Lost Workday (#Days): ☐ Restricted Workday (# Days):
LOSS ANALYSIS CLASSIFICATION (use coding system on back of this sheet)			
Incident Type	Incident Source	Injury/Illness Type	
Shift	Age group	Body Part or System	
Department	Day of Week	Injury/Illness Type	
Hours/Week	Experience on the Job	Body Part or System	
Incident Description (Include Individuals, Location, Equipment, Materials, Safety Devices, and Personal Protective Equipment, Emergency Responders)			
Immediate Causes			
Temporary Precautions Taken			
Corrective Actions			
Supervisor:			
Report Completed by:			

SEX

1. Male
2. Female

SHIFTS

1. 7–3
2. 3–11
3. 11–7

EXPERIENCE ON THE JOB

1. 0–6 Months
2. 6–12 Months
3. 1–2 Years
4. 2–5 Years
5. 5–10 Years
6. 10–20 Years
7. 20 Years +

DEPARTMENT

1. Housekeeping
2. Materials Handling
3. Maintenance
4. Utilities
5. Office Services
6. Personnel
7. Sales
8. Marketing
9. Payroll
10. Accounting
11. Shipping
12. Other

HOURS WORKED PER WEEK

1. Under 40
2. 40–48
3. 48–60
4. Over 60

INCIDENT TYPE

1. Struck–By
2. Struck–Against
3. Caught–In/On/Between
4. Foot–Level–Fall
5. Fall–To–Below
6. Over–Exertion
7. Contact–With
8. Exposure

INCIDENT SOURCE

1. Containers
2. Confined Spaces
3. Furniture, Fixtures
4. Grass Items
5. Hand Tools
6. Hoisting Apparatus
7. Ladder/Scaffold
8. Walking/Working Surfaces
9. Material Handling
10. Vehicles
11. Process Equipment
12. Packaging Equipment
13. Other Equipment
14. Chemical Solid

15. Chemical Liquid
16. Chemical Gas
17. Clothing
18. Products of Combustion
19. Finished Products
20. Raw Materials
21. Miscellaneous Materials
- 22.

Animal/Insect/Reptile/Person

23. Plants
24. Electrical Energy
25. Thermal Energy
26. Hydraulic Energy
27. Pneumatic Energy
28. Radiation Energy
29. Mechanical Energy

BASIC CAUSE

1. Inadequate Knowledge/Training
2. Inadequate Employee Selection/Placement
3. Inadequate Supervision
4. Inadequate Engineering Practices
5. Inadequate Personal Protective Equipment
6. Inadequate Inspection/Maintenance Programs
7. Purchasing Inadequate/Inferior Equipment
8. Inadequate Feedback Systems
9. Inadequate Standards/Practices

AGE

1. 18–25
2. 26–33
3. 34–41
4. 42–49
5. 50–57
6. 58–65
7. 66 Years +

DAY OF WEEK

1. Monday
2. Tuesday
3. Wednesday
4. Thursday
5. Friday
6. Saturday
7. Sunday

YEARS OF SERVICE

1. 0–6 Months
2. 6–12 Months
3. 1–2 Years
4. 2–5 Years
5. 5–10 Years
6. 10–20 Years

7. 20 Years +

INJURY/ILLNESS TYPE

1. Abrasion
2. Puncture
3. Laceration
4. Crushing
5. Amputation
6. Burn (Thermal)
7. Burn (Chemical)
8. Concussion
9. Contusion
10. Dislocation
11. Fracture
12. Electric Shock
13. Heat Stress
14. Cold Stress
15. Hernia
16. Strains
17. Sprains
18. Multiple Injuries
19. Foreign Object
20. Skin Diseases
21. Dust Diseases- Lung
22. Resp. Conditions Due to Toxic Agents
23. Poisoning
24. Disorders Due to Physical Agents
25. Disorders Associated with Repeated Trauma
26. All Other Occupational Illnesses

BODY PART OR SYSTEM

1. Scalp/Skull
2. Ear
3. Eye
4. Face
5. Neck
6. Back
7. Chest
8. Shoulder
9. Abdomen
10. Hips
11. Genitalia
12. Trunk
13. Thigh/Knee/Leg
14. Ankle/Foot/Toes
15. Arm/Elbow/Forearm
16. Wrist
17. Hand
18. Fingers
19. Respiratory System
20. Cardiovascular System
21. Nervous System
22. Excretory System
23. Digestive System
24. Skin
25. Teeth/Mouth
26. Multiple



JOB-HAZARD ANALYSIS

Project Name: _____ Date: _____

Project #: _____ Location: _____ Foreman: _____

Job Description: _____

EMPLOYEES	1) _____	2) _____	3) _____	4) _____
	5) _____	6) _____	7) _____	8) _____
	9) _____	10) _____	11) _____	12) _____

EQUIPMENT	☐ Hard Hat	☐ Face Shield	☐ Gloves (Electrical)	☐ FR Clothing	☐ Personal Fall Arrest
	☐ Safety Glasses	☐ Hearing Protection	☐ Gloves (General Use)	☐ EH Rated Footwear	☐ Other _____
	☐ Safety Goggles	☐ High Visibility Vest	☐ Gloves (Cut Resistant)	☐ Respiratory Protection	☐ Other _____

STEPS OF TASK	HAZARDS FOR EACH TASK	CONTROLS FOR EACH HAZARD
☐ Installation, maintenance or service of electrical equipment	☐ Electrical contact/burns/arc flash	☐ Lockout/Tagout (LOTO) ☐ Energized Electrical Work Permit
☐ Lifts ☐ Ladder Use	☐ Falls ☐ Trips at access point ☐ Striking objects from lift	☐ Use 3-points of contact ☐ Right type and size ladder ☐ Base of ladder clear of trip hazards ☐ Spotter used to move lift ☐ Tie off above 6 feet
☐ Work at Heights	☐ Back & shoulder strains ☐ Struck by/caught in between ☐ Slips & trips ☐ Awkward posture	☐ Use mechanical aids ☐ Use proper lifting techniques ☐ Ensure travel path is clear ☐ Capture waste material at source ☐ Use two-person lifts (above 75 lbs)
☐ Manual Material Handling	☐ Dropped Load ☐ Struck By ☐ Equipment Failure	☐ Proper licensing/training ☐ Avoid body parts between objects ☐ Inspect rigging equipment
☐ Tool Use	☐ Pinch points ☐ Cuts/lacerations ☐ Missing or damaged safety devices	☐ Inspect tools for defects
☐ Confined Space Work	☐ Hazardous atmospheres	☐ Monitor and record air samples ☐ Entrants in full body harness, rescue equipment set up/available
☐ Hoisting Operations	☐ Falls from elevations	☐ Personal fall arrest system to prevent striking lower level/objects
☐ Excavations	☐ Engulfment	☐ If >4' in depth, must have a ladder/ramp for access every 50' ☐ If >5' in depth, sides must be sloped, shored or benched

☐ Other (Describe):	☐ Other (Describe):	☐ Other (Describe):
--	--	--

27.0 Scissor Lifts Field Checklist

Type of Vehicle / Equipment	☐ Rented ☐ Company Owned	Rental Company (if applicable)
Make/Model/Serial Number	Location of Use	
<i>Prior to initial use the operator or supervisor must contact their designated trainer to ensure that this initial Field Training Checklist has been completed. The supervisor has the overall responsibility to ensure employees receive appropriate safety training and follow the rules established during all activities involving this equipment.</i>		
✓	Safety Requirements Covered	
	The operator/users read and understand the manufacturer's manuals	
	Verify the equipment has been properly serviced/maintained according to the manufacture's manuals	
	Operator/users thoroughly trained and qualified in the use of this equipment	
	Operator/users understand all labels, warnings and instructions on the equipment	
	Operator/users practice with the equipment (if unfamiliar) until comfortable/proficient with its operation	
	Operator/users have the appropriate personal protective equipment for the conditions under which the platform will be operated (i.e. fall protection, hard hats)	
	<i>If harness/lanyards are required, ensure employees have been trained in the use and limitations using the Fall Arrest Harnesses and Lanyards.</i>	

✓	Prior to each use, or at the beginning of the work shift, operator/users must check for:
	The lift controls are in safe working condition (functional test).
	The lift platform does not have any fluid leaks, loose parts, structural damage, cracked welds, or other unsafe conditions.
	The tires do not have cuts, bulges, or embedded objects. Ensure recommended amount of air pressure in the tires.
	There are no leaks or damage in the air, hydraulic fluid, and fuel system hoses and lines. Ensure secure connections of fittings and that there are no kinks.
	The wiring is not chafed, worn, or damaged.
	The guardrails, gates, or other safety devices are in place and secure, and have no cracked welds or missing sections.
	The outriggers/stabilizers operate properly.
	That the equipment has not been field modified – unless the modification has been certified in writing by the manufacturer or by any other equivalent entity, such as nationally recognized testing laboratory, to be in conformity with all applicable provisions of ANSI A92.2-1969 and this section and to be at least as same as the equipment before modification.
	All placards, markings, operating control markings, and warning signs are readable. • Make and model of the lift • Rated workload capacity / rated number of occupants • Maximum platform height • Maximum operating pressure of the hydraulic system

By signing this document, I confirm that I have completed this Field Checklist, and have received training on Scissor Lifts and the use of the equipment noted above. I will not use/operate any Scissor Lift or a fall arrest system (harness/lanyard) without adequate training and knowledge of how to safely use the equipment.

	Name (Print)	Name (Signature)	Date
Operator/User			
Operator/User			
Operator/User			

28.0 Daily Lull Checklist

Inspected Area	Yes	No	N/A	Corrective Action
Water/Fluid leaks or puddles				
Tires OK				
Forks adjusted correctly/locked/not cracked				
Chains lubricated				
Seat secured				
Seat belt operational				
Horn working				
Lights working				
Water temp OK				
Hydraulic Fluid level OK				
Battery Charge OK				
Engine Oil OK				
Hoses/Cables OK				
Propane Tank Secured				
Fuel Tank filled				
All placards legible				
Operators manual onboard				
Lift chart legible				
Lift Controls Working				
Tilt Controls Working				
Boom Controls Working				
Leveler Controls Working				
Parking Brake OK				
Service Brake OK				
Steering OK				

By signing this document I confirm that I have completed the inspection of this vehicle in its entirety according to this checklist, and I have received operator safety training on the use of this Powered Industrial Truck.

Inspected By:	Date

29.0 HARNESS INSPECTION

Inspector: _____
 Manufacturer: _____
 Model Number: _____

Inspection Date: /____/____
 Harness Number: _____
 Serial Number: _____
 Date Into Service: _____

**IF INSPECTION REVEALS ANY FAILURES, REMOVE UNIT FROM SERVICE
 IMMEDIATELY AND CONTACT HEALTH AND SAFETY**

INSPECTION	PASS	FAIL	COMMENTS
BUCKLES & D-Rings			
Not broken			
No distortion			
No sharp edges			
No burrs			
No cracks			
No signs of wear			
Corrosion free			
Work freely			
BACK PAD			
Not torn			
WEBBING			
No cuts 1/8 th inch or greater			
Free of frayed fibers			
Free of broken fibers			
No tears			
Pulled Threads			
Broken stitches, 2 or more			
No abrasion			
Mold free			
No burns holes 1/16 th "or larger			
No discoloration			
Clean: oil free, no paint chemical damage			
LABELS & TAGS			
Legible/clearly marked			

I certify that I have inspected the above piece of equipment and find it to be in working order and without defects.

Signature: _____

30.0 LANYARD INSPECTION

Inspector: _____
 Manufacture: _____
 Model Number: _____

Inspection Date: / / Lanyard
 Number: _____
 Serial Number: _____
 Date Into Service: _____

**IF INSPECTION REVEALS ANY FAILURES, REMOVE UNIT FROM SERVICE
 IMMEDIATELY AND CONTACT HEALTH AND SAFETY**

INSPECTION	PASS	FAIL	COMMENTS
WEBBING			
No cuts 1/8 th inch or greater			
Free of frayed fibers			
Free of broken fibers			
No tears			
Pulled Threads			
Broken stitches, 2 or more			
No abrasion			
Mold free			
No burns holes 1/16 th "or larger			
No discoloration			
Clean: oil free, no paint chemical damage			
DECELERATION/SHOCK ABSORBER			
Housing intact			
No signs of impact load or deployment			
LABELS & TAGS			
Clearly marked/legible			
CARABINEER/SNAP HOOKS			
Work freely			
Not broken			
No distortion			
No sharp edges			
No burrs			
No cracks			
No signs of wear			
Corrosion free			
Self locking, closing			

I certify that I have inspected the above piece of equipment and find it to be in working order and without defects.

Signature: _____

31.0 Ladder Safety Inspection Form

Ladder ID:	Location:	Ladder Type: ____ Step ____ Extension ____ Fiberglass ____ Aluminum
Inspector:	Date:	

ITEM	PASS	FAIL	N/A
Ladder has a unique ID and identifies its owner.			
Manufacturer's safety stickers are present and legible. Ladder is clearly identified as to Type (I, IA, II) and load limit.			
Check for bends, splits, cracks, field modifications*, slippery materials, corrosion, or other defects:			
Side Rails:			
Steps/rungs: Top			
step:			
Defects: no sharp edges, splinters, burrs, gouges or field modifications*.			
Welds are factory original with no cracks or damage.			
Crimps/swages are not loose, cracked, or damaged.			
Nuts/bolts are intact, tight, and not stripped or damaged.			
Locks/Spreaders/Hardware: all moving parts operate normally, are adequately lubricated, and are not deformed, defective or damaged.			
Metal components: are factory original or OEM replacements with no excessive/penetrating rust or corrosion.			
Wooden components: no shake, check, wane, compression, rot/decay.			
Coverings: Wooden components have no paint, stain or covering which interferes with visualizing the wood grain.			
<i>Portable ladders</i>			
Stepladder back braces are without cracks/defects/deformities, and show no evidence of having been used for climbing			
Rivets: heads and crimps are tight and not damaged.			
Non-slip rubber feet are present and in good condition.			
Rope/pulley: rope not excessively frayed/worn, pulley operates freely.			
Ladder levels are in good working condition and operate properly.			
<i>Fixed Ladders</i>			
Grab bars extend at least 3' above point of departure			
Cage protects ladders with at least 20' run, from 3' above point of departure to within 8' of floor,			
Cage is without penetrating rust/corrosion, and all welds are intact.			

** field modifications include things like drilled holes, screwed-on tool holders, or any change not authorized by the manufacturer*

DISPOSITION FOLLOWING INSPECTION:

- Remains in service

Out of service for repair, tagged "DANGER, do not use." Out of service, tagged "do not use," to be destroyed

Destroyed on _____ by _____

Date

Print Name

32.0 SRL INSPECTION

Inspector: _____
 Manufacture: _____
 Model Number: _____

Inspection Date: ____/____/____
 SRL Number: _____
 Serial Number: _____
 Date Into Service: _____

IF INSPECTION REVEALS ANY FAILURES, REMOVE UNIT FROM SERVICE IMMEDIATELY AND CONTACT HEALTH AND SAFETY

INSPECTION	PASS	FAIL	COMMENTS
LABELS & TAGS			
Legible/clearly marked			
HOUSING			
No Cracks in casing			
Impact Load indicator intact			
Hook anchor point OK			
CARABINEER/SNAP HOOKS			
Work freely			
Not broken			
No distortion			
No sharp edges			
No burrs			
No cracks			
No signs of wear			
Corrosion free			
Self locking, closing			
CABLE or WEB LANYARD			
Entire length inspected			
Web-no cuts abrasions etc			
Cable-no broken strands, crushed sections, bird-caging			
Connection point to hook OK			
Freely retracts into housing			

I certify that I have inspected the above piece of equipment and find it to be in working order and without defects.

Signature: _____

33.0 Competent Person Scaffold Inspection Checklist

Company: _____ Location: _____ Date: _____
Time: _____ Comp-Person: _____

General Safety Requirements	Yes	No
Has the scaffold been constructed and loaded in accordance with the design of a qualified person and safety factor of 4 to 1?		
Has the maximum load capacity of this scaffold communicated to all employees?		
Is the load on the scaffold (including point loading) within the maximum load capacity of this particular scaffold?		
Are scaffolds and scaffold components inspected before each work shift by a competent person?		
Have employees who erect, disassemble, move, operate, repair, maintain, or inspect the scaffold been trained by a <i>competent person</i> to recognize the hazards associated with this type of scaffold and the performance of their duties related to this scaffold?		
Have employees who use the scaffold been trained by a qualified person to recognize the hazards associated with this scaffold and know the performance of their duties relating to it?		
Is the scaffold plumb, square, and level?		
Are all working platforms fully planked? (With less than 1" between planks or between planks and uprights)		
Where the employer can demonstrate the necessity, is the gap between the last plank and the uprights less than 9 ½ inches?		
Are all working platforms at least 18 inches wide?		
Are the planks overlapped over supports?		
Are all abutted planks resting on separate support surfaces?		
Do planks extend at least 6 inches and no more than 12 inches over the supports?		
Are the planks in good condition and free of visible defects?		
Are the tops and bottom surfaces of scaffold planks visible and free from paint or other opaque coverages?		
Does the scaffold have all required guardrails and toeboards?		
Are the open sides of the scaffold less than 14 inches from the face of the work?		

If open sides are more than 14 inches from the face of the work, is there proper fall protection available?		
Are platforms either extending over the centerlines of their supports by at least 6 inches or cleated, or restrained by hooks?		
Where the platform is less than 10 feet long and extends more than 12 inches over the support, have guardrails been installed?		
Where the platforms are more than 10 feet long, do they not extend more than 18 inches over the supports?		
Where scaffold components from different manufacturers are used, do they fit together without force and has their use been determined to be safe by a competent person?		
Has a Competent Person approved any use of dissimilar metals?		
Are 4:1 (height to width) scaffolds secured to a building or structure as required?		
Have ties been installed at a horizontal member that supports the inner and outer legs?		
Has the first vertical tie been installed at a height less than 4 times the minimum base dimension?		
Have vertical ties been repeated every 20 feet or less for scaffolds that are 3 feet or less in width?		
Are ties installed at each end of the scaffold structure and at no more than 30 foot horizontal intervals		
Are scaffolds erected on firm foundations?		
Is the scaffold on base plates and are mudsills level, sound, and rigid?		
Are footings able to support at least 4 times the maximum intended load without settling? (Beware of frozen/thawing ground)		

Scaffold Use	Yes	No
Are scaffolds and components loaded within their rated capacities?		
Has the scaffold been inspected by a competent person as required?		
Have scaffolds which are occupied been prohibited from movement?		
Do scaffolds meet the clearance requirements from power lines?		
Are slippery conditions on scaffolds corrected before workers are permitted to use them?		
Where stormy conditions or high winds exist, has the competent person been consulted and wind screen or personal fall arrest systems been put to use?		
Are the scaffolds kept free from debris?		

Access	Yes	No
Is safe access provided for all scaffold platforms that are more than 2 feet above or below the point of access?		
Has climbing cross braces been prohibited?		
Have ladders been positioned so as not to tip the scaffold?		
Is the bottom rung of the ladder less than 24 inches above the supporting surface?		

Fall Protection	Yes	No
Are guardrails, including midrails installed on all open sides and open ends of the platform?		
Are guardrails, installed at a height of between 36" and 45"?		
Does the guardrail system meet the necessary strength requirements?		
Have toeboards been installed to prevent objects from falling from scaffolds?		
Where necessary, have screens been installed to protect worker from falling objects?		
Are toeboards at least 3 ½ inches high?		
Has the general public been adequately protected?		

Scaffolds Checklist

Date Prepared: _____

By: _____

Project Name/No. _____

Location: _____

Check the box if the statement is true.

Fill in the blanks where the appears.

Citations in brackets are from the Code of Federal Regulations 29 CFR 1926.

HAZARD IDENTIFICATION

The company has a written Accident Prevention Program that meets OSHA requirements. It includes identification of potential scaffold safety hazards on the site, regular inspections, accident investigation, and correction of hazardous conditions. [1926.21(b)]

USE OF SCAFFOLDS

No scaffolds are necessary on this job because all of the following are true: (1) the work is of a limited nature and short duration; (2) the fall distance is less than 15 feet; (3) adequate risk control exists; and (4) the work is under competent supervision.

No scaffolds are necessary on this job because all of the following are true: (1) the work is of short duration;
(2) the work is on joists or similar members; and (3) the joists are centered 2 feet or closer with planking at least 12" wide.

Scaffolds are used. There is no permanent/solid construction at least 20" wide to stand on, and the work can't be done safely from ladders.

THE QUALIFIED PERSON

The qualified person has a certificate of competence in scaffold erection, dismantling, and use, issued by a trade association or state approved apprenticeship program. **Or** the qualified person has been identified by the company based on other experience or training, and is familiar with the operations to be performed and the hazards involved.

Name of qualified person: _____

Scaffolds are tagged to show that the qualified person has met his or her responsibilities.

PROHIBITED SCAFFOLDS

No lean-to or jack
scaffolds. No shore
scaffolds.

No nailed brackets.

No loose tile, brick, or blocks used in place of a
scaffold. No stilts.

DESIGN OF THE SCAFFOLD

Any wooden pole scaffold over 60 feet is designed by a registered civil engineer. [1643]
Any tube and coupler scaffold over 125 feet is designed by a registered civil engineer.
[1644(b)(5)] Any tubular welded frame scaffold over 125 feet is designated by a registered
civil engineer.

If an engineer designed the scaffold, the drawings are on site during the erection of the scaffold.
[1637(k)(2)] Single or tiered horse scaffolds are not over 10 feet high. [1647(e)(1)]

MATERIALS AND PLANKING

The scaffold uses stress grade lumber (or metal such as aluminum if structural integrity is maintained).
[1637(b)] The wood is not cracked, warped, knotted, or defective. [1637(d)]

All lumber is visually inspected for defects before and during use. No defective lumber is used.

[1637(h)] The planking is at least 2" x 10" scaffold grade plank. [1637(f)(1)]

The 2" x 10" spans no more than 10 feet if the working load is 25 pounds per square foot (light trades). It
spans no more than 8 feet if the load is 50 psf (medium trades), or 7 feet for 75 psf (heavy trades).

[1637(f)(2)] Manufactured planks longer than 10 feet are labeled with their maximum load. [1637(f)(3)]

The platforms are planked solid, except open area under the back railing. [1640(b)(5)(A) and
1644(a)(7)] Planks don't overhang their support by more than 18 inches unless access is prevented by
a barrier. [1637(g)] Metal is not rusted or corroded.

Nails are not smaller than 8-penny. [1637(i)(4)]

Bolts are of a size and in sufficient number at each connection to develop the designed strength of the
scaffold. [1637(r) and Plate B-31 in Appendix]

EXTENSION PLANKING:

Has 5 fingers on each side and is at least 1" x 2-1/8" select straight-grained Douglas fir or
equivalent. [1637(e)(1)]

Is not longer than 12½ feet, with overlap between the 2 halves not less than 1/8 the length of the
extended planking. A substantial stop is provided to maintain this overlap. [1637(e)(2)]

Is not used as a platform on ladder-jack, suspended, or other unstable scaffolds. [1637(e)(4)]

ERECTION AND DISMANTLING OF THE SCAFFOLD

Each level is maintained plumb.

Scaffolds are built from the bottom up and dismantled from the top down. [1637(k)(3) and (4)]

The scaffold is secured to the structure during erection. Ties to the structure are installed as soon as the scaffold is completed to each tie-in area. [1637(k)(3)]

The scaffold is secured to the structure during dismantling. Ties are removed only as the work progresses downward, unless other methods are used to prevent the scaffold from falling over.

The Scaffold is secured to the structure during dismantling. Ties are removed only as the work progresses downward, unless other methods are used to prevent the scaffold from falling over. [1637(k)(4)]

When dismantling, structural members are not removed below the level being dismantled.

[1637(k)(5)]

If platforms are sloped, the slope is no more than 2 feet vertical to 10 feet horizontal. Platforms are also secured so they can't slip from supports. [1637(o)]

When a platform turns a corner, planks are laid so as to avoid tipping. [1637(t)]

INTEGRITY OF SCAFFOLD

Braces, uprights, or supports are not removed unless other members of equivalent strength are substituted. [1637(l)]

The scaffold is not overloaded. [1637(m)]

Planks are capable of sustaining the load.

[1637(f)(4)] The scaffold is tied off and secure.

[1637(c)]

ACCESS

There are safe, unblocked means of access to all scaffold platforms (such as a ladder, walkway, or stairs). [1637(n)(1)]

Ladders or stairways are located so as not to make the scaffold unstable. [1637(n)(2)]

If a ladder is used for access, it is securely attached to the scaffold and extends at least 3 feet above the platform level. [1637(n)(2)(A)]

GUARDRAILS

There are top rails, between 42" and 45" high, for all open sides and ends that are 7½ feet high or more.

Rails are constructed of 2" x 4", double 1" x 4", or equivalent. [1620(a) and (c)]

There are midrails halfway between the work platform and the guardrail. Midrails are constructed of at least 1" x 6" or equivalent. [1620(a) and (c)]

There are vertical posts spaced at 8 foot intervals or closer. Posts are constructed of 2" x 4" or equivalent. [1620(b)]

Guardrails will withstand at least 13 pounds per linear foot. [1620(f)]

There are toeboards at least 4 inches high on all open sides and ends of platforms if there are workers below. If material is piled high, there are also panels or screens. [1621(b) and (c)]

Overhand bricklaying 1926.451(g)(1)(vi)

Each employee performing overhand bricklaying operations from a supported scaffold shall be protected from falling from all open sides and ends of the scaffold (except at the side next to the wall being laid) by the use of a personal fall arrest system or guardrail system (with minimum 200 pound toprail capacity).

WORKING ON THE COMPLETED SCAFFOLD

No one is permitted to work on a scaffold in slippery conditions (unless a necessary part of work).

[1637(p)] There is protection from overhead hazards. [1637(q)]

Only one person at a time may work on extension planking over 3 feet high. [1637(e)(3)]

WOODEN POLE SCAFFOLDS—HEAVY TRADES

A wooden pole scaffold meets the Cal/OSHA requirements below for **heavy trades** if it is used by bricklayers, stonemasons, concrete workers, or other trades using heavy tools or materials. [1641(a)] The load on this scaffold, including workers, does not exceed 75 pounds per square foot. [1504]

Uprights are a minimum of 4" by 4" lumber for scaffolds of 20 feet or less. For scaffolds over 20 feet, uprights are at least 4" by 6". Uprights are spaced no more than 7 feet apart in the direction parallel to the wall, and are secured against slippage. If the uprights are placed on the earth, they are secured to a wooden base at least 2" x 10" x 10". [1641(c)]

Platforms are not more than 4 feet wide, and are made from at least 2" x 10" lumber, laid closely together. They are within 14" of the face of the building (7" for bricklayers and stonemasons). Platforms are supported by ledgers and ribbons, nailed or bolted to the uprights. Planks are either butt-ended and nailed to the ledgers, or they overlap the ledgers at each end by at least 6". A plank does not overlap an unsupported end of another plank. [1641(d) and (g)]

Scaffolds are rigidly tied to the building or structure by means of a double looped No. 12 iron wire, or single looped No. 10 iron wire, or equivalent or stronger material. Ties are connected to the inside uprights and are not more than 15 feet apart horizontally or vertically. [1641(f)(1)]

Scaffolds are diagonally braced with 1" by 6" boards, and are secured to prevent swaying, tipping, or collapsing. [1641(f)(2)]

WOODEN POLE SCAFFOLDS—LIGHT TRADES

A wooden pole scaffold meets the Cal/OSHA requirements below for **light trades** if it is used only by carpenters, lathers, shinglers, painters, plasterers, sheet metal workers, or others not using heavy tools or materials. [1640(a)] The load on this scaffold, including workers, does not exceed 25 pounds per square foot. [1504]

Uprights are a minimum of 2" by 4" lumber for scaffolds of 20 feet or less. For scaffolds over 20 feet, uprights are at least 3" by 4". Uprights are spaced no more than 10' apart in the direction parallel to the wall, and are secured against slippage. The inner row of uprights may be replaced by attaching the scaffold to the permanent structure. If the uprights are placed on the earth, they are secured to a wooden base at least 2" x 10" x 10". [1640(b) and (c)]

Platforms are at least 20" wide and are made from at least 2" x 10" lumber, laid closely together, or from 3/4" Douglas fir plywood. They are within 14" of the face of the building. Platforms are supported by ledgers and ribbons, nailed or bolted to the uprights. A plank does not overlap an unsupported end of another plank. [1640(b) and (c)]

Scaffolds are rigidly tied to the building or structure by means of a double looped No. 12 iron wire, or single looped No. 10 iron wire, or equivalent or stronger material. Ties are connected to the inside uprights and are not more than 20 feet apart horizontally or vertically. [1640(b)(3)]

Scaffolds are diagonally braced with 1" by 6" boards, and are secured to prevent swaying, tipping, or collapsing. [1640(b) and (c)]



34.0 Equipment Damage / Loss / Theft Report Form

Custom Electric employees are required to report any damage, loss or theft of Custom Electric-owned and operated equipment as soon as possible and submit a completed copy of this form within (4) hours of the incident.

Please note that where an injury occurs as a result of any damage, loss or theft of Custom Electric owned and operated equipment, employees are required to report the incident immediately, and submit a completed Incident Report and Investigation Form.

Damage / Loss / Theft - Reported By

Employee Name:

Employee Number:

Incident Information

Incident Date (dd/mm/yy): / /

Time of Incident (24 hour clock):

Reported on: / / Time Reported (24 hour clock):

Supervisor:

Job Site:

Specific Location:

Equipment Information

List of Equipment
Damaged / Lost / Stolen
(Please Specify)

Equipment Identification
Number(s)

Equipment Location at
Time of Damage / Loss

Description of Damage
to Equipment

How Was the Equipment Damaged / Lost / Stolen? (Complete Description)	
Estimated Cost of Repair / Replacement	
Person Responsible for Equipment	

Was the Equipment Damage / Loss / Theft reported to the Police?

☐ Yes

☐ No

If yes, please provide:

Police Report Information	
Police File #:	Officer In Charge:
Station #:	Phone #:
Email:	

A Police Report (if Theft) and replacement cost invoice must be attached.

Acknowledgement & Agreement

Supervisor: _____

Signature: _____

Date: _____



Employer: Custom Electric, Inc.

Employee: _____

Date: _____

35.0

**Appendix D to Sec. 1910.134 (Mandatory) Information for Employees Using Respirators
When Not Required Under the Standard**

Respirators are an effective method of protection against designated hazards when properly selected and worn. Respirator use is encouraged, even when exposures are below the exposure limit, to provide an additional level of comfort and protection for workers. However, if a respirator is used improperly or not kept clean, the respirator itself can become a hazard to the worker. Sometimes, workers may wear respirators to avoid exposures to hazards, even if the amount of hazardous substance does not exceed the limits set by OSHA standards. If your employer provides respirators for your voluntary use, or if you provide your own respirator, you need to take certain precautions to be sure that the respirator itself does not present a hazard.

You should do the following:

1. Read and heed all instructions provided by the manufacturer on use, maintenance, cleaning and care, and warnings regarding the respirators limitations.
2. Choose respirators certified for use to protect against the contaminant of concern. NIOSH, the National Institute for Occupational Safety and Health of the U.S. Department of Health and Human Services, certifies respirators. A label or statement of certification should appear on the respirator or respirator packaging. It will tell you what the respirator is designed for and how much it will protect you.
3. Do not wear your respirator into atmospheres containing contaminants for which your respirator is not designed to protect against. For example, a respirator designed to filter dust particles will not protect you against gases, vapors, or very small solid particles of fumes or smoke.
4. Keep track of your respirator so that you do not mistakenly use someone else's respirator.



GFI Test Form Log

Job Name/#: _____

[illegible]