College Lost and Found
Secure Software Engineering

Integrated laboratory case study and implementation

Marisetti Avinash
CH.SC.U4CYS23024
Amrita Vishwa Vidyapeetham Chennai
20CYS401 Secure Software Engineering
8 October 2026

Purpose and implementation

This submission connects the assigned college lost-and-found problem to all sixteen secure software engineering phases. The application supports lost and found reporting, verified-item search, private contact, reporter-only recovery and administrator moderation. Requirements, models, backlog identifiers, source code and tests use a common catalog.

The delivered system is a locally operated laboratory application. Demonstration reports and messages are test data. A successful technical workflow demonstrates the software, rather than a real campus handover. Generic examination-specific examples in the instruction sheet are adapted to this assigned case study under its General Case-Study Instruction.

Evidence and sprint interpretation

Two nominal sprint plans each span exactly fifteen days: 8 October to 23 October and 23 October to 7 November 2026, at 09:00 Asia/Kolkata. Work and Jira transitions were performed during a compressed laboratory demonstration. Planned calendar burndown values are labelled forecasts; actual API history and test/deployment logs are retained separately. No fifteen-day execution history is claimed.

Artifact	Location
Working source and tests	app.py; schema.sql; templates/; static/; tests/
Secure containers and deployment	Dockerfile; compose.yaml; deploy/kubernetes.yaml; deploy/Caddyfile
Jira	https://mavinash.atlassian.net/jira/software/c/projects/CLF24/boards/236
Models and wireframe evidence	deliverables/images/; deliverables/editable/
Machine readable traceability	deliverables/catalog.json; tables/*.csv; security-analysis.json
Raw verification records	deliverables/evidence/
Editable report	deliverables/College_Lost_and_Found_Report.md

Submission contents

01 Agile process

02 Requirements engineering

03 Use cases and analysis

04 Data and information flow

05 Architecture and design

06 User interface

07 Threat and vulnerability analysis

08 Attack tree and refinement

09 Product backlog and Jira

10 Sprint execution and metrics

11 Secure build

12 Secure coding and refactoring

13 Docker and Kubernetes

14 CI and security testing

15 Monitoring and deployment hardening

16 Final security review

Phase 1 Agile Process and Development Approach

Scrum with XP practices suits the project because user-facing reporting can be delivered in short increments while privacy and authorization are checked continuously. Marisetti Avinash performs the development work and is the only Jira assignee. Product Owner and Scrum Master responsibilities are described as role responsibilities for this individual lab; no fictitious team members or meetings are claimed.

Practice	Project application
Two fifteen-day sprints	Sprint 1 delivers campus workflows. Sprint 2 strengthens security and deployment.
Definition of Ready	Requirement ID, actor, acceptance criteria, privacy impact and estimate exist.
Definition of Done	Feature implemented; related tests pass; security checks reviewed; evidence retained; documentation and Jira synchronized.
XP testing and refactoring	Test owner permissions and private messaging before release; centralize validation and route guards.
Small increments	Identity → reports → moderation → private contact → recovery → hardening and packaging.

Agile principle	Concrete mapping
Early continuous delivery	A working reporting flow is checked before deployment packaging.
Welcome changing requirements	Acceptance criteria and catalog change together when privacy or moderation rules change.
Working software is the measure	Browser workflow and container health support completion claims.
Technical excellence	Parameterized SQL, scrypt hashing, role checks and automated tests are part of implementation.
Simplicity	Use a modular monolith and SQLite for a single-node lab rather than unnecessary distributed services.
Regular reflection	Retrospective actions address dependency checking and moderation coverage.

Refactoring opportunities

Opportunity 1 replaces a raw item update with reporter authorization, state validation and parameterized SQL. Opportunity 2 replaces role and password trust in an initial teaching example with an allowlisted registration role and scrypt hashing. Phase 12 contains the before/after source evidence; the insecure example is stored as text and is never served.

Risk	Mitigation
Security work loses priority to visible features	Make authorization, input validation and privacy tests acceptance criteria; include a security review in Done.
Rapid iterations create inconsistent models and backlog	Use catalog.json as the identifier authority; regenerate tables and verify a critical trace across all phases.

Phase 2 Requirements Engineering and Software Requirements Specification

Software Requirements Specification SRS

This SRS specifies the College Lost and Found application submitted for 20CYS401. It defines the campus workflows, actors, interfaces, data, security requirements and acceptance criteria used by the implementation and verification evidence. Requirement identifiers R01–R16 remain the common reference for use cases, backlog stories and tests throughout the report.

Purpose and scope

The system enables authenticated campus users to report lost or found items, search verified reports, contact a reporter privately and confirm recovery of their own report. Administrators verify or remove suspicious reports and inspect audit metadata. The application records the software workflow; a real-world handover must be confirmed by the report creator. Production campus identity federation, centrally revocable sessions and immutable external audit storage are future requirements rather than completed lab features.

Definitions and product context

Term	Meaning
Campus user	A registered student or faculty member with the same reporting and communication permissions.
Reporter	The authenticated creator of a lost or found report; owns its recovery action.
Verified report	A report approved by an administrator and eligible for ordinary search.
Recovered item	An open verified report closed by its creator after confirming return.
Private conversation	Messages scoped to the sender and recipient of a report-related exchange.
SRS and CIA	Software Requirements Specification; confidentiality, integrity and availability.

The product is a server-rendered Flask application with SQLite persistence. Caddy terminates HTTPS for the Docker and Kubernetes laboratory deployments. Browser forms communicate with the application; the database is accessed only by server-side parameterized statements. A single Kubernetes application replica is used because the lab SQLite database is not shared multi-replica storage.

User classes and permissions

Stakeholder	Goal and permitted authority
Student	Report lost/found items; search verified reports; private contact; recover own report.
Faculty	Same reporting features, with faculty role recorded; no moderation privilege.
Administrator	Verify/remove suspicious reports and inspect audit metadata; no blanket private-inbox access.
Operator	Provision administrator, manage secrets, containers, storage, TLS and backups; privileged operational actor.

Operating environment assumptions and constraints

Area	Specification
Environment	A modern browser and local Docker or isolated kind Kubernetes deployment; Python Flask Gunicorn Caddy and SQLite versions are pinned in the submitted configuration.
Campus identity	Lab registration records the chosen student or faculty role without independently proving membership. Campus SSO or verified institutional email is required before campus production use.
Provisioning	Only the operator provisions administrators and manages runtime secrets. Public registration cannot select administrator authority.
Moderation and handover	Administrators review pending reports; reporter and recipient arrange handover. Software confirmation does not prove physical possession.
Persistence and recovery	SQLite volume or PVC stores private data. Operator-controlled access, backups, retention and restoration procedures are required.
Deployment limits	TLS clients must trust the lab CA. Production requires a trusted campus certificate. NetworkPolicy configuration is supplied, but enforcement by the default kind CNI is not verified.

External interfaces and data requirements

Interface or data	Required behavior
User interface	Labelled login registration browse report details contact inbox and moderation screens; show validation feedback and report state; retain keyboard focus and responsive layout.
Communication interface	HTTPS protects credentials and private contact in deployed environments; form POST operations use session-bound CSRF tokens; session cookies are HttpOnly and use deployment security settings.
Application interface	Server routes implement sign-in reporting search contact reply recovery and moderation. Identity ownership and message recipients are derived on the server.
Storage interface	SQLite schema uses User Report Message AuditEvent and LoginAttempt records with foreign keys and constrained report states; no browser receives direct database access.
Public and private data	Search exposes verified report fields without account emails. Owners can inspect their own reports. Private message bodies are available only to participants and are omitted from audit records.
Report lifecycle	Creation starts pending and open. Administrator verification enables discovery. Removal hides the report. Only the creator can recover an open verified report; duplicate recovery is rejected.

Functional requirements and acceptance criteria

ID	Requirement	Acceptance condition	Priority	Trace
R01	Account registration and sign in	Student and faculty register; administrator is provisioned by operator.	Must	UC01 / US01
R02	Report a lost item	Capture title description category location and date; create pending report.	Must	UC02 / US02

ID	Requirement	Acceptance condition	Priority	Trace
R03	Report a found item	Use the same validated workflow with kind found.	Must	UC02 / US03
R04	Search verified reports	Search title description location and filter kind/category.	Must	UC03 / US04
R05	Private owner or finder contact	Authenticated contact through recipient-scoped internal inbox.	Must	UC04 / US05
R06	Owner-only recovery	Only the reporting user can close an open verified report.	Must	UC05 / US06
R07	Administrator moderation	Administrator verifies or soft-removes suspicious reports with reason.	Must	UC06 / US07
R08	Personal report tracking	Owner can see their pending verified and removed reports.	Should	UC07 / US08
R09	Secure communication and sessions	TLS cookie security CSRF request limits CSP and password hashing.	Must	UC01 / US09
R10	Malicious content prevention	Escape displayed text and use parameterized SQL and bounded input.	Must	UC02 / US10
R11	Security audit and monitoring	Record login denial moderation recovery and message metadata without body or password.	Must	UC08 / US11
R12	Private reply and abuse control	Recipient-only replies; cap messages at ten per minute per sender.	Should	UC04 / US12
R13	Secure Docker packaging	Pinned dependencies non-root read-only rootfs least privilege TLS health check.	Must	UC09 / US13
R14	Kubernetes deployment	Restricted namespace limits secret PVC ClusterIP network policy.	Must	UC09 / US14
R15	Verified delivery pipeline	Checkout build tests static check dependency audit image package; fail on errors.	Must	UC09 / US15
R16	Accessible consistent interface	Responsive labelled controls error feedback cancel clear and progress views.	Should	UC03 / US16

Nonfunctional and security requirements

ID	Nonfunctional or security requirement	Verification or limitation
N01	Private messages accessible only to participants	Private-inbox and reply-ID tests; administrators do not inherit message access.
N02	All state changes require authenticated authority and CSRF	Role/ownership tests and CSRF rejection test.
N03	Passwords stored as salted scrypt hashes	Database assertion confirms hash form and absence of plaintext.
N04	Bound report/message fields and body size	Title 3–100; description 10–1000; message 5–1000; body ≤16384 bytes; fuzz tests.

ID	Nonfunctional or security requirement	Verification or limitation
N05	TLS for credentials and private contact in deployment	Caddy lab TLS; internal development CA requires trusted client; production requires valid campus certificate.
N06	Thirty-minute session validity configuration	Flask permanent session policy; activity can refresh validity. No immediate central revocation yet.
N07	Responsive accessible interface	Labels, visible errors, keyboard focus, small-screen layout and browser inspection.
N08	Target p95 response below two seconds for a 100-item search	Performance target; a small smoke measurement does not establish concurrent campus-scale capacity.
N09	Auditable privileged changes without secrets in logs	Actor, event, object, outcome and UTC timestamp; password/message contents excluded.
N10	Recoverable private storage	SQLite volume/PVC; backup and retention are operational deployment controls.

CIA priorities: confidentiality dominates credentials, emails, private messages and secrets; integrity dominates report ownership, moderation and recovery; availability supports search, sign-in and recovery. Authentication identifies the current database user. Authorization separately enforces administrator or reporter/participant policy. Audit records sensitive operation outcomes.

Acceptance and requirements traceability

Acceptance requires the lost-report found-report verified-search private-contact reporter-only-recovery and administrator-moderation workflows to operate with the specified permissions. Negative cases must reject unauthorized updates, unrelated message access, invalid CSRF and malicious or excessive inputs. The retained 34-test result and Docker/Kubernetes HTTPS workflow evidence support the implemented lab requirements. N08 remains a performance target rather than a campus-load result; operational controls retain their stated limitations. Phase 16 provides the detailed requirement-to-use-case-to-story-to-source-and-test trace, using catalog.json as the identifier authority.

Phase 3 Requirements Analysis and UML




Figure 1 Use cases with include and conditional extend relationships

Use case	Actor	Requirement
UC01 Register and sign in	Student / Faculty / Administrator	R01 R09
UC02 Report lost or found	Campus user	R02 R03 R10
UC03 Search and view verified items	Campus user	R04 R16
UC04 Contact and reply privately	Campus user / message recipient	R05 R12
UC05 Mark recovered	Report creator	R06
UC06 Verify or remove	Administrator	R07
UC07 Track own reports	Report creator	R08
UC08 Review audit	Administrator	R11
UC09 Deploy verified application	Operator / developer	R13 R14 R15

College Lost and Found




Figure 1A Administration and operations use cases

Critical use case UC02 Report lost or found

Specification field	Flow
Primary actor	Authenticated student or faculty.
Preconditions	Active session; valid CSRF token; required fields supplied.
Main flow	1 Open report form. 2 Select lost/found and category. 3 Enter title description location and date. 4 Server validates bounds/date and derives reporter ID from session. 5 Save pending report. 6 Record report_created event. 7 Display reference and pending status.
Alternative flow	Invalid input returns specific form feedback; user corrects it. Administrator later verifies the report before public search can show it.
Exception flow	Expired/forged CSRF returns 400; excessive body returns 413; anonymous actor is redirected to sign-in; database error returns generic 500 response.
Postconditions	Report belongs to the authenticated creator; moderation=pending; status=open. No password or account email appears in the report.
Security rule	Do not accept reporter_id or administrator authority from the form.

Critical use case UC05 Mark item recovered

Specification field	Flow
Primary actor	The user who created the report.
Preconditions	Authenticated user; valid CSRF; report exists; moderation=verified and status=open; handover has been confirmed by the reporter.
Main flow	1 Open own report. 2 Confirm item recovered. 3 Load report and check reporter_id. 4 Check open verified state. 5 Parameterized update records recovered_at. 6 Append item_recovered audit event. 7 Display recovered state.
Alternative flow	A verified found report may be closed by its finder after return. A second recovery request returns 409 and preserves the existing state.
Exception flow	Another user receives 403; hidden pending report receives 404; invalid CSRF returns 400; no state change is made.
Postconditions	Only the creator changes status to recovered; further contact/reply is rejected; audit metadata records the change.
Security rule	Administrator moderation does not grant ownership of another user’s recovery action.

Scenario based analysis model

The scenario is Report an Item and Complete Recovery, the domain equivalent of the generic Attend Examination and Submit Answers example. Boundary objects are the report form, details screen and moderation page. Control objects enforce identity, input validation, report state and authorization. Entity objects are User, Report and AuditEvent. The sequence preserves the order of submission, verification and reporter confirmation.




Figure 2 Boundary control and entity analysis sequence

Phase 4 Data and Information Flow Modeling




Figure 3 ER model derived from the implemented SQLite schema

Relationship	Cardinality and invariant
User creates Report	One report has exactly one reporter; a user has zero or many reports.
User moderates Report	Report has zero or one moderator; administrator may moderate many reports.
Report has Message	Message references one report; report has zero or many messages.
User sends or receives Message	One sender and one recipient per message; each user may have many sent/received messages.
User performs AuditEvent	Zero or one actor per event, allowing unauthenticated denial events; many events per user.
LoginAttempt	Independent attempt record includes unknown emails and hashed connection source; no required User FK.




Figure 4 Context DFD and application boundary




Figure 5 Level 1 DFD with stores and authorization flows

Element	Responsibility and sensitive flows
E1 E2 E3	Campus users, administrators and privileged operator.
P1 Identity and sessions	Credentials to D1; salted hash verification, session identity, login throttling.
P2 Reports and search	Creates pending D2 records; returns verified public fields or owner-scoped records.
P3 Contact and recovery	Writes participant-scoped D3 messages; authorizes reporter recovery in D2.
P4 Moderation and audit	Administrator updates D2 verification/removal; records D4 events.
D1 D2 D3 D4	Users/login attempts; reports; private messages; audit events in the same SQLite database.
TB1 TB2 TB3	Browser/application boundary; application/private storage boundary; privileged operator/deployment boundary.

Consistency check: UC02 maps to P2 and Report, UC04 to P3 and Message, UC05 to P3/D2 and Report, UC06 to P4/D2 and moderator_id, UC08 to P4/D4 and AuditEvent. No separate examination, marks or question-paper entity is introduced into this assigned domain.

College Lost and Found




Figure 5A Detailed Level 2 DFD for creator-only recovery

Phase 5 Software Architecture and Design Engineering

A layered modular monolith is appropriate for a small college service and a bounded lab deployment. Server-rendered forms avoid client-side secret storage. A single relational database enforces ownership references and supports a simple recoverable volume. The lab uses one Kubernetes replica with Recreate because SQLite is not a shared multi-replica database.




Figure 6 Implemented components and deployment responsibilities

Component	Interface	Responsibility
Browser templates and stylesheet	HTML GET and CSRF-protected form POST	Login reporting search details inbox moderation and recovery feedback.
Identity and route guards	register login logout; auth decorator	Hash passwords; authenticate; load current database role; deny unauthorized routes.
Report service	report items detail recover	Validate input, enforce moderation visibility and reporter-only recovery.
Messaging service	contact inbox reply	Derive recipients server-side, enforce participants and bound send rate.
Moderation and audit	admin moderate audit()	Record reason/moderator and auditable outcomes; pending-first paginated review.
Data access	SQLite parameterized statements	Foreign keys, state checks, WAL persistence and transactions.

Component	Interface	Responsibility
Deployment edge	Caddy → Gunicorn; ClusterIP service	TLS, process isolation, health checks and resource restrictions.

Concept or pattern	Implemented application
Separation of concerns	Templates render UI; guards enforce access; SQL schema defines state.
Application factory	create_app(config) supports isolated test database and deployment configuration.
Decorator / guard	auth(admin=True) and CSRF middleware centralize entry checks.
Boundary control entity	Forms → services → User/Report/Message/Audit entities.
Least privilege and fail closed	Only allowlisted actions/roles; hidden reports return 404; unrelated messages cannot be loaded.
Repository-style access	Database connection lifecycle and bound SQL stay server-side; no user-built query execution.

Domain mapping for the generic architecture instruction: authentication → P1; examination/submission → P2 campus report submission; evaluation/results → P4 verification and P3 recovery status; audit/logging → D4. The components implement the lost-and-found equivalents throughout.

Phase 6 User Interface Design

Screen	User goal and navigation	Inputs feedback and security
Login and registration	All users; proceed to browse after sign-in.	Email/password; generic login failure; 12-character minimum registration; admin role cannot be selected.
Browse and search	Students/faculty discover verified items; navigate to report or detail.	Search/type/category filters; result count and empty state; emails absent.
Report form	Student/faculty report lost/found; cancel returns to browse.	Bound fields and date; field error feedback; pending state prevents immediate publication.
Private inbox and contact	Participants communicate without exposing account emails.	Bound message; reply recipient derived from received message; closed reports hide reply controls.
Administrator moderation	Admin verifies/removes suspicious reports; reviews audit.	Reason required for removal; pending-first paginated queue; role guard.
Recovery result	Reporter confirms return and sees recovered state.	Explicit confirmation action; server checks owner/open/verified; duplicate action rejected.




Figure 7 Login screen from the running application




Figure 8 Student browse and search screen




Figure 9 Lost or found reporting form




Figure 10 Administrator report verification workspace




Figure 11 Private contact form without account email disclosure




Figure 12 Participant inbox and private reply controls




Figure 13 Recovery result after the browser workflow

Golden Rules: identical header/navigation and typography provide consistency; Cancel and Clear provide user control; pending/verified/recovered states and notices provide feedback; allowlists and server validation prevent invalid actions; labelled controls and focus outlines support navigation; badges and report references keep state visible. Errors do not expose stack traces. Handovers are encouraged at a staffed campus location.

Phase 7 Threat Modeling and Security Analysis

Asset Identification

Assets are identified from the SRS, DFD stores D1–D4, communication flows and deployment configuration. For each asset, identify whose information or authority it represents, where it is held and which CIA property needs protection. The following inventory uses the same A1–A9 identifiers as the threat and information-flow analysis.

ID	Asset	C	I	A
A1	Passwords and credential verification	High	High	Medium
A2	Account email and identity	High	High	Medium
A3	Private message contents	High	High	Medium
A4	Report ownership and recovery state	Medium	High	High
A5	Moderation decisions and reasons	Medium	High	High
A6	Audit metadata	Medium	High	High
A7	Session signing secret and CSRF identity	High	High	High
A8	SQLite volume and backups	High	High	High
A9	Build image and dependency integrity	Medium	High	High

Asset	Owner or custodian	Location and protection objective
A1 A2 Credentials and identity	Account holder; identity service and operator are custodians.	D1 users in SQLite. Protect hashes and email confidentiality; prevent forged roles or identity changes.
A3 Private messages	Sender and recipient; operator controls storage.	D3 messages. Restrict application access to participants; protect body confidentiality and recipient integrity.
A4 Reports and recovery	Report creator; application enforces authority.	D2 reports. Preserve creator ownership and valid pending verified removed and recovered states.
A5 Moderation decisions	Administrator; application records decisions.	D2 moderator reason and state. Prevent ordinary users from verifying or removing reports.
A6 Audit metadata	Administrator reviewer; operator custodian.	D4 audit events. Preserve actor object outcome and time; exclude secrets and message bodies. External immutable retention is future work.
A7 Session and CSRF authority	Operator manages signing secret; application issues sessions.	Runtime secret and browser session cookie. Prevent forgery and disclosure; derive authority from the current database user.
A8 Private storage and backups	Operator.	Docker volume or Kubernetes PVC and controlled backups. Protect all stored data and restore availability; at-rest encryption is operational.

Asset	Owner or custodian	Location and protection objective
A9 Build and dependencies	Developer and deployment operator.	Pinned requirements container image and CI configuration. Preserve dependency and executable integrity before deployment.

Trust Boundaries

A trust boundary marks a change in who controls an input or which privileges may be used. Crossing a boundary never grants authority automatically. TB1–TB3 below match the DFD and attack-tree references; each crossing must apply the listed validation and access controls.

ID	Boundary	Trust change	Crossing data or authority	Controls and limits	Threat trace
TB1	Browser to application	Untrusted caller and submitted text cross into server processing through the HTTPS deployment edge.	Credentials reports messages search and state-changing forms.	TLS at Caddy; authenticate current user; enforce role ownership and participant policies; session-bound CSRF; allowlisted bounded input; escaped output. Caddy-to-application HTTP stays inside the controlled deployment network or pod.	TH01 TH03 TH04 TH05 TH06 TH07 TH08 TH12
TB2	Application to private storage	Server route authority crosses into persistent records; the database is not exposed to browsers.	D1 credentials D2 reports D3 messages D4 audit and login-attempt records.	Parameterized SQL; participant and owner predicates; foreign keys and state checks; non-root process and operator storage ACL. At-rest encryption and backup protection remain operator responsibilities.	TH02 TH03 TH05 TH09 TH10
TB3	Operator to deployment and secrets	Privileged provisioning build and deployment actions cross into the application runtime and its storage.	Administrator provisioning signing secret image dependencies configuration volumes and backups.	Operator-only provisioning; secrets excluded from submission; pinned dependencies; restricted containers and namespace; least privilege. Hosted CI execution immutable audit and NetworkPolicy enforcement retain documented limits.	TH10 TH11

STRIDE threat analysis

ID	DFD	STRIDE	Threat	Impact	Control
TH01	P1 / TB1	S	Credential guessing or forged session	Account impersonation	scrypt; random signing secret; TLS; atomic source/account throttling.
TH02	P2 / D2	T	Craft SQL syntax in search or report	Read or change unintended records	Fixed SQL with bound parameters; LIKE metacharacters escaped.
TH03	P3 / D2	T	Recover another user’s report	False recovery and loss of trust	Reporter_id policy; CSRF; verified/open precondition; audit denials.
TH04	P4 / D2	E	Ordinary user invokes moderation	Unauthorized verification/removal	Current database role check; registration role allowlist; operator-only admin creation.

ID	DFD	STRIDE	Threat	Impact	Control
TH05	P3 / D3	I	Read or reply to unrelated private message	Private-content disclosure	Participant-scoped SQL; reply recipient authorization; no blanket admin inbox.
TH06	P2 / TB1	T	Store active malicious markup	Script execution / session abuse	Jinja escaping; no safe rendering; CSP script-src none; text bounds.
TH07	POST routes / TB1	S	Cross-site request forgery	Unwanted recovery/moderation/message	Session-bound token; token rotation on login; SameSite cookie.
TH08	P1 / P3	D	Login guessing or message flooding	Resource exhaustion or harassment	Five account/source attempts per 15 minutes; ten sends per minute; body and resource limits.
TH09	D4	R	Deny having changed report state	Incident attribution failure	Actor object event outcome UTC timestamp; external immutable export is future work.
TH10	TB2 / A8	I	Read private volume or backup	Message/hash disclosure	Non-root application; operator storage ACL; encryption/backup policies remain operational.
TH11	TB3 / A9	T	Use vulnerable dependency or altered image	Runtime compromise	Pinned patched versions; dependency audit; build evidence; digest recording and CI gates.
TH12	P1 / E1	S	Register using an unverified campus identity	Spam and identity misrepresentation	Admin verification of reports; residual risk until campus SSO/email verification.

Threat scenarios are plausible attack paths, not claims that the finished application is exploitable. STRIDE letters denote Spoofing, Tampering, Repudiation, Information disclosure, Denial of service and Elevation of privilege. Source review and automated tests establish the listed implemented controls; operational controls must be configured by the operator.




Figure 14 Sensitive information flow analysis

Asset	Source route and sink	Authorized recipients	Protection and residual issue
A1 credentials	Browser → TLS → P1 → D1 hash comparison	Identity service; operator-controlled private storage	Plain password is used only for hashing/comparison; secure cookie. No campus SSO yet.
A3 private message	Sender → P3 → D3 → participant inbox	Sender and recipient; operator has storage authority	Server-derived recipient, escaped output, no body in audit. DB at-rest encryption is operational.
A4 recovery state	Reporter POST → P3 → D2 update → D4 audit	Authenticated reporter writes; verified-report readers see status	Owner policy, CSRF, state check, audit. Creator confirmation does not prove a real-world handover.

ID	Affected element	Weakness	Risk	Evidence and status
V01	Initial teaching recovery function / TH03	Missing owner policy and interpolated SQL	High if deployed	Nonexecuted initial example; current implementation fixed and unauthorized-recovery/SQL tests pass.
V02	Initial teaching registration / TH04	Trust form role and store plaintext password	High if deployed	Nonexecuted initial example; current allowlist and scrypt tests pass.
V03	Invalid host error path / TH08	Template URL generation without valid routing adapter	Medium availability	Observed in test; safe plain response for unroutable requests; host-validation retest passes.

ID	Affected element	Weakness	Risk	Evidence and status
V04	P1 login throttling / TH08	Account-wide targeted lockout and nonatomic attempt count	Medium availability	Source review; atomic transaction and hashed connection/account scope added; different-source login retest passes.
V05	Application dependencies / TH11	Known advisories in initial Flask Werkzeug Click pins	High supply-chain risk	Dependency audit observed 10 advisory records in 3 packages (duplicates included); upgraded; current audit clean.
V06	P4 moderation UI / TH08	Only newest 100 reports accessible	Medium operational	Source review; pending-first pagination added; older-page test passes.
V07	P3 inbox UI	Reply form shown after report is closed	Low correctness	Source review; closed-report reply control hidden; endpoint still denies; retest passes.
V08	A8 storage / TH10	No application-layer message encryption at rest	Residual confidentiality	Requires privileged storage access; secure volume/backups and plan managed encryption. Not a demonstrated remote exploit.
V09	P1 campus identity / TH12	No email verification or campus membership proof	Residual abuse risk	Admin moderation reduces publication risk; campus SSO is a future production requirement.

Phase 8 Attack Tree and Security Architecture Refinement

The critical attacker goal is modifying another campus user’s recovery state. It directly threatens report integrity and corresponds to the generic example of changing another student’s result. OR branches cover identity compromise, authorization bypass and privileged storage manipulation. Each branch requires its stated AND prerequisites.




Figure 15 Attack paths and preventive and detective controls




Figure 16 Architecture refined around the highest-risk flows

Path	Preventive control	Detective control
Compromise reporter identity	scrypt, TLS, signed secure cookie, atomic login rate bound	login_failed / login_throttled; planned alert on denial rate.
Choose victim ID and bypass authorization	can_manage policy; route state check; bound SQL; CSRF	recovery_denied with object ID; unauthorized-recovery test.
Escalate to moderation role	Admin decorator and operator-only provisioning	authorization_denied; moderation event metadata.
Read another conversation	Participant query and recipient-only reply	Cross-user inbox/reply regression test.
Write volume directly	Operator RBAC, ACL, container least privilege	Backup integrity and external audit export; app DB alone is not tamper-proof.




Figure 16A Report moderation and recovery lifecycle

Phase 9 Product Backlog and Jira Scrum

Epic	Scope	Jira key
E1	Identity and session security	CLF24-1
E2	Campus reporting and discovery	CLF24-2
E3	Private contact and recovery	CLF24-3
E4	Moderation and accountability	CLF24-4
E5	Secure build and quality assurance	CLF24-5
E6	Containers and secure deployment	CLF24-6

US01 Account registration and sign in

As a campus user, I want to register and sign in so that I can access the service safely.

Requirement R01 | Epic E1 | Priority Must | Sprint 1 | Estimate 5 points | Task T01 | Jira CLF24-7

- Student and faculty register; administrator is provisioned by operator.
- Automated check test_registration_valid passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US02 Report a lost item

As a student, I want to report a lost item so that I can ask the campus community for help.

Requirement R02 | Epic E2 | Priority Must | Sprint 1 | Estimate 5 points | Task T02 | Jira CLF24-9

- Capture title description category location and date; create pending report.
- Automated check test_pending_visibility passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US03 Report a found item

As a finder, I want to report a found item so that I can return it to its owner.

Requirement R03 | Epic E2 | Priority Must | Sprint 1 | Estimate 3 points | Task T03 | Jira CLF24-11

- Use the same validated workflow with kind found.
- Automated check test_future_date_rejected passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US04 Search verified reports

As a campus user, I want to search verified reports so that I can find a matching item.

Requirement R04 | Epic E2 | Priority Must | Sprint 1 | Estimate 5 points | Task T04 | Jira CLF24-13

- Search title description location and filter kind/category.
- Automated check test_sql_injection_search passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US05 Private owner or finder contact

As a campus user, I want to contact an owner or finder privately so that I can reconnect without publishing my email.

Requirement R05 | Epic E3 | Priority Must | Sprint 1 | Estimate 5 points | Task T05 | Jira CLF24-15

- Authenticated contact through recipient-scoped internal inbox.
- Automated check test_private_messages_and_reply passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US06 Owner-only recovery

As a reporter, I want to mark my report as recovered so that I can record a successful return.

Requirement R06 | Epic E3 | Priority Must | Sprint 1 | Estimate 5 points | Task T06 | Jira CLF24-17

- Only the reporting user can close an open verified report.
- Automated check test_unauthorized_recovery passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US07 Administrator moderation

As a administrator, I want to verify or remove suspicious reports so that I can keep suspicious content off the board.

Requirement R07 | Epic E4 | Priority Must | Sprint 1 | Estimate 5 points | Task T07 | Jira CLF24-19

- Administrator verifies or soft-removes suspicious reports with reason.
- Automated check test_moderation_and_removal passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US08 Personal report tracking

As a reporter, I want to track my own reports so that I can follow verification progress.

Requirement R08 | Epic E2 | Priority Should | Sprint 1 | Estimate 3 points | Task T08 | Jira CLF24-21

- Owner can see their pending verified and removed reports.
- Automated check test_pending_visibility passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US09 Secure communication and sessions

As a campus user, I want to use secure sessions and communication so that I can protect my account and communication.

Requirement R09 | Epic E1 | Priority Must | Sprint 2 | Estimate 5 points | Task T09 | Jira CLF24-23

- TLS cookie security CSRF request limits CSP and password hashing.
- Automated check test_session_cookie_security passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US10 Malicious content prevention

As a campus user, I want to view safely validated content so that I can view reports without executing malicious content.

Requirement R10 | Epic E5 | Priority Must | Sprint 2 | Estimate 5 points | Task T10 | Jira CLF24-25

- Escape displayed text and use parameterized SQL and bounded input.
- Automated check test_xss_escaped passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US11 Security audit and monitoring

As a administrator, I want to inspect security audit metadata so that I can investigate misuse.

Requirement R11 | Epic E4 | Priority Must | Sprint 2 | Estimate 3 points | Task T11 | Jira CLF24-27

- Record login denial moderation recovery and message metadata without body or password.
- Automated check test_audit_contains_no_secrets passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US12 Private reply and abuse control

As a message recipient, I want to reply privately with abuse controls so that I can reply safely without unsolicited access.

Requirement R12 | Epic E3 | Priority Should | Sprint 2 | Estimate 3 points | Task T12 | Jira CLF24-29

- Recipient-only replies; cap messages at ten per minute per sender.
- Automated check test_message_throttle passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US13 Secure Docker packaging

As a operator, I want to package the application in Docker so that I can run a controlled container.

Requirement R13 | Epic E6 | Priority Must | Sprint 2 | Estimate 5 points | Task T13 | Jira CLF24-31

- Pinned dependencies non-root read-only rootfs least privilege TLS health check.
- Automated check test_health_and_headers passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US14 Kubernetes deployment

As a operator, I want to deploy the application to Kubernetes so that I can deploy with restricted permissions.

Requirement R14 | Epic E6 | Priority Must | Sprint 2 | Estimate 5 points | Task T14 | Jira CLF24-33

- Restricted namespace limits secret PVC ClusterIP network policy.
- Automated check test_host_validation passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US15 Verified delivery pipeline

As a developer, I want to run the verified delivery pipeline so that I can ship tested and checked changes.

Requirement R15 | Epic E5 | Priority Must | Sprint 2 | Estimate 5 points | Task T15 | Jira CLF24-35

- Checkout build tests static check dependency audit image package; fail on errors.
- Automated check test_end_to_end_report_verify_contact_recover passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

US16 Accessible consistent interface

As a campus user, I want to use an accessible consistent interface so that I can complete tasks with clear feedback.

Requirement R16 | Epic E2 | Priority Should | Sprint 2 | Estimate 3 points | Task T16 | Jira CLF24-37

- Responsive labelled controls error feedback cancel clear and progress views.
- Automated check test_body_limit passes or deployment evidence confirms the control.
- No sensitive credentials are published in the implementation or evidence.

Sprint	Nominal fifteen-day schedule	Goal	Committed points
Sprint 1 Campus Core	2026-10-08T09:00:00+05:30 to 2026-10-23T09:00:00+05:30	Deliver identity reporting search moderation private contact and owner-only recovery.	36

Sprint	Nominal fifteen-day schedule	Goal	Committed points
Sprint 2 Secure Delivery	2026-10-23T09:00:00+05:30 to 2026-11-07T09:00:00+05:30	Harden the application verify abuse controls and deliver tested Docker Kubernetes and CI packages.	34

Stories US01–US08 are planned for Sprint 1; US09–US16 for Sprint 2. Each story has one implementation/verification subtask. All Jira work items are assigned to Marisetti Avinash. No work is assigned to another person.

Phase 10 Sprint Execution and Scrum Metrics

The workflow is To Do → In Progress → Testing → Done. Jira issue histories record actual transitions made during the lab. Completion is based on the retained implementation and verification evidence; the nominal sprint calendar is a plan, not proof that thirty days elapsed.

Verified Jira data export with all issues Done

```
CLF24 | Board 236 | 2026-10-08T05:28:25.812600+00:00
All issues assigned only to Marisetti Avinash
Columns: To Do > In Progress > Testing > Done

CLF24-1  E1  Done  E1 Identity and session security
CLF24-2  E2  Done  E2 Campus reporting and discovery
CLF24-3  E3  Done  E3 Private contact and recovery
CLF24-4  E4  Done  E4 Moderation and accountability
CLF24-5  E5  Done  E5 Secure build and quality assurance
CLF24-6  E6  Done  E6 Containers and secure deployment
CLF24-7  US01  Done  US01 Account registration and sign in
CLF24-9  US02  Done  US02 Report a lost item
CLF24-11  US03  Done  US03 Report a found item
CLF24-13  US04  Done  US04 Search verified reports
CLF24-15  US05  Done  US05 Private owner or finder contact
CLF24-17  US06  Done  US06 Owner-only recovery
CLF24-19  US07  Done  US07 Administrator moderation
CLF24-21  US08  Done  US08 Personal report tracking
CLF24-23  US09  Done  US09 Secure communication and sessions
CLF24-25  US10  Done  US10 Malicious content prevention
CLF24-27  US11  Done  US11 Security audit and monitoring
CLF24-29  US12  Done  US12 Private reply and abuse control
CLF24-31  US13  Done  US13 Secure Docker packaging
CLF24-33  US14  Done  US14 Kubernetes deployment
CLF24-35  US15  Done  US15 Verified delivery pipeline
CLF24-37  US16  Done  US16 Accessible consistent interface
CLF24-8  T01  Done  T01 Implement and verify Account registration and sign in
CLF24-10  T02  Done  T02 Implement and verify Report a lost item
CLF24-12  T03  Done  T03 Implement and verify Report a found item
CLF24-14  T04  Done  T04 Implement and verify Search verified reports
CLF24-16  T05  Done  T05 Implement and verify Private owner or finder contact
CLF24-18  T06  Done  T06 Implement and verify Owner-only recovery
CLF24-20  T07  Done  T07 Implement and verify Administrator moderation
CLF24-22  T08  Done  T08 Implement and verify Personal report tracking
CLF24-24  T09  Done  T09 Implement and verify Secure communication and sessions
CLF24-26  T10  Done  T10 Implement and verify Malicious content prevention
CLF24-28  T11  Done  T11 Implement and verify Security audit and monitoring
CLF24-30  T12  Done  T12 Implement and verify Private reply and abuse control
CLF24-32  T13  Done  T13 Implement and verify Secure Docker packaging
CLF24-34  T14  Done  T14 Implement and verify Kubernetes deployment
CLF24-36  T15  Done  T15 Implement and verify Verified delivery pipeline
CLF24-38  T16  Done  T16 Implement and verify Accessible consistent interface
```

Figure 17 Monochrome board view derived from verified Jira issue data




Figure 18 Actual signed-in Jira board with completed work




Figure 19 Nominal sprint forecast and compressed execution distinction

Metric	Interpretation / value
Sprint 1 committed estimate	36 story points
Sprint 2 committed estimate	34 story points

Metric	Interpretation / value
Actual Done story points	70
Laboratory defects	Six verified fix groups: invalid-host handling, login throttling, moderation pagination, closed-message UI, vulnerable initial dependencies and the TLS image executable capability.
Carry-over	No unresolved implementation defects among the recorded fix groups after retests. Campus SSO, server-side revocation and immutable logging remain production improvement work.
Velocity interpretation	Completed estimate per sprint in this compressed lab; not an empirically observed fifteen-day team velocity.

Daily Scrum entry 8 October 2026

Progress: implemented identity, reporting, moderation, contact and recovery; ran automated and browser tests; patched vulnerable dependencies. Plan: verify container and cluster deployment, synchronize Jira completion and package the final report. Blockers encountered: sandbox Docker/network access, sprint-name length, Windows locked dependency file and Jira browser authentication. Technical blockers were handled through authorized engine access, shorter names and a fresh runtime; browser screenshots depend on normal user sign-in.

Sprint review

The acceptance demonstration follows report submission → pending state → administrator verification → private contact and reply → reporter recovery. The screenshots and browser-e2e.json record that flow. Search and access-control tests cover the main abuse boundaries. Deployment observations are recorded in Phase 13 and its logs.

Retrospective and improvement actions

- Run dependency audit before choosing initial pins, then keep hash-locked dependencies in the build.
- Include pagination, closed-state feedback and cross-user denial cases in the first acceptance review.
- Before campus release, connect campus SSO and central session revocation, export audits to a separate integrity-protected destination, and validate capacity under a real load profile.

Phase 11 Secure Development and Build Environment

The local repository uses a main branch and a documented short-lived feature-branch/pull-request workflow. Secrets are supplied through environment or a Kubernetes Secret; generated local demonstration credentials and the .env file are ignored and excluded from the submission archive and Docker context.

Control	Evidence or production requirement
Least privilege	Non-root application process; admin/report-owner/participant route policies; read-only CI token permissions.
Secret management	APP_SECRET and Jira credentials read from environment; no Jira token in source/report/archive; local secret files ignored.
Dependency control	Explicit patched versions; requirements.lock hashes; pip-audit result retained.
Review and branch policy	Feature branch → review → main is the intended workflow. Hosted branch protection requires configuring a remote and is not claimed as enforced locally.
Reproducible build and integrity	Pinned Python image digest/dependencies where recorded; build log, image digest and package SHA256 retained.
Automated checks	Bandit, project AST check, unit/integration/system/fuzz tests and dependency audit.
Private artifact scope	Local repository; no public publication of private credentials or campus records.

Initial dependency scan recorded known advisories and was remediated with Flask 3.1.3, Werkzeug 3.1.9 and Click 8.3.3. The search query originally used only trusted SQL fragments and bound values; Bandit still flagged the dynamic construction. Refactoring to fixed SQL removed that warning without relying on a suppression. Final audit JSON and static-check JSON retain the actual results.

Actual local test and static check output

```
test_xss_escaped (test_app.CampusTests.test_xss_escaped) ... ok

----------------------------------------------------------------------
Ran 34 tests in 35.620s

OK

Source: evidence/tests-final.txt; static-check.json; bandit-final.json
{"tool": "project AST security check", "files_checked": 3, "findings": [], "passed": true}
```

Figure 20 Verbatim build and test output exported as monochrome evidence

Phase 12 Secure Coding and Refactoring

Before structure stored as nonexecuted teaching text

```
# Educational initial version. Never execute or deploy this example.
# Weakness 1: no owner authorization; user-supplied identifier controls the write.
def recover_item_before(conn, item_id):
    conn.execute(f"UPDATE reports SET status='recovered' WHERE id={item_id}")

# Weakness 2: trusting a form role allows privilege escalation; raw passwords stored.
def register_before(conn, form):
    conn.execute('INSERT INTO users(email,password_hash,role) VALUES(?,?,?)',
                 (form['email'],form['password'],form['role']))
```

After authorization and validation

```
def can_manage(user, report):
    return bool(user and user['id'] == report['reporter_id'])

# recover() validates CSRF in middleware, then:
if not can_manage(g.user, report):
    abort(403)
if report['moderation'] != 'verified' or report['status'] != 'open':
    abort(409)
# UPDATE binds report ID, user ID and timestamp as parameters.
```

```
role = request.form.get('role')
if role not in ('student', 'faculty'):
    raise ValueError('Select student or faculty.')
password = validate_text(request.form.get('password'), 'Password', 12, 128)
password_hash = generate_password_hash(password, method='scrypt')
```

Improvement	Security and maintainability outcome	Retest
Central owner policy and bound update	Cannot use another report ID to change recovery; repeated rule is readable and testable.	test_unauthorized_recovery; test_recovery_idempotency
Role allowlist and password hash	Self-registration cannot create admin authority; password not stored as plaintext.	test_registration_admin_escalation_ denied; test_password_not_plaintext
Fixed search SQL and validated input	SQL structure stays constant; malicious markup remains escaped; excessive fields fail safely.	test_sql_injection_search; test_xss_escaped; test_fuzz_report_boundary
Atomic attempt reservation and source scope	Concurrent requests cannot exceed the reservation window by racing the counter; another source is not denied solely by account-level attempts.	test_login_throttling; test_attacker_cannot_lock_out_othe r_source
Safe invalid-host error handling	Rejects malicious Host without a template routing error.	test_host_validation

Connection-source limiting uses the direct remote address, stored as a keyed hash. Behind a shared reverse proxy, multiple clients can share that source. Production ingress must enforce its own client-IP rate limits; arbitrary forwarded headers are not trusted by this app. Sensitive text is escaped, errors are bounded and generic where appropriate, and audit metadata excludes password/message contents.

Phase 13 Docker and Kubernetes Development

Docker packages the app behind Gunicorn with an unprivileged UID 10001. A writable data volume holds SQLite; the image filesystem is read-only at runtime. Capabilities are dropped, privilege escalation is disabled, health probes are defined and CPU/memory are bounded. Caddy supplies local HTTPS on port 8443 with an internal certificate authority.

Runtime	Observed status	Evidence
Docker build	Passed; pinned app and TLS images built	evidence/docker-build-final.txt
Docker process and health	Healthy; non-root read-only filesystem; all capabilities dropped	evidence/docker-runtime.json
TLS endpoint	Docker and Kubernetes TLSv1.3; certificate and hostname checks passed	evidence/docker-tls-smoke.json; kubernetes-tls-smoke.json
Kubernetes rollout	Isolated kind deployment 2/2 ready; app and TLS sidecar	evidence/kubernetes.txt
Kubernetes controls	Restricted namespace; non-root; seccomp; PVCs; ClusterIP; limits verified. NetworkPolicy enforcement not established on default kind CNI.	deploy/kubernetes.yaml; evidence/kubernetes-security.json

Actual Docker runtime and validated HTTPS


```
{"name": "/sse-app-1", "image_id":
"sha256:14c0f36b96b9336f56e17e4b74de4fd4fdc051b72765f29018394e75affb9829", "user": "10001:10001",
"running": true, "health": "healthy", "read_only": true, "cap_drop": ["ALL"], "security_options": ["no-
new-privileges:true"], "memory_bytes": 268435456, "nano_cpus": 1000000000, "port_bindings": {"8080/tcp":
[{"HostIp": "127.0.0.1", "HostPort": "8080"}]}}
{"name": "/sse-tls-1", "image_id":
"sha256:31b34af01e55164dd194dc6856fe14e2488d1dea5c4470235d5591df1c12cd85", "user": "10001:10001",
"running": true, "health": null, "read_only": true, "cap_drop": ["ALL"], "security_options": ["no-new-
privileges:true"], "memory_bytes": 134217728, "nano_cpus": 0, "port_bindings": {"8443/tcp": [{"HostIp":
"127.0.0.1", "HostPort": "8443"}]}}

{"version": "TLSv1.3", "cipher": "TLS_AES_128_GCM_SHA256", "certificate_validation": "passed against
local lab CA", "hostname_validation": "localhost passed"}
```


Figure 21 Docker runtime evidence exported from recorded command output

Actual Kubernetes rollout and validated HTTPS

```
Image: "campus-tls:1.0.0" with ID
"sha256:31b34af01e55164dd194dc6856fe14e2488d1dea5c4470235d5591df1c12cd85" not yet present on node
"campus-lab-control-plane", loading...
namespace/campus-lost-found created
persistentvolumeclaim/campus-data created
deployment.apps/campus-app created
service/campus-app created
networkpolicy.networking.k8s.io/campus-isolation created
configmap/campus-tls-config created
persistentvolumeclaim/campus-tls-data created
secret/campus-secret created
Waiting for deployment "campus-app" rollout to finish: 0 of 1 updated replicas are available...
deployment "campus-app" successfully rolled out
Demo identities provisioned; credential values were not printed.
NAME                              READY   STATUS    RESTARTS   AGE   IP           NODE
NOMINATED NODE   READINESS GATES
pod/campus-app-5d94c844fd-gkz44   2/2     Running   0          17s   10.244.0.7   campus-lab-control-
plane   <none>           <none>

NAME                 TYPE        CLUSTER-IP     EXTERNAL-IP   PORT(S)             AGE   SELECTOR
service/campus-app   ClusterIP   10.96.71.169   <none>        8443/TCP,8080/TCP   17s   app=campus-app

NAME                                     STATUS   VOLUME                                     CAPACITY
ACCESS MODES   STORAGECLASS   VOLUMEATTRIBUTESCLASS   AGE   VOLUMEMODE
persistentvolumeclaim/campus-data       Bound    pvc-5b6d13af-ac68-4330-a371-caad57927572   1Gi
RWO            standard       <unset>                 17s   Filesystem
persistentvolumeclaim/campus-tls-data   Bound    pvc-82c29669-7706-45fe-8d87-6850e037cccf   128Mi
RWO            standard       <unset>                 17s   Filesystem

NAME                                          POD-SELECTOR     AGE
networkpolicy.networking.k8s.io/campus-isolation   app=campus-app   18s

{"version": "TLSv1.3", "cipher": "TLS_AES_128_GCM_SHA256", "certificate_validation": "passed against
local lab CA", "hostname_validation": "localhost passed"}
```

Figure 22 Kubernetes deployment evidence exported from recorded command output

Container security practice	Implementation
Minimal versioned image	Python slim runtime, explicit dependency pins; image digest captured.
Non-root execution	USER 10001:10001; writable volume owned by that identity.
Restricted filesystem and privileges	read_only root; /tmp tmpfs; cap_drop ALL; no-new-privileges.
Controlled exposure	Host loopback bindings; TLS 8443; internal app traffic on 8080.
Secrets outside image	Environment APP_SECRET; Docker context excludes local credential files.
Resource and health controls	App 256 MiB/1 CPU; Gunicorn bounded workers; DB health endpoint.

Kubernetes control	Configuration and prerequisite
Namespace isolation	campus-lost-found with restricted Pod Security Admission labels.
Process least privilege	runAsNonRoot, UID/GID 10001, RuntimeDefault seccomp, no escalation, dropped capabilities.
Storage and availability	1Gi PVC, one replica, Recreate strategy; SQLite requires exclusive single-node use.

Kubernetes control	Configuration and prerequisite
Restricted exposure	ClusterIP with unprivileged TLS sidecar on 8443. Loopback port-forward HTTPS was validated against the exported lab CA. Production requires a campus certificate and controlled ingress.
Network policy	Ingress limited to ingress-nginx namespace; egress denied. Enforcement depends on the CNI; kind default networking does not establish enforcement.
Secret management	campus-secret is created from generated local configuration without storing its value in the manifest.
Resource limits	100m/96Mi requested; 1 CPU/256Mi limits; readiness and liveness probes.

Phase 14 CI and Security Testing

The GitHub Actions workflow defines checkout, pinned dependency installation, unit/integration/system/fuzz tests, static checks, dependency audit, Docker build and image packaging. A local equivalent pipeline runs the same checks and preserves logs. A hosted GitHub Actions run is not claimed without a remote run record.

Test category	Concrete checks	Result evidence
Unit module tests	validate_text boundaries and can_manage ownership policy.	tests-final.txt
Integration tests	Database-backed pending visibility, moderation, messaging and recovery state checks.	tests-final.txt
System validation	Report → verify → private message → reply → recovery, both automated and browser UI.	test_end_to_end_report_verify_contact_recover; browser-e2e.json
Simple fuzzing	Nine title-boundary inputs including empty/oversize/control/SQL/markup/Unicode/wildcards. No unhandled 500; accepted markup escapes on display.	test_fuzz_report_boundary
Static analysis	Bandit and project AST rules for dangerous execution debug and literal credentials.	bandit-final.json; static-check.json
Dependency audit	Pinned application dependency inventory checked against advisory service.	dependency-audit-before.json; dependency-audit.json
Container integration	Health TLS and authenticated workflow against running container where logged.	docker-e2e.json; kubernetes-e2e.json

Defect	Severity	Observed issue	Fix	Retest
DEF01	Medium	Invalid Host caused error-template routing failure	Return safe plain error if no url_rule exists	test_host_validation passes
DEF02	Medium	Account-wide / nonatomic login attempt bound	Immediate transaction; keyed source/account scope	Throttle and different-source tests pass
DEF03	Medium	Old pending reports unreachable after 100 new reports	Pending-first paginated moderation queue	test_admin_pagination passes
DEF04	Low	Reply input visible for closed reports	Hide closed report reply input; retain server denial	test_closed_inbox_hides_reply passes
DEF05	High	Known vulnerable initial dependency pins	Upgrade to patched versions; audit again	No known vulnerabilities in final audit
DEF06	Medium	Caddy executable file capability prevented startup after all capabilities were dropped	Remove executable file capability; serve unprivileged 8443 as UID 10001	Docker and Kubernetes TLS workflows pass

The first 31-test run exposed DEF01; final 34-test retests pass. Raw logs distinguish environment setup failures from application defects. These results verify the laboratory implementation; no production exploitation is claimed.

Phase 15 Logging Monitoring Hardening and Deployment

Event	Logged fields	Handling
login_failed / login_throttled	Event outcome timestamp; no password	Investigate elevated denial rate; do not expose identifiers on public dashboard.
authorization_denied / recovery_denied	Actor object event outcome UTC time	Alert on repeated unauthorized actions.
report_verified / report_removed	Actor report ID decision outcome time	Reason/moderator stored on report; audit provides accountability.
item_recovered	Actor report ID success time	Trace integrity-sensitive state change.
message_sent / message_reply	Actor report ID event outcome time	No message body in audit; participant privacy preserved.
registration / login_success / logout	Event actor when authenticated outcome timestamp	Support identity lifecycle review without credential values.

Metric or alert	Threshold or signal	Operator response
Login-denial rate	More than 20 denials in five minutes per source/account group	Review brute-force/lockout pattern and ingress rate controls.
Authorization denial	More than five 403 policy denials in five minutes	Review actor/object access attempts.
Moderation queue age	Pending report older than 24 hours	Administrator checks backlog and removes unsafe content.
Service health and error rate	Health probe failures or 5xx rate over 1%	Inspect process/storage/resource conditions and rollback verified image.
Resource saturation	Memory above 80% or disk free below 15%	Check retention and add capacity; do not delete required evidence blindly.
Message throttling	Repeated rate-limit responses	Investigate harassment and restrict abusive accounts through a future admin policy.
Backup freshness	No verified backup in 24 hours	Run encrypted backup and perform restore verification.

Monitoring metrics are a defined operating plan. The implemented lab exposes health and administrator audit views; a full metrics collector and alert-routing service are future production integrations. Audit records share the SQLite authority with the app and are not independently immutable.

- Access: restrict host/cluster administration, use MFA on Jira and deployment accounts, provision admin separately and review privileges.
- Ports/services: expose only the intended TLS endpoint; keep app and database local/internal; disable development debug.
- Secrets: random APP_SECRET, private local-file ACL, Kubernetes Secret/RBAC; rotate credentials through an operator process.
- Updates: audit dependencies and base image before each release; retain reviewed digests and rollback image.
- Permissions: non-root container, read-only rootfs, cap drop, restricted namespace and bounded writable volume.
- Physical controls: lock workstation and campus server area; restrict removable media and backup access.
- Operational controls: documented recovery, retention policy, encrypted backups, restore exercises and incident owner.
- Deployment checklist: validate configuration; run tests and audits; verify health and TLS; provision admin; test access denial; capture rollout and integrity evidence.

Phase 16 Final Security Review

Trace step	Linked evidence
Requirement	R06 Reporter-only recovery
Use case	UC05 Mark item recovered
DFD	P3 Contact/recovery → D2 Reports; audit to D4
Threat	TH03 Tamper with another user’s recovery state
Vulnerability	V01 Nonexecuted initial teaching function lacks owner check
Attack tree	Authorization bypass branch: choose victim ID AND defeat owner policy
User story	US06 Owner-only recovery; Epic E3
Sprint task	Sprint 1 T06; Jira CLF24-18
Implementation	app.py can_manage() and recover(); bound update and open/verified precondition
Test	test_unauthorized_recovery; test_recovery_idempotency; browser recovery result
Deployment control	TLS edge, externally supplied session secret, non-root read-only container, private DB volume

Highest-risk issue	Enforced controls and remaining boundary
Unauthorized state modification	Reporter/admin policies, CSRF, bound SQL and state checks; denial regression tests.
Private conversation or credential disclosure	Participant-scoped queries, email omission, password hashing, TLS and secure cookies; privileged storage operators remain trusted.
Compromised build/runtime	Patched pinned dependencies, clean audit/static checks, isolated image and cluster controls; public production release requires verified certificate/SSO and operational configuration.

Remaining limitations and future improvements

First, self-registration does not verify campus membership; integrate campus SSO, account lifecycle management and centralized revocable sessions before production use. Second, SQLite and local operator-controlled audit storage fit this single-node lab but do not provide multi-node availability or immutable forensic logging; move to a managed relational store with encrypted backups and a separate audit destination when campus scale requires it.

Final observations

The case-study identifiers align from requirements through tests and deployment controls. Technical results are supported by source, raw logs, API records and application screenshots. Nominal sprint schedules and forecast charts are distinguished from compressed laboratory execution; modelled risk is distinguished from observed defects. The final evidence index records exactly which runtime checks completed.

Authoritative technical references

Flask security guidance
https://flask.palletsprojects.com/en/stable/web-security/

Werkzeug changes
https://werkzeug.palletsprojects.com/en/stable/changes/

Jira REST projects
https://developer.atlassian.com/cloud/jira/platform/rest/v3/api-group-projects/

Jira workflows
https://developer.atlassian.com/cloud/jira/platform/rest/v3/api-group-workflows/

Jira sprint API
https://developer.atlassian.com/cloud/jira/software/rest/api-group-sprint/

kind quick start
https://kind.sigs.k8s.io/docs/user/quick-start/

Kubernetes security checklist
https://kubernetes.io/docs/concepts/security/security-checklist/