OpTool User Guide

Carsten Dominik, Michiel Min, and Ryo Tazaki

October 2022, version 1.9.8

1. Introduction

This tool produces complex dust particle opacities right from the command line. It is derived from Michiel Min's DHS OpacityTool and also implements Ryo Tazaki's MMF theory for highly porous aggregates.

1.1. Capabilities

- stand-alone tool, fully command line driven, no input files need to be edited
- full scattering matrix output in several formats, including for RADMC-3D
- combining materials through mixing into a complex grain with porosity
- built-in: a curated collection of materials for applications in astronomy
- external refractive index data can be used just as easily
- computational methods: (i) **DHS** (**Distribution of Hollow Spheres**) for *irregular grains* and *low-porosity* aggregates. Standard **Mie theory** for *perfect spheres* is available as a limiting case. (ii) **MMF** (**Modified Mean Field**) theory for *high-porosity/fractal aggregates*. (iii) **CDE** approximation in the Rayleigh limit.
- Python interface module for plotting and post-processing

1.2. Terms of use

optool is distributed under the MIT license and can be used, changed and redistributed freely. But we do ask you to provide a reference to optool when using it. Relevant references are listed below and the corresponding BibTeX entries are available in the file optool.bib. optool is hosted on github.

- optool: Dominik, C., Min, M. & Tazaki, R. 2021, Optool, 1.9, Astrophysics Source Code Library, ascl:2104.010
- DHS model for irregular grains: Min, M. et al. 2005, A&A, 432, 909
- MMF model for aggregates: Tazaki, R. & Tanaka, H. 2018, ApJ 860, 79
- DIANA standard Opacities: Woitke, P. et al. 2016, A&A 586, 103
- References to refractive index data used in your particular application.

2. Examples

A simple grain made only of the default pyroxene, for the default grain size distribution $(a^{-3.5}$ powerlaw from 0.05 to 3000 μ m), on the default wavelength grid (0.05 μ m to 1cm).

```
optool pyr
```

Include the scattering matrix in the produced output

```
optool pyr -s
```

Reproduce the DIANA standard dust model, using a specific pyroxene (70% Mg) and carbon, in a mass ratio 0.87/0.13, and with a porosity of 25%.

```
optool pyr-mg70 0.87 c 0.13 -p 0.25
```

List the built-in materials

```
optool -c
```

Add a water ice mantle (built-in data from Warren+08) that is 20% of the core mass

```
optool pyr-mg70 0.87 c 0.13 -m h2o-w 0.2 -p 0.25
```

Like the previous example, but use ice refractive index data from a separate file.

```
optool pyr-mg70 0.87 c 0.13 -p 0.25 -m data/ice_hudgins.dat 0.2
```

Pure water ice grains in a narrow size distribution from 1 to 3 microns, with 15 sample sizes following an $f(a) \propto a^{-2.5}$ powerlaw size distribution. Also, restrict the wavelength range to 10-100 μ m, and turn off DHS to get perfect spheres (Mie).

```
optool h2o -a 1 3 2.5 15 -l 10 100 -mie
```

Use a log-normal size distribution around 2 μ m with σ =0.7 instead.

```
optool h2o -a 0.1 30 2.0:0.7 -l 10 100 -mie
```

For silicon carbide, compute the opacity of a single grain size $(2.5\mu \text{m})$ at $\lambda=8.9\mu\text{m}$.

```
optool -a 2.5 -1 8.9 sic
```

Represent the default dust model (DIANA, you also get this when you do not give any materials at all) in 42 grain sizes, and produce input files for RADMC-3D, one for each grain size, with full scattering matrix, chopping 3 degrees from the scattering peak.

```
optool -na 42 -d -s -radmc -chop 3
```

Use MMF to compute the opacities of dust aggregates made of pyroxene monomers. Use a monomer radius of 0.3 μ m to construct aggregates with compact-volume radii between 10 and 30 μ m, and a fractal dimension of 1.9.

```
optool pyr -a 10 30 -mmf 0.3 1.9
```

Compute CDE for small graphite grains

```
optool gra -a 0.01 0.1 -l 1 30 -cde
```

3. Installation

You can download, compile, and install optool with these simple steps, using the freely available GNU FORTRAN compiler gfortran.

```
git clone https://github.com/cdominik/optool.git  # clone repository
cd optool  # enter code directory
make multi=true  # compile with multicore support

make install bindir=~/bin/  # optional: copy binaries to binary path
pip install -e .  # optional: install the python module
```

In the compilation step, use multi=true to add multicore support (recommended!), ifort=true to use the Intel fortran compiler instead of gfortran, and fits=true to add support for writing FITS files¹. The executable is called optool. The make install step copies it and also optool2tex and optool-complete into bindir.

For shell command line completion support, check the file optool-complete.

4. Command line arguments

-h [OPT]

Show command line options or specific information about option -OPT.

- -q Reduce output to STDOUT to essential warnings and errors.
- -v More verbose output to STDOUT.

4.1. Grain composition

If no composition is specified, the (DIANA) default is -c pyr 0.87 -c c 0.13 -p 0.25.

-c List available built-in materials (the keys for the -c and -m options).

[-c] KEY-or-FILE [MFRAC]

Specify a material to include in the grain. KEYorFILE can be the key for a builtin material, or the path to an lnk file. MFRAC is the mass fraction (default 1.0) of the material. You can give up to 20 materials to build up the grain. Mass fractions do not have to add up to one, they will be renormalized. All materials will be mixed together using the Bruggeman rule, and vacuum can be added through the porosity. A -c switch before each KEY-or-FILE is optional.

-m KEY-or-FILE [MFRAC]

Like -c, but place this material into the grain mantle. Multiple mantle materials will be mixed using the Bruggeman rule, and than that mix will be added to the core using the *Maxwell-Garnett* rule. The -m is *not* optional, it must be present.

-p POROSITY [P_MANTLE]

Porosity, the *volume* fraction of vacuum, a number smaller than 1. The default is 0. A single value will apply to both core and mantle, but a second value will be specific for the mantle (and may be 0).

-diana, -dsharp, -dsharp-no-ice

Use literature standard compositions DIANA (Woitke+2016) or DSHARP (Birnstiel+2018).

¹This requires the cfitsio library to be installed on your system.

4.2. Grain geometry and computational method

If no method is explicitly specified, the default is **-dhs 0.8**, i.e. DHS with $f_{\text{max}}=0.8$.

-dhs [FMAX]

Use the *Distribution of Hollow Spheres* (DHS, Min+ 2005) approach to model deviations from perfect spherical symmetry and low-porosity aggregates. Spheres with inner holes with volume fractions between 0 and f_{max} (default 0.8) are averaged to mimic irregularities. f_{max} =0 means to use solid spheres (Mie theory), i.e. perfectly regular grains. For backward compatibility, -fmax can be used instead of -dhs.

-mmf [AO [DFRAC-OR-FILL [KF]]]

Use Modified Mean Field theory (MMF, Tazaki & Tanaka 2018) to compute opacities of highly porous or fractal aggregates. -c, -m, and -p determine the composition of monomers with radius AO (default $0.1\mu\text{m}$). Particles will be aggregates with a compact size given by the -a switch, giving rise to $N=a^3/a_0^3$ monomers. DFRAC-OR-FILL specifies either the fractal dimension (if >1) or the volume filling factor (if <1). The default is 0.2. KF may be used to change the default prefactor.

-mie

Do a standard Mie calculation for perfect spheres. This is short for **-dhs 0** .

-cde

Compute CDE (continuous distribution of ellipsoids) Rayleigh limit opacities.

4.3. Grain size distribution

-a AMIN [AMAX [APOW [NA]]]

(powerlaw size distribution)

Specify (minimum) grain radius, and optionally maximum grain radius, the size distribution powerlaw and the number of size bins. You may also use options to set individual values with **-amin**, **-amax**, **-apow**, **-na**. The defaults are 0.05 μ m, 3000 μ m, 3.5, and 15 per size decade with a fixed minimum of 5, respectively.

> If only a single size is specified with -a, then $a_{max}=a_{min}$ and $n_a=1$ are implied.

-a AMIN AMAX AMEAN: ASIG [NA]

([log-]normal size distribution)

Specify the centroid size and the logarithmic width for a log-normal size distribution. You may also use **-amean** and **-asig** options to set these values. If ASIG is negative, create a normal distribution with that width (in μ m) around AMEAN.

-a FILE

Read the size distribution from a file. The file format is described in appendix B. To get an example file optool_sd.dat, run optool with the option -wgrid.

4.4. Wavelength grid

-1 LMIN [LMAX [NLAM]]

Specify the (minimum) wavelength, and optionally the maximum wavelength and the number of wavelengths points for the construction of the wavelength grid. The default values are $0.05 \mu m$, $10000 \mu m$, and 300, respectively. You may also use the options -lmin, -lmax, and -nlam (or -nl) to set individual values.

> If only one wavelength is specified with -l, then $\lambda_{\max} = \lambda_{\min}$ and $n_{\lambda} = 1$ are implied.

-1 FILE

Read the wavelength grid from FILE. To get an example file optool_lam.dat, run optool with the option -wgrid. An lnk file could be used here as well!

4.5. Controlling the output

The standard output is the file dustkappa.dat, with the opacities and the asymmetry parameter g. The following options control and extend the output.

-o [DIR]

Put the output files in directory DIR instead of the current working directory. ./output will be used if -o is present but DIR is not specified.

-s [NANG]

Include the scattering matrix in the output. NANG may optionally change the the number of equally-spaced angular grid points to cover the range of angles between 0 and 180 degrees. The default for NANG is 180 and should normally be just fine.

-d [NSUB]

Divide the computation up into n_a parts to produce a file for each grain size. Each size will be an average over a range of NSUB (default 5) grains around the real size.

-chop [NDEG]

Cap the first NDEG (2 if unspecified) degrees of the forward scattering peak.

-fits

Write dustkappa.fits instead of ASCII output. With -d, write na files.

-radmc [LABEL]

RADMC-3D uses a different angular grid and scattering matrix normalization. File names will contain LABEL if specified and have the extension .inp.

-print [VAR]

Write to STDOUT instead of files. The default is to write λ , $\kappa_{\rm abs}$, $\kappa_{\rm sca}$, $\kappa_{\rm ext}$, and g. When VAR is any of kabs, ksca, kext, or g, write only that, without header. You can use this to extract a single value, for example the 850μ m extinction opacity of grains between 1 and 3mm: optool -a 1000 3000 -l 850 -print kext

-wgrid

Write the files optool_sd.dat and optool_lam.dat with the grain size distribution and the wavelengths grid, respectively.

5. Material properties

optool needs refractive index data to work. For your convenience, a useful list of materials is compiled into optool. You can also find and use other data.

5.1. Built-in materials

To access one of the built-in materials, specify the corresponding key string like pyr-mg70. In each material class we have selected a useful default, accessible with an even simpler generic key (for example, pyr is an alias for pyr-mg70). Most of the built-in refractive index datasets have a reasonably wide wavelength coverage - the few exceptions are highlighted by bold-face numbers. If a material is being used outside of the measured region, optool will still function, using extrapolated optical properties.

Even the limited number of materials we have selected to include with optool can be daunting. To get started with some kind of standard opacity, we recommend to work with pyroxene pyr, carbon c, and, at low temperatures, water ice h2o (Woitke+ 2016). If you need to account for sulfur, you may want to include troilite tro (Birnstiel+ 2016).

Table 1: Built-in materials

-c Key	-c Key	Material	State	ρ	λ_{min}	$\lambda_{\sf max}$	Reference
generic	full key			g/cm ³	μ m	μ m	
-	pyr-mg100	MgSiO ₃	amorph	2.71	0.2	500	Dorschner+95
	pyr-mg95	$Mg_{0.95}Fe_{0.05}SiO_3$	amorph	2.74	0.2	500	Dorschner+95
	pyr-mg80	$Mg_{0.8}Fe_{0.2}SiO_3$	amorph	2.9	0.2	500	Dorschner+95
pyr	pyr-mg70	$Mg_{0.7}Fe_{0.3}SiO_3$	amorph	3.01	0.2	500	Dorschner+95
	pyr-mg60	$Mg_{0.6}Fe_{0.4}SiO_3$	amorph	3.1	0.2	500	Dorschner+95
	pyr-mg50	$Mg_{0.5}Fe_{0.5}SiO_3$	amorph	3.2	0.2	500	Dorschner+95
	pyr-mg40	$Mg_{0.4}Fe_{0.6}SiO_3$	amorph	3.3	0.2	500	Dorschner+95
ens	pyr-c-mg96	$Mg_{0.96}Fe_{0.04}SiO3$	cryst	2.8	2.0	99	Jäger+98
ol	ol-mg50	MgFeSiO ₄	amorph	3.71	0.2	500	Dorschner+95
	ol-mg40	$Mg_{0.8}Fe_{1.2}SiO_4$	amorph	3.71	0.2	500	Dorschner+95
for	ol-c-mg100	Mg_2SiO_4	cryst	3.27	5.0	200	Suto+06
	ol-c-mg95	$Mg_{1.9}Fe_{0.1}SiO_4$	cryst	3.33	2.0	8190	Fabian+01
fay	ol-c-mg00	Fe_2SiO_4	cryst	4.39	3.0	250	Fabian+01
	astrosil	MgFeSiO ₄	mixed	3.3	6e-5	1e5	Draine+03
С	C-Z	С	amorph?	1.8	0.05	1e4	Zubko+96
	c-p	С	amorph	1.8	0.11	800	Preibisch+93
gra	c-gra	C graphite	cryst	2.16?	0.001	1000	Draine+03
org	c-org	CHON organics	amorph	1.4	0.1	1e5	Henning+96
	c-nano	C nano-diamond	cryst	2.3	0.02	110	Mutschke+04
iron	fe-c	Fe	metal	7.87	0.1	1e5	Henning+96
tro	fes	FeS	metal	4.83	0.1	1e5	Henning+96
	sic	SiC	cryst	3.22	0.001	1000	Laor93
qua	sio2	SiO ₂	amorph	2.65	0.0006	500	Kitamura+07
cor	cor-c	Al_2O_3	cryst	4.0	0.5	40	Koike+95
h2o	h2o-w	Water ice	cryst	0.92	0.04	2e6	Warren+08
	h2o-a	Water ice	amorph	0.92	0.04	2e6	Hudgins+93
co2	co2-w	CO ₂ ice	cryst	1.6	0.05	2e5	Warren+86
nh3	nh3-m	NH_3 ice	cryst	0.75	0.14	200	Martonchik+83
СО	co-a	CO ice	amorph	0.81	3.8	5.8	Palumbo+06
	co2-a / c	CO ₂ ice	am / cr	1.2	2.5	20	Gerakines+20
	ch4-a / c	CH₄ ice	am / cr	0.47	2.0	20	Gerakines+20
	ch3oh-a / c	CH₃OH ice	am / cr	0.78/1.02	2.0	24	Gerakines+20

5.2. External refractory index files (lnk files)

optool can use external refractive index data in files with the following format²:

- The file may start with several comment lines (lines starting with !, #, or *).
- The next line contains two numbers, the number of wavelengths n_{λ} and the specific density ρ of the material in g/cm³.
- The remaining lines should form three columns of data: $\lambda[\mu m]$ (sorted either up or down), and the real and imaginary parts of the refractive index, n and k.

We provide additional data ready for use with optool in a separate repository. Other resources are the Jena database, ARIA and original papers in the literature. Don't forget to add the line with n_{λ} and ρ ! If that is not possible, optool will count the lines and you can specify the density after the mass fraction, like this: optool -c path/to/file.lnk 0.7 3.42. Please do not forget to include references for any optical properties used in your study.

²This file structure is also compatible with what is needed to set the wavelength grid with -1 FILE.

6. Output files

dustkappa.dat

This is an ASCII file containing the basic opacity results. It starts with a comment section describing the dust model and also showing the exact command line that was used to produce the file. The header is followed by the format number (3, currently), followed by the number of wavelengths in the grid, both on lines by themselves. This is followed by a block with these columns:

- 1. wavelength λ [micron]
- 2. mass absorption cross section $\kappa_{\rm abs}$ [cm²/g]
- 3. mass scattering cross section $\kappa_{\rm sca}$ [cm²/g]
- 4. asymmetry parameter g

dustkapscatmat.dat

ASCII file with cross sections and full scattering matrix. It is an extended version of the dustkappa.dat file. This file has a format number (0), the number of wavelengths and then the number of angular points after the comment section. After an empty line, the same opacity block as in dustkappa.dat is present. Another empty line is followed by a list of the grid angles, another empty line, and then the scattering matrix elements for all wavelengths and all angles. The comment section at the start of the file shows the structure in a formal way. See the appendix for information about the normalization of the scattering matrix and about the angular grid that is used for it. Also, see the -radmc switch which will modify³ the output to make sure it can be used as an input file for RADMC-3D.

To save space, optool can write a *sparse file* that stores the full scattering matrix only for selected wavelengths (for example, the ones that will be used for image generation). Use -sparse LAM or -sparse LAM1 LAM2 to define a wavelength (interval)⁴ for the matrix to be stored. Multiple -sparse switches are allowed.

dustkappa.fits

The FITS-file is written when using the -fits switch. It has two HDU blocks. The first contains the cross sections per unit mass (units cm²/g). It is a $n_{\lambda} \times 4$ matrix with these columns: wavelength in micron, $\kappa_{\rm ext}$, $\kappa_{\rm abs}$, $\kappa_{\rm sca}$. The second block is a $n_{\lambda} \times 6 \times n_{\rm ang}$ matrix, containing the 6 elements of the scattering matrix (F₁₁, F₁₂, F₂₂, F₃₃, F₃₄, and F₄₄) for $n_{\rm ang}$ equidistant scattering angles from forward scattering (element 0) to backward scattering (element $n_{\rm ang}$ -1), for each λ .

optool.tex

As a little gimmick, you can run optool2tex with the exact same command line arguments as used in an optool run. optool.tex then contains text and a table, describing the methods used for the opacity computation and listing the composition of the grains. All relevant references are given - the BibTeX file optool.bib is required for the file to be processed properly. You can rework this text to include it into your paper. For more details, read the comment section in optool2tex.

³This includes a change of the angular grid and a change in the normalization of the scattering matrix. ⁴The file will always have the matrix for at least two adjacent wavelengths around the specified λ , so that an interpolation to the exact wavelenth will be stable.

7. Python interface

optool comes with a python module optool.py that runs optool in the background⁵ and puts all computed quantities as numpy arrays into a python object. This makes it straight forward to inspect and further process the output. Here is how to use it:

```
import optool
p = optool.particle('~/bin/optool pyr 0.8 -m ice 0.2 -na 24 -d')
```

The argument to optool.particle() must be a valid shell command⁶ to run optool, if necessary with the full path to the optool binary. Depending on the presence of the optool's -d switch, the command will produce opacities either for $n_p = 1$ particle, or for $n_p = n_a$ particles. Most of the attributes (with the exception of the global wavelength and angular grids) will therefore be arrays with the first dimension equal to n_p , even if $n_p = 1$. The resulting object will have the following attributes:

Attribute	Type/Shape	Quantity		
cmd	string	The full command given in the particle() call		
radmc	boolean	Output follows RADMC conventions		
scat	boolean	Scattering matrix is available		
nlam	int	Number of wavelength points		
lam	float[nlam]	The wavelength grid		
nang	int	Number of scattering angles		
scatang	float[nang]	The angular grid		
materials	[[[]]]	Lists with [location, m_{frac} , ρ ,material]		
np	int	Number of particles, either 1 or (with -d) n _a		
fmax	float[np]	Maximum volume fraction of vacuum for DHS		
<pre>pcore, pmantle</pre>	float[np]	Porosity of the core/mantle material		
amin, amax	float[np]	min/max grain size used for each particle		
nsub	int[np]	Number of sizes averaged for each particle		
apow	float[np]	Negative size distribution power law (e.g. 3.5)		
amean, asig	float[np]	Centroid & width of (log-)normal distribution		
a1, a2, a3	float[np]	Mean $< a >$, $\sqrt{< a^2 >}$, and $\sqrt[3]{< a^3 >}$		
rho	float[np]	Specific density of grains		
kabs,ksca,kext	float[np,nlam]	Absorption, scattering, extinction cross section		
gsca	float[np,nlam]	Asymmetry parameter		
f11,, f44	<pre>float[np,nlam,nang]</pre>	Scattering matrix element F_{11}, \ldots, F_{44}		
chop	float[np]	Degrees chopped off forward scattering		
plot()	method	Plot the cross sections and matrix elements		
computemean()	method	Compute Planck/Rosseland mean opacities		
<pre>tmin,tmax,ntemp</pre>	float,float,int	Temperature grid for mean opacities		
temp	<pre>float[ntemp]</pre>	Temperatures used for mean opacities		
kplanck, kross	<pre>float[np,ntemp]</pre>	Mean opacities, after calling computemean()		
norm	string	Current scattering matrix normalization		
scatnorm()	method	Check/change scat. matrix normalization		
sizedist()	method	Sum opacities over a size distribution		

 $^{^{5}}$ The module runs the command as a subprocess, with output to a temporary subdirectory.

⁶As a string, or as a list like ['/path/to my/command', 'arg1', 'arg2',...].




Figure 1: Screenshot of plots created by running p.plot() on an optool particle.

Applying the plot() method to a particle object like p.plot() will produce:

- a plot showing the opacities κ_{abs} , κ_{sca} , and κ_{ext} as a function of wavelength, along with the asymmetry parameter g (on a linear y-scale). Note that the blue g curve does not have its own axis, imagine the full y axis going from 0 to 1 for g.
- a plot showing the scattering matrix elements as a function of scattering angle, with sliders to go through grain sizes and wavelengths. When interpreting the y axis, note that we plot the positive/negative \log_{10} of positive/negative matrix elements, compressing the range from 10^{-2} to 10^2 into a line (use the grey lines as a guide, ignore the y-axis labels).
- If the computemean method has been called first, the mean opacities κ_{Planck} and κ_{Ross} are shown in a separate plot. The mean opacities are per unit of grain mass, so please apply a dust-to-gas mass ratio to obtain opacities for a gas-dust mixture.

The python module has a few more tricks up its sleeve (for details check the documentation inside the Python module file optool.py):

• A lnktable class to read, plot, modify and write lnk files.

```
x = optool.lnktable('lnk_data/sio2-Kitamura2007.lnk')
x.plot()
```

• Compute Planck and Rosseland mean opacities

```
p = optool.particle('optool pyr 0.87 c 0.13 -p 0.25')
p.computemean(tmin=10.,tmax=1500.,ntemp=300)
```

• Particle arithmetic: multiplying optool.particle objects with factors and adding them, or applying size distributions to a pre-computed set of opacities. The following page contains a number of examples.

Compute the opacities of 100 olivine silicate grain sizes and of 50 carbon grain sizes, and store the opacities in cache directories. This works by specifying the directory as the second argument. In a new session, if the directories still exist and were produced using the same commands, the opacities are simply read back in.

```
import optool
import numpy as np
sil = optool.particle('optool -d -a 0.001 100 0 100 ol-mg50',cache='sil')
carb = optool.particle('optool -d -a 0.001 3.0 0 50 c',cache='carb')
```

Apply powerlaw size distributions, and limit the size of the contributing grains. Note that a power law $f(a) \propto a^{-3.5}$ implies using a power $a^{-2.5}$ when computing the number of particles per size bin on a logarithmic size grid. No normalization is necessary - the sizedist method will take care of that.

```
nsil = sil.a1**(-2.5)  # power law, no normalization required
nsil[sil.a1<0.01] = 0  # no grains smaller than 0.01um
nsil[sil.a1>0.3] = 0  # no grains larger than 0.3um
sil_pl = sil.sizedist(nsil)  # pass the relative number for each size
nc = carb.a1**(-2.5)  # power law, no normalization required
nc[carb.a1>0.3]=0  # no grains larger than 0.3um
carb_pl = carb.sizedist(nc)  # pass the relative number for each size
```

sil_pl and carb_pl are now objects with a single opacity each, obtained by adding opacities with the weights of the size distribution. The opacities are still per g of total grain mass. Let's add these two opacities with mass weights, to get something resembling an interstellar dust opacity produced by a mixture of silicate and carbon grains:

```
ptot = 0.7*sil_pl + 0.3*carb_pl  # weights should add up to 1
ptot.plot()  # plot the resulting opacity
```

Now let's assume we are looking at an interstellar cloud, where the dust is just one percent of the total mass. We want to have the opacity per unit of gas mass instead, and we need Planck and Rosseland mean opacities:

Other size distributions can be made just as easily. Here is a log-normal size distribution for the silicate grains, with a peak abundance at a size of $a_m=1.3$ microns, and a logarithmic width of $\sigma=1.2$:

```
sil_ln = sil.sizedist( np.exp( -0.5*(np.log(sil.a1/1.3)/1.2)**2) )
sil_ln.write('dkap_ln.dat')  # write opacity to a file
```

A. Units

Due to conventions in our field, the input and output of optool uses the following units

- microns for grain sizes and wavelengths.⁷
- g/cm^3 for mass densities of materials
- cm² g⁻¹ for opacities $\kappa_{\rm abs}$, $\kappa_{\rm sca}$, and $\kappa_{\rm ext}$
- sr⁻¹ or cm² g⁻¹ sr⁻¹ for the scattering matrix elements, see below.

B. Size distribution

optool implements powerlaw, log-normal, and normal size distributions. Each of these will be subject to a minimum and a maximum grain size. The grain size grid is logarithmic, so $da \propto a$. The logarithmic bins are then filled according to:

powerlaw
$$n(a) \propto a^{-p+1}$$
 log-normal distribution, triggered by $\sigma > 0$ $n(a) \propto \exp\left[-\frac{1}{2}\left(\frac{\ln(a/a_{\rm m})}{\sigma}\right)^2\right]$ normal distribution⁸, triggered by $\sigma < 0$ $n(a) \propto \exp\left[-\frac{1}{2}\left(\frac{a-a_{\rm m}}{\sigma}\right)^2\right]$

Other size distributions can be constructed using the python interface. Finally, optool can also read a size distribution from a file, and this is also the way to provide an arbitrary size grid. The first data line in the file gives the number of grain size bins, followed by lines with two numbers each: grain size in micron and number of grains in the corresponding bin. To get an example file, run optool with the option -wgrid):

C. Scattering Matrix: The fine print

C.1. Phase function normalization

A number of different normalizations for the scattering matrix are being used in the literature and in computational tools. The differences are significant, and it is important to be aware of the choice. For optool we are using a convention (Hovenier (2004)) in which the average over all directions of the 1-1 element of the scattering matrix equals unity, i.e. the integral will be 4π :

$$\oint_{(4\pi)} F_{11}(\lambda, \Theta) d\Omega = 2\pi \int_{-1}^{1} F_{11}(\lambda, \mu) d\mu = 4\pi \quad , \tag{1}$$

with $\mu = \cos \Theta$. optool can also produce output for RADMC-3D which uses instead

$$\oint_{(4\pi)} Z_{11}(\lambda, \Theta) d\Omega = 2\pi \int_{-1}^{1} Z_{11}(\lambda, \mu) d\mu = \kappa_{\text{sca}}(\lambda) \quad . \tag{2}$$

The books by Bohren & Huffman and by Mishchenko use different normalizations again. You can change the normalization of the scattering matrix in the python interface with the scatnorm() method. By default, that method checks the current normalization. Using an argument 'r', 'b', 'm', or 'h' will modify the normalization.

⁷When giving a grain size or a wavelength on the command line, you can write 1.3*mm, 340*GHz, or 4000/cm and optool will do the right thing, converting to 1300μ m, 881.7μ m, and 2.5μ m, respectively.

⁸A normal distribution is not sampled symmetrically on a logarithmic size grid - please make sure your sampling is fine enough around the mean size.

C.2. Forward-scattering peak

Particles that are much larger than the wavelength of the considered radiation can show extreme forward scattering, where much of the *scattered* radiation is sent into just a few degrees around the forward direction. This can be difficult to handle for radiative transfer codes which have limited angular resolution or limited sampling. MCMax3D has the nspike keyword to deal with this issue. Other tools (e.g. RADMC-3D) require this to be taken care of by the process that creates the opacity files. The -chop switch specifies a number of degrees around the forward scattering direction. Inside that cone, the scattering matrix gets limited to the value at the edge of the cone. To compensate and ensure energy conservation, the scattering cross section will be reduced accordingly. As a result, the radiation that would be *scattered* into this narrow range of angles will be treated as if it did have *no interaction at all* with the grain.

C.3. Angular grid

optool uses an angular grid in one-degree steps from 0 to 180 degrees. The full degrees are the cell *interfaces* of that grid. optool computes the scattering matrix at the cell *midpoints*, i.e. at 0.5°, 1.5° etc to 179.5°, for a total of 180 values. The scattering matrix is normalized in this way, so that a numerical integral gives the correct result.

RADMC-3D requires the values of the scattering matrix on the cell boundaries, so at 0°, 1° etc to 180°, for a total of 181 values. For the input files for RADMC-3D, we interpolate and extend the computed values to the cell boundaries.


D. How to ingest refractive index data for another material

Using external refractive index data means that you have to keep track of where those files are. It can be convenient to compile your favorite materials into optool, so that accessing them will be as simple as using the built-in materials. Here is how to do that:

- Give your lnk file a name exactly like pyr-mg70-Dorschner1995.lnk, where the start of the name (pyr-mg70) is the key to access the material and Dorschner1995 (the text after the final -) is the reference.
- 2. Put this file into the lnk_data directory.
- 3. Optionally edit lnk_data/lnk-help.txt, so that optool -c will list the new material. Note that, in order to define generic keys, optool looks for pairs that look like genkey -> fullkey in this file.
- 4. Run make ingest to update optool_refind.f90, now with your new material.
- 5. Recompile and install the code.

E. Overview of optical properties

This grid plot shows the imaginary parts of all built-in materials, in the wavelength range from 0.05 to 300 μ m. Some if the ices have only data in a small range, where the vibrational transitions lie. However, these materials can be used over a much broader wavelength range, because the extrapolation becomes problematic only in the UV where electronic transitions kick in.



F. Internals

This appendix describes some key aspects of the internal workings of the code.

Refractive index data

Measured refractive index data is obtained from data compiled into the code, or read-in from a file. That data is then interpolated and extrapolated onto the wavelength grid requested for the computation. Extrapolation toward short wavelengths is done keeping the refractive indices constant. Extrapolation toward long wavelengths assumes that the last two measured data points define a powerlaw. Interpolation in the measured grid is done using double-logarithmic interpolation.

Mixing

Once the refractive index for all involved materials is available, the core and the mantle mixtures are created independently, using the Bruggeman rule. Mass fractions are converted into volume fractions, and porosity is implemented using vacuum as an additional material. The subroutine doing the mixing uses an iterative procedure that is very stable, also for a large number of components.

If there is a mantle, the Maxwell Garnett rule is applied with the core being treated as an inclusion inside a mantle matrix.

DHS

In order to simulate irregularities in grains (irregular shapes, or the properties of low-porosity aggregates), optool averages the opacities of grains with an inner empty region, over a range of volume fractions of this inner region between 0 and $f_{\rm max}$. The subroutine used to compute the opacities and scattering matrix elements for these structures is DMiLay (Toon & Ackerman 1981). When the size parameter $x=2\pi a/\lambda$ exceeds a value of 10^4 , no DHS averaging is used. A standard Mie calculation is performed, using the routine MeerhoffMie (de Rooij+ 1984), for a fixed size parameter of 5000, with proper scaling to the actual size of the particle. Numerical inaccuracies in the DMiLay routine can lead to an unphysical result with $q_{\rm sca}>q_{\rm ext}$, implying a negative $q_{\rm abs}$, in a situation where the imaginary part of the refractive index is extremely small. optool enforces $q_{\rm abs}>q_{\rm ext}/10^4$, with no consequences for practical applications.

MMF

To construct fluffy/fractal aggregates, optool needs the number of monomers N, the fractal dimension $D_{\rm f}$, and a scaling factor $k_{\rm f}$ which are related to the radius of gyration $R_{\rm g}$ of the aggregate by $N=k_{\rm f}(R_{\rm g}/a_0)^{D_{\rm f}}$. The size a of the particles as specified by the -a switch is interpreted as the compact⁹ size of all material in the aggregate, so that $N=a^3/a_0^3$, where a_0 is the monomer radius. The average volume filling factor f can be expressed by $f=N\cdot(\sqrt{3/5}\,a_0/R_{\rm g})^3$. To determine the structure of the aggregates, the user can specify a structure parameter. If that parameter is >1, it is interpreted as the fractal dimension $D_{\rm f}$. Using a fixed fractal dimension means that the volume filling factor will decrease with aggregate size. If the parameter is <1, it is interpreted as a fixed volume filling factor f that applies to all aggregate sizes - with the implication that then the fractal dimension increases as a function of size. The fractal prefactor $k_{\rm f}$ is chosen automatically so that the asymptotic density of small aggregates is the monomer material density.

⁹still including the porosity specified with the **-p** switch (which is porosity residing in the monomers themselves), but not any "porosity" resulting from the aggregate structure

To force another value for the prefactor, it can be given explicitly as the third value of the mmf option. The following table summarizes the relevant equations.

	-mmf AO DF	-mmf AO FILL	-mmf AO DF KF
f	$N^{(D_{\rm f}-3)/3}$	given by user	$\sqrt{27/125} k_{\rm f}^{3/D_{\rm f}} N^{3-1/D_{\rm f}}$
D_{f}	given by user	$3 \ln N / \ln(N/f)$	given by user
$k_{ m f}$	$(5/3)^{D_{\rm f}/2}$	$(5/3)^{D_{\rm f}/2}$	given by user

With the structure defined, optool then applies the formalism from Tazaki & Tanaka (2018) and Tazaki (2021) to compute cross sections and the scattering matrix. optool also computes the phase shift $\Delta\phi$ to check the validity of the scattering matrix. If the condition $\Delta\phi<1$ for accurate scattering matrix results is violated, a warning will be issued and the scattering matrix will be set to zero at the relevant wavelengths. However, the opacities will remain applicable. You can request to get the result computed under the assumption of single scattering at wavelengths where the phase shift is too large. This may be usable for absorbing materials, but we do not have a clear criterion on when it will be accurate. For this result, use -mmfss instead of -mmf. optool will then also print the wavelength below which the scattering matrix needs to be used with caution.

CDE

CDE (Continuous Distribution of Ellipsoids) is an analytical formalism by Bohren & Huffman (1998) to compute the opacity of a very broad shape distribution. This method is only applicable in the Rayleigh limit $x = 2\pi a \ll \lambda$ and $|mx| \ll 1$. optool will issue a warning if the computation leaves the bounds of this condition. The scattering matrix will be computed from a single sphere in the Rayleigh limit.

G. Troubleshooting

- If you get oscillations in the opacities, in particular at long wavelengths, the grain size resolution is not sufficient. Use more grain sizes (-a, -na and -d switches).
- If you do not remember how to reproduce a specific run, just check the output file header. It contains the exact command that was used to produce the file.

H. Acknowledgments

We are indebted to

- the Jena Database of Optical Constants and the Aerosol Refractive Index Archive for their invaluable collections of refractive index datasets.
- Rens Waters, Thomas Henning, Xander Tielens, Elisabetta Palumbo, Laurent Pilon, Jeroen Bouwman, and Melissa McClure for discussions around optical properties of cosmic dust analogues.
- Charlène Lefèvre for SIGMA, which inspired me to add grain mantles.
- Kees Dullemond for discussions about the RADMC-3D input format and the scattering matrix, for the idea to write optool2tex and for letting me include his incredible python plotting routine viewarr (available on github).
- Gabriel-Dominique Marleau for testing and feedback, in particular on optool2tex.
- Thiébaut Schirmer for triggering the addition of a log-normal size distribution.

I. Bibliography

- Birnstiel, T. et al. 2018, ApJ 869, 45
- Bohren, C.F. and Huffman, D.R. 1998, Wiley-VCH, Absorption and Scattering of Light by Small Particles
- Draine, B. 2003, ApJ 598, 1017
- Draine, B. 2003, ApJ 598, 1026
- Dorschner, J. et al. 1995, A&A 300, 503
- Fabian, D. et al. 2001, A&A 378, 228
- Gerakines, P. and Hudson, R. 2020, ApJ 901, 52
- Henning, Th. and Stognienko, R. 1996, A&A 311,291
- Hovenier, J., 2004, Report available on ADS.
- $\bullet\,$ Jäger, C. et al. 1998, A&A 339, 904
- Kitamura, R. et al. 2007, Applied Optics 46,33, p. 8188
- Koike, C. et al. 1995, Icarus 114, 203
- Laor, A. and Draine, B. 1993, ApJ 402, 441
- Martonchik, J. 1984, Applied Optics 23, 541
- Min, M. et al. 2005, A&A, 432, 909
- Min, M. et al. 2016, A&A, 585, 13
- Mishchenko, M. et al. 2002, Cambridge University Press, Scattering, absorption, and emission of light by small particles
- Mutschke, H. et al. 2004, A&A 423, 983
- Okuzumi, S. et al. 2009, ApJ 707, 1247
- Palumbo, E. et al. 2006, PCCP 8, 279
- Preibisch, Th. et al. 1993, A&A 279, 577
- de Rooij W. and van der Stap, C. 1984, A&A 131, 237
- Steyer, T. 1974, PhD Thesis, The University of Arizona
- Tazaki, R. et al. 2016, ApJ 823, 70
- $\bullet\,$ Tazaki, R. & Tanaka, H. 2018, ApJ 860,79
- Tazaki, R. 2021, MNRAS, in press
- Toon, O. & Ackerman, T. 1981, Applied Optics 20, 3657
- Warren, S. and Brandt, R. 2008, JGRD,113, D14220
- Warren, S. 1986, Applied Optics 25, 2650
- Woitke, P. et al. 2016, A&A 586, 103
- Zubko, V. et al. 1996, MNRAS 282, 1321