

CS 3500 – Programming Languages & Translators

Homework Assignment #1

- This assignment is **due by 8 p.m. on Friday, August 31, 2018**.
- This assignment will be worth **2%** of your course grade.
- You are to work on this assignment **by yourself**.
- You should **take a look at the sample input and output files** posted on the Canvas website **before** you actually submit your assignment for grading.

Basic Instructions:

For this assignment you are to use *flex* to create a C++ program that will perform **lexical analysis** for a small programming language called MFPL (described below). If your *flex* file is named **mfpl.l**, you should be able to compile and execute it on one of the campus Linux machines (such as *rcnnucs213.managed.mst.edu* where *nn* is **01-32**) using the following commands (where *inputFileName* is the name of some input file):

```
flex mfpl.l
g++ lex.yy.c -o mfpl_lexer
mfpl_lexer < inputFileName
```

Your program should **output information about each token** that it encounters in the input source program. You will need a token type **UNKNOWN** for any tokens that cannot be properly categorized as an operator, keyword, identifier, etc. (effectively, these are lexical errors). Sample input and output are given at the end of this document.

Your program should **continue processing tokens** from the input file **until end-of-file is detected**. Note that your program should **NOT** do anything other than recognize tokens (e.g., no syntax checking, etc.), as that is the **only** purpose of lexical analysis.

MFPL Programming Language:

For now, all you need to be concerned with are the **tokens** in the MFPL programming language.

An **identifier** in MFPL must start with a letter or underscore, followed by any number of letters, digits, and/or underscores.

An **integer constant** in MFPL is a sequence of one or more digits, **optionally** preceded by + or -. Don't worry about a size limit on integer constants.

A **string constant** in MFPL is the same as a valid string constant in C++. Note that a string constant that begins on one line must be terminated with an ending double quote character " on that same line. Don't worry about doing any special processing for characters preceded with a backslash character like \n, \t, or \".

The only **keywords** in MFPL are the following: **let***, **if**, **lambda**, **print**, **input**, **and**, **or**, **not**, **t**, **nil**. The language is case-sensitive, so those keywords must be in lowercase (otherwise, they should be recognized as identifiers).

The only **operator symbols** are the following: **+**, **-**, *****, **/**, **<**, **>**, **<=**, **>=**, **=**, **/=**

This programming language also uses **parentheses**, so you need to recognize **(** and **)**. Don't check for matching parentheses, etc. as that is not the responsibility of a lexical analyzer.

Comments in this programming language are similar to the C++ **//** style of comments, except that **;** is used instead of **//**. Comments simply should be scanned over and ignored (i.e., not included in your output!).

In summary, your program should report the following types of tokens (and their lexemes):

LETSTAR, LAMBDA, INPUT, PRINT, IF, LPAREN, RPAREN,
ADD, MULT, DIV, SUB, AND, OR, NOT, LT, GT, LE, GE, EQ, NE,
IDENT, INTCONST, STRCONST, T, NIL, UNKNOWN

Because we are using an automated script (program) for grading, you **MUST** use exactly these token names; **otherwise, you will receive a ZERO for this assignment!!!**

Sample Input and Output:

You should output the **token and lexeme information for every token** processed in the input file even if the lexeme is not unique for the token (for example, the lexeme for every **LAMBDA** token will be **lambda**).

Given below is some sample input and output (also posted as files on Canvas). With the exception of whitespace, the output produced by your program should be **identical** for this input!

Input:

```
let* ( some lambda input + -1234 ;what about this?
*/- 0123 99 + x _underscore_this) &&^
;;; yet another comment
print if flex let 203978 -2 + "30x^2" % !
1+2
3 + 4 > t
-5+ 6
"a
bc"
7
5 >= nil and 4 or not toBe1 <==78
/= -42
```

Output:

TOKEN: LETSTAR	LEXEME: let*
TOKEN: LPAREN	LEXEME: (
TOKEN: IDENT	LEXEME: some
TOKEN: LAMBDA	LEXEME: lambda
TOKEN: INPUT	LEXEME: input
TOKEN: ADD	LEXEME: +
TOKEN: INTCONST	LEXEME: -1234
TOKEN: MULT	LEXEME: *
TOKEN: DIV	LEXEME: /
TOKEN: SUB	LEXEME: -
TOKEN: INTCONST	LEXEME: 0123
TOKEN: INTCONST	LEXEME: 99
TOKEN: ADD	LEXEME: +
TOKEN: IDENT	LEXEME: x
TOKEN: IDENT	LEXEME: _underscore_this
TOKEN: RPAREN	LEXEME:)
TOKEN: UNKNOWN	LEXEME: &
TOKEN: UNKNOWN	LEXEME: &
TOKEN: UNKNOWN	LEXEME: ^
TOKEN: PRINT	LEXEME: print
TOKEN: IF	LEXEME: if
TOKEN: IDENT	LEXEME: flex
TOKEN: IDENT	LEXEME: let
TOKEN: INTCONST	LEXEME: 203978
TOKEN: INTCONST	LEXEME: -2
TOKEN: ADD	LEXEME: +
TOKEN: STRCONST	LEXEME: "30x^2"
TOKEN: UNKNOWN	LEXEME: %
TOKEN: UNKNOWN	LEXEME: !
TOKEN: INTCONST	LEXEME: 1
TOKEN: INTCONST	LEXEME: +2
TOKEN: INTCONST	LEXEME: 3
TOKEN: ADD	LEXEME: +
TOKEN: INTCONST	LEXEME: 4
TOKEN: GT	LEXEME: >
TOKEN: T	LEXEME: t
TOKEN: INTCONST	LEXEME: -5
TOKEN: ADD	LEXEME: +
TOKEN: INTCONST	LEXEME: 6
TOKEN: UNKNOWN	LEXEME: "
TOKEN: IDENT	LEXEME: a

TOKEN: IDENT	LEXEME: bc
TOKEN: UNKNOWN	LEXEME: "
TOKEN: INTCONST	LEXEME: 7
TOKEN: INTCONST	LEXEME: 5
TOKEN: GE	LEXEME: >=
TOKEN: NIL	LEXEME: nil
TOKEN: AND	LEXEME: and
TOKEN: INTCONST	LEXEME: 4
TOKEN: OR	LEXEME: or
TOKEN: NOT	LEXEME: not
TOKEN: IDENT	LEXEME: toBe1
TOKEN: LT	LEXEME: <
TOKEN: LE	LEXEME: <=
TOKEN: EQ	LEXEME: =
TOKEN: INTCONST	LEXEME: 78
TOKEN: NE	LEXEME: /=
TOKEN: INTCONST	LEXEME: -42

You might find it helpful to use the *diff* command to compare your output with the sample output posted on Canvas. To do this, first *flex* and compile your program, and run it on the sample input file **hw1_mfpl.txt** that is posted on Canvas, redirecting the output to a file named **myOutput.out** using the following commands:

```
flex mfpl.l
g++ lex.yy.c -o mfpl_lexer
mfpl_lexer < hw1_mfpl.txt > myOutput.out
```

Assuming there were no errors in that process, you can now compare your output (which should be in file **myOutput.out**) with the output file posted on Canvas (**hw1_mfpl.txt.out**), ignoring differences in spacing, using the following command (typed all on one line):

```
diff myOutput.out hw1_mfpl.txt.out --ignore-space-change --side-by-side
--ignore-case --ignore-blank-lines
```

To learn more about the *diff* command, see <http://ss64.com/bash/diff.html>

What to Submit for Grading:

Name your *flex* file using your last name followed by your first initial with the .l extension (e.g., Homer Simpson would name his file **simpsonh.l**). Do **NOT** submit your file using the name **mfpl.l** or **you will receive a ZERO on the assignment** (since no one's last name in this class is Mfp).

Submit **only** your *flex* file (**not** your *lex.yy.c* file) via Canvas. You can submit multiple times before the deadline; only your last submission will be graded.

The grading rubric is given below so that you can see how many points each part of this assignment is worth. Note that the next assignment builds upon this one, so **it is critical that this assignment works properly in all respects!**

	Points Possible	Mostly or completely incorrect (0% of points possible)	Needs improvement (70% of points possible)	Adequate, but still some deficiencies (80% of points possible)	Mostly or completely correct (100% of points possible)
Comments correctly processed and ignored	10				
Identifiers correctly recognized and identified (IDENT)	10				
Signed integers recognized and identified (INTCONST)	5				
Unsigned integers recognized and identified (INTCONST)	5				
Arithmetic operators (+, -, *, /) correctly recognized and identified (ADD, SUB, MULT, DIV)	5				
Relational operators (<, >=, etc.) correctly recognized and identified (LT, GE, etc.)	10				
Keywords correctly recognized and identified (IF, INPUT, PRINT, etc.)	15				
Parentheses correctly recognized and identified (LPAREN, RPAREN)	5				
String constants correctly recognized and identified (STRCONST)	10				
Unknown tokens correctly processed and identified as UNKNOWN	5				
Program processes an entire input file and correctly handles end-of-file	5				
Program outputs both token type and lexeme information for all tokens	10				
Whitespace correctly processed and ignored	5				