D	D_1	A	B	a	b	d	H	H_1	T	K Stopper fixed	E	Ls	ℓ	a_1	b_1	eH7	⑥Provided bolt	⑦Provided dowel pins
25	31	84	48	66	30	9	30	50	20	20	5	50	66	33	15	8		CB 8—35	MSTM 8—30
32	40	100	58	76	36	11	40	60	20	25	5	60	76	38	18	8	$^{+0.015}_{0}$	CB10—40	MSTM 8—30
38	48	130	75	100	44	11	50	70	25	30	10	70	100	50	22	10		CB10—45	MSTM10—40
50	60	155	90	125	60	14	65	90	25	40	10	90	125	62.5	30	10		CB12—50	MSTM10—40
60	70	190	120	150	80	18	75	100	30	50	15	100	150	75	40	13	$^{+0.018}_{0}$	CB16—60	MSTM13—50

Catalog No. Type	D	L	Base unit price 1～9 pieces MYAK	MYKP	MYJK	MJKP
MYAK MYKP MYJK MJKP	25	90 100 110 120				
		130 140 150 160				
		170 180 200				
	32	110 120 130 140 150				
		160 170 180 200				
		220 240 260				
	38	130 140 150 160				
		170 180 200 220		Quotation		
		240 260 300				
	50	170 180 200				
		220 240 260				
		300 350				
	60	200 220				
		240 260				
		300 350				

Order

Catalog No. — L

MYKP 50 — 200

Price Quotation




Days to Ship Quotation






Alterations

Catalog No. — L(LC) — (M·B·H·N·C···etc.)

MYJK 50 — LC230 — B—H

Quotation

Alteration	Code	Spec.	D	$/Code
	LC	Post length change 1mm increments LCmin.≦LC＜Lmax. **Details of alteration P.862**	25·32 38·50 60	
	Holder M	Machining for mounting of a stroke end block Tap holes are machined for attaching a stroke end block. **Details of alteration P.862**	25～60	Quotation
	Bushing B Holder H	Machining of flange for reversed bushing and/or holder orientation Use of the reversed bushing and/or holder allows the die height to be reduced. Alterations B and H can be combined at the same time. The post length is measured from the holder bottom. **Details of alteration P.862**	25·32 38·50 60	

Alteration	Code	Spec.	D	$/Code
	BKC	Bushing H_1 dimension tolerance change H_1±0.2 ⇨ ±0.1	25·32 38·50 60	
	HKC	Holder H dimension tolerance change H±0.2 ⇨ ±0.1	25·32 38·50 60	
	N	Addition of locating dowel holes Locating dowel holes are machined on holder. (2 positions) Can be used for MYAK and MYJK. Dowel pins are not provided.	25·32 38·50 60	Quotation
	C	Addition of locating dowel hole (1 hole at center) Locating dowel hole is machined at center of post. Dowel pin is not provided.	25·32 38·50 60	
	BSC	Ball cage change Provided ball cage is changed to the high rigidity type. Aluminum: MBS→MBSH Resin: MBJ→MBJH		$/Code Quotation

MiSUMi Press 2012 For technical support ⇒ diemold@misumiusa.com It's all about TIME