D	D_1	A	B	a	b	d	H	H_1	T	Ls	M Stopper distance	ℓ	a_1	b_1	eH7	⑥Provided bolts	⑦Provided dowel pins
20	26	74	44	56	30	6.6	30	50	15	50	0～20	56	28	15	6 $^{+0.012}_{0}$	CB 6—30	MSTM 6—20
25	31	84	48	66	30	9	30	50	20	50	0～20	66	33	15	8 $^{+0.015}_{0}$	CB 8—35	MSTM 8—30
32	40	100	58	76	36	11	40	60	20	60	0～25	76	38	18	8	CB10—40	MSTM 8—30
38	48	130	75	100	44	11	50	70	25	70	0～29	100	50	22	10	CB10—45	MSTM10—40
50	60	155	90	125	60	14	65	90	25	90	0～42	125	62.5	30	10	CB12—50	MSTM10—40

Catalog No. Type	D	L	Base unit price 1～9 pieces MYA	MYAP	MYJ	MYJP
MYA MYAP MYJ MYJP	20	90 100 110 120				
		130 140 150 160				
	25	90 100 110 120				
		130 140 150 160				
		170 180 200				
	32	110 120 130 140 150				
		160 170 180 200		Quotation		
		220 240 260				
	38	130 140 150 160				
		170 180 200 220				
		240 260 300				
	50	170 180 200				
		220 240 260				
		300 350				

Order

Catalog No. — L

MYJ 25 — 90

Price Quotation




Days to Ship Quotation






Alterations

Catalog No. — L(LC) — (M·B·H·N·C···etc.)

MYAP 50 — LC230 — B—H

Quotation

Alteration	Code	Spec.	D	$/Code
	LC	Post length change 1mm increments LCmin.≦LC＜Lmax. **Details of alteration** P.862	20·25·32 38·50	Quotation
	Holder M	Machining for mounting of a stroke end block Tap holes are machined for attaching a stroke end block. ⊗ Cannot be used for D20. **Details of alteration** P.862	25～50	
	Bushing B Holder H	Machining of flange for reversed bushing and/or holder orientation Use of the reversed bushing and/or holder allows the die height to be reduced. ⊗ Alterations B and H can be combined at the same time. Ⓥ The post length is measured from the holder bottom. **Details of alteration** P.862	20·25·32 38·50	

Alteration	Code	Spec.	D	$/Code
	BKC	Bushing H_1 dimension tolerance change H_1±0.2 ⇨ ±0.1 ⊗ Cannot be used for D20.	25·32 38·50	
	HKC	Holder H dimension tolerance change H±0.2 ⇨ ±0.1 ⊗ Cannot be used for D20.	25·32 38·50	
	N	Addition of locating dowel holes 2 locating dowel holes are machined on the holder. Ⓥ Can be used for MYA and MYJ. Ⓥ Dowel pins are not provided.	20·25·32 38·50	Quotation
	C	Addition of locating dowel hole (1 hole at center) Locating dowel hole is machined at center of post. Ⓥ Dowel pin is not provided.	20·25·32 38·50	
	BSC	Ball cage change Provided ball cage is changed to the high-rigidity type. Aluminum: MBS→MBSH Resin : MBJ→MBJH	$/Code MBSH MBJH	Quotation

D	ℓ	e
20	56	6
25	66	8
32	76	8
38	100	10
50	125	10

D	Slider length	MBSH	MBJH
20	50		
25	50		
32	60		
38	70		
50	90		

MiSUMi Press 2012 For technical support ⇒ diemold@misumiusa.com It's all about TIME