

402Pilot: An x402 Decision Layer for Autonomous Agent Micropayments

Course Project Report

Yin Li*

Yanbo He†

Wanting Xiong‡

yligt@connect.hkust-gz.edu.cn

yhe376@connect.hkust-gz.edu.cn

wxiong945@connect.hkust-gz.edu.cn

The Hong Kong University of Science and Technology (Guangzhou)
Guangzhou, Guangdong, China

Abstract

Programmable-payment protocols such as x402 make per-request agent payments executable, but they do not decide which service a budgeted agent should buy. We study this missing buyer-side layer as *agent-native payment decision-making*: contextual provider selection under a draining wallet, uncertain service outcomes, and non-stationary reliability or prices. We propose *402Pilot*, a protocol-agnostic decision layer above payment execution, and instantiate it with *PA-DCT*, a payment-aware discounted contextual Thompson-sampling policy. *PA-DCT* maintains separate discount-tracked posteriors over service utility and realized cost, allowing both reliability drift and price drift to be tracked from post-payment feedback. We evaluate on *402Pilot-Bench*, a frozen-replay benchmark with 823 tasks, five provider pipelines, and three market scenarios. *PA-DCT* pays an exploration cost in the stationary setting, but provides the most robust adaptive trade-off under non-stationarity: during a mid-tier outage it improves full-horizon mean quality by 15 percentage points over the cheapest fixed provider while remaining budget-feasible, and under a premium price promotion it improves over the reliable mid-tier baseline on quality, ROI, and payment-aware gap.

Keywords

Agent payments, x402, micropayments, contextual bandits, non-stationary learning, Thompson sampling

1 Introduction

x402-style payment protocols expose machine-readable payment requirements, per-request settlement, and increasingly dynamic service metadata, including pricing information [18]. These capabilities make agent micropayments executable, but execution alone does not answer the buyer’s decision question: how should an autonomous agent with a finite wallet decide which service is worth buying in a changing market?

Several lines of prior work supply pieces of this problem, but not the full buyer-side loop. Budgeted bandits model resource-constrained learning [3, 21]; discounted methods address non-stationarity [7, 17]; contextual Thompson sampling estimates task-conditioned value [2]; and LLM routing studies quality–cost trade-offs across heterogeneous models [4, 6, 12, 14, 20]. These ingredients are usually analyzed outside a protocol-mediated quote–pay–observe loop in which the buyer sees payable endpoints, pays one of them, and updates from realized prices and service outcomes. Payment protocols expose the execution substrate, and auction mechanisms study strategic allocation [16]; neither provides an online spending policy for a single autonomous buyer.

We call this setting *agent-native payment decision-making*. It differs from human-operated provider selection in three ways. First, the policy is part of an autonomous system, so routine operation cannot rely on a human resetting state or curating providers after each change. Second, the wallet drains with every paid call; each payment is irreversible and reveals only the chosen provider’s outcome. Third, market conditions change: service quality, reliability, and effective price can shift while the policy observes them only through post-payment feedback. These properties make autonomous micropayment an online economic decision problem, not only a settlement problem.

This report proposes *402Pilot*, a narrow decision layer that separates provider selection from payment execution. The payment stack handles how to pay; *402Pilot* decides which affordable service is worth buying and updates that decision rule from post-payment feedback. We instantiate the layer with *PA-DCT* (Payment-Aware Discounted Contextual Thompson Sampling), a learning policy that maintains two discount-tracked beliefs for each provider–task bucket: one over service utility and one over realized cost. Its ranking rule combines wallet pressure, task context, discounted updating, and posterior sampling, allowing the same policy to react to reliability drift and price drift without hard-coding provider labels or assuming fixed prices.

We make three contributions. **C1:** we formulate agent-native payment decision-making and introduce *402Pilot* as a protocol-agnostic buyer-side decision layer. **C2:** we instantiate the layer with *PA-DCT*, a payment-aware discounted contextual Thompson-sampling policy with separate utility and cost beliefs. **C3:** we construct *402Pilot-Bench*, a frozen-replay benchmark that evaluates

*Student ID: 20489800.

†Student ID: 50040464.

‡Student ID: 50022371.

Table 1: Bandit ingredients related to PA-DCT. Budget denotes resource constraints, Drift non-stationary adaptation, and Context task-conditioned value estimation.

Method	Budget	Drift	Context
BTS / BwK [3, 21]	✓	–	–
Linear CBwK [1]	✓	–	✓
DS-TS / Discounted UCB [7, 17]	–	✓	–
Contextual TS / LinUCB [2, 11]	–	–	✓
PA-DCT (ours)	✓	✓	✓

buyer policies under stationary operation, reliability shocks, and price shocks.

2 Related Work

Programmable payment protocols. x402 embeds payment into HTTP and exposes payment requirements to software agents; its V2 direction adds discovery, dynamic recipients, extensible schemes, and service metadata [18]. AP2 provides payment-agnostic authorization for agent-led commerce [15]; A2A-x402 and A402 bind agent-to-agent service execution to cryptocurrency-style settlement [8, 13]; and recent surveys organize agent payments around discovery, authorization, execution, and accounting [23]. 402Pilot is complementary: it treats these systems as rails and studies the buyer’s spending policy above them.

Bandit ingredients and LLM routing. Budgeted Thompson Sampling and bandits with knapsacks model resource constraints [3, 21]; contextual bandits condition value on task features [2, 11]; and discounted or sliding-window methods track non-stationary feedback [7, 17, 19]. Cost-aware LLM routing systems such as Frugal-GPT, RouteLLM, Hybrid LLM, MixLLM, and LLM Bandit also study quality–cost tradeoffs [4, 6, 12, 14, 20]. The key distinction is the information contract: routing systems usually assume published prices or offline labels, while 402Pilot learns from receipt-revealed charges and chosen-arm outcomes under a draining wallet.

3 Problem and Layer

We model repeated provider selection by a single autonomous buyer with a finite wallet. There are K payable providers and a horizon T . At round t , a task context $\mathbf{x}_t$ arrives, the buyer has remaining budget B_t , and provider a has effective charge $p_{a,t} > 0$. The wallet/payment interface returns the affordable set

$$\mathcal{A}_t = \{a \in \{1, \dots, K\} : p_{a,t} \leq B_t\}. \quad (1)$$

If $\mathcal{A}_t$ is empty, the run stops. Otherwise the policy chooses $a_t \in \mathcal{A}_t$, pays for that provider, and receives one feedback sample (q_t, f_t, c_t) , where $q_t \in [0, 1]$ is service quality, $f_t \in \{0, 1\}$ marks non-delivery, and $c_t = p_{a_t,t}$ is the realized charge. The wallet evolves as

$$B_{t+1} = B_t - c_t. \quad (2)$$

The policy does not observe unchosen outcomes, and the decision-layer contract only assumes access to the affordable set before payment; selected calls reveal numeric charges through receipts.

Service delivery is summarized as utility $u_t = q_t - v f_t$. We combine utility with normalized realized cost and wallet pressure:

$$\begin{aligned} \tilde{c}_t &= \text{clip}(c_t/c_{\max}, 0, 1), \\ \lambda_{\text{norm}} &= \lambda_t/(1 + \lambda_t), \\ r_t &= (1 - \lambda_{\text{norm}})u_t - \lambda_{\text{norm}}\tilde{c}_t. \end{aligned} \quad (3)$$

For $0 \leq v \leq 1$, $r_t \in [-1, 1]$. The pressure multiplier λ_t grows when spending is ahead of the linear plan:

$$\begin{aligned} \text{burn}_t &= \frac{(B - B_t)/B}{t}, \\ \text{burn_dev}_t &= \frac{\text{burn}_t - 1/T}{1/T}, \\ \lambda_t &= \lambda_0 \exp(\alpha \text{burn_dev}_t). \end{aligned} \quad (4)$$

Because λ_t depends on the policy’s own wallet trajectory, evaluation reports payment-aware gap together with quality, budget use, and ROI rather than treating raw cumulative r_t as a single leaderboard score.

402Pilot turns this formulation into a boundary between the autonomous agent and the payment substrate (Fig. 1). On the payment side, it consumes quoted candidates, masks infeasible actions, delegates the selected payment and service call, records spend, and receives a receipt. On the policy side, it exposes a small interface: $\text{select}(\mathbf{x}_t, \mathcal{A}_t) \rightarrow a_t$ and $\text{update}(\mathbf{x}_t, a_t, u_t, c_t)$. The layer does not modify x402, hold funds, or implement settlement. Its purpose is to turn payment execution into a learning interface: the substrate constrains what can be bought, and the policy learns what is worth buying.

4 The PA-DCT Policy

PA-DCT instantiates the policy side of 402Pilot. For each provider a and task bucket k , it maintains two Normal–Normal posteriors: a Q-posterior over utility and a C-posterior over realized cost. In the benchmark, $k(\mathbf{x}_t)$ maps tasks to four buckets: coding, multi-hop QA, closed-form web QA, and open-ended QA. Each cell stores an effective count $n^{a,k}$, a utility sum $S^{a,k}$, and a cost sum $S_c^{a,k}$. The Q-posterior is

$$\begin{aligned} \Sigma_q^{a,k} &= \left(\frac{1}{\sigma_{0,q}^2} + \frac{n_t^{a,k}}{\sigma_q^2} \right)^{-1}, \\ \theta_q^{a,k} &= \Sigma_q^{a,k} \left(\frac{\mu_{0,q}}{\sigma_{0,q}^2} + \frac{S_t^{a,k}}{\sigma_q^2} \right), \end{aligned} \quad (5)$$

and the C-posterior uses the same form with $(\theta_c^{a,k}, \Sigma_c^{a,k})$, prior mean $\bar{c}_a$, and cost sum $S_c^{a,k}$. The learned C-posterior is what lets PA-DCT respond to price drift: if prices were fixed and visible before selection, the specification price would be sufficient; in the 402Pilot contract, effective charges are learned from receipts.

To track non-stationarity, PA-DCT discounts every cell at the start of each round:

$$n_t^{a,k} = \gamma n_{t-1}^{a,k}, \quad S_t^{a,k} = \gamma S_{t-1}^{a,k}, \quad S_{c,t}^{a,k} = \gamma S_{c,t-1}^{a,k}. \quad (6)$$

After the chosen call, only the selected cell receives the new observation. At selection time, PA-DCT samples utility and cost from the corresponding posteriors for each affordable arm and scores

$$s_a = (1 - \lambda_{\text{norm}})\hat{u}^{a,k_t} - \lambda_{\text{norm}} \text{clip}(\hat{c}^{a,k_t}/c_{\max}, 0, 1). \quad (7)$$




Figure 1: The 402Pilot per-round decision flow. A task and quoted candidates Q_t enter the layer; the wallet masks candidates to $\mathcal{A}_t$ and exposes pressure λ_t ; PA-DCT selects the paid arm; the execution substrate returns a response and receipt; and the layer passes chosen-arm feedback (u_t, c_t) to the policy.

Algorithm 1 PA-DCT policy loop.

Require: Spec costs $\bar{c}_a$; discount γ ; normalizer $c_{\max}$.

- 1: **for** each served round t with $\mathcal{A}_t \neq \emptyset$ **do**
- 2: Discount all cell counts and sums by γ
- 3: $k_t \leftarrow k(\mathbf{x}_t)$; $\lambda_{\text{norm}} \leftarrow \lambda_t / (1 + \lambda_t)$
- 4: **for** $a \in \mathcal{A}_t$ **do**
- 5: Sample $\hat{u}^{a,k_t}$ and $\hat{c}^{a,k_t}$ from Q/C posteriors
- 6: $s_a \leftarrow (1 - \lambda_{\text{norm}}) \hat{u}^{a,k_t} - \lambda_{\text{norm}} \text{clip}(\hat{c}^{a,k_t} / c_{\max}, 0, 1)$
- 7: Select $a_t \leftarrow \arg \max_{a \in \mathcal{A}_t} s_a$
- 8: Observe (u_t, c_t) and update only cell (a_t, k_t)

The policy chooses the affordable arm with the largest sampled score. Wallet pressure shifts the decision toward cost control when burn rate is high, discounting lets stale evidence fade after market changes, and posterior sampling preserves exploration. All experiments use a single locked configuration: $\gamma = 0.999$, $\nu = 0.5$, $\alpha = 2.0$, and $c_{\max} = \$0.01$.

5 Evaluation

The evaluation asks whether a buyer-side decision layer helps when reliability or prices change after deployment. Live provider calls would add cost and confound policy effects with API drift, so 402Pilot-Bench uses frozen replay: responses are pre-generated and scored for each task-provider pair, and all policies replay the same task order, response-version draws, wallet budget, and scenario events under paired seeds.

Benchmark, providers, and scenarios. The benchmark contains 823 effective tasks across coding (HumanEval [5]), multi-hop QA (HotpotQA [22]), closed-form web QA (TriviaQA-web [9]), and open-ended QA (OpenAssistant [10]). It stores five response versions for each task-provider pair, yielding 20,575 scored responses after one documented TriviaQA exclusion. The five providers form a price-quality ladder (P-cheap/P-mid/P-premium) plus a same-price reference/decoy trio: P-mid is reliable, P-adv produces fluent

Table 2: Provider set used in 402Pilot-Bench. P-mid, P-adv, and P-flaky share the same price tier and base model.

Provider	Price	Pipeline / role
P-cheap	0.0005	qwen3.5-flash; uniform prompt; weakest cheap tier
P-mid	0.002	GPT-5.4-mini; uniform prompt; reliable mid tier
P-premium	0.01	GPT-5.4; uniform prompt; strongest premium tier
P-adv	0.002	GPT-5.4-mini; 60% adversarial prompt; fluent wrong answers
P-flaky	0.002	GPT-5.4-mini; 40% timeout injection; billed timeouts

wrong answers, and P-flaky returns billed timeouts. A selector that only reads static metadata cannot separate these three arms.

The scenarios are S1 stationary operation, S2 a P-mid reliability outage from rounds 3,000–5,500, and S3 a P-premium price drop from \$0.01 to \$0.002 at round 1,000. Each policy-scenario cell uses 30 paired seeds, 10,000 rounds, and a \$50 budget; at the original premium price, this budget buys only 5,000 premium calls, so a policy must manage wallet pressure rather than simply choosing the strongest model throughout.

Comparators and metrics. We compare PA-DCT against Random, fixed-arm policies, BudgetRule, Contextual DS-TS, Contextual BTS, and a replay True Oracle. BudgetRule is a static cascade-style heuristic: premium above 50% remaining budget, mid above 20%, and cheap below that. Contextual DS-TS tracks discounted utility but lacks wallet pressure and cost learning; Contextual BTS learns utility and cost but does not discount and scores by a raw utility/cost ratio. Metrics are mean quality $\bar{q}_T$, budget use, ROI, and PA-gap/ T to the replay True Oracle. ROI is an efficiency diagnostic rather than the objective: a cheap policy can have high ROI while serving low-quality answers. All means average over the same 30 seed identifiers within each scenario, and claimed differences use paired-seed tests.

Table 3: Main results on 402Pilot-Bench, averaged over 30 seeds. Columns report mean quality, budget used (%), ROI, and PA-gap/ T to the replay True Oracle (lower is better). Bold marks the best non-oracle entry in rank-comparable quality, ROI, and PA-gap columns; budget use is descriptive.

Policy	S1 Stationary				S2 Mid Outage				S3 Premium Promo			
	$\bar{q}_T$	budget	ROI	Gap	$\bar{q}_T$	budget	ROI	Gap	$\bar{q}_T$	budget	ROI	Gap
Random	0.688	66	209	0.365	0.676	66	205	0.375	0.688	37	370	0.274
Always-P-cheap	0.610	10	1220	0.167	0.610	10	1220	0.164	0.610	10	1220	0.195
Always-P-mid	0.819	40	410	0.101	0.757	40	379	0.174	0.819	40	410	0.129
Always-P-premium	0.433	100	87	1.072	0.433	100	87	1.070	0.865	56	309	0.400
BudgetRule	0.831	80	208	0.692	0.769	80	192	0.722	0.859	56	307	0.405
Contextual DS-TS	0.559	100	112	0.858	0.514	100	103	0.884	0.840	48	349	0.264
Contextual BTS	0.612	10	1187	0.169	0.612	10	1187	0.166	0.612	10	1187	0.197
PA-DCT (ours)	0.797	42	378	0.133	0.761	43	357	0.166	0.831	39	429	0.121
True Oracle	0.901	32	561	0.000	0.901	33	551	0.000	0.906	25	722	0.000

Main results. Table 3 shows that PA-DCT is an adaptive trade-off rather than a one-column winner. In stationary S1, the reliable mid-tier arm is strong and PA-DCT pays an exploration cost: Always-P-mid reaches the lowest non-oracle PA-gap/ T while PA-DCT trails by about 2.2 quality points. In S2, the policy learns around the mid-tier outage and reaches $\bar{q}_T = 0.761$ while spending 43% of the wallet, compared with 0.610 for the cheapest fixed policy and 0.757 for Always-P-mid. BudgetRule slightly improves quality, but spends 80% of the budget and suffers a large PA-gap because it follows fixed thresholds rather than feedback. In S3, PA-DCT captures the premium promotion, improving over Always-P-mid on quality (0.831 vs. 0.819), ROI (429 vs. 410), and PA-gap/ T (0.121 vs. 0.129).

The learning baselines sharpen the failure modes. Contextual DS-TS tracks utility drift but lacks wallet pressure and exhausts the budget in S1/S2. Contextual BTS learns cost but does not discount old evidence and optimizes a raw utility/cost ratio, so under the 20 $\times$ cost spread it locks onto P-cheap and misses the S3 opportunity. The allocation curves in Fig. 2 show why the combined design matters: PA-DCT moves away from P-mid during the outage, shifts toward P-premium after the price drop, and stays mid-dominated when no shock occurs.

Robustness across axes. Taken as a trade-off panel, Table 3 shows that PA-DCT is the only non-oracle policy without a clear failure mode across the three markets. Cheap policies and Contextual BTS conserve budget but under-serve tasks; premium-heavy policies and BudgetRule can buy quality in the wrong regime and pay a large PA-gap; Contextual DS-TS tracks quality drift but lacks wallet pressure and exhausts the budget in S1/S2. As a compact robustness descriptor, PA-DCT has the lowest mean rank (2.89/8, lower is better) and the smallest worst rank (4/8) across the nine rank-comparable cells in Table 3. The per-axis numbers remain the load-bearing evidence, but this summary matches the central finding: the decision layer matters because the buyer must keep learning and adapting under market change, not merely win one static metric.

Table 4: Compact ablation evidence. Gap is PA-gap/ T ; † marks mid-run bankruptcy.

Variant	S1	S2	S3
Full PA-DCT	0.133	0.166	0.121
–P no pressure	0.855 †	0.878 †	0.259
–D no discount	0.109	0.170	0.114
–TS greedy	0.130	0.175	0.145
–C _{post spec cost}	–	–	0.144

Quality under a budget. The learned reallocations matter because the cheap safe policy under-serves tasks, while static high-quality policies can spend in the wrong places. In S2, PA-DCT gains 15.1 quality points over Always-P-cheap while spending only 43% of the wallet, and its smaller gain over Always-P-mid is significant under paired seeds ($\Delta\bar{q}_T = +0.004$, $p = 1.67 \times 10^{-3}$). In S3, PA-DCT improves over Always-P-mid on quality, ROI, and PA-gap/ T at the same time. Always-P-premium reaches the highest S3 quality once premium becomes cheap, but it does so with lower ROI and much worse PA-gap because it pays for premium before the promotion as well.

Statistical checks. Paired-seed tests match these claims. The S3 improvements over Always-P-mid on quality, ROI, and PA-gap/ T are all significant ($p < 10^{-20}$), and PA-DCT has a significantly smaller PA-gap/ T than both learning baselines in S1 and S3. The S1 disadvantages against Always-P-mid and BudgetRule are also significant, which is why we treat them as the exploration cost of maintaining shock-ready posteriors rather than hide them. The one borderline cell is S2 PA-gap/ T : PA-DCT is numerically close to Always-P-cheap and Contextual BTS, while delivering much higher quality than those cheap-biased policies.

Ablation summary. Table 4 grounds the component claims. Removing pressure ranking bankrupts S1/S2; no discount slows outage



Figure 2: PA-DCT provider-allocation share over rounds. Shaded regions mark shock windows: the policy remains mid-dominated in S1, moves away from P-mid during S2, and shifts toward P-premium in S3.

recovery; spec-only cost misses S3; and greedy selection raises variance and misses S3 in several seeds. Contextual bucketing mainly protects task-specific behavior.

6 Discussion and Conclusion

402Pilot does not replace payment protocols; it supplies the missing buyer policy above them. The boundary is deliberately narrow: it assumes posted payable candidates, chooses only from the affordable set, learns only from chosen outcomes, and leaves discovery, authorization, settlement faults, and observability to the surrounding payment stack. This makes the learning problem compatible with x402-style execution while making wallet pressure and receipt-revealed cost first-class decision signals.

The main limitation is that the quantitative evaluation is controlled. Frozen replay makes policy comparisons reproducible, but it does not measure live settlement latency, facilitator failures, congestion, or provider drift in deployment. The benchmark also covers a finite set of task types, providers, and scripted shocks.

Overall, the evidence supports a simple conclusion: autonomous payment systems need learning at the buyer layer, not only safer settlement mechanisms. PA-DCT is not universally optimal in a static market, but it is the policy in this comparison that keeps service quality, spending efficiency, and payment-aware objective jointly competitive when reliability and prices change.

Code and supplement. The companion technical report contains the supplementary notation, proof scope, computation notes, detailed ablations, sensitivity sweeps, and local x402 quote-pay-receipt witness: https://github.com/MCCodeAI/402Pilot/raw/main/docs/technical_report.pdf. Code and evaluation materials are available at <https://github.com/MCCodeAI/402Pilot>.

Author contributions. Yin Li led ideation, method design, experiments, implementation, analysis, and writing. Yanbo He contributed to paper discussions, result audit, and baseline optimization. Wanting Xiong contributed related work, project discussion, and audit.

References

- [1] Shripa Agrawal and Nikhil R. Devanur. 2016. Linear Contextual Bandits with Knapsacks. In *Advances in Neural Information Processing Systems*, Vol. 29. <https://proceedings.neurips.cc/paper/2016/hash/f3144cfe89a60d6a1afaf7859c5076b-Abstract.html>
- [2] Shripa Agrawal and Navin Goyal. 2013. Thompson Sampling for Contextual Bandits with Linear Payoffs. In *Proceedings of the 30th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 28)*. PMLR, 127–135. <https://proceedings.mlr.press/v28/agrawal13.html>
- [3] Ashwinkumar Badanidiyuru, Robert Kleinberg, and Aleksandr Slivkins. 2018. Bandits with Knapsacks. *Journal of the ACM* 65, 3 (2018), 13:1–13:55. doi:10.1145/3164539
- [4] Lingjiao Chen, Matei Zaharia, and James Zou. 2023. FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. *arXiv preprint arXiv:2305.05176* (2023). doi:10.48550/arXiv.2305.05176
- [5] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Amanda Askell, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Heben Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Joshua Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. 2021. Evaluating Large Language Models Trained on Code. *arXiv preprint arXiv:2107.03374* (2021). doi:10.48550/arXiv.2107.03374
- [6] Dujian Ding, Ankur Mallick, Chi Wang, Robert Sim, Subhabrata Mukherjee, Victor Rühle, Laks V. S. Lakshmanan, and Ahmed Hassan Awadallah. 2024. Hybrid LLM: Cost-Efficient and Quality-Aware Query Routing. In *International Conference on Learning Representations*. <https://openreview.net/forum?id=02f3mUqtqM>
- [7] Aurélien Garivier and Eric Moulines. 2011. On Upper-Confidence Bound Policies for Switching Bandit Problems. In *Algorithmic Learning Theory (ALT 2011) (Lecture Notes in Computer Science, Vol. 6925)*. Springer, 174–188. doi:10.1007/978-3-642-24412-4_16
- [8] Google Agentic Commerce. 2025. A2A x402 Extension. <https://github.com/google-agentic-commerce/a2a-x402>. GitHub repository, release v0.1.0. Accessed: 2026-05-19.
- [9] Mandar Joshi, Eunsol Choi, Daniel S. Weld, and Luke Zettlemoyer. 2017. TriviaQA: A Large Scale Distantly Supervised Challenge Dataset for Reading Comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. 1601–1611. doi:10.18653/v1/P17-1147
- [10] Andreas Köpf, Yannic Kilcher, Dimitri von Rütte, Sotiris Anagnostidis, Zhi Rui Tam, Keith Stevens, Abdullah Barhoum, Duc Nguyen, Oliver Stanley, Richard Nagyi, Shahul ES, Sameer Suri, David Glushkov, Arnav Dantuluri, Andrew Maguire, Christoph Schuhmann, Huu Nguyen, and Alexander Mattick. 2023. OpenAssistant Conversations: Democratizing Large Language Model Alignment. In *Advances in Neural Information Processing Systems*, Vol. 36. Curran Associates, Inc., Red Hook, NY, USA, 47669–47681. https://papers.nips.cc/paper_files/paper

- /2023/hash/949f0f8f32267d297c2d4e3ee10a2e7e-Abstract-Datasets_and_Benchmarks.html
- [11] Lihong Li, Wei Chu, John Langford, and Robert E. Schapire. 2010. A Contextual-Bandit Approach to Personalized News Article Recommendation. In *Proceedings of the 19th International Conference on World Wide Web*. ACM, 661–670. doi:10.1145/1772690.1772758
 - [12] Yang Li. 2025. LLM Bandit: Cost-Efficient LLM Generation via Preference-Conditioned Dynamic Routing. *arXiv preprint arXiv:2502.02743* (2025). doi:10.48550/arXiv.2502.02743
 - [13] Yue Li, Lei Wang, Kaixuan Wang, Zhiqiang Yang, Ke Wang, Zhi Guan, and Jianbo Gao. 2026. A402: Binding Cryptocurrency Payments to Service Execution for Agentic Commerce. *arXiv preprint arXiv:2603.01179* (2026). doi:10.48550/arXiv.2603.01179
 - [14] Isaac Ong, Amjad Almahairi, Vincent Wu, Wei-Lin Chiang, Tianhao Wu, Joseph E. Gonzalez, M. Waleed Kadous, and Ion Stoica. 2024. RouteLLM: Learning to Route LLMs with Preference Data. *arXiv preprint arXiv:2406.18665* (2024). doi:10.48550/arXiv.2406.18665
 - [15] Stavan Parikh and Rao Surapaneni. 2025. Powering AI Commerce with the New Agent Payments Protocol (AP2). <https://cloud.google.com/blog/products/ai-machine-learning/announcing-agents-to-payments-ap2-protocol>. Google Cloud Blog. Accessed: 2026-05-19.
 - [16] Pronoy Patra, Sankarshan Damle, Manisha Padala, and Sujit Gujar. 2026. Truthful Reverse Auctions for Adaptive Selection via Contextual Multi-Armed Bandits. *arXiv preprint arXiv:2602.14476* (2026). doi:10.48550/arXiv.2602.14476 No peer-reviewed venue verified as of 2026-05-19.
 - [17] Han Qi, Yue Wang, and Li Zhu. 2023. Discounted Thompson Sampling for Non-Stationary Bandit Problems. *arXiv preprint arXiv:2305.10718* (2023). doi:10.48550/arXiv.2305.10718
 - [18] Erik Reppel, Carson Roscoe, and Josh Nickerson. 2025. Introducing x402 V2: Evolving the Standard for Internet-native Payments. <https://www.x402.org/writing/x402-v2-launch>. Accessed: 2026-05-19.
 - [19] Francesco Trovò, Stefano Paladino, Marcello Restelli, and Nicola Gatti. 2020. Sliding-Window Thompson Sampling for Non-Stationary Settings. *Journal of Artificial Intelligence Research* 68 (2020), 311–364. doi:10.1613/jair.1.11407
 - [20] Xinyuan Wang, Yanchi Liu, Wei Cheng, Xujiang Zhao, Zhengzhang Chen, Wenchao Yu, Yanjie Fu, and Haifeng Chen. 2025. MixLLM: Dynamic Routing in Mixed Large Language Models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*. Association for Computational Linguistics, Albuquerque, New Mexico, 10912–10922. doi:10.18653/v1/2025.naacl-long.545
 - [21] Yingce Xia, Haifang Li, Tao Qin, Nenghai Yu, and Tie-Yan Liu. 2015. Thompson Sampling for Budgeted Multi-Armed Bandits. In *Proceedings of the 24th International Joint Conference on Artificial Intelligence*. 3960–3966. <https://www.ijcai.org/Proceedings/15/Papers/556.pdf>
 - [22] Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. 2018. HotpotQA: A Dataset for Diverse, Explainable Multi-Hop Question Answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*. 2369–2380. doi:10.18653/v1/D18-1259
 - [23] Yuanzhe Zhang, Yuexin Xiang, Yuchen Lei, Qin Wang, Tian Qiu, Yujing Sun, Spiridon Zarkov, Tsz Hon Yuen, Andreas Deppeler, Jiangshan Yu, and Kwok-Yan Lam. 2026. SoK: Blockchain Agent-to-Agent Payments. *arXiv preprint arXiv:2604.03733* (2026). doi:10.48550/arXiv.2604.03733