

Klaviyo → Redo Flow Field Mapping

Research reference — mime migration project

2026-04-20

This document maps every field in a Klaviyo flow definition to its equivalent in Redo's **advanced flow** (user-facing: **automation**) schema. Findings are grounded in the Redo codebase `redo/model/src/advanced-flow/` and a gap analysis of 34 real flows from the otishi Klaviyo corpus.

Status values: **MAPS** (1:1), **DEGRADED** (semantics partially lost), **DROP SILENT** (skip without warning — redundant or auto-handled), **DROP + WARN** (skip with surfaced warning), **UNSUPPORTED** (no Redo equivalent), **REWRITE REQUIRED** (non-trivial transformation), **REQUIRED** (Redo needs a value not present in Klaviyo), **DEFERRED** (punt to V2), **PROMPT MERCHANT**, **UNCERTAIN** (needs spike).

Section 1. Flow root document

Source: Klaviyo flow JSON `data.attributes` vs `redo/model/src/advanced-flow/advanced-flow-db-parser.ts:2852`

Klaviyo field	Redo field	Status	Notes
name	name	MAPS	
status	enabled (boolean)	MAPS	live → true ; draft / disabled / manual / anything else → false . Importer does not filter by status — every flow imports; only live flows arrive enabled.
trigger_type	(derived from trigger step)	MAPS	metric / list / segment
archived	(no equivalent)	DROP	
created / updated	createdAt / updatedAt	MAPS	
(no equivalent)	team	REQUIRED	from import CLI (store ID)
(no equivalent)	schemaType	REQUIRED	derived from trigger — see Section 2
(no equivalent)	category	REQUIRED	always "Marketing" for our use
(no equivalent)	versionGroupId	REQUIRED	auto-generated
(no equivalent)	createdByUserId	REQUIRED	from import CLI

Section 2. Trigger types

Source: redo/model/src/advanced-flow/triggers.ts:160 (MarketingTriggerKey) and redo/model/src/advanced-flow/schemas/schemas.ts:132 (SchemaType)

Klaviyo trigger → Redo MarketingTriggerKey + SchemaType. Metric IDs listed are from the otishi corpus and are Klaviyo-account-scoped — a metric-ID resolver per merchant is needed at migration time.

Klaviyo trigger	Metric ID (otishi)	Redo trigger key	Redo schemaType	Status
Started Checkout	metric	checkout_abandoned	marketing_checkout_abandonment	MAPS
Added to Cart	metric	cart_abandoned	marketing_cart_abandonment	MAPS
Viewed Product	metric	browse_abandoned	marketing_browse_abandonment	MAPS
Active on Site	metric	browse_abandoned	marketing_browse_abandonment	DEGRADED
Placed Order	metric	(none)	custom_event	DEGRADED
Fulfilled Order	metric	(none)	custom_event	DEGRADED
Survey Submitted	metric	(none)	custom_event	DEGRADED
Social Snowball events	metric	(none)	custom_event	DEGRADED
Back in Stock	metric	back_in_stock	marketing_back_in_stock	MAPS
Low Inventory	metric	low_inventory	marketing_low_inventory	MAPS
Price Drop	price-drop	price_drop	marketing_price_drop	MAPS
Date / Anniversary / Birthday	date	date	marketing_date	MAPS
Warranty Registration	metric	warranty_registration	marketing_warranty_registration	MAPS
Added to List (email)	list	email_signup / email_signup_shopify	email_marketing_signup	MAPS
SMS list subscription	list	sms_confirmed	sms_marketing_signup	MAPS
Segment entry	segment	customer_group_entered	marketing_segment_membership_change	MAPS
Segment exit	segment	customer_group_exited	marketing_segment_membership_change	MAPS
CommentSold cart (detected)	metric+filter	commentsold_cart_abandoned	marketing_commentsold_cart_abandonment	MAPS
CommentSold browse	metric+filter	commentsold_browse_abandoned	marketing_commentsold_browse_abandonment	MAPS

Klaviyo trigger	Metric ID (otishi)	Redo trigger key	Redo schemaType	Status
CommentSold checkout	metric+filter	commentsold_checkout_abandoned	marketing_commentsold_checkout_abandonment	MAPS
Unconfigured (empty triggers)	—	(skip entire flow)	—	DROP + WARN

CommentSold trigger detection

CommentSold is **not** a distinct Klaviyo trigger type. CS-integrated merchants use the standard Shopify metrics (Placed Order, Started Checkout, Added to Cart) and discriminate via a `metric-property` trigger filter on `Source Name`:

- **Source Name equals "CommentSold"** → map to `commentsold_*` variant trigger
- **Source Name not-equals "CommentSold"** → standard trigger, exclude CS flows
- **Flow name prefix CS or Shopify** | is an auxiliary signal but not load-bearing

Evidence: Alexander Jane corpus has 4 CS-prefixed flows all on metric IDs shared with Shopify flows, distinguished only by the trigger filter.

Auto-generated skip conditions (load-bearing)

Redo's abandonment triggers fire on the *event* (cart-add, checkout-started, page-view) — not after any abandonment delay. To preserve the "don't send if the customer actually converted during the WAIT" semantics, the Redo UI auto-inserts a `skipConditions` entry on the trigger step:

- **cart_abandoned** → skip when `isCartAbandoned == false`
- **checkout_abandoned** → skip when `isCheckoutAbandoned == false`
- **browse_abandoned** → skip when `isBrowseAbandoned == false`

These fields are runtime booleans on the schema instance (`redo/model/src/advanced-flow/schemas/marketing/marketing.ts`). **Our importer must emit these skip conditions explicitly** — they are not auto-added by `AdvancedFlowsRepo.createAdvancedFlow`, only by the UI. Without them, every cart-add event sends, even when the customer has already checked out.

Section 3. Profile filter (trigger-level filters)

Source: klaviyo flow.definition.profile_filter vs advanced-flow-db-parser.ts:228 (skipConditions)

Klaviyo condition type	Redo mapping	Status	Notes
profile-metric	covered by Redo auto-generated skipCondition	DROP SILENT	Boilerplate "exclude converters." Redo auto-emits the equivalent at trigger-instance level.
profile-not-in-flow	covered by Redo default smart-sending	DROP SILENT	Klaviyo's N-day re-entry guard. Redo's channel-level smart-sending covers most of the intent.
profile-property	InlineSegment condition	MAPS	Supports string equals/contains, list contains, and date after/before predicates.
profile-marketing-consent	(no equivalent)	DROP SILENT	Redo SMS/email step self-filters on subscription status.
profile-group-membership	ExistingSegment skip condition	MAPS	List membership check. Quikcamo: 6 trigger-level + 3 conditional-split uses.
profile-region	(research: Redo GDPR region filter?)	UNCERTAIN	EU exclusion gate. Quikcamo: 6 instances. Needs spike.

Section 4. Action / step types

Source: redo/model/src/advanced-flow/steps.ts (StepType enum)

Klaviyo action.type	Redo StepType	Status	Notes
send-email	SEND_EMAIL	MAPS	See Section 5. Heavy use across all 3 merchants.
send-sms	SEND_SMS	MAPS	See Section 6. MMS + transactional flags seen in Alexander Jane.
send-webhook	SEND_WEBHOOK or DO_NOTHING	REWRITE REQUIRED	See Section 7. >5 unmapped tokens → replace with DO_NOTHING (enrichment webhook skip).
time-delay	WAIT	MAPS	See Section 8. Handle named IANA timezones, weekday subsets, delay_until_time.
conditional-split	CONDITION	MAPS	See Section 9. Group-membership + greater-than operators add coverage.
trigger-split	CONDITION (TriggerData predicate)	MAPS	Routes on event property. Quikcamo has chained trigger-splits (up to 3 in series). AJ has 2 simple uses.
ab-test	AB_TEST	MAPS	See Section 10. Handle experiment_status: live/completed/draft.
update-profile	MANAGE_CUSTOMER_TAGS (only Boolean props)	DEGRADED	Quikcamo: 11 uses. Always create/update a Boolean on properties['X']. Maps only if Redo MANAGE_CUSTOMER_TAGS supports the key.
list-update	MANAGE_STATIC_SEGMENT	MAPS	Quikcamo: 5 uses. Add/remove from a Klaviyo list; needs segment mirrored in Redo.
target-date	(paired with date trigger)	PARTIAL	Quikcamo: 1 use (anniversary flow). Adjusts time-of-day of the triggered execution.
notification	(internal Klaviyo only)	DROP	0 in any corpus.

Section 5. send-email field mapping

Source: Klaviyo send-email.data vs advanced-flow-db-parser.ts:754 (SendEmailStep) + EmailTemplate schema

Klaviyo field	Redo location	Status	Notes
template_id	SEND_EMAIL.templateId	MAPS	After placeholder template creation at import time.
from_email	EmailTemplate.fromEmail	MAPS	
from_label	EmailTemplate.fromName	MAPS	
subject_line	EmailTemplate.subject	MAPS	
preview_text	EmailTemplate.previewText	MAPS	
reply_to_email	(null in corpus)	DROP	
cc_email / bcc_email	(null in corpus)	DROP	
smart_sending_enabled	shouldSkipSmartSending (trigger step, inverted)	MAPS	Redo smart-sending is default-on at channel level. Klaviyo true → omit field; Klaviyo false → set shouldSkipSmartSending: true.
transactional	(maybe maps to Redo transactional sender)	PROMPT MERCHANT	1 flow uses it (Key Fulfillment). Research needed.
add_tracking_params	(research — Redo auto?)	DROP if no	Mostly true in corpus.
custom_tracking_params	(null in corpus)	DROP	
additional_filters	(null in corpus)	DROP	

Section 6. send-sms field mapping

Source: Klaviyo send-sms.data vs redo SEND_SMS step

Klaviyo field	Redo location	Status	Notes
body	SEND_SMS.body	MAPS	
image_id	SMS image (via Klaviyo Images API fetch + host)	REWRITE REQUIRED	AJ: 3 instances of MMS. Need to download the asset from Klaviyo and re-host for Redo.
dynamic_image	Liquid-rendered image URL	MAPS	AJ: 1 instance. Pass the Liquid string through the rewriter (Section 7).
transactional	Redo transactional SMS flag	PROMPT MERCHANT	AJ: 1 instance (SWnjKi shipment SMS). Confirm Redo allows transactional from automation.
include_contact_card	(no direct equivalent)	DROP + WARN	AJ: 1 instance. Niche feature.
shorten_links	(likely auto in Redo)	DROP	
add_org_prefix	(compliance — Redo auto)	DROP	
add_info_link	(compliance — Redo auto)	DROP	
add_opt_out_language	(compliance — Redo auto)	DROP	
sms_quiet_hours_enabled	(Redo auto-respects per merchant settings)	DROP	

Section 7. send-webhook field mapping

Source: Klaviyo send-webhook.data vs advanced-flow-db-parser.ts:804 (SendWebhookStep)

Klaviyo field / token	Redo location	Status	Notes
url	destinationUrl	MAPS	Literal copy.
headers (object)	headers (array of {key,value})	MAPS	Shape transform only.
body	payload (string)	REWRITE REQUIRED	Klaviyo Liquid → Redo variable syntax.
method	(Redo assumes POST)	DROP	All otishi webhooks are POST.
(no OAuth2 in corpus)	oauth2Config	DEFERRED	Prompt merchant for credentials if encountered in future.
{{ person.email default:'' }}	(Redo variable syntax — TBD)	REWRITE REQUIRED	Needs klaviyo-to-redo-template.ts rewriter. Unmapped vars kept as literals + warning.
{{ event.extra.X }}	(Redo trigger-data ref)	REWRITE REQUIRED	Requires metric-ID resolver + Redo variable schema.

Section 8. time-delay field mapping

Source: Klaviyo time-delay.data vs advanced-flow-db-parser.ts:711 (WaitStep)

Klaviyo field	Redo location	Status	Notes
unit (days/hours/minutes)	timeUnit (Days/Hours/Minutes)	MAPS	
value	numDays or numSeconds	MAPS	numDays for unit=days, else numSeconds.
timezone ("profile" or IANA)	(implicit in Redo; IANA may lose meaning)	DEGRADED	Quikcamo: 15+ instances of US/Eastern. Research Redo WAIT timezone support.
weekdays (subset)	(no equivalent)	DROP + WARN	AJ: ["friday", "saturday"]. Semantically important when present; emit warning.
delay_until_time ("HH:MM:SS")	(no equivalent)	DROP + WARN	Quikcamo + AJ. Merchant set a specific time-of-day for the send.
secondary_value (null/0)	(no jitter equivalent)	DROP	Null or 0 across all corpora; no random-range delays observed.
reentry_criteria.unit: alltime	(no re-entry suppression in Redo)	DROP + WARN	AJ + Quikcamo. Merchant said "never re-enter this flow."

Section 9. conditional-split → CONDITION mapping

Source: Klaviyo conditional-split vs advanced-flow-db-parser.ts:199 (ConditionExpression)

Redo supports 4 data sources: **TriggerData** (schema boolean expression), **ExistingSegment** (segment ID list), **InlineSegment** (AND/OR of conditions), **OfferResponse**.

Klaviyo condition type	Redo mapping	Status	Notes
profile-metric (count equals/greater-than 0/1/2)	InlineSegment (count predicate)	MAPS	All 3 merchants. Operators: equals, greater-than, greater-than-or-equal. Requires metric-ID resolution.
profile-property	InlineSegment (property predicate)	MAPS	String equals/contains, list contains, date after/before.
profile-group-membership	ExistingSegment (by list ID)	MAPS	Quikcamo: 3 uses. Requires segment mirror in Redo.
profile-marketing-consent	(drop gate — Redo SMS self-filters)	DROP + WARN	Otishi: 1 use.
profile-sample (random N%)	rewrite to AB_TEST step	REWRITE REQUIRED	Otishi: 1 use. Direct shape match to Redo AB_TEST.
property-has-viewed-product	InlineSegment or TriggerData	UNCERTAIN	Not seen. Needs spike when first encountered.
property-has-ordered-product	InlineSegment or TriggerData	UNCERTAIN	Not seen.
multi-condition-in-group (AND)	InlineSegment with ConjunctionMode.AND	MAPS	AJ: e.g. count ≥ 2 AND count ≠ 3 to select exactly 2.

Section 10. ab-test field mapping

Source: Klaviyo ab-test.data vs Redo AB_TEST step

Klaviyo field	Redo location	Status	Notes
experiment_status: live	AB_TEST active branches	MAPS	Standard split shape.
experiment_status: completed	single SEND_EMAIL from main_action	MAPS	Quikcamo: 5 instances. Winner baked into main_action; variations discarded.
experiment_status: draft	AB_TEST (unpublished)	MAPS	AJ: 1 instance. Treat same as live.
main_action	control / winner branch	MAPS	
variations[]	variation branches	MAPS	
allocations (% per variation)	weights (per branch)	MAPS	
winner_metric	(no equivalent)	DROP + WARN	unique-clicks, etc. Lost at import.
automatic_winner_selection_settings	(no equivalent)	DROP + WARN	Klaviyo auto-promotes; Redo requires manual selection.
custom_tracking_params with {variation_label}	rewrite or drop	DROP + WARN	Quikcamo. No direct Redo equivalent for variation-name UTM injection.
smart_sending_enabled inside main_action	shouldSkipSmartSending on the resulting step	MAPS	Pass through per-email; do not assume default (Quikcamo mixed values).

Section 11. Step linking

Both systems use a flat step array with explicit string IDs and pointer-based linking (linked-list / DAG). Near 1:1 — this is the easiest part of the migration.

Klaviyo field	Redo field	Status	Notes
action.id	step.id	MAPS	String identifier within the flow.
action.links.next	step.nextId	MAPS	Sequential step pointer.
action.links.next_if_true	step.nextTrueId	MAPS	For CONDITION steps.
action.links.next_if_false	step.nextFalseId	MAPS	For CONDITION steps.

Section 12. Summary, legend, and open questions

Status legend

Status	Meaning
MAPS	Structural 1:1 — no transformation required.
DEGRADED	Works but semantics partially lost (e.g. Active on Site → browse_abandoned).
DROP SILENT	Safe to skip without a warning (redundant or handled implicitly by Redo).
DROP + WARN	Skip with a per-flow warning in the import report.
UNSUPPORTED	No Redo equivalent. Behavior gap on import.
REWRITE REQUIRED	Non-trivial transformation needed at migration time.
REQUIRED	Redo requires a value not present in Klaviyo (must be supplied by CLI / defaults).
DEFERRED	Punt to V2. Not encountered in otishi corpus.
PARTIAL	Some constructs map cleanly; others need degradation.
PROMPT MERCHANT	Ask during import run.
UNCERTAIN	Needs a short spike before implementation.

Otishi corpus stats

34 flows extracted via Klaviyo GET /flows/ (API revision 2025-10-15 with additional-fields[flow]=definition). Breakdown:

- **3 empty** flows (zero actions, drafts) — skip entirely.
- **4 never-wired** flows (actions present but no trigger) — skip entirely.
- **27 real flows** worth migrating: ~18 fully mappable, ~8 need degradation, ~1 blocked (Abandoned Checkout STACK64 A/B test — core intent is the 50/50 random split).

Open questions (spike before implementation)

1. Redo webhook payload variable syntax. Klaviyo uses Liquid (`{{ person.email|default:'' }}`). Redo's SEND_WEBHOOK payload is `string` — confirm what template syntax is interpolated at send time, and build the Klaviyo→Redo rewriter accordingly.

2. Channel-level send dedup in Redo. If Redo's SMS/email send step natively suppresses rapid duplicate sends, the impact of dropping Klaviyo's `profile-not-in-flow` guards is small. 15-minute spike, changes the V1 scope decision on 12 flows.

3. Redo AB_TEST control-branch support. Does Redo's AB_TEST step expose a control/holdout branch analogous to Klaviyo's `main_action`? Affects how we map the one ab-test action in otishi.

4. Redo transactional sender from automation context. Key Fulfillment flow is marked `transactional: true`. Does Redo allow an automation-driven email to flag itself transactional and bypass unsubscribe?

5. Redo InlineSegment predicate catalog. What condition types can an inline segment contain? Specifically: count predicates on arbitrary metrics, custom-property lookups, consent-status checks. Drives Sections 3 and 9.

Section 13. Coverage across 3 merchants (appendix)

Feature usage across otishi (34 flows), Quikcamo (49), Alexander Jane (20). Shows where each pattern was encountered and whether V1 of the mapper will handle it.

Feature	otishi	Quikcamo	Alexander Jane	V1 status
Cart/browse/checkout abandonment triggers	yes	yes	yes	V1
Added-to-list (welcome) + SMS signup	yes	yes	yes	V1
Segment entry/exit	1	yes	0	V1
Price Drop trigger	0	0	1	V1
Date / Anniversary trigger	0	1	0	V1
CommentSold-flavored triggers (filter-detected)	0	0	4	V1
Unconfigured / empty-trigger flows	4	1	3	V1 (skip + warn)
send-email	yes	yes	yes	V1
send-sms (non-MMS)	yes	yes	yes	V1
send-sms with MMS image_id	0	0	3	V1 (Klaviyo Images fetch)
send-sms with dynamic_image	0	0	1	V1
send-sms with transactional: true	0	0	1	V1 (prompt merchant)
send-sms include_contact_card	0	0	1	V1 (drop + warn)
send-webhook (integration: Senden/PHNTM)	4	0	0	V1
send-webhook (enrichment: STACK64)	3	0	0	V1 (replace with DO_NOTHING)
send-webhook (simple merchant-owned)	0	1	0	V1
time-delay (plain unit+value)	yes	yes	yes	V1
time-delay with named IANA timezone	0	15+	0	V1 (research Redo support)
time-delay with delay_until_time	0	yes	yes	V1 (drop + warn)
time-delay with weekday subset	0	0	1	V1 (drop + warn)
conditional-split (profile-metric count)	yes	yes	yes	V1
conditional-split (profile-property)	yes	yes	yes	V1
conditional-split (profile-group-membership)	0	3	0	V1

Feature	otishi	Quikcamo	Alexander Jane	V1 status
conditional-split (profile-marketing-consent)	1	0	0	V1 (drop + warn)
conditional-split (profile-sample random N%)	1	0	0	V1 (rewrite to AB_TEST)
trigger-level profile-group-membership	0	6	0	V1
trigger-level profile-region (EU exclusion)	0	6	0	V1 (research)
trigger-split action	0	9 (chained)	2	V1
update-profile action	0	11	0	V1 (boolean props only)
list-update action	0	5	0	V1
target-date action (paired with date trigger)	0	1	0	V1
ab-test (live)	1	0	0	V1
ab-test (completed)	0	5	0	V1 (emit single email)
ab-test (draft)	0	0	1	V1
smart_sending_enabled: false per-email	0	many	some	V1
{variation_label} token in tracking params	0	yes	0	V1 (drop + warn)
OAuth2-authenticated webhook	0	0	0	V2 (not seen)
Custom-event trigger (truly merchant-defined)	0	0	0	V2 (not seen)
property-has-viewed-product / has-ordered	0	0	0	V2 (not seen)
Delay jitter (random range)	0	0	0	V2 (not seen)
MMS with real assets	0	0	yes	V1

Corpus: 103 flows total

otishi (34 flows, small SMS-forward merchant): webhooks + profile-sample + live A/B. **Quikcamo** (49 flows, largest sample): trigger-split cascades, update-profile, list-update, anniversary flow, named IANA timezones, group-membership filters, GDPR region exclusions. **Alexander Jane** (20 flows, medium): price-drop trigger, MMS, transactional SMS, weekday subsets, CommentSold filter discrimination.