Esquelet per fer les taules de REQUEST/RESPONSE de les preguntes:

ID: **1A**
From: To:
HTTP Request
GET `/productes/test/index.html` HTTP/1.1
`Accept: text/html`
`Accept-Language: en-GB,en;q=0.9,es-ES;q=0.8,es;q=0.7,ca-ES;q=0.6,ca;q=0.5,en-US;q=0.4`
`Connection: keep-alive`
`Host: www.prova.com`
User-Agent: Mozilla/5.0
\r\n

ID: **1X**
From: To:
HTTP Response
`HTTP/1.1 200 OK`
Date: Wed,18 Nov 2026 10:57:00 GMT
Connection: keep-alive
Server: Apache/2.4
Content-language: ca
Content-type: text/html; charset=UTF-8
Content-length: 3130 bytes
Last-Modified: Wed,19 Nov 2025 10:40:00 GMT
\r\n
<!DOCTYPE html><html>….</html>

P1) http://www.prova.com/productes/test/index.html

Client: Recurs en **català** i si no en English.

Proxy: **No** té index.html en **caché**

ID: **1A**
From: To:
HTTP Request

ID: **1B**
From: To:
HTTP Request

ID: **1C**
From: To:
HTTP Response

ID: **1D**
From: To:
HTTP Response

P2.1) http://www.prova.com/productes/test/index.html
Client: Recurs en **català** i si no en English.

Proxy: **Sí** té index.html en **caché** consultat el dia 06/11/2024 **10:51**. Actualment son les **10:57h**.

Porxy: Temps de validació dels fitxers **2 min**.

Server: **No ha modificat** l'index.html.

Utilitzeu capçalera **If-Modified-Since**

ID: **1A**
From: **To:**
HTTP Request

ID: **1B**
From: **To:**
HTTP Request

ID: **1C**
From: **To:**
HTTP Response

ID: **1D**
From: **To:**
HTTP Response

P2.2) Igual que l'exercici anterior:http://www.prova.com/productes/test/index.html
Client: Recurs en **català** i si no en English.

Proxy: **Sí** té index.html en **caché** consultat el dia 06/11/2024 **10:51**. Actualment son les **10:57h**.

Porxy: Temps de validació dels fitxers **2 min**.

Server: **No ha modificat** l'index.html.

Utilitzeu el **request method HEAD.** També us caldrà utilitzar la capçalera **Last-Modified.**

ID: **1A**
From: To:
HTTP Request

ID: **1B**
From: To:
HTTP Request

ID: **1C**
From: To:
HTTP Response

ID: **1D**
From: To:
HTTP Response

P3) http://www.prova.com/productes/test/index.html
Client: Recurs en **català** i si no en English.

Proxy: **Sí** té index.html en **caché** només versió en **English**. Actualment son les **10:57h**.

Server: **Sí** té index.html en **català**.

ID: **1A**
From: To:
HTTP Request

ID: **1B**
From: To:
HTTP Request

ID: **1C**
From: To:
HTTP Response

ID: **1D**
From: To:
HTTP Response