# Final: API Spec

## CS 493: Cloud Application Development

### **Michael Commins**

### Fall 2019

## Oregon State University

Application URL: <a href="https://comminsfinal.appspot.com">https://comminsfinal.appspot.com</a>
Login URL: <a href="https://comminsfinal.appspot.com">https://comminsfinal.appspot.com</a>

Ion-User Entity Descriptions		
User Entity Model	4	
Create a boat	5	
View all boats	8	
View a boat	10	
Patch a boat	12	
Put a boat	15	
Delete a boat	18	
Create a load	19	
View all loads	21	
View a load	23	
Patch a load	24	
Put a load	26	
Delete a load	28	
Assign a load to a boat	29	
Remove a load from a boat	31	
View all loads of a given boat	33	
Get all boats from a user	35	

## **Non-User Entity Descriptions**

### **Boat**

### **Attributes**

Name	Туре	Description	Stored in Database?
name	String	The name of the Boat.	Yes
		Must be unique. Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed.	
		Whitespaces cannot be the first character or the only character.	
type	String	The type of the Boat. E.g., Sailboat, Catamaran, etc.	Yes
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed.	
		Whitespaces cannot be the first character or the only character.	
length	Integer	Length of the Boat in feet.	Yes
		Must be positive.	
loads	Array	Array containing the 'id' attributes of one or more Load entities	Yes
		associated with the Boat.	
		Can be empty.	
owner	String	The identifier of the User entity that created the Boat. Yes	
id	String	Unique identifier for the Boat.	Yes
self	String	URL where the Boat is located.	No

### Relationships

The Boat entity has a one-to-many relationship with the Load entity. One or more Loads can be associated with a single Boat, but each Load can only be associated with a single Boat.

The Boat entity has a many-to-one relationship with the User entity. One or more boats can be associated with a single User, but each Boat can only be associated with a single User.

### Load

### Attributes

Name Type		Description	Stored in
			Database?
weight	Integer	The weight of the load.	Yes
		Must be positive.	
content	String	The contents of the load.	Yes

		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
delivery_date	String	The date the load is due to be delivered Yes	
carrier	String	The 'id' attribute of the Boat associated with the Load. Yes	
		Can be null.	
id	String	Unique identifier for the Load.	
self	String	URL where the Load is located. No	

## Relationships

The Load entity has a many-to-one relationship with the Boat entity. One or more Loads can be associated with a single Boat, but each Load can only be associated with a single Boat.

## **User Entity Model**

### **User Identification**

A user is identified by the 'sub' value of the JSON Web Token received when a user logs in through Google from the Login URL.

Users should supply the JWT in the Authorization header of requests that access resources managed by the user.

In order to GET all Boats created by a user, a ':user\_id' parameter must be supplied in the request containing the 'sub' attribute from the JWT.

### Relationships

The User entity has a one-to-many relationship with the Boat entity. One or more boats can be associated with a single User, but each Boat can only be associated with a single User. When a Boat is created, the identifier of the creating user can be found in the 'owner' attribute of the Boat.

## Create a boat

POST /boats

Request

**Request Parameters** 

None

Request Body

Required

Request Body Format

**JSON** 

Request Authorization

Bearer Token (JWT)

## Request JSON Attributes

Name	Туре	Description	Required?
name	String The name of the boat.		Yes
		Must be unique. Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
type	String	The type of the boat. E.g., Sailboat, Catamaran, etc.	Yes
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
length	Integer	Length of the boat in feet.	Yes
		Must be positive.	

## Request Body Example

```
{
   "name": "Shape",
   "type": "Yatch",
   "length": 99
}
```

### Response

## Response Body Format

**JSON** 

### Response Statuses

Outcome	Status Code	Notes	
Success	201 Created	A new boat was created with the given attributes.	
		Attributes other than those above are ignored.	
Failure	400 Bad Request	If the request is missing any of the 3 required attributes	
		or any of them are invalid, the boat is not created.	
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the	
		JWT does not match the 'owner' attribute of the boat.	
Failure	403 Forbidden	The given name attribute already exists on another boat	
Failure	406 Not Acceptable	Client asks for response media type the server cannot	
		offer	

### Response Examples

#### Success

```
Status: 201 Created

{
    "name": "Shape",
    "type": "Yatch",
    "loads": [],
    "length": 99,
    "owner": "104384644578499349548",
    "id": "4790047639339008",
    "self": "https://comminsfinal.appspot.com/boats/4790047639339008"
}
```

#### Failure

```
Status: 400 Bad Request

{
"Error": "The request object has at least one missing or invalid attribute"
}
```

### Failure

```
Status: 401 Unauthorized

{
"Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

```
Status: 403 Forbidden
{
```

```
"Error": "The name attribute of the request object is not unique" }
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## View all boats

Returns all boats in the database. Does not require authorization. Lists first five entries and a URL to the next five entries. Lists total number of entries in boat collection.

#### **GET** /boats

### Request

**Request Parameters** 

None

**Request Body** 

None

**Request Authorization** 

None

### Response

**Response Body Format** 

**JSON** 

### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer

### Response Examples

#### Success

```
Status: 200 OK
{
    "items": [
        {
            "name": "Shape",
            "type": "Yatch",
            "loads": [],
            "length": 99,
            "owner": "104384644578499349548",
            "id": "4790047639339008",
            "self": "https://comminsfinal.appspot.com/boats/4790047639339008"
        },
            "length": 99,
            "owner": "104384644578499349548",
            "name": "Odyssey",
            "type": "Yatch",
            "loads": [],
            "id": "5667370274127872",
```

```
"self": "https://comminsfinal.appspot.com/boats/5667370274127872"
        },
        {
            "name": "Argo",
            "type": "Yatch",
            "loads": [],
            "length": 99,
            "owner": "104384644578499349548",
            "id": "5715789755711488",
            "self": "https://comminsfinal.appspot.com/boats/5715789755711488"
        },
            "owner": "104384644578499349548",
            "name": "Iliad",
            "type": "Yatch",
            "loads": [],
            "length": 99,
            "id": "5742796208078848",
            "self": "https://comminsfinal.appspot.com/boats/5742796208078848"
        },
            "owner": "104384644578499349548",
            "name": "Aeneid",
            "type": "Yatch",
            "loads": [],
            "length": 99,
            "id": "5746055551385600",
            "self": "https://comminsfinal.appspot.com/boats/5746055551385600"
        }
    ],
    "entries": 6,
"next": "http://comminsfinal.appspot.com/boats?cursor=CikSI2oObX5jb21taW5zZmluYWxyEQsSBEJvYXQ
YgICAgJ3AmgoMGAAgAA=="
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

### View a boat

Retrieve a single boat.

GET /boats/:id

### Request

### **Request Parameters**

Name	Туре	Description	Required?
id	String	ID of the boat	Yes

### Request Body

None

### **Request Authorization**

Bearer Token (JWT)

### Response

### **Response Body Format**

**JSON** 

### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the
		JWT does not match the 'owner' attribute of the boat.
Failure	404 Not Found	No boat with this id exists
Failure	406 Not Acceptable	Client asks for response media type the server cannot
		offer

### Response Examples

#### Success

```
Status: 401 Unauthorized

{

"Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

### Failure

```
Status: 404 Not Found

{
"Error": "No boat with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Patch a boat

Edit one or more attributes of an existing boat.

## PATCH /boats/:id

## Request

## **Request Parameters**

Name	Туре	Description	Required?
id	String	ID of the boat	Yes

## Request Body

Required

## Request Body Format

**JSON** 

## **Request Authorization**

Bearer Token (JWT)

### Request JSON Attributes

Name	Type	Description	Required?
name	String	The name of the boat.	No
		Must be unique. Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
type	String The type of the boat. E.g., Sailboat, Catamaran, etc.		No
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
length	Integer	Length of the boat in feet.	No
		Must be positive.	

## Request Body Example

```
{
  "type": "Catamaran",
  "length": 28
}
```

### Response

## Response Body Format

**JSON** 

### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	Attributes other than those above and empty/null values are ignored.
Failure	400 Bad Request	If an attribute is invalid, the boat is not created.
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the JWT does not match the 'owner' attribute of the boat.
Failure	403 Forbidden	The given name attribute already exists on another boat
Failure	404 Not Found	No boat with this id exists
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer

### Response Examples

#### Success

#### Failure

```
Status: 400 Bad Request

{
"Error": "The request object has at least one missing or invalid attribute"
}
```

```
Status: 401 Unauthorized

{
"Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

```
Status: 403 Forbidden

{
"Error": "The name attribute of the request object is not unique"
}
```

#### Failure

```
Status: 404 Not Found
{
"Error": "No boat with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

### Put a boat

Allows you to create a new boat to replace a boat with the given id. The URL of the new boat is stored in the Location header of the response. Transfers the Loads associated with the old boat to the new boat.

PUT /boats/:id

### Request

### **Request Parameters**

Name	Туре	Description	Required?
id	String	ID of the boat	Yes

### Request Body

Required

### Request Body Format

**JSON** 

### **Request Authorization**

Bearer Token (JWT)

### Request JSON Attributes

Name	Туре	Description	Required?
name	String	The name of the boat.	Yes
		Must be unique. Must be 1-28 characters. Can be the same as the current name of the boat being replaced.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
type String		The type of the boat. E.g., Sailboat, Catamaran, etc.	Yes
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
length	Integer Length of the boat in feet.		Yes
		Must be positive.	

### Request Body Example

```
{
  "name": "Sea Witch",
  "type": "Catamaran",
  "length": 28
}
```

### Response

## Response Body Format

**JSON** 

### **Response Statuses**

Outcome	Status Code	Notes
Success	303 See Other	The boat with the given id was overwritten successfully
		with a new boat. The location of the new boat is specified
		in the 'Location' header of the response.
Failure	400 Bad Request	If the request is missing any of the 3 required attributes
		or any of them are invalid, the boat is not created.
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the
		JWT does not match the 'owner' attribute of the boat.
Failure	403 Forbidden	The given name attribute already exists on another boat
Failure	404 Not Found	No boat with this id exists
Failure	406 Not Acceptable	Client asks for response media type the server cannot
		offer

### Response Examples

#### Success

#### Failure

```
Status: 400 Bad Request

{
"Error": "The request object has at least one missing or invalid attribute"
}
```

```
Status: 401 Unauthorized

{
"Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

```
Status: 403 Forbidden

{
    "Error": "The name attribute of the request object is not unique"
}
```

#### Failure

```
Status: 404 Not Found
{
"Error": "No boat with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Delete a boat

## DELETE /boats/:id

### Request

**Request Parameters** 

None

Request Body

None

**Request Authorization** 

Bearer Token (JWT)

### Response

No body

Response Body Format

Success: No body

Failure: JSON

### **Response Statuses**

Outcome	Status Code	Notes
Success	204 No Content	
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the JWT does not match the 'owner' attribute of the boat.
Failure	404 Not Found	No boat with this id exists

### **Response Examples**

#### Success

Status: 204 No Content

### Failure

```
Status: 401 Unauthorized

{
    "Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

```
Status: 404 Not Found
{
"Error": "No boat with this id exists"
}
```

## Create a load

POST /loads

Request

**Request Parameters** 

None

Request Body

Required

Request Body Format

**JSON** 

## Request JSON Attributes

Name	Туре	Description	Required?
weight	Integer	The weight of the load.	Yes
		Must be positive.	
content	String	The contents of the load.	Yes
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are	
		allowed. Whitespaces cannot be the first character or	
		the only character.	
delivery_date	String	The date the load is due to be delivered	Yes

### Request Body Example

```
{
  "weight": 1,
  "content": "marbles",
  "delivery_date": "01/01/01"
}
```

### Response

**Response Body Format** 

**JSON** 

### Response Statuses

· ·			
Outcome	Status Code	Notes	
Success	201 Created		
Failure	400 Bad Request	If the request is missing either of the 2 required attributes, the load is not created	
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer	

### **Response Examples**

Success

Status: 201 Created

```
{
    "id": "5678164130922496",
    "weight": 1,
    "content": "marbles",
    "delivery_date": "01/01/01",
    "carrier": null,
    "self": "https://comminsfinal.appspot.com/loads/5678164130922496"
}
```

```
Status: 400 Bad Request

{
"Error": "The request object is missing at least one of the required attributes"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## View all loads

Returns all loads in the database. Lists first five entries and a URL to the next five entries. Lists total number of entries in load collection.

#### **GET /loads**

### Request

**Request Parameters** 

None

**Request Body** 

None

Response

**Response Body Format** 

JSON

### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer

### **Response Examples**

#### Success

```
Status: 200 OK
    "items": [
        {
            "content": "a sandwich",
            "weight": 40,
            "delivery_date": "03/03/03",
            "carrier": null,
            "id": "4860816083910656",
            "self": "https://comminsfinal.appspot.com/loads/4860816083910656"
        },
        {
            "content": "gravel",
            "weight": 3,
            "delivery_date": "04/04/04",
            "carrier": null,
            "id": "5080222944722944",
            "self": "https://comminsfinal.appspot.com/loads/5080222944722944"
        },
            "delivery_date": "05/10/15",
```

```
"carrier": "5667370274127872",
            "content": "apples",
            "weight": 12,
            "id": "5106919723237376",
            "self": "https://comminsfinal.appspot.com/loads/5106919723237376"
        },
            "content": "heavier marbles",
            "weight": 2,
            "delivery_date": "02/02/02",
            "carrier": null,
            "id": "5137355874762752",
            "self": "https://comminsfinal.appspot.com/loads/5137355874762752"
        },
            "content": "Gumballs",
            "weight": 6,
            "delivery_date": "06/07/08",
            "carrier": null,
            "id": "5139217877303296",
            "self": "https://comminsfinal.appspot.com/loads/5139217877303296"
        }
    ],
    "entries": 6,
"http://comminsfinal.appspot.com/loads?cursor=CikSI2oObX5jb21taW5zZmluYWxyEQsSBExvYWQYgICAwP
bCkAkMGAAgAA=="
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## View a load

GET /loads/:id

### Request

### **Request Parameters**

Name	Туре	Description	Required?
id	String	ID of the load	Yes

### Request Body

None

### Response

### **Response Body Format**

**JSON** 

### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	
Failure	404 Not Found	No load with this id exists
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer

### Response Examples

#### Success

```
Status: 200 OK

{
    "id": "123abc",
    "weight": 1
    "carrier": "abc123",
    "content": "marbles",
    "delivery_date": "01/01/01",
    "self": "https://comminsfinal.appspot.com/loads/123abc"
}
```

### Failure

```
Status: 404 Not Found

{
"Error": "No load with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Patch a load

Edit one or more attributes of an existing load.

## PATCH /loads/:id

## Request

## **Request Parameters**

Name	Туре	Description	Required?
id	String	ID of the load	Yes

## Request Body

Required

## Request Body Format

**JSON** 

## Request JSON Attributes

Name	Туре	Description	Required?
weight	Integer	The weight of the load.	No
		Must be positive.	
content	String	The contents of the load.	No
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed.	
		Whitespaces cannot be the first character or the only	
		character.	
delivery_date	String	The date the load is due to be delivered No	

## Request Body Example

```
{
  "weight": 80,
  "content": "Marshmallows"
}
```

## Response

## Response Body Format

JSON

## Response Statuses

Outcome	Status Code	Notes
Success	200 OK	Attributes other than those above and empty/null values
		are ignored.
Failure	400 Bad Request	If an attribute is invalid, the load is not created.
Failure	403 Forbidden	The given name attribute already exists on another load
Failure	404 Not Found	No load with this id exists

Failure	406 Not Acceptable	Client asks for response media type the server cannot
		offer

### **Response Examples**

#### Success

```
Status: 200 OK

{
    "id": 5678164130922496,
    "weight": 80,
    "content": "Marshmallows",
    "delivery_date": "01/01/01",
    "self": "https://comminsfinal.appspot.com/loads/5678164130922496"
}
```

#### Failure

```
Status: 400 Bad Request

{
"Error": "The request object has at least one missing or invalid attribute"
}
```

#### Failure

```
Status: 403 Forbidden

{
"Error": "The name attribute of the request object is not unique"
}
```

#### Failure

```
Status: 404 Not Found

{
"Error": "No load with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Put a load

Allows you to create a new load to replace a load with the given id. The URL of the new load is stored in the Location header of the response.

PUT /boats/:id

### Request

### **Request Parameters**

Name	Туре	Description	Required?
id	String	ID of the load	Yes

### Request Body

Required

### Request Body Format

**JSON** 

### Request JSON Attributes

Name	Туре	Description	Required?
weight	Integer	The weight of the load.	Yes
		Must be positive.	
content	String	The contents of the load.	Yes
		Must be 1-28 characters.	
		Only alphanumeric characters and whitespaces are allowed. Whitespaces cannot be the first character or the only character.	
delivery_d ate	String	The date the load is due to be delivered	Yes

### Request Body Example

```
{
    "weight": 12,
    "content": "apples",
    "delivery_date": "05/10/15"
}
```

### Response

### Response Body Format

JSON

### **Response Statuses**

Outcome	Status Code	Notes
Success	303 See Other The boat with the given id was overwritten successfu	
		with a new boat. The location of the new boat is specified
		in the 'Location' header of the response.

400 Bad Request	If the request is missing any of the 3 required attributes		
	or any of them are invalid, the boat is not created.		
403 Forbidden	The given name attribute already exists on another boat		
404 Not Found	No boat with this id exists		
406 Not Acceptable	Client asks for response media type the server cannot offer		
	403 Forbidden 404 Not Found		

### **Response Examples**

#### Success

```
Status: 303 See Other

{
    "id": 5678164130922496,
    "weight": 12,
    "content": "apples",
    "delivery_date": "05/10/15",
    "self": "https://comminsfinal.appspot.com/loads/5678164130922496"
}
```

#### Failure

```
Status: 400 Bad Request

{
"Error": "The request object has at least one missing or invalid attribute"
}
```

#### Failure

```
Status: 403 Forbidden

{
"Error": "The name attribute of the request object is not unique"
}
```

#### Failure

```
Status: 404 Not Found

{
"Error": "No boat with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Delete a load

## DELETE /loads/:id

### Request

**Request Parameters** 

None

Request Body

None

Response

No body

Response Body Format

Success: No body

Failure: JSON

### **Response Statuses**

Outcome	Status Code	Notes		
Success	204 No Content			
Failure	404 Not Found	No load with this id exists		
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer		

### **Response Examples**

#### Success

Status: 204 No Content

#### Failure

```
Status: 404 Not Found

{
"Error": "No load with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## View all loads of a given boat

## GET /boats/:id/loads

### Request

**Request Parameters** 

None

**Request Body** 

None

Request Authorization

Bearer Token (JWT)

Response

**Response Body Format** 

JSON

#### **Response Statuses**

Outcome	Status Code	Notes		
Success	200 OK			
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the		
		JWT does not match the 'owner' attribute of the boat.		
Failure	404 Not Found	No boat with this id exists.		
Failure	406 Not Acceptable	Client asks for response media type the server cannot		
		offer		

### **Response Examples**

### Success

```
Status: 401 Unauthorized

{
"Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

### Failure

```
Status: 404 Not Found

{
"Error": "No boat with this id exists"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Assign a load to a boat

PUT /boats/:bid/:lid

Request

**Request Parameters** 

None

Request Body

None

Note: You will need to set Content-Length to 0 in your request when calling out to this endpoint.

Response

No body

**Response Body Format** 

Success: No body

Failure: JSON

**Request Authorization** 

Bearer Token (JWT)

### **Response Statuses**

Outcome	Status Code	Notes		
Success	204 No Content	Succeeds only if a boat exists with this bid, a load exists		
		with this lid and the load is not already assigned to		
		another boat.		
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the		
		JWT does not match the 'owner' attribute of the boat.		
Failure	403 Forbidden	The load is already assigned to a boat.		
Failure	404 Not Found	No boat with this bid exists, and/or no load with this lid		
		exits.		
Failure	406 Not Acceptable	Client asks for response media type the server cannot		
		offer		

### Response Examples

Success

Status: 204 No Content

```
Status: 401 Unauthorized

{
"Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

```
Status: 403 Forbidden

{
"Error": "The load is already assigned to a boat"
}
```

### Failure

```
Status: 404 Not Found
{
"Error": "The specified boat and/or load don't exist"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Remove a load from a boat

### DELETE /boats/:bid/:lid

Request

**Request Parameters** 

None

Request Body

None

**Request Authorization** 

Bearer Token (JWT)

Response

No body

Response Body Format

Success: No body

Failure: JSON

### **Response Statuses**

Outcome	Status Code	Notes		
Success 204 No Content		Succeeds only if a boat exists with this bid, a load exists with this lid and this load is assigned to this boat.		
Failure	401 Unauthorized	The JWT is missing, invalid, or the 'sub' attribute in the JWT does not match the 'owner' attribute of the boat.		
Failure	404 Not Found	No boat with this bid is at the load with this lid.		
Failure	406 Not Acceptable	Client asks for response media type the server cannot offer		

### Response Examples

Success

Status: 204 No Content

#### Failure

```
Status: 401 Unauthorized

{
    "Error": "Could not find a boat with the given id belonging to the owner in the JWT."
}
```

```
Status: 404 Not Found

{
"Error": "No boat with this bid has a load with this lid"
}
```

```
Status: 406 Not Acceptable

{
"Error": "The requested response media type is not supported"
}
```

## Get all boats from a user

Get all boats that have been created by a user.

_					
(	GET /users/·user	id/·hoats			

## Request

## **Request Parameters**

Name	Туре	Description	Required?
user_id	String	ID of the user	Yes

Request Body

None

Request Authorization

Bearer Token (JWT)

Response

Response Body Format

JSON