




US 20100141548A1

(19) **United States**(12) **Patent Application Publication**  
**Quintero Illera et al.**(10) **Pub. No.: US 2010/0141548 A1**(43) **Pub. Date: Jun. 10, 2010**(54) **MULTILEVEL AND SPACE-FILLING  
GROUND-PLANES FOR MINIATURE AND  
MULTIBAND ANTENNAS**Mar. 10, 2004, now Pat. No. 7,362,283, which is a  
continuation of application No. PCT/EP01/10589,  
filed on Sep. 13, 2001.(76) Inventors: **Ramiro Quintero Illera**, Barcelona  
(ES); **Carles Puente Baliarda**,  
Barcelona (ES)**Publication Classification**(51) **Int. Cl.**  
**H01Q 1/48** (2006.01)(52) **U.S. Cl.** ..... **343/848**Correspondence Address:  
**WINSTEAD PC**  
**P.O. BOX 50784**  
**DALLAS, TX 75201 (US)**(57) **ABSTRACT**(21) Appl. No.: **12/652,412**(22) Filed: **Jan. 5, 2010****Related U.S. Application Data**(63) Continuation of application No. 12/033,446, filed on  
Feb. 19, 2008, now Pat. No. 7,688,276, which is a  
continuation of application No. 10/797,732, filed on

An antenna system includes one or more conductive elements acting as radiating elements, and a multilevel or space-filling ground-plane, wherein said ground-plane has a particular geometry which affects the operating characteristics of the antenna. The return loss, bandwidth, gain, radiation efficiency, and frequency performance can be controlled through multilevel and space-filling ground-plane design. Also, said ground-plane can be reduced compared to those of antennas with solid ground-planes.






Fig. 1




Fig. 2





Fig. 3





Fig. 4





Fig. 5




Fig. 6




Fig. 7






Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15






Fig. 16




Fig. 17




Fig. 18




Fig. 19

# MULTILEVEL AND SPACE-FILLING GROUND-PLANES FOR MINIATURE AND MULTIBAND ANTENNAS

## CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is a continuation of U.S. patent application Ser. No. 12/033,446, filed on Feb. 19, 2008. U.S. patent application Ser. No. 12/033,446 is a continuation of U.S. Pat. No. 7,362,283, issued on Apr. 22, 2008. U.S. Pat. No. 7,362,283 is a continuation of PCT/EP01/10589, filed on Sep. 13, 2001. U.S. patent application Ser. No. 12/033,446, U.S. Pat. No. 7,362,283 and International Patent Application PCT/EP01/10589 are incorporated herein by reference.

## OBJECT AND BACKGROUND OF THE INVENTION

**[0002]** 1. Technical Field of the Invention

**[0003]** The present invention relates generally to a new family of antenna ground-planes of reduced size and enhanced performance based on an innovative set of geometries. These new geometries are known as multilevel and space-filling structures, which had been previously used in the design of multiband and miniature antennas. A throughout description of such multilevel or space-filling structures can be found in "Multilevel Antennas" (Patent Publication No. WO01/22528) and "Space-Filling Miniature Antennas" (Patent Publication No. WO01/54225).

**[0004]** 2. Description of the Related Art

**[0005]** The current invention relates to the use of such geometries in the ground-plane of miniature and multiband antennas. In many applications, such as for instance mobile terminals and handheld devices, it is well known that the size of the device restricts the size of the antenna and its ground-plane, which has a major effect on the overall antenna performance. In general terms, the bandwidth and efficiency of the antenna are affected by the overall size, geometry, and dimensions of the antenna and the ground-plane. A report on the influence of the ground-plane size in the bandwidth of terminal antennas can be found in the publication "Investigation on Integrated Antennas for GSM Mobile Phones", by D. Man-teuffel, A. Bahr, I. Wolff, Millennium Conference on Antennas & Propagation, ESA, AP2000, Davos, Switzerland, April 2000. In the prior art, most of the effort in the design of antennas including ground-planes (for instance microstrip, planar inverted-F or monopole antennas) has been oriented to the design of the radiating element (that is, the microstrip patch, the PIFA element, or the monopole arm for the examples described above), yet providing a ground-plane with a size and geometry that were mainly dictated by the size or aesthetics criteria according to every particular application.

**[0006]** One of the key issues of the present invention is considering the ground-plane of an antenna as an integral part of the antenna that mainly contributes to its radiation and impedance performance (impedance level, resonant frequency, bandwidth). A new set of geometries are disclosed here, such a set allowing to adapt the geometry and size of the ground-plane to the ones required by any application (base station antennas, handheld terminals, cars, and other motor-vehicles and so on), yet improving the performance in terms of, for instance, bandwidth, Voltage Standing Wave Ratio (hereafter VSWR), or multiband behaviour.

**[0007]** The use of multilevel and space-filling structures to enhance the frequency range an antenna can work within was well described in patent publication numbers WO01/22528 and WO01/54225. Such an increased range is obtained either through an enhancement of the antenna bandwidth, with an increase in the number of frequency bands, or with a combination of both effects. In the present invention, said multilevel and space-filling structures are advantageously used in the ground-plane of the antenna obtaining this way either a better return loss or VSWR, a better bandwidth, a multiband behaviour, or a combination of all these effects. The technique can be seen as well as a means of reducing the size of the ground-plane and therefore the size of the overall antenna.

**[0008]** A first attempt to improve the bandwidth of microstrip antennas using the ground-plane was described by T. Chiou, K. Wong, "Designs of Compact Microstrip Antennas with a Slotted Ground Plane". IEEE-APS Symposium, Boston, 8-12 Jul., 2001. The skilled in the art will notice that even though the authors claim the improved performance is obtained by means of some slots on the antenna ground-plane, those were unintentionally using a very simple case of multilevel structure to modify the resonating properties of said ground-plane. In particular, a set of two rectangles connected through three contact points and a set of four rectangles connected through five contact points were described there. Another example of an unintentional use of a multilevel ground structure in an antenna ground-plane is described in U.S. Pat. No. 5,703,600. There, a particular case of a ground-plane composed by three rectangles with a capacitive electromagnetic coupling between them was used. It should be stressed that neither in the paper by Chiou and Wong, nor in patent U.S. Pat. No. 5,703,600, the general configuration for space-filling or multilevel structures were disclosed or claimed, so the authors were not attempting to use the benefits of said multilevel or space-filling structures to improve the antenna behaviour.

**[0009]** Some of the geometries described in the present invention are inspired in the geometries already studied in the 19<sup>th</sup> century by several mathematicians such as Giuseppe Peano and David Hilbert. In all said cases the curves were studied from the mathematical point of view but were never used for any practical engineering application. Such mathematical abstractions can be approached in a practical design by means of the general space-filling curves described in the present invention. Other geometries, such as the so called SZ, ZZ, HilbertZZ, Peanoinc, Peanodec or PeanoZZ curves described in patent publication WO01/54225 are included in the set of space-filling curves used in an innovative way in the present invention. It is interesting to notice that in some cases, such space-filling curves can be used to approach ideal fractal shapes as well.

**[0010]** The dimension (D) is often used to characterize highly complex geometrical curves and structures such as those described in the present invention. There exists many different mathematical definitions of dimension but in the present document the box-counting dimension (which is well-known to those skilled in mathematics theory) is used to characterize a family of designs. Again, the advantage of using such curves in the novel configuration disclosed in the present invention is mainly the overall antenna miniaturization together with and enhancement of its bandwidth, impedance, or multiband behaviour.

**[0011]** Although usually not as efficient as the general space-filling curves disclosed in the present invention, other

well-known geometries such as meandering and zigzag curves can also be used in a novel configuration according to the spirit and scope of the present invention. Some descriptions of using zigzag or meandering curves in antennas can be found for instance in patent publication WO96/27219, but it should be noticed that in the prior-art such geometries were used mainly in the design of the radiating element rather than in the design of the ground-plane as it is the purpose and basis of several embodiments in the present invention.

**[0012]** It is known the European Patent EP-688.040 which discloses a bidirectional antenna including a substrate having a first and second surfaces. On a second surface are arranged respectively, a ground conductor formed by a single surface, a strip conductor and a patch conductor.

#### SUMMARY OF THE INVENTION

**[0013]** The key point of the present invention is shaping the ground-plane of an antenna in such a way that the combined effect of the ground-plane and the radiating element enhances the performance and characteristics of the whole antenna device, either in terms of bandwidth, VSWR, multiband behaviour, efficiency, size, or gain. Instead of using the conventional solid geometry for ground-planes as commonly described in the prior art, the invention disclosed here introduces a new set of geometries that forces the currents on the ground-plane to flow and radiate in a way that enhances the whole antenna behaviour.

**[0014]** The basis of the invention consists of breaking the solid surface of a conventional ground-plane into a number of conducting surfaces (at least two of them) said surfaces being electromagnetically coupled either by the capacitive effect between the edges of the several conducting surfaces, or by a direct contact provided by a conducting strip, or a combination of both effects.

**[0015]** The resulting geometry is no longer a solid, conventional ground-plane, but a ground-plane with a multilevel or space-filling geometry, at least in a portion of said ground-plane.

**[0016]** A Multilevel geometry for a ground-plane consists of a conducting structure including a set of polygons, all of said polygons featuring the same number of sides, wherein said polygons are electromagnetically coupled either by means of a capacitive coupling or ohmic contact, wherein the contact region between directly connected polygons is narrower than 50% of the perimeter of said polygons in at least 75% of said polygons defining said conducting ground-plane. In this definition of multilevel geometry, circles and ellipses are included as well, since they can be understood as polygons with infinite number of sides.

**[0017]** On the other hand, an Space-Filling Curve (hereafter SFC) is a curve that is large in terms of physical length but small in terms of the area in which the curve can be included. More precisely, the following definition is taken in this document for a space-filling curve: a curve composed by at least ten segments which are connected in such a way that each segment forms an angle with their neighbours, that is, no pair of adjacent segments define a larger straight segment, and wherein the curve can be optionally periodic along a fixed straight direction of space if, and only if, the period is defined by a non-periodic curve composed by at least ten connected segments and no pair of said adjacent and connected segments defines a straight longer segment. Also, whatever the design of such SFC is, it can never intersect with itself at any point except the initial and final point (that is, the whole curve

can be arranged as a closed curve or loop, but none of the parts of the curve can become a closed loop). A space-filling curve can be fitted over a flat or curved surface, and due to the angles between segments, the physical length of the curve is always larger than that of any straight line that can be fitted in the same area (surface) as said space-filling curve. Additionally, to properly shape the ground-plane according to the present invention, the segments of the SFC curves included in said ground-plane must be shorter than a tenth of the free-space operating wavelength.

**[0018]** Depending on the shaping procedure and curve geometry, some infinite length SFC can be theoretically designed to feature a Hausdorff dimension larger than their topological-dimension. That is, in terms of the classical Euclidean geometry, it is usually understood that a curve is always a one-dimension object; however when the curve is highly convoluted and its physical length is very large, the curve tends to fill parts of the surface which supports it; in that case, the Hausdorff dimension can be computed over the curve (or at least an approximation of it by means of the box-counting algorithm) resulting in a number larger than unity. The curves described in FIG. 2 are some examples of such SFC; in particular, drawings 11, 13, 14, and 18 show some examples of SFC curves that approach an ideal infinite curve featuring a dimension  $D=2$ . As known by those skilled in the art, the box-counting dimension can be computed as the slope of the straight portion of a log-log graph, wherein such a straight portion is substantially defined as a straight segment. For the particular case of the present invention, said straight segment will cover at least an octave of scales on the horizontal axis of the log-log graph.

**[0019]** Depending on the application, there are several ways for establishing the required multilevel and space-filling metallic pattern according to the present invention. Due to the special geometry of said multilevel and space-filling structures, the current distributes over the ground-plane in such a way that it enhances the antenna performance and features in terms of:

**[0020]** (a) Reduced size compared to antennas with a solid ground-plane.

**[0021]** (b) Enhanced bandwidth compared to antennas with a solid ground-plane.

**[0022]** (c) Multifrequency performance.

**[0023]** (d) Better VSWR feature at the operating band or bands.

**[0024]** (e) Better radiation efficiency.

**[0025]** (f) Enhanced gain.

**[0026]** It will be clear that any of the general and newly described ground-planes of the present invention can be advantageously used in any of the prior-art antenna configurations that require a ground-plane, for instance: antennas for handheld terminals (cellular or cordless telephones, PDAs, electronic pagers, electronic games, or remote controls), base station antennas (for instance for coverage in micro-cells or pico-cells for systems such as AMPS, GSM900, GSM1800, UMTS, PCS1900, DCS, DECT, WLAN, . . . ), car antennas, and so on. Such antennas can usually take the form of microstrip patch antennas, slot-antennas, Planar Inverted-F (PIFA) antennas, monopoles and so on, and in all those cases where the antenna requires a ground-plane, the present invention can be used in an advantageous way. Therefore, the invention is

not limited to the aforementioned antennas. The antenna could be of any other type as long as a ground-plane is included.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0027] For a better understanding of the present invention, reference will now be made to the appended drawings in which:

[0028] FIG. 1 shows a comparison between two prior art ground-planes and a new multilevel ground-plane. Drawing 1 shows a conventional ground-plane formed by only one solid surface (rectangle, prior-art), whereas drawing 2 shows a particular case of ground-plane that has been broken in two surfaces 5 and 6 (rectangles) connected by a conducting strip 7, according to the general techniques disclosed in the present invention. Drawing 3 shows a ground-plane where the two conducting surfaces 5 and 6, separated by a gap 4, are being connected through capacitive effect (prior-art).

[0029] FIG. 2 shows some examples of SFC curves. From an initial curve 8, other curves 9, 10, and 11 are formed (called Hilbert curves). Likewise, other set of SFC curves can be formed, such as set 12, 13, and 14 (called SZ curves); set 15 and 16 (known as ZZ curves); set 17, 18, and 19 (called HilbertZZ curves); set 20 (Peanodec curve); and set 21 (based on the Giuseppe Peano curve).

[0030] FIG. 3A shows a perspective view of a conventional (prior-art) Planar Inverted-F Antenna or PIFA (22) formed by a radiating antenna element 25, a conventional solid surface ground-plane 26, a feed point 24 coupled somewhere on the patch 25 depending upon the desired input impedance, and a short-circuit 23 coupling the patch element 25 to the ground-plane 26. FIG. 3B shows a new configuration (27) for a PIFA antenna, formed by an antenna element 30, a feed point 29, a short-circuit 28, and a particular example of a new ground-plane structure 31 formed by both multilevel and space-filling geometries.

[0031] FIG. 4A is a representational perspective view of the conventional configuration (prior-art) for a monopole 33 over a solid surface ground-plane 34. FIG. 4B shows an improved monopole antenna configuration 35 where the ground-plane 37 is composed by multilevel and space-filling structures.

[0032] FIG. 5A shows a perspective view of a patch antenna system 38 (prior-art) formed by a rectangular radiating element patch 39 and a conventional ground-plane 40. FIG. 5B shows an improved antenna patch system composed by a radiating element 42 and a multilevel and space-filling ground-plane 43.

[0033] FIG. 6 shows several examples of different contour shapes for multilevel ground-planes, such as rectangular (44, 45, and 46) and circular (47, 48, and 49). In this case, circles and ellipses are taken as polygons with infinite number of sides.

[0034] FIG. 7 shows a series of same-width multilevel structures (in this case rectangles), where conducting surfaces are being connected by means of conducting strips (one or two) that are either aligned or not aligned along a straight axis.

[0035] FIG. 8 shows that not only same-width structures can be connected via conducting strips. More than one conducting strips can be used to interconnect rectangular polygons as in drawings 59 and 61. Also it is disclosed some examples of how different width and length conducting strips among surfaces can be used within the spirit of the present invention.

[0036] FIG. 9 shows alternative schemes of multilevel ground-planes. The ones being showed in the FIGS. 68 to 76) are being formed from rectangular structures, but any other shape could have been used.

[0037] FIG. 10 shows examples (77 and 78) of two conducting surfaces (5 and 6) being connected by one (10) or two (9 and 10) SFC connecting strips.

[0038] FIG. 11 shows examples wherein at least a portion of the gap between at least two conducting surfaces is shaped as an SPC connecting strip.

[0039] FIG. 12 shows a series of ground-planes where at least one of the parts of said ground-planes is shaped as SFC. In particular, the gaps (84, 85) between conducting surfaces are shaped in some cases as SFC.

[0040] FIG. 13 shows another set of examples where parts of the ground-planes such as the gaps between conducting surfaces are being shaped as SFC.

[0041] FIG. 14 shows more schemes of ground-planes (91 and 92) with different SFC width curves (93 and 94). Depending on the application, configuration 91 can be used to minimize the size of the antenna while configuration 92 is preferred for enhancing bandwidth in a reduced size antenna while reducing the backward radiation.

[0042] FIG. 15 shows a series of conducting surfaces with different widths being connected through SFC conducting strips either by direct contact (95, 96, 97, 98) or by capacitive effect (central strip in 98).

[0043] FIG. 16 shows examples of multilevel ground-planes (in this case formed by rectangles).

[0044] FIG. 17 shows another set examples of multilevel ground-planes.

[0045] FIG. 18 shows examples of multilevel ground-planes where at least two conducting surfaces are being connected through meandering curves with different lengths or geometries. Some of said meandering lines can be replaced by SFC curves if a further size reduction or a different frequency behaviour is required.

[0046] FIG. 19 shows examples of antennas wherein the radiating element has substantially the same shape as the ground-plane, thereby obtaining a symmetrical or quasymmetrical configuration, and where said radiating element is placed parallel (drawing 127) or orthogonal (drawing 128) to said ground-plane.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0047] In order to construct an antenna assembly according to embodiments of our invention, a suitable antenna design is required. Any number of possible configurations exists, and the actual choice of antenna is dependent, for instance, on the operating frequency and bandwidth, among other antenna parameters. Several possible examples of embodiments are listed hereinafter. However, in view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention. In particular, different materials and fabrication processes for producing the antenna system may be selected, which still achieve the desired effects. Also, it would be clear that other multilevel and space-filling geometries could be used within the spirit of the present invention.

[0048] FIG. 3A shows in a manner already known in prior art a Planar Inverted-F (22) Antenna (hereinafter PIFA Antenna) being composed by a radiating antenna element 25, a conventional solid surface ground-plane 26, a feed point 24

coupled somewhere on the patch **25** depending upon the desired input impedance, and a short-circuit **23** coupling the patch element **25** to the ground-plane **26**. The feed point **24** can be implemented in several ways, such a coaxial cable, the sheath of which is coupled to the ground-plane and the inner conductor **24** of which is coupled to the radiating conductive element **25**. The radiating conductive element **25** is usually shaped like a quadrangle, but several other shapes can be found in other patents or scientific articles. Shape and dimensions of radiating element **25** will contribute in determining operating frequency of the overall antenna system. Although usually not considered as a part of the design, the ground-plane size and geometry also has an effect in determining the operating frequency and bandwidth for said PIFA. PIFA antennas have become a hot topic lately due to having a form that can be integrated into the per se known type of handset cabinets.

**[0049]** Unlike the prior art PIFA ground-planes illustrated in FIG. 3A, the newly disclosed ground-plane **31** according to FIG. 3B is composed by multilevel and space-filling structures obtaining this way a better return loss or VSWR, a better bandwidth, and multiband behaviour, along with a compressed antenna size (including ground-plane). The particular embodiment of PIFA **27** is composed by a radiating antenna element **30**, a multilevel and space-filling ground-plane **31**, a feed point **29** coupled somewhere on the patch **30**, and a short-circuit **28** coupling the patch element **30** to the ground-plane **31**. For the sake of clarity but without loss of generality, a particular case of multilevel ground-plane **31** is showed, where several quadrangular surfaces are being electromagnetically coupled by means of direct contact through conducting strips and said polygons, together with an SFC and a meandering line. More precisely, the multilevel structure is formed with 5 rectangles, said multilevel structure being connected to a rectangular surface by means of SFC (**8**) and a meandering line with two periods. It is clear to those skilled in the art that those surfaces could have been any other type of polygons with any size, and being connected in any other manner such as any other SFC curve or even by capacitive effect. For the sake of clarity, the resulting surfaces defining said ground-plane are lying on a common flat surface, but other conformal configurations upon curved or bent surfaces could have been used as well.

**[0050]** For this preferred embodiment, the edges between coupled rectangles are either parallel or orthogonal, but they do not need to be so. Also, to provide the ohmic contact between polygons several conducting strips can be used according to the present invention. The position of said strips connecting the several polygons can be placed at the center of the gaps as in FIG. 6 and drawings **2**, **50**, **51**, **56**, **57**, **62**, **65**, or distributed along several positions as shown in other cases such as for instance drawings **52** or **58**.

**[0051]** In some preferred embodiments, larger rectangles have the same width (for instance FIG. 1 and FIG. 7) but in other preferred embodiments they do not (see for instance drawings **64** through **67** in FIG. 8). Polygons and/or strips are linearly arranged with respect an straight axis (see for instance **56** and **57**) in some embodiments while in others embodiments they are not centered with respect to said axis. Said strips can also be placed at the edges of the overall ground-plane as in, for instance, drawing **55**, and they can even become arranged in a zigzag or meandering pattern as in drawing **58** where the strips are alternatively and sequentially placed at the two longer edges of the overall ground-plane.

**[0052]** Some embodiments like **59** and **61**, where several conducting surfaces are coupled by means of more than one strip or conducting polygon, are preferred when a multiband or broadband behaviour is to be enhanced. Said multiple strip arrangement allows multiple resonant frequencies which can be used as separate bands or as a broad-band if they are properly coupled together. Also, said multiband or broadband behaviour can be obtained by shaping said strips with different lengths within the same gap.

**[0053]** In other preferred embodiments, conducting surfaces are connected by means of strips with SFC shapes, as in the examples shown in FIG. 3, 4, 5, 10, 11, 14, or 15. In said configurations, SFC curves can cover even more than the 50% of the area covered by said ground-plane as it happens in the cases of FIG. 14. In other cases, the gap between conducting surfaces themselves is shaped as an SFC curve as shown in FIG. 12 or 13. In some embodiments, SFC curves feature a box-counting dimension larger than one (at least for an octave in the abscissa of the log-log graph used in the box-counting algorithm) and can approach the so called Hilbert or Peano curves or even some ideally infinite curves known as fractal curves.

**[0054]** Another preferred embodiment of multilevel and space-filling ground-plane is the monopole configuration as shown in FIG. 4. FIG. 4A shows a prior art antenna system **32** composed by a monopole radiating element **33** over a common and conventional solid surface ground-plane **34**. Prior art patents and scientific publications have dealt with several one-piece solid surfaces, being the most common ones circular and rectangular. However, in the new ground-plane configuration of our invention, multilevel and space-filling structures can be used to enhance either the return loss, or radiation efficiency, or gain, or bandwidth, or a combination of all the above, while reducing the size compared to antennas with a solid ground-plane. FIG. 4B shows a monopole antenna system **35** composed by a radiating element **36** and a multilevel and space-filling ground-plane **37**. Here, the arm of the monopole **33** is presented as a cylinder, but any other structure can be obviously taken instead (even helical, zigzag, meandering, fractal, or SFC configurations, to name a few).

**[0055]** To illustrate that several modifications of the antenna can be done based on the same principle and spirit of the present invention, another preferred embodiment example is shown in FIG. 5, based on the patch configuration. FIG. 5A shows an antenna system **38** that consist of a conventional patch antenna with a polygonal patch **39** (squared, triangular, pentagonal, hexagonal, rectangular, or even circular, multilevel, or fractal, to name just a few examples) and a common and conventional one-piece solid ground-plane **40**. FIG. 5B shows a patch antenna system **41** that consists of a radiating element **42** (that can have any shape or size) and a multilevel and space-filling ground-plane **43**. The ground-plane **43** being showed in the drawing is just an example of how multilevel and space-filling structures can be implemented on a ground-plane.

**[0056]** Preferably, the antenna, the ground-plane or both are disposed on a dielectric substrate. This may be achieved, for instance, by etching techniques as used to produce PCBs, or by printing the antenna and the ground-plane onto the substrate using a conductive ink. A low-loss dielectric substrate (such as glass-fibre, a teflon substrate such as Cuclad® or other commercial materials such as Rogers® 4003 well-known in the art) can be placed between said patch and ground-plane. Other dielectric materials with similar proper-



ties may be substituted above without departing from the intent of the present invention. As an alternative way to etching the antenna and the ground-plane out of copper or any other metal, it is also possible to manufacture the antenna system by printing it using conductive ink. The antenna feeding scheme can be taken to be any of the well-known schemes used in prior art patch antennas as well, for instance: a coaxial cable with the outer conductor connected to the ground-plane and the inner conductor connected to the patch at the desired input resistance point; a microstrip transmission line sharing the same ground-plane as the antenna with the strip capacitively coupled to the patch and located at a distance below the patch, or in another embodiment with the strip placed below the ground-plane and coupled to the patch through an slot, and even a microstrip transmission line with the strip co-planar to the patch. All these mechanisms are well known from prior art and do not constitute an essential part of the present invention. The essential part of the present invention is the shape of the ground-plane (multilevel and/or space-filling), which contributes to reducing the size with respect to prior art configurations, as well as enhancing antenna bandwidth, VSWR, and radiation efficiency.

[0057] It is interesting to notice that the advantage of the ground-plane geometry can be used in shaping the radiating element in a substantially similar way. This way, a symmetrical or quasi-symmetrical configuration is obtained where the combined effect of the resonances of the ground-plane and radiating element is used to enhance the antenna behavior. A particular example of a microstrip (127) and monopole (128) antennas using said configuration and design in drawing 61 is shown in FIG. 19, but it appears clear to any skilled in the art that many other geometries (other than 61) could be used instead within the same spirit of the invention. Drawing 127 shows a particular configuration with a short-circuited patch (129) with shorting post, feeding point 132 and said ground-plane 61, but other configurations with no shorting post, pin, or strip are included in the same family of designs. In the particular design of the monopole (128), the feeding post is 133.

[0058] Although various embodiments of the method and apparatus of the present invention have been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiments disclosed, but is capable of numerous rearrangements, modifications, and substitutions without departing from the spirit and scope of the invention as set forth in the foregoing specification and following claims.

What is claimed:

1. An antenna system comprising:

an antenna element; and

a ground plane comprising:

at least two conducting surfaces each having a plurality of sides defined by at least one edge;

at least one conducting strip connecting the at least two conducting surfaces for allowing current to flow between the at least two conducting surfaces;

the at least one conducting strip being narrower than the width of any of the at least two conducting surfaces; the ground plane being disposed in a plane substantially parallel to a plane of the antenna element;

the ground-plane further comprising at least one of a space-filling-curve shape and a multilevel structure, wherein the multilevel structure includes:

a set of conducting polygons, the polygons each having the same number of sides;

the polygons are electromagnetically coupled by means of either a capacitive coupling or ohmic contact; and

a contact region between directly connected polygons is narrower than half of the perimeter of said polygons in at least seventy-five percent of said polygons defining the conducting ground plane.

2. The antenna system according to claim 1, wherein the at least two conducting surfaces are on a common planar or curved surface.

3. The antenna system according to claim 1, wherein:

two edges of the at least two conducting surfaces are substantially parallel to each other, and the at least one conducting strip connecting the at least two conducting surfaces is placed substantially centered with respect to the gap defined by the two substantially parallel edges.

4. The antenna system according to claim 1, wherein:

the ground plane includes at least three conducting surfaces, in which one pair of any of two adjacent conducting surfaces is connected by means of at least one conducting strip; and

remaining pairs of adjacent conducting surfaces are electromagnetically connected by means of a capacitive effect or by direct contact provided by the at least a conducting strip.

5. The antenna system according to claim 4, wherein the strips are substantially aligned along a straight axis.

6. The antenna system according to claim 4, wherein the strips are not aligned along a straight axis.

7. The antenna system according to claim 1, wherein the ground plane comprises at least two conducting strips, the at least two conducting strips connecting at least two of the at least two conducting surfaces at least at two points located at edges of the at least two conducting surfaces.

8. The antenna system according to claim 1, wherein at least one of the at least one conducting strip is aligned along an edge defining an external perimeter of the ground plane.

9. The antenna system according to claim 1, the ground-plane comprising a plurality of conducting surfaces on the same planar or curved surface, wherein at least two of the conducting surfaces are connected by a conducting strip.

10. The antenna system according to claim 1, wherein each pair of the at least two adjacent conducting surfaces are connected by at least one conducting strip.

11. The antenna system according to claim 1, wherein all the conducting surfaces defining the ground plane have a substantially rectangular shape, the conducting surfaces being sequentially aligned along a straight axis, each pair of the conducting surfaces defining a gap therebetween, at least two opposite edges of at least one of the gaps being connected by at least one of the at least one conducting strip.

12. The antenna system according to claim 1, wherein:

all of the at least two conducting surfaces defining the ground plane have the same horizontal width and are sequentially aligned along a straight vertical axis;

each pair of adjacent conducting surfaces of the at least two conducting surfaces define a gap therebetween;

each pair of adjacent conducting surfaces of the at least two conducting surfaces are connected across the gap by a conducting strip of the at least one conducting strip;

the strip is aligned along an edge of the external perimeter of the ground plane, the edge of the external perimeter is

alternatively and sequentially chosen at the right and left sides with respect to a vertical axis crossing the center of the ground plane.

**13.** The antenna system according to claim **1**, wherein at least one of the at least one conducting strip is shaped as a zigzag or meandering curve.

**14.** An antenna system comprising:  
an antenna element; and

a ground plane comprising:

at least two conducting surfaces each having a plurality of sides defined by at least one edge;

at least one conducting strip connecting the at least two conducting surfaces for allowing current to flow between the at least two conducting surfaces;

the at least one conducting strip being narrower than the width of any of the at least two conducting surfaces;

the ground plane being disposed in a plane substantially parallel to a plane of the antenna element;

the ground-plane further comprising at least one of a space-filling-curve shape and a multilevel structure, the multilevel structure comprising a set of conducting polygons, the polygons each having the same number of sides;

at least one of the conducting surfaces or at least one of the conducting strips of the ground plane is shaped as a space filling curve (SFC), the SFC including at least ten connected straight segments; and

the at least ten connected straight segments are smaller than a tenth of the operating free-space wave length and are

spatially arranged in such a way that no two adjacent and connected segments form another longer straight segment.

**15.** The antenna system according to claim **14**, wherein the at least ten connected straight segments intersect at tips of the SFC.

**16.** The antenna system according to claim **14**, wherein the SFC comprises a plurality of corners formed by each pair of adjacent segments of the at least ten connected straight segments, the plurality of corners each being rounded.

**17.** The antenna system according to claim **14**, wherein the SFC is periodic along a fixed straight direction of space if the period is defined by a non-periodic curve comprising at least ten connected segments and no pair of the adjacent and connected segments define a straight longer segment.

**18.** The antenna system according to claim **14**, wherein the SFC has a box-counting dimension larger than one, the box-counting dimension is computed as the slope of the straight portion of a log-log graph, wherein the straight portion is a straight segment over at least an octave of scales on the horizontal axis of the log-log graph.

**19.** The antenna system according to claim **1**, wherein the SFC comprises at least one of a Hilbert, Peano, SZ, ZZ, HilbertZZ, Peanoinc, Peanodec, or PeanoZZ curve.

**20.** The antenna system according to claim **14**, wherein at least one of the at least one conducting strip is shaped as a SFC.

\* \* \* \* \*