

Vulnerability Identification


MD Mahfuz Sarker Mahi

Conduct Vulnerability scans on “103.122.138.130/24” & “seu.edu.bd”


Total Vulnerability: 22

Mixed: 2, Info: 20(False Positive)

Critical	High	Medium	Low
0	1	3	0



Conduct Vulnerability scans on “103.122.138.130/24”



Conduct Vulnerability scans on “seu.edu.bd”

CADS003  Config

[← Back to All Scans](#)

Hosts 3 Vulnerabilities 22 Notes 1 History 1

Filter Search Vulnerabilities 22 Vulnerabilities

☐	Sev	CVSS	VPR	EPSS	Name	Family	Count		
☐	MIXED	...	...	...	 SNMP (Multiple Issues)	SNMP	11		
☐	MIXED	...	...	...	 SSL (Multiple Issues)	General	8		
☐	INFO	...	...	...	 HTTP (Multiple Issues)	Web Servers	8		
☐	INFO	...	...	...	 TLS (Multiple Issues)	General	6		
☐	INFO				Nessus SYN scanner	Port scanners	10		
☐	INFO				Service Detection	Service detection	8		
☐	INFO				Strict Transport Security (STS) Detection	Service detection	4		
☐	INFO				Nessus Scan Information	Settings	3		
☐	INFO				OS Fingerprints Detected	General	3		
☐	INFO				OS Identification	General	3		
☐	INFO				Traceroute Information	General	3		
☐	INFO				Non-compliant Strict Transport Security (STS)	Service detection	2		
☐	INFO				Remote Services Not Using Post-Quantum Ciphers	General	2		
☐	INFO				Shor's Harvest Now Decrypt Later	General	2		
☐	INFO				TLS Version 1.2 Protocol Detection	Service detection	2		

Hosts 3Vulnerabilities 22Notes 1History 1

Search Vulnerabilities

7 Vulnerabilities

☐	Sev ▾	CVSS ▾	VPR ▾	EPSS ▾	Name ▾	Family ▾	Count ▾	
☐	HIGH	7.5 *	5.2	0.9243	SNMP Agent Default Community Name (public)	SNMP	1	
☐	INFO				SNMP Server Detection	SNMP	3	
☐	INFO				SNMP Supported Protocols Detection	SNMP	3	
☐	INFO				SNMP Protocol Version Detection	SNMP	1	
☐	INFO				SNMP Query Routing Information Disclosure	SNMP	1	
☐	INFO				SNMP Query System Information Disclosure	SNMP	1	
☐	INFO				SNMP Request Network Interfaces Enumeration	SNMP	1	

Hosts 3Vulnerabilities 22Notes 1History 1

HIGH

SNMP Agent Default Community Name (public)

Description

It is possible to obtain the default community name of the remote SNMP server.

An attacker may use this information to gain more knowledge about the remote host, or to change the configuration of the remote system (if the default community allows such modifications).

Solution

Disable the SNMP service on the remote host if you do not use it.
Either filter incoming UDP packets going to this port, or change the default community string.

Output

```
The remote SNMP server replies to the following default community
string :

public
```

To see debug logs, please visit individual host

Port ▾

Hosts

161 / udp / snmp103.122.138.9

High Vulnerability risk level CVSS Score 7.5

Hosts3

Vulnerabilities22

Notes1

History1

Search Vulnerabilities

4 Vulnerabilities

☐	Sev	CVSS	VPR	EPSS	Name	Family	Count	
☐	MEDIUM	6.5			SSL Certificate Cannot Be Trusted	General	2	
☐	INFO				SSL Certificate Information	General	2	
☐	INFO				SSL Cipher Suites Supported	General	2	
☐	INFO				SSL Perfect Forward Secrecy Cipher Suites Supported	General	2	

CADS003 / Plugin #51192

[Back to Vulnerability Group](#)

Hosts 3
Vulnerabilities 22
Notes 1
History 1

MEDIUM SSL Certificate Cannot Be Trusted

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below:

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

Solution

Purchase or generate a proper SSL certificate for this service.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>
<https://en.wikipedia.org/wiki/X.509>

Output

```

The following certificate was at the top of the certificate
chain sent by the remote host, but it is signed by an unknown
certificate authority :

|-Subject : C=CN/SI=JS/L=NJ/O=BM/OU=VEN/CN=LOCAL-1022A6409997
|-Issuer  : C=CN/SI=JS/L=NJ/O=BM/OU=VEN/CN=CA-1022A6409997

```

To see debug logs, please visit individual host

Port	Hosts
8443 / tcp / www	103.122.138.131 103.122.138.132

Medium Vulnerability risk level CVSS Score 6.5

Medium Vulnerability risk level CVSS Score 6.5

Hosts 1

Vulnerabilities 17

Notes 1

History 1

Search Vulnerabilities

4 Vulnerabilities

Sev	CVSS	VPR	EPSS	Name	Family	Count		
☐	MEDIUM	6.5		TLS Version 1.0 Protocol Detection	Service detection	1	🔍	✎
☐	MEDIUM	6.5		TLS Version 1.1 Deprecated Protocol	Service detection	1	🔍	✎
☐	INFO			TLS Version 1.1 Protocol Detection	Service detection	1	🔍	✎
☐	INFO			TLS Version 1.2 Protocol Detection	Service detection	1	🔍	✎

Scan Details

Policy: Basic Network Scan

Status: Completed

Severity Base: CVSS v3.0 ✎

Scanner: Local Scanner

Start: Today at 5:51 PM

End: Today at 6:11 PM

Elapsed: 20 minutes

Vulnerabilities

Critical

High

Medium

Low

Info

Final Scan / Plugin #104743

[Back to Vulnerability Group](#)

ConfigureAudit TrailLaunch▼ReportExport

Hosts1Vulnerabilities17Notes1History1

MEDIUM

TLS Version 1.0 Protocol Detection

>

Plugin Details

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Output

TLSv1 is enabled and the server supports at least one cipher.

To see debug logs, please visit individual host

Port -

Hosts

443 / tcp / www

seu.edu.bd

Severity:Medium

ID:104743

Version:1.10

Type:remote

Family:Service detection

Published:November 22, 2017

Modified:April 19, 2023

Risk Information

Risk Factor: Medium

CVSS v3.0 Base Score: 6.5

CVSS v3.0 Vector: CVSS:3.0/AV:N/ACH:PR:N/UI:N/S:U/CH:L/L:A:N

CVSS v2.0 Base Score: 6.1

CVSS v2.0 Vector: CVSS2#AV:N/ACH:Au:N/C:C/I:P/A:N

Vulnerability Information

Asset Inventory: True

Reference Information

CWE: 327

Final Scan / Plugin #157288

[Back to Vulnerability Group](#)

ConfigureAudit TrailLaunch▼ReportExport

Hosts1Vulnerabilities17Notes1History1

MEDIUM

TLS Version 1.1 Deprecated Protocol

< >

Plugin Details

Description

The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

See Also

<https://datatracker.ietf.org/doc/html/rfc8996>
<http://www.nessus.org/u?c8ae820d>

Output

TLSv1.1 is enabled and the server supports at least one cipher.

To see debug logs, please visit individual host

Port -

Hosts

443 / tcp / www

seu.edu.bd

Severity:Medium

ID:157288

Version:1.4

Type:remote

Family:Service detection

Published:April 4, 2022

Modified:May 14, 2024

Risk Information

Risk Factor: Medium

CVSS v3.0 Base Score: 6.5

CVSS v3.0 Vector: CVSS:3.0/AV:N/ACH:PR:N/UI:N/S:U/CH:L/L:A:N

CVSS v2.0 Base Score: 6.1

CVSS v2.0 Vector: CVSS2#AV:N/ACH:Au:N/C:C/I:P/A:N

Vulnerability Information

Asset Inventory: True

Reference Information

CWE: 327