## Homework 4

Michael Brodskiy

Professor: D. Wood

October 12, 2023

1. Consider an infinite grounded conducting plane bent at a 90° angle between the yz and xz planes as shown, with a charge placed at x=4a, y=a. Use appropriate image charge(s) to find an expression for the potential V(x,y,z) in the region x>0, y>0. First, we know that the image charges assume the following layout:




Figure 1: The Layout of Image Charges

By the principle of superposition, we know that the voltage at a point will simply be the sum of all voltages. Thus, we can assign each charge, starting with the top left, a distance  $d_1 - d_4$ . We can find the following:

$$d_1 = \sqrt{(x+4a)^2 + (y-a)^2 + z^2} = \sqrt{x^2 + y^2 + z^2 + 17a^2 + 8ax - 2ay}$$

$$d_2 = \sqrt{(x-4a)^2 + (y-a)^2 + z^2} = \sqrt{x^2 + y^2 + z^2 + 17a^2 - 8ax - 2ay}$$

$$d_3 = \sqrt{(x+4a)^2 + (y+a)^2 + z^2} = \sqrt{x^2 + y^2 + z^2 + 17a^2 + 8ax + 2ay}$$

$$d_4 = \sqrt{(x-4a)^2 + (y+a)^2 + z^2} = \sqrt{x^2 + y^2 + z^2 + 17a^2 - 8ax + 2ay}$$

We can then write the voltage as:

$$V = V_1 + V_2 + V_3 + V_4$$
$$= \frac{q}{4\pi\varepsilon_0} \left[ -\frac{1}{d_1} + \frac{1}{d_2} + \frac{1}{d_3} - \frac{1}{d_4} \right]$$

This gives us the final expression:

$$V(x,y,z) = \frac{q}{4\pi\varepsilon_o} \left[ \frac{1}{\sqrt{(x-4a)^2 + (y-a)^2 + z^2}} + \frac{1}{\sqrt{(x+4a)^2 + (y+a)^2 + z^2}} - \frac{1}{\sqrt{(x+4a)^2 + (y-a)^2 + z^2}} - \frac{1}{\sqrt{(x-4a)^2 + (y+a)^2 + z^2}} \right]$$

2. The boundary at x = 0 consists of two metal strips: one, from y = 0 to y = a/2 is held at a constant potential  $+V_0$  and the other, from y = a/2 to y = a is held at a constant potential of  $V_0$ . Solve for the potential V(x, y, z) inside the slot. Feel free to use the relevant results from Example 3.3 or from lecture as a starting point.

We can first write the Laplace equation:

$$\frac{\partial^2 V}{\partial x^2} + \frac{\partial^2 V}{\partial y^2} = 0$$

Given the boundary conditions, we may write:

$$V(x,y) = \sum_{n=1}^{\infty} c_n e^{-\frac{n\pi x}{a}} \sin\left(\frac{n\pi y}{a}\right)$$

We find the value of  $c_n$  by rearranging:

$$c_n = \frac{2}{a} \left[ \int_0^{\frac{a}{2}} V_o \sin\left(\frac{n\pi y}{a}\right) dy - \int_{\frac{a}{2}}^a V_o \sin\left(\frac{n\pi y}{a}\right) dy \right]$$

$$c_n = \frac{2V_o a}{an\pi} \left[ \left( -\cos\left(\frac{n\pi y}{a}\right) \Big|_0^{\frac{a}{2}} \right) + \left( \cos\left(\frac{n\pi y}{a}\right) \Big|_{\frac{a}{2}}^{a} \right) \right]$$
$$c_n = \frac{2V_o}{n\pi} \left[ 1 + \cos(n\pi) - 2\cos\left(\frac{n\pi}{2}\right) \right]$$

From this, we can see that  $c_n = 0$  for any odd values of n. Furthermore, if n is a multiple of 4,  $c_n = 0$  as well. Thus, we can see that  $c_n$  is non-zero only for  $n = 2, 6, 10, \ldots$  for which:

$$c_n = \frac{8V_o}{n\pi}$$

We can now substitute into our previous equation to obtain:

$$V(x,y) = \frac{8V_o}{\pi} \sum_{n=1}^{\infty} \frac{e^{-\frac{n\pi x}{a}\sin(\frac{n\pi y}{a})}}{n}$$

3. Consider a long (semi-infinite) rectangular conducting pipe oriented  $V_0$  parallel to the z-axis, with dimensions  $a \times b$  in the xy-plane. The pipe itself is grounded, and the rectangle at the closed end is at a constant potential  $V_0$ . Find an expression for the potential everywhere inside the pipe (for z > 0).

For this problem, we must apply a three dimensional Laplace equation, with boundary conditions:

$$\frac{\partial^2 V}{\partial x^2} + \frac{\partial^2 V}{\partial y^2} + \frac{\partial^2 V}{\partial z^2} = 0 \Rightarrow \begin{cases} V = 0, & \begin{cases} x = 0 \\ x = a \\ y = 0 \\ y = b \end{cases} \\ V = V_o, & z = 0 \\ V \to 0, & z \to \infty \end{cases}$$

We can then divide the equation by V(x, y, z) to obtain:

$$\underbrace{\frac{1}{V_x} \frac{\partial^2 V_x}{\partial x^2}}_{-A^2} + \underbrace{\frac{1}{V_y} \frac{\partial^2 V_y}{\partial y^2}}_{-B^2} + \underbrace{\frac{1}{V_z} \frac{\partial^2 V_z}{\partial z^2}}_{C^2} = 0$$

Note: the  $z^2$  term will be positive to guarantee at least one exponentially decaying solution. This gives us:

$$C^2 = A^2 + B^2$$
 
$$\frac{\partial^2 V_x}{\partial x^2} = -A^2 V_x \qquad \frac{\partial^2 V_y}{\partial y^2} = -B^2 V_y \qquad \frac{\partial^2 V_z}{\partial z^2} = (A^2 + B^2) V_z$$

Given this form, we know the solutions will be of form:

$$V_x = P\sin(Ax) + Q\cos(Ax)$$
$$V_y = R\sin(Bx) + S\cos(Bx)$$
$$V_z = Te^{\sqrt{A^2 + B^2}z} + Ue^{-\sqrt{A^2 + B^2}z}$$

To simplify, we can now apply some of our boundary conditions from above. Let us first apply the last condition  $(V_z \to 0 \text{ as } z \to \infty)$ . This gives us S = 0:

$$V_x = P\sin(Ax) + Q\cos(Ax)$$
$$V_y = R\sin(Bx) + S\cos(Bx)$$
$$V_z = Ue^{-\sqrt{A^2 + B^2}z}$$

Now, by conditions one and three, we know that, when V = 0, x = 0 and y = 0, giving Q = 0 and T = 0:

$$V_x = P \sin(Ax)$$
$$V_y = R \sin(Bx)$$
$$V_z = Ue^{-\sqrt{A^2 + B^2}z}$$

From conditions two and four, we know that, when V = 0, x = a and y = b, which gives us:

$$V_x = P \sin\left(\frac{m\pi x}{a}\right)$$

$$V_y = R \sin\left(\frac{n\pi y}{b}\right)$$

$$V_z = Ue^{-\pi\sqrt{\frac{m^2}{a^2} + \frac{n^2}{b^2}}z}$$

Thus, we get V(x, y, z):

$$V(x,y,z) = PRU \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right) e^{-\pi\sqrt{\frac{m^2}{a^2} + \frac{n^2}{b^2}}z}$$

We can assume PRU is some constant, which will be expressed as M:

$$V(x,y,z) = M \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right) e^{-\pi\sqrt{\frac{m^2}{a^2} + \frac{n^2}{b^2}}z}$$

We can find all values of M by summing and replacing M with  $M_{mn}$ :

$$V(x,y,z) = \sum_{m=1}^{\infty} \sum_{n=1}^{\infty} M_{mn} \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right) e^{-\pi\sqrt{\frac{m^2}{a^2} + \frac{n^2}{b^2}}z}$$

Applying the final boundary condition, or  $V = V_o$  when z = 0, we can obtain:

$$V_o = \sum_{m=1}^{\infty} \sum_{n=1}^{\infty} M_{mn} \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right)$$

Now, we multiply both sides by  $\sin\left(\frac{m'\pi x}{a}\right)$  and  $\sin\left(\frac{n'\pi y}{b}\right)$  and integrate to get:

$$\sum_{m=1}^{\infty} \sum_{n=1}^{\infty} M_{mn} \int_{0}^{a} \int_{0}^{b} \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right) \sin\left(\frac{m'\pi x}{a}\right) \sin\left(\frac{n'\pi y}{b}\right) dx dy$$
$$= \int_{0}^{a} \int_{0}^{b} V_{o} \sin\left(\frac{m'\pi x}{a}\right) \sin\left(\frac{n'\pi y}{b}\right) dx dy$$

Then we get:

$$M_{mn} \frac{a}{2} \delta_{mm'} \frac{b}{2} \delta_{nn'} = \int_0^a \int_0^b V_o \sin\left(\frac{m'\pi x}{a}\right) \sin\left(\frac{n'\pi y}{b}\right) dx dy$$
$$M_{m'n'} = \frac{4}{ab} \int_0^a \int_0^b V_o \sin\left(\frac{m'\pi x}{a}\right) \sin\left(\frac{n'\pi y}{b}\right) dx dy$$

We can replace all of the m' and n' by m and n again, since we effectively removed all of the m and n's from the equation:

$$M_{mn} = \frac{4V_o}{ab} \int_0^a \int_0^b \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right) dx dy$$

Analyzing the equations, we can see that, when m or n is odd,  $M_{mn} = 0$ , and, if m and n are both even, then:

$$M_{mn} = \frac{16V_o}{\pi^2 mn}$$

Thus, the final solution, for z > 0, becomes:

$$V(x, y, z) = \frac{16V_o}{\pi^2} \sum_{m, n=1,3,5,\dots}^{\infty} \frac{1}{mn} \sin\left(\frac{m\pi x}{a}\right) \sin\left(\frac{n\pi y}{b}\right) e^{-\pi\sqrt{\frac{m^2}{a^2} + \frac{n^2}{b^2}}z}$$

4. Consider an empty spherical shell of charge of radius R where the potential on the surface is given by  $V(R, \theta) = V_o \sin^2(\theta)$ .

Hint: Express  $\sin^2(\theta)$  as a polynomial function of  $\cos(\theta)$ .

(a) Find  $V(r, \theta)$  inside the shell.

The potential inside and outside can be expressed as:

$$\sum_{l=0}^{\infty} a_l r^l P_l(\cos(\theta)) \qquad r < R$$

$$\sum_{l=0}^{\infty} \frac{b_l}{r^{l+1}} P_l(\cos(\theta)) \qquad r \ge R$$

Given that  $V_0 \sin^2(\theta) \to [1 - \cos^2(\theta)]$ , we can use Legendre polynomials:

$$V(R,\theta) = V_o \left( P_0(\cos(\theta)) - \frac{2P_2(\cos(\theta)) + P_0(\cos(\theta))}{3} \right)$$
$$= \frac{2V_o}{3} \left( P_0(\cos(\theta)) - P_2(\cos(\theta)) \right)$$

Written in polynomial expansion form, we find:

$$a_0 R^0 P_0(\cos(\theta)) + a_2 R^2 P_2(\cos(\theta)) = \frac{2V_0}{3} \left( P_0(\cos(\theta)) - P_2(\cos(\theta)) \right)$$

Thus, we see:

$$a_0 = \frac{2V_0}{3} \qquad a_2 = -\frac{2V_0}{3R^2}$$

Finally, we find that the potential within the shell is:

$$V(r,\theta) = \frac{2V_0}{3} - \frac{V_0 r^2}{3R^2} [3\cos^2(\theta) - 1]$$

(b) Find  $\vec{E}(R,\theta)$  just inside the shell.

To find the electric field, we can apply:

$$\vec{E} = -\vec{\nabla}V$$

This becomes:

$$\vec{\nabla} \left[ \frac{2V_0}{3} - \frac{V_0 r^2}{3R^2} [3\cos^2(\theta) - 1] \right] = -\frac{\partial V}{\partial r} \hat{\mathbf{r}} - \frac{1}{r} \frac{\partial V}{\partial \theta} \hat{\boldsymbol{\theta}}$$
$$-\frac{\partial}{\partial r} \left[ \frac{2V_0}{3} - \frac{V_0 r^2}{3R^2} [3\cos^2(\theta) - 1] \right] \hat{\mathbf{r}} - \frac{1}{r} \frac{\partial}{\partial \theta} \left[ \frac{2V_0}{3} - \frac{V_0 r^2}{3R^2} [3\cos^2(\theta) - 1] \right] \hat{\boldsymbol{\theta}}$$

Finally, we get:

$$\vec{E}(R,\theta) = \frac{2V_0 r}{3R^2} [3\cos^2(\theta) - 1]\hat{\mathbf{r}} - \frac{V_0 r}{R^2} \sin(2\theta)\hat{\theta}$$

(c) Find  $V(r, \theta)$  out of the shell. Using a similar process to (a), we find:

$$\frac{b_0}{R} P_0(\cos(\theta)) + \frac{b_2}{R^3} P_2(\cos(\theta)) = \frac{2V_0}{3} \left( P_0(\cos(\theta)) - P_2(\cos(\theta)) \right)$$

This gives us:

$$b_0 = \frac{2V_0R}{3} \qquad b_2 = -\frac{2V_0R^3}{3}$$

And finally, we end up with:

$$V(r,\theta) = \frac{2V_0R}{3r} - \frac{V_0R^3}{3r^3} [3\cos^2(\theta) - 1]$$

(d) Find  $\vec{E}(R,\theta)$  just outside the shell. Similarly to (b), we can find the electric field outside the shell using:

$$\vec{E} = -\vec{\nabla}V$$

This gives us:

$$-\vec{\nabla} \left[ \frac{2V_0R}{3r} - \frac{V_0R^3}{3r^3} [3\cos^2(\theta) - 1] \right]$$
$$-\frac{\partial}{\partial r} \left[ \frac{2V_0R}{3r} - \frac{V_0R^3}{3r^3} [3\cos^2(\theta) - 1] \right] \hat{\mathbf{r}} - \frac{1}{r} \frac{\partial}{\partial \theta} \left[ \frac{2V_0R}{3r} - \frac{V_0R^3}{3r^3} [3\cos^2(\theta) - 1] \right] \hat{\theta}$$

Finally, we obtain:

$$\vec{E}(R,\theta) = \left(\frac{2V_0R}{3r^2} - \frac{V_0R^3}{r^4} [3\cos^2(\theta) - 1]\right) \hat{\mathbf{r}} - \frac{V_0R^3}{r^4} \sin(2\theta)\hat{\theta}$$

(e) Find  $\sigma(R,\theta)$  on the shell. [answer:  $\sigma = \frac{V_o \varepsilon_o}{3R} (7 - 15 \cos^2(\theta))$ ] At the surface, we can assume that r = R, and use the following formula:

$$\frac{\sigma}{\varepsilon_o} = (E_{r,out} - E_{r,in})$$

This gives us:

$$\sigma = \frac{V_0 \varepsilon_o}{R} \left( \left[ \frac{2}{3} - 3\cos^2(\theta) + 1 \right] - \left[ 2\cos^2(\theta) - \frac{2}{3} \right] \right)$$
$$\sigma = \frac{V_0 \varepsilon_o}{R} \left( \frac{7}{3} - 5\cos^2(\theta) \right)$$

By factoring the one-third, we can finally obtain:

$$\sigma = \frac{V_0 \varepsilon_o}{3R} \left( 7 - 15 \cos^2(\theta) \right)$$

- 5. An empty spherical shell of radius R has potential  $V_0$  on the upper hemisphere and  $V_0$  on the lower hemisphere
  - (a) Calculate the first two non-zero terms of the expression for the potential outside of the sphere to obtain an approximate expression for  $V(r, \theta)$  in this region. First and foremost, we know the expression for the voltage outside may be written as:

$$\sum_{l=0}^{\infty} \frac{B_l}{r^{l+1}} P_l(\cos(\theta))$$

The constant,  $B_l$ , may be calculated using:

$$B_{l} = \frac{(2l+1)}{2} R^{l+1} V_{0} \left[ \int_{0}^{\frac{\pi}{2}} P_{l}(\cos(\theta)) \sin(\theta) d\theta - \int_{\frac{\pi}{2}}^{\pi} P_{l}(\cos(\theta)) \sin(\theta) d\theta \right]$$

For l = 0, we get:

$$B_0 = \frac{V_0 R}{2} [0] = 0$$

For l=1, we get:

$$B_{1} = \frac{3V_{0}R^{2}}{2} \left[ \int_{0}^{\frac{\pi}{2}} \frac{\sin(2\theta)}{2} d\theta - \int_{\frac{\pi}{2}}^{\pi} \frac{\sin(2\theta)}{2} d\theta \right]$$
$$B_{1} = \frac{3V_{0}R^{2}}{2}$$

For l=2, we get:

$$B_2 = \frac{5V_0 R^3}{2} \left[ \int_0^{\pi} \frac{3\cos^2(\theta)\sin(\theta) - \sin(\theta)}{2} d\theta \right] = 0$$

For l=3, we get:

$$B_3 = \frac{7V_0 R^4}{2} \left[ \int_0^{\pi} \frac{5 \cos^3(\theta) \sin(\theta) - 3 \cos(\theta) \sin(\theta)}{2} d\theta \right] = -\frac{7V_0 R^4}{8}$$

We now plug these coefficients into the sum to get:

$$V(r,\theta) = \frac{3V_0 R^2}{2r^2} \cos(\theta) - \frac{7V_0 R^4}{16r^4} \left(5\cos^3(\theta) - 3\cos(\theta)\right)$$

(b) From this approximate expression, compute the value of  $V(R, \theta)$  (on the surface of the shell) for  $\theta = 0, \theta = \pi/4$ , and  $\theta = 3\pi/4$  compare the results with the exact values at those locations

First and foremost, we know r = R, which gives us:

$$V(R, \theta) = \frac{3}{2} V_0 \cos(\theta) - \frac{7}{16} V_0 \left( 5 \cos^3(\theta) - 3 \cos(\theta) \right)$$

We can then check:

• At  $\theta = 0$ :

$$V(R,0) = \frac{3}{2}V_0 - \frac{7}{16}V_0(2)$$
$$V(R,0) = \frac{5}{8}V_0$$

• At  $\theta = \frac{\pi}{4}$ :

$$V\left(R, \frac{\pi}{4}\right) = \frac{3\sqrt{2}}{4}V_0 - \frac{7}{16}V_0\left(\frac{5(2)^{\frac{3}{2}}}{8} - \frac{3\sqrt{2}}{2}\right)$$

$$= \frac{3\sqrt{2}}{4}V_0 - \frac{7}{16}V_0\left(\frac{5\sqrt{2}}{4} - \frac{3\sqrt{2}}{2}\right)$$

$$= \frac{3\sqrt{2}}{4}V_0 + \frac{7\sqrt{2}}{64}V_0$$

$$V\left(R, \frac{\pi}{4}\right) = \frac{55\sqrt{2}}{64}V_0$$

• At  $\theta = \frac{3\pi}{4}$ 

$$V\left(R, \frac{3\pi}{4}\right) = -\frac{3\sqrt{2}}{4}V_0 - \frac{7}{16}V_0\left(-\frac{5(2)^{\frac{3}{2}}}{8} + \frac{3\sqrt{2}}{2}\right)$$

$$= -\frac{3\sqrt{2}}{4}V_0 - \frac{7}{16}V_0\left(-\frac{5\sqrt{2}}{4} + \frac{3\sqrt{2}}{2}\right)$$

$$= -\frac{3\sqrt{2}}{4}V_0 - \frac{7\sqrt{2}}{64}V_0$$

$$V\left(R, \frac{3\pi}{4}\right) = -\frac{55\sqrt{2}}{64}V_0$$