Memory-Mapped I/O and Object-Oriented Programming
Embedded Design: Enabling Robotics
EECE2160

Michael Brodskiy
Brodskiy.M@Northeastern.edu

April 6, 2023

Date Performed:	March 30, 2023
Partner:	Dylan Powers
Instructor:	Professor Shazli

Abstract

This laboratory experiment, intended to introduce memory mapping and object-oriented programming concepts in C++, involved reading and writing to the DE1-SoC FPGA board. Starting with some pre-made register read and write code, conversions between binary and decimal number systems were used to infer the status of switches, LEDs, and push-buttons on the board. Functions were then written to interface with the board; these functions were then converted to an object-oriented program, with two classes: `DE1SoCfpga` and `LEDControl`.

KEYWORDS: memory mapping, object-oriented, read and write, DE1-SoC, binary, decimal, function, class

1 Equipment

Available equipment included:

- DE1-SoC board
- DE1-SoC Power Cable
- USB-A to USB-B Cable
- Computer
- MobaXTerm SSH Terminal
- USB-to-ethernet Adapter

2 Introduction

Memory-mapping is a technique that accesses the virtual file representing I/O devices and maps a set of control flags into memory locations which enables a user to modify or read the state of the device. In Lab 8, the goal was to introduce the concept of memory-mapped I/O to access devices available on the DE1-SoC, including the LEDs, the switches, and the push buttons. To accomplish this, the `/dev/mem` file was the accessed file that was used to map physical addresses to virtual addresses. Then with the mapped relations between the physical and virtual addresses, programs were written to control the LEDs, switches, and push buttons using pointers.

3 Discussion & Analysis

3.1 Pre-lab

Existing Functions:

a. `char *Initialize(int *fd)`

   First and foremost, `Initialize()` points the `fd` pointer at the location of a physical device in memory, and gives it read, write, and synchronization access. Next, an `if` statement checks for the possibility of errors; that is, if the pointer `fd` is equal to -1, then an error is printed, and the program exits with exit code 1 (error). The physical device is then mapped to a virtual device, and given a virtual memory address, using the `mmap()` function. Another `if` statement then checks whether the memory mapping was successful or not; if yes, the virtual memory location of the device is returned. Otherwise, an error is printed, the `fd` pointer connection to memory is closed, and exit code 1 is returned.

b. `void Finalize(char *pBase, int fd)`

   The `Finalize()` function checks whether the device attached to the memory address pointer `pBase` is successfully unmapped from memory. If successful,

it closes the connection to the device using address `fd`. Otherwise, an error is printed, and exit code 1 is returned.

c. `int RegisterRead(char *pBase, unsigned int reg_offset)`

   By combining the base address pointer `pBase` and the device mapping offset value (`reg_offset`), the value that is read from the device at the memory address `pBase` is returned by `RegisterRead()`.

d. `void RegisterWrite(char *pBase, unsigned int reg_offset, int value)`

   Similar to `RegisterRead()`, `RegisterWrite` combines the base address pointer `pBase` and the device mapping offset, `reg_offset`, to find the device, and then assigns a specified value to that address.

Writing a switch read function:

Listing 1: Switch Reading Code

```
/**Reads the value of a switch
 * -Uses base address of I/O
 * @param pBaseBase address returned by'mmap'
 * @param switchNumSwitch number (0 to 9)
 * @returnSwitch value read
 */
int Read1Switch(char *pBase, int switchNum) {

    // Read the switch register
    int switchRegisterValue = RegisterRead(pBase, SW_BASE);

    // Mask the value to extract the specified switch bit
    int switchBitMask = 1 << switchNum;

    // if the result is non-zero, then the switch is on,
        off otherwise
    int switchValue;
    //use the bitwise AND operator and compare result
        against the bit mask
    if (switchRegisterValue & switchBitMask) {
        switchValue = 1;
    } else {
        switchValue = 0;
    }

    return switchValue;

}
```

Writing a switch write function:

Listing 2: Switch Writing Code

```
/** Changes the state of an LED (ON or OFF)
 *  @param pBase Base address returned by 'mmap'
 *  @param ledNum LED number (0 to 9)
 *  @param state State to change to (ON or OFF)
 */
void Write1Led(char *pBase,int ledNum, int state) {

    if (ledNum < 0 || ledNum > 9) {
        cout << "ERROR: Invalid LED number. Only LED
            numbers 0 to 9 are valid." << endl;
        return;

    }

    // Read the LED redister
    int ledRegisterValue = RegisterRead(pBase, LEDR_BASE);

    // Set the state of the specified LED based on the
        state parameter
    if (state == 1) {
        ledRegisterValue = (1 << ledNum);
    } else {
        ledRegisterValue &= ~(1 << ledNum);
    }

    // Write the new LED register value
    RegisterWrite(pBase, LEDR_BASE, ledRegisterValue);

    // Read the LED register again and print out the value
        to double check (this can be commented out)
    int UpdatedRegisterValue = RegisterRead(pBase,
        LEDR_BASE);
    cout << "LED Register Updated Value: " <<
        UpdatedRegisterValue << endl << endl;

}
```

3.2 Assignment 1

3.3 Assignment 2

3.4 Assignment 3

3.5 Assignment 4

3.6 Assignment 5

4 Conclusion

Overall, this lab was an effective introduction to the concept of C++ object-oriented programming. By first having the user create functions to interface with the board, and then having the user create a class, it was easier to grasp the idea of a class. The conversion of the program from procedural to object-oriented was, in this manner, facilitated.

5 Appendix

Listing 3: Object-Oriented Source Code

```
/*
 * =====================================================================
 *
 *       Filename:  PushButtonClass.cpp
 *
 *    Description:  Interfaces with switches and push-buttons on the De1-SoC board using
 *                  class De1-SoC
 *
 *        Version:  1.0
 *        Created:  03/30/2023
 *       Revision:  none
 *       Compiler:  GCC
 *
 *         Authors:  Michael Brodskiy (Brodskiy.M@Northeastern.edu)
 *                   Dylan Powers (Powers.D@Northeastern.edu)
 *
 * =====================================================================
 */

#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>
```

```
23 #include <fcntl.h>
24 #include <sys/mman.h>
25 #include <iostream>
26 #include <cmath>
27 #include <unistd.h>
28
29 using namespace std;
30
31 class DE1SoCfpga {
32
33 private:
34
35     char *pBase;
36     int fd;
37
38 public:
39
40
41     /**
42     * Initialize general-purpose I/O
43     * - Opens access to physical memory /dev/mem
44     * - Maps memory into virtual address space
45     *
46     * @return Address to virtual memory which is mapped to
          physical,
47     * or MAP_FAILED on error.
48     */
49     DE1SoCfpga() {
50
51         // Open /dev/mem to give access to physical
              addresses
52         fd = open( "/dev/mem", (O_RDWR | O_SYNC));
53         if (fd == -1) // check for errors in openning /dev/
              mem
54         {
55             cout << "ERROR: could not open /dev/mem..." <<
                  endl;
56             exit(1);
57         }
58         // Get a mapping from physical addresses to virtual
              addresses
59         char *virtual_base = (char *)mmap (NULL,
              LW_BRIDGE_SPAN, (PROT_READ | PROT_WRITE),
              MAP_SHARED, fd, LW_BRIDGE_BASE);
60         if (virtual_base == MAP_FAILED) // check for errors
61         {
```

```
62              cout << "ERROR: mmap() failed..." << endl;
63              close (fd); // close memory before exiting
64              exit(1); // Returns 1 to the operating system;
65          }
66          pBase = virtual_base;
67
68      }
69
70
71      /**
72      * Close general-purpose I/O.
73      *
74      * @param pBase Virtual address where I/O was mapped.
75      * @param fd File descriptor previously returned by '
            open'.
76      */
77      ~DE1SoCfpga() {
78
79          if (munmap (pBase, LW_BRIDGE_SPAN) != 0) {
80
81              cout << "ERROR: munmap() failed..." << endl;
82              exit(1);
83
84          }
85
86          close (fd); // close memory
87
88      }
89
90      /**
91      * Write a 4-byte value at the specified general-purpose
            I/O location.
92      *
93      * @parem offset Offset where device is mapped.
94      * @param value Value to be written.
95      */
96      void RegisterWrite(unsigned int offset, int value) {
97
98          * (volatile unsigned int *)(pBase + offset) = value
                ;
99
100     }
101
102     /**
103     * Read a 4-byte value from the specified general-
            purpose I/O location.
```

```
104     *
105     * @param offset Offset where device is mapped.
106     * @return Value read.
107     */
108     int RegisterRead(unsigned int offset) {
109 
110         return * (volatile unsigned int *)(pBase + offset);
111 
112     }
113 
114 };
115 
116 class LEDControl {
117 
118 private:
119 
120     DE1SoCfpga *board; // Declare a DE1SoCfpga class
121     bool prevVal[4]; // Store previous button values
        globally
122     bool butValue[4]; // Store current button values
        globally
123 
124     // Physical base address of FPGA Devices
125     const unsigned int LW_BRIDGE_BASE = 0xFF200000; // Base
         offset
126 
127     // Length of memory-mapped IO window
128     const unsigned int LW_BRIDGE_SPAN = 0x00005000; //
        Address map size
129 
130     // Cyclone V FPGA device addresses
131     const unsigned int LEDR_BASE = 0x00000000; // Leds
        offset
132     const unsigned int SW_BASE = 0x00000040; // Switches
        offset
133     const unsigned int KEY_BASE = 0x00000050; // Push
        buttons offset
134 
135 public:
136 
137     // Initialize the LEDControl class
138     LEDControl() {
139 
140         board = new DE1SoCfpga();
141         for (int i = 0; i < 4; i++) {
142 
```

```
143             prevVal[i] = false;
144             butValue[i] = false;
145 
146         }
147 
148     }
149 
150     // Destroy the board and LEDControl objects
151     ~LEDControl() {
152 
153         delete board;
154 
155     }
156 
157     /**Reads the value of a switch
158     * -Uses base address of I/O
159     * @param switchNum Switch number (0 to 9)
160     * @return Switch value read
161     */
162     int Read1Switch(int switchNum) {
163 
164         // Read the switch register
165         int switchRegisterValue = board->RegisterRead(
                SW_BASE);
166 
167         // Mask the value to extract the specified switch
                bit
168         int switchBitMask = 1 << switchNum;
169 
170         // if the result is non-zero, then the switch is on
                , off otherwise
171         int switchValue;
172         //use the bitwise AND operator and compare result
                against the bit mask
173         if (switchRegisterValue & switchBitMask) {
174             switchValue = 1;
175         } else {
176             switchValue = 0;
177         }
178 
179         return switchValue;
180 
181     }
182 
183     /** Changes the state of an LED (ON or OFF)
184     *  @param ledNum LED number (0 to 9)
```

```
185     *  @param state State to change to (ON or OFF)
186     */
187     void Write1Led(int ledNum, int state) {
188 
189         if (ledNum < 0 || ledNum > 9) {
190             cout << "ERROR: Invalid LED number. Only LED
                    numbers 0 to 9 are valid." << endl;
191             return;
192 
193         }
194 
195         // Read the LED register
196         int ledRegisterValue = board->RegisterRead(
                LEDR_BASE);
197 
198         // Set the state of the specified LED based on the
                state parameter
199         if (state == 1) {
200             ledRegisterValue = (1 << ledNum);
201         } else {
202             ledRegisterValue &= ~(1 << ledNum);
203         }
204 
205         // Write the new LED register value
206         board->RegisterWrite(LEDR_BASE, ledRegisterValue);
207 
208         // Read the LED register again and print out the
                value to double check (this can be commented out
                )
209         int UpdatedRegisterValue = board->RegisterRead(
                LEDR_BASE);
210         cout << "LED Register Updated Value: " <<
                UpdatedRegisterValue << endl << endl;
211 
212     }
213 
214     /** Reads all the switches and returns their value in a
             single integer
215     * @return   A value that represents the value of the
            switches
216     */
217     int ReadAllSwitches() {
218 
219         return board->RegisterRead(SW_BASE);
220 
221     }
```

```
222
223     /** Set the state of the LEDs with the given value
224     * @param value      Value between 0 and 1023 written to
            the LEDs
225     */
226     void WriteAllLeds(int value) {
227
228         board->RegisterWrite(LEDR_BASE, value);
229
230     }
231
232     int PushButtonGet() {
233
234         // Read the switch register
235         int butRegisterValue = board->RegisterRead(KEY_BASE
                );
236
237         // Mask the value to extract the specified switch
                bit
238         int butBitMask[4];
239         for (int i = 0; i < 4; i++) {
240
241             butBitMask[i] = 1 << i;
242
243         }
244
245         // if the result is non-zero, then the switch is on
                , off otherwise
246         //use the bitwise AND operator and compare result
                against the bit mask
247         for (int i = 0; i < 4; i++) {
248
249             if (butRegisterValue & butBitMask[i]) {
250
251                 butValue[i] = true;
252                 if (butValue[i] != prevVal[i]) { prevVal[i]
                        = !prevVal[i]; }
253
254             } else {
255
256                 butValue[i] = false;
257                 if (butValue[i] != prevVal[i]) { prevVal[i]
                        = !prevVal[i]; }
258
259             }
260         }
```

```
261
262         int quantDiff = 0;
263         bool diff[] = {false, false, false, false};
264
265         for (int i = 0; i < 4; i++) {
266
267                 if (butValue[i] && prevVal[i]) {
268
269                     diff[i] = true;
270                     quantDiff++;
271
272                 }
273
274         }
275
276         if (quantDiff == 2) return 4;
277         else if (quantDiff == 0) return -1;
278         else {
279
280                 for (int i = 0; i < 4; i ++) {
281
282                     if (diff[i]) return i;
283
284                 }
285
286         }
287
288     }
289
290 };
291
292 int main() {
293
294     int ledDisp = 0;
295     LEDControl *control = new LEDControl();
296     // ************** Put your code here
        ***********************
297     while(true) {
298
299             usleep(225000);
300             int change = control->PushButtonGet();
301             if (change == 0) {
302
303                 ledDisp++;
304                 control->WriteAllLeds(ledDisp);
305                 if (ledDisp > 1023) ledDisp = 0;
```

```
306
307             } else if (change == 1) {
308
309                 ledDisp -= 1;
310                 control->WriteAllLeds(ledDisp);
311                 if (ledDisp < 0) ledDisp = 1023;
312
313             } else if (change == 2) {
314
315                 ledDisp *= 2;
316                 if (ledDisp > 1023) ledDisp -= 1024;
317                 control->WriteAllLeds(ledDisp);
318
319             } else if (change == 3) {
320
321                 ledDisp /= 2;
322                 control->WriteAllLeds(ledDisp);
323
324             } else if (change == 4) {
325
326                 control->WriteAllLeds(control->
                        ReadAllSwitches());
327                 ledDisp = control->ReadAllSwitches();
328
329             }
330
331     }
332     // Done
333     delete control;
334
335 }
```