Lecture 5 — Linear Time Invariant Systems

Michael Brodskiy

Professor: I. Salama

September 25, 2024

- The Impulse Response

  - Linear algebra concepts apply to LTI system analysis; if the response to basis input signals are known, any general input can be expressed as a linear combination of these basis signals, allowing the output to be determined

  - The system is fully characterized by its responses to the basis signals

  - In the time domain representation, we use delayed unit impulse functions as basis signals

  - The impulse response, $h(t)/h[n]$, of a linear time invariant system is defined as the response of the system to a unit impulse input, $x(t) = \delta(t)/x[n] = \delta[n]$

  - The response of a linear time invariant system with impulse response $h[n]$ to a general input $x[n]$ can be obtained using the convolution sum; the convolution sum sifts through the sequence values, $x[k]$. respresented by an impulse located at $n = k$, and finds the corresponding response given by $h[n - k]$

$$x[n] = \sum_{k=-\infty}^{\infty} x[k]\delta[n - k] \Longrightarrow y[n] = \sum_{k=-\infty}^{\infty} x[k]h[n - k]$$

- The Convolution Sum

  - The convolution sum may also be expressed as:

$$y[n] = x[n] * h[n] = h[n] * x[n] = \sum_{k=-\infty}^{\infty} x[n - k]h[k]$$