

The three-pocket Balius case fits at 1.25 mm stand-off

Balius native case at 1.25 mm tab-to-board spacing




The dense PLA shell adds 73.7 g to the 251.8 g bare board. The middle-cell clearance is 0.003 mm and the closest washer clears by 0.328 mm. In the local pull model the left cell first reaches its pocket at about **1.14 N toward the middle cell** (0.020 mm) or **6.7 N away** (0.165 mm). The forces come from the bare strips up to contact.

The snug case increases board travel in the seeded clips




During the displayed base-Z interval, PCB travel normal to the board reached **0.168 mm bare**, **0.390 mm with nylon screws** and **0.248 mm with aluminium**. All 22 paired movie subjects are available.

Balanced nylon pocket force agrees across two meshes




With the 0.01 N force criterion, the 2 and 1.5 mm nylon meshes give **0.5684 and 0.5716 N** at lock, a **0.55% difference**. All saved mounting-force balances pass. Local peak pressure still changes by **18.4%**. Across the tested meshes, peak PCB deflection falls about **39% with nylon** and **51% with aluminium** relative to bare.

The local fixture and the complete board respond differently




At **8.54 N**, the left cell moved **4.824 μm bare**, **4.816 μm with nylon screws** and **4.812 μm with aluminium screws**. It cleared both cases. In the local fixture the cell reached the nylon-mounted case, reducing travel from 0.500 mm bare to about 0.034 mm.

Aluminium cuts board travel relative to nylon but raises base-Z stress




Under base Z, peak PCB stress was **32.5 MPa RMS bare**. Refining the case gave **69.8 MPa with nylon** and **94.3 with aluminium**. Filled markers are native spectra. Open markers integrate the finer native modes independently. All retain the installed contact state.

Board-normal vibration loads the middle cell's nickel bond




The largest base-Z bond load rose from **30.2 N bare** to **40.1 N with nylon** and **50.5 N with aluminium**. The finer meshes gave **48.8 and 53.3 N**. All cased base-Z peaks occur at the middle cell. Bars use native histories. Diamonds integrate the finer native modes independently.

The middle pocket unloads and carries force again




Under base Z, the first interval with all original pocket points unloaded began at **5.61 ms with aluminium** and **11.54 ms with nylon** (11.64 ms on finer nylon). At 28.79 ms the middle cell cleared the case by **3.90–4.01 μm with nylon** and **1.73–1.84 μm with aluminium** on the nominal meshes. New contacts could change this motion.

PLA demand exceeds its coupon reference with aluminium screws




Refinement shifted the largest through-layer demand to **71.5% of the coupon mean with nylon** and **210.8% with aluminium**, both under base X. Horizontal marks exclude the 2 mm bearing band. Fine screw peaks were **37.4 and 96.2 MPa**; two integration methods agreed within 0.302%. These elastic histories retain the installed contact state.

Under base X, the left and middle cells move closer together



The left cell's peak travel relative to its clamps fell by **29% with nylon** and **12% with aluminium**. Rotation accounted for **82%** of that travel in all three assemblies. With the middle cell free to move, peak approach rose from **19 μm bare** to **85 and 71 μm**. Contact stays fixed at bolt lock in these native histories.

M4 tension raises the vibration level for a pocket contact change



With **1 N mean M4 tension**, a new pocket point touched at about **0.0085** g **RMS with nylon** and **0.0068** g **with aluminium** on the 2 mm mesh. On finer nylon, a point that opened during tightening seated again at **0.0011** g. These are modeled contact changes under the board-normal waveform. Actual screw tension is unmeasured.