
# The outer washers meet the case before the cells




Plan view through the cover. Red marks the first four loaded washers.

**Lowering the case from 3 mm**

The four outer washers touch after 0.603 mm of travel. The rigid tabs are still 2.397 mm from the PCB. The first cell touches after 1.760 mm.

**Flush installation**

At 0.80 mm travel, the four screw drives carried **80 N with nylon** and **116 N with aluminium**. Both models exceeded the PLA tensile reference before seating. Only 4–5% of each nylon-mounted tab was within 0.05 mm of the PCB at 2.75 mm travel. With aluminium, 18–19% was that close at the full 3 mm travel.

# The hole pattern leaves little room for an M4 screw

| | PCB | Case |
|---|---|---|
| Bore diameter [mm] | 4.200 | 5.000–5.090 |
| Hole pitch X [mm] | 62.865 | 62.855 |
| Hole pitch Y [mm] | 114.427 | 113.241 |


Each end of the centred pattern is about 0.593 mm off-axis. The smaller bore pair allows 0.600 mm with a nominal M4 shank.

**Hardware under study**

Four M4 case screws in aluminium or nylon. The nylon reference is McMaster-Carr 93640A145.

The dense PLA case adds about 74 g to a 252 g bare assembly. Print orientation and infill affect its installed stiffness and mass.


# The raised nylon case lowers vibration stress in all six nickel strips




With base X excitation, the highest strip stress was **291.9 MPa RMS** bare, **256.2** with nylon screws and **286.5** with aluminium. All three maxima occurred at the same corner of the right-hand cell attachment.

In the seeded history, all three elastic models crossed the local pull study's assumed 185 MPa yield stress within 39 ms. Both raised cases still had clearance at the cells. In the nine-second base-Z record, peak force at one cell end rose from 30.2 N bare to 32.2 N with nylon and 33.3 N with aluminium in the linear model.

# Both raised cases limit cell travel under the same pull





At **8.54 N**, the bilinear nickel model gave 0.50 mm travel bare and about 0.20 mm with either raised case. The multilinear nickel model gave 0.203 mm bare.

At the same **0.421 mm travel**, the required pull was 8.26 N bare, 101.0 N with nylon screws and 210.0 N with aluminium. The aluminium case crossed the first printed-PLA tensile reference in the next increment.

Positive X pull at 3 mm stand-off. Fixed screw tops and rigid tab bearings transmit a couple at every screw.

# Mounting height changes how the screws bend the PCB





The same PCB node moved 47.46 $\mu$m bare, 32.13 $\mu$m with nylon screws and **27.13 $\mu$m** with aluminium screws. The reductions from bare were 32% and 43%, respectively.

With the raised mounts, all cell, strip and washer gaps stayed open. At 0.80 mm of flush screw travel, peak corner movement toward the cells was **0.197 mm with nylon** and **0.216 mm with aluminium**.

Bars show the six original bolts locked after tightening to 750 N each. Both cased bars use 3 mm stand-offs.

# Both raised cases introduce modes below 486 Hz





The first cased mode rises from **253 Hz with nylon** to **320 Hz with aluminium**. Its shape remains closely matched across 399,194 solid nodes (MAC 0.989).

The closest match to bare mode 20 (2364 Hz) is mode 27 in both raised assemblies, at 2365 Hz with nylon and 2368 Hz with aluminium. With the original unpreloaded contacts, mode 1 stayed at 66.61 Hz in all three assemblies.

Bolt-locked flexible assemblies at 3 mm stand-off. Undamped mode shapes about the tightened state.

# Both raised mounts increase board-normal motion under each base input




With base Z excitation, peak PCB stress rose from **32.5 MPa RMS** bare to **64.8** with nylon screws and **84.2** with aluminium. Aluminium reduced board travel relative to nylon in all three tests.

Under base X, peak RMS stress in the PCB fell by less than 2% with either mount. In the nine-second X waveform, tension across the printed layers peaked at 64 MPa with nylon and 110 MPa with aluminium. At each mount's peak, all three cell surfaces intersected the case wall in the linear model. Paired movies.