The snug Balius battery case and the bare power board

Three-cell fit, mounting loads and vibration response

9 November 2026 | Study in progress | SolidWorks native export and ANSYS MAPDL 2026 R1

What fits at 1.25 mm

The three-pocket Balius SolidWorks part follows the spacing of the archived cells and clears all four outer washers at a nominal 1.250 mm gap between the mounting tabs and the underside of the PCB. The middle cell has only 0.003 mm of clearance. Print dimensions, battery sleeves and assembly alignment can therefore determine whether a real cell starts in contact.




Figure 1: The left panel cuts through the battery midspan. Each cell label gives its shortest three-dimensional distance to the case. The right panel cuts through the two closest points on the outer washer and case, using a separate magnified scale.

Assembly quantity	Bare board	Snug Balius geometry
Battery cells / nickel-strip attachments	3 / 6	3 / 6
Original battery-fastener preload	6 × 750 N	6 × 750 N
Added mounting screws	0	4 (nylon or aluminium)
Printed solid volume	0	62.980 cm^3
Mass of board plus printed shell*	251.82 g	325.51 g

*The bare value is the archived model mass. A dense PLA shell at 1.17 g/cm^3 adds 73.69 g, or 29.3%. The estimate excludes the four added screws and spacer material. Actual print mass has not been measured.

Mounting and contact assumptions

The native export has 6.350 mm thick tabs at the four case screw bearings. The nominal distance from the PCB underside to each modeled screw-bearing plane is 7.600 mm. Both variants use the same hole registration and air around the cells. The added screw shanks have nominal M4 geometry. The plastic scenario uses the nylon properties from the original comparison; the metal scenario uses aluminium. The 1.25 mm spacers are represented by the same assumed printed-PLA compression law. The four added screws have no specified installation torque.

Comparison baseline and native rerun

The reference is the same no-case assembly across both screw-material comparisons. It includes the original board, all three batteries, their nickel strips, and the six preloaded fasteners. The global comparison uses the eight original mounting faces, three separate base-excitation axes, the original 20–2000 Hz spectrum and the nine-second seeded acceleration records. The edge-cell fixtures retain the earlier clamp preload, weld idealization, and nickel laws so changes in reaction or strain can be traced to the snug case.

Verified no-case result	Value
Peak PCB displacement during bolt tightening	47.46 μm
First connected prestressed natural frequency	485.96 Hz
Peak PCB Z displacement, base Z	52.67 μm RMS
Peak PCB equivalent stress, base X	90.33 MPa RMS
Bilinear nickel, force at +0.500 / −0.500 mm cell travel	+8.54 / −8.51 N

Static displacement, RMS response and prescribed-travel reactions describe different load cases.

Resolving the initial contact

The nominal 2 mm case mesh has 45,549 quadratic tetrahedra and 77,166 nodes. Its integrated volume differs from CAD by 0.00089%. The 3 and 1.5 mm meshes have 18,051 and 99,818 tetrahedra. All three have positive minimum scaled Jacobians. Both finer meshes cleared all three undeformed cells at both surface sampling levels. The 3 mm mesh showed an apparent middle-cell intersection at the coarser sampling level. At the higher level the middle cell first touched at 1.2412–1.2414 mm stand-off on the 2 mm mesh and 1.2406–1.2408 mm on the 1.5 mm mesh, compared with 1.2396–1.2400 mm in CAD. The native minimum initial gaps on the two finer meshes were 2.969 and 2.984 μm. Page 4 compares their actual loaded responses.

Response quantities

The native comparisons will report mounting reactions, board deformation, cell and washer contact, matched natural modes, signed and RMS vibration quantities, tension along and across the printed layers, and edge-cell force and nickel damage for both pull directions where supported by the fixture. The 22 movie subjects use the bare board as the reference on shared physical or display scales. The following pages identify the native solver results and the independent reconstructions from those results. Appendix A preserves the previous study with its original geometries and page numbering.

Both snug mounts reduce PCB deflection during tightening

We tightened the six original battery fasteners to 750 N each, then locked their adjustments. The largest PCB displacement fell from 47.46 μm bare to 28.91 μm with nylon case screws and 23.09 μm with aluminium, reductions of 39.1% and 51.4%. The bare and nylon peaks occurred at the same board corner. With aluminium, the maximum moved 9.77 mm along the same edge. The comparison used the same 217,704 PCB nodes in all three assemblies.




Figure 2: Left, native displacements after bolt lock. Cell-body peaks were 9.83, 9.80 and 9.81 μm for bare, nylon and aluminium. Right, the maximum recorded case contact pressure at each equilibrium. The dashed line marks the change from prescribed bolt force to locked adjustment.

The middle pocket carries load before vibration begins

All loaded case faces belonged to the cylindrical wall of the middle pocket. The first active state occurred between 0.40 and 0.70 of the tightening step with nylon and between 0.70 and 1.00 with aluminium. Reconstructing the deformed case, three cells and six washers independently at two surface sampling levels also identified contact with the middle cell alone at lock. The closest sampled washer gaps were 0.321 mm with nylon and 0.324 mm with aluminium at the finer level.

Snug case quantity	Nylon screws	Aluminium screws
Active contact faces after bolt lock	5	1
Highest contact pressure during tightening [MPa]	1.080	0.163
Highest contact pressure after lock [MPa]	0.345	0.041
Largest loaded-corner penetration over both steps [μm]	0.222	0.034
Peak PLA tension in-plane / across layers [MPa]	0.334 / 0.344	1.052 / 0.760
Peak screw extreme-fibre tension after lock [MPa]	1.25	2.40

Each model converged at eight saved states. All six locked bolt forces were within 0.015 N of the 750 N target. The highest through-layer PLA tension reached 0.85% of the printed-coupon mean with nylon and 1.88% with aluminium. The contact pressures come from a small patch on the 2 mm case mesh. The mesh check on page 4 quantifies their sensitivity. Vibration and side pull are separate load cases.

Mesh sensitivity of board displacement and pocket pressure

Three nylon-case meshes retained the same bare-board mesh, printed geometry, screw axes, 7.60 mm screw grip and PCB bearing nodes. All eight tightening and locking stations matched. The case mesh changes both the surface triangles and the nodes inside each tab's bearing footprint.

Nylon mount under bolt preload	3 mm	2 mm	1.5 mm
Quadratic case tetrahedra	18,051	45,549	99,818
Case-side bearing nodes per screw	86–89	103–104	106–108
Native minimum initial gap [μm]	2.930	2.969	2.984
Peak PCB displacement at lock [μm]	28.919	28.915	28.970
First saved state carrying contact, step 1	0.70	0.70	0.70
Active case faces at lock	4	5	7
Peak contact pressure during tightening [MPa]	1.025	1.080	1.178
Peak contact pressure at lock [MPa]	0.170	0.345	0.270
Peak in-plane PLA tension [MPa]	0.392	0.334	0.456
Peak through-layer PLA tension [MPa]	0.299	0.344	0.398

Board displacement and pocket loading

All three meshes place the maximum displacement at the same PCB corner and the locked contact on the middle cell. The full spread in peak PCB displacement is 0.055 μm, or 0.19%. Each mesh predicts about 39% less displacement than the 47.46 μm bare-board result.

The integrated pocket force at lock fell from 0.594 to 0.572 N on the two finer meshes. At the end of tightening it fell from 3.447 to 1.939 N, a 44% change at the same applied load. The peak local pressure at lock also varies nonmonotonically across the three meshes. These data support the reduction in board deflection and identify the cell carrying the load. Local pressure and the intermediate force history require further convergence checks. Page 10 shows the force at each equilibrium.

The first two default-contact shapes persist with either mount

We repeated the October default-contact eigenanalysis on the refined board mesh before bolt tightening. The solver returned 20 positive frequencies for the bare board and for each snug mount. These controls reproduce the original mounting constraints and contact definitions. The operating-state modes require a separate extraction about the tightened assembly.




Figure 3: Left, the 20 lowest extracted frequencies for each assembly. Right, the modal assurance criterion (MAC) compares displacement vectors at equal rank on the 368,754 common structural nodes. A value of one indicates proportional shapes on those nodes.

Mode 1 was 66.611 Hz bare, 66.614 Hz with nylon and 66.615 Hz with aluminium. Both case-to-bare MAC values exceeded 0.99999. Mode 2 was also closely matched at about 154.8 Hz. At rank 3 the frequencies were 468.8, 263.9 and 357.2 Hz and the equal-rank shapes differed. The closest of the first 20 cased shapes to bare mode 3 occurred at rank 7 with nylon (MAC 0.714) and rank 4 with aluminium (MAC 0.823).

Mode 20 was 2247.6 Hz bare, 1809.5 Hz with nylon and 1847.7 Hz with aluminium. The same-rank MAC values were 0.012 and below 0.001, respectively. Even the closest shapes among the first 20 cased modes had MAC below 0.15 against bare mode 20. A frequency shift of a single physical mode cannot be inferred from these three rank-20 frequencies.

Why the original mesh also lists a 1.69 Hz mode

The two coarse-board controls each recovered 20 frequencies with the Sturm check. Their 1.69 Hz mode is localized on the single solid element representing component L3. Every other solid reached less than 0.20% of its peak amplitude, and its largest directional effective mass was 4.44 parts per million of assembly mass. The first bare-board shape at 62.805 Hz reappeared at rank 2 with either screw, at 62.807 and 62.809 Hz (MAC above 0.999999 on 95,215 shared solid nodes).

Paired 4K movies

The snug-fit movie catalogue links the bare and cased views for modes 1 and 20. The catalogue also includes the twentieth bolt-locked mode. Dedicated 20-mode extractions reproduced the wide-basis rank-20 frequencies of 1982.33 Hz with nylon and 2011.37 Hz with aluminium. Within each mount, the two extractions gave MAC above 0.9999 on the full solid mesh. Each modal film uses the same 6 mm peak display amplitude and camera pose. The nylon and aluminium panels identify the frequency, rank and shape match. The display amplitude is a visualization scale.

Vibration of the tightened board and case

We restarted each assembly from its last converged bolt-locked equilibrium. The lowest frequency was 485.96 Hz bare, 294.94 Hz with nylon and 415.42 Hz with aluminium. Both mounts introduced shapes below the first bare frequency. Comparing the two screw materials, their lowest shapes had a full-solid MAC of 0.921 and a case-only MAC of 0.929. Aluminium raised the frequency of this matched shape by 40.8%. The cells' peak amplitudes were only 3.8% and 8.6% of the PCB peaks in the nylon and aluminium first modes, respectively.




Figure 4: Left, each tick marks a native natural frequency through 1.3 kHz. Right, the maximum board-normal RMS displacement anywhere on the PCB, relative to the base. Each axis was excited separately with the October 20–2000 Hz spectrum and 2% modal damping. The independent calculation integrates the signed native modes and their participation factors.

Which modes correspond to the bare board?

On the common original assembly, the best matches to the first bare shape occurred at 633.99 Hz with nylon (MAC 0.697) and 426.84 Hz with aluminium (0.694). The first bare mode therefore cannot be tracked reliably by its rank. The 826.30 Hz bare shape persisted at 825.20 and 825.21 Hz, with MAC values above 0.995 for both screws.

Board response to the original base spectrum

Peak PCB Z displacement [μm RMS]	Base X	Base Y	Base Z
Bare	23.37	19.45	52.67
Snug, nylon screws	86.31	104.58	139.49
Snug, aluminium screws	78.96	66.78	75.86

Both mounts reduced PCB deflection during bolt tightening. Under base-Z vibration, the calculated RMS board motion increased to 2.65 times bare with nylon and 1.44 times bare with aluminium. The native bases retained 38 bare modes and 48 modes for each mount up to 4 kHz. Removing modes above 3.5 kHz changed all nine tabulated peaks by less than 0.003%. The independent bare calculation reproduced the 18 archived native displacement peaks within 0.013%. The six cased MAPDL spectra reproduced the independent peak PCB Z displacements within 0.002 μm. Pages 11–12 compare the native stresses across directions.

Case-mesh qualification

After tightening, MAPDL flagged the same PLA tetrahedron in both mounts at its 179.9° edge-angle limit. On each locked mesh, an independent polynomial bound confirmed a positive Jacobian determinant throughout all 45,549 case elements. The flagged element had the smallest lower bound, 0.01286 mm^3 in both cases. The separate 1.5 mm nylon prestressed basis will test frequency and vibration-response sensitivity.

Outer cells can reach the case during vibration

The modal model holds the contact conditions present at bolt lock. To test this assumption, we applied the signed modal displacement at physical scale to the case, three cells and six washers. For each base direction we selected the frames with the lowest and highest input acceleration in the original 480-frame film interval. This gives six samples at identical excitation times for each screw material. We reconstructed the quadratic contact surfaces at two subdivision levels and first checked that the zero-motion geometry reproduced the native tightening result.




Figure 5: Closest sampled signed distance from each cell to the PLA at bolt lock and at the two selected base-Z frames. A negative distance places a sampled cell-surface vertex inside the case. Triangle-intersection tests also checked each complete surface. Left and right follow increasing PCB X.

At bolt lock the middle pocket carried load with both screw materials. At base-Z frame 353 (1.02155 s), all three cell surfaces intersected the nylon-mounted case. With aluminium screws, the left and middle cells intersected. At frame 451 (1.02753 s), both outer cells cleared both cases. The aluminium model also opened a 0.0046 mm sampled gap at the middle cell. Both spatial refinements agreed on every classification, and all six washers cleared at every sampled instant.

Base axis	Film frame	Time [s]	Intersecting cells, nylon	Intersecting cells, aluminium
X	75	1.00458	Left, middle	Middle, right
X	183	1.01117	Middle	Middle
Y	85	1.00519	Left, middle	All three
Y	28	1.00171	Middle	Middle
Z	353	1.02155	All three	Left, middle
Z	451	1.02753	Middle	None

Outer-pocket engagement also appeared during the 0.10 s startup ramp. We selected two earlier base-Z stations using left-cell motion relative to the case and checked all the surfaces again. At 82.14 ms all three cells intersected the nylon-mounted case, while only the middle cell intersected the aluminium-mounted case. At 83.83 ms the aluminium case also intersected the right cell. Both geometric refinements agreed. These instants precede the first calculated PLA strength-reference crossing on page 9.

The extra supports can redirect load once an outer cell engages. The spectrum values on page 6 quantify the response with the installed contact state held fixed. To check load transfer at frame 353, paired local nonlinear models will drive the same region of each mount with the signed base-Z displacement. Each has a contact-enabled and a free control at two cut sizes. The six samples above establish neither the first contact time nor its duration.

Base-X vibration raises board travel and reduces peak stress

MAPDL applied the original 20–2000 Hz random acceleration along PCB X to the bare assembly and both installed cases. The three native runs used the same 2% modal damping. The table gives the largest one-sigma response within each named part. Each maximum can occur at a different node.

Base X, native MAPDL response	Bare	Nylon screws	Aluminium screws
PCB Z displacement [μm RMS]	23.37	86.31	78.96
PCB absolute Z acceleration [g RMS]	52.29	95.37	78.87
PCB equivalent stress [MPa RMS]	90.32	82.68	79.35
Cell-body equivalent stress [MPa RMS]	21.02	18.03	20.50
Nickel-strip equivalent stress [MPa RMS]	291.90	267.55	259.29
PLA through-layer normal stress [MPa RMS]	—	4.97	11.87
Screw longitudinal stress [MPa RMS]	—	7.74	23.36

Peak PCB equivalent stress fell by 8.5% with nylon screws and 12.1% with aluminium screws under this excitation. The independent calculation on page 6 reproduced all three native PCB Z displacement maxima within 0.001 μm. The equivalent board material gives a comparison of assembly response. A service margin for the populated PCB requires the laminate data and package-specific board-strain limits.

How the middle cell transfers vibration load

At bolt lock the middle cell touches the case and remains attached to its two nickel strips. We summed the signed native modal element forces separately at the two strip bonds and at the loaded pocket. The case-side resultant opposed the force recovered on the middle cell outside the bond footprints. Including all three interfaces reproduced the independently integrated modal cell inertia within a relative error of 6×10^{-6} across the modes. The other two cells continued to transmit load through the strip bonds in this linearization.

With base-X excitation, independent spectrum integration gave middle-pocket force components of 17.53 N RMS along X and 7.75 N RMS along Z with nylon screws. Aluminium gave 15.83 and 6.07 N RMS. These dynamic components assume the middle contact stays engaged. The native base-X solid-element force records provided a separate check on the modal calculation. Page 7 shows where the fixed contact assumption breaks in the seeded motion.

Nickel response and movie coverage

The global nickel strips are linear elastic. The archived local damage model uses an exploratory yield reference of 185 MPa. Including preload, the first base-X seeded stress crossing fell at 38.12–38.13 ms bare, 37.83–37.84 ms with nylon and 40.39–40.41 ms with aluminium. Establishing permanent strain or tearing requires the nonlinear strip model. The movie catalogue lists each reviewed pair by base direction and response component. The RMS camera orbits show a fixed statistical field on a shared colour scale.

Printed-tab tension peaks beside the screw bearing

During each nine-second excitation we combined the locked stress tensor and signed modal stresses at the same integration station and element corner. The search covered all 182,196 unaveraged PLA corners and all 589,825 time stations per base direction. Across the layers, the largest value reached 31.17 MPa under base Y with nylon and 84.20 MPa under base Z with aluminium. Both occurred 0.60 mm from the coupled bearing nodes of the tab near PCB $(X, Y) = (66, 4)$ mm.




Figure 6: The first two panels divide the peak signed PLA tensile stress by the corresponding printed-coupon mean. The dashed line marks the coupon mean. Small horizontal marks on the bars show the highest result at least 2 mm from any tied bearing node. The right panel gives peak axial-plus-bending tensile stress at a modelled screw-section point. Each panel uses the same seeded input for a given base direction.

What the percentages measure

The reference strengths are the reported means for uniaxial printed specimens, 40.5 MPa through layers and 52.3 MPa in plane. Nylon mounting reached 77% through layers and 38% in plane, both under base Y. Aluminium reached 208% through layers and 115% in plane under base Z. Across all three aluminium runs, excluding the 2 mm bearing band brought the highest layer-normal and in-plane results to 46% and 74% of their respective means. The rigid screw-bearing footprint and the actual print orientation matter to this local comparison. PolyLite PLA reference data.

For aluminium screws the calculated through-layer tension first crossed the coupon mean at 129.64–129.65 ms under Z, 190.57–190.58 ms under X and 517.99–518.01 ms under Y. The in-plane reference was crossed only under Z, at 845.18–845.20 ms. The exact oscillator integration reproduced all four crossing brackets at the original 1/65,536 s sample interval. The nylon histories remained below both coupon means throughout.

At both worst through-layer instants, the deformed surfaces of all three cells intersected the case in the linear reconstruction. The elastic continuation holds the initial contact tangent fixed even when a new pocket would engage. The aluminium peak is a demand beyond the coupon reference. Predicting cracking or a failure time would require changed contact and a calibrated print failure law.

What the screw carries

The four circular M4 beam shanks were evaluated at 25 section points at each end. The highest tensile value was 35.90 MPa for nylon under base Y and 96.21 MPa for aluminium under base X. Bending contributed 35.00 and 91.73 MPa, respectively, at those exact instants. The nylon part has no verified tensile rating for this comparison, and the aluminium alloy and temper are unspecified. The native base-X one-sigma stresses agree with the independent spectrum integration over all 200 shank points to better than 0.004% in relative field norm.

An exact oscillator solution for the piecewise-linear acceleration changed the 24 PLA maxima across both screw materials, tensile directions, base axes and bearing-distance scopes by at most 0.43% from the average-acceleration integration. Both methods use the same installed stiffness and material law.

The nylon middle pocket carries about 0.6 N at bolt lock

The six original fasteners were each tightened to 750 N. The case carried a much smaller load at the middle cell. The 2 mm and 1.5 mm meshes gave peak resultants of 8.323 and 8.571 N during tightening. At bolt lock they gave 0.594 and 0.572 N across five and seven loaded case faces, respectively. All loaded faces belonged to the same middle pocket.




Figure 7: Left, forces summed over every case contact element on each mesh. Right, the 2 mm model gives the times when the signed modal increment along the lock-force direction first passed +0.594 and −0.594 N during each separate base acceleration. The label gives the later crossing, which bounds how long the installed pressure pattern can remain consistent.

Why the fixed-contact force becomes inconsistent

The five active frictionless faces point towards the same side of the middle cell. Over their full curved surfaces, the cosine between the case normals and the resultant direction exceeded 0.993. A compressive force on any of those faces contributes with the same sign along this direction. Once the signed vibration increment has exceeded the installed force in both directions, one excursion would require the pocket to pull on the cell.

In the nominal 2 mm model that condition occurred by 18.41 ms for base X, 25.56 ms for base Y and 12.69 ms for base Z, taking the later bound from two time-integration methods. Reducing the modal cutoff from 4 to 3 kHz left the three Newmark bounds at the same integration stations. The 2 kHz cutoff changed the bounds by at most 0.046 ms. The corresponding 1.5 mm vibration bound requires its own prestressed modes.

At the six sampled crossing instants, tests of the complete quadratic surfaces found the outer cells clear and the middle cell still touching or overlapping the case. The force check detects a need to redistribute the installed pressure before those snapshots show an outer cell reaching its pocket. It cannot establish when the middle cell fully lifts off. The nonlinear controls include an intact shell with all three cells, six nickel strips and six washers so both outer pockets can engage.

How closely did the installed models balance?

On the 2 mm mesh, the whole-model force residual was 3.01 N at peak pocket load and 0.028 N at lock. On the 1.5 mm mesh the corresponding values were 2.97 and 0.00071 N. A global residual measures imbalance across the assembly. It does not directly measure the error in one pocket force. A same-mesh repeat with a 0.01 N force criterion will check the sensitivity to nonlinear convergence. The two independent readbacks of contact force agreed within 10^{-10} N at every station on both meshes.

Under base Y, stress rises across most of the PCB

The peak equivalent stress under Y excitation increased from 17.85 MPa RMS bare to 50.21 MPa with nylon screws and 48.40 MPa with aluminium. The bare peak lies at (10.0, 16.0) mm in the PCB plane. The nylon peak shifts to (9.5, 118.2) mm, and the aluminium peak to (62.6, 5.5) mm.




Figure 8: Native base-Y stress fields in the original board coordinates. A ring marks the peak in each assembly. The three maps share one square-root colour scale, labelled in MPa RMS. Each mesh footprint shows the largest stored equivalent stress among all corners through the board thickness.

How much of the board changes?

We matched the two thickness layers by their common mid-plane nodes, giving 19,507 columns across 39,014 quadratic PCB elements. The footprint areas sum to 8,150.067 mm^2. Dividing the native element volume at the first bare preload station by nominal thickness gave 8,150.066 mm^2. Comparing each column to the same place on the bare board, the base-Y stress rose by more than 10% over 98.0% of the footprint with nylon and 97.6% with aluminium.

Base-Y equivalent stress [MPa RMS]	Bare	Nylon	Aluminium
Area-weighted median	0.264	0.695	0.622
Area-weighted 95th percentile	1.85	8.84	7.22
Highest element-corner result	17.85	50.21	48.40

Under base X the highest stress fell with both mounts, but the area-weighted 95th percentile rose from 3.54 MPa bare to 9.97 MPa with nylon and 10.06 MPa with aluminium. A lower peak at one corner can therefore coexist with higher stress across a substantial part of the board.

Board-normal vibration separates screw stiffness from peak stress

Under base Z, aluminium screws limited peak board-normal motion to 75.86 μm RMS, compared with 139.49 μm with nylon. The aluminium assembly nevertheless developed the larger peak PCB stress, 98.65 versus 69.37 MPa RMS. The bare values were 52.67 μm and 32.48 MPa. All nine spectra used the original load level and damping and held each assembly's contact state fixed at bolt lock.




Figure 9: Native MAPDL results for separate X, Y and Z base excitations. The left panel shows peak board-normal motion relative to the base. The right shows the largest stored equivalent stress within the PCB. Each maximum is taken over the whole PCB for that load case.

Which excitation frequencies drive the peak stress?

At each assembly's own governing PCB corner, we integrated the signed modal stresses over disjoint forcing-frequency bands, retaining all cross-correlations between modes. The bands sum to the full mean square. Under base X, the 500–800 Hz band accounted for 95–97% of the mean square in all three assemblies. Under base Z, the strongest band changed with the mount.

Base-Z assembly	Strongest forcing band	Share of stress mean square
Bare	800–1200 Hz	74.9%
Snug, nylon screws	200–350 Hz	94.7%
Snug, aluminium screws	350–500 Hz	92.1%

The full signed-tensor calculation reproduced all nine native peak PCB stresses within 0.1%. Reducing the modal cutoff from 4 to 3.5 kHz changed those peaks by at most 0.20%. This checks modal truncation within the 2 mm case model. The finer case mesh has its own installed contact state and prestressed calculation.

Peak nickel-strip equivalent stress under base Z also increased, from 38.13 MPa RMS bare to 122.82 MPa with nylon and 138.21 MPa with aluminium. The signed linear startup histories first crossed the local model's assumed 185 MPa yield reference at 70.30–70.31 ms and 61.25–61.26 ms, respectively. The bare history stayed below it over the first 100 ms. These conditional elastic crossings locate a demand for nonlinear analysis. Permanent strain and tearing require the local material and contact histories.

Appendix A. Previous battery-case study

Assembly fit, bolt tightening, side pull and vibration response

9 November 2026 | Native structural analysis in ANSYS MAPDL 2026 R1.02 | 22 paired movies

The mounting height determines whether the cells are already loaded

Placing the four tabs directly against the board creates approximately 1.18 mm of interference at the cell crowns. Each of the three cell solids shares about 1.70 cm^3 with the undeformed enclosure. A 3 mm tab stand-off clears the cells, nickel strips, washers and fasteners present in the 35-body mechanical STEP assembly. Thus a flush installation must displace or deform parts as the screws tighten. With the supplied Balius STEP, the outer washers touch at 2.397 mm stand-off. The Balius SolidWorks part has different washer clearance (page 29). Translating a rigid cell along the PCB X axis first closes a gap after 0.146–0.325 mm, depending on the cell and direction. Flexible relative motion determines whether contact occurs under load.




Figure A.1: Section through the middle of the cells, in PCB coordinates. The solid outlines show as-designed geometry before tightening. The mounting tabs lie beyond this section.

What the raised case changes

Under X-axis vibration, the 3 mm case increased peak board-normal motion from 23.37 μm RMS bare to 145.55 with nylon screws and 120.00 with aluminium. Under base Z the peak PCB stress rose from 32.5 MPa RMS bare to 64.8 with nylon and 84.2 with aluminium (page 13). With the bilinear nickel law, an 8.54 N pull moved the edge cell 0.50 mm bare and about 0.20 mm with either raised case. With the multilinear law, a fixed 0.3375 mm travel required 10.15 N bare, 63.82 N with nylon and 125.98 N with aluminium screws (page 26). Nylon also gave the lowest cell-body X acceleration. Aluminium reduced board movement relative to nylon and increased the local stress across the PLA layers at a screw bearing. In the flush mounting trials, the printed-PLA tensile reference was exceeded before the tabs touched. At the last nylon equilibrium, only 4–5% of each tab lay within 0.05 mm of the board. With aluminium, that fraction was 18–19% even at the full 3 mm screw travel (page 19).

Reference assembly

The October assembly has 208 bodies and a modeled mass of 251.82 g. Eight stand-off end faces carry the base motion. Two nickel strips attach each cell to the assembly. In the connected reference, six existing screws were loaded to 750 N apiece and locked. Its first mode was 485.964 Hz. Independent base excitation between 20 and 2000 Hz gave a maximum PCB directional displacement of 0.052674 mm RMS under Z excitation and a maximum PCB equivalent stress of 90.325 MPa RMS under X excitation. These archived quantities supply reference checks for the repeats.

Registration and fastener selection

The four nonplated corner holes in PCB1 ODB++ have finished diameter 4.200 mm. The hole pattern measures 62.865×114.427 mm. The case bores have two diameters, 5.000 and 5.090 mm, on a 62.855×113.241 mm pattern. Centring the two patterns leaves about 0.593 mm of offset at each end. The sum of the radial clearances of a nominal 4 mm shank in the smaller case bore and in the board is 0.600 mm. The approximately 0.007 mm difference is the available nominal alignment margin there. Printed hole size, fastener major diameter and drilling tolerances therefore matter for installation.

Tab stand-off [mm]	Cell overlap [mm^3/cell]	Washer bodies intersected	Other intersections
0	1696–1698	4	6 nickel strips
1.2715	0	4	None found
2	0	4	None found
3	0	0	None found

Table A.1: Solid intersections between the unstrained case and mechanical STEP bodies. The board's lower face defines the tab seating datum.

Starting from 3 mm of tab stand-off, the four outer washers meet the descending case after 0.603 mm. The middle cell first touches after 1.760 mm and the two outer cells after 1.790 mm. Once a washer touches, actual motion depends on deformation of the case and fasteners. A rigid assembly at the nominal registration therefore needs more than 2.397 mm of stand-off for clearance. Manufacturing tolerances and assembly misalignment would change that value.




Figure A.2: Left, downward travel from the 3 mm position. Solid intersections 0.05 mm beyond each onset independently confirm contact. Right, subdividing the same curved finite-element surfaces moves the middle-cell contact toward the STEP solution. The underlying case mesh and the physical geometry are fixed.

Materials and mounting representation

The supplied single-solid STEP has volume 63.069 cm^3. At a printed-PLA reference density of 1.17 g/cm^3, a dense case weighs 73.79 g, about 29.3% of the bare assembly mass. The material axes place the print layers parallel to the PCB for this scenario. PolyLite PLA coupon tensile moduli are 3.427 GPa in the print plane and 3.065 GPa through the layers. Shear moduli and Poisson ratios are engineering assumptions. Actual infill, orientation, print parameters and case mass require measurement. The published coupons used 100% infill. Polymaker technical data sheet.

The candidate model uses four M4 beam shanks with an effective tensile area of 8.78 mm^2. The comparison uses 69 GPa for aluminium and an exploratory 3.0 GPa for nylon. The nominal nylon hardware is McMaster-Carr 93640A145, M4 × 0.7 thread, 12 mm long. The represented bearing patches transfer loads between each end and its solid mesh. Compression-only members represent tab seating, with an assumed PLA annulus at the raised attachment points. The four case screws have no measured installation torque. The 750 N in the reference applies to the six original battery fasteners. McMaster-Carr metric socket-head screws.

Numerical checks and remaining comparisons

The initial mesh has 16,108 curved quadratic tetrahedra. A 43,659-element refinement is available. Both have positive minimum scaled Jacobians. The native preparation check counted four screw beams, four compression seats and 8,038 candidate case contact faces. The raised cases passed the preload checks used for their vibration comparisons. In both flush cases the PLA exceeded its tensile reference before the tabs seated (page 19). The October bare-cell damage run and its repeat first registered damage around 43 N. A physical breaking load remains undetermined.

The bare-board repeat reproduces the six locked bolt loads

The original battery attachment provides the initial stress field for the connected modal and vibration analyses. In the first nonlinear load step each of the six pretension elements receives 750 N. In the second step MAPDL holds the attained section adjustment fixed. The reaction at the pretension degree of freedom then measures how much load the locked joint retains. The four case screws are absent from this reference run.

Existing bolt	Locked adjustment [μm]	Locked reaction [N]
1	28.297	749.99935
2	22.205	749.99945
3	18.597	749.99908
4	30.457	749.99680
5	20.686	749.99942
6	18.772	749.99868

Table A.2: Fresh MAPDL extraction after length locking. Every row agrees with the October export at its stored precision. The largest departure from the applied 750 N is 0.00321 N.


The solver stored eight equilibrium states and completed the two load steps in approximately 59 minutes on 12 distributed processes. The largest total displacement at lock was 0.0474595 mm. The repeated result differs from the October Mechanical export by 3.4×10^{-8} in relative terms. The model produced 45 warnings, including overlapping contacts, automatically removed redundant constraints and the fixed orientation of pretension elements during large-displacement analysis. The warning text printed in the main solver listing matched the reference run. This comparison establishes repeatability for the existing attachment. Page 7 compares the locked bare and raised assemblies. The vibration response requires separate modal and random-response results.

How the side-pull comparison measures load transfer

The local model drives the outer cell sideways through its rigid pilot while the two nickel strips bend. In the washer-clamped fixture, each strip is compressed with 750 N and the clamp height is then locked. During the pull, the cell can translate in the other two directions and rotate. The cased fixture adds a deformable printed enclosure, four screw shanks and compression-only tab seats. The neighboring cells and screw tops are fixed in this local approximation. The native model check counted 9,502 potential PLA contact faces. These contacts carry compression between PLA and the cell or washer surfaces. Direct PLA-to-nickel contact is omitted from this local fixture. That omission matters most in the flush geometry, where the CAD also intersects the strips.

The audit sums external forces and moments about the displaced cell centre at each converged increment. Both nominal nickel studies used the same bare mesh and 750 N clamp preloads. At 0.500 mm lateral travel, the bilinear model (148 MPa initial yield) required 8.54 N, and the multilinear damage model (185 MPa initial yield) required 11.33 N. At the same 8.54 N, the refined multilinear bare and raised-nylon histories both gave 0.20190 mm between saved states at 0.20166 and 0.20215 mm. The two loading schedules used different increments. Page 6 compares enclosures using the bilinear law throughout.

With the continuous nickel-damage law, the October run and its fresh repeat reached the same 110 equilibria. Both first crossed the 10^{-4} damage threshold between 3.250 and 3.275 mm, at 42.87–43.37 N. The maximum force difference over the two curves was 2.5×10^{-8} N. At their last converged state (3.347 mm, 44.86 N), four flat shell elements exceeded the threshold on the bottom face, two per strip, over 1.50 mm^2 of original shell area. The force was still rising when convergence stopped. The rupture load remains undetermined.



Native bare edge-cell pull through the last converged equilibrium. The right panel enlarges the onset interval. Damage is the largest reported shell-section value in the two strips.

Both default-contact meshes reproduce the October modal spectra

Each unpreloaded model used the archived mounting constraints and searched for 20 undamped natural frequencies between 1 and 10,000 Hz. The original mesh returned modes from 62.805 to 2205.547 Hz and the refined mesh from 66.611 to 2247.595 Hz. The maximum relative differences from the corresponding October exports were 1.78×10^{-8} and 1.74×10^{-9}. Repeating a given discretization thus produced the same frequency spectrum to the stated precision.




Figure A.3: Fresh ANSYS results with the original default contacts. Rank orders the frequencies within each mesh. A shared rank can contain different mode shapes, particularly where modes exchange order.

The first original-mesh run returned only four modes and exited normally. The repeat kept the same input geometry, material properties, supports and search range. It changed the Block Lanczos algorithm to its alternate formulation and requested the Sturm sequence check. This recovered the complete spectrum. The default models retain the detached nine-body group in the earlier connection diagnosis. The bearing, locking and contact states of the six-bolt model provide the starting point for the connected vibration comparison.

PCB stress over the 480 frames of the seeded motion movie

Each of the three 9 s October base records has 589,825 samples at 65,536 Hz. After a 0.1 s ramp, the periodic 20–2000 Hz input reaches 14.136 g RMS. The native histories used 38 prestressed modes for the bare board, 49 with raised nylon screws and 48 with raised aluminium screws. All use 2% damping. Each clip shows 480 signed states from 1.000061 to 1.029297 s at 60 frames per second.

The six signed dynamic stress components were summed at each of 312,112 PCB element corners before calculating von Mises stress. The fresh native X history reproduced all 480 October bare-board frame maxima within 0.000028%; the independent integration agreed within 0.00182%. The largest native value in this clip was 154.41 MPa bare, 169.95 MPa with nylon screws and 151.03 MPa with aluminium screws. The nylon peak occurred about 3.85 ms earlier and at a different board node from the bare peak.




Figure A.4: Maximum dynamic PCB stress at each of the original 480 movie times. The three curves use signed native MAPDL coordinates on the corresponding tightened modal bases. Each dot marks a clip maximum.

Over the same frames, native peak board-normal displacements for base X/Y/Z were 0.040/0.047/0.168 mm bare, 0.244/0.154/0.290 mm with nylon and 0.114/0.125/0.314 mm with aluminium. All 22 pairs use native fields. The seven time-history pairs display motion at 50× scale and 273× slow motion. Paired movies.

Does the contact model start with the gap measured in CAD?

An enclosure that presses on the cells at the start of a raised-case calculation will appear to stiffen the assembly before the real parts would touch. We checked the undeformed contact pairs separately from the load solution. The local fixture uses one target for the moving edge cell and another for the fixed neighboring cells and washers. The global assembly uses deformable targets. The search radius tells MAPDL which nearby facets to examine; it does not set the physical clearance.

At 3 mm tab stand-off	Default search	0.6 mm search	2 mm search
Local: moving edge cell	+0.212	+0.212	+0.212
Local: fixed cells and washers	−7.685	+0.200	+0.200
Global: enclosure to assembly	+0.199	+0.199	+0.199

Table A.3: Initial native contact check in millimetres. Positive values are gaps; negative values are overlaps. Default search radii ranged from 10.6 to 11.1 mm. The 1 mm search reproduced the 0.6 and 2 mm columns.

The CAD solids do not intersect at this stand-off. We rejected the first raised local calculation because its 7.685 mm overlap contradicted that independent check. It did not reach a converged load increment. The replacement uses a 1 mm search radius for the two added contact pairs and leaves the nickel clamp contacts unchanged. The comparison calls for the cell travel at first closure, contact pressure, penetration, and load transferred to the case mounts.

The shortest unloaded distance from any cell to the STEP case is 0.144–0.161 mm. Translating the edge cell rigidly along X first closes the gap at 0.163 mm in positive X and 0.308 mm in negative X. In the loaded fixture the cell also rotates and moves vertically.

The cell reaches the STEP case before the native contact pair carries load

We recovered each cell pose from the motion of 784 nickel nodes rigidly attached to the cell. In both raised nominal damage fixtures, those motions fitted one rigid transformation to within 10^{-5} mm and reproduced the independently exported cell-pilot translations. A separate displacement readback covered all 29,610 printed-case nodes. At the stations below, their maximum movement was below 10^{-9} mm.

Cell travel	STEP solids	Meshed contact faces	Native contact reaction
0.1375 mm	0.02583 mm gap	Disjoint	0 N
0.1875 mm	0.1183 mm^3 overlap	Intersecting	0 N
0.211914 mm	0.4864 mm^3 overlap	Intersecting	0 N

Both screw materials gave all three rows. The final row is the last open state of each refined pull. Independent intersection tests used the actual cell target facets and only the PLA faces selected for contact. Both surface refinements gave the same classification.

At 0.1875 mm the cell was 23.4–23.6 μm past first STEP contact along X with its rotation and transverse translations held at their measured values. At the final open station for either screw material this excess travel reached 47.8–48.0 μm. Testing only the target vertices missed intersections between faces at 0.1875 mm. The finer load steps on page 25 resolve when this model carries force. Contact discretization also affects how that force relates to the physical assembly.

Why the flush installation needs a separate check

The flush STEP has real interference. In the local model, a 2 mm search recovered the 1.178 mm crown overlap of the moving cell. A 1 mm search found only 1.000 mm, and a 0.6 mm search found only 0.598 mm. Tightening the search around the flush configuration can therefore hide real interference. Conversely, the default global search reported a peak overlap of 10.093 mm, versus 1.848 mm with a 2 mm search. These values identify a contact-model discrepancy. They do not establish an installation force. The flush comparison requires a verified path into contact, including the washers and strips, and force balance in the installed assembly before the vibration solve.

Both raised cases restrain the edge cell after contact

The local fixture pulls the outer cell in positive X. Its other translations and rotations are free. With the case on a 3 mm stand-off, the last open state was at 0.196 mm and the first closed state at 0.221 mm for either screw material. Under the 8.54 N load that moved the bare cell 0.50 mm, both cased cells travelled about 0.20 mm. The interpolated estimates were 0.207 mm with nylon and 0.202 mm with aluminium. Both lie in the same 0.025 mm interval between native states.




Figure A.5: All three native pull histories. The blue band brackets first contact. The dashed aluminium segment extends from the last state below both PLA tensile references to states above at least one reference.

At 0.420625 mm prescribed cell travel	Bare	Raised nylon	Raised aluminium
Cell reaction in X [N]	8.26	100.99	209.96
Load on four case supports in X [N]	—	80.00	174.54
Peak equivalent plastic strain in nickel [%]	1.013	1.176	1.370
External work applied to cell [mJ]	2.63	11.91	22.56
Energy stored in printed case [mJ]	—	5.41	12.93
Energy stored in four screw shanks [mJ]	—	2.05	2.61

At a fixed travel the stiffer aluminium attachment increased both the case load and the strain in the nickel. At a fixed 8.54 N, the native states bracketing that force instead gave 0.36–0.44% peak nickel plastic strain for the two cased curves, versus 1.25% bare. Integrating native nodal forces and moments over the displacements of the PLA and shanks independently reproduced their stored energies within 0.009% of each component's maximum change.

Where the aluminium comparison leaves the coupon range

With aluminium screws, peak in-plane PLA tension crossed 52.3 MPa between 0.421 and 0.446 mm. Through-layer tension crossed 40.5 MPa between 0.446 and 0.471 mm. Both peaks were within 0.54 mm of the idealized screw bearing. At 0.50 mm the elastic continuation returned 291.5 N with aluminium, versus 138.5 N with nylon and 8.54 N bare. The nylon case stayed below both references, reaching 28.6 and 23.5 MPa. Its most tensile shank fibre reached 30.5 MPa, including 29.3 MPa from bending.

All fixtures saved 33 converged states. Peak penetration at a loaded cell/case corner was 0.0116 mm with nylon and 0.0198 mm with aluminium. The native cell contact forces and case-support reactions balanced to within 0.0019 N. These pulls assume fixed screw tops and omit direct PLA-to-nickel contact. At 0.421 mm cell travel, the axial-load resultants at the four tab bearings acted 5.41–6.54 mm from the screw axes with nylon and 5.41–5.49 mm with aluminium. All eight offsets exceed the modeled 3.75 mm bearing radius. A one-sided axial pressure across that footprint cannot carry the same force and moment. The computed pull stiffness therefore depends on how the installed joints transmit a couple. Page 17 gives the force check.

Both raised cases reduce board deflection during tightening

The bare board and both 3 mm stand-off assemblies completed eight equilibrium states under the same six-bolt tightening sequence. Each original bolt carried 750 N before its length was locked and retained 749.996–750.000 N afterward. The two cased models differ only in the properties assigned to the four case screws. The load in this comparison comes from the six original bolts.





Figure A.6: Peak displacement magnitude relative to the undeformed assembly after bolt locking. Each comparison uses the same mesh nodes on each part. Micrometres are used here to show the small changes at the cells and nickel strips.

The peak PCB displacement occurred at node 207485 in all three models. It fell from 47.46 μm bare to 32.13 μm with nylon screws and 27.13 μm with aluminium screws, reductions of 32.3% and 42.8%. Changing the four case screws from nylon to aluminium reduced this peak by another 5.00 μm, or 15.6% relative to nylon. The cell-body peak changed by at most 0.30% from bare and the nickel-strip peak by 0.51%. All 8,038 case-to-assembly contact faces stayed open in both raised assemblies, with zero contact pressure at every stored state. The case altered board bending through its four corner attachments.

ANSYS DPF recovered translations on 217,704 common PCB nodes. On the bare control the two displacement readers agreed on every component. The six pretension adjustments agreed with native MAPDL readback within 10^{-11} m in all three assemblies.

The PCB bends toward the cells in both flush installations

The PCB moved less than 1 μm through 0.50 mm screw travel. At 0.80 mm, after washer contact, the same corner at $(0, 0)$ had moved 0.197 mm toward the cells with nylon screws and 0.216 mm with aluminium. The aluminium screws raised the total drive force by 44% and peak board motion by 9.6%. The four PCB bearings moved 0.104–0.145 mm with nylon and 0.125–0.163 mm with aluminium.



Upper PCB face at 0.80 mm screw travel, with one displacement scale for both maps. Positive movement is toward the cells. The curves show the maximum across all 217,704 board nodes relative to six-bolt lock.

At 0.80 mm, the largest increase in upper-face principal tensile strain from six-bolt lock was 0.601% with nylon and 0.958% with aluminium. We compared the same element corner before and after driving. Excluding points within 2 mm of a tied PCB bearing node gave 0.601% and 0.670%, respectively. These local elastic strains describe the board laminate model.

The raised enclosure adds resonances below the first bare-board mode

We extracted undamped natural frequencies about the verified bolt-locked states, using the same mounting constraints and a 1–4000 Hz search. The assembled masses were 251.82 g bare, 325.82 g with the raised nylon-screw case and 326.10 g with aluminium screws. The models returned 38, 49 and 48 modes, respectively. The lowest three frequencies were 253, 289 and 339 Hz with nylon and 320, 372 and 378 Hz with aluminium. All six fall below the first bare-board mode at 486 Hz.




Figure A.7: Each tick marks one native frequency in the excitation band. Lines connect five bare-to-nylon matches above MAC 0.94, and nylon-to-aluminium matches above MAC 0.97 where the assigned match is also the best available match.

The 253 Hz mode carried 17.9% of the assembled mass in X translation. In this shape the largest cell displacement was 2.8% of the peak on the PCB, while the peak on the case was 126% of the PCB peak. Those are amplitude ratios *within a mode*; the actual vibration displacement requires a forcing spectrum and damping. The 253 Hz mode had no close counterpart in the bare set: its highest shape correlation was 0.56. Conversely, the bare 781.35 Hz mode matched cased mode 9 at 782.88 Hz (correlation 0.943). This battery-motion mode shifted by only 0.20% even though its rank changed from fourth to ninth.

Effective translational mass, fraction of whole assembly	X	Y	Z
Bare, all 38 retained modes	87.2%	89.0%	89.6%
Raised nylon, all 49 retained modes	90.1%	91.5%	90.8%
Raised aluminium, all 48 retained modes	90.1%	91.4%	90.3%

How the shape comparison was made

Both modal meshes contain their assembly's static deformation. Before comparing vectors, we checked every original solid node against its own preload displacement and matched the 369,584 node IDs and their undeformed coordinates. The modal assurance criterion (MAC) is the squared, unweighted correlation of the global X, Y and Z eigenvector components at these nodes. It ranges from zero to one and is independent of the sign and normalization of a mode. It excludes the new case nodes so that both vectors describe the same structure. Modes with weak or competing matches remain ambiguous. For the two screw materials we also matched all 399,194 solid nodes, including 29,610 PLA nodes. The first mode rose by 26.5% from 253.16 to 320.17 Hz with full-solid MAC 0.989 and PLA-only MAC 0.994. It is a closely corresponding shape. The next two matches had full-solid MACs of 0.739 and 0.785.

The October bolted movie shows mode 20 at 2364.18 Hz. The two raised assemblies have mode 20 at 1836.45 and 1950.27 Hz. Its MAC with the bare mode is below 0.00023 in both. Searching the full native bases instead places the closest shape at mode 27, at 2365.06 Hz with nylon (MAC 0.717) and 2368.47 Hz with aluminium (MAC 0.640). The movie preserves the original rank and identifies this match on screen.

The linear model predicts more PCB motion with the raised case

We applied the October base acceleration spectrum separately along X, Y and Z to the three bolt-locked assemblies. For the 3 mm stand-off with nylon screws, the independent calculation predicts greater out-of-plane PCB motion for all three excitation directions. Under X excitation the peak PCB response in Z rises from 23.37 to 145.55 μm RMS, a factor of 6.23. In the same calculation the largest cell response in X falls from 61.43 to 53.79 μm RMS (12.4%). With aluminium screws, the peak PCB Z responses were 120.00, 82.33 and 100.55 μm RMS for base X, Y and Z. Compared with nylon, these fall by 17.6%, 5.0% and 23.6%. In particular, the 32% reduction in static board deflection during tightening did not carry over to this vibration metric.




Figure A.8: Each group compares the largest board-normal RMS displacement anywhere on the PCB under the same single-axis base spectrum. Peaks can occur at different nodes. Values describe motion relative to the supports.

How we checked the response

The independent calculation uses each native mode's signed displacement field and directional participation factor. We integrate the modal frequency responses against the one-sided acceleration spectrum (20–2000 Hz, 14.14 g RMS, 2% modal damping), including cross terms between modes driven by the same base input. This preserves cancellation and reinforcement. Halving the quadrature spacing from 0.25 to 0.125 Hz changed the modal covariance by less than 6×10^{-8} in relative norm. For the bare assembly we compared all 18 peak directional displacements: three base directions, three response components, and both whole-assembly and PCB scopes. The worst difference from October's native ANSYS random-response output was 0.013%. The three native MAPDL repeats reproduced all 51 October Mechanical maxima within 4.75×10^{-8} relative, including displacement, absolute acceleration, equivalent stress and the three normal elastic strains on the PCB. Peak PCB equivalent stresses under base X, Y and Z were 90.325, 17.850 and 32.482 MPa RMS.

We repeated the independent integration with modal cutoffs of 2000, 3000, 3500 and 4000 Hz, keeping the input spectrum fixed. For the raised nylon case under base X, both the 20-mode and 49-mode calculations gave a peak PCB Z displacement of 145.55 μm RMS. Across all three inputs, increasing the cutoff from 3500 to 4000 Hz changed the nine PCB directional peaks by at most 0.22% bare and 0.056% cased. The bare PCB's Y response to base Y differed by 8.32% with the 2000 Hz cutoff. These checks apply to displacement within the available basis.

The two native base-X solutions independently gave 120.00 μm for the raised aluminium case and 145.55 μm for the raised nylon assembly's peak PCB Z displacement. All 30 directional displacement peaks across five part selections per cased model agreed with the independent integrals within 0.0017%. Both calculations linearize about the tightened contact state.

The 3 mm stand-off does not prevent dynamic cell contact in the model

The tab stand-off is not the air gap at the cells. The smallest sampled cell clearance on the tightened mesh was 0.143 mm. We paired nearby opposing surfaces and calculated their simultaneous relative motion along the local separation direction. Under base X the most exposed cell location had 0.145 mm clearance and 0.098 mm RMS relative motion. The gap there is only 1.47 times that RMS displacement. This ratio suggests contact is plausible, but it does not tell us when contact occurs.




Figure A.9: Raised case, nylon screws, October X-axis waveform. Left: first-order gap of the selected pair. A negative value indicates that the linear solution continues past projected contact. Right: actual-scale section of both triangulated surfaces displaced by the same signed modes. The curves are a diagnostic of the fixed-open model.

We independently integrated the nine-second October acceleration history and reconstructed the two skins at the instant of greatest projected approach for this pair, 2.9276 s into the waveform. At the tightened rest position the cell and case meshes had no intersections. In the selected deformed state, 895 triangle pairs intersected, and a separate signed-distance calculation placed 24 cell vertices more than 1 μm inside the PLA skin. The deepest sampled vertex lay 0.214 mm inside the PLA. Subdividing the curved elements twice more gave 0.215 mm at the same instant. Both surfaces had positive clearance before excitation. Their intersection shows where the fixed-open vibration assumption breaks down.

Excitation	Cell pair gap [mm]	Relative RMS [mm]	Intersecting cell/PLA pairs
Base X	0.145	0.098	895
Base Y	0.143	0.019	0
Base Z	0.236	0.112	0

Table A.4: Each row selects the cell pair with the greatest RMS-to-gap ratio for that excitation, then checks the whole cell and case skins at one instant. A zero count at one instant does not establish separation throughout the record.

The surface search used both centroids and vertices of facing triangles within 1.2 mm in both directions, including the midside nodes of curved elements. Under base Z the nearest-line projection became negative, but the cell and case skins did not intersect at the selected instant. Tangential motion matters: a negative projected gap alone is insufficient evidence. Under base X both independent geometric checks found overlap. Until a nonlinear transient calculation or vibration test measures the response after closure, use the preceding fixed-contact RMS results as a comparison of the two linear models, not an installed flight stress, impact load or clearance margin.

The local flush installation stopped before the tabs seated

Four nylon screws drew the printed case toward a rigid board datum from an initial 3 mm stand-off. The existing washer clamps were tightened first. ANSYS saved 88 converged equilibria before the third load step failed at the next increment. The final converged screw-head travel was 2.8685 mm, leaving 0.1315 mm of the commanded travel. The solver never reached the sideways pull.





Figure A.10: Left, the computed total screw reaction rose to 2.066 kN. The shaded interval marks the first exceedance of the 0.05 mm numerical penetration screen. Right, the tab surfaces tilted during drawdown. At the last equilibrium every tab crossed the nominal PCB plane at some points and remained clear at others.



The native fixture first loaded the four outer washers at 0.59–0.63 mm of screw travel. This brackets the independent STEP result of 0.603 mm (page 2). At 0.63 mm, two closed contact facets at each washer carried 4.89–4.92 N in board Z, totalling 19.63 N. Each loaded node lay within 0.8 μm of its assigned washer. The next nearest candidate was over 8.6 mm farther away. These local reactions apply to the fixture with fixed neighboring hardware.

The moving edge cell and its two nickel strips stayed clear throughout the partial path. Loaded-corner penetration first exceeded 0.05 mm at 1.67–1.71 mm travel and reached 0.119 mm. The largest departure from force balance was 0.030 N.

Final saved equilibrium	Tab 1	Tab 2	Tab 3	Tab 4
Screw-head reaction [N]	484	517	530	536
Minimum gap to board datum [mm]	−0.332	−0.357	−0.366	−0.369
Median sampled gap [mm]	0.248	0.227	0.236	0.214

In this local fixture the seating springs moved with the screw grips, allowing a tilted tab to cross the board plane. The peak computed PLA equivalent stress reached 233 MPa under the elastic print model. The physical installation force, failure sequence, and full-flush side-pull response remain unresolved. The whole-board installation model instead places contact directly between each tab and the flexible PCB surface, so the model can develop a normal reaction at the bearing land.

Contact deflects the raised case along the middle cell

The fixed-open calculation on page 10 placed parts of all three cell surfaces inside the enclosure at the selected X-waveform sample. Along the middle cell, the affected PLA facets extended from 25.2 to 95.6 mm in board Y. We therefore retained the whole length of this contact region in two native submodels. Their outer boundaries lay 9 or 15 mm from the middle-cell contact line. Each retained the original quadratic elements and directional PLA properties.

For each domain we imposed the tightened board displacements, then applied the signed motion at 2.9276 s to the two local cell bodies and the outer cut faces of the PLA. We increased the imposed motion from zero to its full value and unloaded in a series of static equilibria. With cell contact disabled, the free PLA nodes followed the parent solution to within 1 μm. With frictionless contact active, the largest change in their motion was 249 μm in the smaller domain and 244 μm in the larger one.




Figure A.11: Each curve gives the force needed to impose this particular displacement path. The larger domain leaves a wider section of PLA free to flex. The peak reaction fell by 16.2%. The local models hold the cell motion fixed as the case pushes back.

At the fully imposed displacement	9 mm domain	15 mm domain
Resultant cell reaction [kN]	3.079	2.581
Active contact faces	24	24
Active faces touching the artificial cut	0	0
Maximum sampled skin overlap, contact disabled [mm]	0.2165	0.2164
Maximum sampled skin overlap, contact enabled [mm]	0.0424	0.0445

The independent geometry check measured signed distances on vertices and facet centres inside a common 8 mm band. Some tessellated surfaces still intersected even though the largest loaded-corner penetration recorded by ANSYS was below 0.5 μm at this state. Changing the cut size changed the force appreciably despite whole-model force imbalances below 0.004 N. These results establish local deflection under imposed motion. A flight impact load requires the cells and the surrounding board to respond to contact together.

Which cell first reaches the case in the transient window?

Using the native X history from rest, we checked every integration sample through 89.478 ms on all three curved cell skins. The centre cell was clear at 85.327 ms and intersected the case at 85.342 ms. The left cell first intersected at 85.388 ms. The right cell remained clear through the window. Both local domains captured the two intervals of centre-cell overlap. The left cell lies outside both domains, so the local reactions describe only part of the assembly load path.

At the prescribed time stations, the sealed transient inputs reproduced native translations at all driven nodes within 0.0022 μm. Between stations, linear interpolation in the 9 mm domain differed from the native motion by up to 1.04 μm with a 61.04 μs table interval and 0.26 μm with a 30.52 μs interval. These checks quantify the motion imposed on the submodels. The force curves above are from the static loading and unloading calculation.

The raised case increases PCB stress under Y and Z excitation

The native MAPDL comparison used the same X-axis base spectrum and 2% damping on both assemblies. Each original board bolt had already been tightened and locked. With four nylon case screws at the 3 mm stand-off, the peak PCB equivalent stress fell by 1.6%, from 90.325 to 88.847 MPa RMS. Its location moved about 54 mm across the board. The PCB's maximum normal strains in X and Y both increased.




Figure A.12: PCB plan view in the original mesh coordinates. Each solid footprint shows its largest stored equivalent-stress RMS among its corners. Higher values are drawn last through the thickness. Red circles mark the maxima at $(60.55, 101.11)$ and $(9.54, 118.21)$ mm. Both maps use the same colour scale.

Peak response, one sigma	Base axis	Bare	3 mm nylon	3 mm aluminium
PCB Z displacement [μm]	X	23.37	145.55	120.00
	Y	19.45	86.65	82.33
	Z	52.67	131.64	100.56
PCB equivalent stress [MPa]	X	90.32	88.85	88.65
	Y	17.85	57.05	50.29
	Z	32.48	64.77	84.19
Nickel equivalent stress [MPa]	X	291.90	256.24	286.46
	Y	15.11	21.85	21.86
	Z	38.13	38.38	38.20

Under base Z, aluminium screws gave less board travel than nylon screws and higher peak PCB stress. Each entry is a maximum over the named part. The spectra hold the tightened contact state fixed (pages 10 and 12).

An independent sum of the signed modal stresses reproduced all nine native stress-peak locations across 312,112 PCB element corners. Reducing the modal cutoff from 4 to 3.5 kHz changed the nine peak values by at most 0.20%. With only the modes below 2 kHz, the bare base-Y peak was 34.65% lower. The excitation band remained 20–2000 Hz throughout.

The printed tab carries a local load across its layers

The printed case and PCB react differently to the choice of screw. At the 3 mm stand-off, changing nylon screws to aluminium reduced peak PCB movement during tightening (page 7), while the greatest tensile stress normal to the layers anywhere in the PLA rose from 0.688 to 1.515 MPa. The independent orthotropic elastic-law check reproduced the stored tightening strains to within 4.0×10^{-8} relative field norm across all 64,432 element corners.

For X-axis vibration with nylon screws, the native peak layer-normal stress was 17.16 MPa RMS, 0.53 mm from the nearest node tied to a screw bearing. Among corners at least 2 mm from those nodes it was 5.72 MPa RMS. The static tension at the corner of greatest RMS was 0.688 MPa. The six native component fields and stored equivalent-stress RMS agreed with integration of the signed modal stresses to within 0.001% relative field norm.




Figure A.13: Left, independent reconstruction at element 1215221, node 815413, with the static tension included. The band preserves sample maxima and minima in 20 ms windows. Right, maximum stored through-layer RMS over locations at or beyond each distance from a coupled screw-bearing node.

Cell clearance at the peak printed-layer stress

The native nine-second histories gave peak layer-normal tension above the printed-coupon mean of 40.5 MPa under all three base inputs. The table uses the corner of highest layer-normal RMS for each input and includes the locked preload. All three cell skins intersected the case at the X stress peak. At the Y and Z stress peaks, the curved skins were disjoint. These selected instants describe a linear model with fixed contact.

Base	Peak [MPa]	Coupon [%]	Time [s]	Left gap [mm]	Centre gap [mm]	Right gap [mm]
X	64.3	159	5.74146	−0.201	−0.186	−0.123
Y	44.0	109	5.18582	0.128	0.111	0.133
Z	56.2	139	7.76979	0.121	0.132	0.114

Raised nylon mount. Each gap is the minimum signed distance sampled on that cell's skin at the stress peak, with eight segments per quadratic edge. Negative gaps indicate overlap. The surface-intersection check agreed at two refinements.

Over 589,825 samples per axis, the native modal coordinates agreed with independent integration to within 0.0015% in relative norm. The attachment-force histories agreed within 0.0005 N over the X movie clip. The material reference comes from the PolyLite PLA coupon data. Actual print orientation, infill, bearing compliance and impact response remain unmeasured, so the table cannot establish whether the physical tabs crack.

Aluminium screws reduce board motion and concentrate load in the tab

The two raised models differ only in the properties of the four case screws. Both native base-X spectra used the same excitation, printed case and board mesh. Relative to nylon, aluminium reduced the peak PCB Z displacement by 17.6% and the PCB Z acceleration by 18.6%. The two PCB equivalent-stress peaks were within 0.22% of each other. Changing to aluminium moved the peak back to the same node as the bare reference.

Native base-X response, RMS	Bare	Raised nylon	Raised aluminium
PCB Z displacement [μm]	23.37	145.55	120.00
PCB Z acceleration [g]	52.29	67.45	54.92
Cell-body X acceleration [g]	103.51	91.81	100.90
PCB equivalent stress [MPa]	90.325	88.847	88.655
PLA layer-normal stress [MPa]	—	17.16	24.78
PLA layer-normal stress, at least 2 mm from bearings [MPa]	—	5.72	5.41

The aluminium case had a peak layer-normal stress of 24.78 MPa RMS at a corner 0.50 mm from a coupled bearing node. That is 44.4% above the nylon peak. Among corners at least 2 mm away, aluminium gave a slightly lower peak. This dependence on the bearing region motivates the finer case mesh and inspection of how the actual screw head bears on the print.




Figure A.14: Raised aluminium-screw case, independent response to the October X waveform. Near the selected point, the tightened gap was 0.145 mm and the normal relative motion was 0.070 mm RMS, compared with 0.098 mm for nylon. The section is plotted at physical scale.

Cell clearance at the aluminium mount's peak layer stress

At the monitored X peak, all three cell skins crossed the PLA. The left cell had the greatest sampled overlap. The table compares the monitored stress maximum for each of the three independent base directions with the signed cell gaps from the same native time sample. Physical loads after impact and across the actual screw bearing remain unresolved.

Base	Peak [MPa]	Coupon [%]	Time [s]	Left gap [mm]	Centre gap [mm]	Right gap [mm]
X	110.1	272	8.09808	−0.175	−0.155	−0.100
Y	91.6	226	5.14613	0.100	0.087	0.115
Z	104.2	257	6.32817	0.160	0.143	0.140

Raised aluminium mount under the original nine-second waveforms. The monitored corner maximizes layer-normal RMS for the given input axis. The signed distances and surface checks use the same definitions as on page 14.

The raised case lowers the highest nickel-strip stress under base X

Each cell connects to the board through a nickel strip at each end. We compared the same 11,348 element corners across all three assemblies under the October X-axis vibration spectrum. With nylon case screws, peak equivalent stress fell in all six strips. The largest value occurred at the same corner on the high-Y strip of the right-hand cell in all three assemblies. It fell from 291.9 MPa RMS bare to 256.2 MPa with nylon (12.2%) and 286.5 MPa with aluminium (1.9%). Aluminium raised the middle cell's two strip peaks by 2.6% and 2.7% relative to bare.




Figure A.15: Native one-sigma equivalent stress, maximized separately in each nickel strip. Low and high Y identify the strip ends near board coordinates 22 and 99 mm. Left, middle and right refer to increasing board X. For every strip, its maximum stayed at the same element corner across screw choices.

The assumed nickel yield stress is reached while the cells still clear the case

The global model uses linear elastic nickel with modulus 220 GPa. The separate October nonlinear pull model assumes a 185 MPa initial yield stress for annealed nickel and a modulus of 205 GPa. To compare the two, we reconstructed the global *signed* stress history during the first 0.1 s of the seeded October base-X waveform. At each sampled instant we added the six stress components from the locked preload to their respective dynamic components, then calculated von Mises stress at each corner. Independent spectral integration also reproduced all six native RMS component fields and the stored equivalent-stress field to within 0.0033% relative field norm.

First sampled crossing of 185 MPa	Bare	Raised / nylon	Raised / aluminium
Base X, time bracket [ms]	38.116–38.132	38.956–38.971	38.116–38.132
Peak after tightening alone [MPa]	161.9	162.1	162.1
Base X, minimum clearance bound [mm]	—	0.038	0.068

Table A.5: Each time refers to this excitation with its prescribed 0.1 s ramp. The material threshold is a property assumed in the local model. Actual strip temper and weld properties would be needed to infer yielding or fatigue life.

The clearance check covers every quadratic exterior face on all three cells and the PLA. At the tightened position their separation exceeded 0.130 mm. We bounded the subsequent motion of each face by tracking its quadratic Bézier control points in a common translating frame at 65,536 samples/s. The two bodies' maximum excursions summed to 0.092 mm with nylon and 0.062 mm with aluminium through their respective threshold crossings. This places the early stress excursion before direct cell-to-case contact in both calculations. The air gap can close later in the same waveform (pages 10 and 15).

With base Z excitation, only the raised aluminium model crossed 185 MPa during the first 100 ms. The first crossing occurred at 77.911–77.927 ms on the middle cell attachment (STEP body 17). The same moving-surface bound gave at least 0.0256 mm of cell-to-case clearance through that sample. With base Y, all three models stayed below the reference throughout the 100 ms window.

The local flush fixture exceeds the printed-PLA tensile references early in tightening

The four outer washers first loaded the nylon-screw fixture at 0.59–0.63 mm of screw-head travel. Between 0.91 and 0.95 mm, the greatest tensile stress in the assumed print plane crossed 52.3 MPa. Through-layer tension crossed 40.5 MPa between 0.99 and 1.03 mm. These are typical tensile strengths for the 100%-infill reference coupons. Comparing the native true stresses with these nominal coupon strengths gives an approximate check on the range of the elastic model. Polymaker coupon data.




Figure A.16: Native converged local states with rigid neighboring hardware and prescribed screw-head travel. Left, maximum tensile stress over the 16,108 quadratic PLA elements. Right, section-node tension including bending and the direct axial component in the four idealized short screw shanks. Curves stop at the last sampled travel before loaded penetration first exceeded 0.05 mm.

Local material reference	First corner crossing [mm]	First element with all four corners above [mm]
In-plane tension, 52.3 MPa	0.91–0.95	1.55–1.59
Through-layer tension, 40.5 MPa	0.99–1.03	2.57–2.61
Through-layer elongation, 1.8%	1.23–1.27	No sampled element

Table A.6: The coupon elongation corresponds to logarithmic strain $\ln(1.018) = 0.01784$. The first in-plane and through-layer stress crossings occurred 3.72 and 3.78 mm from the nearest coupled bearing node. Contact penetration already exceeded the local screen by the time all four corners of an element crossed the through-layer stress reference.

At 0.95 mm travel each prescribed screw head carried 64.0–64.5 N along board Z. The largest direct axial screw stress was 7.37 MPa. Including bending, the most tensile modelled screw fibre reached 85.34 MPa. A rigid connection between the screw rotation and its bearing footprint strongly influences that value. The McMaster-Carr listing for the representative nylon screw (93640A145) gives its dimensions and lists tensile strength as unrated. Its installed strength, head rocking and thread engagement therefore remain unverified. McMaster-Carr screw data.

How much moment each tab bearing carries

At 0.91 mm of screw travel, before the first coupon crossing, the four local tab bearings carried 56.5–56.9 N each along board Z. For each bearing, we summed the axial nodal forces $F_{z,i}$ and their first moment about the screw axis. The equivalent offset $e = \|\sum_i \mathbf{r}_{xy,i} F_{z,i}\| / |\sum_i F_{z,i}|$ was 4.44–4.46 mm. Pressure acting in one direction inside a circular footprint of radius R gives $e \leq R$. For the modeled $R = 3.75$ mm, reproducing the observed moment using axial forces alone would require at least 5.2–5.4 N in the opposing direction per bearing. Forces from the printed solid and the screw/seat assembly agreed within 0.000003 N and moments within 0.00001 N mm. An actual joint can also transfer moment through the shank, thread or head restraint.

For comparison, tightening the six original bolts in the raised full-board models produced a maximum case-screw fibre tension of 1.15 MPa with nylon and 1.63 MPa with aluminium. Neither raised case reached a printed-PLA coupon reference during tightening. The local flush trial subsequently crossed the board datum (page 11). Resolving the force required for an actual flush seat depends on the full-board contact path and the as-built material and joint behaviour.

The left and centre cells reach the raised nylon case in the X movie

The open-gap model puts the cell and PLA skins into intersection in frames 253–270 of the 480-frame X-axis movie. That is 4.20–4.48 s into playback, at 1.015442–1.016479 s in the load record. Checking all 1,917 integration samples in the clip identified two cells. The centre cell crossed first, then the left cell one sample later. The right cell stayed clear. All three stayed clear throughout the film interval for the other five mount and excitation combinations.




Figure A.17: Left, the cell and PLA surface check repeated at every displayed instant for each 3 mm mount and input axis. Right, the exterior surfaces at frame 262, cut in a plane through the closest PLA point and the most deeply embedded sampled cell vertex. Both section axes use the same scale.

Cell	Entry bracket [ms]	Exit bracket [ms]	Overlap at 15.869 ms [μm]
Left	15.335–15.350	16.388–16.403	12.1
Centre	15.320–15.335	16.418–16.434	11.3
Right	Clear at all 1,917 samples		—

Table A.7: Physical time from the first movie sample. The 15.26 μs integration step brackets entry and exit. Overlap is the sampled cell-vertex depth inside the curved PLA skin at one common instant. The nine-second MAPDL runs reproduced the independent surface classifications at all 1,917 movie-interval samples for both raised mounts and all three input axes.

At each mount's own peak dynamic PCB stress in the X clip, the smallest sampled cell-vertex gap was 0.149 mm at frame 228 for nylon and 0.146 mm at frame 290 for aluminium. The fixed-contact motion calculation omits any change in stress or trajectory caused by earlier contact.

Sensitivity to integration step and modal cutoff

Independent integration displaced all 8,038 exterior quadratic PLA faces and all 938 cell faces. Subdividing their convex hulls established separation at clear samples. Two successive triangle refinements confirmed each crossing. The full closed skins gave 15.0 μm of sampled overlap with four segments per edge and 14.6 μm with eight at frame 262. The movie magnifies movement 50 times. The section above uses physical displacements.

For the nylon X history we halved and quartered the integration step, holding the piecewise-linear acceleration input fixed. Relative to the exact response of the modal oscillators to that input, the modal-coordinate differences fell from 0.401% to 0.100% and 0.025%. All three time steps and the exact integration gave the same entry and exit brackets at the original sampling times. Retaining 35 modes through 2.95 kHz or 39 through 3.44 kHz gave the same brackets as the full 49-mode basis. Impact forces still require a contact-response calculation. Raised cases under X-axis excitation.

The flush tabs make edge contact while most of each face stays open

With nylon screws all four tabs first carried pressure between 2.60 and 2.675 mm travel. With aluminium all four were still clear at 2.90 mm and carried pressure at the final 3.00 mm equilibrium. Even there only 18.3–18.9% of each aluminium-mounted tab lay within 0.05 mm of the board. The far sides retained 2.43–2.44 mm gaps. Both models exceeded the printed-PLA tensile references before tab contact. The resulting shapes describe an elastic continuation beyond the material data.




Figure A.18: Near-seat area throughout the last increments. Lines mark the largest fraction among the four feet and shading spans their range. The maps show the high-X, low-Y tab at each trial's last equilibrium. White marks the bore, and the darkest blue denotes gaps of 0.25 mm or greater.

Tab position	Nylon near-seat area [%]	Nylon largest gap [mm]	Al smallest gap [mm]
Low X, low Y	4.4	2.425	0.218
Low X, high Y	4.7	2.422	0.217
High X, low Y	5.1	2.417	0.204
High X, high Y	4.9	2.418	0.210

Table A.8: Near-seat area is the fraction of each overlapping tab footprint within 0.05 mm of the board. It was zero at every aluminium-mounted tab. All quantities are at 2.75 mm screw travel.

With nylon, the first through-layer tensile stress crossed 40.5 MPa between 0.95 and 1.10 mm, at a node tied to the idealized screw bearing. In-plane tension crossed 52.3 MPa at 1.10–1.25 mm. When the search excluded points within 2 mm of tied bearing nodes, both references were first crossed at 1.25–1.40 mm. The latter interval follows the first crossing of the 15 μm hardware-penetration screen (1.10–1.25 mm). At 2.75 mm the contact field reached 71 μm penetration. The nylon trial stopped at this equilibrium after three cutbacks. An installation-load rating requires measured print and contact behaviour.

The combined nylon result reproduced all 28 equilibria. The hardware contact audit included all 8,038 PLA contact faces. At 0.95 mm travel, before the first coupon crossing, the four original outer battery bolts gained 10.3–14.0 N above their 750 N locked preload. The two centre bolts changed by −0.9 and +1.4 N. At 0.95 mm the four drives supplied 25.59 mJ of work (28.41 mJ using alternate saved states). The PCB gained 8.81 mJ of stiffness energy, the PLA 8.01 mJ and the four screws 6.59 mJ. All element groups together accounted for 24.59 mJ.

Aluminium screws increase the load at the same drawdown

In the two whole-board trials the screw shank geometry was identical. Only modulus, Poisson ratio and density differed between the decks. The first loaded hardware contact fell between 0.50 and 0.65 mm of relative travel for both mounts. At 0.80 mm, the four drives together carried 80.0 N with nylon and 115.6 N with aluminium. Peak through-layer PLA tension was 18.2 and 37.2 MPa respectively, against the 40.5 MPa coupon reference. With aluminium, both the in-plane and through-layer tensile references were first exceeded between 0.80 and 0.95 mm, while all four tab contacts remained open. In the 0.80 mm aluminium snapshot only the four outer washers intersected the PLA. Refining the curved surfaces gave up to 24.0 μm of sampled washer overlap, compared with 7.9 μm at loaded native contact corners. The smallest sampled cell clearance was 0.066 mm. At 3.00 mm travel, only the four outer washers intersected the PLA. Maximum sampled washer overlap was 0.136 mm and loaded native contact penetration was 0.109 mm, above the 0.015 mm screen. The three cells remained clear. A physically supported flush vibration state remains unresolved.

The raised nylon case lowers the transverse load on all three cells

Under base-X vibration, the X component of the right-hand cell's net dynamic force fell from 30.51 N RMS bare to 26.67 N with nylon screws and 29.73 N with aluminium. These are reductions of 12.6% and 2.6%. Nylon also reduced this load on the left and centre cells. Aluminium raised the centre-cell load from 25.60 to 26.28 N RMS. The PSD calculation keeps the tightened cell-to-case gap open. The two nickel attachments on each cell therefore carry its net dynamic load until additional contact occurs.




Figure A.19: Net force component parallel to each of three separate base excitations. Markers within each group correspond to the same physical cell. The ordinate is shared across panels. The material model gives each cell a mass of 55.38 g.

Base X, cell force [N RMS]	Bare board	3 mm / nylon	3 mm / aluminium
Left	29.97	28.51	29.80
Centre	25.60	25.13	26.28
Right	30.51	26.67	29.73

Along the excited direction, the Y and Z cases changed by less than 0.13 N on each cell. A transverse component can still grow. With Y input the X force on the left cell was 0.12 N RMS bare, 1.75 N with nylon and 1.01 N with aluminium. Page 22 compares the signed forces at both cell-to-nickel attachments.

Mass averaging and verification

For each native mode we integrated the signed translations over each curved ten-node cell tetrahedron with its material density. The relative acceleration transfer function follows from differentiating modal displacement twice. We added the common base acceleration before integrating over the 20–2000 Hz spectrum. Combining the signed quantities in this order accounts for phase cancellation within the cell. Multiplying the resulting centre-of-mass acceleration by cell mass gives the force.

The four- and five-point-per-coordinate volume rules agreed within 10^{-9} in relative norm. Reducing the upper modal cutoff from 4 to 3.5 kHz changed the driven-axis forces by at most 0.30%. Independent nodal acceleration RMS fields matched all nine native PSD fields within 0.044% in relative norm over cell nodes. Separately, the original bare-board native time histories and original signed shapes reproduced the independently integrated seeded cell accelerations within 0.0075%.

For the eight stationary seconds of the historical forcing, the driven-axis RMS loads differed from the continuous-spectrum estimates by at most 0.88%. The largest discrepancy over all components was 10.4% and occurred in a smaller transverse component. Evaluating the same sampled waveform with the discrete Newmark transfer function reproduced the time integration. At one-quarter of the historical time step, its largest discrepancy from the continuous-frequency response at the same Fourier bins fell to 0.59%.

The raised case preserves the first unpreloaded mode

The first default-contact mode remained at 66.61 Hz for the bare board and both raised cases. The signed displacements of the 368,754 original solid nodes give a modal assurance criterion (MAC) above 0.999999 for both screw materials. The 20th modes tell a different story. Although each is the 20th frequency in its own assembly, the three shapes differ substantially.




Figure A.20: The upper panel orders each assembly's 20 native frequencies. The lower panel compares the bare and cased displacement vectors at equal rank. A value near one means that the original solid nodes moved in the same relative pattern.

Mounting	Mode 1 [Hz]	Mode 20 [Hz]	Mode 20 MAC to bare
Bare	66.611	2247.59	1.000
3 mm, nylon screws	66.614	1732.16	0.042
3 mm, aluminium screws	66.615	1847.75	< 0.001

The closest shape to bare mode 20 within either raised set was mode 19. Even those correlations were weak (0.129 for nylon and 0.137 for aluminium). The displayed aluminium mode 20 instead matches bare mode 14 at 1847.75 Hz (MAC 1.000). A matching shape for bare mode 20 may lie above the extracted range.

Reading the mode movies

Both default-contact movie pairs preserve the October mode ranks, a common colour range, and a 6 mm peak display amplitude. The raised panels identify the screw material, native frequency and shape correlation. These runs retain the original unpreloaded contacts. The tightened assembly has different equilibrium contact conditions and prestressed frequencies (page 8). Across the full catalogue, all 22 subjects now have a bare view and a comparison of both raised configurations. The flush assemblies still need an admissible installed state before their vibration fields can be shown.

The two cell attachments carry opposing lengthwise forces

The raised nylon case reduced the X force at both ends of all three cells under X excitation. Under Z excitation, however, both raised cases increased the force along the cell axis (Y) at all six attachments. The largest change occurred on the right-hand cell. The two ends carried 2.07 and 1.54 N RMS bare, 4.14 and 3.91 N with nylon screws, and 3.55 and 3.33 N with aluminium screws.




Figure A.21: Each line joins the low-Y and high-Y ends of one cell. Left, the X force for base X. Right, the lengthwise Y force for base Z. Each marker gives the one-sigma force integrated over a complete cell-to-nickel attachment.

Why the whole-cell force can stay small

For the right-hand cell under base Z, the two lengthwise force histories had correlations of −0.88 bare, −0.97 with nylon and −0.97 with aluminium in the spectrum calculation. When the signed forces were added before taking RMS, the corresponding net loads were only 1.03, 0.99 and 0.90 N. The opposing forces matter to the individual attachments even when they nearly cancel across the cell.

Right cell, base X	Bare	Raised nylon	Raised aluminium
Low-Y end, X force [N RMS]	15.33	13.40	14.94
High-Y end, X force [N RMS]	15.19	13.27	14.80
Combined X force [N RMS]	30.52	26.66	29.73

Force recovery and checks

Both sides of each bond were identified from the native contact and target connectivity. For each tightened mode, the assembled solid-element stiffness and inertia forces cancel at free cell nodes. Summing the residuals on a bonded face gives its signed modal force. The adjacent nickel strip reproduced the opposite resultant to within 0.00032% in vector norm for every mode. Independent frequency integration then combined the six bond resultants over the original base spectrum with 2% modal damping.

For 90 sampled cell and nickel elements, the independently combined stiffness-force components agreed with all nine native PSD cases within 0.0056% in relative norm. Under base X the summed X loads agreed with the whole-cell inertia calculation (page 20) within 0.42%. Across Y and Z the corresponding differences reached 4.73% and 2.16%. Removing modes above 3.5 kHz changed any component by at most 0.362 N. The original October mode forces and native coordinates reproduced all 480 bare-board movie frames for all three drives within 0.00043 N per component.

The bonds cover the areas joined in the model. Actual weld sizes, local separation and the response after cell-to-case impact remain unmeasured.

Case support shifts the peak dynamic load at the nickel attachments

For each of the three original nine-second acceleration records, we recovered all three force components at both nickel attachments on each cell. We took the vector magnitude at each of the 589,825 saved instants, then found the largest magnitude across the six ends. These forces describe the extra load from vibration above the locked preload in the linear model.




Figure A.22: Left, the maximum at a single cell end under each base direction. Right, the simultaneous signed components at the low-Y end of the right-hand cell. All three assemblies reached their base-Z maximum there at 1.86743 s. The positive lengthwise force increased with both raised mounts.

Drive	Bare [N]	3 mm nylon [N]	3 mm aluminium [N]	Governing attachment
Base X	69.39	66.39	68.23	Left cell, low-Y end
Base Y	29.25	29.17	29.79	Left cell, end varies
Base Z	30.22	32.21	33.30	Right cell, low-Y end

Table A.9: Largest dynamic force magnitude at one cell-to-nickel bond over the full record. Under base Y the bare and nylon peaks occur at the high-Y end and the aluminium peak occurs at the low-Y end.

Under base X the peak end load fell by 4.3% with nylon and 1.7% with aluminium. Under base Z it rose by 6.6% and 10.2%. At the base-Z peak the Z component stayed close to −29 N in all three assemblies. The lengthwise component rose from 8.17 N bare to 13.21 N with nylon and 15.32 N with aluminium. The force on an individual attachment can therefore grow even while the two lengthwise end loads partly cancel across the cell (page 22).

Response before the nickel yield reference is reached

The first 38.116 ms of base X precede the first sampled exceedance of the local pull model's 185 MPa nickel reference in any assembly (page 16). Over this common interval, the right cell's low-Y end carried the largest force in all three assemblies. Its magnitude reached 9.57 N bare, 8.92 N with nylon and 9.50 N with aluminium. The bounds on the raised assemblies' relative surface motion leave the cells clear of the PLA through this interval. The full-record peaks above include later excursions beyond the elastic and fixed-contact assumptions.

Numerical checks and physical scope

The main results use signed native MAPDL time histories and bonded-interface forces from the prestressed modes. A separate integration of the same base motion reproduced the complete force fields within 0.002% in relative norm. Restricting the modes to 3.5 kHz changed the nine peak magnitudes by at most 1.09%. The bonded end area idealizes the battery-to-nickel attachment. The model supplies a dynamic resultant over that area. Predicting a weld failure load requires the actual weld geometry and material response.

During startup, screw material changes which limit appears first

In the raised aluminium mount under base X, tension across the assumed print layers reached the 40.5 MPa coupon mean at 63.54 ms. The first sampled cell-to-case intersection followed at 69.78 ms. With nylon screws the middle cell first intersected the case at 85.34 ms, while both PLA tensile stresses stayed below their respective coupon means throughout the 100 ms ramp. The nickel model had already exceeded its separate trial yield reference under X in all three assemblies (page 16).




Figure A.23: Peak tensile stress over 6,555 samples of each native waveform, including the locked preload. Bars include all 64,432 PLA element corners. White markers give the maxima among corners at least 2 mm from any node tied to a screw bearing. Dashed lines mark the coupon means.

		First sampled event [ms]			Cell gap at layer
Screws	Base	Layer tension	In-plane tension	Cell intersection	crossing [mm]
Nylon	X	—	—	85.34	—
Nylon	Y	—	—	—	—
Nylon	Z	—	—	—	—
Aluminium	X	63.54	85.21	69.78	0.035
Aluminium	Y	77.45	—	—	0.135
Aluminium	Z	81.39	—	—	0.132

Table A.10: Times identify the first integration station meeting each criterion. The previous station was 15.26 μs earlier. Dashes in the three event columns mean the criterion was absent through 100.006 ms. Gap is the minimum sampled cell-vertex distance from the case across all three cells at the layer crossing.

The three aluminium layer crossings occurred within 0.54 mm of a node tied to a screw bearing. Outside the 2 mm band, both stresses remained below the coupon means for every input and screw material. On the aluminium X path, a cell surface was already inside the PLA when in-plane tension reached 52.3 MPa. The local bearing representation matters to the stress maximum. The comparison identifies where the fixed-contact, elastic calculation first reaches these particular screens. Failure of an actual printed tab depends on its print and bearing conditions.

Checks on the order of events

Signed modal stresses were added to the locked stress tensor before evaluating layer-normal tension and the greatest in-plane principal stress. The search covered both screw mounts, all three base inputs and every stored station. The exact response of each modal oscillator to the piecewise-linear input reproduced the native tensile crossing brackets. Omitting modes above 3.5 kHz preserved those brackets and the first base-X cell crossing for both mounts. Independent integration shifted the first aluminium X intersection by one sample (15.26 μs) and reproduced the nylon onset. The cell check used the complete curved exterior surfaces. A separate intersection test at two surface refinements confirmed the cell states at the four aluminium tensile crossings.

With nylon screws, the raised PLA case carries most of the pull at 0.50 mm

The bare fixture and the raised fixture with nylon screws used the same nominal nickel damage law, 2,304 shell elements and two 750 N washer clamps. At a prescribed 0.500 mm of sideways travel, the bare edge cell required 11.33 N. The raised case required 141.82 N, of which the four case screws carried 112.62 N (79.4%). At this displacement the neighbouring-cell support carried no net X load. The largest tensile stresses in the PLA were 28.75 MPa in the print plane and 23.60 MPa across the layers.

Local sliding at the washer–nickel interfaces began in the same 0.0500–0.0875 mm travel interval in both fixtures, before the cell touched the case. At 0.500 mm the peak element-averaged frictional stress rose from 0.801 MPa bare to 1.144 MPa cased, and peak accumulated tangential motion rose from 1.29 to 1.77 μm. Ten bare and eleven cased contact corners registered sliding. Every face with a sliding corner also retained a sticking corner.




Figure A.24: Left, dashed lines join the original interval endpoints. The solid lines use 64 refined increments and coincide at 8.54 N. With nylon the native contact pair first carried load between 0.21191 and 0.21240 mm. Right, the load paths through the last station below the PLA and contact limits. The local fixture holds the other cells and the case screw tops fixed.

Nickel model	Bare travel at 8.54 N	Raised travel at 8.54 N	Force at 0.50 mm, bare / cased
Bilinear	0.500 mm	0.207 mm	8.54 / 138.53 N
Multilinear with damage	0.20190 mm	0.20190 mm	11.33 / 141.82 N

Table A.11: At 8.54205 N the refined bare, nylon and aluminium multilinear fixtures all gave 0.201904 mm between the same two saved stations. Both cases carried zero contact force there. At 0.212402 mm the first loaded face carried 0.114 N with nylon and 0.210 N with aluminium. The forces at 0.50 mm are saved equilibria for bare and nylon.

Printed-material scope and the last equilibrium

The fixed neighbour began sharing the load between 0.625 and 0.675 mm of cell travel. At 0.675 mm the applied pull was 389.45 N. The case screws carried 176.89 N, the fixed neighbour carried 147.66 N and the original clamps carried 64.90 N. Between 0.675 and 0.725 mm the peak in-plane tension first exceeded the 52.3 MPa printed-coupon mean. The crossing occurred 4.36 mm from the nearest coupled bearing node. The first through-layer stress crossing followed at 0.800–0.825 mm. These local results depend on the actual stiffness of the mounts and neighbouring cells.

ANSYS retained 59 converged states, including 50 pull states, through 0.923275 mm. It terminated when the next increment failed to converge after cutbacks. None of the three nickel section summaries reached the 10^{-4} damage reporting threshold at any converged state. The two strips retained a graph path from the modelled battery attachment to the clamp at every station under the original October 0.99 section-damage diagnostic. The later equilibria extend beyond the onset of the printed-material limit. The contact-position comparison on page 5 also limits the interpretation of the low-load response. The physical rupture load remains unresolved.

How the raised case changes strain in the nickel strips

The three local fixtures used the same 2,304 nickel shell elements, multilinear plasticity and damage law, and 750 N washer preloads. In positive X, both original raised contact pairs first carried load between 0.1875 and 0.21875 mm. The STEP surfaces already intersected at the lower station (page 5). The last travel saved at exactly the same value in all three models before either raised fixture exceeded its material limits was 0.3375 mm.

Fixture	Cell pull [N]	Case screws [N]	Strip clamps [N]	Peak nickel plastic strain
Bare	10.15	—	10.15	0.673%
3 mm, nylon	63.82	46.30	17.52	0.727%
3 mm, aluminium	125.98	100.18	25.81	0.783%

Table A.12: Native reactions at 0.3375 mm. The fixed neighbour carried no lateral reaction at this travel. The maximum strain occurred in the same flat nickel shell element in all three models.




Figure A.25: Each marker is a converged native state. The vertical line marks the 10.15 N reaction of the bare fixture at 0.3375 mm. Curves connect neighbouring states. Strain is the maximum element-averaged equivalent plastic strain across the three saved shell sections.

At equal travel, the aluminium fixture took almost twice the force of the nylon fixture. Both cased cells also strained the nickel more than the bare cell. At equal force, the comparison reverses. The cased stations bracketing 10.15 N had peak strains of 0.260–0.349% with nylon screws and 0.260–0.352% with aluminium, compared with 0.673% at the bare station. The load bracket spans first contact in both cased fixtures. The difference between the screw materials at that force remains unresolved.

Where the aluminium result reaches its material limit

At 0.425 mm the aluminium fixture carried 218.57 N, including 179.80 N through its four case screws. At the next saved equilibrium, 0.475 mm, in-plane PLA tension reached 60.16 MPa and through-layer tension reached 44.10 MPa. Both exceeded the printed-coupon means (52.3 and 40.5 MPa), within 0.54 mm of a tied screw-bearing node. With nylon screws the first tensile crossing occurred later, between 0.675 and 0.725 mm.

The aluminium solve retained 37 lateral equilibria through 0.87435 mm and stopped on the next increment. All 37 passed the original force-balance checks. The largest loaded-corner penetration was 0.0439 mm against the 0.05 mm local contact screen. Both nickel strips retained their modeled load paths and all three section damage summaries remained zero. The late equilibria exceed the PLA reference range, and the physical rupture load remains undetermined.

Nickel material-law check

Three single-element tensile coupon reruns reproduced the October reaction, transverse displacement, axial stress, equivalent plastic strain and damage at all 1,074 shared stations. The peak reactions lay between 66.87 and 66.89 N. All three paths softened and stopped before the requested 1 mm extension. These numerical coupons verify the implemented material law. Predicting separation of the assembled strips also requires material and attachment measurements.

How the vibration loads compare with component strength

The high through-layer tension occurs in the **printed PLA tab beside the screw bearing**. The four case screws change how force enters the tab. For the assumed print, the manufacturer's tensile specimens reached a mean of 40.5 MPa across the layers and 52.3 MPa in the print plane. Each percentage below is the largest tensile stress in the stated record divided by its corresponding coupon mean. These ratios include bolt preload.




Figure A.26: Dashed lines mark 100% of mean coupon strength. Left: peak signed through-layer stress at the bearing corner with the highest layer-normal RMS for each nine-second test. Centre and right: maxima over all PLA corners during the first 0.1 s. X, Y and Z were separate base excitations.

For board-normal vibration the monitored PLA tab reached 56.2 MPa with nylon screws and 104.2 MPa with aluminium screws. Both peaks occurred with the sampled cell and case skins clear at that instant. The linear model continues to store elastic stress beyond the coupon strength. At these peaks, actual load redistribution or cracking would require the print properties and screw-bearing compliance of the installed case. The earlier aluminium startup crossings occurred within 0.54 mm of a node tied to a screw bearing.

Other components

Nickel strips. The nickel damage model assumes 185 MPa initial yield. Bolt tightening alone reached about 162 MPa (88% of this reference). Under base X the signed, preload-inclusive stress crossed 185 MPa in all three assemblies within 39 ms (page 16). The actual temper and weld geometry are needed to assess strip rupture or fatigue life.

Board and soldered parts. Board-normal base vibration produced 32.5, 64.8 and 84.2 MPa RMS in the equivalent PCB material for bare, nylon and aluminium, respectively. These statistical stresses show how the board response changes. A strength margin for a populated assembly requires the actual laminate allowables and package-specific limits on local board strain or solder fatigue.

Case screws and cell attachments. At 0.3375 mm lateral travel the modeled peak tensile screw-fibre stresses were 13.1 MPa (nylon) and 34.2 MPa (aluminium). The nylon reference screw has no rated tensile strength in its listing, and the aluminium alloy and temper are unspecified. The attachment calculations give force over the idealized bonded footprint. A tested weld strength is needed to turn that force into a margin.

Printed PLA tensile data | IPC/JEDEC guidance on measuring board strain near components

A 2.5 mm stand-off leaves clearance at the lips and under the cells

For the supplied Balius STEP at its nominal hole alignment, four outer washers set the closest rigid mounting position. They first touch at a 2.397 mm tab-to-PCB spacing. At 2.500 mm they clear by 0.103 mm. The cells approach the sides of their circular pockets much more closely than the floors.




Figure A.27: Section at the case midspan using the STEP profile and 10.700 mm cell radii. The 1.32 mm dimension is vertical beneath the middle cell. Washers and mounting tabs sit outside this plane. The drawing uses the same scale for both axes.

Tab-to-PCB spacing	Left cell minimum	Middle cell minimum	Right cell minimum
2.400 mm	0.082 mm	0.065 mm	0.082 mm
2.500 mm	0.093 mm	0.076 mm	0.093 mm
3.000 mm	0.161 mm	0.144 mm	0.161 mm

Shortest three-dimensional surface distances between each undeformed cell and the case. The 2.400 mm setting leaves just 0.003 mm between the case and the first four washers.

Holding the board and cells fixed, the middle cell would first touch as spacing fell to about 1.240 mm, then the outer cells near 1.210 mm. Reaching either position requires interference with the existing washers. A 2.5 mm spacer can therefore give a close nominal side fit, while simultaneous supported contact of all three rigid cells requires a change to the installation geometry or compliance. Actual print dimensions, washer stack and cell positions determine the as-built clearances.

Which battery case fits the archived board?

The Balius SolidWorks part gives the closest nominal fit of the three files examined. The supplied Balius STEP and the fresh native export share the same three cell-pocket axes and radii. The native part provides additional space around the washers. SolidWorks 2026 SP4.1 exported the default configuration of each native part to AP203 STEP with zero reported errors or warnings. Each export reopened as one solid.




Figure A.28: Midspan sections at equal scale. For this pocket comparison, the middle cell axis coincides with one pocket axis in each direction. Red marks where the outer cells intersect the Zphr case in this pose. The mounting holes are checked separately.

Balius at 1.25 mm tab-to-board spacing

A rigid sweep over the 35 archived hardware solids found that the native part reaches the middle cell first at 1.240 mm stand-off. The outer cells reach their pockets at 1.210 mm if the geometry is allowed to continue through first contact. The earliest outer-washer contact in that continuation is at 0.733 mm. With the original supplied STEP, the washers touch at 2.397 mm, before any cell can reach its pocket.

Case and tab spacing	Middle cell gap	Outer cell gaps	Smallest outer-washer gap
Supplied Balius STEP, 2.50 mm	0.076 mm	0.093 mm	0.103 mm
Balius native export, 2.50 mm	0.076 mm	0.093 mm	1.250 mm
Balius native export, 1.25 mm	0.003 mm	0.020 mm	0.328 mm

At 1.25 mm all three cells sit close to the native pockets. The small clearances depend on the actual print, battery sleeves, washer stack and board alignment. The reported structural and vibration results use the originally supplied STEP.

Zphr pocket and screw alignment

Zphr has six pockets of radius 11.000 mm and pitch 25.623 mm. The three 10.700 mm-radius cells have adjacent pitches of 23.893 and 23.859 mm. Centring the middle cell in a Zphr pocket puts the outer cell axes 1.729 and 1.764 mm off-centre in the neighbouring pockets. The available concentric radial clearance is only 0.300 mm.

The 14 Zphr bores have 3.400 mm through diameter. Comparing inter-hole distances over every assignment of four bores to the board corners proves that at least one centre is displaced by at least 10.525 mm under any rigid planar alignment. A nominal M3 screw can accommodate only 0.800 mm of centre offset across the case and PCB bores. Changing stand-off alone cannot register this pattern.

The raised case engages later when the pull reverses

We pulled the same outer cell in both directions along PCB X. For each mounting configuration, the two solved input decks had the same geometry, clamp preload, bilinear nickel law and load increments. The only numerical change was the sign of the prescribed cell travel. Each native result contains 33 converged equilibria.




Figure A.29: Applied cell force at equal travel magnitudes for the bare board and the two 3 mm mounts. Dashed segments follow the linear PLA model beyond its first printed-material reference. All six curves use the October bilinear nickel law. The multilinear nickel results are on pages 25–26.

Force at a common displacement

At 0.420625 mm, all six fixtures remained within the printed-material and contact-penetration screens where applicable. The bare forces in opposite directions differed by only 0.027 N. Reversing the pull reduced force by 70% with nylon case screws and 76% with aluminium screws.

	Applied cell force [N]		Via four case screws [N]	
Mount	$+X$	$-X$	$+X$	$-X$
Bare	8.26	8.24	—	—
Nylon	100.99	30.17	80.00	18.91
Aluminium	209.96	49.42	174.54	35.58

Force magnitudes at 0.420625 mm of cell travel. Each value comes from a saved native equilibrium. The original nickel clamps carry the remainder in these fixtures.

Clearance and first load

Under a pure X translation of the undeformed STEP cell, the gap first closes after 0.163 mm toward positive X and 0.308 mm toward negative X. In the native fixtures the cell can also rotate. The moving-cell contact pair first registered closure between 0.196–0.221 mm in positive X and 0.346–0.371 mm in negative X for both screw materials. The later engagement leaves less reverse travel over which the case can take load.

At 0.500 mm in negative X, the applied force was 8.51, 64.73 and 113.46 N for the bare board, nylon and aluminium respectively. The corresponding maximum nickel plastic strains were 1.252, 1.346 and 1.434%. Peak in-plane PLA tension at that reverse endpoint reached 23.58 MPa with nylon and 43.07 MPa with aluminium (45% and 82% of the 52.3 MPa coupon mean). Both reverse paths stayed within the recorded contact and PLA screens. The fixed screw tops represent a local fixture. These loads describe a prescribed displacement and do not establish a rupture load.