

The three-pocket Balius case fits at 1.25 mm stand-off




The dense PLA shell adds 73.7 g to the 251.8 g bare board. The middle-cell clearance is 0.003 mm and the closest washer clears by 0.328 mm. In the local pull model the left cell first reaches its pocket at about **1.14 N toward the middle cell** (0.020 mm) or **6.7 N away** (0.165 mm). The forces come from the bare strips up to contact.

The snug case increases board travel in the seeded clips




During the displayed base-Z interval, PCB travel normal to the board reached **0.168 mm bare**, **0.390 mm with nylon screws** and **0.248 mm with aluminium**. All 22 paired movie subjects are available.

Balanced nylon pocket force agrees across two meshes




With the 0.01 N force criterion, the 2 and 1.5 mm nylon meshes give **0.5684 and 0.5716 N** at lock, a **0.55% difference**. All saved mounting-force balances pass. Local peak pressure still changes by **18.4%**. Across the tested meshes, peak PCB deflection falls about **39% with nylon** and **51% with aluminium** relative to bare.

Stiffer screws raise local restraint and contact pressure




At 0.2069 mm, aluminium requires **243 N versus 110 N with nylon**. At 0.2194 mm both cases load the fixed middle cell: forces become **598 versus 538 N**, only 11% apart. The middle cell carries 349 and 424 N respectively. Driven-cell peak pressures are **49.9 and 30.0 MPa**; mesh convergence remains open. The fixed neighbours make this a local-fixture result.

Aluminium cuts board travel relative to nylon but raises base-Z stress




Under base Z, peak PCB stress was **32.5 MPa RMS bare**. Refining the case gave **69.8 MPa with nylon** and **94.3 with aluminium**. Filled markers are native spectra. Open markers integrate the finer native modes independently. All retain the installed contact state.

Board-normal vibration loads the middle cell's nickel bond




The largest base-Z bond load rose from **30.2 N bare** to **40.1 N with nylon** and **50.5 N with aluminium**. The finer meshes gave **48.8 and 53.3 N**. All cased base-Z peaks occur at the middle cell. Bars use native histories. Diamonds integrate the finer native modes independently.

The middle pocket unloads and carries force again




Under base Z, the original pocket points first all unloaded at **5.61 ms with aluminium** and **11.54 ms with nylon** (11.64 ms on finer nylon). At 28.79 ms the middle cell cleared the nominal meshes by **3.90–4.01 μm with nylon** and **1.73–1.84 μm with aluminium**. A separate native projection preload gave zero force despite 0.128 μm of surface overlap. Contact resolution remains open.

PLA demand exceeds its coupon reference with aluminium screws




Refinement shifted the largest through-layer demand to **71.5% of the coupon mean with nylon** and **210.8% with aluminium**, both under base X. Horizontal marks exclude the 2 mm bearing band. Fine screw peaks were **37.4 and 96.2 MPa**; two integration methods agreed within 0.302%. These elastic histories retain the installed contact state.

Under base X, the left and middle cells move closer together




The left cell's peak travel relative to its clamps fell by **29% with nylon** and **12% with aluminium**. Rotation accounted for **82%** of that travel in all three assemblies. With the middle cell free to move, peak approach rose from **19 μm bare** to **85 and 71 μm**. Contact stays fixed at bolt lock in these native histories.

M4 tension raises the vibration level for a pocket contact change



With **1 N mean M4 tension**, a new pocket point touched at about **0.0085** g **RMS with nylon** and **0.0068** g **with aluminium** on the 2 mm mesh. On finer nylon, a point that opened during tightening seated again at **0.0011** g. These are modeled contact changes under the board-normal waveform. Actual screw tension is unmeasured.

Outer-cell contact timing is still sensitive to the case mesh



Under base X, the 3 mm mesh puts the **right pocket first**; the 2 and 1.5 mm meshes put the **left first**. Base-Y timing is nonmonotonic with refinement. All shown trajectories retain the installed contact state. A separate native curvature control failed the mounting-force balance; a tighter repeat is queued.