MED Library C API version 1.0.1

(medlib_m11)

Library Naming & Tags:

- Format versions will be named as: "MED F_{maj}.F_{min}." where "F_{maj}" is the major format version, "F_{min}" is the minor format version.
- Libraries will be named as: "MED F_{maj}.F_{min}.L" where "L" is the library version for the major format version. There will be no sub-versioning of the library versions.
- MED major format versions are restricted to one digit (and thus capped at 9 under this schema). MED
 minor format versions start at zero, and are not restricted to one digit.
- A minor format version is guaranteed to be cross compatible with all versions in it's major category.
- Minor format versions may add fields to the format in protected regions, but no preexisting fields will be removed or moved.
- Library Tags: All functions, constants, macros, and data types defined in the library are tagged with the suffix "_mF_{mai}L" (or "MED format F_{mai}, library L" (for format F_{mai}))
- Minor format versions are not included in the tags. This is to keep them concise, and because all minor format versions are cross compatible with all versions in their major category.
- Library version numbering restarts at one with the release of a new major format version.
- There will be no sub-versioning of the library versions.
- All library versions associated with a particular format version are guaranteed to work on MED files of that format version.
- Cross compatibility will be maintained between MED format versions only if practical.
- In this document, the tag "_m1x" refers to MED format version 1, any library version.
- The full library name, & thus the minor format versions it supports, will be given in the header comments.

Examples:

- "MED 1.0.1 C API" is the C API for MED format 1.0, library version 1. This API will work on all MED 1 format files, but not necessarily MED 2-n format files. The tag for this library is "_m11".
- "MED 1.1.2 C API" is the C API for MED format 1.0, library version 2. This API will work on all MED 1.0 and 1.1 format files. The tag for this library is " m12".
- The tag "_m213" indicates "MED format version 2.0-x, library version 13". This library will work on all MED 2 format files, but not necessarily MED 1 or MED 3-n format files.
- The tags allow different versions of the MED libraries to used within the same code. One such use might be in code for a MED 1 to MED 2 converter.

The MED library is evolved and renamed from the Multiscale Electrophysiology Format (MEF), versions 1-3. The library is open source, and curated by Dark Horse Neuro, Inc. (DHN). Source code is available through the <u>medformat.org</u> website. The layout of the format is described in "MED 1.0 Records Specification"

The MED 1.0 C library is composed of four files:

- medlib m10.c
- medlib m10.h
- medrec m10.c
- medrec_m10.h

The "_m10" suffix denotes "MED 1.0" and is found on all functions and defines in the library. Future library versions will change this suffix accordingly, allowing for easy concurrent use of two library versions, such as in version converters.

The medlib_m10 files contain library functions that are not intended for user manipulation except in collaboration with DHN to maintain library uniformity. In contrast, the medrec_m10 files are designed to allow user addition of custom record types. Generally useful record types that are shared with DHN will be permanently incorporated into this code. The functions required for adding new record types are described in "MED 1.0 Records Specification"

```
typedef char
                 si1;
typedef unsigned char
                 ui1;
typedef short
                 si2;
typedef unsigned short
                 ui2;
typedef int
                 si4;
typedef unsigned int
                 ui4;
typedef long int
                 si8;
typedef long unsigned int
                 ui8;
typedef float
                 sf4;
typedef double
                 sf8;
typedef long double
                 sf16;
                     // NOTE: it may require an explicit compiler instruction
                      // to implement true long floating point math.
                      // In icc the instruction is:
                      // "-Qoption,cpp,-extended_float_types"
```

These typedefs are used throughout the library to facilitate compilation on systems with different word sizes.

The first character indicates signedness, "s" for signed, "u" for unsigned.

The second character indicates format: "i" for integer type, "f" for floating point type.

The final number indicates the number of bytes in the type, 1, 2, 4, 8, or 16

example: "si4" indicates a signed integer of 4 byte length

A balanced ternary schema including true, unknown, & false states. This is used throughout the library, and is typically represented by an si1 type, typdef'ed to TERN m10.

```
// Structures
typedef struct {
      // Common MED Structures
      PASSWORD_DATA_m10
                                   password_data;
      // Time Constants
      si8
                                   recording_time_offset;
      si4
                                   standard_UTC_offset;
      si1
                                   standard_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10];
                                   standard_timezone_string[TIMEZONE_STRING_BYTES_m10];
      si1
      TERN_m10
                                   observe_DST;
      TERN_m10
                                   RTO_known;
                                   daylight_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10];
      si1
      si1
                                   daylight_timezone_string[TIMEZONE_STRING_BYTES_m10];
      DAYLIGHT_TIME_CHANGE_CODE_m10
                                   daylight_time_start_code; // si1[8] / si8
      DAYLIGHT_TIME_CHANGE_CODE_m10
                                   daylight_time_end_code; // si1[8] / si8
      TIMEZONE_INFO_m10
                                   *timezone_table;
      ui4
                                   recording_time_offset_mode;
      // Alignment Fields
      TERN m10
                                   universal_header_aligned;
      TERN_m10
                                   metadata_section_1_aligned;
      TERN_m10
                                   time_series_metadata_section_2_aligned;
      TERN_m10
                                   video_metadata_section_2_aligned;
      TERN_m10
                                   metadata_section_3_aligned;
                                   all_metadata_structures_aligned;
      TERN_m10
      TERN_m10
                                   time_series_indices_aligned;
      TERN_m10
                                   video_indices_aligned;
                                   CMP_block_header_aligned;
      TERN_m10
      TERN_m10
                                   CMP_record_header_aligned;
      TERN_m10
                                   record_header_aligned;
      TERN_m10
                                   record_indices_aligned;
      TERN_m10
                                   all_record_structures_aligned;
      TERN_m10
                                   all_structures_aligned;
      // CMP
      sf8
                                   *CMP_normal_CDF_table;
      // CRC
                                   **CRC_table;
      ui4
                                   CRC_mode;
      ui4
      // AES tables
      si4
                                   *AES_sbox_table;
                                   *AES_rcon_table;
      si4
                                   *AES_rsbox_table;
      // SHA256 tables
                                   *SHA_h0_table;
      ui4
      ui4
                                   *SHA_k_table;
      // UTF8 tables
      ui4
                                   *UTF8_offsets_table;
      si1
                                   *UTF8_trailing_bytes_table;
      // Miscellaneous
      TERN_m10
                                   verbose;
                                   behavior_on_fail;
      ui4
} GLOBALS_m10;
// Global Defaults
#define GLOBALS_VERBOSE_DEFAULT_m10
                                                     FALSE m10
#define GLOBALS_RECORDING_TIME_OFFSET_DEFAULT_m10
                                                     a
#define GLOBALS_RECORDING_TIME_OFFSET_NO_ENTRY_m10
                                                     0
```

```
#define GLOBALS_RECORDING_TIME_OFFSET_MODE_DEFAULT_m10
                                                             (RTO_APPLY_ON_OUTPUT_m10 | RTO_REMOVE_ON_INPUT_m10)
#define GLOBALS_STANDARD_UTC_OFFSET_DEFAULT_m10
#define GLOBALS_OBSERVE_DST_DEFAULT
                                                            UNKNOWN_m10
#define GLOBALS_STANDARD_TIMEZONE_ACRONYM_DEFAULT_m10
                                                             "UTC"
#define GLOBALS STANDARD TIMEZONE STRING DEFAULT m10
                                                             "Coordinated Universal Time"
#define GLOBALS_DAYLIGHT_TIMEZONE_ACRONYM_DEFAULT_m10
                                                             "UTC"
#define GLOBALS_DAYLIGHT_TIMEZONE_STRING_DEFAULT_m10
                                                             "Coordinated Universal Time"
#define GLOBALS_BEHAVIOR_ON_FAIL_DEFAULT_m10
                                                             EXIT_ON_FAIL_m10
#define GLOBALS_CRC_MODE_DEFAULT_m10
                                                            CRC_CALCULATE_ON_OUTPUT_m10
#define GLOBALS ALLOC TRACKING DEFAULT m10
                                                            FALSE m10
#define GLOBALS_INIT_ALLOC_TRACKING_ARRAY_LEN_m10
                                                            100
#define GLOBALS_ALLOC_TRACKING_FUNCTION_STRING_LEN_m10
                                                            42
```

These values are used throughout the library in a thread-safe manner. They are initialized to the application heap via the function initialize_MED_globals(), which is in turn called by initialize_medlib(). These two functions are described below.

The recording_time_offset and standard_UTC_offset constants will be described with the recording time offset functions. The alignment fields will be discussed with the alignment checking functions. The CRC_mode constants and CRC_table will be described with the CRC functions. Likewise, the AES, UTF-8 and, SHA lookup tables will be discussed in their respective sections below.

```
/************************** Error Checking Standard Functions *******************/
// Error Handling Constants
#define USE_GLOBAL_BEHAVIOR_m10
#define RESTORE_BEHAVIOR_m10
                                    1
#define EXIT_ON_FAIL_m10
                                    2
#define RETURN_ON_FAIL_m10
                                    4
#define SUPPRESS_ERROR_OUTPUT_m10
                                    8
#define SUPPRESS_WARNING_OUTPUT_m10
                                    16
#define SUPPRESS_ALL_OUTPUT_m10
                                     (SUPPRESS_ERROR_OUTPUT_m10 | SUPPRESS_WARNING_OUTPUT_m10)
#define RETRY ONCE m10
// Function Prototypes
      *e_calloc_m10(ui8 n_members, ui8 el_size, const si1 *function, si4 line, ui4 behavior_on_fail);
void
void
       **e_calloc_2D_m10(ui8 dim1, ui8 dim2, ui8 el_size, const si1 *function, si4 line, ui4 behavior_on_fail);
FILE
      *e_fopen_m10(si1 *path, si1 *mode, const si1 *function, si4 line, ui4 behavior_on_fail);
size_t e_fread_m10(void *ptr, ui8 size, ui8 n_members, FILE *stream, si1 *path, const si1 *function, si4 line,
             ui4 behavior_on_fail);
      e_free_m10(void *ptr, const si1 *function, si4 line);
void
      e_free_2D_m10(void **ptr, si8 dim1, const si1 *function, si4 line);
void
si4
      e_fseek_m10(FILE *stream, ui8 offset, si4 whence, si1 *path, const si1 *function, si4 line, ui4
             behavior_on_fail);
      e_ftell_m10(FILE *stream, const si1 *function, si4 line, ui4 behavior_on_fail);
si8
ui8
      e_fwrite_m10(void *ptr, ui8 size, ui8 n_members, FILE *stream, si1 *path, const si1 *function, si4 line,
             ui4 behavior_on_fail);
void
      *e_malloc_m10(ui8 n_bytes, const si1 *function, si4 line, ui4 behavior_on_fail);
void
      *e_realloc_m10(void *ptr, ui8 n_bytes, const si1 *function, si4 line, ui4 behavior_on_fail);
      **e_realloc_2D_m10(void **curr_ptr, size_t curr_dim1, size_t new_dim1, size_t curr_dim2, size_t
void
              new_dim2, size_t el_size, const si1 *function, si4 line, ui4 behavior_on_fail);
      e_system_m10(si1 *command, TERN_m10 null_std_streams, const si1 *function, si4 line, ui4
si4
             behavior_on_fail);
void
      force_behavior_m10(ui4 behavior);
```

These functions are provided for convenience. They call their corresponding standard c functions (e.g. e_calloc_m10() calls calloc()), but have built in error messaging. The behavior_on_fail parameter defines what the function does on failure. They are written to maintain thread-safety.

force_behavior_m10() is described with the general functions, but essentially changes global behavior, and is one of the few library functions that *is not thread-safe*.

Example:

```
ui4    behavior;
si4    *data;

behavior = (RETURN_ON_FAIL | SUPPRESS_ERROR_OUTPUT);
data = (si4 *) e_calloc_m10((size_t) buffer_size, sizeof(si4), __FUNCTION__, __LINE__, behavior);
```

_FUNCTION__ and _LINE__ are compiler macros replaced with the function name and line of the function in which they occur; these can contain any string and number, however, for more complex failure tracking. Because of the way in which the behavior parameter is defined, on failure, this call to e_calloc_m10() will return NULL, as would calloc(), and no error messages will be displayed. If USE_GLOBAL_BEHAVIOR is passed into this parameter, the global value of behavior_on_fail will be used. This is the most common usage in the library. At the time of this writing the default global behavior_on_fail value is EXIT_ON_FAIL, which will produce error messages and then exit the program.

```
// Alignment Function Prototypes
TERN_m10
            check_all_alignments_m10(const si1 *function, si4 line);
TERN_m10
            check_metadata_alignment_m10(ui1 *bytes);
TERN_m10
            check_metadata_section_1_alignment_m10(ui1 *bytes);
            check_metadata_section_3_alignment_m10(ui1 *bytes);
TERN_m10
TERN_m10
            check_record_header_alignment_m10(ui1 *bytes);
            check_record_indices_alignment_m10(ui1 *bytes);
TERN_m10
TERN_m10
            check_CMP_block_header_alignment_m10(ui1 *bytes);
            check_CMP_record_header_alignment_m10(ui1 *bytes);
TERN_m10
TERN_m10
            check_time_series_indices_alignment_m10(ui1 *bytes);
TERN_m10
            check_time_series_metadata_section_2_alignment_m10(ui1 *bytes);
TERN_m10
            check_universal_header_alignment_m10(ui1 *bytes);
            check_video_indices_alignment_m10(ui1 *bytes);
TERN_m10
TERN_m10
            check_video_metadata_section_2_alignment_m10(ui1 *bytes);
```

The structures in the MED library are designed such that they can be read in directly from their sources (e.g. disk, network) to the structure without explicit assignment operations for each of the fields. Because compilers can rearrange fields within structures, this can fail in principle, but the fields are laid out such that this would be quite unlikely.

For example, on a 64 bit CPU structures are generally laid out on 8 byte boundaries. If they are not inherently 8 byte aligned, the compiler will often pad the structure. Explicitly padding the structure to create 8 byte alignment will alleviate this problem. Likewise an 8 byte data type should fall on a natural 8 byte boundary within the structure, if it does not the compiler may try to rearrange or pad the structure.

In practice designing a structure such that the compiler will leave it intact is usually quite easy. In the case of alignment failure, the library would need to be updated to perform explicit assignment.

The alignment checking functions simply compare compiler generated offsets to expected offsets from the layout on disk. If all the field offsets match, the functions return TRUE, if they do not they return FALSE. Prior to checking, the global alignment flags are each set to UNKNOWN. In addition to a return value, each of these functions also sets its corresponding GLOBAL field to TRUE or FALSE.

The function check_all_alignments_m10() calls all of the other alignment checking functions and returns TRUE if all of those functions return TRUE. This function also takes a function and line argument similar to the error checking functions. This function is called from initialize_medlib_m10(), and so need not be called explicitly if initialize_medlib_m10() is called.

If a buffer (the "bytes" field) is passed the function will not allocate any memory for the testing. If NULL is passed in the "bytes" field the function will allocate memory for the testing and then free it once the check is complete.

```
example 1 (exerpted from check all alignments m10()):
bytes = (ui1 *) e_malloc_m10(METADATA_FILE_BYTES, __FUNCTION__, __LINE__, USE_GLOBAL_BEHAVIOR);
// METADATA is largest fixed file structure, so this will be enough memory to check all
// the library structures
// check all structures
return_value = MED_TRUE;
if ((check_universal_header_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_metadata_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_CMP_block_header_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_time_series_indices_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_video_indices_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_record_indices_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_record_header_alignment_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
if ((check_record_structure_alignments_m10(bytes)) == MED_FALSE)
      return_value = MED_FALSE;
free(bytes);
return(return_value);
example 2 (the most common use):
return_value = check_all_alignments(__FUNCTION__, __LINE__);
/********************************
// Standard String Function Prototypes
si4
      sprintf_m10(si1 *target, si1 *format, ...);
void
      snprintf_m10(si1 *target, si4 target_field_bytes, si1 *format, ...);
si4
      strcat_m10(si1 *target_string, si1 *source_string);
si4
      strcpy_m10(si1 *target_string, si1 *source_string);
      strncat_m10(si1 *target_string, si1 *source_string, si4 target_field_bytes);
void
void
      strncpy_m10(si1 *target_string, si1 *source_string, si4 target_field_bytes);
// UTF8 Prototypes: these are described with the other UTF8 functions, but are mentioned here only because they
// are string functions with standard correlates.
      UTF8_fprintf_m10(FILE *stream, si1 *fmt, ...);
si4
si4
      UTF8_printf_m10(si1 *fmt, ...);
si4
      UTF8_strlen_m10(si1 *s);
As a group, these functions facilitate working with MED strings. When there is a target string, unoccupied bytes are filled
with zeros, per the MED specification.
```

As a group, these functions facilitate working with various aspects of the MED format. Each will be described separately below.

FUNCTION: all_zeros_m10()

```
// Prototype
TERN_m10 all_zeros_m10(ui1 *bytes, si4 field_length);
```

This function returns TRUE if field pointed to by "bytes" contains all zeros, and FALSE if not. The expected length of the field is passed in "field length". It is useful in checking fields whose "no entry" value is defined to be all zeros.

```
example ( extracted from show_universal_header_m10() ):

if (all_zeros(uh->level_1_password_validation_field, PASSWORD_VALIDATION_FIELD_BYTES) == TRUE_m10)
    printf("Level 1 Password Validation_Field: no entry\n");
```

FUNCTION: allocate_channel_m10()

```
// Prototype
               *allocate_channel_m10(CHANNEL_m10 *chan, FILE_PROCESSING_STRUCT_m10 *proto_fps, si1
CHANNEL_m10
enclosing_path, si1 *chan_name, ui4 type_code, si4 n_segs, TERN_m10 chan_recs, TERN_m10 seg_recs);
// Structures
typedef struct {
       FILE_PROCESSING_STRUCT_m10
                                      *metadata_fps;
       FILE_PROCESSING_STRUCT_m10
                                      *record_data_fps;
       FILE_PROCESSING_STRUCT_m10
                                      *record_indices_fps;
       si4
                                      number_of_segments;
       SEGMENT_m10
                                      **seaments:
                                      path[FULL_FILE_NAME_BYTES_m10]; // full path to channel
       si1
                                             // directory (including channel directory itself)
                                      name[BASE_FILE_NAME_BYTES_m10];
       si1
       TIME_SLICE_m10
                                      time_slice;
} CHANNEL_m10;
```

This function allocates a CHANNEL_m10 structure and returns a pointer to it. If a channel structure pointer is passed, this structure is used; if NULL is passed, the channel structure is allocated.

If a prototype FPS is passed (NULL for no prototype), it is used to initialize the channel files.

Enclosing_path is the path to the directory enclosing the channel, not the channel directory itself.

Chan_name is the channel's base name, with no path or extension.

type code is one of the defined channel types. Currently these are defined:

```
TIME_SERIES_CHANNEL_TYPE_m10 (== TIME_SERIES_CHANNEL_DIRECTORY_TYPE_CODE_m10) VIDEO_CHANNEL_TYPE_m10 (== VIDEO_CHANNEL_DIRECTORY_TYPE_CODE_m10) UNKNOWN_CHANNEL_TYPE_m10 (== NO_FILE_TYPE_CODE_m10)
```

But MED may include other channel types in the future.

n_segs is the number of segments to allocate for the channel. A segment structure is easily re-used, so allocation of just one segment is a common choice.

Chan recs & seg recs select whether to allocate channel-level & segment-level record file structures.

If records are requested, enough memory for one record of size LARGEST_RECORD_BYTES_m10 is allocated (call reallocate_file_processing_struct_m10() to change this). If records are requested, enough memory for one record index is also allocated (reallocate_file_processing_struct_m10() can also change this).

FUNCTION: allocate_file_processing_struct_m10()

```
// Prototype
                              *allocate_file_processing_struct_m10(FILE_PROCESSING_STRUCT_m10 *fps, si1
FILE_PROCESSING_STRUCT_m10
*full_file_name, ui4 type_code, si8 raw_data_bytes, FILE_PROCESSING_STRUCT_m10 *proto_fps, si8 bytes_to_copy);
This function allocates a FILE_PROCESSING_STRUCT and returns a pointer to it.
// Structures
typedef struct {
       TERN_m10
                                             mutex; // used by MED functions to ensure thread
                                                     // safety
       PASSWORD_DATA_m10
                                              *password_data; // this will typically be the same
                                              full_file_name[FULL_FILE_NAME_BYTES_m10]; // full
       si1
                                                                    // path including extension
                                              *fp; // file pointer
       FILE
                                              fd; // file descriptor
       si4
                                             file_length;
       si8
       UNIVERSAL_HEADER_m10
                                              *universal_header;
       FILE_PROCESSING_DIRECTIVES_m10
                                             directives;
                                             // the MED file types
       union {
               METADATA_m10
                                              *metadata;
                                              *records;
               ui1
               RECORD_INDEX_m10
                                              *record_indices;
               TIME_SERIES_INDEX_m10
                                              *time_series_indices;
               VIDEO_INDEX_m10
                                              *video_indices;
       };
       si8
                                             raw_data_bytes;
       ui1
                                              *raw_data;
                                              *cps; // associated with time series data FPS, NULL
       CMP_PROCESSING_STRUCT_m10
                                                     // in others
} FILE_PROCESSING_STRUCT_m10;
typedef struct {
       TERN m10
                        close_file;
       TERN_m10
                        flush_after_write;
                        update_universal_header; // when writing
       TERN_m10
                        leave_decrypted; // if encrypted during write, return from write
       TERN_m10
                                          // function decrypted, also leave times unoffset
       TERN_m10
                        free_password_data; // when freeing FPS
       TERN m10
                        free_CMP_processing_struct; // when freeing FPS
       ui4
                        lock_mode;
       ui4
                        open_mode;
} FILE_PROCESSING_DIRECTIVES_m10;
// Constants
                                              -1
#define FPS_FILE_LENGTH_UNKNOWN_m10
#define FPS_FULL_FILE_m10
                                              -1
#define FPS_NO_LOCK_TYPE_m10
                                             (~(F_RDLCK | F_WRLCK | F_UNLCK)) // from <fcntl.h>
#define FPS_NO_LOCK_MODE_m10
#define FPS_READ_LOCK_ON_READ_OPEN_m10
                                             1
                                             2
#define FPS_WRITE_LOCK_ON_READ_OPEN_m10
#define FPS_WRITE_LOCK_ON_WRITE_OPEN_m10
#define FPS_WRITE_LOCK_ON_READ_WRITE_OPEN_m10
                                                     8
#define FPS_READ_LOCK_ON_READ_m10
                                             16
#define FPS_WRITE_LOCK_ON_WRITE_m10
                                             32
#define FPS_NO_OPEN_MODE_m10
                                              0
#define FPS_R_OPEN_MODE_m10
                                             1
```

```
2
#define FPS_R_PLUS_OPEN_MODE_m10
#define FPS_W_OPEN_MODE_m10
                                             4
#define FPS_W_PLUS_OPEN_MODE_m10
                                             8
#define FPS A OPEN MODE m10
                                             16
#define FPS_A_PLUS_OPEN_MODE_m10
#define FPS_GENERIC_READ_OPEN_MODE_m10
                                             (FPS_R_OPEN_MODE_m10 | FPS_R_PLUS_OPEN_MODE_m10 | \
                                             FPS_W_PLUS_OPEN_MODE_m10 | FPS_A_PLUS_OPEN_MODE_m10)
                                             (FPS_R_PLUS_OPEN_MODE_m10 | FPS_W_OPEN_MODE_m10 | \
#define FPS_GENERIC_WRITE_OPEN_MODE_m10
                                             FPS_W_PLUS_OPEN_MODE_m10 | FPS_A_OPEN_MODE_m10 | \
                                             FPS A PLUS OPEN MODE m10)
#define FPS_PROTOTYPE_FILE_TYPE_CODE_m10
                                             TIME_SERIES_METADATA_FILE_TYPE_CODE_m10 // any
                                                     // metadata type would do
#define FPS_FD_NO_ENTRY_m10
                                             -2
                                             -3
#define FPS_FD_EPHEMERAL_m10
// File Processing Directives Defaults
#define FPS_DIRECTIVE_CLOSE_FILE_DEFAULT_m10
                                                                    TRUE_m10
#define FPS_DIRECTIVE_FLUSH_AFTER_WRITE_DEFAULT_m10
                                                                    TRUE_m10
#define FPS_DIRECTIVE_FREE_PASSWORD_DATA_DEFAULT_m10
                                                                    FALSE_m10
#define FPS_DIRECTIVE_FREE_CMP_PROCESSING_STRUCT_DEFAULT_m10
                                                                    TRUE_m10
#define FPS DIRECTIVE UPDATE UNIVERSAL HEADER DEFAULT m10
                                                                    FALSE m10
#define FPS_DIRECTIVE_LEAVE_DECRYPTED_DEFAULT_m10
                                                                    FALSE m10
#define FPS_DIRECTIVE_LOCK_MODE_DEFAULT_m10
                                                                    FPS_NO_LOCK_MODE_m10 // Unix
                                                                    // file locking may cause
                                                                    // problems with networked
                                                                    // file systems
// #define FPS_DIRECTIVE_LOCK_MODE_DEFAULT_m10
                                                     (FPS READ LOCK ON READ OPEN m10 |
                                                     // FPS WRITE LOCK ON WRITE OPEN m10 |
                                                     // FPS_WRITE_LOCK_ON_READ_WRITE_OPEN_m10)
#define FPS_DIRECTIVE_OPEN_MODE_DEFAULT_m10
                                                                    FPS_NO_OPEN_MODE_m10
                                                                    FPS_FULL_FILE_m10 // bytes
#define FPS_DIRECTIVE_IO_BYTES_DEFAULT_m10
                                                                    // to read or write
#define FPS UNIVERSAL HEADER ONLY m10
```

The FILE_PROCESSING_STRUCT (FPS) is the fundamental file handling unit of the MED library. The raw_data field contains the data as it is arranged in the MED structures, **and on disk**. The universal_header pointer within the FPS will be assigned the value of the start of the raw_data array. Depending on file type, one of the other pointers within the structure will be assigned to the raw_data array after the universal header region.

The passed parameter raw_data_bytes is the amount of memory to be allocated to the raw_data field minus the amount needed for a universal header, as all MED files have a universal header.

The FILE_PROCESSING_STRUCT's file_length field reflects the size of the file on disk (in bytes). This is set to zero on allocation, but is updated during read and write operations using MED library functions.

If a prototype FILE_PROCESSING_STRUCT is passed in proto_fps, its directives, password data, and raw data are copied to the new FILE_PROCESSING_STRUCT (unless bytes_to_copy plus universal header bytes is greater than raw_data_bytes). The amount of raw_data copied is specified in the bytes_to_copy field. Bytes_to_copy does not include the bytes universal header bytes, as this is assumed. If copying is performed, the universal header's CRC will be not be recalculated, and may be inaccurate. This is updated in write_file_m10() before write out, and so is not usually an issue. It could be explicitly calculated with calculate_CRC_m10().

If the prototype pointer is NULL, the file processing directives and universal header are set to their default values.

The FILE_PROCESSING_DIRECTIVES are used by the reading and writing functions. Specifically, **close_file** tells reading & writing functions to close the file when they are finished. **free_password_data** tells functions freeing a FILE_PROCESSING_STRUCT to free this also. This is often undesirable as the pointer to a single PASSWORD_DATA structure is often shared between many FILE_PROCESSING_STRUCTs. At this writing the default value of the **free_password_data** directive is FALSE. **lock_mode** specifies *advisory locking* on the file. All the MED library functions observe the advisory locking mechanism, to facilitate parallel processing of files. Note that, as this is *advisory* only,

external functions may choose to ignore these locks. **open_mode** specifies how a file should be opened, and corresponds to standard Unix / Posix opening modes. This parameter interacts with the **lock_mode** parameter.

The type_code specifies which of the FILE_PROCESSING_STRUCT pointers will be assigned to the raw_data after the universal header. The type_string field of the universal header is also set by the type_code. If the type_code is zero, these assignments are not made.

The raw_data_bytes parameter specifies how much memory to allocate to the raw_data array. This value is copied into the corresponding member of the new FPS.

example 1: allocate an empty FILE_PROCESSING_STRUCT (just space for a universal header)

```
fps = allocate_file_processing_struct_m10(NULL, NULL, NO_TYPE_CODE_m10, 0, NULL, 0);
NO_TYPE_CODE_m10 == 0, so fps = allocate_file_processing_struct_m10(NULL, NULL, 0, 0, NULL, 0); would be the same
```

example 2: allocate a metadata FILE_PROCESSING_STRUCT and copy its universal header from the prototype FPS, "other fps"

```
fps = allocate_file_processing_struct_m10(NULL, full_file_name, TIME_SERIES_METADATA_FILE_TYPE_CODE_m10,
METADATA_FILE_BYTES_m10, other_fps, FPS_UNIVERSAL_HEADER_ONLY_m10);
FPS_UNIVERSAL_HEADER_ONLY_m10 == 0, so fps = allocate_file_processing_struct_m10(NULL, full_file_name, TIME_SERIES_METADATA_FILE_TYPE_CODE_m10,
METADATA_FILE_BYTES_m10, other_fps, 0); would be the same
```

example 3: allocate a metadata FILE_PROCESSING_STRUCT and copy all of the data, including the universal header, from "other metadata fps".

```
fps = allocate_file_processing_struct_m10(NULL, full_file_name, TIME_SERIES_METADATA_FILE_TYPE_CODE_m10,
METADATA_FILE_BYTES_m10, other_metadata_fps, METADATA_FILE_BYTES_m10);
```

FUNCTION: allocate_metadata_m10()

```
// Prototype
METADATA_m10
                *allocate_metadata_m10(METADATA_m10 *metadata, ui1 *data_ptr);
// Structures
typedef struct {
       METADATA_SECTION_1_m10
                                                     section_1;
       union {
               TIME_SERIES_METADATA_SECTION_2_m10
                                                    time_series_section_2;
               VIDEO_METADATA_SECTION_2_m10
                                                    video_section_2;
       METADATA_SECTION_3_m10
                                                     section_3;
} METADATA_m10;
typedef struct {
               level_1_password_hint[PASSWORD_HINT_BYTES_m10];
       si1
               level_2_password_hint[PASSWORD_HINT_BYTES_m10];
       si1
               section_2_encryption_level;
       si1
       si1
               section_3_encryption_level;
       ui1
               protected_region[METADATA_SECTION_1_PROTECTED_REGION_BYTES_m10];
       ui 1
               discretionary_region[METADATA_SECTION_1_DISCRETIONARY_REGION_BYTES_m10];
} METADATA_SECTION_1_m10;
typedef struct {
       // channel type independent fields
               session_description[METADATA_SESSION_DESCRIPTION_BYTES_m10]; // utf8[511]
               channel_description[METADATA_CHANNEL_DESCRIPTION_BYTES_m10]; // utf8[255]
       si1
               segment_description[METADATA_SEGMENT_DESCRIPTION_BYTES_m10]; // utf8[255]
       si1
               equipment_description[METADATA_EQUIPMENT_DESCRIPTION_BYTES_m10]; // utf8[510]
       si1
               acquisition_channel_number;
       si4
       // channel type specific fields
               reference_description
       si1
```

```
[TIME_SERIES_METADATA_REFERENCE_DESCRIPTION_BYTES_m10]; // utf8[255]
       sf8
               sampling_frequency;
       sf8
               low_frequency_filter_setting;
       sf8
               high_frequency_filter_setting;
       sf8
              notch_filter_frequency_setting;
       sf8
               AC_line_frequency;
       sf8
               amplitude_units_conversion_factor;
       si1
               amplitude_units_description \
                      [TIME_SERIES_METADATA_AMPLITUDE_UNITS_DESCRIPTION_BYTES_m10]; // utf8[31]
       sf8
               time_base_units_conversion_factor;
       si1 time_base_units_description \
                      [TIME_SERIES_METADATA_TIME_BASE_UNITS_DESCRIPTION_BYTES_m10]; // utf8[31]
       si8
               absolute_start_sample_number;
       si8
               number_of_samples;
       si8
               number_of_blocks;
       si8
              maximum_block_bytes;
       ui4
              maximum_block_samples;
       ui4
              maximum_block_difference_bytes;
       sf8
              maximum_block_duration;
       si8
              number_of_discontinuities;
       si8
              maximum_contiquous_blocks;
       si8
              maximum_contiquous_block_bytes;
       si8
              maximum_contiguous_samples;
       ui1
               protected_region[TIME_SERIES_METADATA_SECTION_2_PROTECTED_REGION_BYTES_m10];
       ui1
               discretionary_region \
                      [TIME_SERIES_METADATA_SECTION_2_DISCRETIONARY_REGION_BYTES_m10];
} TIME_SERIES_METADATA_SECTION_2_m10;
typedef struct {
       // type-independent fields
               session_description[METADATA_SESSION_DESCRIPTION_BYTES_m10]; // utf8[511]
       si1
               channel_description[METADATA_CHANNEL_DESCRIPTION_BYTES_m10]; // utf8[511]
               segment_description[METADATA_SEGMENT_DESCRIPTION_BYTES_m10]; // utf8[511]
       si1
       si1
               equipment_description[METADATA_EQUIPMENT_DESCRIPTION_BYTES_m10]; // utf8[510]
               acquisition_channel_number;
       si4
        // type-specific fields
       si8
              horizontal_resolution;
       si8
               vertical_resolution;
       sf8
               frame_rate;
       si8
              number_of_clips;
       si8
              maximum_clip_bytes;
              video_format[VIDEO_METADATA_VIDEO_FORMAT_BYTES_m10]; // utf8[31]
       si1
       si4
              number_of_video_files;
       ui1
              protected_region[VIDEO_METADATA_SECTION_2_PROTECTED_REGION_BYTES_m10];
               discretionary_region[VIDEO_METADATA_SECTION_2_DISCRETIONARY_REGION_BYTES_m10];
} VIDEO_METADATA_SECTION_2_m10;
typedef struct {
               recording_time_offset;
       DAYLIGHT_TIME_CHANGE_CODE_m10 daylight_time_start_code; // si1[8] / si8
       DAYLIGHT_TIME_CHANGE_CODE_m10 daylight_time_end_code; // si1[8] / si8
               standard_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10]; // ascii[8]
               standard_timezone_string[TIMEZONE_STRING_BYTES_m10]; // ascii[31]
       si1
               daylight_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10]; // ascii[8]
       si1
               daylight_timezone_string[TIMEZONE_STRING_BYTES_m10]; // ascii[31]
       si1
               subject_name_1[METADATA_SUBJECT_NAME_BYTES_m10]; // utf8[31]
       si1
               subject_name_2[METADATA_SUBJECT_NAME_BYTES_m10]; // utf8[31]
       si1
       si1
               subject_name_3[METADATA_SUBJECT_NAME_BYTES_m10]; // utf8[31]
               subject_ID[METADATA_SUBJECT_ID_BYTES_m10]; // utf8[31]
       si1
               recording_country[METADATA_RECORDING_LOCATION_BYTES_m10]; // utf8[63]
       si1
               recording_territory[METADATA_RECORDING_LOCATION_BYTES_m10]; // utf8[63]
       si1
       si1
               recording_city[METADATA_RECORDING_LOCATION_BYTES_m10]; // utf8[63]
               recording_institution[METADATA_RECORDING_LOCATION_BYTES_m10]; // utf8[63]
       si1
       si1
               geotag_format[METADATA_GEOTAG_FORMAT_BYTES_m10]; // ascii[31]
```

```
si1 geotag_data[METADATA_GEOTAG_DATA_BYTES_m10]; // ascii[1023]
si4 standard_UTC_offset;
ui1 protected_region[METADATA_SECTION_3_PROTECTED_REGION_BYTES_m10];
ui1 discretionary_region[METADATA_SECTION_3_DISCRETIONARY_REGION_BYTES_m10];
} METADATA_SECTION_3_m10;
```

This function allocates a metadata structure (if NULL is passed), and the memory for the structures it contains (again, if NULL is passed). Internal memory is allocated to metadata->metadata, and caller must free that before freeing the metadata structure itself (you can also use free_metadata_m10() which does this for you). The function sets the internal pointers appropriately. Use of this functions is typically unnecessary as allocate_file_processing_struct_m10() for a metadata FPS perform this allocation and assignment.

FUNCTION: apply_recording_time_offset_m10()

```
// Prototype
void apply_recording_time_offset(si8 *time);
```

The global recording time offset is applied to the passed µUTC time. The converse function is remove_recording_time_offset() described below.

FUNCTION: calculate_metadata_CRC_m10()

```
// Prototype
void calculate_metadata_CRC_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Calculates the CRC for a metadata FPS, and enters that value in the universal header body CRC.

FUNCTION: calculate_record_data_CRCs_m10()

```
// Prototype
void calculate_record_data_CRCs_m10(FILE_PROCESSING_STRUCT_m10 *fps, RECORD_HEADER_m10
*record_header, si8 number_of_items);
```

Calculates the CRCs for number_of_items record data entries, and enters their values in the record headers. It also updates the universal header body_CRC for each record. The record_header pointer is the beginning of an array of records.

FUNCTION: calculate_record_indices_CRCs_m10()

```
// Prototype
void calculate_record_indices_CRCs_m10(FILE_PROCESSING_STRUCT_m10 *fps, RECORD_INDEX_m10
*record_index, si8 number_of_items);
```

Calculates the CRCs for number_of_items record indices, and updates the universal header body_CRC for each index. The record index pointer is the beginning of an array of record indices.

FUNCTION: calculate_time_series_data_CRCs_m10()

```
// Prototype
```

```
void calculate_time_series_data_CRCs_m10(FILE_PROCESSING_STRUCT_m10 *fps,
CMP_BLOCK_FIXED_HEADER_m10 *block_header, si8 number_of_items);
```

Calculates the CRCs for number_of_items CMP blocks (time series data blocks entries), and enters their values in the CMP block headers. It also updates the universal header body_CRC for each record. The block_header pointer is the beginning of an array of CMP blocks.

FUNCTION: calculate_time_series_indices_CRCs_m10()

```
// Prototype
void calculate_time_series_indices_CRCs_m10(FILE_PROCESSING_STRUCT_m10 *fps,
TIME_SERIES_INDEX_m10 *time_series_index, si8 number_of_items);
```

Calculates the CRCs for number_of_items time series indices, and updates the universal header body_CRC for each index. The time_series_index pointer is the beginning of an array of time series indices.

FUNCTION: channel_type_from_path_m10()

```
// Prototype
ui4 channel_type_from_path_m10(si1 *path);
```

Returns MED type code based on extension of the passed file name or path. UNKNOWN_CHANNEL_TYPE_m10 is returned for an unrecognized extension.

FUNCTION: check_password_m10()

```
// Prototype
si4 check_password(si1 *password, const si1 *function, si4 line);
```

Checks that the password pointer is not NULL, and that the password length is less than or equal to PASSWORD_BYTES. Returns 0 on success, 1 on failure. This function does not validate the password against the password validation fields. Process_password_data() does this. In fact, process_password_data() is the only library function to call check_password().

```
example ( from process_password_data_m10() ):

if (check_password(unspecified_password, __FUNCTION__, __LINE__) == 0)

// password is not NULL, and is of valid length
```

FUNCTION: condition_time_slice_m10()

```
// Prototype
void condition_time_slice_m10(TIME_SLICE_m10 *slice)
```

Does the following to the passed time slice:

- 1) Offsets unoffset times (using global recording time offset)
- 2) Makes relative times (negative) absolute (using global session_start_time)
- 3) Sets start_time & end_time to BEGINNING_OF_TIME_m10 & END_OF_TIME_m10 if no index parameters are specified
- 4) Sets slice->conditioned to TRUE m10

NOTE: globals session_start_time & recording_time_offset must be set before using this function.

FUNCTION: current_uutc_m10()

```
// Prototype
inline si8 current_uutc_m10(void);
```

Returns the current µUCT based on the system clock.

FUNCTION: days_in_month_m10()

```
// Prototype
inline si4 days_in_month_m10(si4 month, si4 year);
```

Returns the days in a month based on the month and year. Note month is [0 - 11], where January == 0 (as in struct tm.tm_mon in <time.h>). This function expects the full value of the year (note struct tm.tm_year is (year - 1900) in <time.h>).

FUNCTION: decrypt_metadata_m10()

```
// Prototype
TERN_m10 decrypt_metadata_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Decrypts metadata in a metadata FPS in place. Returns TRUE_m10 on success, FALSE_m10 on failure.

FUNCTION: decrypt_records_m10()

```
// Prototype
TERN_m10 decrypt_records_m10(RECORD_HEADER_m10 *record_header, si8 number_of_items);
```

Decrypts the number_of_items records pointed to by record_header. Returns TRUE_m10 on success, FALSE_m10 on failure.

FUNCTION: decrypt_time_series_data_m10()

```
// Prototype
TERN_m10 decrypt_time_series_data_m10(CMP_BLOCK_FIXED_HEADER_m10 *block_header, si8
number_of_items);
```

Decrypts the number_of_items CMP blocks pointed to by block_header. Returns TRUE_m10 on success, FALSE_m10 on failure.

FUNCTION: DST_offset_m10()

```
// Prototype
si4 DST_offset_m10(si8 uutc);
```

Returns seconds to add to standard time (as UUTC) to adjust for DST on that date, in the timezone specified in the MED globals.

FUNCTION: encrypt_metadata_m10()

```
// Prototype
TERN_m10 encrypt_metadata_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Encrypts sections 2 and 3 of metadata file (passed in fps), if they are currently decrypted, to the encryption level specified in section 1 of the metadata. It marks encrypted sections as encrypted (positive of encryption level) in section 1 of the metadata. It returns TRUE m10 on success, FALSE m10 on failure.

FUNCTION: encrypt_records_m10()

Encrypts number_of_items records if currently decrypted to the level specified in the record headers. It marks the encrypted records as encrypted (positive of encryption level) in the record headers. It returns TRUE_m10 on success, FALSE_m10 on failure.

FUNCTION: encrypt_time_series_data_m10()

Encrypts number_of_items CMP blocks pointed to by cps->block_header. It marks the encrypted CMP block as encrypted in the CMP block header flags. It returns TRUE_m10 on success, FALSE_m10 on failure.

FUNCTION: error_message_m10()

```
// Prototype
void error_message_m10(si1 *fmt, ...);
```

Prints an error message to stderr in accordance with the parameters of the behavior_on_fail global variable. Used like fprintf(). Also see message_m10(), warning_message_m10() and force_behavior_m10().

Example:

```
error_message_m10("%s(): Cannot encrypt data (called from line %d)", __FUNCTION__, \
```

```
__LINE__);
```

If you wish to ensure an exit(), regardless go the global behavior, do something like this:

```
if (x == 0) {
    error_message_m10("%s(): Divide by zero", __FUNCTION__);
    exit(1);
}
```

FUNCTION: escape_spaces_m10()

```
// Prototype
void escape_spaces_m10(si1 *string, si8 buffer_len);
```

Escapes all spaces (inserts a backslash ('\')) before all unescaped spaces in the string.

FUNCTION: extract_path_parts_m10()

```
// Prototype
void extract_path_parts_m10(si1 *full_file_name, si1 *path, si1 *name, si1 *extension);
```

Non-destructively copies the path (**full_file_name** string up to enclosing directory) into **path** (if not NULL), the name (last component in full_file_name) into **name** (if not NULL), and the extension (last component in full_file_name after a ".") into **extension** (if not NULL). Pass NULL for any components that are not needed. Terminal forward slashes ("/") are removed. the path is prepended with the current working directory if the **full_file_name** does not begin from root. example:

```
si1 *passed_session_directory = "/Data/Session_1.medd";
extract_path_and_name(passed_session_directory, session_path, session_name,
session_extension);
```

On return, session_path contains "/Data", session._name contains "Session_1", and extension contains "medd". If only the name was required the following call would suffice:

extract_path_and_name(passed_session_directory, NULL, session_name, NULL);

FUNCTION: extract_terminal_password_bytes_m10()

```
// Prototype
si4 extract_terminal_password_bytes_m10(si1 *password, si1 *password_bytes);
```

UTF-8 passwords can contain up to 4 bytes per character. In UTF-8 encoding, the most unique byte in each character is the terminal byte. This function extracts those bytes from the UTF-8 password (passed in **password**) to password_bytes, which is used to generate the encryption key for the AES algorithms. Unused bytes are zeroed. This function is called by process password data m10().

FUNCTION: file_exists_m10()

```
// Prototype
ui4 file_exists_m10(si1 *path);

#define DOES_NOT_EXIST_m10 0
#define FILE_EXISTS_m10 1
#define DIR_EXISTS_m10 2
```

Returns FILE_EXISTS_m10 if path describes a file. Returns DIR_EXISTS_m10 if path describes a directory. Returns DOES_NOT_EXIST_m10 if path does not point to either a file or directory. If path does not begin from root, the current working directory is prepended.

FUNCTION: find_discontinuities_m10()

```
// Prototype
si8 *find_discontinuities_m10(TIME_SERIES_INDEX_m10 *tsi, si8 num_disconts, si8
number_of_indices, TERN_m10 remove_offsets, TERN_m10 return_sample_numbers);
```

Allocates and returns an array of indices (into the tsi array) of blocks with discontinuities. If remove_offsets == TRUE_m10, the tsi start sample numbers will be "unflagged" to their true numbers. If return_sample_numbers == TRUE_m10, start sample numbers will be returned in the array, rather than indices.

```
FUNCTION: fps_close_m10()
```

```
// Prototype
void fps_close(FILE_PROCESSING_STRUCT *fps);
```

Closes the file associated with the FPS's FILE pointer and sets it to NULL. It also sets the FPS's file descriptor to -1 (closed file).

FUNCTION: fps_lock_m10()

```
// Constants
#define FPS_NO_LOCK_TYPE
                                           ~(F_RDLCK | F_WRLCK | F_UNLCK) // <fcntl.h>
#define FPS_NO_LOCK_MODE
#define FPS_READ_LOCK_ON_READ_OPEN
                                           1
                                           2
#define FPS_WRITE_LOCK_ON_READ_OPEN
#define FPS_WRITE_LOCK_ON_WRITE_OPEN
                                           4
#define FPS_WRITE_LOCK_ON_READ_WRITE_OPEN 8
#define FPS_READ_LOCK_ON_READ
                                           16
#define FPS_WRITE_LOCK_ON_WRITE
                                           32
// Prototype
      fps_lock_m10(FILE_PROCESSING_STRUCT_m10 *fps, si4 lock_type, const si1 *function, \
si4
      si4 line, ui4 behavior_on_fail);
```

Sets an *advisory lock* on the file specified by the FPS directive's lock_mode. The lock is set in blocking mode (i.e. it waits until a lock can be obtained). **lock_type** specifies either a read or write lock. The function & line arguments are provided to know from whence the function was called in the case of failure.

NOTE: advisory locks often do not work on networked file systems.

FUNCTION: fps_mutex_off_m10()

```
// Prototype
inline void fps_mutex_off_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Removes mutex lock on an FPS. The mutex is used by read_file_m10() & write_file_m10() to make sure fps is not in use while reading or writing. Other functions may also use this mechanism.

FUNCTION: fps_mutex_on_m10()

```
// Prototype
inline void fps_mutex_on_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Activates mutex lock on an FPS. The mutex is used by read_file_m10() & write_file_m10() to make sure fps is not in use while reading or writing. Other functions may also use this mechanism.

FUNCTION: fps_open_m10()

```
#define FPS_W_PLUS_OPEN_MODE
                                     8
#define FPS_A_OPEN_MODE
                                     16
#define FPS_A_PLUS_OPEN_MODE
                                     32
#define FPS_GENERIC_READ_OPEN_MODE
                                    (FPS_R_OPEN_MODE |
                                     FPS_R_PLUS_OPEN_MODE |
                                     FPS_W_PLUS_OPEN_MODE |
                                     FPS_A_PLUS_OPEN_MODE)
#define FPS_GENERIC_WRITE_OPEN_MODE (FPS_R_PLUS_OPEN_MODE |
                                     FPS_W_OPEN_MODE |
                                     FPS_W_PLUS_OPEN_MODE |
                                     FPS_A_OPEN_MODE |
                                     FPS_A_PLUS_OPEN_MODE)
// Prototype
      fps_open_m10(FILE_PROCESSING_STRUCT_m10 *fps, const si1 *function, si4 line, ui4 \
si4
            behavior_on_fail);
```

Opens the file specified by the FPS according to the FPS directive open_mode. If the mode permits file creation, the file will be created. If higher level directories are needed to open the file in the specified location, they too are created. Once open, the file is optionally locked according to the FPS directive's lock_mode. The file descriptor and file length are also updated.

FUNCTION: fps read m10()

Locks the file, reads in bytes bytes, and unlocks the file. Lock type is specified by the FPS directive's lock mode.

FUNCTION: fps unlock m10()

Releases the *advisory lock* on the file specified by the FPS. The function & line arguments are provided to know from whence the function was called in the case of failure.

NOTE: advisory locks often do not work on networked file systems.

FUNCTION: fps_write_m10()

Writes out_bytes bytes. If write_lock_on_write is the specified in the FPS directive's lock_mode, the file will be locked prior to the write and unlocked after the write. The file descriptor and file length are also updated. If update_universal_header is

set in the directives, the universal header CRCs will be updated, and the universal header rewritten. The file pointer is repositioned to the end of the file.

FUNCTION: free_channel_m10()

```
// Prototype
void free_channel_m10(CHANNEL_m10 *channel, TERN_m10 channel_allocated_en_bloc);
```

Frees all the memory pointed to by a CHANNEL structure including all memory associated with SEGMENT structures within it. If channel allocated en bloc == FALSE m10, the passed CHANNEL structure will itself be freed also.

FUNCTION: free_file_processing_struct_m10()

Frees a FILE_PROCESSING_STRUCT's raw_data buffer if not NULL, and then frees the FILE_PROCESSING_STRUCT. It also closes the FILE pointer, if it is open and the close_file directive == TRUE_m10. If the FPS contains a CMP processing struct and the free_CMP_processing_struct directive == TRUE_m10, this will also be freed. If the free_password_data directive == TRUE_m10, the FILE_PROCESSING_STRUCT's password_data will be freed. If allocated_en_bloc == FALSE_m10, the FPS structure will itself be freed also.

FUNCTION: free_metadata_m10()

```
// Prototype
void *free_metadata_m10(METADATA_m10 *metadata);
```

Frees passed metadata structure and associated memory.

FUNCTION: free_segment_m10()

```
// Prototype
void free_segment_m10(SEGMENT_m10 *segment, TERN_m10 segment_allocated_en_bloc);
```

Frees all the memory pointed to by a SEGMENT structure. If segment_allocated_en_bloc == FALSE_m10, the passed SEGMENT structure will itself be freed also.

FUNCTION: free_session_m10()

```
// Prototype
void free_session_m10(SESSION *session);
```

Frees all the memory pointed to by a SESSION structure including all memory associated with CHANNEL structures within it, and the SEGMENT structures within them. The passed SESSION structure will itself be freed also.

FUNCTION: generate_file_list_m10()

This function may seem a bit arcane, but it is really quite useful. It returns a list of files given the inputs as follows:

- 1. If the passed file_list not NULL, a new file list is still returned; the passed list will be freed if free_input_file_list == TRUE_m10. The point of this is to allow passing of lists with regex that will be expanded. If enclosing directory is not NULL, and the passed file list entries do not begin from root, the enclosing directory will be prepended to the file list entries prior to expansion.
- 2. If the passed file_list is NULL, the enclosing directory, name, or extension are not NULL, they will be incorporated into the a regex expansion. If name is NULL, it is replaced by "*" in the expansion; this is not true for enclosing_directory or extension.

The number of entries in the returned file_list is returned in n_out_files. Generate_file_list_m10() can be used to get a directory list also.

NOTE: If a file_list is passed should not be statically allocated, if free_input_file_list == TRUE_m10.

The path parts specify how the output file_list will be constructed.

Example 1:

Returns list of all time series channel directories (extension == "ticd") in /Data/MED_Files/Session_1, as full paths.

Example 2:

Returns list of all time series channel directories names in /Data/MED_Files/Session_1, as names only. Such a list could be used labels in a viewer, or to create a derivative MED session.

Example 3:

Returns the following in file_list (you can imagine the full session directory contents):

grid1.ticd

```
grid2.ticd
grid3.ticd
depth2.ticd
depth4.ticd
depth6.ticd
micro_1.ticd
micro_2.ticd
camera_1.vicd
camera_2.vicd
On return, "n_out_files" will of
```

On return, "n_out_files" will contain "10", and the input file_list will have been freed.

hex_str[HEX_STRING_BYTES(ENCRYPTION_KEY_BYTES)];

```
FUNCTION: generate_hex_string_m10()
```

```
// Prototype
si1 *generate_hex_string_m10(ui1 *bytes, si4 num_bytes, si1 *string);
#define HEX_STRING_BYTES_m10(x) ( ((x) + 1) * 3 )
```

Creates a hexadecimal string from "num_bytes" of the bytes in "bytes" into the string pointed to by "string". If string is NULL, it will be allocated. The length of the string required is: (num_bytes + 1) * 3. This is conveniently generated by the macro HEX_STRING_BYTES().

```
example 1:
```

ui1

FUNCTION: generate_MED_path_components_m10()

```
// Prototype
ui4 generate_MED_path_components_m10(si1 *path, si1 *MED_dir, si1 *MED_name);
```

Given a path to a MED directory or file, returns the full path to the enclosing directory in MED_dir, and the isolated name of the file (no path or extension) in MED_name, and the MED type code of the enclosing directory is the return value. If either MED_dir or MED_name are NULL, they will not be filled in.

The utility of this is to regularize a MED directory or file name into its path (including name and directory extension), and the isolated name. Thus:

```
generate_MED_path_components_m10(path_to_MED_file, MED_path, MED_name);
```

AND

```
generate MED path components m10(path to MED directory, MED path, MED name);
```

... result in the same contents of MED_path and MED_name and the same returned type for the directory.

These components can be used to easily build other MED file names, given the naming conventions of the MED hierarchy.

FUNCTION: generate_numbered_names_m10()

```
// Prototype
si1 **generate_numbered_names_m10(si1 **names, si1 *prefix, si4 number_of_names);
```

Given a prefix and number of names, the function returns a file_list with these names constructed using FILE_NUMBERING_DIGITS_m10 to prefix necessary zeros. Numbering is from 1. If names is NULL, it will be allocated, otherwise it will be used, and is presumed to be large enough.

FUNCTION: generate_recording_time_offset_m10()

```
// Constants
#define USE_SYSTEM_TIME -1
// Prototype
si8  generate_recording_time_offset_m10(si8 recording_start_time_uutc);
```

The function calculates the recording time offset from the passed recording_start_time_uutc and local time zone information. The recording time offset is stored in the MED globals. If recording_start_time_uutc equals USE SYSTEM TIME, the recording time offset will be based on the system time act the time of the function call,.

The function returns the recording time offset (useful only if USE_SYSTEM_TIME was passed).

FUNCTION: generate_segment_name_m10()

```
// Prototype
si1 *generate_segment_name_m10(FILE_PROCESSING_STRUCT *fps, si1 *segment_name);
```

A simple convenience function to generate the segment name from the channel name and segment number in the FPS's universal header. The result is stored in **segment_name** if it is not NULL. The result is allocated and returned otherwise. If allocated, the calling function is responsible for freeing it.

FUNCTION: generate_UID_m10()

```
// Prototype
ui8 generate_UID_m10(ui8 *uid);
```

Generates an 8-byte random number that is not one of the MED reserved values. If NULL is passed for uid, this function will return a uid value, but is not thread-safe.

Examples:

```
generate_UUID(&universal_header->file_UID);
or
universal_header->file_UID = generate_UUID(NULL); // not thread safe
FUNCTION: get_channel_target_values_m10()
// Prototype
TERN_m10
            get_channel_target_values_m10(CHANNEL_m10 *channel, si8 *target_uutc, si8 \
            *target_sample_number, si4 *target_segment_number, ui1 mode);
// Target Value Constants
#define FIND_START_m10
                                 1
                                 2
#define FIND END m10
Given a target uutc or target sample number and a CHANNEL structure, finds target uutc, target sample number, and
target segment number. The mode parameter must be either FIND START m10, or FIND END m10. The unknown
member of (target uutc, target sample number) should contain (UUTC NO ENTRY m10,
SAMPLE NUMBER NO ENTRY m10). Returns TRUE m10 on success, FALSE m10 on failure.
FUNCTION: get segment range m10()
// Prototype
      get_segment_range_m10(si1 **channel_list, si4 n_channels, TIME_SLICE_m10 *slice);
si4
typedef struct {
      TERN_m10
                  conditioned;
            start_time:
      si8
      si8
            end_time;
            start_sample_number; // session-relative (global indexing)
      si8
      si8
            end_sample_number; // session-relative (global indexing)
      si8
            local_start_sample_number; // segment-relative (local indexing)
            local_end_sample_number; // segment-relative (local indexing)
      si8
      si8
            number_of_samples;
      si4
            start_segment_number;
      si4
            end_seament_number;
      si8
            session_start_time;
      si8
            session_end_time;
            sample_number_reference_channel_name[BASE_FILE_NAME_BYTES_m10]; // channel
      si1
base name
            sample_number_reference_channel_index; // index of the sample number
      si4
                                                 //reference channel in the session
channel array
} TIME_SLICE_m10;
```

Finds the segment start and en number for the range described in the passed time slice. idx_ref_chan is needed if the channels in the channel list have different sampling frequencies, and the time slice specifies sample numbers.

idx_ref_chan is the name of the channel that should be used to decide cutoffs. Other members of the time slice will be filled in. The function returns the number of segments that need to be read.

See heading "Time Slice Usage" below.

FUNCTION: get_segment_target_values_m10()

Given a target_uutc or target_sample_number and a SEGMENT structure, finds target_uutc, and target_sample_number. The mode parameter must be either FIND_START_m10, or FIND_END_m10. The unknown member of (target_uutc, target_sample_number) should contain (UUTC_NO_ENTRY_m10, SAMPLE_NUMBER_NO_ENTRY_m10).

If the passed target_uutc or target_sample_number do not fall with in the segment, segment start or end parameters are returned as appropriate; hence the function returns void as it cannot fail.

FUNCTION: get_session_target_values_m10()

Given a target_uutc or target_sample_number and a SESSION structure, finds target_uutc, target_sample_number, and target_segment_number. The mode parameter must be either FIND_START_m10, or FIND_END_m10. The unknown member of (target_uutc, target_sample_number) should contain (UUTC_NO_ENTRY_m10, SAMPLE_NUMBER_NO_ENTRY_m10). Returns TRUE_m10 on success, FALSE_m10 on failure.

idx_ref_chan is needed if the channels in the channel list have different sampling frequencies, and the target specifies a sample number. idx_ref_chan is the name of the channel that should be used to decide cutoffs.

See get segment range m10() also.

FUNCTION: initialize_file_processing_directives_m10()

```
// Structures
typedef struct {
    TERN_m10     close_file;
    TERN_m10     flush_after_write;
    TERN_m10     update_universal_header; // when writing
```

```
TERN_m10
                  leave_decrypted; // if encrypted during write, return from write
                                    // function decrypted, also leave times unoffset
      TERN_m10
                  free_password_data; // when freeing FPS
                  free_CMP_processing_struct; // when freeing FPS
      TERN m10
      ui4
                  lock_mode;
      ui4
                  open_mode;
} FILE_PROCESSING_DIRECTIVES_m10;
// File Processing Directives Defaults
#define FPS_DIRECTIVE_CLOSE_FILE_DEFAULT_m10
                                                                  TRUE m10
                                                                   TRUE m10
#define FPS_DIRECTIVE_FLUSH_AFTER_WRITE_DEFAULT_m10
#define FPS_DIRECTIVE_FREE_CMP_PROCESSING_STRUCT_DEFAULT_m10
                                                                  TRUE_m10
#define FPS_DIRECTIVE_UPDATE_UNIVERSAL_HEADER_DEFAULT_m10
                                                                   FALSE m10
#define FPS_DIRECTIVE_LEAVE_DECRYPTED_DEFAULT_m10
                                                                   FALSE_m10
#define FPS_DIRECTIVE_LOCK_MODE_DEFAULT_m10
                                                                   FPS_NO_LOCK_MODE_m10
                  // Unix file locking may cause problems with networked file systems
// #define FPS_DIRECTIVE_LOCK_MODE_DEFAULT_m10 (FPS_READ_LOCK_ON_READ_OPEN_m10 | \
      FPS_WRITE_LOCK_ON_WRITE_OPEN_m10 | FPS_WRITE_LOCK_ON_READ_WRITE_OPEN_m10)
#define FPS_DIRECTIVE_OPEN_MODE_DEFAULT_m10
                                                                  FPS_NO_OPEN_MODE_m10
// Prototype
FILE PROCESSING DIRECTIVES m10
*initialize_file_processing_directives_m10(FILE_PROCESSING_DIRECTIVES_m10 *directives);
```

If NULL is passed a FILE_PROCESSING_DIRECTIVES structure is allocated and it's pointer returned. In either case, the fields of the structure are set to their default values.

FUNCTION: initialize_globals_m10()

```
// Prototype
void initialize_globals_m10(void);
```

Allocates (if NULL) and initializes globals_m10, the MED globals structure on the global heap. Variables are initialized to their default values, and tables are assigned or constructed. The globals are used by many functions in the library. It includes boolean fields stating whether structure alignment has been confirmed, lookup tables for CRC calculation, UTF8 printing, AES encryption, and SHA hash functions, the session recording time offset and UTC offset, and a verbose flag which if set will cause many library functions to show the output of their processing.

This function is called by initialize_medlib(), but can be called before initialize_medlib() to change a default value.

Example (used to see verbose output of initialization functions):

```
initialize_globals_m10();
globals_m10->verbose = TRUE_m10;
initialize_medlib();

FUNCTION: initialize_medlib_m10()
```

```
// Prototype
si4 initialize_medlib_m10(void);
```

Initializes MED_globals to default values (if the MED_globals pointer is NULL, which it is at the launch of the library), checks CPU endianness, checks MED structure alignments, seeds the random number generator with the current time, sets the file creation umask, and a loads the CRC, UTF8, AES, and SHA lookup tables into the global heap (not stack). Returns MED_TRUE if all structures are aligned, MED_FALSE if not. The function currently exits if the cpu endianness is not little endian. This can be changed if there is a demand for big endian processing going forward.

This example initializes MED_globals to their default values. It then sets verbose to MED_TRUE. Because MED_globals is not NULL, initialize_medlib() will not call initialize_MED_globals(), allowing verbose output of initialization routines, and preserving any other non-default global setting changes that were made.

FUNCTION: initialize_metadata_m10()

The function sets all fields in a METADATA structure to their NO_ENTRY values. No encryption is performed. Section 2 fields are set according to the FPS/s channel type.

If initialize for update == TRUE m10, the following section 2 fields are set to Zero rather than their No Entry values:

```
// time series, section 2
number_of_samples
number_of_blocks
maximum_block_byte
maximum_block_samples
maximum_block_difference_bytes
maximum_block_duration
number_of_discontinuities
maximum_contiguous_blocks
maximum_contiguous_block_bytes
maximum_contiguous_samples

// video, section 2
number_of_clips
maximum_clip_bytes
```

```
FUNCTION: initialize time slice m10()
// Structure
typedef struct {
      TERN_m10
                  conditioned;
            start_time;
      si8
      si8
            end_time;
      si8
            start_sample_number; // session-relative (global indexing)
            end_sample_number; // session-relative (global indexing)
      si8
            local_start_sample_number; // segment-relative (local indexing)
      si8
      si8
            local_end_sample_number; // segment-relative (local indexing)
      si8
            number_of_samples;
      si4
            start_segment_number;
      si4
            end_segment_number;
      si8
            session_start_time;
      si8
            session_end_time;
      si1
            sample_number_reference_channel_name[BASE_FILE_NAME_BYTES_m10]; // channel
                                                                           // base name
      si4
            sample_number_reference_channel_index; // index of the index reference
                                           // channel in the session channel array
} TIME_SLICE_m10;
// Prototype
TIME_SLICE_m10 *initialize_time_slice_m10(TIME_SLICE_m10 *slice);
The function allocates (if NULL is passed) and initializes the contents of a time slice structure.
See heading "Time Slice Usage" below.
FUNCTION: initialize_universal_header()
// Prototype
      initialize_universal_header_m10(FILE_PROCESSING_STRUCT_m10 *fps, ui4 type_code, \
si4
      TERN_m10 generate_file_UID, TERN_m10 originating_file);
// Universal Header Structure
typedef struct {
      // start robust mode region
      ui4
            header_CRC;
                           // CRC of the universal header after this field
                            // CRC of the entire file after the universal header
      ui4
            body_CRC;
      si8 file_end_time;
            number_of_entries;
      si8
            maximum_entry_size;
      ui4
      // end robust mode region
            segment_number;
      union { // anonymous union
```

```
struct {
                        type_string[TYPE_BYTES_m10];
                  si1
                  ui1
                        MED_version_major;
                  ui1
                        MED_version_minor;
                        byte_order_code;
                  ui1
            };
            struct {
                  ui4
                        type_code;
                  si1
                        type_string_terminal_zero; // not used - there for clarity
            };
      };
      si8
            session_start_time;
      si8
            file_start_time;
      si1
            session_name[BASE_FILE_NAME_BYTES_m10];
            channel_name[BASE_FILE_NAME_BYTES_m10];
      si1
      si1
            anonymized_subject_ID[UNIVERSAL_HEADER_ANONYMIZED_SUBJECT_ID_BYTES_m10];
      ui8
            session_UID;
      ui8
            channel_UID;
      ui8
            segment_UID;
      ui8
            file_UID;
      ui8
            provenance_UID;
            level_1_password_validation_field[PASSWORD_VALIDATION_FIELD_BYTES_m10];
      ui1
            level_2_password_validation_field[PASSWORD_VALIDATION_FIELD_BYTES_m10];
      ui1
      ui1
            level_3_password_validation_field[PASSWORD_VALIDATION_FIELD_BYTES_m10];
      ui1
            protected_region[UNIVERSAL_HEADER_PROTECTED_REGION_BYTES_m10];
            discretionary_region[UNIVERSAL_HEADER_DISCRETIONARY_REGION_BYTES_m10];
      ui1
} UNIVERSAL_HEADER_m10;
```

The function sets universal header fields to default values. If generate_file_UID == TRUE_m10, it will be created. If originating_file == TRUE_m10, the provenance_UID will be set to the value of the file_UID. It fills in the current library's MED version and endianness.

example:

```
initialize_universal_header(fps, TIME_SERIES_METADATA_FILE_TYPE_CODE_m10, TRUE_m10);
```

Initializes a time series metadata universal header with a new file UID, and the provenance UID set to the new file UID.

Returns the correlation of the distribution in the data to that expected from a normal distribution. Essentially a Kolmogorov-Smirnov test normalized to range [-1 to 0) = 0 & [0 to 1] = [0 to 254]. 255 is reserved for no entry. 0 is completely uncorrelated; 254 is "perfect" correlation. This is used as a noise score, and to decide whether lossy compression should be performed on a block if the CMP processing directive "require_normality" == TRUE_m10.

```
FUNCTION: MED_type_string_from_code_m10()
// Prototype
si1
       *MED_type_string_from_code_m10(ui4 code);
Returns a pointer to a type string for all MED types, or NULL if the code does not exist.
FUNCTION: MED_type_code_from_string_m10()
// Prototype
ui4
      MED_type_code_from_string_m10(si1 *string);
Returns a type code for all MED type strings, or NO FILE TYPE CODE m10 if no code exists for the passed string.
FUNCTION: merge_metadata_m10()
// Prototype
TERN m10
             merge_metadata_m10(FILE_PROCESSING_STRUCT_m10 *md_fps_1, \
              FILE_PROCESSING_STRUCT_m10 *md_fps_2, FILE_PROCESSING_STRUCT_m10 \
              *merged_md_fps);
If merged md fps == NULL, comparison results will be placed in md fps 1->metadata.
Returns TRUE m10 if md fps 1->metadata == md fps 2->metadata, FALSE m10 otherwise.
FUNCTION: merge_universal_headers_m10()
// Prototype
             merge_universal_headers_m10(FILE_PROCESSING_STRUCT_m10 *fps_1, \
TERN m10
             FILE_PROCESSING_STRUCT_m10 *fps_2, FILE_PROCESSING_STRUCT_m10 *merged_fps);
If merged fps == NULL, comparison results will be placed in fps 1->universal header.
Returns TRUE m10 if fps 1->universal header == fps 2->universal header, FALSE m10 otherwise.
FUNCTION: message_m10()
// Prototype
void message_m10(si1 *fmt, ...);
Prints a warning message to stdout unless:
       (globals m10->behavior on fail & SUPPRESS MESSAGE OUTPUT m10) != 0
and returns. Used like printf(). Also see error_message_m10(), warning_message_m10(), and force_behavior_m10().
Example:
message_m10("%s(): Test Message (called from line %d)", __FUNCTION__, \
__LINE__);
```

FUNCTION: numerical_fixed_width_string_m10()

```
// Prototype
si1 *numerical_fixed_width_string_m10(si1 *string, si4 string_bytes, si4 number);
```

Returns string, prepended with necessary number of zeros, to make a string of string_bytes characters containing the digits of number. If NULL is passed for string, it is allocated, and up to the caller to free. Useful in generating MED segment names, among other things.

FUNCTION: pad_m10()

```
// Prototype
si8  pad_m10(ui1 *buffer, si8 content_len, ui4 alignment);
```

Fills buffer beyond content_len (in bytes) with PAD_BYTE_VALUE, to next boundary determined by alignment. Returns (content_len + pad_bytes).

FUNCTION: process_password_data_m10()

```
// Prototype
TERN_m10
            process_password_data_m10(si1 *unspecified_password, si1 \
      *L1_password, si1 *L2_password, si1 *L3_password, si1 *L1_hint, si1 *L2_hint, \
      FILE_PROCESSING_STRUCT_m10 *fps);
// Structures
typedef struct {
            level_1_encryption_key[ENCRYPTION_KEY_BYTES_m10];
      ui1
            level_2_encryption_key[ENCRYPTION_KEY_BYTES_m10];
      si1
            level_1_password_hint[PASSWORD_HINT_BYTES_m10];
            level_2_password_hint[PASSWORD_HINT_BYTES_m10];
      ui1
            access_level;
            processed; // 0 or 1 (not ternary)
      ui1
} PASSWORD_DATA_m10;
```

Fills global PASSWORD DATA structure and set it to processed.

If no passwords are passed (all are NULL), it simply sets the PASSWORD_DATA structure to an access_level of zero (access to unencrypted data only).

If an unspecified_password is passed, the function will determine whether the password is a level 1 or level 2 password and set the access_level of the PASSWORD_DATA structure accordingly via the password_validation_fields in the passed universal header. Appropriate decryption keys are generated and put into the PASSWORD_DATA structure. This is generally used for reading MED files.

If a level_1_password, level_2_password, or level_3_password is passed, the password validation fields will be generated into the passed universal_header structure. The access_level of the PASSWORD_DATA structure will be set according to whether a level_1 or level_2 password was passed. Appropriate encryption keys are generated and put into the PASSWORD_DATA structure. This is generally used for writing new MED files. Note that for level 2 access, a level 1 password must be passed, even if level 1 encryption is never used in the new MED files.

NOTE: If the FILE_PROCESSING_STRUCT corresponds to a metadata file, the password hints will be copied to the PASSWORD DATA structure, otherwise they will be left empty. See set time and password data m10() also.

The function also sets processed field to TRUE.

Example 1:

```
process_password_data(password, NULL, NULL, NULL, NULL, fps);
```

Processes an unspecified password for reading by validating against the password validation fields in the universal_header. Depending on the access level, a level 1 or both a level 1 and level 2 decryption keys are generated into their appropriate fields in the PASSWORD DATA structure. A PASSWORD DATA structure pointer is returned.

Example 2:

```
process_password_data(NULL, level_1_password, level_2_password, \
NULL, NULL, NULL, fps);
```

In writing a new MED file, a level 1 and level 2 password are passed, and their password validation fields are written into the universal header. Both level 1 and level 2 encryption keys are generated into their appropriate fields in the PASSWORD_DATA structure.

FUNCTION: read_channel_m10()

```
// Prototype
CHANNEL_m10 *read_channel_m10(CHANNEL_m10 *chan, si1 *chan_dir, TIME_SLICE_m10 *slice, \
      si1 *password, TERN_m10 read_time_series_data, TERN_m10 \
      read_record_data);
// Channel Types
UNKNOWN_CHANNEL_TYPE_m10
                              -1
                                    // (NO_FILE_TYPE_CODE_m10)
TIME_SERIES_CHANNEL_TYPE_m10 1
                                    // (TIME_SERIES_CHANNEL_DIRECTORY_TYPE_CODE_m10)
                              2
VIDEO_CHANNEL_TYPE_m10
                                    // (VIDEO_CHANNEL_DIRECTORY_TYPE_CODE_m10)
// Structure
typedef struct {
      FILE_PROCESSING_STRUCT_m10
                                    *metadata_fps; // ephemeral
      FILE_PROCESSING_STRUCT_m10
                                    *record_data_fps;
      FILE_PROCESSING_STRUCT_m10
                                    *record_indices_fps;
                                    number_of_segments;
      si4
      SEGMENT_m10
                                    **segments;
                                    path[FULL_FILE_NAME_BYTES_m10];
      si1
      si1
                                    name[BASE_FILE_NAME_BYTES_m10];
      TIME_SLICE_m10
                                    time_slice;
} CHANNEL_m10;
```

This function will read the channel pointed to by chan_dir (full path to the channel directory) and fill in the the fields in the CHANNEL structure. If a channel structure is not passed (NULL passed), one will be allocated. A password should be passed to read encrypted fields if the global password structure has not already been set. In the case that no data is encrypted or only unencrypted data is needed, NULL can be passed for both fields.

If read_time_series_data == TRUE_m10, the time series segment data specified by slice will be read into its SEGMENT structures; otherwise only the segment data's universal header will be read into this field and the file pointer will be left at the beginning of the CMP block data for random or sequential reading. The same is true for the read_record_data parameter.

The CHANNEL metadata structure is ephemeral, i.e is the same as those contained in a segment FPS, but is not associated with a real file, rather it is constructed via a merge of all the segment metadata structures. It contains summary information of the segment metadata files. Fields whose values vary across segments and whose value cannot be expressed as a maximum, etc. are filled with their NO_ENTRY values. Likewise the universal header of this FPS represents a merge of the metadata universal headers from the segments.

The function returns a pointer to a CHANNEL structure, which is allocated if NULL was passed for chan.

example:

```
(void) read_MED_channel(&session->channels[i], full_file_name, NULL, NULL, password,
MED_FALSE, MED_FALSE);
```

This call reads the channel specified by full_file_name into a preallocated CHANNEL structure. A password is passed. The read_time_series_data and read_record_data flags are set to MED_FALSE, so only the universal headers will be read in from the segment files. All segments will be read because slice was NULL.

See heading "Time Slice Usage" below.

FUNCTION: read_file_m10()

```
// Prototype
                              *read_file_m10(FILE_PROCESSING_STRUCT_m10 *fps, si1 \
FILE_PROCESSING_STRUCT_m10
      *full_file_name, si8 number_of_items, ui1 **data_ptr_ptr, si8 *items_read, si1 \
      *password, ui4 behavior_on_fail);
// Structures
typedef struct {
      TERN m10
                                          mutex:
                                          full_file_name[FULL_FILE_NAME_BYTES_m10];
      si1
      FILE
                                           *fp; // file pointer
                                          fd; // file descriptor
      si4
                                          file_length;
      si8
      UNIVERSAL_HEADER_m10
                                           *universal_header;
                                          directives;
      FILE_PROCESSING_DIRECTIVES_m10
      METADATA_m10
                                           *metadata;
      TIME_SERIES_INDEX_m10
                                           *time_series_indices;
      VIDEO_INDEX_m10
                                          *video_indices;
      ui1
                                           *records;
      RECORD_INDEX_m10
                                           *record_indices;
      si8
                                          raw_data_bytes;
                                           *raw_data;
      ui1
      CMP_PROCESSING_STRUCT_m10
                                           *cps;
} FILE_PROCESSING_STRUCT_m10;
typedef struct {
                  close_file;
      TERN_m10
      TERN_m10
                  flush_after_write;
                  update_universal_header;
      TERN_m10
      TERN_m10
                  leave_decrypted;
                  free_password_data; // when freeing FPS
      TERN_m10
      TERN_m10
                  free_CMP_processing_struct; // when freeing FPS
```

```
ui4 lock_mode;
ui4 open_mode;
} FILE_PROCESSING_DIRECTIVES_m10;

// Constants
#define FPS_FULL_FILE_m10 -1
#define FPS UNIVERSAL HEADER ONLY m10 0
```

The function reads any MED file type, identified by its full path in full_file_name, (or the same field in a passed FPS), into a FILE_PROCESSING_STRUCT (FPS). If NULL is passed for the FPS one will be allocated. If the FPS's full_file_name field is NULL the passed file_name will be copied into this field. The file will be opened if it is not already open. If the close_file directive is set to FALSE_m10, the file will be left open, otherwise it will be closed after reading. The number_of_items parameter specifies how much of the file to read, how this translates into bytes will depend upon the file type.

The data are read into the raw_data field of the FPS. The FPS's universal_header pointer is set to point to the beginning of the raw data. The appropriate file type's structure pointer in the FPS is set to point to the raw data after the universal header.

If password_data is NULL, the function will process the passed password as an unspecified password and generate password_data. Otherwise password_data will be assigned to that field in the FPS.

read_MED_file() validates file CRCs according to the global CRC_mode. It decrypts encrypted data to the access level allowed by the password data. It offsets times according to the global recording_time_offset_mode.

If data_ptr_ptr is NULL data is read into the FPS's raw_data array. If *data_ptr_ptr is within the raw_data array boundaries, the data will be read into *data_ptr_ptr, and the array will be enlarged as necessary (modifying *data_ptr_ptr). If *data_ptr_ptr is custom, data will be read to there, but read_file_m10() will have no way of knowing if the target array is large enough, so this is the caller's responsibility.

The function returns a pointer to a FILE_PROCESSING_STRUCT or NULL if unsuccessful.

Example:

Reads the time series data file pointed to by full_file_name. read_MED_file() allocates and returns a pointer to the FPS. A PASSWORD_DATA structure is supplied, so password is not processed, and need not be passed. Only the universal header read in as the number_of_items is 0 (== UNIVERSAL_HEADER_ONLY_m10). The file is closed after reading as the FPS directive's default for close_file is TRUE_m10.

FUNCTION: read_segment_m10()

```
*time_series_indices_fps;
      FILE_PROCESSING_STRUCT_m10
      FILE_PROCESSING_STRUCT_m10
                                     *video_indices_fps;
      FILE_PROCESSING_STRUCT_m10
                                     *record_data_fps;
      FILE_PROCESSING_STRUCT_m10
                                     *record_indices_fps;
      FILE_PROCESSING_STRUCT_m10
                                     *segmented_session_record_data_fps;
                                     *seamented_session_record_indices_fps;
      FILE_PROCESSING_STRUCT_m10
                                     path[FULL_FILE_NAME_BYTES_m10];
      si1
      si1
                                     name[SEGMENT_BASE_FILE_NAME_BYTES_m10];
      TIME_SLICE_m10
                                     time_slice:
} SEGMENT_m10;
```

This function will read the segment pointed to by seg_dir (full path to the segment directory) and fill in the the fields in the SEGMENT structure. If a segment structure is not passed (NULL passed), one will be allocated. Either an unspecified password, or PASSWORD_DATA structure should be passed to read encrypted fields. In the case that no data is encrypted or only unencrypted data is needed, NULL can be passed for both fields.

If read_time_series_data == TRUE_m10 (and it is a time series segment), the time series data will be read into the SEGMENT structure's data_fps raw_data according to the limits in slice, or the full file if slice is NULL; otherwise only the segment data's universal header will be read and the file will be left open with the file pointer pointing to the CMP blocks. If read record data == TRUE m10, the same process is followed, but for segment records.

The function returns a pointer to the SEGMENT structure.

example:

```
segment = read_MED_segment(NULL, full_file_name, NULL, NULL, MED_TRUE, MED_TRUE);
```

This call will read the all the files of the segment pointed to by full_file_name and allocate and populate a SEGMENT structure. The passed password_data is assigned in the FILE_PROCESSING_STRUCTs. The time series data file is opened, read in full, and closed. Likewise for the segment record files, if present. This is an uncommon use for large data files as reading all of the data into memory is frequently impractical.

See heading "Time Slice Usage" below.

FUNCTION: read_session_m10()

```
// Prototype
SESSION_m10 *read_session_m10(si1 *sess_dir, si1 **chan_list, si4 n_chans, \
      TIME_SLICE_m10 *slice, si1 *idx_ref_chan, si1 *password, \
      TERN_m10 read_time_series_data, TERN_m10 read_record_data);
typedef struct {
      FILE_PROCESSING_STRUCT_m10
                                    *time_series_metadata_fps; // ephemeral
      FILE_PROCESSING_STRUCT_m10
                                    *video_metadata_fps; // ephemeral
      si4
                                    number_of_segments;
                                    number_of_time_series_channels;
      si4
      CHANNEL_m10
                                    **time_series_channels;
                                    number_of_video_channels;
      si4
      CHANNEL_m10
                                    **video_channels;
                                    *record_data_fps;
      FILE_PROCESSING_STRUCT_m10
      FILE PROCESSING STRUCT m10
                                    *record_indices_fps;
```

This function will read all the files associated with the session pointed to by sess_dir (full path to the session directory), or the channels listed in chan_list, and fill in the the fields in the SESSION structure. If a SESSION structure is not passed (NULL passed), one will be allocated. Either an unspecified password, or PASSWORD_DATA structure should be passed to read encrypted fields. In the case that no data is encrypted or only unencrypted data is needed, NULL can be passed for both fields.

If read_time_series_data == TRUE_m10 (for time series segments), the time series data will be read into the SEGMENT structure's data_fps raw_data according to the limits in slice, or the full file if slice is NULL; otherwise only the segment data's universal header will be read and the file will be left open with the file pointer pointing to the CMP blocks. If read record data == TRUE m10, the same process is followed, but for segment records.

The function returns a pointer to the SEGMENT structure.

Example:

This call will allocate a SESSION structure and read all files associated with the MED session specific by sess_dir and fill in the fields of at the SESSION structure and all of its substructures. It will not read the segment data, or record data, but the universal headers of those files will be read, and the files will be left open. Their file pointers will be left at the beginning of the data after the universal header. All other files will be read completely into their FILE PROCESSING STRUCTs and closed.

See heading "Time Slice Usage" below.

```
FUNCTION: read_time_series_data_m10()
```

This function reads a sample range from a segment. The parameters local_start_idx and local_end_idx are segment relative. The data are decompressed to seg->time_series_data_fps->cps->decompressed_ptr, and this pointer is updated.

It returns the number of samples read, which may be less than (local_end_idx - local_start_idx + 1) if either exceeds the segment boundaries.

FUNCTION: reallocate file processing struct m10()

This function reallocates the raw_data array to new_raw_data_bytes bytes. Existing data are preserved, extra bytes are zeroed. The raw_data_bytes field of the FPS is updated and appropriate pointers in the FPS are updated.

FUNCTION: recover_passwords_m10()

```
// Prototype
void recover_passwords_m10(si1 *L3_password, UNIVERSAL_HEADER_m10 *universal_header);
```

This function will recover level 1 & level 2 passwords if they were created with a level 3 password, and it is passed.

FUNCTION: remove_recording_time_offset_m10()

```
// Prototype
inline void remove_recording_time_offset_m10(si8 *time);
```

The global recording time offset is removed from the passed μUTC time.

FUNCTION: reset_metadata_for_update_m10()

```
// Prototype
void reset_metadata_for_update_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Resets a metadata structure section 2 fields for update. See initialize_metadata_m10() for details. Useful when acquiring new segment data and reusing the same segment metadata structures.

FUNCTION: sample_number_for_uutc_m10()

```
// Target Value Constants
#define DEFAULT MODE m10
                                0
#define FIND_START_m10
                                 1
#define FIND_END_m10
                                 2
                                 3
#define FIND_CENTER_m10
#define FIND_CURRENT_m10
                                4
                                 5
#define FIND_NEXT_m10
#define FIND_CLOSEST_m10
                                6
// Prototype
      sample_number_for_uutc_m10(si8 ref_sample_number, si8 ref_uutc, si8 target_uutc,
sf8 sampling_frequency, FILE_PROCESSING_STRUCT_m10 *time_series_indices_fps, ui1 mode);
```

Return a sample number for a given uutc. Mode should be a member of { FIND_CURRENT_m10, FIND_CLOSEST_m10, FIND_NEXT_m10 }.

```
FIND_CURRENT_m10 (default): sample period within which the target_uutc falls FIND_CLOSEST_m10: sample number closest to the target_uutc
```

FIND NEXT m10: sample number following the sample period within which the target uutc falls

```
(FIND NEXT m10 == FIND CURRENT m10 + 1)
```

Examples:

- Return sample number extrapolated from ref_sample_number sample_number_for_uutc_m10(ref_sample_number, ref_uutc, target_uutc, sampling_frequency, NULL, 0, mode);
- 2) Return sample number extrapolated from closest time series index in local (segment-relative) sample numbering sample_number_for_uutc_m10(SAMPLE_NUMBER_NO_ENTRY_m10, UUTC_NO_ENTRY_m10, \ target_uutc, sampling_frequency, tsi, number_of_indices, mode);
- 3) Return sample number extrapolated from closest time series index in absolute (channel-relative) sample numbering. In this case ref_sample_number is the segment absolute start sample number. sample_number_for_uutc_m10(ref_sample_number, UUTC_N0_ENTRY_m10, \target_uutc, sampling_frequency, tsi, number_of_indices, mode);

FUNCTION: search segment metadata m10()

```
// Prototype
TERN_m10 search_segment_metadata_m10(si1 *MED_dir, TIME_SLICE_m10 *slice);
```

Used to find segment range encompassed by slice when Sgmt records do not exist (plug: they are optional, but tiny, and make this process much more efficient). Returns TRUE m10 on success, FALSE M10 on failure.

See heading "Time Slice Usage" below.

FUNCTION: search_Sgmt_records_m10()

```
// Prototype
TERN_m10 search_Sgmt_records_m10(si1 *MED_dir, TIME_SLICE_m10 *slice);
```

Used to find segment range encompassed by slice (plug: Sgmt records are optional, but tiny, and make this process much more efficient). Returns TRUE m10 on success, FALSE M10 on failure.

See heading "Time Slice Usage" below.

FUNCTION: segment_sample_number_to_time_m10()

```
// Prototype
si8 segment_sample_number_to_time_m10(si1 *seg_dir, si8 local_sample_number, si8
absolute_start_sample_number, sf8 sampling_frequency, ui1 mode)
```

For a given segment, this function returns a μ UTC time for a given sample index. If absolute_start_sample_number == SAMPLE_NUMBER_NO_ENTRY_m10 or sampling_frequency == FREQUENCY_NO_ENTRY_m10, the function will get these values from the segment metadata file. If they are known, passing them makes the function more efficient.

The returned value is an absolute index, numbered relative to the session, not the segment.

FUNCTION: set_global_time_constants_m10()

```
// Structure
typedef struct {
            country[METADATA_RECORDING_LOCATION_BYTES_m10];
            country_acronym_2_letter[3]; // two-letter acronym; (ISO 3166 ALPHA-2)
      si1
      si1
            country_acronym_3_letter[4]; // three-letter acronym (ISO-3166 ALPHA-3)
      si1
            territory[METADATA_RECORDING_LOCATION_BYTES_m10];
      si1
            territory_acronym[TIMEZONE_STRING_BYTES_m10];
      si1
            standard_timezone[TIMEZONE_STRING_BYTES_m10];
      si1
            standard_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10];
      si4
            standard_UTC_offset; // seconds
      si4
            observe_DST;
      si1
            daylight_timezone[TIMEZONE_STRING_BYTES_m10];
            daylight_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10];
      si1
      si1
            daylight_time_start_description[METADATA_RECORDING_LOCATION_BYTES_m10];
      si8
            daylight_time_start_code; // DAYLIGHT_TIME_CHANGE_CODE_m10
      si1
            daylight_time_end_description[METADATA_RECORDING_LOCATION_BYTES_m10];
      si8
            daylight_time_end_code; // DAYLIGHT_TIME_CHANGE_CODE_m10
} TIMEZONE_INFO_m10;
// Prototype
void set_qlobal_time_constants_m10(TIMEZONE_INFO_m10 *timezone_info, si8
session_start_time);
```

Uses information in timezone_info to find the matching entry in the global timezone table, and then set time globals accordingly. Only enough information to make a solitary match is necessary. If there are multiple possible matches, a prompt dialog is initiated. If a value is passed for session_start_time (I.e. not zero), the global recording_time_offset is set also.

session start time parameter:

- pass zero to just match the timezone info (e.g. to get the standard UTC offset based on locale)
 - global recording time offset is not set
 - set global recording_time_offset by calling generate_recording_time_offset_m10() separately after generating the session_start_time parameter
- pass CURRENT_TIME_m10 to use the current time to generate the global recording time_offset
- pass an unoffset μUTC to use that to generate the global recording_time_offset

FUNCTION: set_time_and_password_data_m10()

```
// Prototype
TERN_m10 set_time_and_password_data_m10(si1 *unspecified_password, si1 \
     *MED_directory, si1 *section_2_encryption_level, si1 *section_3_encryption_level);
```

Finds the closest metadata file given a MED directory, and reads it using the unspecified password. The metadata is used to fill in the global time data, and the unspecified password is used, in conjunction with the metadata file, to fill the global a password data structure. The metadata section 2 & 3 encryption levels are also returned. The metadata file is closed and freed. This function is useful when beginning to read a series of files in a MED session, as these functions need only be performed once. TRUE is returned on success, FALSE on failure.

NOTE: reading any metadata file with read file m10(), and then freeing it, will accomplish the same thing as this function.

```
FUNCTION: show_file_processing_struct_m10()
// Prototype
void show_file_processing_struct_m10(FILE_PROCESSING_STRUCT_m10 *fps);
// Structures
typedef struct {
      TERN_m10
                                            mutex;
      si1
                                            full_file_name[FULL_FILE_NAME_BYTES_m10];
      FILE
                                                    // file pointer
                                            fd;
                                                    // file descriptor
      si4
      si8
                                            file_length;
      UNIVERSAL_HEADER_m10
                                            *universal_header;
      FILE_PROCESSING_DIRECTIVES_m10
                                            directives;
      PASSWORD_DATA_m10
                                            *password_data;
      METADATA_m10
                                            *metadata;
      TIME_SERIES_INDEX_m10
                                            *time_series_indices;
      VIDEO_INDEX_m10
                                            *video_indices;
      ui1
                                            *records;
                                            *record_indices;
      RECORD_INDEX_m10
      si8
                                            raw_data_bytes;
                                            *raw_data;
      ui1
      CMP_PROCESSING_STRUCT_m10
                                            *cps;
} FILE_PROCESSING_STRUCT_m10;
Displays all the elements of a FILE_PROCESSING_STRUCT_m10 structure.
FUNCTION: show_globals_m10()
// Prototype
void show_globals_m10();
Displays MED globals.
FUNCTION: show_metadata_m10()
// Structure
typedef struct {
      METADATA_SECTION_1_m10
                                                  section_1;
      union {
            TIME_SERIES_METADATA_SECTION_2_m10
                                                  time_series_section_2;
            VIDEO_METADATA_SECTION_2_m10
                                                  video_section_2;
      };
      METADATA_SECTION_3_m10
                                                  section_3;
} METADATA_m10;
```

void show_metadata_m10(FILE_PROCESSING_STRUCT_m10 *fps, METADATA_m10 *md);

// Prototype

Displays all the elements of a METADATA structure of the type specified by the passed FPS or METADATA structure pointer. Only one of the two parameters needs to be passed. The other can be NULL.

```
FUNCTION: show_password_data_m10()
```

```
// Structures
typedef struct {
           level_1_encryption_key[ENCRYPTION_KEY_BYTES_m10];
      ui1
            level_2_encryption_key[ENCRYPTION_KEY_BYTES_m10];
      ui1
      si1
           level_1_password_hint[PASSWORD_HINT_BYTES_m10];
            level_2_password_hint[PASSWORD_HINT_BYTES_m10];
      si1
      ui1
            access_level;
            processed; // 0 or 1 (not ternary)
      ui1
} PASSWORD_DATA_m10;
// Prototype
void show_password_data_m10(FILE_PROCESSING_STRUCT_m10 *fps);
```

Displays all the elements of a PASSWORD_DATA structure. Only one of the two parameters needs to be passed; the other can be NULL.

FUNCTION: show_records_m10()

```
// Constants
#define UNKNOWN_NUMBER_OF_ENTRIES_m10 -1
#define ALL_TYPES_CODE_m10 (ui4) 0xFFFFFFF

// Prototype
void show_records_m10(FILE_PROCESSING_STRUCT_m10 *fps, ui4 type_code);
```

This function displays the contents of the records data file of type type_code, or all records if type_code == ALL_TYPES_CODE_m10. If the record needs to be decrypted and the access level is sufficient, the record will be decrypted. show_records_m10() calls show_record_m10() for each record to be displayed. show_record_m10() resides in the medrec_m10.c file. The number of records is read from the universal header's number_of_entries field. If that field contains UNKNOWN_NUMBER_OF_ENTRIES_m10, the function will still work (but could fail in the case of an incomplete terminal record).

```
FUNCTION: show_time_slice_m10()
```

```
// Prototype
void show_time_slice_m10(TIME_SLICE_m10 *slice);
```

This function displays the contents of a time slice.

FUNCTION: show_timezone_info_m10()

```
// Structure
typedef struct {
```

```
si1
            country[METADATA_RECORDING_LOCATION_BYTES_m10];
      si1
            country_acronym_2_letter[3]; // (ISO 3166 ALPHA-2)
      si1
            country_acronym_3_letter[4]; // (ISO-3166 ALPHA-3)
            territory[METADATA_RECORDING_LOCATION_BYTES_m10];
      si1
      si1
            territory_acronym[TIMEZONE_STRING_BYTES_m10];
      si1
            standard_timezone[TIMEZONE_STRING_BYTES_m10];
            standard_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10];
      si1
            standard_UTC_offset; // seconds
      si4
      si4
            observe_DST;
      si1
            daylight_timezone[TIMEZONE_STRING_BYTES_m10];
      si1
            daylight_timezone_acronym[TIMEZONE_ACRONYM_BYTES_m10];
      si1
            daylight_time_start_description[METADATA_RECORDING_LOCATION_BYTES_m10];
            daylight_time_start_code; // DAYLIGHT_TIME_CHANGE_CODE_m10 as si8
      si8
      si1
            daylight_time_end_description[METADATA_RECORDING_LOCATION_BYTES_m10];
            daylight_time_end_code; // DAYLIGHT_TIME_CHANGE_CODE_m10 as si8
      si8
} TIMEZONE_INFO_m10;
// Prototype
void show_timezone_info_m10(TIMEZONE_INFO_m10 *timezone_entry);
This function displays the contents of a TIMEZONE INFO m10 structure.
FUNCTION: show_universal_header_m10()
// Structure
typedef struct {
      // start robust mode region
      ui4
            header_CRC;
                           // CRC of the universal header after this field
                        // CRC of the entire file after the universal header
      ui4
            body_CRC;
            file_end_time;
      si8
      si8
            number_of_entries;
      ui4
            maximum_entry_size;
      // end robust mode region
      si4
            seament_number;
      union { // anonymous union
            struct {
                  si1
                        type_string[TYPE_BYTES_m10];
                        MED_version_major;
                  ui1
                        MED_version_minor;
                  ui1
                        byte_order_code;
                  ui1
            };
            struct {
                        type_code;
                  ui4
                        type_string_terminal_zero; // not used - there for clarity
                  si1
            };
      };
            session_start_time;
      si8
      si8
            file_start_time;
      si1
            session_name[BASE_FILE_NAME_BYTES_m10];
```

```
si1
            channel_name[BASE_FILE_NAME_BYTES_m10];
      si1
            anonymized_subject_ID[UNIVERSAL_HEADER_ANONYMIZED_SUBJECT_ID_BYTES_m10];
      ui8
            session_UID;
      ui8
            channel_UID;
      ui8
            segment_UID;
      ui8
            file_UID;
            provenance_UID;
      ui8
            level_1_password_validation_field[PASSWORD_VALIDATION_FIELD_BYTES_m10];
      ui1
      ui1
            level_2_password_validation_field[PASSWORD_VALIDATION_FIELD_BYTES_m10];
            level_3_password_validation_field[PASSWORD_VALIDATION_FIELD_BYTES_m10];
      ui1
            protected_region[UNIVERSAL_HEADER_PROTECTED_REGION_BYTES_m10];
      ui1
      ui1
            discretionary_region[UNIVERSAL_HEADER_DISCRETIONARY_REGION_BYTES_m10];
} UNIVERSAL_HEADER_m10;
// Prototype
void show_universal_header_m10(FILE_PROCESSING_STRUCT_m10 *fps, UNIVERSAL_HEADER_m10
*uh);
```

This function displays the contents of a UNIVERSAL_HEADER_m10 structure. Only one of the two parameters needs to be passed; the other can be NULL.

```
FUNCTION: size_string_m10()

// Prototype
si1 *size_string_m10(si1 *size_str, si8 n_bytes);

// size_str buffer should be of length SIZE_STRING_BYTES_m10;
```

Returns a pointer to a string describing the number of bytes (n_bytes) in the largest size units covered by the size. If size_str is not NULL it will be used for the return string; if not a pointer to a static string is returned, which is not thread safe.

SECTION: Time Slice Usage

```
// Structure
typedef struct {
      TERN_m10
                  conditioned;
            start_time;
      si8
      si8
            end_time;
      si8
            start_sample_number; // session-relative (global indexing)
            end_sample_number; // session-relative (global indexing)
      si8
            local_start_sample_number; // segment-relative (local indexing)
      si8
            local_end_sample_number; // segment-relative (local indexing)
      si8
            number_of_samples;
      si8
      si4
            start_segment_number;
      si4
            end_segment_number;
      si8
            session_start_time;
      si8
            session_end_time;
      si1
            sample_number_reference_channel_name[BASE_FILE_NAME_BYTES_m10]; // channel
```

```
// base name
            sample_number_reference_channel_index; // index of the index reference
      si4
                                          // channel in the session channel array
} TIME_SLICE_m10;
// Constants
#define BEGINNING_OF_SAMPLE_NUMBERS_m10
                                          ((si8) 0x00000000000000000)
#define END_OF_SAMPLE_NUMBERS_m10
                                          ((si8) 0x7FFFFFFFFFFFFF)
#define SAMPLE_NUMBER_NO_ENTRY_m10
                                          ((si8) 0x80000000000000000)
#define UUTC_NO_ENTRY_m10
                                          ((si8) 0x80000000000000000)
#define UUTC_EARLIEST_TIME_m10
                                          ((si8) 0x0000000000000000)
                                          // 00:00:00.000000 Thursday, 1 Jan 1970, UTC
#define UUTC LATEST TIME m10
                                          ((si8) 0x7FFFFFFFFFFFFF)
                                          // 04:00:54.775808 Sunday, 10 Jan 29424, UTC
#define BEGINNING_OF_TIME_m10
                                          UUTC_EARLIEST_TIME_m10
#define END_OF_TIME_m10
                                          UUTC_LATEST_TIME_m10
```

The time slice is used throughout the library to pass a set of parameters that describe a portion of time that occurred within a MED session. The slice will accept either times or indices as boundaries. The search functions fill in the unfilled values, i.e. if times are passed, samples will be returned. The boundary values themselves might also be modified, if for instance the session end time occurs before the requested time.

```
To begin with the first sample in a session:
slice->start_time = BEGINNING_OF_TIME_m10; ...AND... slice->start_sample_number =
SAMPLE_NUMBER_NO_ENTRY_m10;
...OR...
slice->start_sample_number = BEGINNING_OF_SAMPLE_NUMBERS_m10; ...AND... slice->start_time =
UUTC_NO_ENTRY_m10;

To finish with the last sample in a session:
slice->end_time = END_OF_TIME_m10; ...AND... slice->end_sample_number = SAMPLE_NUMBER_NO_ENTRY_m10;
...OR...
slice->end_sample_number = END_OF_SAMPLE_NUMBERS_m10; ...AND... slice->end_time = UUTC_NO_ENTRY_m10;
```

NOTE: If indices are passed as the search medium, and the sampling frequency varies between channels in the selected channel set, an **index_reference_channel_name** must be supplied. This is the channel to which the passed indices refer. The other channels will be returned based on the points in time that the passed indices refer to in the index reference channel. If no index reference channel is passed when one is required, a warning is displayed and the first channel in the channel set will be used as the index reference channel.

The functions handle offset and un-offset times without modification. If the times are < 0, they are considered to be microseconds **relative to the session start time**. E.g. to get the first second of data: $slice->start_time = 0$; $slice->end_time = 999999$. These times are considered relative. On return, the times will be replaced by absolute times (offset applied).

FUNCTION: time_string_m10()

```
// Text Color String Constants
#define TC_BLACK_m10 "\033[30m"
#define TC_RED_m10 "\033[31m"
#define TC_GREEN_m10 "\033[32m"
#define TC_YELLOW_m10 "\033[33m"
#define TC_BLUE_m10 "\033[34m"
```

```
#define TC_MAGENTA_m10
                                 "\033[35m"
#define TC CYAN m10
                                 "\033\\\ 36m\"
#define TC_WHITE_m10
                                 "\033\\\ 37m\"
#define TC_BRIGHT_BLACK_m10
                                 "\033\[30;1m"
#define TC_BRIGHT_RED_m10
                                 "\033[31;1m"
#define TC_BRIGHT_GREEN_m10
                                 "\033\[\]32;1m"
#define TC_BRIGHT_YELLOW_m10
                                 "\033\[33;1m"
#define TC_BRIGHT_BLUE_m10
                                 "\033\[34;1m"
#define TC_BRIGHT_MAGENTA_m10
                                 "\033\G35;1m"
#define TC_BRIGHT_CYAN_m10
                                 "\033[36;1m"
#define TC_BRIGHT_WHITE_m10
                                 "\033\[37;1m"
#define TC_RESET_m10
                                 // Prototype
      *time_string_m10(si8 uutc, si1 *time_str, TERN_m10 fixed_width, TERN_m10 \
si1
relative_days, si4 colored_text, ...);
// time_str buffer should be of length TIME_STRING_BYTES_m10;
```

Returns a string with local date and time from a µUTC time. If time_str is not NULL it will be used for the return string; if not a pointer to a static string is returned, which is not thread safe.

If uutc == 0, the current time will be returned.

If fixed width == TRUE m10, the string will be formatted so that all times have the same width.

If relative_days == TRUE_m10, the string date will be displayed as days from session start; first day is "Day 0001". This is often a more intuitive format, particularly for offset times, which otherwise would display day 1 as "January 1, 1970".

If colored_text == TRUE_m10, two more arguments are expected: date_color & time_color. The arguments should be one of the defined text color strings (above).

If a recording time offset is applied the standard timezone acronym is set to "oUTC", and the standard timezone string is set to "offset Coordinated Universal Time".

If Daylight Saving Time (DST) was in effect at the passed time, in the recording locale, it will be applied and reflected in the timezone acronym and string.

FUNCTION: ts_sort_m10()

```
// Prototype
si8 ts_sort_m10(si4 *x, si8 len, NODE_m10 *nodes, NODE_m10 *head, NODE_m10 *tail, si4 \
    return_sorted_ts, ...);
```

This is an efficient sorting algorithm for *time series data*. If nodes are NULL they will be allocated and freed, but head and tail nodes should still be passed. If return_sorted_ts == TRUE_m10, an extra argument should be passed which is the array into which to place the sorted data. This can be the input array if desired. The node array (linked list) is often the target form of the data; expanding back to a sorted array may be unnecessary and inefficient.

FUNCTION: unescape_spaces_m10()

```
// Prototype
```

```
void unescape_spaces_m10(si1 *string);
```

This function removes backslashes occurring before spaces in the passed string.

```
FUNCTION: uutc_for_sample_number_m10()
```

```
// Prototype
si8
      uutc_for_sample_number_m10(si8 ref_sample_number, si8 ref_uutc, si8 \
      target_sample_number, sf8 sampling_frequency, FILE_PROCESSING_STRUCT_m10 \
      *time_series_indices_fps, ui1 mode);
// Target Value Constants
#define DEFAULT_MODE_m10
                                0
                                 1
#define FIND START m10
#define FIND_END_m10
                                 2
                                 3
#define FIND_CENTER_m10
#define FIND_CURRENT_m10
                                4
                                 5
#define FIND_NEXT_m10
#define FIND_CLOSEST_m10
                                6
```

Return a μ UTC for a given sample number. Mode should be a member of { FIND_START_m10, FIND_END_m10, FIND_CENTER m10 }.

Sample time is defined as the period from sample onset until the next sample. FIND_START_m10 (default): first uutc >= start of target_sample_number period FIND_END_m10: last uutc < start of next sample period

FIND CENTER_m10: uutc closest to the center of the sample period

Examples:

- 1) Return uutc extrapolated from ref_uutc with sample numbering in context of ref_sample_number & target_sample_number
- 2) Return uutc extrapolated from ref_uutc, assumed to occur at sample number 0, with local (segment-relative) sample numbering

3) Return uutc extrapolated from ref_uutc with local (segment-relative) sample numbering

4) Return uutc extrapolated from closest time series index using absolute sample numbering uutc = uutc_for_sample_number_m10(ref_sample_number, UUTC_NO_ENTRY_m10, \ target_sample_number, sampling_frequency, time_series_indices_fps, mode);

FUNCTION: validate_record_data_CRCs_m10()

```
// Prototype
TERN_m10 validate_record_data_CRCs_m10(RECORD_HEADER_m10 *record_header, si8 \
```

```
number_of_items);
```

The function validates the record header CRCs for number_of_items records pointed to by record_header. Returns TRUE m10 if all CRCs are valid, FALSE M10 otherwise.

```
FUNCTION: validate time series data CRCs m10()
// Prototype
TERN_m10
             validate_time_series_data_CRCs_m10(CMP_BLOCK_FIXED_HEADER_m10 \
             *block_header, si8 number_of_items);
The function validates the CMP block header CRCs for number of items CMP blocks pointed to by block header.
Returns TRUE m10 if all CRCs are valid, FALSE M10 otherwise.
FUNCTION: warning_message_m10()
// Prototype
void warning_message_m10(si1 *fmt, ...);
Prints a warning message to stderr unless:
      (globals m10->behavior on fail & SUPPRESS WARNING OUTPUT m10) != 0
and returns. Used like fprintf(). Also see error_message_m10(), message_m10(), and force_behavior_m10().
Example:
warning_message_m10("%s(): No samples in block (called from line %d)\n", __FUNCTION__, \
__LINE__);
FUNCTION: write_file_m10()
// Constants
#define FPS_FULL_FILE_m10
                                               -1
#define FPS_UNIVERSAL_HEADER_ONLY_m10
                                               0
// Prototype
```

The function will write out the file contained in the FILE_PROCESSING_STRUCT. If the file is not yet open, it will be opened. If the file requires encryption it will be encrypted. Times will be offset according to the global recording_time_offset_mode. The file CRCs will be calculated according to the global CRC_mode and the entered into the universal header. It returns the number of bytes written. If the close_file directive is set to TRUE_m10, the file will be closed after writing, otherwise it will be left open.

write_file_m10(FILE_PROCESSING_STRUCT_m10 *fps, ui8 number_of_items, void \

Specifics of function behavior:

```
1) If (fps->fp == NULL)
```

si8

- a) Opens file for writing and creates directory tree to the file if it doesn't exist
- b) Writes out universal header to set file pointer to end of universal header
- c) Clobbers file if it exists

*data_ptr, ui4 behavior_on_fail);

```
2) If (number of items == FPS FULL FILE m10)
    number of items set to universal header->number of entries
3) If (number of items == 0) // for clarity in code, the constant FPS_UNIVERSAL_HEADER_ONLY_m10 is defined as 0
      a) the universal header will be written out
      b) universal header is not updated unless fps->directives.update universal header == TRUE m10
      c) the file pointer will be left at the end of the universal header
4) Data is written from data ptr to the current file pointer
      if (data ptr == NULL), data ptr is set to end of universal header
5) All times are offset
6) All encryptable file types are encrypted
7) All CRCs are calculated or updated
8) The universal header field number of entries is increased by the calling argument number of items. If overwriting
existing data, or truncating a file, this field should be set explicitly.
9) The universal header field maximum entry size is updated if the size of any of the items written exceeds its current
value. If overwriting existing data, or truncating a file, this field should be set explicitly.
10) Output is written to files according to number of items:
      a) time series data files: an item is a compressed data block
      b) time series indices files: an item is a time series index
      c) record data files: an item is a record
      d) record index files: an item is a record index
      e) metadata files: an item is a metadata structure
11) If (fps->directives.update universal header == TRUE m10)
      a) the universal header CRC will be updated and the universal header will be written out
      b) the file pointer is repositioned to the end of the file
12) If (fps->directives.close file == TRUE m10)
      the universal header is updated before closure: fps->directives.update universal header does not need to be set
13) If (behavior on fail == USE GLOBAL BEHAVIOR m10)
       behavior on fail is set to globals m10->behavior on fail
***********************************
// Structures
typedef struct {
      // CMP block header fixed region start
      ui8
                block_start_UID;
      ui4
                block_CRC;
      ui4
                block_flags;
                start_time;
      si8
                acquisition_channel_number;
      si4
                total_block_bytes;
      ui4
       // CMP block encryption start
      ui4
                number_of_samples;
      ui2
                number_of_records;
```

```
ui2
              record_region_bytes;
     ui4
              parameter_flags;
     ui2
             parameter_region_bytes;
              protected_region_bytes;
     ui2
             discretionary_region_bytes;
     ui2
     ui2
             model_region_bytes;
             total_header_bytes;
     ui4
     // CMP block header variable region start
} CMP_BLOCK_FIXED_HEADER_m10;
typedef struct {
                 mode; // CMP_COMPRESSION_MODE_m10, CMP_DECOMPRESSION_MODE_m10
     ui4
     ui4
                 algorithm; // RED, PRED, or MBE
     si1
                  encryption_level; // encryption level for data blocks:
                                    // passed in compression
     TERN_m10
                 fall_through_to_MBE; // if MBE would be smaller than RED/PRED,
                                       // use MBE for that block
                 reset_discontinuity; // if discontinuity directive == TRUE_m10,
     TERN_m10
                                       // reset to FALSE_m10 after compressing the
                                       // block
     TERN_m10
                 include_noise_scores;
                 no_zero_counts; // in RED & PRED codecs (when blocks must be
     TERN_m10
                                  // encoded with non-block statistics. This is a
                                  // special case.)
     TERN_m10
                  free_password_data; // when freeing CPS
                 set_derivative_level; // value passed in "derivative_level"
     TERN_m10
                                        // parameter
     TERN_m10
                 find_derivative_level; // mutually exclusive with
                                         // "set_derivative_level"
     // lossy compression directives
                 detrend_data; // Lossless operation, but most useful for lossy
     TERN_m10
                                // compression.
                 require_normality; // For lossy compression - use lossless if data
     TERN_m10
                                     // amplitudes are too oddly distributed. Pairs
                                     // with "minimum_normality" parameter.
     TERN_m10
                 use_compression_ratio; // Used in "find" directives. Mutually
                                         // exclusive with
                                         // "use_mean_residual_ratio".
                 use_mean_residual_ratio; // Used in "find" directives. Mutually
     TERN_m10
                                           // exclusive with
                                           // "use_compression_ratio".
                 use_relative_ratio; // divide goal ratio by the block coefficient
     TERN_m10
                                      // of variation in lossy compression routines
                                      // (more precision in blocks with higher
                                      // variance)
                 set_amplitude_scale; // value passed in "amplitude_scale"
     TERN m10
                                       // parameter
                 find_amplitude_scale; // mutually exclusive with
     TERN_m10
                                        // "set_amplitude_scale"
                 set_frequency_scale; // value passed in "frequency_scale"
     TERN_m10
```

```
// parameter
                  find_frequency_scale; // mutually exclusive with
      TERN m10
                                         // "set_frequency_scale"
} CMP_DIRECTIVES_m10;
typedef struct {
                  number_of_block_parameters;
      si4
                  *block_parameters; // pointer beginning of parameter region of block
      ui4
                                      // header
                  block_parameter_map[CMP_PF_PARAMETER_FLAG_BITS_m10];
      ui4
                  minimum_sample_value; // found on compression, stored for use in
      si4
                                         // METADATA (and MBE, if used)
      si4
                  maximum_sample_value; // stored for use in METADATA (and MBE, if used)
                  discontinuity; // set if block is first after a discontinuity, passed
      TERN_m10
                                  // in compression, returned in decompression
                  no_zero_counts_flag;
      ui1
                  derivative_level; // used by with set_derivative_level directive, also
      ui 1
                                     // returned in decode
      // lossy compression parameters
                  goal_ratio; // either compression ratio or mean residual ratio
      sf8
      sf8
                  actual_ratio; // either compression ratio or mean residual ratio
      sf8
                  goal_tolerance; // tolerance for lossy compression mode goal, value of
                                   // <= 0.0 uses default values, which are returned</pre>
                  maximum_goal_attempts; // maximum loops to attain goal compression
      si4
      ui1
                  minimum_normality;
                  amplitude_scale; // used with set_amplitude_scale directive
      sf4
                  frequency_scale; // used with set_frequency_scale directive
      sf4
                  user_number_of_records;
      ui2
      ui2
                  user_record_region_bytes; // set by user to reserve bytes for records
                                             // in header
      ui4
                  user_parameter_flags; // user bits to be set in parameter flags of
                                         // block header (library flags will be set
                                         // automatically)
      ui2
                  protected_region_bytes; // not currently used
                  user_discretionary_region_bytes; // set by user to reserve bytes for
      ui2
                                                    // discretionary region in header
} CMP_COMPRESSION_PARAMETERS_m10;
typedef struct {
      TERN_m10
                  mutex;
                  **count; // used by RED/PRED encode & decode
      ui4
      CMP_STATISTICS_BIN_m10 **sorted_count; // used by RED/PRED encode & decode
      ui8
                  **cumulative_count; // used by RED/PRED encode & decode
                  **minimum_range; // used by RED/PRED encode & decode
      ui8
                  **symbol_map; // used by RED/PRED encode & decode
      ui1
                  *input_buffer;
      si4
                  *compressed_data; // passed in decompression, returned in compression,
      ui1
                                     // should not be updated
                                    *block_header; // points to beginning of current
      CMP_BLOCK_FIXED_HEADER_m10
```

```
// block within compressed_data array,
                                                   // updatable
      si4
                  *decompressed_data; // returned in decompression or if lossy data
                                       // requested, used in some compression modes,
                                       // should not be updated
                  *decompressed_ptr: // points to beginning of current block within
      si4
                                      // decompressed_data array, updatable
                  *original_data; // passed in compression, should not be updated
      si4
                  *original_ptr; // points to beginning of current block within
      si4
                                  // original_data array, updatable
                  *difference_buffer; // passed in both compression & decompression
      si1
                  *derivative_buffer; // used if needed in compression & decompression,
      si1
                                       // size of maximum block differences
      si4
                  *detrended_buffer; // used if needed in compression, size of
                                      // decompressed block
      si4
                  *scaled_amplitude_buffer; // used if needed in compression, size of
                                             // decompressed block
                  *scaled_frequency_buffer; // used if needed in compression, size of
      si4
                                             // decompressed block
      CMP_DIRECTIVES_m10
                              directives;
      ui1
                  *records;
      CMP_PARAMETERS_m10
                              parameters;
                  *protected_region;
      ui1
                  *discretionary_region;
      ui1
      ui1
                  *model_region;
      PASSWORD_DATA_m10 *password_data;
} CMP_PROCESSING_STRUCT_m10;
// Macros
#define CMP_MAX_DIFFERENCE_BYTES_m10(block_samps)
                                                      // full si4 plus 1 keysample flag
                                                      // byte per sample
#define CMP_MAX_COMPRESSED_BYTES_m10(block_samps, n_blocks) // (no compression + header +
                                                            // maximum pad bytes) for
                                                            // n_blocks blocks
// NOTE: does not take variable region bytes into account and assumes fall through to MBE
#define CMP_IS_DETRENDED_m10(block_header_ptr)
#define CMP_VARIABLE_REGION_BYTES_v1_m10(block_header_ptr) // does not require
                                                           // total_header_bytes
#define CMP_VARIABLE_REGION_BYTES_v2_m10(block_header_ptr) // requires total_header_bytes
// Compression Modes
#define CMP_COMPRESSION_MODE_NO_ENTRY_m10
                                                ((ui1) 0)
#define CMP_DECOMPRESSION_MODE_m10
                                                ((ui1) 1)
#define CMP_COMPRESSION_MODE_m10
                                                ((ui1) 2)
// Lossy Compression Modes
#define CMP_AMPLITUDE_SCALE_MODE_m10
                                                ((ui1) 1)
#define CMP_FREQUENCY_SCALE_MODE_m10
                                                ((ui1) 2)
```

FUNCTION: CMP_allocate_processing_struct_m10()

```
// Prototype
CMP_PROCESSING_STRUCT_m10
*CMP_allocate_processing_struct_m10(CMP_PROCESSING_STRUCT_m10 *cps, ui4 mode, si8
data_samples, si8 compressed_data_bytes, si8 difference_bytes, ui4 block_samples,
CMP_PROCESSING_DIRECTIVES_m10 *directives, CMP_COMPRESSION_PARAMETERS_m10 *parameters);
```

Allocates a CMP_PROCESSING_STRUCT (CPS). Within the CPS, various buffers are allocated. The PASSWORD_DATA structure is assigned. The directives are set to their defaults. The compression parameters are set to their defaults. If the cps parameter is not NULL, it will not be allocated. This is most common when an array of CPS's has been pre-allocated, and this function is being used to perform initialization, and allocation it's contents.

If directives or parameters are NULL, they are set to their defaults, if not, their contents are copied into the CPS.

data_samples: the size of the input or output data arrays, may be large enough to hold many blocks

block_samples: number of samples in a single block (typically maximum number) global_flag: assign the allocated CPS to the global CPS pointer.

example:

```
cps = CMP_allocate_processing_struct_m10(NULL, CMP_DECOMPRESSION_MODE_m10, max_samps,
CMP_MAX_COMPRESSED_BYTES_m10(max_samps, 1), 0,
CMP_MAX_DIFFERENCE_BYTES_m10(max_samps), max_samps, NULL, NULL, FALSE_m10);
```

Create an CPS large enough to compress one block of size max_samps. Lossless compression is the default, so no decompressed, offset, or scaled data buffers are requested.

FUNCTION: CMP_calculate_mean_residual_ratio_m10()

```
// Prototype
inline sf8 CMP_calculate_mean_residual_ratio_m10(si4 *original_data, si4 *lossy_data,
ui4 n_samps);
```

Calculates and returns the mean residual ratio between the original_data and lossy_data buffers. Used in the mean residual ratio lossy compression mode.

FUNCTION: CMP_calculate_statistics_m10()

Checks that the appropriate buffers are allocated in a CPS for the type of operation being performed. The operation is determined by the values of the members of the CPS's compression and directives structures. It returns TRUE_m10 if the appropriate buffers are allocated and FALSE_m10 if not unless the behavior_on_fail global is set to exit. Deficient allocations are printed to stderr, as are unnecessarily allocated buffers. This function may used if the programmer is uncertain which buffers to allocate for specific compression & decompression requirements. It is not called by any of the other functions in the library and must be called independently.

example:

```
cps = CMP_allocate_processing_struct_m10(NULL, CMP_DECOMPRESSION_MODE_m10, max_samps,
CMP_MAX_COMPRESSED_BYTES_m10(max_samps, 1), 0,
CMP_MAX_DIFFERENCE_BYTES_m10(max_samps), max_samps, NULL, NULL, FALSE_m10);

cps->compression.mode = RED_FIXED_COMPRESSION_RATIO;

force_behavior(RETURN_ON_FAIL);
CMP_check_CPS_allocation_m10(cps);
force_behavior(RESTORE_BEHAVIOR);

FUNCTION: CMP_decode_m10()

// Prototype
```

Decompress data passed in the CPS from block_header pointer to the CPS decompressed_ptr field. If CRC validation is requested in the directives, the block CRC will be checked, if the block does not have a valid CRC, it will not be decompressed and the function will return zero. If the block is encrypted and the access level is sufficient, the block will be decrypted before decompression. Encryption status is returned in the encryption directive. Scaling and retrending are performed as necessary. The block discontinuity status is returned in the discontinuity directive.

```
FUNCTION: CMP_decrypt_m10()
```

Decrypts data in the block pointed to by the block header pointer in place.

void CMP_decode_m10(CMP_PROCESSING_STRUCT_m10 *cps);

FUNCTION: CMP detrend m10()

```
// Prototype
void CMP_detrend_m10(si4 *input_buffer, si4 *output_buffer, si8 len,
CMP_PROCESSING_STRUCT_m10 *cps);
```

Detrends data from input_buffer to output_buffer. The detrended slope and intercept values entered into CPS's block header. If the input buffer == output buffer detrending is done in place.

FUNCTION: CMP_encode_m10()

```
// Prototype
void CMP_encode_m10(CMP_PROCESSING_STRUCT_m10 *cps, si8 start_time, si4
acquisition_channel_number, ui4 number_of_samples);
```

Compress data from original_ptr to block_header pointer (compressed data array). This is the main entry point into the library's compression routines. It detrends the data if set in the directives, and uses lossless or lossy compression as specified in the directives. It also sets the discontinuity flag in the block header.

FUNCTION: CMP_encrypt_m10()

Encrypts data in the block pointed to by the block_header pointer in place.

FUNCTION: CMP_find_amplitude_scale_m10()

```
// Prototype
void CMP_find_amplitude_scale_m10(CMP_PROCESSING_STRUCT_m10 *cps, void (*compression_f)
(CMP_PROCESSING_STRUCT_m10 *cps));
```

This is used in lossy compression in amplitude scaling mode.

FUNCTION: CMP_find_extrema_m10()

```
// Prototype
void CMP_find_extrema_m10(si4 *input_buffer, si8 len, si4 *minimum, si4 *maximum,
CMP_PROCESSING_STRUCT_m10 *cps);
```

This function will find the minimum & maximum in input_buffer, and return those values in the minimum & maximum poster arguments. If CPS is not NULL, all the other parameters can be, and the results in the CPS parameters, minimum_sample_value & maximum_sample_value will also be filled in.

```
Example 1: Find min & max of input_buffer CMP_find_extrema_m10(input_buffer, buffer_len, &minimum, &maximum, NULL);
```

Example 2: Find min & max of cps->input_buffer & place results in minimum, maximum, and CPS CMP_find_extrema_m10(NULL, 0, &minimum, &maximum, cps);

Example 3: Find min & max of cps->input_buffer & place results in CPS CMP_find_extrema_m10(NULL, 0, NULL, NULL, cps);

FUNCTION: CMP_find_frequency_scale_m10()

```
// Prototype
```

```
void CMP_find_frequency_scale_m10(CMP_PROCESSING_STRUCT_m10 *cps, void (*compression_f)
(CMP_PROCESSING_STRUCT_m10 *cps));
```

This is used in lossy compression in frequency scaling mode.

FUNCTION: CMP_free_processing_struct_m10()

```
// Prototype
void CMP_free_processing_struct_m10(CMP_PROCESSING_STRUCT_m10 *cps));
```

Frees any arrays allocated within the CPS, and the CPS itself.

FUNCTION: CMP_generate_lossy_data_m10()

```
// Prototype
void CMP_generate_lossy_data_m10(CMP_PROCESSING_STRUCT_m10 *cps, si4 *input_buffer, si4
*output_buffer);
```

Used by lossy compression algorithms to measure mean residual ratio.

FUNCTION: CMP_get_variable_region_m10()

```
// Prototype
void CMP_get_variable_region_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Used by CMP_decode() to calculate the size of the variable region of a CMP block header, based on the header flags.

FUNCTION: CMP_initialize_normal_CDF_table_m10()

```
// Prototype
sf8 *CMP_initialize_normal_CDF_table_m10(TERN_m10 global_flag);
```

Initializes the global Normal Cumulative Distribution Function table, used to determine if block data is normally distributed for lossy compression functions.

FUNCTION: CMP_lad_reg_m10()

```
// Prototype
void CMP_lad_reg_m10(si4 *input_buffer, si8 len, sf8 *m, sf8 *b);
```

Returns least absolute deviation regression (LAD) slope (m) and intercept (b) of the input buffer. The abscissa is presumed to be [1:len].

FUNCTION: CMP_lin_reg_m10()

```
// Prototype
```

```
void CMP_lin_reg_m10(si4 *input_buffer, si8 len, sf8 *m, sf8 *b);
```

Returns least squares deviation (LAD) slope (m) and intercept (b) of the input buffer. The abscissa is presumed to be [1:len]..

FUNCTION: CMP_MBE_decode_m10()

```
// Prototype
void CMP_MBE_decode_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Decompress data from block_header pointer to decompressed_ptr in CPS if compressed with Minimal Bit Encoding (MBE). This is called by CMP decode m10() for MBE encoded blocks.

FUNCTION: CMP_MBE_encode_m10()

```
// Prototype
void CMP_MBE_encode_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Compress data using Minimal Bit Encoding (MBE) from cps->input_buffer to block_header. This is called by CMP_encode_m10(), or as fall through from CMP_RED_encode_m10() and CMP_PRED_encode_m10().

FUNCTION: CMP_offset_time_m10()

```
// Prototype
void CMP_offset_time_m10(CMP_BLOCK_FIXED_HEADER_m10 *block_header, si4 action);
```

Apply or remove recording time offset from CMP block header according to global recording_time_offset_mode. Action is either of the defined values RTO_INPUT_ACTION_m10 or RTO_OUTPUT_ACTION_m10, depending on calling scenario.

FUNCTION: CMP_PRED_decode_m10()

```
// Prototype
void CMP_PRED_decode_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Decompress data from block_header pointer to decompressed_ptr in CPS if compressed with the Predictive RED (PRED) algorithm. This is called by CMP_decode_m10() for PRED encoded blocks.

FUNCTION: CMP_PRED_encode_m10()

```
// Prototype
void CMP_PRED_encode_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Compress data from cps->input_buffer to cps->block_header with the Predictive RED (PRED) algorithm. This is called by CMP encode m10().

FUNCTION: CMP_quantile_value_m10()

```
// Prototype
sf8    CMP_quantile_value_m10(sf8 *x, si8 len, sf8 quantile, TERN_m10 preserve_input, sf8
*buff);
```

Returns the requested quantile value i.e 0.0 == minimum, 1.0 == maximum, 0.5 == median, etc. If the input array can be destroyed, set preserve_input to TRUE_m10, as this is most efficient, if it cannot, set preserve_input to FALSE_m10. Under these circumstances a buffer is required, if one is passed it will be used, if not it will be allocated and freed with each call.

FUNCTION: CMP_RED_decode_m10()

```
// Prototype
void CMP_RED_decode_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Decompress data from block_header pointer to decompressed_ptr in CPS if compressed with the Range Encoded Derivatives (RED) algorithm. This is called by CMP_decode_m10() for RED encoded blocks.

FUNCTION: CMP_RED_encode_m10()

```
// Prototype
void CMP_RED_encode_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Compress data from cps->input_buffer to cps->block_header with the Range Encoded Derivatives (RED) algorithm. This is called by CMP_encode_m10().

FUNCTION: CMP_retrend_m10()

```
// Prototype
void CMP_retrend_m10(si4 *input_buffer, si4 *output_buffer, si8 len, sf8 m, sf8 b);
```

Retrend data from input_buffer to output_buffer. If input_buffer == output_buffer retrending data will be done in place. "m" & "b" are slope & intercept of trendline.

FUNCTION: CMP_round_m10()

Return rounded si4 from sf8, taking into account the MED reserved values: NAN_m10, POSITIVE_INFINITY_m10, & NEGATIVE INFINITY m10.

```
FUNCTION: CMP_scale_amplitude_m10()
```

```
// Prototype
void CMP_scale_amplitude_m10(si4 *input_buffer, si4 *output_buffer, si8 len, sf8
scale_factor);
```

Scale amplitude from input_buffer to output_buffer. If input_buffer == output_buffer scaling will be done in place.

FUNCTION: CMP_scale_frequency_m10()

```
// Prototype
void CMP_scale_frequency_m10(si4 *input_buffer, si4 *output_buffer, si8 len, sf8
scale_factor);
```

Scale frequency from input_buffer to output_buffer. If input_buffer == output_buffer scaling will be done in place.

FUNCTION: CMP_set_variable_region_m10()

```
// Prototype
void CMP_set_variable_region_m10(CMP_PROCESSING_STRUCT_m10 *cps);
```

Performs all requested data conditioning (detrending, scaling, rectifying) & metrics calculations prior to compression, based on CPS directives. This is called by CMP_encode_m10();

FUNCTION: CMP_show_block_header_m10()

```
// Prototype
void CMP_show_block_header_m10(CMP_BLOCK_FIXED_HEADER_m10 *bh);
```

Displays contents of a CMP block header. Useful in debugging.

FUNCTION: CMP_show_block_model_m10()

```
// Prototype
void CMP_show_block_model_m10(CMP_BLOCK_FIXED_HEADER_m10 *block_header);
```

Displays the compression model vales and parameters in CMP block header. Useful in debugging.

FUNCTION: CMP_unscale_amplitude_m10()

```
// Prototype
```

```
void CMP_unscale_amplitude_m10(si4 *input_buffer, si4 *output_buffer, si8 len, sf8
scale_factor);
```

Unscale amplitude from input buffer to output buffer. If input buffer == output buffer scaling will be done in place.

FUNCTION: CMP unscale frequency m10()

```
// Prototype
void CMP_unscale_frequency_m10(si4 *input_buffer, si4 *output_buffer, si8 len, sf8
scale_factor);
```

Unscale frequency from input_buffer to output_buffer. If input_buffer == output_buffer scaling will be done in place.

FUNCTION: CMP_update_CPS_pointers_m10()

}

```
// Prototype
inline CMP_BLOCK_FIXED_HEADER_m10
*CMP_update_CPS_pointers_m10(CMP_PROCESSING_STRUCT_m10 *cps, ui1 flags);
// Update CPS Pointer Flags
#define CMP_UPDATE_ORIGINAL_PTR_m10 ((ui1) 1)
#define CMP_UPDATE_BLOCK_HEADER_PTR_m10 ((ui1) 2)
#define CMP_UPDATE_DECOMPRESSED_PTR_m10 ((ui1) 4)
```

A function to update pointers in the CPS during rounds of compression or decompression. The examples below will make its utility more clear.

Example 1: Increment original_ptr & block_header in CPS during sequential compression

cps->block_header = CMP_update_CPS_pointers_m10(cps, \

CMP_UPDATE_BLOCK_HEADER_PTR_m10 | CMP_UPDATE_DECOMPRESSED_PTR_m10);

```
/*********************************** CRC Utilities ***************************/
                                      *******
FUNCTION: CRC_calculate_m10()
// Prototype
inline ui4 CRC_calculate_m10(const ui1 *block_ptr, si8 block_bytes);
// Constant
#define CRC_POLYNOMIAL_m10
                                  ((ui4) 0xEDB88320)
#define CRC_START_VALUE_m10
                                  ((ui4) 0x00000000)
Returns the 32-bit CRC for a block of length block bytes, pointed to by block ptr.
Note library CRC routines are customized to the polynomial defined above; it cannot be changed arbitrarily.
crc = CRC_calculate_m10(block_ptr, block_bytes);
is equivalent to:
crc = CRC_update_m10(CRC_calculate_m10, block_bytes, CRC_START_VALUE);
FUNCTION: CRC_combine_m10()
// Prototype
      CRC_combine_m10(ui4 block_1_crc, ui4 block_2_crc, si8 block_2_bytes);
Returns the 32-bit CRC for two blocks with known CRCs as if they were joined and calculated as one. This allows efficient
incremental addition of blocks with known CRCs as occurs in CMP blocks and MED records.
Example: update universal header body CRC from with record CRC (from calculate record data CRCs m10()):
// calculate record CRC
record_header->record_CRC = CRC_calculate_m10((ui1 *) record_header + \
      RECORD_HEADER_CRC_START_OFFSET_m10, record_header->total_bytes - \
      RECORD_HEADER_CRC_START_OFFSET_m10);
// calculate record header CRC
header_CRC = CRC_calculate_m10((ui1 *) record_header, \
      RECORD_HEADER_CRC_START_OFFSET_m10);
// combine record header & record body CRCs
full_record_CRC = CRC_combine_m10(header_CRC, record_header->record_CRC, \
      record_header->total_bytes - RECORD_HEADER_CRC_START_OFFSET_m10);
// combine universal_header->body_CRC & full_record_CRC
fps->universal_header->body_CRC = CRC_combine_m10(fps->universal_header->body_CRC, \
      full_record_CRC, record_header->total_bytes);
```

FUNCTION: CRC_initialize_table_m10()

```
// Prototype
ui4 **CRC_initialize_table_m10(TERN_m10 global_flag);
```

Allocates and initializes the CRC table generated from the CRC polynomial into heap space. If global_flag is set, the MED_globals pointer CRC_table is also set to this value. This function is called by initialize_medlib_m10().

FUNCTION: CRC_update_m10()

```
// Prototype
inline ui4 CRC_update_m10(const ui1 *block_ptr, si8 block_bytes, ui4 current_crc);
```

Returns the CRC of a block based on the current CRC of the bytes preceding that block.

FUNCTION: CRC_validate_m10()

Returns TRUE_m10 if the calculated CRC of the block pointed to by block_ptr matches the value passed in crc to validate. If they do not match, FALSE m10 is returned.

```
// Prototypes
si4 UTF8_charnum(si1 *s, si4 offset); // byte offset to character number
void UTF8_dec(si1 *s, si4 *i); // move to previous character
si4 UTF8_escape(si1 *buf, si4 sz, si1 *src, si4 escape_quotes); // convert UTF-8 "src"
to
    // ASCII with escape sequences.
```

si4 UTF8_escape_wchar(si1 *buf, si4 sz, ui4 ch); // given a wide character, convert it to an ASCII escape sequence stored in buf, where buf is "sz" bytes. returns the number of characters output

```
si4 UTF8_f
uments may be in UTF-8. You can avoid this function and just use ord
```

uments may be in UTF-8. You can avoid this function and just use ordinary printf()
// if the current locale is UTF-8.

```
UTF8_hex_digit(si1 c); // utility predicates used by the above
si4
     UTF8_inc(si1 *s, si4 *i); // move to next character
void
      *UTF8_initialize_offsets_from_UTF8_table(si4 global_flag);
ui4
      *UTF8_initialize_trailing_bytes_for_UTF8_table(si4 global_flag);
si1
      UTF8_is_locale_utf8(si1 *locale); // boolean function returns if locale is UTF-8,
si4
      // otherwise
      *UTF8_memchr(si1 *s, ui4 ch, size_t sz, si4 *charn); // same as the above, but
si1
searches
      // a buffer of a given size instead of a NUL-terminated string.
ui4
      UTF8_nextchar(si1 *s, si4 *i); // return next character, updating an index
variable
     UTF8_octal_digit(si1 c); // utility predicates used by the above
si4
     UTF8_offset(si1 *str, si4 charnum); // character number to byte offset
si4
si4
     UTF8_printf(si1 *fmt, ...); // printf() where the format string and arguments may
be in
      // UTF-8. You can avoid this function and just use ordinary printf() if the current
      // locale is UTF-8.
     UTF8_read_escape_sequence(si1 *str, ui4 *dest); // assuming src points to the
si4
character
      // after a backslash, read an escape sequence, storing the result in dest and
returning
      // the number of input characters processed
     UTF8_seqlen(si1 *s); // returns length of next UTF-8 sequence
si4
      *UTF8_strchr(si1 *s, ui4 ch, si4 *charn); // return a pointer to the first
si1
occurrence of
      // ch in s, or NULL if not found. character index of found character returned in
*charn.
     UTF8_strlen(si1 *s); // count the number of characters in a UTF-8 string
si4
     UTF8_toucs(ui4 *dest, si4 sz, si1 *src, si4 srcsz); // convert UTF-8 data to wide
si4
      // character
     UTF8_toutf8(si1 *dest, si4 sz, ui4 *src, si4 srcsz); // convert wide character to
si4
UTF-8 data
      UTF8_unescape(si1 *buf, si4 sz, si1 *src); // convert a string "src" containing
si4
escape
      // sequences to UTF-8 if escape_quotes is nonzero, quote characters will be
preceded by
      // backslashes as well.
     UTF8_vfprintf(FILE *stream, si1 *fmt, va_list ap); // called by UTF8_fprintf()
si4
si4
     UTF8_vprintf(si1 *fmt, va_list ap); // called by UTF8_printf()
```

```
si4 UTF8_wc_toutf8(si1 *dest, ui4 ch); // single character to UTF-8
```

Not all of the UTF-8 functions are used in the library, but they are included in the library for end-user and potential future use. Some of the included functions are used by other UTF-8 functions, and thus require inclusion. Only those functions that are currently used in other (non-UTF-8) medlib functions are described in this section.

FUNCTION: UTF8_initialize_tables_m10()

```
// Prototype
TERN_m10 UTF8_initialize_tables_m10(void);
```

Allocates and initializes the UTF8 tables into heap space. This function is called by initialize_medlib().

FUNCTION: UTF8_fprintf()

```
// Prototype
si4 UTF8_fprintf_m10(FILE *stream, si1 *fmt, ...);
```

Used like fprintf(), but accommodates UTF-8 as well as conventional strings.

FUNCTION: UTF8_nextchar_m10()

```
// Prototype
ui4  UTF8_nextchar_m10(si1 *s, si4 *i);
```

Returns the next character in the UTF-8 string s, updating the index variable i. Used by extract_terminal_password_bytes().

FUNCTION: UTF8_printf_m10()

```
// Prototype si4 UTF8_printf_m10(si1 *fmt, ...);
```

Used like printf(), but accommodates UTF-8 as well as conventional strings.

FUNCTION: UTF8_strlen_m10()

```
// Prototype
si4 UTF8_strlen_m10(si1 *s);
```

Returns the number of UTF-8 characters in the UTF-8 string s. Used by check_password().

```
******* AES Utilities *************
 // Function Prototypes
    AES_add_round_key(si4 round, ui1 state[][4], ui1 *RoundKey);
    AES_decrypt(ui1 *in, ui1 *out, si1 *password, ui1 *expanded_key);
void
    AES_encrypt(ui1 *in, ui1 *out, si1 *password, ui1 *expanded_key);
void
void
    AES_key_expansion(si4 Nk, si4 Nr, ui1 *RoundKey, si1 *Key);
    AES_cipher(si4 Nr, ui1 *in, ui1 *out, ui1 state[][4], ui1 *RoundKey);
void
     AES_get_sbox_invert(si4 num);
si4
si4
    AES_get_sbox_value(si4 num);
si4
     *AES_initialize_rcon_table(si4 global_flag);
si4
     *AES_initialize_rsbox_table(si4 global_flag);
si4
     *AES_initialize_sbox_table(si4 global_flag);
    AES_inv_cipher(si4 Nr, ui1 *in, ui1 *out, ui1 state[][4], ui1 *RoundKey);
void
    AES_inv_mix_columns(ui1 state[][4]);
void
    AES_inv_shift_rows(ui1 state[7][4]);
void
void
    AES_inv_sub_bytes(ui1 state[][4]);
    AES_mix_columns(ui1 state[][4]);
void
void
    AES_shift_rows(ui1 state[][4]);
void
    AES_sub_bytes(ui1 state[][4]);
```

Not all of the AES functions are used by the other functions in the library, but are used by other AES functions, and thus require inclusion. Only those functions that are currently used in other (non-AES) medlib functions are described in this section.

FUNCTION: AES_initialize_tables_m10()

```
// Prototype
TERN_m10     AES_initialize_tables_m10(void);
```

Allocates and initializes the AES tables into heap space. This function is called by initialize medlib().

FUNCTION: AES_decrypt_m10()

```
// Prototype
void AES_decrypt_m10(ui1 *in, ui1 *out, si1 *password, ui1 *expanded_key);
```

Decrypts a 16 byte (128 bit) block of AES-128 encrypted data in the "in" buffer to the "out" buffer. The decryption can be done in place ("in" equals "out"), and is most often done this way within the library functions. Either expanded_key or password must be non-NULL. If both are non-NULL, the expanded key will be used, as it is more efficient. An expanded key can be obtained from the function AES_key_expansion(). If a password is to be used, an expanded key is generated from it, used, and discarded. A password is a 16 byte sequence. If, as is usually the case, this is a string, unused bytes should be zeroed, as these bytes, while meaningless to the string, cannot vary for reproducible decryption. If a UTF-8 string is used for a password, the medlib routines extract the terminal (most unique) bytes from each character to be used as the password bytes. This can be done with the function extract_terminal_password_bytes(); it is not done in this function.

```
FUNCTION: AES_encrypt_m10()
```

```
// Prototype
void AES_encrypt_m10(ui1 *in, ui1 *out, si1 *password, ui1 *expanded_key);
```

Encrypts a 16 byte (128 bit) block of data in the "in" buffer to the "out" buffer using the AES-128 algorithm. The encryption can be done in place ("in" equals "out"), and is most often done this way within the library functions. Either expanded_key or password must be non-NULL. If both are non-NULL, the expanded key will be used, as it is more efficient. An expanded key can be obtained from the function AES_key_expansion(). If a password is to be used, an expanded key is generated from it, used, and discarded. A password is a 16 byte sequence. If, as is usually the case, this is a string, unused bytes should be zeroed, as these bytes, while meaningless to the string, cannot vary for reproducible encryption. If a UTF-8 string is used for a password, the medlib routines extract the terminal (most unique) bytes from each character to be used as the password bytes. This can be done with the function extract_terminal_password_bytes(); it is not done in this function.

```
FUNCTION: AES_key_expansion_m10()
// Prototype
```

void AES_key_expansion_m10(ui1 *expanded_key, si1 *key);

Generates an expanded key from a key. A key is a 16 byte sequence. If, as is usually the case, the key is a password, unused bytes should be zeroed, as these bytes, while meaningless to the string, cannot vary for reproducible encryption / decryption. If a UTF-8 string is used for a password, the medlib routines extract the terminal (most unique) bytes from each character to be used as the password bytes. This can be done with the function extract_terminal_password_bytes(); it is not done in this function.

```
void SHA_finalize_m10(SHA_CTX_m10 *ctx, ui1 *hash);
void SHA_initialize_m10(SHA_CTX_m10 *ctx);

TERN_m10 SHA_initialize_tables_m10(void);
void SHA_transform_m10(SHA_CTX_m10 *ctx, const ui1 *data);
void SHA_update_m10(SHA_CTX_m10 *ctx, const ui1 *data, si8 len);
```

SHA-256 is the 256-bit version of the SHA-2 cryptographic hash function. Only the 256-bit version is included in the library. Not all of the SHA functions are used by other functions in the library, but are used by other SHA functions, and thus require inclusion. Only those functions that are currently used in other (non-SHA) medlib functions are described in this section.

```
FUNCTION: SHA_initialize_tables()

// Prototype
ui4 *SHA_initialize_h0_tables(void);
```

Allocates and initializes SHA tables into heap space. This function is called by initialize_medlib().

```
FUNCTION: SHA_hash_m10()

// Prototype
ui1 *SHA_hash_m10(const ui1 *data, si8 len, ui1 *hash);

// Constant
#define SHA_OUTPUT_SIZE 256
```

Returns a 256 byte SHA-256 hash of the data (of length len) in hash. This function is used by process_password_data().

MED Records API

User defined records are defined and coded in "medrec_m10.c" and "medrec_m10.h". The functions required for adding a new record type are described here. Record types themselves are described in the file "MED 1.0 Records Specification".

All records have an identically structured record header, followed by a customizable body. The body length must be padded out to a multiple of 16 bytes in length to facilitate individual record encryption with AES-128.

Structures within records should have all members aligned to their type and the total size evenly divisible by 8 (for 64-bit CPUs).

Records are named with 4 ascii characters and have a major and minor version associated with them so that they can evolve, as needed, with time. These 4 characters also define a type code as the bytes of a 4 byte unsigned integer. **Note that translation of ascii to hexadecimal on little endian machines requires reversing the byte ordering in the hexadecimal representation.**

```
Each new record type should have two or three associated functions:
1) a "show" function)
2) an "alignment" function
"Show" functions display the contents of the records and have the following form:
Name: show rec xxxx type m10()
(where "xxxx" is the record type name)
// Prototype
void show_medrec_xxxx_type_m10(RECORD_HEADER_m10 *record_header);
(where a RECORD_HEADER_m10 is a structure defined in "medlib_m10.h")
The "show" function should handle all versions of the record type. An example "show function is shown below for the
"Note" record type.
      show_rec_Note_type_m10(RECORD_HEADER_m10 *record_header)
void
{
      si1
             *Note;
      // Version 1.0
      if (record_header->version_major == 1 && record_header->version_minor == 0) {
             Note = (si1 *) record_header + REC_Note_v10_TEXT_OFFSET_m10;
             UTF8_printf("Note text: %s\n", Note);
      // Unrecognized record version
      else {
             warning_message_m10("Unrecognized Note version (%hhd.%hhd)\n", \
             record_header->version_major, record_header->version_minor);
      }
      return;
}
```

All show function constants are defined in "medrec_m10.h". The function show_record_m10() defined in medrec_m10.c must be modified in the switch statement, copied below, to add new record types.

```
switch (type_code) {
      case REC_Sqmt_TYPE_CODE_m10:
             show_rec_Sgmt_type_m10(record_header);
             break:
      case REC_Stat_TYPE_CODE_m10:
             show_rec_Stat_type_m10(record_header);
             break;
      case REC_Note_TYPE_CODE_m10:
             show_rec_Note_type_m10(record_header);
             break;
      case REC_Seiz_TYPE_CODE_m10:
             show_rec_Seiz_type_m10(record_header);
             break:
      case REC_SyLg_TYPE_CODE_m10:
             show_rec_SyLq_type_m10(record_header);
             break;
      default:
             warning_message_m10("%s(): 0x%x is an unrecognized record type code", \
                    __FUNCTION__, type_code);
             break;
}
"Alignment" functions have the following form:
Name: check rec xxxx type alignment m10()
(where "xxxx" is the record type name)
// Prototype
TERN m10
             check_rec_xxxx_type_alignment_m10(ui1 *bytes);
(where "bytes" is an optional buffer to check alignment with)
New record "alignment" functions check the alignment of any structures represented in the record body. Those structures
```

are defined in "medrec m10.h". The function check record structure alignments m10() defined in medrec m10.c must be modified in the serial if statements, copied below, to add a new record type.

```
if ((check_rec_Sqmt_type_alignment_m10(bytes)) == FALSE_m10)
      return_value = FALSE_m10;
if ((check_rec_Stat_type_alignment_m10(bytes)) == FALSE_m10)
      return_value = FALSE_m10;
if ((check_rec_Note_type_alignment_m10(bytes)) == FALSE_m10)
      return_value = FALSE_m10;
if ((check_rec_Seiz_type_alignment_m10(bytes)) == FALSE_m10)
      return_value = FALSE_m10;
if ((check_rec_SyLg_type_alignment_m10(bytes)) == FALSE_m10)
      return_value = FALSE_m10;
```