

源码

```
1  #include <iostream>
2  #include <string>
3
4  using std::cout;
5  using std::endl;
6  using std::string;
7
8  template <typename T>
9  void swap(T& x,T &y)
10 {
11     T t;
12     t = x,x=y,y=t;
13 }
14
15 template <typename T>
16 void test_swap(T &x,T &y)
17 {
18     cout<<"x="<<x<<",y="<<y<<endl;
19     swap(x,y);
20     cout<<"交换后:"<<endl;
21     cout<<"x="<<x<<",y="<<y<<endl;
22     cout<<endl;
23 }
24
25 int main()
26 {
27     int x1 = 3,y1=4;
28     test_swap(x1,y1);
29
30     double x2=3.3,y2=4.4;
31     test_swap(x2,y2);
32
33     char x3='Y',y3='N';
34     test_swap(x3,y3);
35
36     string x4={"YES"},y4={"NO"};
37     test_swap(x4,y4);
38     return 0;
39 }
```

运行结果

● `x=3,y=4`

交换后：

`x=4,y=3`

`x=3.3,y=4.4`

交换后：

`x=4.4,y=3.3`

`x=Y,y=N`

交换后：

`x=N,y=Y`

`x=YES,y=NO`

交换后：

`x=NO,y=YES`