Aulaweb

Dibris ► My courses ► Robotics Engineering (Scuola Politecnica) ► Anno Accademico 2013/14 ► 65863-1314 ► Motion ► Lab. 4 - Optical flow estimation (UPDATED 07/11) You are

logged in as Muhammad Farhan Ahmed (Logout)

Dibris

My home

Dibris

My profile

Current course

65863-1314

Participants

Badges

General

Lab n. 1

Lab n. 2

Lab n. 3

Motion



Lab. 4 Optical flow
estimation
(UPDATED
07/11)

Lab session n. 4 - submission

Projective transformations

Lab. 4 - Optical flow estimation (UPDATED 07/11)

Computer Vision

EMARO - European Master on Advanced Robotics

Robotics Engineering Master Degree

Lab. Session n. 4

Implementation of the Lucas-Kanade algorithm

Write a Matlab function implementing the Lucas-Kanade algorithm to compute optical flow from a sequence of images.

You may use the following sequences, of rather different complexities, to test your implementation:

- sphere
- tree
- video-surveillance

Lucas-Kanade

For each position $\mathbf{x}=(x,y)$ of the image, we consider a NxN neighbourhood (e.g. N=5, 7) Q which produces a system of NxN equations in the two unknowns $(u_x, v_y)=\mathbf{u}$ (which are the components of the optical flow computed in position \mathbf{x}). If we denote with \mathbf{x}_i the points in Q, then

$$\nabla I(\mathbf{x}_i, t)^{\mathsf{T}} \mathbf{u} = -I_t(\mathbf{x}_i, t)$$

The left side of the equations is based on the computation of the image gradients (see the lab. session on edge detection), while on the right of the equal there is the temporal derivative, which may be approximated as

1 of 2

Single view geometry and camera calibration Stereopsis

Other methods for 3D reconstruction

My courses

Courses

Administration



Course administration

My profile settings

$$I_t(\mathbf{x}_i, t) = I(\mathbf{x}_i, t) - I(\mathbf{x}_i, t - 1)$$

Now, the NxN equations form a system of type Au=b, that can be solved as

$$\mathbf{u} = (A^T A)^{-1} A^T \mathbf{b}$$

What to produce

• A function that, given two images, computes the optical flow in each point:

To evaluate the confidence of your estimated in each point, it may be of help seeing how well conditioned is the system.

- A main that loads the sequence image by image, calls the LucasKanade function on pairs of images adjacent in time, and visualizes the result. For the latter functionality you can use the matlab function quiver: assuming that U and V are the matrices of the two optical flow components,
 - first change the reference system (from origin in the top-left to bottom-left): Uf=flipud(U), Vf=flipud(V)
 - then try to visualize the full matrices: quiver(Uf, Vf). It might be too dense...
 - thus try with a subsampling quiver (Uf(1:10:size(Uf,1), 1:10:size(Uf,2)), Vf(1:10:size(Vf,1), 1:10:size(Vf,2)))

Note: The Lucas-Kanade algorithm fails in presence of large displacements between consecutive frames. In this case, a hierarchical approach allows to improve the estimates.

2 of 2