NH 480s - 55HP - 2WD

Technical Specification

Engine Power Operating Weight No. of Cylinders **Bore Stroke**

Piston Displacement Maximum Power Maximum Torque

Pump Battery Air Filter **Fuel Filter Fuel Tank Capicity**

Transmission

Brakes Brakes (Parking)

Steering Driver's Seat Power Take Off Hyd. Pump **Pump Capacity Maximum lifting capacity**

Tyre (Front) Tyre (Rear) D.T.O

55HP 1710Kg.

03

100 x 115mm

2710cc

@2500rpm 55HP

@1500rpm 22.7 KGm

Distribution injection Type with mechanical speed governor

12 volts 90/95 Ah.

Oil bath with pre cleaner and Semi automatic dust unloader

02 replaceable cartridges

54 Litres

Gear box with constant mesh gears:8 forward and 2 reserve speeds: Synchromesh on

3rd, 4th, 7th, & 8th speeds.

Service disc type with mechanical control. With hand lever, on right side of operator.

Manual, Recirculating ball type, Centre relay lever joint to lubricated for life.

Fully upholstered, with paralellogram suspension, adjustable to driver's weight.

540rpm (1 318" - 6 spline Shaft) @ 2160 engine rpm.

Gear type pump driven from engine.

22.7L / min.

1450 Kg.

6.00-16

12.1/11-28

Speed same as engine - Anti clockwise optional







+92 317 0001 715 +92 317 0001 572



info@agroasiatractors.com sales@agroasiatractors.com



www.AgroAsiaTractors.com