## NH 640 - 75HP - 2WD

## **Technical Specification**

Engine Power
Operating Weight
No. of Cylinders
Bore Stroke
Piston Displacement

Maximum Power
Maximum Torque

Pump Battery Air Filter Fuel Filter Fuel Tank Capicity

Transmission

Brakes Brakes (Parking) Steering

Driver's Seat
Power Take Off
Hyd. Pump
Pump Capacity
Maximum lifting capacity
Tyre (Front)

Maximum lifting ca Tyre (Front) Tyre (Rear) D.T.O 75HP 2070Kg.

04

100 X 115 mm

3613 cc

@ 2500rpm 75HP @ 1400rpm 24.9 Kgm.

Distribution injection type with mechanical speed governor.

12 volts 115 Ah.

Oil bath with pre cleaner and Semi automatic dust unloader

02 replaceable cartridges

54 Litres

Gear box with constant mesh gears:8 forward and 2 reserve speeds: Synchromesh on

3rd, 4th, 7th, & 8th speeds.

Service dry Badn type with mechanical control.

With hand lever, on right side of operator.

Hydraulic power with independent oil pump of flow capacity 12liter/minute and

separate oil tank capacity 1.8 liters with complete filtering system.

Fully upholstered, with parallelogram suspension, adjustable to driver's weight.

540rpm (1 318" - 6 spline Shaft) @ 1967 engine rpm

Gear type pump driven from engine.

24.8 1/min.

1650 Kg.

7.50-16

16.9/14-30

Speed same as engine - Anti clockwise.







+92 317 0001 715 +92 317 0001 572



info@agroasiatractors.com sales@agroasiatractors.com



www.AgroAsiaTractors.com