

NH 7056- 85HP - 4WD

Technical Specification

Engine Power	85HP
Operating Weight	2600Kg.
No. of Cylinders	04
Bore Stroke	104 X 115 mm
Piston Displacement	3908 cc
Maximum Power	@ 2600rpm
Maximum Torque	@ 1500rpm
Pump	Distribution injection type.
Battery	12 volts 110/120 Ah.
Air Filter	Oil bath with pre cleaner and Semi automatic dust unloader
Fuel Filter	02 replaceable cartridges
Fuel Tank Capacity	61 Litres
Transmission	Gear box with constant mesh gears:8 forward and 2 reserve speeds: Synchromesh on 3rd, 4th, 7th, & 8th speeds.
Brakes	Service disc type, oil bath, mechanical control, simultaneous or independent
Brakes (Parking)	Dependent, operating on service breaks, with hand control lever and flashing light.
Steering	Hydrostatic power steering with independent circuit
Driver's Seat	Deluxe, with parallelogram suspension and hydraulic shock absorber, adjustable to driver's weight, reach and height.
Power Take Off	540rpm (1 3/8" - 6 spline Shaft) @ 1970 engine rpm
Hyd. Pump	Gear type pump driven from engine.
Pump Capacity	34.5 L/min.
Maximum lifting capacity	2200 Kg.
Tyre (Front)	12.4/11-24
Tyre (Rear)	18.4/15-30
D.T.O	Speed same as engine - Anti clockwise optional.



+92 317 0001 715
+92 317 0001 572



info@agroasiatractors.com
sales@agroasiatractors.com



www.AgroAsiaTractors.com