

Package ‘statr’

June 7, 2018

Type Package

Title Matt Galloway Personal R Package

Version 0.1.0

Description This is a personal R package. It contains a number of various R functions for organization and convenience purposes.

URL <https://github.com/MGallow/statr>

BugReports <https://github.com/MGallow/statr/issues>

License GPL (>= 2)

ByteCompile TRUE

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

Imports dplyr,
ggplot2,
magrittr,
formatR,
grid,
devtools,
ADMMsigma

Suggests testthat,
knitr,
rmarkdown,
pkgdown

SystemRequirements GNU make

VignetteBuilder knitr

R topics documented:

bsearch	2
compound	3
data_gen	3
dense	4
denseQR	4
derivative	5

diagnostic	5
dsearch	6
LDA	6
multiplot	7
predict_QDA	7
QDA	8
scatter	8
tidy	9
timeit	9
tridiag	9
Index	10

bsearch	<i>Bisection search</i>
---------	-------------------------

Description

Minimizes a univariate strictly pseudoconvex function over the interval [a, b]. This is augmented code from Adam Rothman’s STAT 8054 course (2017).

Usage

```
bsearch(dg, a, b, L = 1e-07, quiet = FALSE)
```

Arguments

dg	the derivative of the function to minimize, where dg(u, ...) is the function evaluated at u.
a	left endpoint of the initial interval of uncertainty.
b	right endpoint of the initial interval of uncertainty.
L	the maximum length of the final interval of uncertainty.
quiet	should the function stay quiet?
...	additional argument specifications for dg

Value

returns the midpoint of the final interval of uncertainty.

compound

*Generate compound symmetric matrices***Description**

Generate a p-dimensional compound symmetric matrix.

Usage

```
compound(p = 8, n = NULL)
```

Arguments

p	desired dimension
n	option to generate n observations from covariance matrix S

Examples

```
X = compound(p = 10, n = 100)$X
```

data_gen

*Normal Linear Data Generator***Description**

True beta values are generated from p independent draws from $N(0, 1/p)$ distribution. X_{-1} are n independent draws from (p - 1) multivariate normal $N(0, \text{Sigma})$ where Sigma has (j, k) entry $\text{theta}^{\text{abs}(j - k)}$.

Y is then generated using the $X = (1, X_{-1})$ and true beta values with an iid error term that follows distribution $N(0, \text{var})$. We can specify the desired number of replications (reps).

Usage

```
data_gen(n, p, theta, var = 0.5, reps = 200)
```

Arguments

n	desired sample size
p	desired dimension
theta	parameter used to generate covariance matrix
var	variance of generated y values
reps	number of replications

Value

generated design matrix (X), response values (Y)(matrix if reps > 1), true beta values

dense	<i>Generate dense matrices</i>
-------	--------------------------------

Description

Generate p-dimensional matrices so that its inverse is dense.

Usage

```
dense(p = 8, base = 0.9, n = NULL)
```

Arguments

p	desired dimension
base	base multiplier
n	option to generate n observations from covariance matrix S

Examples

```
dense(p = 10, base = 0.9)
```

denseQR	<i>Generate dense matrices (via spectral decomposition)</i>
---------	---

Description

Generate p-dimensional matrices so that its inverse is dense. The matrix will be generated so its first 'num' eigen values are 1000 and the remaining are 1. The orthogonal basis is generated via QR decomposition of

Usage

```
denseQR(p = 8, num = 5, n = NULL)
```

Arguments

p	desired dimension
num	number of 'large' eigen values. Note num must be less than p
n	option to generate n observations from covariance matrix S

Examples

```
denseQR(p = 10, num = 10)
```

`derivative`*Derivative*

Description

Takes the approximate derivative for a given function

Usage

```
derivative(g, x, delta = 1e-07)
```

Arguments

<code>g</code>	the derivative of the function to minimize, where $dg(u, \dots)$ is the function evaluated at u .
<code>x</code>	value to evaluate the derivative at
<code>delta</code>	defaults to $10e-8$

`diagnostic`*Diagnostic*

Description

This function simply streamlines the process of creating diagnostic plots with ggplot

Usage

```
diagnostic(data., x., y.)
```

Arguments

<code>data.</code>	data frame
<code>x.</code>	x-axis
<code>y.</code>	y-axis

Value

a residual plot and QQ plot

Examples

```
diagnostic(iris, Sepal.Length, Sepal.Width)
```

dsearch	<i>Dichotomous search</i>
---------	---------------------------

Description

Minimizes a univariate strictly quasiconvex function over the interval [a, b]. This is augmented code from Adam Rothman's STAT 8054 course (2017).

Usage

```
dsearch(g, a, b, L = 1e-07, eps = (L/2.1), quiet = FALSE)
```

Arguments

g	the function to minimize, where $g(u, \dots)$ is the function evaluated at u .
a	left endpoint of the initial interval of uncertainty.
b	right endpoint of the initial interval of uncertainty.
L	the maximum length of the final interval of uncertainty.
eps	search parameter, must be less than $L/2$
quiet	should the function stay quiet?
...	additional argument specifications for g

Value

returns the midpoint of the final interval of uncertainty.

LDA	<i>Linear Discriminant Analysis</i>
-----	-------------------------------------

Description

this function fit the LDA model

Usage

```
LDA(X, y, method = c("MLE", "diagonal", "ridge"), lam = NULL)
```

Arguments

X	n x p matrix where the i th row is the values of the predictor for the i th case
y	n entry response vector where the i th entry is the response category in 1, ..., C for the i th case
method	estimation method
lam	optional tuning parameter specification

Value

returns a list with the parameter estimates

multiplot	<i>Multiple Plot</i>
-----------	----------------------

Description

Taken from: [http://www.cookbook-r.com/Graphs/Multiple_graphs_on_one_page_\(ggplot2\)/](http://www.cookbook-r.com/Graphs/Multiple_graphs_on_one_page_(ggplot2)/)

Usage

```
multiplot(..., plotlist = NULL, cols = 1, layout = NULL)
```

Arguments

...	object can be passed in
plotlist	plotlist
cols	number of columns in layout
layout	a matrix specify the layout. If present, 'cols' is ignored

Value

plots

predict_QDA	<i>Predict QDA</i>
-------------	--------------------

Description

this function classifies test data using a fitted QDA model

Usage

```
predict_QDA(fit, Xtest)
```

Arguments

fit	this is a list with elements pi.hats, mu.hats, and Sigma.hats where pi.hats is a list of C response category sample proportions, mu.hats is a list of C p-dimensional sample mean proportions, Sigma.hats is a list of C p by p Sample covariance matrices
Xtest	this is a matrix with ntest rows and p column, each row is a test case

Value

returns a vector of ntest entries, where the ith entry is the estimated response category (some value in 1, ..., C) for the ith test case.

QDA

Quadratic Discriminant Analysis

Description

this function fit the QDA model

Usage

```
QDA(X, y, method = c("MLE", "diagonal", "ridge"), lam = NULL)
```

Arguments

X	n x p matrix where the ith row is the values of the predictor for the ith case
y	n entry response vector where the ith entry is the response category in 1, ..., C for the ith case
method	estimation method
lam	optional tuning parameter specification

Value

returns a list with the parameter estimates

scatter

Scatter

Description

This function simply streamlines the process of creating a scatterplot with ggplot

Usage

```
scatter(data., x., y.)
```

Arguments

data.	data frame
x.	x-axis
y.	y-axis

Value

a scatterplot

Examples

```
scatter(iris, Sepal.Length, Sepal.Width)
```

`tidy`*Tidy*

Description

tidys package R code and updates package documentation. Directly uses Yihui Xie's 'formatR' package.

Usage

```
tidy()
```

`timeit`*Time-It*

Description

Simple function that prints the computation time of a function

Usage

```
timeit(f)
```

Arguments

`f` the function to time

Value

returns the elapsed time

`tridiag`*Generate tri-diagonal matrices*

Description

Generate p-dimensional matrices so that its inverse is tri-diagonal.

Usage

```
tridiag(p = 8, base = 0.7, n = NULL)
```

Arguments

`p` desired dimension
`base` base multiplier
`n` option to generate n observations from covariance matrix S

Examples

```
tridiag(p = 10, base = 0.7)
```

Index

bsearch, [2](#)
compound, [3](#)
data_gen, [3](#)
dense, [4](#)
denseQR, [4](#)
derivative, [5](#)
diagnostic, [5](#)
dsearch, [6](#)

LDA, [6](#)

multiplot, [7](#)

predict_QDA, [7](#)

QDA, [8](#)

scatter, [8](#)

tidy, [9](#)
timeit, [9](#)
tridiag, [9](#)