

API Documentation:

Create Forward Order

Overview

This API allows you to create a forward order for different sellers. The API accepts the necessary order details as input and inserts the order into the database. It returns the order number and status as a JSON response.

Endpoint

`POST /api/createForwardOrder.php`

Request Parameters

Parameter	Type	Description
api_key	string	The API key for authentication and seller mapping.

customer_name	string	The name of the customer.
customer_email	string	The email address of the customer.
customer_address1	string	The first line of the customer's address.
customer_address2	string	The second line of the customer's address.
customer_address_landmark	string	The landmark near the customer's address.
customer_address_state	string	The state of the customer's address.
customer_address_city	string	The city of the customer's address.
customer_address_pincode	string	The PIN code of the customer's address.
customer_contact_number1	string	The primary contact number of the customer.
customer_contact_number2	string	The secondary contact number of the customer.
product_id	string	The ID of the product.
product_name	string	The name of the product.

sku	string	The SKU (stock keeping unit) of the product.
mrp	string	The MRP (maximum retail price) of the product.
product_size	string	The size of the product.
product_weight	string	The weight of the product.
product_color	string	The color of the product.
pay_mode	string	The payment mode ("COD" or "PREPAID").
quantity	string	The quantity of the product.
total_amount	string	The total amount for the order.
client_order_no	string	The client's order number.

Response

The API returns a JSON response with the following structure:

json

Copy code

```
{ "order_no" "12345" "status" "success" }
```

- `order_no`: The order number generated for the inserted order.
- `status`: The status of the API request. It can be "success" or "failed".

In case of an error, the response will have the following structure:

json

Copy code

```
{ "status": "failed", "message": "Error message" }
```

- `status`: The status of the API request, which will be "failed".
- `message`: A descriptive error message indicating the cause of the failure.

Error Handling

If an error occurs during the execution of the API, it will return a JSON response with the following structure:

json

Copy code

```
{ "status": "failed", "message": "An error occurred. Please try again later." }
```

The error message will be logged via the `error_log` function for debugging purposes.

Example Usage

Request



Response

json

```
{ "order_no" "54321" "status" "success" }
```

Curl Example

curl

```
curl --location 'https://www.shipcorrect.com/api/createForwardOrder.php' \
--header 'Content-Type: application/json' \
--data-raw '{
  "api_key": "dd2b48e36cf8eb837d7b",
  "customer_name": "John Doe",
  "customer_email": "john@example.com",
  "customer_address1": "123 Street Name",
  "customer_address2": "Near Landmark",
  "customer_address_landmark": "Near Landmark",
  "customer_address_state": "Maharashtra",
  "customer_address_city": "Mumbai",
  "customer_address_pincode": "400001",
  "customer_contact_number1": "9876543210",
  "customer_contact_number2": "",
  "product_id": "12345",
  "product_name": "Zendor Product",
  "sku": "SKU1714057923123",
  "mrp": "499.00",
  "product_size": "6x8",
  "product_weight": "0.5",
  "product_color": "Standard",
  "pay_mode": "COD",
  "quantity": "1",
  "total_amount": "499.00",
  "client_order_no": "662a64a0b87e30e47e9834ef"
}'
```

ShipCorrect Order Tracking API Documentation

Overview

The ShipCorrect Order Tracking API allows you to retrieve real-time tracking information for a given order. This API provides details such as AWB (Airway Bill) number, courier name, tracking status, and a list of scan stages.

****Base URL:**** `https://www.shipcorrect.com/api/trackOrder.php`

Authentication

To use the API, you need to include your API key in the request header.

****Header:****

- `Content-Type: application/json`

Track Order

Request

****Endpoint:**** `/api/trackOrder.php`

****Method:**** `POST`

****Request Body:****

```
``json
{
  "order_no": "620092",
  "api_key": "YOUR_API_KEY"
}
```

Response

The API returns a JSON object containing the tracking information for the specified order.

```
``json
{
  "order_no": "620092",
  "awb": "81512801580",
  "courier_name": "Bluedart",
  "tracking_status": "Delivered",
  "scan_stages": [
    {
      "date": "2024-01-11 11:17:00",
      "status": "Delivered",
    }
  ]
}
```

```

        "description": null
    },
    {
        "date": "2024-01-11 09:35:00",
        "status": "Out For Delivery",
        "description": null
    },
    {
        "date": "2024-01-10 15:01:00",
        "status": "In Transit",
        "description": null
    },
    {
        "date": "2024-01-09 00:00:00",
        "status": "In Transit",
        "description": "Picked Up"
    }
],
"status": "success"
}
...

```

Response Fields

- `order\_no`: The unique identifier for the order.
- `awb`: Airway Bill number assigned to the shipment.
- `courier\_name`: The name of the courier handling the shipment.
- `tracking\_status`: The current status of the shipment.
- `scan\_stages`: An array of scan stages, each providing information about a specific event in the shipment's journey.
 - `date`: Date and time of the scan event.
 - `status`: The status associated with the scan event.
 - `description`: Additional information about the scan event, if available.
- `status`: Indicates the overall success or failure of the API request.

Status Codes

- `200 OK`: The request was successful.
- `401 Unauthorized`: Authentication failure (invalid API key).
- `404 Not Found`: The specified order could not be found.
- `500 Internal Server Error`: An internal server error occurred.

Example

cURL Request

```
```bash
```

```
curl --location 'https://www.shipcorrect.com/api/trackOrder.php' \
--header 'Content-Type: application/json' \
--header 'api_key: YOUR_API_KEY' \
--data '{
 "order_no": "620092",
 "api_key": "YOUR_API_KEY"
}'
...
```

### ### cURL Response

```
```json
{
  "order_no": "620092",
  "awb": "81512801580",
  "courier_name": "Bluedart",
  "tracking_status": "Delivered",
  "scan_stages": [
    {
      "date": "2024-01-11 11:17:00",
      "status": "Delivered",
      "description": null
    },
    {
      "date": "2024-01-11 09:35:00",
      "status": "Out For Delivery",
      "description": null
    },
    {
      "date": "2024-01-10 15:01:00",
      "status": "In Transit",
      "description": null
    },
    {
      "date": "2024-01-09 00:00:00",
      "status": "In Transit",
      "description": "Picked Up"
    }
  ],
  "status": "success"
}
...
```
```

This documentation provides a detailed guide on how to use the ShipCorrect Order Tracking API to retrieve information about the status and tracking stages of a specific order.