

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [5-G-Product of Array elements-Minimum](#)

<b>Started on</b>	Monday, 7 October 2024, 7:30 PM
<b>State</b>	Finished
<b>Completed on</b>	Monday, 7 October 2024, 8:17 PM
<b>Time taken</b>	46 mins 28 secs
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

## Question 1

Correct

Mark 1.00 out of 1.00

Given two arrays array\_One[] and array\_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs( 1 element from each) is minimum. That is SUM (A[i] \* B[i]) for all i is minimum.

**For example:**

Input	Result
3 1 2 3 4 5 6	28

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3  int comp1(const void *a, const void *b){
4      return (*(int*)a)-(*(int*)b);
5  }
6  int comp2(const void *a, const void *b){
7      return (*(int*)b)-(*(int*)a);
8  }
9
10 int main(){
11     int n,sum=0;
12     scanf("%d",&n);
13     int arr1[n],arr2[n];
14     for(int i=0; i<n; i++){
15         scanf("%d", &arr1[i]);
16     }
17     for(int i=0; i<n; i++){
18         scanf("%d", &arr2[i]);
19     }
20     qsort(arr1,n,sizeof(int),comp1);
21     qsort(arr2,n,sizeof(int),comp2);
22     for(int i=0; i<n; i++){
23         sum += arr1[i]*arr2[i];
24     }
25     printf("%d", sum);
26     return 0;
27 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓

	Input	Expected	Got	
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 4-G-Array Sum max problem

Jump to...

1-Number of Zeros in a Given Array ▶