



SQL STORED ROUTINES



www.its.ac.id



[its_campus](#)



[institut teknologi sepuluh nopember](#)



SQL Procedures

- Functions have specific limitations
 - Must return a value
 - All arguments are input-only
 - Typically cannot affect current transaction status (i.e. function cannot commit, rollback, etc.)
 - Usually not allowed to modify tables, except in particular circumstances
- Stored procedures are more general constructs without these limitations
 - Generally can't be used in same places as functions
 - e.g. can't use in `SELECT` clause
 - Procedures don't return a value like functions do



Example Procedure

Write a procedure that returns both the number of accounts a customer has, and their total balance

- Results are passed back using out-parameters

```
CREATE PROCEDURE account_summary(  
    IN customer_name VARCHAR(20),  
    OUT a_count INTEGER,  
    OUT total_balance NUMERIC(12,2)  
)  
BEGIN  
    SELECT COUNT(*), SUM(balance)  
    INTO a_count, total_balance  
    FROM depositor AS d NATURAL JOIN account  
    WHERE d.customer_name = customer_name;  
END
```

- Default parameter type is IN



Calling a Procedure

- Use the CALL statement to invoke a procedure
`CALL account_summary(...);`
- To use this procedure, must also have variables to receive the values
- MySQL SQL syntax:
`CALL account_summary('Johnson', @j_count, @j_total);`
`SELECT @j_count, @j_total;`
- @var declares a temporary session variable

@j_cnt	@j_tot
2	1400.00



Conditional Operations

SQL provides an if-then-else construct

```
IF cond1 THEN command1  
ELSEIF cond2 THEN command2  
ELSE command3  
END IF
```

- Branches can also specify compound statements instead of single statements
 - Enclose compound statements with `BEGIN` and `END`
- Can leave out `ELSEIF` and/or `ELSE` clauses, as usual



Looping Constructs

- SQL also provides looping constructs

- WHILE loop:

```
DECLARE n INTEGER DEFAULT 0;  
WHILE n < 10 DO  
    SET n = n + 1;  
END WHILE;
```

- REPEAT loop:

```
REPEAT  
    SET n = n - 1;  
UNTIL n = 0  
END REPEAT;
```



Iteration Over Query Results

- Sometimes need to issue a query, then iterate over each row in result
 - Perform more sophisticated operations than a simple SQL query can perform
- Examples:
 - Many kinds of values that standard OLTP databases can't compute quickly!
 - Assign a rank to a collection of rows:
 - Can compare each row to all other rows, typically with a cross-join
 - Or, sort rows then iterate over results, assigning rank values
 - Given web logs containing individual HTTP request records:
 - Compute each client's "visit length," from requests that are within 20 minutes of some other request from the same client



Cursors

- Need to issue a query to fetch specific results
- Then, need to iterate through each row in the result
 - Operate on each row's values individually
- A cursor is an iterator over rows in a result set
 - Cursor refers to one row in query results
 - Can access row's values through the cursor
 - Can move cursor forward through results
- Cursors can provide different features
 - Read-only vs. read-write
 - Forward-only vs. bidirectional
 - Static vs. dynamic (when concurrent changes occur)



Cursor Notes

- Cursors can be expensive
- Can the operation use a normal SQL query instead?
 - (Usually, the answer is yes...)
 - Cursors let you do what databases do, but slower
- Cursors might also hold system resources until they are finished
 - e.g. DB might store query results in a temporary table, to provide a read-only, static view of query result
- Syntax varies widely across DBMSes
- Most external DB connectivity APIs provide cursor capabilities



Stored Routines and Cursors

- Can use cursors inside stored procedures and UDFs

- Syntax:

```
DECLARE n INTEGER DEFAULT 0;  
FOR r AS SELECT balance FROM account  
        WHERE branch_name='Perryridge'  
DO  
    SET n = n + r.balance;  
END FOR
```

- Iterates over account balances from *Perryridge* branch, summing balances
- *r* is implicitly a cursor
 - FOR construct automatically moves the cursor forward
- (Could compute this with a simple SQL query, too...)



MySQL Cursor Syntax

- Must explicitly declare cursor variable

```
DECLARE cur CURSOR FOR  
SELECT ... ;
```

- Open cursor to use query results:

```
OPEN cur;
```

- Fetch values from cursor into variables

```
FETCH cur INTO var1, var2, ... ;
```

- Next row is fetched, and values are stored into specified variables
 - Must specify the same number of variables as columns in the result
 - A specific error condition is flagged to indicate end of results
 - Close cursor at end of operation
- ```
CLOSE cur;
```
- Also happens automatically at end of enclosing block



## Handling Errors

- Many situations where errors can occur in stored procedures
  - Called conditions
  - Includes errors, warnings, other signals
  - Can also include user-defined conditions
- Handlers can be defined for conditions
- When a condition is signaled, its handler is invoked
  - Handler can specify whether to continue running the procedure, or whether to exit procedure instead



## Conditions

- Predefined conditions:
  - NOT FOUND
    - Query fetched no results, or command processed no results
  - SQLWARNING
    - Non-fatal SQL problem occurred
  - SQLEXCEPTION
    - Serious SQL error occurred



## Conditions (2)

- Can also define application-specific conditions
  - Examples:
    - “Account overdraft!”
    - “Inventory of item hit zero.”
- Syntax for declaring conditions:

```
DECLARE acct_overdraft CONDITION
DECLARE zero_inventory CONDITION
```
- Not every DBMS supports generic conditions
  - e.g. MySQL supports assigning names to existing SQL error codes, but not creating new conditions



## Handlers

- Can declare handlers for specific conditions
- Handler specifies statements to execute
- Handler also specifies what should happen next:
  - Continue running the procedure where it left off
  - Exit the stored procedure completely
- Syntax:
  - A continue-handler:  
`DECLARE CONTINUE HANDLER FOR condition statement`
  - An exit-handler:  
`DECLARE EXIT HANDLER FOR condition statement`
  - Can also specify a statement-block instead of an individual statement



## Handlers (2)

- Handlers can do very simple things
  - e.g., set a flag to indicate some situation
- Can also do very complicated things
  - e.g., insert rows into other tables to log failure situations
  - e.g., properly handle an overdrawn account





## Total Account Balance – MySQL

- Declared as a function – returns a value

```
CREATE FUNCTION acct_total(cust_name VARCHAR(20))
RETURNS NUMERIC(12,2)
BEGIN
 -- Variables to accumulate into
 DECLARE bal NUMERIC(12,2);
 DECLARE total NUMERIC(12,2) DEFAULT 0;

 -- Cursor, and flag for when fetching is done
 DECLARE done INT DEFAULT 0;
 DECLARE cur CURSOR FOR
 SELECT balance
 FROM account NATURAL JOIN depositor AS d
 WHERE d.customer_name = cust_name;
```



## Total Account Balance (2)

```
-- When fetch is complete, handler sets flag
-- 02000 is MySQL error for "zero rows fetched"
DECLARE CONTINUE HANDLER FOR SQLSTATE '02000'
 SET done = 1;
OPEN cur;
REPEAT
 FETCH cur INTO bal;
 IF NOT done THEN
 SET total = total + bal;
 END IF;
UNTIL done END REPEAT;
CLOSE cur;
RETURN total;
END
```



## Using Our User-Defined Function

- Can compute total balances now:

```
SELECT customer_name,
 acct_total(customer_name) AS total
FROM customer;
```



## Stored Routine Benefits

- Very effective for manipulating large datasets in unusual ways, within the database
  - Don't incur communications overhead of sending commands and exchanging data
  - Database can frequently perform such tasks more efficiently than the applications can
- Often used to provide a secure interface to data
  - e.g., banks will lock down data tables, and only expose certain operations through stored procedures
- Can encapsulate business logic in procedures
  - Forbid invalid states by requiring all operations go through stored procedures



## Stored Routine Drawbacks

- Increases load on database system
  - Can reduce performance for all operations being performed by DBMS
  - Need to make sure the operation really requires a stored procedure...
    - Most projects do not need stored procedures!
- Very hard to migrate to a different DBMS
  - Different vendors' procedural languages have many distinct features and limitations



**Thank You!**