



MHH772 / 90DaysOfDevOps



Code Pull requests Agents Actions Projects Wiki Security and quality Insights

Settings



master

90DaysOfDevOps / 2026 / day-17



LondheShubham153 Added day 17 tasks

836601a · 7 months ago



This branch is 16 commits ahead of TrainWithShubham/90DaysOfDevOps:master



Contribute



Sync fork

Name

Name

Last commit date



..



README.md

Added day 17 tasks

7 months ago

README.md



Day 17 – Shell Scripting: Loops, Arguments & Error Handling

Task

Level up your scripting — use loops, handle arguments, and deal with errors.

You will:

- Write **for** and **while** loops
- Use **command-line arguments** (\$1 , \$2 , \$# , \$@)
- Install packages via script
- Add basic **error handling**

Expected Output

- A markdown file: `day-17-scripting.md`
- All scripts you write during the tasks

Challenge Tasks

Task 1: For Loop

1. Create `for_loop.sh` that:
 - Loops through a list of 5 fruits and prints each one
2. Create `count.sh` that:
 - Prints numbers 1 to 10 using a for loop

Task 2: While Loop

1. Create `countdown.sh` that:
 - Takes a number from the user
 - Counts down to 0 using a while loop
 - Prints "Done!" at the end

Task 3: Command-Line Arguments

1. Create `greet.sh` that:
 - Accepts a name as `$1`
 - Prints `Hello, <name>!`
 - If no argument is passed, prints `"Usage: ./greet.sh "`
2. Create `args_demo.sh` that:
 - Prints total number of arguments (`$#`)
 - Prints all arguments (`$@`)
 - Prints the script name (`$0`)

Task 4: Install Packages via Script

1. Create `install_packages.sh` that:

- Defines a list of packages: `nginx` , `curl` , `wget`
- Loops through the list
- Checks if each package is installed (use `dpkg -s` or `rpm -q`)
- Installs it if missing, skips if already present
- Prints status for each package

Run as root: `sudo -i` OR `sudo su`

Task 5: Error Handling

1. Create `safe_script.sh` that:

- Uses `set -e` at the top (exit on error)
- Tries to create a directory `/tmp/devops-test`
- Tries to navigate into it
- Creates a file inside
- Uses `||` operator to print an error if any step fails

Example:

```
mkdir /tmp/devops-test || echo "Directory already exists"
```



2. Modify your `install_packages.sh` to check if the script is being run as root — exit with a message if not.

Hints

- For loop: `for item in list; do ... done`
- While loop: `while [ condition ]; do ... done`
- Arguments: `$1` first arg, `$#` count, `$@` all args
- Check root: `if [ "$EUID" -ne 0 ]; then echo "Run as root"; exit 1; fi`
- Check package: `dpkg -s <pkg> &> /dev/null && echo "installed"`

Documentation

Create `day-17-scripting.md` with:

- Each script's code and output
- What you learned (3 key points)

Submission

1. Add your scripts and `day-17-scripting.md` to `2026/day-17/`
2. Commit and push to your fork

Learn in Public

Share your scripting progress on LinkedIn.

  master ▾ [90DaysOfDevOps](#) / [2026](#) / [day-17](#) /  ↑ Top

Happy Learning! **TrainWithShubham**