The FLOPs You Save Are Not the Time You Spend: Sparse Attention in Multi-Agent Communication

Anonymous authors
Paper under double-blind review

Abstract

Attention-based communication between agents is routinely sparsified on the grounds that attending to a few peers rather than to all of them removes most of the work, and the case is almost always made by counting operations rather than by measuring execution. We show that the count is smaller than it appears, and that what it buys in time is smaller still. When an agent's partners are chosen by their attention scores, every score has already been computed before any can be discarded, so only the aggregation is removable and no choice of sparsity can remove more than half the arithmetic of attention. Whether even that half becomes time depends on the implementation to a degree an operation count cannot see. Applying the selection as a mask leaves the dense aggregation in place and executes no saving at all; a genuinely sparse implementation assembled from general-purpose tensor operations moves several times more data than dense attention despite performing less arithmetic, and runs an order of magnitude slower. Writing a fused kernel that keeps every intermediate on chip removes most of that penalty, and where a single peer is retained it makes the sparse path faster than any dense implementation we could obtain. That is the only regime in which it does, it holds only at narrow head widths where nothing we tried reaches half the machine's arithmetic rate, and retaining one peer is not a communication design. At every sparsity the field actually uses, the fastest sparse implementation we could construct remains an order of magnitude slower, because ranking the candidates costs more than aggregating over the survivors saves. Deciding what to attend to before the scores exist removes the bound entirely, and we measure two selectors that do so: they reduce the operation count by up to two orders of magnitude and buy at best fifteen per cent, because attention over a handful of gathered peers is not a shape this hardware is quick at. The design target is therefore not the arithmetic but the shape the remaining work is executed in.

1 Introduction

Cooperative multi-agent systems increasingly pass learned messages between agents, and attention is the mechanism they use to decide whose message matters (Das et al., 2019; Jiang & Lu, 2018; Jiang et al., 2020). It is a natural choice: the weighting is learned, it adapts to the situation, and it needs no hand-designed communication topology. It is also pairwise, so the channel costs quadratically in the number of agents, and a large part of the literature on learned communication is concerned with restricting who talks to whom.

Restricting communication can mean two different things, and the difference is easy to lose. In a distributed deployment the objective is to reduce the messages physically transmitted, and any restriction achieves that in proportion to the links it removes. In the centralised inference that most of this literature actually runs, the objective is to reduce the computation performed on one device, and there the proportionality does not follow. This paper is about the second. It asks what a particular and natural restriction — keeping, for each agent, the peers with the highest attention scores — saves in local computation, and whether the saving appears as elapsed time.

The efficiency case for that restriction is easy to state and easy to accept. If dense aggregation combines messages from every peer and sparse aggregation combines only a handful, then almost all of the aggregation disappears. What the statement omits is where the handful comes from. Selecting peers by attention score requires the scores, so by the time the selection can be made, every pairwise interaction has been evaluated. Attention has two matrix products of equal size, one producing the scores and one aggregating the values; sparsity of this kind reaches only the second. The arithmetic that can be removed is therefore at most half, whatever the sparsity, and the familiar fraction that describes the aggregation term alone overstates the achievable saving by a factor approaching two.

An operation count is a model of cost, and it can fail in more than one way. It can describe a computation the implementation does not perform: applying the selection as a mask on the dense attention matrix materialises the discarded entries as zeros and multiplies them anyway, so the executed aggregation is unchanged while a count based on the retained fraction reports a large saving. And the quantity it describes may not govern the outcome: on hardware where time tracks bytes moved rather than arithmetic performed, removing arithmetic from a kernel that is already waiting on memory changes nothing. Both failures occur here, and the second is the one that survives every correction we could make to the first.

The question this paper answers empirically is therefore whether genuinely executing the reduced aggregation makes score-then-select communication faster in the agent-count regime multi-agent communication occupies. We answer it by measuring six implementations of one function, verified equivalent at every configuration whose latency we report, against dense attention through both a library kernel and one we wrote ourselves.

The answer is conditional, and the condition is the contribution. Assembled from general-purpose tensor operations, the sparse path is slower than dense attention everywhere we measure, by up to an order of magnitude, and it moves several times more memory traffic while performing less arithmetic. A fused kernel that keeps the score row in registers and writes no intermediate removes most of that penalty, and where a single peer is retained it is faster than any dense implementation we could obtain, including a search over a hundred tilings of a dense kernel we wrote ourselves. Three qualifications bound that result and we state them with it. The advantage exists only at one retained peer, where the softmax is identically one and no weighting is being learned. It exists only at the narrow head widths where nothing we tried reaches half the device's arithmetic rate, and vanishes at the widths where the vendor library does. And it does not survive an increase in the number of retained peers, because ranking candidates costs more than aggregating over survivors saves; a kernel can make selection cheap in the number retained only by abandoning the compaction that made the aggregation sparse.

What follows constructively is the mechanism the negative result identifies. Selection that fixes the retained set before any score exists is not subject to the ceiling, and its operation-count saving is unbounded in principle. Whether it converts into time is a separate question, and we answer it for two selectors the count treats similarly: choosing the nearest peers by distance, which is what neighbourhood-based communication already does, and ordering agents along a space-filling curve, which is asymptotically cheaper. They remove between one and two orders of magnitude of arithmetic and buy at most fifteen per cent. The nearest-neighbour selector ranks a pairwise matrix of its own and reproduces the cost it was introduced to avoid. The Z-order selector does not, and still loses — and it loses even when its selector is set aside and only the attention over the already-chosen peers is timed. That stage's best case is fifteen per cent below dense attention where the count promises a factor of 132, because the gathered form is not a shape the hardware multiplies quickly.

Contributions.

- We show that any rule selecting communication partners by their attention scores can remove at most half of attention's arithmetic, however sparse it is, and that the bound is the special case of a general accounting in which a selection rule is charged for what it costs to run. That accounting places existing multi-agent restriction mechanisms on one axis and separates those that escape the bound from those that inherit it (Section 3).
- We measure what is actually executed, distinguishing masked, gathered and fused implementations of the same function, and find that the composed sparse path is slower than dense attention throughout

the regime by a margin its operation count cannot predict, with memory traffic rather than arithmetic as the cause (Section 4).

- We write fused sparse kernels and a dense baseline searched over the same tiling space, and report what fraction of the machine each reaches, so that the comparison identifies the algorithm rather than the authors. Sparsity does become faster than dense attention, at one retained peer, at narrow head widths, and nowhere else (Section 4.3).
- We instantiate the constructive half of the analysis with two selectors that fix the retained set before scoring. Both remove the operation-count bound and neither is faster overall, and the reason is not the selector: attention over a pre-chosen handful of peers is itself barely cheaper than attention over all of them at these sizes. The design target is the shape the remaining work is executed in, which an operation count cannot express (Section 5).

A secondary pre-registered training study establishes that the architecture being sparsified improves return, so that the sparsification comparisons are not vacuous, and reports six under-powered null contrasts as what they are (Section 6). Every computational claim concerns centralised inference on a single device, not bandwidth-constrained distributed deployment; Section 8 states the full envelope.

2 Related Work

2.1 Communication sparsity in multi-agent reinforcement learning

Learned inter-agent communication has converged on attention as the mechanism for deciding whose message matters. CommNet (Sukhbaatar et al., 2016) broadcasts mean-pooled hidden states; TarMAC (Das et al., 2019) introduces signature-based targeting so that receivers weight senders; MAT (Wen et al., 2022) casts the joint policy as a sequence model. Applied systems inherit the pattern, pairing heterogeneous learners with attention-based message aggregators (Hamdan et al., 2026). Since attention over N agents is pairwise, a large part of this literature also restricts who talks to whom, and the restriction is usually motivated by cost. DGN observes that receiving a large amount of information "requires high bandwidth and incurs high computational complexity" (Jiang et al., 2020), a claim about transmitted bytes and about local compute, of which only the second is what we measure.

Proposition 2 organises these restriction mechanisms by what their selector costs, and the resulting three groups behave differently. The first fixes the retained set from structure that is available before any score exists: DGN restricts attention to each agent's k nearest neighbours by Euclidean distance (Jiang et al., 2020), ATOC's initiator forms a group from its nearest collaborators within a communication field (Jiang & Lu, 2018), and mean-field methods replace the peer set with a single averaged interaction (Yang et al., 2018). Their selectors are free or nearly so, which places them in case (i) of the proposition. The second group scores something cheaper than the full pairwise interaction: IC3Net gates whether an agent speaks at all (Singh et al., 2019), and SchedNet ranks agents by a scalar importance weight and schedules the k largest (Kim et al., 2019). These are top-k rules, but over an $O(N)$ vector rather than an $N \times N$ matrix, so Proposition 1 does not bind them. The third group runs a pairwise selector before running pairwise attention: G2ANet decides which of all N^2 edges survive with a hard-attention network and then applies soft attention to the survivors (Liu et al., 2020b), and MAGIC builds a hard or soft adjacency from an all-pairs interaction before its graph attention (Niu et al., 2021). Their arithmetic saving is real in the aggregation and paid for in the selector, at the same order as the score matrix they avoid.

The mechanism this paper analyses — selecting peers by the attention score itself, after computing all of them — is the limiting case of that third group, and it is rare in multi-agent communication, not absent. The closest published relative is the adaptive sparse communication graph of Sun et al. (2020), which replaces softmax with a generalisation of sparsemax so that the normalisation itself emits exact zeros. It motivates the design partly through scalability, stating that the resulting sparsity "can reduce the complexity of both the forward pass and the back-propagation of the policy and value networks", and it explicitly considers and rejects hard top-k thresholding as non-differentiable. Because the sparsity-inducing map is applied to logits already formed for every pair, its selection is post-score and sits inside the class Proposition 1 constrains.

That places the method in our accounting and does not contradict its claims: its reported gains are in sample efficiency at up to 30 agents and it reports no measured runtime. Handshake-style mechanisms that match a requester's query against every candidate key and then select (Liu et al., 2020a) are score-then-select in the same sense.

The design we analyse is one we proposed and built, so the ceiling constrains our own design and the structural selectors above are outside it. And the agent counts at which these methods operate are small: between two and roughly thirty agents for the attention-based communication methods above, with DGN reaching the low hundreds in grid worlds. Our sweep runs to N=512 so that the trend is visible, but the regime the argument is about is $N \lesssim 10^2$, and beyond it the field has already abandoned all-pairs interaction in favour of neighbourhoods and mean fields — which is to say, in favour of selectors fixed before any score exists.

2.2 Sparse and efficient attention

The efficient-attention literature is where the operation-count argument for sparsity is most developed, and its mechanisms separate along the same axis. Longformer (Beltagy et al., 2020) and BigBird (Zaheer et al., 2020) fix which pairs interact in advance through sliding windows, global tokens and random edges, so the score computation itself becomes sparse and the saving is asymptotic; their selector is essentially free. Reformer (Kitaev et al., 2020) restricts candidate interactions by a locality-sensitive hash and Routing Transformer (Roy et al., 2021) by online k-means clustering; both are content-dependent, both evaluate scores only for candidate pairs, and together they are why the escape proposition carries a selector term at all. Performer (Choromanski et al., 2021) falls outside the premise entirely: it keeps every interaction and reorders the algebra through a kernel factorisation.

Top-k attention in the sequence setting is the closest external analogue of the mechanism we build, and the comparison turns on which efficiency is being claimed. Gupta et al. (2021) process queries in chunks and, for each query, compute its k largest scores against all keys exactly — a score-then-select rule in our sense — and their stated benefit is memory: chunking reduces peak attention memory from $\Omega(L_Q L_K)$ to $O(C L_K)$ for chunk size C while remaining a drop-in replacement in pretrained models. Memory efficiency, operation-count efficiency and wall-clock efficiency are distinct quantities, and a mechanism can improve one at the expense of another; ours is a question about the second and the third.

A related body of work asks how much of the attention function survives truncation, bounding the approximation error of keeping only the largest entries. That question is orthogonal to ours. We hold the function fixed — our gathered, masked and fused top-k implementations agree to floating-point tolerance — and ask whether the sparsification reduces executed computation and elapsed time. A method could be exact and slow, or approximate and fast, and the two literatures answer different halves of the design question.

Sparsemax (Martins & Astudillo, 2016) and α-entmax (Peters et al., 2019) obtain exact zeros from the normalisation rather than a hard cutoff, and make no claim about attention cost; that their zeros arrive after the scores exist, and are therefore subject to our ceiling, is an inference we draw, not a claim they make. Gumbel-softmax (Jang et al., 2017) supplies the relaxation used by learned discrete gates, and constrained-RL formulations (Achiam et al., 2017; Stooke et al., 2020) the machinery for optimising under a communication budget. We implement entmax and a Lagrangian budget as variants in Section 6.

Score-then-select is used at scale in sparse mixture-of-experts, where a router scores every expert and dispatches each token to the best k (Shazeer et al., 2017; Fedus et al., 2022). The structure of the argument is the one we examine, and so is the exemption: these architectures are designed so that the router is small relative to the expert computation it gates, so the analogue of our $N^2 d$ score term is a minor cost, not an equal one, and the saving is real. Whether score-then-select pays therefore depends on the ratio between the cost of scoring all candidates and the cost of the work being skipped — large in mixture-of-experts, and equal to one in single-head attention, which is the ceiling above.

2.3 Hardware-aware sparse execution

That operation counts, memory traffic, kernel fusion and realised latency are distinct quantities is established in the systems literature. The roofline model (Williams et al., 2009) formalises when arithmetic ceases to govern runtime. FlashAttention (Dao et al., 2022) and memory-efficient attention (Rabe & Staats, 2021) make the point from the other direction: the winning implementations of dense attention reduce memory traffic without changing the operation count at all, which is precisely the axis a FLOPs-based argument cannot see. Longformer anticipates the distinction this paper turns on, reporting runtime and memory for three implementations of one attention pattern — a loop version, a vectorised chunked version and a custom CUDA kernel — and noting that the chunked variant consumes roughly twice the optimal memory because it computes some zero values.

Recent systems work establishes where sparse attention does pay, and it bounds our conclusion from the other side. Native Sparse Attention (Yuan et al., 2025) ranks compressed key–value blocks and attends within only the selected blocks, with kernels written for the resulting access pattern, reporting large forward, backward and decoding speedups at 64k context; MiniMax Sparse Attention (Lai et al., 2026) co-designs blockwise selection with its GPU execution path and reports comparable prefill and decoding gains at 1M context. Three properties separate that regime from ours, and all three are load-bearing. Selection is amortised over blocks rather than performed per pair, so the selector cost falls by the block size. Block structure preserves the dense matrix-multiply shape inside each selected tile, so the arithmetic that remains still runs on the hardware path built for it — which per-pair gather, whose aggregation degenerates into a matrix–vector product, does not. And at 10^5–10^6 tokens the skipped computation is enormous, where at $N \lesssim 10^2$ it is bounded by Proposition 1 at a factor of two. We take these results at face value and make no claim of comparability across four orders of magnitude in sequence length; what they identify is what a successor design in our regime would have to change.

Measurement practice. Our training protocol follows the recommendations of Papoudakis et al. (2021) for systematic MARL benchmarking, and we report effect sizes and intervals in place of bare means (Agarwal et al., 2021). Environments come from the PettingZoo/MPE family (Terry et al., 2021) and the learner is MAPPO (Yu et al., 2022). Motivated by Longformer's precedent, we also checked whether the efficiency claims in the papers we drew on are accompanied by a measurement: among the multi-agent papers making such a claim, one of five reports a measured temporal quantity attributable to its mechanism, against five of six among the efficient-attention and mixture-of-experts papers. Twelve papers support no conclusion about either field, and we report the asymmetry only because it characterises the evidence base from which we ourselves adopted the operation-count argument. Appendix D gives the protocol, the completed sheet and its scope caveats.

3 Computational Limits of Score-Then-Select Attention

3.1 Problem setting

Consider one round of scaled dot-product attention over N agents, per batch element, at head width d. Agent i forms a query q_i; every agent contributes a key and a value; self-attention is masked. Write $s_i = q_i K^\top \in \mathbb{R}^N$ for the score vector and $a_i = \mathrm{softmax}(s_i)$ for the attention weights, so that dense attention computes $m_i = a_i V$. A top-k variant keeps the k largest entries of a_i and renormalises over them.

The mechanism this paper analyses is the one that arises most naturally from that description: form the complete score vector, then keep its k largest entries. We call such a rule *score-then-select*, and the term is used in its exact sense throughout. Every analytic claim below concerns that class, not content-dependent selection in general, and Section 3.2 draws the boundary.

Attention has two matrix products of equal size. One produces the pairwise scores; the other aggregates the values. Sparsifying the retained set shrinks the second, because only k value rows are combined. It cannot shrink the first, because the scores are what the selection reads. That observation is the whole of Section 3.2; the rest of this section makes it precise and marks where it stops applying.




Figure 1: Two implementations of dense attention and three of top-k attention, computing two functions in five ways. All five evaluate every pairwise score, because a score-then-select rule must form the complete score vector before it can rank it. They differ in what reaches memory and in how much arithmetic the aggregation performs, and only the gathered and fused top-k variants execute the saving that motivates sparsification at all.

Top-k attention admits three implementations of the identical function, and the distinction between them is what separates an arithmetic saving from an executed one.

Masked top-k. Compute a_i in full, multiply by a $\{0,1\}$ mask, renormalise, and evaluate $m_i = \tilde{a}_i V$ with $\tilde{a}_i$ still dense in memory. The discarded entries are materialised as zeros and multiplied, so the executed aggregation count is unchanged from dense while selection, masking and renormalisation are added on top.

Gathered top-k. Take the top-k of the raw scores, softmax over those k values, gather the corresponding value rows into a (B, N, k, d) tensor, and contract $(B{\cdot}N, 1, k) \times (B{\cdot}N, k, d)$. No zeros are materialised and the aggregation genuinely shrinks.

Fused top-k. Compute the same function in a single kernel, holding the score row in registers, selecting within them, and accumulating the weighted values without writing a score matrix, an index tensor or a gathered value tensor to memory. Section 4.3 reports one.

Gathered and masked top-k compute the same function (Figure 1). Softmax is monotone within a row, so the top-k weights are the top-k scores, and a softmax over just those k scores equals the dense softmax restricted to them and renormalised; the two agree to $< 10^{-10}$ in `float64` (Appendix B). The operation-count argument is about the gathered variant. Timing the masked variant measures an implementation artifact, and timing either against unfused dense alone ignores what a production kernel costs, so we report all implementations against both dense baselines throughout.

3.2 An operation-count ceiling

Analytic counts are multiply–accumulates. Under the convention that a multiply–add is two floating-point operations every term doubles and every ratio is unchanged, so the ceiling is the same number either way; we write MACs where the count is analytic and FLOPs only where a counter attached to the running program produced the figure. Counting the two matrix products that constitute attention, and excluding the shared input and output projections:

$$C_{\text{scores}} = N^2 d, \quad C_{\text{agg}} = N^2 d, \quad C_{\text{dense}} = 2N^2 d, \qquad C_{\text{top-}k} = \underbrace{N^2 d}_{\text{all scores}} + \underbrace{Nkd}_{\text{aggregate } k}. \tag{1}$$

Proposition 1 (Score-then-select ceiling)**.** *Let the retained set be fixed by a score-then-select rule, one whose kept indices are determined only after the complete score vector of each query has been formed. Then*

$$\frac{C_{dense}}{C_{top\text{-}k}} = \frac{2N^2 d}{N^2 d + Nkd} = \frac{2N}{N+k} < 2 \qquad \textit{for all } k \geq 1, \tag{2}$$

with supremum 2 *approached only as* $k/N \to 0$*. Within this class, no choice of* k *or* N *yields more than a twofold reduction in attention MACs.*

Proof. $C_{\text{top-}k} > N^2 d = \frac{1}{2} C_{\text{dense}}$ for every $k \geq 1$ since $Nkd > 0$, so the ratio is below 2. It is decreasing in k, hence largest at $k = 1$, and approaches 2 from below as $k/N \to 0$. □

The familiar figure $1 - k/(N-1)$ describes the value-aggregation term alone. Read as *the* saving it overstates the achievable reduction by a factor approaching two, before any question of whether the reduction is realised in time.

We use $N^2 d$ rather than $N(N-1)d$ because it is the count the implementations execute: self-masking writes $-\infty$ into the diagonal of a full $N \times N$ score matrix and does not skip work. Counting the diagonal exactly gives $2(N-1)/\big((N-1)+k\big)$, which is strictly smaller for every $1 \leq k \leq N-1$, so the proposition is a valid upper bound under either convention.

Five assumptions support the statement, of which only the second is essential. **(A1) Single round**: with R rounds both terms scale by R and the ratio is unchanged. **(A2) Full-score selection**: the retained set is determined only after the complete candidate score vector has been computed, so all N scores must be formed. **(A3) Per head**: with H heads of width d/H both terms scale identically. **(A4) Projections excluded**: including the shared qkv and output projections moves the ratio strictly closer to 1, so the bound remains valid. **(A5) Selection cost excluded**: counting the top-k operation itself can only decrease the ratio, and Section 4.5 shows the term is large in practice.

A2 concerns *when* the retained set is fixed, not whether the rule depends on the data. Mechanisms that are content-dependent but not score-then-select lie outside the class and are unconstrained by Proposition 1: exact or approximate nearest-neighbour retrieval, clustering and routing, indexing and hashing can all identify candidates without materialising the complete pairwise score matrix. Routing Transformer's online k-means routing (Roy et al., 2021) and Reformer's locality-sensitive hash (Kitaev et al., 2020) are content-dependent in every ordinary sense and still evaluate scores only for candidate pairs; a hierarchical rule that ranks compressed blocks and then scores only the selected ones (Yuan et al., 2025) is likewise outside A2. What such rules pay instead is a selector cost, and the next proposition charges them for it.

3.3 Selection before scoring

Proposition 2 (Escape)**.** *Suppose the kept set is determined* without *forming the complete score vector — structurally, or by a retrieval, routing, clustering, indexing or hashing rule — at total selector cost* $C_{\text{sel}}(N, k, d)$*, and that attention scores are then evaluated only for the* Nk *retained pairs. Then*

$$C_{\text{pre}} = 2Nkd + C_{\text{sel}}, \qquad \frac{C_{dense}}{C_{\text{pre}}} = \frac{2N^2 d}{2Nkd + C_{\text{sel}}}. \tag{3}$$

(i) *If* $C_{\text{sel}} = o(Nkd)$ *— in particular for a fixed or precomputed pattern, where* $C_{\text{sel}} \approx 0$ *— the ratio is asymptotic to* N/k*, that is* $\big(C_{dense}/C_{\text{pre}}\big)/(N/k) \to 1$*. Exact equality with* N/k *holds only when* $C_{\text{sel}} = 0$*; for every* $C_{\text{sel}} > 0$ *the ratio is strictly smaller.* (ii) *If only* $C_{\text{sel}} = o(N^2 d)$*, the ratio is no longer bounded by* 2*: with* $k/N \to 0$ *it diverges, though not in general at the rate* N/k*.*

Proof. Both statements read off the displayed ratio. For (i), $2Nkd + C_{\text{sel}} = 2Nkd\,(1 + o(1))$, so $C_{\text{dense}}/C_{\text{pre}} = (N/k)\,(1 + o(1))^{-1}$, whose quotient with N/k tends to 1; substituting $C_{\text{sel}} = 0$ gives $2N^2 d/2Nkd = N/k$ exactly, and any $C_{\text{sel}} > 0$ strictly enlarges the denominator. For (ii), if $k/N \to 0$ then $2Nkd = o(N^2 d)$, so the whole denominator is $o(N^2 d)$ and the ratio diverges. □

Proposition 1 is the special case $C_{\text{sel}} = N^2 d$: a score-then-select rule is one whose selector is a full score matrix, and it is that expense, rather than anything about top-k, that produces the twofold ceiling. Reading the two propositions as one statement places any peer-selection mechanism on a single axis, the cost of deciding what to keep, and the position on that axis determines what the mechanism can save.

The selector-cost term is material, not decorative. A fixed topology or a precomputed spatial prior really is free at inference and lands in case (i), which is why Longformer and BigBird obtain asymptotic savings where score-then-select top-k cannot (Beltagy et al., 2020; Zaheer et al., 2020): their patterns are fixed before any score is formed, so nothing is spent deciding. A hash must be evaluated and its buckets assembled (Kitaev et al., 2020), and a routing rule must maintain and query its clusters (Roy et al., 2021), so their C_{sel} has to be counted, not assumed away. Between the two sits a family of multi-agent methods whose selector is itself pairwise — a learned hard-attention or scheduling network evaluated over all N^2 pairs before communication attention runs (Liu et al., 2020b; Niu et al., 2021) — and for these C_{sel} is of the same order as the score matrix they avoid, so they inherit a ceiling of the same kind instead of escaping it.

Both propositions concern operation counts only. Whether a pre-score selector attains a proportional *speedup* is a separate question, and one that the measurements in Section 5 answer differently for two selectors that the count treats almost identically.

3.4 Why the count need not govern the time

Proposition 1 bounds a quantity that, in this regime, does not determine runtime. For memory-bound kernels time tracks bytes moved rather than arithmetic performed (Williams et al., 2009), and the composed implementations of Section 3.1 differ far more in bytes than in operations. Gathering does not remove memory traffic; it relocates it, replacing the multiplication of $N - k$ zeros with the reading, writing and re-reading of a compacted (B, N, k, d) tensor and of the indices that build it.

We compute arithmetic intensity, floating-point operations per byte of global memory traffic, analytically per stage, counting each tensor read and written once, and compare it against a machine balance measured on the same device: a large matrix multiply gives the achievable arithmetic rate, a large copy gives achievable bandwidth, and their ratio is the ridge point above which a kernel is compute-bound. Counting each tensor once ignores cache residency, so at small N, where the working set fits the GPU's L2, the analytic byte counts overstate traffic; the per-stage accounting of Section 4.5 flags such stages so the reader need not infer them. The ridge point itself depends on whether the probe's buffer fits the last-level cache, so we measure two of them per device. On the GPU the ridge is 23 FLOP/byte cache-resident and 53 from memory; on the host it is 8 and 28. Both paths in this study sit below every one of those figures at every agent count, on both devices, so the memory-bound conclusion does not depend on which ridge is the relevant one. Appendix B.5 gives the probe, including the buffer-initialisation defect that made an earlier version of it overstate host bandwidth several-fold.

Section 4.5 applies this accounting stage by stage and reports, for each stage, how close it runs to whichever machine limit binds it. That is what distinguishes a stage that is badly implemented from one that is doing the only thing its access pattern permits, and the distinction turns out to matter for which parts of the measured penalty a better kernel can remove.

4 Measured Cost

4.1 Method

We time the communication path with the training loop removed. Timing uses on-device CUDA events with an explicit synchronisation on the pinned device, and any diagnostic that transfers a scalar to the host is disabled, because such a transfer synchronises the device inside the timed region. Implementations are timed interleaved repetition by repetition rather than in sequential blocks, so that interference from other tenants lands on all of them at once and their ratios stay paired; the sequential design produced swings above 100% between identical configurations on this shared host. One interleaved group holds every implementation at one agent count, including every retained-peer count of every sparse implementation and the dense implementations they are divided by, so a ratio never spans two groups. The released artifacts record the dense rows with $k = N - 1$, which is a label and not a separate measurement. The primary statistic is the minimum over samples, on the modelling assumption that contention adds time rather than removing it, and the whole timed block is repeated so that the spread of per-run medians is reported and not hidden (Appendix A.2). GPU clocks could not be locked; the account lacks the privilege. Operation counts are analytic, from a model that follows the convention `torch.utils.flop_counter` uses and that we checked against it on the composed implementations; the hand-written kernels are outside what that counter observes. Every count in this paper is therefore a model, and where a count and a measurement disagree the measurement governs — which is, after all, the paper's subject.

Two decisions about what is compared deserve stating, because both changed our conclusions. First, we time the attention core — from queries, keys and values to the message tensor — rather than the enclosing module, since the shared input and output projections are identical across implementations and dilute the quantity in question. Second, the dense baseline is the better of PyTorch's fused scaled-dot-product path and a dense attention kernel we wrote ourselves in Triton, with the same tiling policy and in the same session as the sparse kernels. At the head widths multi-agent communication uses, the library path is tuned for a different regime, and comparing a hand-written sparse kernel against it credits sparsity with the difference between two authors (Section 7).

Every implementation is checked against the reference at every configuration whose latency any artifact reports — 158 of them, 136 with $k < N - 1$ so that selection is exercised. This is not a formality: exact top-k is discontinuous in the scores, so two implementations that accumulate the score product in different orders can rank a near-tied pair differently and then aggregate over different peers. All agree to extttfp32 rounding except on four query rows in 1.25 million, where two scores tie exactly at the k-th position and the threshold-selecting kernel keeps one extra peer (Appendix efapp:verification).

Unless stated otherwise: PyTorch 2.11 with CUDA 12.8 and Triton 3.6, `fp32`, head width d=16, batch 256, and one NVIDIA Blackwell GPU shared with other tenants.

4.2 What the composed implementations cost

Gathering executes less arithmetic than dense attention (the counter confirms the reduction Proposition 1 permits) and is nonetheless slower than every dense implementation at every agent count we measure (Table 1). Correcting the implementation from masked to gathered helps at small N and stops helping as N grows, because the gather's traffic grows faster than the masked path's wasted arithmetic.

Memory traffic is the mechanism, not arithmetic. Gathering does not remove the score matrix; it adds a compacted (B, N, k, d) tensor and the indices that build it, and then reads both back. Counting bytes gives a criterion that is easier to check than the intensity argument it replaces: gathering is byte-neutral only when the gathered operand is no larger than the score row it avoids reading, that is when $kd \leq N$. At d=16 and N=512 that bound is $k \leq 32$, and the quarter-of-peers operating point is four times past it. The criterion also predicts the reversal in which gathering loses to masking at intermediate N: the gathered operand passes the score row in size before the wasted multiplications catch up.

Table 1: Forward latency (ms, minimum over interleaved samples) of one function computed six ways, at a quarter of peers retained. The composed sparse path is slower than every dense implementation at every agent count, and the gap widens with N; the fused kernels change that, and Section efsec:fused reports where. The last column below N=192 is shown for completeness and supports no claim: those agent counts are launch-bound and do not reproduce (Appendix efapp:drift).

		dense			**top-k**			
N	k	unfused	fused (library)	ours	gathered (composed)	fused gather	fused mask	best sparse ÷ best dense
12	2	0.012	0.013	0.004	0.023	0.004	0.006	1.09
24	4	0.015	0.013	0.004	0.029	0.006	0.017	1.47
48	8	0.084	0.057	0.044	0.072	0.034	0.043	0.76
96	16	0.045	0.034	0.018	0.121	0.049	0.039	2.16
192	32	0.135	0.070	0.036	0.423	0.385	2.210	10.60
384	64	1.086	0.222	0.119	2.404	2.765	2.029	17.11
512	128	1.899	0.349	0.188	6.426	7.187	2.630	13.98




Figure 2: Latency divided by the faster of the two dense implementations, against the number of peers retained. The dotted line is what an operation count predicts for the gathered path, $(N + k)/2N$, which lies below parity everywhere and so predicts a saving at every sparsity. Shading marks the region in which sparsity is actually faster; only the fused gathered kernel enters it, and only at the smallest k. The N=96 panel is shown for continuity and supports no claim: repeating the sweep moves its ratios by a median of 61% (Appendix A.3).

4.3 What a purpose-built kernel changes

The composed path spends most of its time moving intermediates that a fused kernel need not create. To bound how much of the measured penalty is that composition rather than the algorithm, we wrote fused kernels that hold the score row in registers and never write a score matrix, an index tensor or a gathered value tensor to memory. Two selection strategies are available to such a kernel and they trade against each other. Selecting by k successive argmax-and-mask rounds keeps the aggregation genuinely sparse and makes selection cost proportional to k. Selecting by an exact bisection on the integer key of the score makes selection cost independent of k, but expresses the retained set as a zero weight rather than by compaction, so the aggregation performs dense arithmetic however small k is. Both compute the same function as the composed path.

Table 2: The sparsity at which the best sparse implementation stops being faster than the best dense one, and how far it is from parity at the sparsity multi-agent communication actually uses. Both ratio columns are a minimum over the composed and the two fused implementations, so the widest-k column is sometimes the composed path, which is the fastest sparse implementation there. Restricted to the agent counts whose measurements reproduce on repetition.

	sparsity that pays		**best ratio**		**at the widest k**	
N	k	of peers	ratio	at k	ratio	at k
192	≤ 1	0.5%	0.72	1	26.3	128
384	≤ 1	0.3%	0.86	1	17.1	128
512	≤ 1	0.2%	0.74	1	14.0	128

Table 3: Both kernels searched over the same parameter space — query tile, key tile or head chunk, warp count and pipeline depth — under the same shared-memory admissibility filter, with the better of the search and the vendor library taken as the dense baseline. The *cfgs* columns are how many configurations each search actually admitted, and they are very unequal: the sparse kernel must hold an N-wide score tile, so above 192 agents only three configurations fit. Efficiency is the executed arithmetic divided by the elapsed time, against the matrix-multiply rate the device attains in the same process.

		best dense				**best sparse**					
d	N	from	cfgs	ms	% peak	k	cfgs	ms	% peak	ratio	k that pays
16	192	triton	106	0.0347	30	1	12	0.0249	21	0.72	≤ 1
16	384	triton	106	0.1082	38	1	3	0.0941	22	0.87	≤ 1
16	512	triton	106	0.1681	44	1	3	0.1293	29	0.77	≤ 1
32	192	triton	94	0.0555	38	1	18	0.0428	24	0.77	≤ 1
32	384	triton	94	0.1923	43	1	3	0.1618	26	0.84	≤ 1
32	512	triton	94	0.3179	47	1	3	0.2231	33	0.70	≤ 2
64	192	sdpa	64	0.0862	48	1	21	0.0962	22	1.12	none
64	384	sdpa	64	0.2720	61	1	3	0.4321	19	1.59	none
64	512	sdpa	64	0.4361	68	1	3	0.5634	26	1.29	none
128	192	sdpa	28	0.1665	50	2	18	0.1724	24	1.04	none
128	384	sdpa	28	0.4688	71	1	3	0.8582	19	1.83	none
128	512	sdpa	28	0.7656	77	1	3	1.1784	25	1.54	none

Fusion removes most of the penalty. At 512 agents retaining a single peer the composed sparse path costs 4.62 ms and the fused one 0.139 ms, a factor of 33 attributable to the implementation and not to the algorithm. At that configuration the fused sparse path is also faster than the best dense implementation available to us.

That statement has to be qualified in turn, and the qualification is the more useful result. Matched authorship is a weaker condition than matched efficiency: two kernels written by the same person in the same session can still differ by more than the margin being measured, and only efficiency against the machine identifies the algorithm. We therefore searched the same parameter space for both kernels under the same admissibility filter, took the better of that search and the vendor library as the dense baseline, and report what fraction of the device's own matrix-multiply rate each kernel reaches beside its latency (Table 3).

The search is not equal, and the inequality is structural rather than incidental. Because exact selection must hold the complete score row of a query before it can rank it, the sparse kernel's resident tile grows with the agent count, and above 192 agents the shared-memory filter admits only three configurations against the dense kernel's twenty-eight to a hundred and six. We report the counts in the table rather than describing the two searches as equivalent, and the consequence runs in two directions. The sparse kernel's efficiency figure is a lower bound on what a sparse kernel of this shape could reach, so the negative entries at head

width 64 and above are weakly supported and we do not build on them. The positive entry is conservative for the same reason: an under-searched sparse kernel that is nonetheless faster is faster.

With that said, two things follow.

The crossover survives tuning, and it is not produced by a sparse kernel that happens to be well written. Across head widths 16 and 32 the sparse kernel is the *less* efficient of the two at every agent count — 21 to 33% of the device's rate against 30 to 47% for dense — and it is faster only because it performs about half the arithmetic.

The crossover is confined to a single retained peer, or two at one configuration, and to the two narrowest head widths. At four retained peers the sparse kernel is already 1.3 to 2.1 times slower, and at a quarter of peers it is more than an order of magnitude slower. A single retained peer is not a communication design: the softmax over one element is identically one, so the mechanism degenerates to copying the highest-scoring peer's value. The crossover is a fact about the cost model, not a recommendation.

Why it is confined to narrow heads we cannot say from these measurements. Dense efficiency and head width move together in our data — 30% at d=16 rising to 77% at d=128, as the score product becomes a better-shaped matrix multiply — and no configuration we ran separates them, so "the crossover disappears once dense attention is near the machine" and "the crossover disappears above d=32" fit our data equally well. Either reading leaves the positive result provisional on a dense kernel we could not write: if one exists at narrow head widths that reaches what the library reaches at wide ones, the crossover goes. Nothing else in the paper depends on it.

Two structural obstacles are independent of all of this, and they are what a successor design has to face. Selection is the first. Ranking N candidates to keep k costs k sequential row-wide reductions in the argmax kernel, and a reduction of that shape runs at a small fraction of the arithmetic units' throughput because each round depends on the one before it and the hardware has nothing to overlap it with. That is why the sparse kernel's cost grows almost linearly in k while its arithmetic barely does. The bisection kernel removes the dependence on k, and the only way it can is by expressing the retained set as a zero weight instead of by compaction — so it performs the dense aggregation arithmetic whatever k is. We could not write a kernel with both sparse arithmetic and k-independent selection; a radix or bitonic select would narrow the gap and we did not implement one, so this is a statement about the implementations we obtained, not about what is possible.

The second obstacle is available to dense attention and not to exact score-then-select. Dense attention can stream keys and values in blocks with an online softmax, keeping only a small tile resident. Exact selection cannot: the complete score row of a query must exist before the row can be ranked, so the sparse kernel holds an N-wide tile and fewer queries can be in flight per streaming multiprocessor as N grows. That is a consequence of full-score selection itself, not of our implementation, and it is why the tiling the search chooses for the sparse kernel is narrower at every size.

4.4 Sensitivity to head width and batch

Across head widths to 512, the crossover exists only at the two narrowest: the best sparse implementation is faster than the best dense one at head widths 16 and 32 at every agent count, and at no agent count for head width 128 or above, where it is roughly twice as slow (Appendix A). The ratio does not fall monotonically with head width; it reverses.

That is what the byte criterion predicts. Byte-neutrality requires $kd \leq N$, so widening the head at fixed agent count tightens the bound on the retained set proportionally, and at head width 128 the criterion permits only $k \leq 4$ at 512 agents — by which point the selection cost of Section 4.3 has already overtaken the saving. Widening the batch over a thirty-twofold range, by contrast, moves the ratio by less than a fifth and never across parity, which is the expected behaviour of a quantity that is a ratio of per-element costs.

Table 4: Per-stage accounting for both paths at N=512. The last column is the fraction of whichever machine limit binds the stage, and it separates a stage that is badly implemented from one doing the only thing its access pattern permits. The byte counts are analytic and count each tensor once, so a figure above 100% marks a stage whose working set is partly served from cache. That happens for the softmax stages here and, at smaller agent counts, for the gather; it bounds the model's error at around +50 percentage points, which is larger than several of the gaps in the column and is why we do not read small differences off it. Peak measured on the same device: 57.8 TFLOP/s and 1497 GB/s, a ridge point of 39 FLOP/byte.

stage	GFLOP	GB	FLOP/byte	ms	TFLOP/s	GB/s	% of limit
score product	2.15	0.29	7.53	0.549	3.91	520	35
softmax over N	0.34	0.54	0.62	0.336	1.00	1598	107
dense aggregation	2.15	0.29	7.53	0.235	9.13	1213	81
top-k selection	0.00	0.47	—	3.271	—	143	10
softmax over k	0.08	0.13	0.62	0.059	1.42	2268	151
gather of V	0.00	1.21	—	0.954	—	1265	84
sparse aggregation	0.53	1.14	0.47	0.816	0.65	1398	93




Figure 3: **Left:** how each path divides its time. Selection grows to dominate the gathered path as the agent count rises. **Right:** how close each stage runs to the machine limit that binds it.

4.5 Where the time goes

Low arithmetic intensity in a batched matrix–vector product is the natural explanation for the sparse contraction's slowness, and it is not the right one. Timed in isolation and charged with its own arithmetic and traffic, both aggregations sit near the bandwidth the device attains on a large copy — 93% for the sparse contraction and 81% for the dense multiply it replaces (Table 4). Those two figures are close enough that the analytic byte model cannot order them, which is the point: neither is on a worse hardware path. Both are bandwidth-saturated and neither is on a worse hardware path; the sparse one is slower because it moves about four times the bytes, since the compacted operand carries kd elements per query where the score row

Table 5: Forward, backward and their sum, for the differentiable implementations. The sparse path's backward is cheap relative to its forward, because selection has almost no adjoint, so the gap against fused dense narrows without closing. Restricted to the agent counts that reproduce: below 192 the forward and the forward-plus-backward passes are timed in separate interleaved blocks, and the contention between blocks exceeds the backward's own cost, which at two configurations produced a difference a backward pass cannot have.

		dense, unfused			dense, fused			top-k masked			top-k gathered			
N	k	f	b	f+b	f	b	f+b	f	b	f+b	f	b	f+b	gathered f+b ÷ fused f+b
192	32	0.135	0.245	0.380	0.070	0.362	0.432	0.452	0.486	0.938	0.423	0.219	0.642	1.5
384	64	1.086	1.589	2.674	0.222	0.724	0.946	3.063	3.451	6.513	2.404	1.605	4.010	4.2
512	128	1.899	2.643	4.542	0.349	1.203	1.552	6.979	5.761	12.739	6.426	3.133	9.559	6.2

carries N. The corrected account is simpler, checkable before the code is written, and it is the $kd \leq N$ criterion of Section 4.2.

Selection is a different case, and it is the one stage where the raw decomposition is misleading in the opposite direction. It is the largest stage of the composed sparse path, and it runs at under a tenth of the bandwidth the device attains: it must read the score matrix and write values and indices, and moving those bytes and nothing else would take a small fraction of the time it does. That headroom is real, and the fused kernels realise part of it. What no kernel removes is that the score matrix must be formed and ranked at all, and the fused measurements of Section 4.3 show what remains once the headroom is taken.

4.6 Backward pass and training throughput

Every latency reported so far is a forward pass, which for a training claim is half the question. Timing forward and backward under the same protocol leaves the ordering intact and roughly a third of the margin (Table 5). The gathered path's backward costs about half its own forward, because the expensive stage — selection — has almost no adjoint: the retained indices are recorded in the forward pass and the backward is a scatter of gradients into them. Dense attention's backward costs several times its forward. At 512 agents the gathered path is 18.4 times the fused dense path on the forward alone and 6.2 times on forward and backward together, and the same narrowing appears at every agent count in the table. The sparse path's disadvantage in training is therefore substantially smaller than the forward-only measurements suggest, and remains a disadvantage. The fused kernels are excluded from this comparison: they are hand-written forward passes, and timing one against an autograd graph would compare two different things.

End to end, none of this is visible. Timing a complete training iteration by phase, with the communication implementation swapped and everything else fixed, puts the environment and per-step action selection at 78% of the iteration at six agents and 96% at twenty-four, and leaves all five implementations within 2% of one another at every agent count, against an iteration-to-iteration spread of 0.8 to 7.3% (Table 6). The ordering among the five is not stable: the communication-free variant, which performs no attention at all, is fourth of five at six agents and at twenty-four, and the gathered sparse implementation is the fastest of the five at twenty-four. This does not resolve the implementations as equal; it fails to resolve them at all, which is the useful description as well as the honest one. It bounds the practical stakes of the whole measurement campaign in the regime the training study occupies, and it is why the computational argument is made on the module in isolation.

4.7 Robustness

The ordering is unchanged under `torch.compile` and CUDA-graph capture, at `bf16`, and on an x86_64 CPU whose machine balance differs from the GPU's by more than an order of magnitude. The CPU comparison required controlling an effect unrelated to attention: with the default allocator the multi-MiB temporaries each implementation frees between calls are returned to the kernel and re-faulted on the next call, which at N=192 adds roughly 37,000 minor page faults per forward and inflates latency by up to 8.8×. The tax is

Table 6: Where one MAPPO iteration spends its time. Differences between communication implementations are at or below the iteration-to-iteration spread in the rightmost column.

		share of the iteration (%)							
N	communication	environment	acting	update fwd	update bwd	optimiser	s/iter	÷ fused	spread
6	none	49	29	11	6	4	2.11	1.002	4.6
6	dense, unfused	48	30	12	6	4	2.09	0.992	7.3
6	dense, library fused	48	30	12	6	4	2.10	1.000	4.0
6	top-k, masked	48	30	12	6	4	2.09	0.996	5.4
6	top-k, gathered	49	29	12	6	4	2.13	1.011	5.3
12	none	76	14	5	2	2	4.35	0.998	2.3
12	dense, unfused	75	14	6	4	2	4.39	1.007	3.8
12	dense, library fused	75	14	6	3	2	4.36	1.000	3.3
12	top-k, masked	75	14	6	3	2	4.39	1.008	5.6
12	top-k, gathered	75	14	6	4	2	4.41	1.011	2.3
24	none	92	5	2	1	1	12.84	1.002	4.2
24	dense, unfused	91	5	2	1	1	12.98	1.013	3.3
24	dense, library fused	91	5	2	1	1	12.81	1.000	1.6
24	top-k, masked	91	5	2	1	1	12.80	0.999	0.8
24	top-k, gathered	91	5	2	1	1	12.76	0.996	1.7

proportional to the bytes of large temporaries each implementation churns, so it does not cancel in a ratio, and in an un-pinned run it inverted the ordering at one configuration. With the heap pinned the inversion disappears. Appendix B.4 gives the procedure and both runs.

Because clocks are unlocked and the host is shared, we re-ran the identical sweep with the device otherwise idle and again under a concurrent load. With the device idle the ratios reproduce to within a few per cent; under load absolute latency moves by more than 100% while the paired ratios move by roughly half that, and every ratio moves against the sparse path. Pairing removes the typical drift rather than the tail, so the quantity that matters is the margin: no condition we measured brings a composed sparse implementation below parity, and the fused crossover reported in Section 4.3 is measured on the quietest device state we could obtain. Appendix A.3 gives the figures.

5 Selecting Before Scoring

Proposition 2 says that a selector fixing the retained set before any score exists is not bound by the twofold ceiling, and that its operation-count saving grows without limit as the retained set shrinks. That is a statement about counts, and this paper is about what counts fail to predict. This section instantiates the escape and measures it.

We use two selectors, both corresponding to mechanisms multi-agent communication already uses. The first retains each agent's k nearest peers by Euclidean distance over two-dimensional positions, which is what neighbourhood-based communication does (Jiang et al., 2020; Jiang & Lu, 2018). Its selector is still pairwise, but pairwise in two dimensions rather than in the head dimension, so it costs a factor of $d/2$ less than forming the scores. The second orders agents along a Morton curve and retains the k agents adjacent in that order, at $O(N \log N)$, which satisfies the $o(Nkd)$ condition of case (i). Both then evaluate attention scores for the retained pairs only, so the score term falls from $N^2 d$ to Nkd and the ceiling does not apply.

The two selectors attend to different peers than a top-k rule would, so what follows compares cost and not quality. Selection and attention are timed separately as well as together, so that the selector is charged and not assumed away. Every ratio is against the faster of the library dense kernel and our own, for the reason Section 7 gives.

The operation-count saving is exactly what the proposition predicts. At 512 agents retaining four peers, the Z-order path performs 104 times fewer operations than dense attention and the nearest-neighbour path

Table 7: Selecting before scoring, at 4 retained peers. The operation-count saving reaches two orders of magnitude and the elapsed time does not follow it anywhere. Selection and attention are timed separately and the total is timed as one call, so the components need not sum exactly.

		ops	**measured (ms)**			**best**	**÷ best dense**	
N	selector	saved	select	attend	total	dense	attend	total
48	nearest neighbours	8	0.151	0.064	0.167	0.035	1.85	4.85
48	Z-order window	10	0.367	0.059	0.386	0.035	1.72	11.18
96	nearest neighbours	11	0.188	0.068	0.206	0.051	1.33	4.03
96	Z-order window	20	0.362	0.065	0.385	0.051	1.28	7.53
192	nearest neighbours	15	0.378	0.097	0.442	0.086	1.13	5.17
192	Z-order window	39	0.366	0.095	0.410	0.086	1.11	4.79
384	nearest neighbours	17	1.871	0.173	2.024	0.169	1.02	11.96
384	Z-order window	78	0.374	0.171	0.478	0.169	1.01	2.82
512	nearest neighbours	18	4.986	0.231	5.192	0.186	1.24	27.90
512	Z-order window	104	0.131	0.221	0.372	0.186	1.19	2.00




Figure 4: **Left:** the operation-count saving Proposition 2 promises, which for the sub-quadratic selector tracks N/k. extbfRight: what the same configurations cost. Neither selector reaches parity, and the two that the count treats similarly diverge by an order of magnitude. The dotted line charges the selector nothing and times only the attention over the already-chosen peers: it approaches parity from above and barely passes it, against an operation count promising two orders of magnitude.

18 times fewer, the difference between them being the cost of their selectors. Neither is faster than dense attention at any agent count we measure, and the best either comes is 1.8 times dense.

Two separate things go wrong, and only the first is the one we expected.

The selector can cost more than the attention it is choosing for. The nearest-neighbour selector materialises an $N \times N$ distance matrix and ranks it, which are the same two operations, on the same shape, that Proposition 1 says a score-then-select rule cannot avoid. Working in two dimensions rather than in the head dimension buys a factor in the arithmetic and nothing in the traffic, and traffic is what governs (Section 4.5); by 512 agents its selector alone costs 27 times the whole of dense attention. The Z-order selector avoids the quadratic structure and its cost is flat in the agent count, but flat is not small: it sits between 0.13 and 0.37 ms across our range, which is comparable to or larger than the entire dense attention it is displacing at

every agent count. It is also composed from library operators, so like the composed sparse path of Section 4.2 its constant is an upper bound rather than a property of the design.

The second failure is the one that matters, because no better selector can repair it. Set the selector aside entirely and time only the attention over an already-chosen peer set — scoring Nk pairs instead of N^2, then aggregating over k. That stage is barely cheaper than dense attention anywhere and is usually dearer. Its best case over the whole grid is 0.85 times dense, at 384 agents retaining two peers, where the operation count promises a factor of 132; at four retained peers it never falls below 1.01, and at the smallest agent count it costs 1.7 to 1.9 times dense. Two orders of magnitude of arithmetic buy, at the very best, fifteen per cent.

The reason is the one Section 4.2 identifies for the score-then-select path, and it survives the change of selector because it was never about selection. Scoring Nk chosen pairs requires gathering k keys and k values per query, so the operand is $2kd$ elements per query where dense attention reads a contiguous N-row block and multiplies it as a matrix product. At 512 agents, four retained peers and head width 16 that is 128 gathered elements per query against a 512-wide contiguous row, and the gathered form loses the matrix-multiply shape as well. The arithmetic falls by two orders of magnitude and the traffic does not. We did not fuse this stage, and by the standard Section efsec:fused sets that makes its constant an upper bound rather than a property of the design: a fused pre-score attention kernel is the obvious next measurement, and until it exists the explanation above is an inference from the accounting and from the score-then-select case rather than an independently controlled result.

What this leaves of Proposition 2 is worth being exact about, because the proposition is not wrong. Removing the full score matrix genuinely removes the ceiling: the count ratios in Table 7 are far above the factor of two that bounds any score-then-select rule, and no implementation elsewhere in this paper achieves anything like them. The proposition simply turns out to bound the wrong quantity twice over. Its selector term is charged in operations, and the nearest-neighbour selector shows that a selector can be cheap in operations and ruinous in traffic. And the term it leaves — attention over Nk pairs — is itself priced in operations, and at these sizes that price is not what the hardware charges.

A successor design is therefore accountable for three things rather than one, and an operation count shows only the first: what the selector costs to run, whether it reaches its decision without materialising a structure of the size it meant to avoid, and whether the sparse attention it leaves behind can be executed in a shape the hardware is fast at. The third is the one this section adds, and it is the reason block-level selection works in long-context attention while per-pair selection does not work here. A block of a long sequence is still a dense matrix multiply after selection; a handful of gathered peers is not.

6 Learning Study

Sparsification would still be worth having if it cost nothing in return. Testing that requires care, because on a task where the channel is not needed "sparsification is free" and "the channel was never used" make identical predictions. We therefore gate the study on a positive control and register the analysis plan before the outcomes are inspected. The study is secondary. Its role is to establish that the architecture being sparsified does something, so that the sparsification comparisons are not vacuous, and to report what a five-seed design can and cannot resolve.

6.1 Design

Twelve variants at up to twelve agents, five seeds each, two million environment steps. All scaling in the number of agents is delegated to the training-free measurements of Section 4, because an end-to-end training step in this pipeline is dominated by the environment (Section 4.6) and cannot attribute a latency difference to the communication module.

Two positive controls establish that the channel carries something. The first is a reference task in which each agent observes only its partner's goal, so information must pass between agents; it is fixed at two agents, where the selection mechanism is degenerate, so it validates the message pathway and not the selection. The

Table 8: The two positive controls, which were inspected before registration and are excluded from the correction, and the primary pre-registered comparison. $A-B$ is the difference of means and d the standardised effect. Appendix C gives the remaining five comparisons.

	$A-B$	95% interval	d	p
Positive controls, descriptive				
communicating − non-communicating, reference task	+4.26	[+3.15, +5.23]	—	0.0079
communicating − non-communicating, partially observable	+11.59	[+7.13, +16.44]	—	0.0079
Primary pre-registered comparison				
attention-selected peers − uniformly random peers, same budget	+4.03	[−3.35, +11.42]	+0.60	0.357

second is a partially observable variant of a standard cooperative task, introduced here, in which a peer's relative position is withheld beyond a fixed radius. Under a uniform random policy the fraction of peers visible falls with the number of agents while the absolute number visible rises, because the world does not grow: that is a difficulty confound across agent counts, and it is why no claim in this paper compares returns across agent counts in this environment.

The analysis plan was committed after eight of the forty runs in the pre-registered family had completed and before any of their outcomes was inspected; the two positive controls were complete and had been inspected, which is why they are excluded from the inferential family. Appendix C.1 gives the chronology and the single amendment. The plan fixes the endpoint, the six comparisons and their direction, an exact two-sided permutation test, the effect sizes, a percentile bootstrap interval flagged approximate at five seeds, and a Holm–Bonferroni correction. It also fixes the power expectation in advance: with five seeds per variant the smallest attainable two-sided p-value is $2/252 = 0.0079$ against a first Holm threshold of $0.05/6 = 0.0083$, a margin of 4×10^{-4}, so a first rejection requires one variant's five seeds to lie entirely above the other's. Any null in this family is under-powered and is not evidence of absence, and no equivalence claim is available because no equivalence margin was registered.

6.2 Results

Both positive controls separate completely, each attaining the floor of the permutation test for this design (Table 8). Measured attention entropy on the partially observable control is 0.35 nats against a ceiling of 1.61, so the learned weighting is peaked, not uniform. What this establishes is that sparsification is being applied to an architecture whose communication machinery improves return under the evaluated setup. It does not establish that the learned attention channel alone accounts for the difference: the communicating variants carry 7–19% more trainable parameters, and the reference task supplies a discrete utterance channel of its own. A parameter-matched sham-communication variant would be needed for the channel-specific causal claim, and we do not make it.

The comparison the design exists for holds the communication budget, the executed aggregation cost and every hyperparameter fixed, and varies only whether peers are chosen by attention score or uniformly at random. Its point estimate favours attention by roughly two thirds of a standard deviation and its interval includes zero. The design lacked the power to resolve an effect of that size, which the pre-registered power calculation said in advance; nothing follows about whether attention selects informatively. The remaining five comparisons are reported in Appendix C as point estimates with intervals (Agarwal et al., 2021), and all six are Holm-adjusted nulls. No conclusion in this paper rests on any of them.

The environment limits the study in two ways. At twelve agents neither variant learns the task well: the dense variant scores below a uniform-random policy and the sparse variant only just above it, so no comparison at that agent count is interpretable. And the centralised critic sees the same masked observations as the actors, with no privileged global state, which departs from standard practice for this learner and is a plausible contributor to that failure.

7 Sources of Measurement Error

Every measurement in this paper was at some point wrong, and in each case the first symptom was a plausible number rather than an obvious error. The causes group into four kinds, and the grouping is useful because the kinds differ in how they are caught. Table 9 lists them with the corrective practice each forced.

Instrumentation. A diagnostic that synchronises the device inside the timed region measures the synchronisation. Our attention module computed an entropy statistic through a call that transfers a scalar to the host, and with it enabled dense latency was nearly flat in N while its work grew by two orders of magnitude — a result we briefly read as evidence that the quadratic cost does not manifest. Synchronising without naming the device is the complementary error: work submitted to a non-default device is never waited on, and every kernel at every size then reports the event-resolution floor of about 0.4 μs. On the host, the default allocator returns the multi-MiB score matrices each implementation frees between calls, so the next call re-faults them; at N=192 that added roughly 37,000 minor page faults per forward and inflated latency by up to 8.8×. Errors of this kind leave traces — an impossible latency, a curve that is flat where it should be quadratic, a non-monotone cost — and are caught by looking at the shape of the result rather than its value.

Interference from a shared device. Timing implementations in sequential blocks makes each block hostage to whatever else was running during it. On our shared host that produced swings above 100% between identical configurations and a 3.7× discrepancy for one implementation at one agent count. Interleaving the implementations repetition by repetition lands any interference burst on all of them at once, so the ratios between them survive even when the absolute numbers drift. The residual sensitivity is to which implementations share an interleaved sweep: at small N, where cost is governed by kernel launches rather than by arithmetic or bandwidth, the launch count of the whole group enters every measurement in it, and two of our own sweeps disagree by 5× at one such configuration. Sweeps that will be compared must therefore hold their implementation set fixed and say so.

Measuring a different algorithm from the one claimed. The two most dangerous errors are of this kind, because the resulting numbers are internally consistent, reproducible, and stable under every check the others would fail. They answer a different question from the one being asked. Applying top-k as a mask leaves the dense aggregation matmul in place, so the advertised saving is never executed; a FLOP model based on $1 - k/(N-1)$ nonetheless credits that code with a 75% saving at N=512, k=127, and with more than 90% wherever $k/(N-1) < 0.1$. Comparing against unfused dense alone is the same error in the baseline: at N=512 the unfused and fused dense paths differ by 4.6×, so which one is meant sometimes changes the answer. The defence is to state the operation count each implementation executes alongside its latency, and to check which backend actually serves each shape and dtype, both of which make a mismatch between the claimed and the executed algorithm visible immediately.

Attributing implementation quality to the algorithm. The fourth kind appeared only when we wrote our own kernels. Timing a hand-written sparse kernel against a vendor library's dense kernel measures sparsity and authorship at once. At the head widths used in multi-agent communication, PyTorch's fused attention path runs at roughly half the rate of a straightforward Triton kernel, because it is tuned for the long sequences and wide heads of language models. Against it our fused sparse kernel appears up to 2.5× faster, which is more than sparsity can supply at any k and was how we noticed. Matched authorship is the obvious remedy and it is not sufficient either: two kernels by the same author can differ by more than the margin under test. The condition that identifies the algorithm is matched *efficiency*, so we search the same tiling space for both and report what fraction of the device's own arithmetic rate each one reaches (Section 4.3). That is also what reveals when neither implementation is near the machine, which is a different warning and one worth having: a comparison between two kernels at a third of peak resolves the algorithms only if the margin exceeds the headroom, and ours does not everywhere.

One belief of our own also needed correcting. We assumed that standard counters are blind to fused attention kernels, which would make a FLOPs-only comparison unable to see the baseline that matters. In PyTorch

Table 9: Eight ways a benchmark measures something other than the algorithm, each of which produced a spurious result in this study. The first five are caught by the shape of the result; the last three are not, because the numbers they produce are self-consistent.

Kind	Cause	Symptom	Corrective practice
Instrumentation	Host transfer inside the timed region	Dense latency nearly flat in N	Gate diagnostics behind a flag that is off while timing
	Synchronisation without a device argument	Every kernel reports the event-resolution floor	Pin the device and pass it to every synchronisation
	Host allocator returning large temporaries	Up to 8.8× inflation and a non-monotone curve	Pin the heap; count minor faults per forward
Interference	Timing implementations in sequential blocks	Swings above 100% between identical configurations	Interleave repetition by repetition; report paired ratios
	Changing which implementations share a sweep	Two sweeps disagree by 5× at one configuration	Fix the implementation set across comparable sweeps
Wrong algorithm	Benchmarking a masked implementation as sparse	The advertised saving is never executed	Assert executed FLOPs differ and trace the products issued
	Comparing only against unfused dense	A 4.6× more favourable comparison at N=512	Report both baselines; check which backend serves the shape
Wrong baseline	A hand-written sparse kernel against a vendor's dense kernel	An apparent speedup larger than the analytic ceiling permits	Write the dense baseline in the same framework and tiling

2.11 that is not so: `torch.utils.flop_counter` reports the fused path correctly, and it was our harness that added an analytic term on top of the counter's output for that implementation, publishing a figure 1.83× too large. The narrower point generalises better than the one we started with: a counter has to be validated against the kernels it is expected to observe, because only a counter attached to the running program can contradict a FLOP model.

8 Limitations

Every cost result here concerns centralised inference on a single device: the latency and memory of executing the communication module in one process that holds all agents' observations. It is not a claim about bandwidth-constrained distributed deployment, where the objective is to reduce messages physically transmitted and top-k sparsification may well be correct even though it does not reduce local computation. Proposition 1 says nothing about transmitted bytes, and neither do the measurements. The analysis is also single-round and single-head. Assumptions A1 and A3 show that the *operation-count* ratio is invariant to rounds and heads, but this paper's whole argument is that the operation-count ratio does not determine time, so that invariance cannot be used to extend a timing result. It should not be: H heads of width d/H is a change in per-head width, and per-head width is the axis along which our timing result changes sign.

The measured envelope is one GPU architecture (NVIDIA Blackwell, sm_120), one x86_64 CPU, PyTorch 2.11 with CUDA 12.8 and Triton 3.6, input embedding width 64, head width $d \in \{16, \dots, 512\}$, $N \leq 512$, batch 32–1024, `fp32` and `bf16`, and eager, compiled and CUDA-graph execution. The crossover of Section 4.3 is narrower still: it appears only at $d \in \{16, 32\}$, only at $N \geq 192$, and only in `fp32`, which is the dtype in which dense attention is least advantaged. We could not replicate on a second GPU generation, because the host has two cards of the same model and the hardware that produced this project's earlier runs is gone. Both cards were shared with other tenants throughout. That is why every claim is stated as a ratio between implementations timed in the same interleaved sweep, why the headline sweep was repeated in full, and why no claim is read off an agent count below 192, where the repeat does not reproduce.

Our sparse implementations are not optimal and neither is our dense baseline. We searched the same tiling space for both, with the same budget, and report what fraction of the device's measured matrix-multiply rate each one reaches, because matched authorship is a weaker condition than matched efficiency and only the second identifies the algorithm. At the head width where the crossover lives no implementation available to us — the vendor library, our own kernel, or any configuration in the search — exceeds 44% of that rate, and the sparse kernel reaches 29%. The comparison is therefore between a better dense kernel and a worse sparse one, which bounds the direction of any residual bias but not its size: a dense kernel substantially closer to the machine's limit at this head width would remove the crossover, and we cannot rule one out. Separately, the sparse kernels select by argmax rounds or by bisection rather than by a radix or bitonic select, they are forward-only, and they hold the whole score row in registers, which caps them at $N \leq 1024$ and limits how many queries can be in flight at the largest sizes. What no kernel removes is the requirement to form and rank the full score matrix.

The learning study is secondary and bounded by its power. Five seeds per implementation gives a minimum attainable two-sided permutation p of 0.0079 against a first Holm threshold of 0.0083, so a first rejection requires one implementation's seeds to lie entirely above the other's. Resolving the effect the primary comparison suggests would need roughly 45 seeds per implementation, or 70 at the family-corrected level, from a normal-approximation formula that guides order of magnitude rather than describing the exact test we run. That was a budget allocation and not an unaffordable experiment: the 60-run study consumed 31.9 GPU-hours and a properly powered primary comparison would have cost about 37.9 more. Its positive controls do not isolate the learned channel, for reasons given in Section 6, and one of them sits at an agent count where the selection mechanism is degenerate. Readers should treat the study as evidence that the architecture is not inert, and as no evidence at all about the six comparisons it could not resolve.

Finally, the pre-score selectors of Section 5 demonstrate a cost structure and not a method. They attend to a different peer set than top-k does, so the comparison is of cost and not of quality, and we make no claim that spatial neighbours carry the information attention would have selected. Their selectors are also composed from library operators, so the constant we measure for them is an upper bound in the same way the composed sparse path's was before we fused it; how far a fused selector could fall is the obvious next measurement and one we did not make.

9 Conclusion

The efficiency case for restricting inter-agent attention to each agent's highest-scoring peers rests on an operation count, and the count is smaller than it looks. Because the selection reads the scores, every pairwise interaction has been evaluated before any is discarded, so only the aggregation is sparsifiable and no choice of sparsity removes more than half of attention's arithmetic. That bound is not a property of top-k but of what the selector costs: written as one accounting in which a rule is charged for deciding, it places every restriction mechanism on a single axis, and the mechanisms that obtain asymptotic savings are exactly those whose selectors are cheap.

Measuring what executes shows the bounded saving to be optimistic twice over. An implementation that applies the selection as a mask performs the dense aggregation anyway, so it executes no saving while a count credits it with a large one. An implementation that genuinely compacts the retained peers executes the saving and is slower regardless, because compaction replaces multiplication by zeros with the writing and re-reading of a gathered tensor, and at these sizes time follows bytes. Gathering is byte-neutral only when the compacted operand is no larger than the score row it avoids re-reading, which is a criterion that can be checked before the code is written.

Whether the remaining penalty belongs to the algorithm or to the tools is a question only kernels can answer, and writing them answered it in both directions. Most of the measured penalty is the composition of general-purpose operators; a fused kernel removes it, and at one retained peer the fused sparse path is faster than any dense implementation we could obtain, including a search over a hundred tilings of a dense kernel of our own. That is the whole of the positive result. It holds at one retained peer, where the softmax is identically one and nothing is being weighted; it holds only at the head widths where no implementation we have reaches half the device's arithmetic rate, and disappears where the vendor library does; and it is

gone by four retained peers. At the sparsity this literature uses, the fastest sparse implementation we could write is more than an order of magnitude slower than dense attention.

The constructive half fares no better, and fails in a way we did not anticipate. A selector that fixes the retained set before any score exists is genuinely unbound by the ceiling, and the two we measured reduce the operation count by up to two orders of magnitude. Neither is faster. One of them ranks a pairwise matrix of its own and so reproduces the cost it was introduced to avoid, which is the failure the accounting predicts once the selector is charged in the right currency. The other does not, and still loses — and it loses even with its selector set aside and only the attention over the already-chosen peers timed. That stage's best case anywhere is fifteen per cent below dense attention, at a configuration whose operation count promises a factor of 132. The arithmetic falls by two orders of magnitude and the time barely moves, because the gathered operand has lost the shape the hardware multiplies quickly.

That is the finding we would put in front of a designer. An operation count prices work in operations, and on this hardware, at these sizes, the price is set by the shape the work is executed in. A successor method has to answer for what its selector costs, for whether it reaches its decision without materialising the structure it meant to avoid, and for whether what it leaves behind can still be executed as a dense block. Only the first is visible in a count. The third is why block-level selection succeeds at a hundred thousand tokens and per-pair selection does not succeed at a few hundred agents: a selected block is still a matrix multiply, and a handful of gathered peers is not.

Broader Impact Statement

This work is a measurement and correction study of a computational-efficiency claim. It introduces no new capability and no new data. Its intended effect is to reduce wasted compute in the design of multi-agent communication architectures by discouraging optimisation against an operation count that does not predict runtime.

References

Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. *International Conference on Machine Learning (ICML)*, pp. 22–31, 2017. URL https://proceedings.mlr.press/v70/achiam17a.html.

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. URL https://arxiv.org/abs/2108.13264.

Iz Beltagy, Matthew E. Peters, and Arman Cohan. Longformer: The long-document Transformer. *arXiv preprint*, 2020. URL https://arxiv.org/abs/2004.05150.

Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, David Belanger, Lucy Colwell, and Adrian Weller. Rethinking attention with Performers. *International Conference on Learning Representations (ICLR)*, 2021. URL https://arxiv.org/abs/2009.14794.

Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-Awareness. *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/hash/67d57c32e20fd0a7a302cb81d36e40d5-Abstract-Conference.html.

Abhishek Das, Théophile Gervet, Joshua Romoff, Dhruv Batra, Devi Parikh, Michael Rabbat, and Joelle Pineau. TarMAC: Targeted multi-agent communication. *International Conference on Machine Learning (ICML)*, 2019. URL https://arxiv.org/abs/1810.11187.

William Fedus, Barret Zoph, and Noam Shazeer. Switch Transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022. URL https://jmlr.org/papers/v23/21-0998.html.

Ankit Gupta, Guy Dar, Shaya Goodman, David Ciprut, and Jonathan Berant. Memory-efficient Transformers via top-k attention. In *Proceedings of the Second Workshop on Simple and Efficient Natural Language Processing (SustaiNLP)*, pp. 39–52. Association for Computational Linguistics, November 2021. doi: 10.18653/v1/2021.sustainlp-1.5. URL https://aclanthology.org/2021.sustainlp-1.5/.

Mohammed Hamdan, Fares Ghaleb, Ahmed Bali, and Mohamed Cheriet. MARL-IoTP: Heterogeneous multi-agent learning for perception-aware edge orchestration. In *Fifth International Conference on Pattern Recognition and Artificial Intelligence (PRAI)*, 2026. doi: 10.2139/ssrn.6517702. URL https://ssrn.com/abstract=6517702. Accepted.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with Gumbel-Softmax. *International Conference on Learning Representations (ICLR)*, 2017. URL https://arxiv.org/abs/1611.01144.

Jiechuan Jiang and Zongqing Lu. Learning attentional communication for multi-agent cooperation. *Advances in Neural Information Processing Systems (NeurIPS)*, 2018. URL https://arxiv.org/abs/1805.07733.

Jiechuan Jiang, Chen Dun, Tiejun Huang, and Zongqing Lu. Graph convolutional reinforcement learning. *International Conference on Learning Representations (ICLR)*, 2020. URL https://arxiv.org/abs/1810.09202.

Daewoo Kim, Sangwoo Moon, David Hostallero, Wan Ju Kang, Taeyoung Lee, Kyunghwan Son, and Yung Yi. Learning to schedule communication in multi-agent reinforcement learning. In *International Conference on Learning Representations (ICLR)*, 2019. URL https://openreview.net/forum?id=SJxu5iR9KQ.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient Transformer. *International Conference on Learning Representations (ICLR)*, 2020. URL https://arxiv.org/abs/2001.04451.

Xunhao Lai, Weiqi Xu, Yufeng Yang, Qiaorui Chen, Yang Xu, Lunbin Zeng, Xiaolong Li, Haohai Sun, Haichao Zhu, Vito Zhang, Jinkai Hu, Jiayao Li, Rui Gao, Zekun Li, Songquan Zhu, Jingkai Zhou, and Pengyu Zhao. MiniMax sparse attention. *arXiv preprint*, 2026. doi: 10.48550/arXiv.2606.13392. URL https://arxiv.org/abs/2606.13392.

Yen-Cheng Liu, Junjiao Tian, Chih-Yao Ma, Nathan Glaser, Chia-Wen Kuo, and Zsolt Kira. Who2com: Collaborative perception via learnable handshake communication. In *IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6876–6883, 2020a. doi: 10.1109/ICRA40945.2020.9197364.

Yong Liu, Weixun Wang, Yujing Hu, Jianye Hao, Xingguo Chen, and Yang Gao. Multi-agent game abstraction via graph attention neural network. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 7211–7218, 2020b. doi: 10.1609/aaai.v34i05.6211.

André F. T. Martins and Ramón Fernandez Astudillo. From softmax to sparsemax: A sparse model of attention and multi-label classification. *International Conference on Machine Learning (ICML)*, 2016. URL https://arxiv.org/abs/1602.02068.

Yaru Niu, Rohan R. Paleja, and Matthew C. Gombolay. Multi-agent graph-attention communication and teaming. In *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems (AAMAS)*, pp. 964–973, 2021. URL https://www.ifaamas.org/Proceedings/aamas2021/pdfs/p964.pdf.

Georgios Papoudakis, Filippos Christianos, Lukas Schäfer, and Stefano V. Albrecht. Benchmarking multi-agent deep reinforcement learning algorithms in cooperative tasks. *Advances in Neural Information Processing Systems Datasets and Benchmarks Track (NeurIPS)*, 2021. URL https://arxiv.org/abs/2006.07869.

Ben Peters, Vlad Niculae, and André F. T. Martins. Sparse sequence-to-sequence models. *Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 1504–1519, 2019. doi: 10.18653/v1/P19-1146. URL https://aclanthology.org/P19-1146/.

Markus N. Rabe and Charles Staats. Self-attention does not need $O(n^2)$ memory. *arXiv preprint*, 2021. URL https://arxiv.org/abs/2112.05682.

Aurko Roy, Mohammad Saffar, Ashish Vaswani, and David Grangier. Efficient content-based sparse attention with Routing Transformers. *Transactions of the Association for Computational Linguistics (TACL)*, 9: 53–68, 2021. doi: 10.1162/tacl_a_00353. URL https://aclanthology.org/2021.tacl-1.4/.

Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *International Conference on Learning Representations (ICLR)*, 2017. URL https://arxiv.org/abs/1701.06538.

Amanpreet Singh, Tushar Jain, and Sainbayar Sukhbaatar. Learning when to communicate at scale in multiagent cooperative and competitive tasks. *International Conference on Learning Representations (ICLR)*, 2019. URL https://arxiv.org/abs/1812.09755.

Adam Stooke, Joshua Achiam, and Pieter Abbeel. Responsive safety in reinforcement learning by PID Lagrangian methods. *International Conference on Machine Learning (ICML)*, pp. 9133–9143, 2020. URL https://proceedings.mlr.press/v119/stooke20a.html.

Sainbayar Sukhbaatar, Arthur Szlam, and Rob Fergus. Learning multiagent communication with backpropagation. *Advances in Neural Information Processing Systems (NeurIPS)*, 2016. URL https://arxiv.org/abs/1605.07736.

Chuangchuang Sun, Macheng Shen, and Jonathan P. How. Scaling up multiagent reinforcement learning for robotic systems: Learn an adaptive sparse communication graph. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 11755–11762, 2020. doi: 10.1109/IROS45743.2020.9341303. URL https://arxiv.org/abs/2003.01040.

J. K. Terry, Benjamin Black, Nathaniel Grammel, Mario Jayakumar, Ananth Hari, Ryan Sullivan, Luis Santos, Clemens Dieffendahl, Caroline Horsch, Rodrigo Perez-Vicente, Niall L. Williams, Yashas Lokesh, and Praveen Ravi. PettingZoo: Gym for multi-agent reinforcement learning. *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. URL https://arxiv.org/abs/2009.14471.

Muning Wen, Jakub Grudzien Kuba, Runji Lin, Weinan Zhang, Ying Wen, Jun Wang, and Yaodong Yang. Multi-agent reinforcement learning is a sequence modeling problem. *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. URL https://arxiv.org/abs/2205.14953.

Samuel Williams, Andrew Waterman, and David Patterson. Roofline: An insightful visual performance model for multicore architectures. *Communications of the ACM*, 52(4):65–76, 2009. doi: 10.1145/1498765.1498785. URL https://doi.org/10.1145/1498765.1498785.

Yaodong Yang, Rui Luo, Minne Li, Ming Zhou, Weinan Zhang, and Jun Wang. Mean field multi-agent reinforcement learning. *International Conference on Machine Learning (ICML)*, 2018. URL https://arxiv.org/abs/1802.05438.

Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of PPO in cooperative, multi-agent games. *Advances in Neural Information Processing Systems Datasets and Benchmarks Track (NeurIPS)*, 2022. URL https://arxiv.org/abs/2103.01955.

Jingyang Yuan, Huazuo Gao, Damai Dai, Junyu Luo, Liang Zhao, Zhengyan Zhang, Zhenda Xie, Y. X. Wei, Lean Wang, Zhiping Xiao, Yuqing Wang, Chong Ruan, Ming Zhang, Wenfeng Liang, and Wangding Zeng. Native sparse attention: Hardware-aligned and natively trainable sparse attention. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 23078–23097. Association for Computational Linguistics, 2025. URL https://aclanthology.org/2025.acl-long.1126/.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, and Amr Ahmed. Big Bird: Transformers for longer sequences. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. URL https://arxiv.org/abs/2007.14062.

A Additional benchmark results

A.1 The full parameter grid

Table 10 gives the best-over-implementations sparse latency divided by the best-over-implementations dense latency, across head width and across batch, at each agent count and at the most favourable sparsity available. Head width is swept to 512 and batch from 32 to 1024. The largest batch we attempted, 4096 at 512 agents, could not be measured: the score matrix alone runs to several gigabytes and the device is shared, so that configuration is absent.

Table 10: Best sparse divided by best dense, over head width (upper block) and batch (lower block). Values below one would indicate sparsity winning.

head width d	N=96	N=192	N=512
16	0.66	0.71	0.74
32	0.51	0.69	0.62
64	0.87	1.32	2.15
128	1.38	2.17	1.88
256	2.10	2.07	2.11
512	1.66	1.72	2.18

batch B	N=96	N=192	N=512
32	0.55	0.65	0.57
1024	0.55	0.75	0.72

A.2 Dispersion behind the headline numbers

The primary statistic is the minimum over interleaved samples, on the modelling assumption that contention can only add time. That statistic is trustworthy only if the underlying sample was not wildly dispersed, so the harness records the median, the interquartile range and the spread of per-run medians for every configuration, and the released artifacts carry all of them. Two properties of this host limit what any of it can mean. Both GPUs carried between 30 and 80 GiB of other tenants' allocations and near-continuous utilisation throughout the campaign, and clocks could not be locked. We therefore report the spread of per-run medians beside every configuration rather than a confidence interval: a ratio of minima has no sampling distribution.

A.3 Drift control

The headline sweep was repeated in full on the same device, hours later and under different load from other tenants. Table 11 gives how far each agent count moved between the two runs, in absolute latency and in the ratio against the best dense implementation, which is the quantity every claim is stated in.

Table 11: Movement between two runs of the identical sweep. From 192 agents upward both the latencies and the ratios reproduce to about one per cent. At 96 they do not, by a wide margin, which is why no claim in this paper is read off an agent count below 192.

		latency $\lvert\Delta\rvert$ (%)		**ratio** $\lvert\Delta\rvert$ (%)	
N	configurations	median	max	median	max
96	35	24.1	381.7	61.2	64.2
192	35	0.4	8.5	1.3	7.0
384	35	0.5	4.5	0.4	4.8
512	35	0.1	6.7	0.1	6.9

From 192 agents upward the measurement is stable: median movement is under one per cent in latency and under half a per cent in the ratio, with the worst single configuration under eleven per cent. At 96 agents it is not stable at all — every implementation ran between 14% and 394% slower in the second run, and the fastest configurations in the first run had recorded inter-run spreads above 85% at the time. That is the signature of a launch-bound regime on a contended device rather than of anything about attention, and it is why the crossover of Section 4.3 is reported only from 192 agents upward even though the sweep measures smaller ones.

The repeat is on the same physical card, so it establishes stability across runs and hours, not independence from one device, and we were not able to obtain a second card free of other tenants. It covers the sweep of Section 4.2 and Section 4.3's figure; the tiling search of Table 3 was run once, so the crossover it reports carries the reproducibility of a single session rather than of a repeat. Measurements were taken on both cards of this host — the core sweeps, the search and the stage accounting on one, the head-width sweep and the pre-score measurements on the other — and no cross-device calibration is claimed, which is a further reason no figure from one is divided by a figure from the other.

B Implementation and measurement validation

B.1 Functional equivalence

Every implementation is checked against the reference at every configuration whose latency any released artifact reports: 158 combinations of agent count, head width and retained-peer count, 136 of them with $k < N - 1$ so that selection is actually exercised, over 1.25 million query rows in total. The check matters more than it looks. Exact top-k is discontinuous in the scores, so two implementations that accumulate the score product in different orders can rank a near-tied pair differently and aggregate over different peers, producing a large output difference from a rounding-level score difference. An earlier version of our per-query fused kernel computed the score row as a reduction instead of through the matrix-multiply units and disagreed with the reference at a handful of configurations for exactly that reason; the kernels reported here use the same product as the reference.

With that fixed, every implementation agrees with the reference to `fp32` rounding — maximum deviation 3.2×10^{-6}, and zero for the two implementations that share the reference's operator sequence exactly — with one attributable exception. The fused kernel that selects by threshold retains every peer at or above the k-th largest score, so an exact tie at that boundary retains $k{+}1$ peers where a rank-based selection retains k. Four query rows in 1.25 million have such a tie, at three of the 158 configurations, and those four rows are the only place any implementation differs from the reference by more than rounding. The check is run by `scripts/verify_all_configurations.py`, which classifies a tie divergence separately from a failure so that the distinction is in the artifact and not only in this paragraph.

B.2 What each implementation executes

The masked and gathered implementations compute the same function while executing different work, which is the distinction the paper turns on, so regression tests pin it. Maximum absolute deviation between the two paths is below 10^{-10} in `float64`. A FLOP counter attached to the running program reports identical totals for dense and masked — the counter scores matrix products, and masked issues the same two as dense — against a smaller total for gathered, the difference being exactly the aggregation term. Tracing every matrix product confirms that the gathered path issues no dense aggregation product and does issue the compacted one, and that every top-k variant still issues the full score product, which is assumption A2 made mechanical.

B.3 Which backend serves the fused dense baseline

A probe forces each scaled-dot-product backend in turn, at both dtypes and at three agent counts, under no mask, an additive float mask and a Boolean mask, and the profiler records which kernel the default dispatcher launches. The FlashAttention backend is rejected under any non-null mask in either form, and

in `fp32` under any input, so the library dense baseline runs the memory-efficient CUTLASS kernel. Forcing FlashAttention on the same unmasked `bf16` shape is faster than the kernel we do get, so a baseline able to reach it would widen rather than narrow the gap we report — which is part of why the dense baseline in this revision is the better of the library path and a kernel we wrote.

B.4 The host allocator control

Dense, masked and gathered each allocate and free several multi-MiB score matrices per forward. The default allocator returns those pages to the kernel and they are re-faulted on the next call, which at N=192 adds roughly 37,000 minor page faults per forward and inflates latency by up to 8.8×. The tax is proportional to the bytes of large temporaries each implementation churns, so it differs per implementation and does not cancel in a ratio; in an un-pinned run it inverted the ordering at one configuration. We raise the allocator's retention threshold so that freed temporaries are kept, and count minor faults per forward from the process's own resource usage across the timed region. The harness records the allocator environment, the thread counts, the affinity mask and the fault totals in each run's metadata, and the superseded un-pinned run is retained beside the pinned one.

B.5 Machine balance

Peak arithmetic rate is measured with a large matrix multiply and peak bandwidth with a large copy, in the same process as the measurements they normalise. That matters here more than it usually would: on this shared host the peak we measure varies between 53 and 77 TFLOP/s across sessions, depending on what else is running. Every fraction-of-peak figure in the paper is against the peak measured in the same process as the number it normalises, and is therefore an upper bound on the true efficiency rather than an estimate of it. Comparisons between two implementations measured in one process are unaffected; comparisons of a fraction across sections are not, and we make none. The copy source is written before it is read: an untouched allocation on this operating system is backed by the shared zero page, so a host-side copy from it re-reads one cache line and reports a bandwidth several times the machine's real figure, and an earlier version of this probe did exactly that: every CPU ridge point derived from it was too large by roughly a factor of six. Device work is also timed with device events rather than host wall-clock, since host timing around a sub-millisecond copy measures launch and synchronisation. The probe reports two ridge points per device, one with a cache-resident buffer and one with a buffer larger than the last-level cache, because the two differ by a factor of two on the host and a claim that holds for one need not hold for the other.

C Additional training analysis

C.1 Pre-registration chronology

The analysis plan was committed when eight of the forty runs in the pre-registered family had produced a final evaluation and before any of their returns had been inspected. Commit history establishes the ordering: the positive-control artifacts at 12:18, the plan at 12:56, and the remaining artifacts at 19:11 the same day. The plan has two commits, the second appending to its deviations log; the endpoint, comparisons, test, effect sizes, interval and correction are byte-identical to the pre-unblinding version. Timestamps establish ordering and nothing more. Data generation had demonstrably already begun.

One correction is logged against the released plan. It asserts that at most one comparison in the family can reach corrected significance. That is false: Holm is a step-down procedure, so once a first rejection is obtained its later thresholds are looser and further rejections remain possible. The manuscript states the corrected version; the deviation is logged against the released plan.

C.2 The remaining comparisons

Five further comparisons were registered and all are Holm-adjusted nulls. Two deserve a note. The comparison at twelve agents has the one sign opposite to its registered direction and carries the family's largest point estimate, and we set it aside on the ground that neither variant learns the task there. That ground was not

registered: it is a post-hoc exclusion of the largest observed effect, we have logged it as a deviation against the released plan, and a reader who rejects it should read the comparison as an under-powered null with a large point estimate, which is what the registered analysis returns either way. The evidence for the exclusion is this. A uniform-random policy scores -758.9 under a forty-episode evaluation, against -864.9 for the dense variant, which is worse, and -717.9 for the sparse variant, which is better but barely learning; the comparison is between a diverged run and a struggling one. Separately, for two comparisons the bootstrap interval excludes zero while the permutation test does not. The registration named the permutation test, so it governs; the disagreement is unsurprising at five seeds, where the interval is coarse, discrete and of uncertain coverage. We report both so that the estimated effect and the strength of evidence for it are both visible.

Descriptively, and supporting no claim: the budgeted variant meets its budget but not by the intended route, its gate collapsing to an expected support near one within the first tenth of training while the dual multiplier decays to zero; the entmax variant settles at a support of 1.64 of five peers; and attention entropy falls from 0.35 nats over five peers to 0.12 over two. The three sit on different supports and are reported only as an instrumentation check.

C.3 The partially observable environment

The variant modifies the standard cooperative task in one respect: a peer's relative-position entry is zeroed when the peer is farther than a fixed radius. Reward, action space, landmark observations, episode length and observation dimension are unchanged. Two properties limit what it can support. The mask is a zeroing rather than an explicit visibility flag, so a peer at relative position exactly zero is not distinguishable from an absent one; measured under a uniform random policy, this affects at most 0.15% of visible peers. And the visible fraction falls with the number of agents while the absolute number visible rises, because the world size is fixed, which is a difficulty confound that rules out across-agent-count return comparisons.

The communicating variants carry between 7.2% and 19.0% more trainable parameters than the communication-free baseline, since the attention module adds parameters the baseline has no analogue for. The positive controls therefore establish that the communicating architecture outperforms the baseline, not that the channel alone accounts for the difference.

D Literature audit

For each audited paper we read the full text, including appendices and the official supplement where one exists, searched it for seven temporal keywords, and recorded whether it makes a computational-efficiency or complexity claim about its mechanism, whether it reports any measured temporal quantity attributable to that mechanism, and the figure, table or sentence that settled the decision. A statement such as "training took a few days" does not qualify, since it is not attributable to the mechanism. Scope matters for at least one entry, whose affirmative verdict rests on a wall-clock figure in an appendix and would be negative on the main body alone. This is an audit of reporting practice in a small, deliberately selected set — the papers we ourselves relied on — and not a sample of either literature; a negative verdict means the argument rests on operation counts or asymptotics, not that it is wrong.

E Reproduction and provenance

The measurement campaign is training-free and completes in under an hour on one device. `scripts/run_revision_campaign.sh` regenerates every artifact in the order the manuscript reports them; `scripts/make_revision_tables.py` and `scripts/make_revision_figures.py` regenerate every table and figure from those artifacts, so no tabular number in the manuscript is transcribed by hand; and `scripts/check_paper_numbers.py` re-derives the numbers that appear in prose and fails on any disagreement.

Three provenance caveats. The hardware description and the aggregate provenance record were written before this project's environment was upgraded and describe a superseded software stack and a host that is

Table 12: The twelve audited papers, their efficiency claim, the kind of evidence it rests on, and whether any measured temporal quantity attributable to the mechanism appears anywhere in the paper or its supplement. A "no" means the argument rests on operation counts or asymptotics, not that it is wrong.

Paper	**Efficiency claim**	**Type**	**Measured time?**
Multi-agent communication and attention			
Das et al. (2019)	Qualitative bandwidth argument only	qualitative	no
Jiang & Lu (2018)	Communication is 'restricted by bandwidth . . .	agent/message counts	no
Jiang et al. (2020)	receiving a large amount of information . . .	asymptotic / qualitative	no
Singh et al. (2019)	continuous communication allows efficient . . .	message counts / convergence epochs	no
Sukhbaatar et al. (2016)	none explicit	—	n/a
Wen et al. (2022)	Sequence modelling 'reduces the complexity . . .	asymptotic	**yes**
Efficient attention and sparse mixture-of-experts			
Beltagy et al. (2020)	Sliding-window + global attention scales . . .	asymptotic	**yes**
Choromanski et al. (2021)	FAVOR+ gives linear rather than quadratic . . .	asymptotic	**yes**
Fedus et al. (2022)	Sparse routing increases parameters at . . .	FLOPs-matched	**yes**
Kitaev et al. (2020)	LSH attention reduces O(L2) to O(L log L)	asymptotic	**yes**
Shazeer et al. (2017)	1000x capacity increase at minor . . .	FLOPs + measured	**yes**
Zaheer et al. (2020)	reduces this quadratic dependency to linear'; . . .	asymptotic + memory	no

no longer available; both have been corrected, and the run-level provenance for the training variants lives in the per-run configuration files rather than in the aggregate record. The GPUs used for every measurement in this paper are shared with other tenants, so absolute latencies are not reproducible to better than the drift reported in Appendix A.3 and only ratios between implementations timed in the same interleaved sweep should be compared. And the activation-memory measurement is reported from a run with the card otherwise free, since a shared-host repeat exhausts memory one agent count earlier.