

RAPPORT BDD (SUNDAY 01/02/2026) :

Share trajet is a site web where a user can play two roles the first one is to be a simple user or a passenger where he will search for a trajet in our site web by using the city name the depart and the destination and the date and the filters and situation and and by using our search function the user will get a number of resultants of what he wants or being in the second role which is a conductor where he will do the opposite so he will be the publisher of trajet in our site web and all of this will be possible if and only if we use a data base for our site web which we did using **PostgreSQL, PGadmin, docker** .

1_tables overview:

Users: Stores user account information.

1_UserID (PK): Unique identifier for each user.

2_name, first_name: User's full name.

3_email: Login email.

4_Password: Hashed password.

5_preferences: User preferences (e.g., notifications, language).

6_role: User role (e.g., driver, passenger).

7_profile_picture: Profile image URL/path.

8_bio: Short biography or description.

User_document: Stores documents uploaded by users for verification (e.g., ID, license).

1_UserDocument (PK): Document ID.

2_user (FK): References Users(UserID).

3_file_path: Path to the document file.

4_uploaded_at: Timestamp of upload.

5_verified: Boolean indicating if the document is verified.

6_verified_by (FK): References Users(UserID) (admin who verified).

7_verified_at: Timestamp of verification.

Trajets: Stores trip information.

1_TrajetID (PK): Unique trip ID.

2_ville_depart, ville_arrivee: Start and destination cities.

3_date, heure_depart: Departure date and time.

4_nbr_places: Number of available seats.

5_price: Total price for the trip.

6_distance: Trip distance in km.

7_is_confort: Boolean for comfort option.

8_pause_required: Boolean for rest stops.

9_price_platform: Platform fee.

10_price_driver: Driver's earnings.

Reservation: Stores reservations made by passengers.

1_ReservationID (PK): Unique reservation ID.

2_nbr_places: Number of seats reserved.

3_status: Status (e.g., pending, confirmed, cancelled).

4_created_at, approved_at, cancelled_at: Timestamps for actions.

Rating

Stores ratings and comments left by users after a trip.

RatingID (PK): Unique rating ID.

1_comment: Text comment.

2_reservation (FK): References Reservation(ReservationID).

3_note: Numerical rating (e.g., 1–5).

Messagerie: Stores messages between users.

1_MessageID (PK): Unique message ID.

2_sender (FK): References Users(UserID).

3_reciever (FK): References Users(UserID).

4_text: Message content.

5_media: Media file path (if any).

6_media_type: Type of media (image, video, etc.).

7_is_Read: Boolean indicating if the message has been read.

8_created_at: Timestamp of message.

Notifications: Stores system notifications.

1_NotificationID (PK): Unique notification ID.

2_recipient, sender (FK): References Users(UserID).

3_type: Notification type (e.g., booking, reminder).

4_content: Notification content.

5_RelatedID: ID of related entity (e.g., ReservationID).

6_OnModel: Model name of the related entity.

7_IsRead: Boolean indicating if read.

8_created_at: Timestamp.

refresh_tokens: Stores refresh tokens for authentication.

1_refresh_token_id (PK): Unique token ID.

2_TokenHash: Hashed token.

3_created_at, expires_at: Timestamps.

4_revoked: Boolean indicating if token is revoked.

Preferences: Stores possible user preferences.

1_PreferenceID (PK): Unique preference ID.

2_PreferenceName: Name of the preference (e.g., “email_notifications”).

Roles: Stores possible user roles.

1_RoleID (PK): Unique role ID.

2_RoleName: Name of the role (e.g., “admin”, “driver”, “passenger”).

2_Relationships

The diagram also includes junction/link tables (not explicitly named but implied by relationships):

=>Has (**Users** ↔ **Preferences**): Many-to-many relationship between users and preferences.

=>Has (**Users** ↔ **Roles**): Many-to-many relationship between users and roles.

=>Post (**Users** ↔ **Trajets**): One user (driver) can post many trips; a trip is posted by one user.

=>Reserve (**Users** ↔ **Reservation**): A user (passenger) can make many reservations; a reservation belongs to one user.

=>give_access (**Reservation** ↔ **Trajets**): A reservation gives access to a trip (many-to-one).

=>has (**Reservation ↔ Rating**): A reservation can have one rating (optional).

=>give (**Users ↔ Rating**): A user can give many ratings; a rating is given by one user.

=>declenche (**Users ↔ Notifications**): A user can trigger many notifications.

=>Send/Receive (**Users ↔ Messagerie**): Users can send and receive many messages.

3_Relationship table:

Relationship	Type	Description
Users ↔ user_document	One-to-Many	A user can upload many documents; a document belongs to one user.
Users ↔ Trajets	One-to-Many	A user (driver) can post many trips; a trip belongs to one driver.
Users ↔ Reservation	One-to-Many	A user (passenger) can make many reservations; a reservation belongs to one user.
Users ↔ Rating	One-to-Many	A user can give many ratings; a rating belongs to one user.
Users ↔ Messagerie	One-to-Many (sender/receiver)	A user can send/receive many messages.
Users ↔ Notifications	One-to-Many (recipient/sender)	A user can send/receive many notifications.

Trajets ↔ Reservation	One-to-Many	A trip can have many reservations; a reservation is for one trip.
Reservation ↔ Rating	One-to-One	A reservation can have one rating (optional).
Users ↔ Preferences	Many-to-Many	A user can have many preferences; a preference can be chosen by many users.
Users ↔ Roles	Many-to-Many	A user can have many roles; a role can be assigned to many users.

SAIDI_MAHMOUD_2CP7