

CH-230-A

# **Programming in C and C++**

C/C++

## **Tutorial 12**

Dr. Kinga Lipskoch

Fall 2021

## Operator Overloading (1)

- ▶ Overloaded operators allow a different syntax for function/method calls
- ▶ Operator overloading allows the programmer to use language operators for user defined data type. For example

```
1  Car first, second, third;  
2  ...  
3  third = first + second;
```

what this could mean is left to the programmer

- ▶ New operators cannot be introduced

## Operator Overloading (2)

- ▶ It is possible to overload operators only for user defined data types
  - ▶ Thus it is not possible to alter the meaning of the `+` operator between `ints`, `floats`, and so on
    - ▶ C code should compile with C++ compilers without changing its functionality
- ▶ Overloading an operator should help the reader of the program and not the programmer
  - ▶ You can define an operator `+` between two instances of a salary class which subtracts them
  - ▶ Whether this makes sense or not is up to your design choices and skills

## Sorting Students by Grade

### With overloaded operators

```
1 Student *list;  
2 ...  
3 for (i = ...)   
4     if (list[i] > list[j]) {  
5         tmp = list[i];  
6         list[i] = list[j];  
7         list[j] = tmp;  
8     }  
9 ...
```

### Without overloaded operators

```
1 Student *list;  
2 ...  
3 for (i = ...) {  
4     if (list[i].getGrade() >  
5         list[j].getGrade()) {  
6         ...  
7     }  
8 }  
9 ...
```

Which one is “cleaner”?

## Using/Calling Operators

- ▶ From the previous example it should be clear that no magic things are happening, but just a compact (and clear) syntax for method calls can be used
- ▶ Whenever the compiler finds an operator involving user defined types, it verifies if it is possible to find a proper definition
- ▶ Operators are **overloaded** as there can be more than just one version: + between two instances of car, + between an instance of car and an instance of bike, and so on
- ▶ Types help in determining the version which should be called

## Operators, Methods or friend Functions

- ▶ To carry out their task operators need to access class data
- ▶ Then, they have to be either methods or friend functions
  - ▶ There are some guidelines  
`Student3.h`   `Student3.cpp`   `studentoperator.cpp`
- ▶ It is possible to overload both unary and binary operators

## Overloading the = Operator

- ▶ Overloading the = operator is fundamental if your class deals with pointers as properties
- ▶ Language provided = operator performs field to field copy
- ▶ If the class has pointers, different instances end up with sharing the same memory
  - ▶ Also, there could be memory leaks  
`charbuffer.h`    `charbuffer.cpp`
- ▶ The operator = must be a method and must return a reference to the class
  - ▶ This allows iterated assignments (`a=b=c;`)

# Overloadable Operators

| Unary Operators   | Binary Operators   |
|---|--|
| + - & ! ~<br>++ --<br>(both prefix and postfix)<br>[ ] -> ( ) | + - * / % ^ &   <<<br>>> += -= *= /= %= ^=<br>&=  = >>= <<= == !=<br>< > <= >= &&    ->* |

new and delete can be overloaded as well



## What Should Operators Return?

- ▶ A reference, if they modify the involved argument(s) (like `=`, `+=`, etc.)
- ▶ Return a reference to the modified object, usually by using `this`
- ▶ A new instance if they do not modify arguments, but rather use them to produce new information (like most binary operators: `+`, `-`, etc.)
- ▶ A `bool` if it is a boolean operator

## Member or friend?

The following table proposed in the textbook can be taken as a general guideline

| Operator                        | Use              |
|---------------------------------|------------------|
| Unary operators                 | Member           |
| = ( ) [ ] -> ->*                | Must be member   |
| += -= /= *= ^= &=  = %= >>= <<= | Member           |
| Other binary operators          | Friend or member |

`complex.h`      `complex.cpp`      `testcomplex2.cpp`

## Overloading << and >>

- For example for the Complex class:

```
1      friend ostream& operator<<(ostream& out,  
    const Complex &z)  
2  
3      friend istream& operator>>(istream& in,  
    Complex &z)
```

# Polymorphism

- ▶ The last cornerstone of OOP has no correspondence in non-OOP languages
- ▶ It deals with writing code which can correctly operate even with data types unknown at compile time
- ▶ Just one additional keyword, `virtual`, which offers a wide range of applications

## Starting from Upcasting

- ▶ Upcasting means that a derived class can be used wherever an ancestor class is expected
  - ▶ This because the interface of the parent is inherited
- ▶ A derived class can redefine a method, i.e., it can provide a new implementation
- ▶ `randomnonvirtual.cpp`
- ▶ `randomvirtual.cpp`

## What Happens?

- ▶ In the first example the redefinition of the method was not perceived, while in the second “the expected” behavior was observed
- ▶ It should be evident that at compile time there is not enough information to bind the method call to the right method to execute
  - ▶ This is called [late binding](#)

## The virtual Keyword

- ▶ When a method is declared as `virtual`, late binding is requested
- ▶ `virtual` should be specified just in the declaration of the base class
- ▶ Late binding is inherited from there on
  - ▶ The redefinition of virtual methods is called **overriding**
- ▶ When dealing with virtual methods, each object carries some sort of info to make its identification possible at runtime

## virtual and Pointers

- ▶ Be aware: the late binding feature works only if you deal with pointers to instances, and not if you directly work with instances
  - ▶ And of course, also with C++ references
- ▶ When passing objects to methods/functions, using C++ references speeds up parameters passing and enables polymorphism



## The Added Value of Polymorphism

- ▶ By mean of polymorphism it is possible to write general purpose code
  - ▶ When possible, general code always deals with base classes, and calls virtual methods
- ▶ Then, the code will work even with later introduced data types (new classes)

## What Should be virtual?

- ▶ The decision is up to the designer
  - ▶ Some languages (like Java) make all methods virtual
- ▶ Virtual method calls introduce overhead
  - ▶ Run time binding
  - ▶ Making always every method virtual is poor design
- ▶ The choice is done at the base class level
  - ▶ If a method is not virtual in the base class, it cannot be made virtual in a derived class

## How Does Polymorphism Work?

- ▶ In order to correctly manage it, it is useful to know how polymorphism is implemented
  - ▶ For every class with virtual methods, a table is created; the table holds the address of the virtual methods (VTABLE)
  - ▶ In addition, a pointer to this table is stored inside the class; this pointer is invisible (VPTR)
  - ▶ When a virtual method is called, the pointer is used to access the table, and then from the table the address of the function is read
  - ▶ As each class with virtual elements is shaped this way, the compiler can insert the code to resolve the calls without knowing the type
  - ▶ The intermediate indirection through VTABLE is the reason for the slower performance of virtual method calls

## Calls Through the Virtual Table

```
1 class Base {
2     public:
3         virtual void
4             method()=0;
5         // VPTR INSERTED
6 };
7 class Derived
8     : public Base {
9     public:
10         void method() { };
11         // VPTR INSERTED
12 };
13 ...
14 Base *a= new Derived;
15 a->method();
```

