





**Universität  
Zürich<sup>UZH</sup>**

Universität Zürich, Philosophische Fakultät  
Zentralbibliothek Zürich, MAS Bibliotheks- und  
Informationswissenschaft

---

## **Machine indexing of institutional repositories: indexing Edoc with Annif as proof of concept**

Dr. Maximilian G. Hindermann   
Spalentorweg 46, CH-4051 Basel  
+41 79 277 0612  
maximilian.hindermann@gmail.com

Silke Bellanger, Referentin 

Dr. Andreas Ledl, Ko-Referent 

9. April 2021

## **Abstract**

The potential of some institutional repositories is hampered by the lack of subject indexing. I argue that this situation can be amended with the help of machine indexing. As proof of concept I show that Edoc — the University of Basel’s repository — can be successfully indexed using the Annif-client Python library. In order to do so, I assess the performance of hundreds of Annif configurations in assigning subject terms to a sample data set against a gold standard constructed from cleaned and reconciled author keywords.

*"Never spend 6 minutes doing something by hand when you can spend 6 hours failing to automate it."*

Zhuowei Zhang

## Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	Problem statement and goal . . . . .	5
1.2	Method . . . . .	5
<b>2</b>	<b>Edoc data</b>	<b>6</b>
2.1	Edoc data extraction . . . . .	6
2.2	Data description . . . . .	6
<b>3</b>	<b>Sample data set</b>	<b>7</b>
3.1	Selection . . . . .	7
3.2	Construction . . . . .	7
3.3	Analysis . . . . .	9
<b>4</b>	<b>Machine indexing</b>	<b>9</b>
4.1	Annif . . . . .	9
4.2	Implementation . . . . .	12
<b>5</b>	<b>Gold standard</b>	<b>13</b>
5.1	Definition . . . . .	13
5.2	Extract and clean keywords . . . . .	14
5.3	Analysis . . . . .	15
5.4	Reconciliation . . . . .	17
5.5	Discussion . . . . .	19
<b>6</b>	<b>Assessment</b>	<b>22</b>
6.1	Precision, recall, F1-score . . . . .	22
6.2	Creating the data foundation . . . . .	23
6.3	General results . . . . .	24
6.4	Departmental results . . . . .	30
<b>7</b>	<b>Conclusion and outlook</b>	<b>33</b>
	<b>Bibliography</b>	<b>34</b>
<b>8</b>	<b>Appendix</b>	<b>36</b>

# 1 Introduction

In this section, the problem and goal of this project are stated and the employed methodology is outlined.

## 1.1 Problem statement and goal

Edoc is the institutional repository of the University of Basel. It runs on the EPrints 3 document management system (see <https://github.com/eprints/eprints>). Edoc was conceived in 2009 as repository for electronic dissertations and grew in scope when the University of Basel adapted its first open access policy in 2013. In early 2021, Edoc contained roughly 68'000 items, most of them journal articles without full text support. Even though descriptive and administrative metadata are collected for each item, this does not include subject terms. The lack of subject indexing hampers the repository's usability and potential with respect to the topic-based monitoring of research output and, to a lesser extent, information retrieval. The goal of this project is to remedy this situation with the help of machine indexing.

## 1.2 Method

The proof of the pudding is in the creation of a software prototype. The prototype must take a subset of the data from Edoc as input and provide index terms for each item in this subset as output. In order to fulfill this aim we can distinguish five steps corresponding to sections 2 to 6 below:

1. Understand the Edoc data.
2. Select and construct an Edoc sample data set.
3. Use Annif to index the items in the Edoc sample data set.
4. Construct a gold standard from the keywords.
5. Assess the quality of the output based on the gold standard.

The focus of this project lies primarily on practical implementation of the prototype although care is taken to spell out design decisions in as much detail as is needed. All code written and data generated during the process of implementing the prototype is available at <https://github.com/MHindermann/mas> and comes in three categories:

- Text and images available at `/text/`
- Codebase and data available at `/files/`
- Documentation available at `/docs/`

## 2 Edoc data

In this section, I will describe the Edoc data and how it was extracted.

### 2.1 Edoc data extraction

Even though Edoc is a public server, its database does not have a web-ready API. In addition, since Edoc is a production server, its underlying database cannot be used directly on pain of disturbing the provided services. The data hence needs to be extracted from Edoc in order to work with it. This could for example be achieved by cloning the database of the server and running it on a local machine. However, this route was not available due to the limited resources of the responsible co-workers. I thus employed a workaround: Edoc has a built-in advanced search tool where the results can be exported. Even though it is not possible to extract all database items by default, only one of the many available search fields has to be filled in. The complete database can hence be extracted by only filling in the `date` field and using a sufficiently permissive time period such as 1940 to 2020 since the oldest record in the database was published in 1942. On January 21 2021, this query yielded 68'345 results. These results were then exported as a 326 MB JSON file called `1942-2020.json`. `1942-2020.json` has two drawbacks. First, the maximum file size on GitHub is 100 MB. And second, `1942-2020.json` is too big to be handled by standard editors requiring special editors. For these reasons `1942-2020.json` was split into smaller files that are easier handled and can be uploaded to GitHub. For this `Utility.split_json` was used yielding 14 files of size 20 MB or less containing 5000 or fewer entries each. These files are called `raw_master_{year}.json` and saved under `/raw/`.

### 2.2 Data description

Each Edoc item has 43 main data fields. Most of these data fields belong to the class of descriptive metadata. The data entry for an item's descriptive metadata is undertaken by the person who uploads the item which is (in most cases) one of the item's authors. Note that an item is first uploaded to the University of Basel's research database (<https://www.forschdb2.unibas.ch>) before being automatically fed into Edoc. There are explicit rules on how to enter the data as summarized in the user manual (Universität Basel, n.d.). However, there is no (or at least no systematic) manual or automatic validation of the entered data. This means that some data fields are very heterogenous and require further parsing (see section "Gold standard"). The

data fields that are of interest to the project at hand are discussed in more detail in section “Sample data set” below.

### **3 Sample data set**

In this section, I will explain how the sample data set was selected and constructed. “Selection” hereby means the task of specifying a subset of the Edoc data; by “construction” I mean the task of implementing this selection.

#### **3.1 Selection**

There are a number of constraints for selecting the sample data set pertaining to an items’s text, evaluability, and the data set’s scope.

The first constraint stems from Annif, the machine indexing framework that will be used (see section “Machine indexing” for more details). Put simply, machine indexing assigns index terms to a text based on training data. The training data consists of a set of texts, a vocabulary, and function from vocabulary to texts. In this context we mean by “text” a sequence of words in a natural language and by “vocabulary” a set of words. Intuitively, the training data consists of pairs of text and subject terms that meet some standard. The training data and the vocabulary are already supplied by Annif, we only need to provide a text for each item that we want to be assigned index terms. Therefore, we only select items with text.

The second constraint is that we must be able to evaluate the quality of the index terms assigned by Annif to any item in the sample data set.

The third and final constraint takes into account the possibility of having to extend the prototype to the complete Edoc data. On the one hand, the sample data set should be small enough to allow for easy handling and rapid iteration. On the other hand, the sample data set should not be trivial but reflect the quirks and inadequacies of the complete dataset. In other words, we are looking for an abstraction rather than an idealization in the sense of Stokhof and van Lambalgen (2011).

#### **3.2 Construction**

The first constraint is that each item in the sample data set needs to have a text. Intuitively, this text could consist of a title, an abstract, or even a full text, or any combination of the above. Similar to manual indexing, having

more information (that is, longer texts) usually implies a higher indexing quality in machine indexing. However, this assumption needs to be confirmed empirically for the given machine indexing framework and data set. If indeed confirmed, it might be advisable only to index items that have a certain minimal text length. Therefore, in order to construct the sample data set, we require each item to have a non-empty value in the data fields **title**, **abstract**, and **id\_number** as proxy to retrieve a full text remotely. Note that even more context could be provided by taking into account other data fields such as **type**, **publication** or **department**. Especially the latter might be valuable when disambiguating homonymous or polysemous words. For example, consider the item <https://edoc.unibas.ch/id/eprint/76510> which is titled “Blacking Out.” Without further context, this title could refer (amongst others) to a physiological phenomenon, a sudden loss of electricity, or a measure taken in wartime. Knowing that the item was published by a researcher employed by the Faculty of Business and Economics (and not, say, by the Faculty of Medicine) gives us reason to exclude the first meaning. However, this idea cannot be implemented with the out of the box instance of Annif employed in this chapter (see section “Machine indexing”).

The second constraint is that the index terms assigned to each item in the sample data set must be assessable. How the assessment is conducted in detail is discussed in section “Assessment”. For now, it is sufficient to say that we require a standard against which we can evaluate the assigned index terms. By “standard” I mean that given a vocabulary of index terms and our sample data set, for every item in the sample data set, there is an approved subset of the vocabulary. The production of a standard from scratch is of course is very costly since a person, usually highly skilled in a certain academic domain, must assign and/or approve each item’s index terms. For this reason we try to avoid having to produce a standard. One way of doing so is by requiring items in the sample data set to have non-empty **keywords** data field. The caveats of this approach are discussed in section “Assessment”.

Taking into account the third constraint simply means that we do not employ any further restrictions. We can hence construct the Edoc sample data set by choosing exactly those items from **/raw/** which have non-empty data fields **title**, **abstract**, **id\_number**, and **keywords**. We do so by calling `Data.select_from_file` iteratively for all files in **/raw/** using the aforementioned data fields as parameters. The resulting file is saved in **/sample/** as `sample_master.json`.



### 3.3 Analysis

Of the 68'345 items in `/raw/`, all have a title (non-empty `title` data field), a little more than half of the items have an abstract (37'381 items with non-empty `abstract` data field), roughly half of the items have an ID (35'355 items with non-empty `id_number` data field),<sup>1</sup> and less than 10% of the items have keywords (6'660 items with non-empty `keywords` data field). The Edoc sample data set requires all the above data fields to be non-empty; `/sample/sample_master.json` has 4'111 items and hence constitutes 6% of the raw data.

In order to determine how well the sample data set represents the raw Edoc data, a one-sample  $\chi^2$  goodness of fit test was conducted on each selection data field (following Parke 2013, chap. 1). The results indicate that the sample data proportions of items are significantly different from the raw Edoc data per department (see Figure 1 for more details).

The sample data set is hence not representative of the raw Edoc data. This is not surprising since its construction is strongly biased. This bias has the effect that the sample data set is significantly skewed towards English journal publications in the sciences, medicine and economics from the 21st century (again, this is shown by a one-sample  $\chi^2$  goodness of fit test, see Figure 2 for more details). The upshot of this analysis is that the humanities are underrepresented in the sample data set. Therefore, any results with respect to the quality of machine indexing discussed below might not be applicable to the humanities.

## 4 Machine indexing

In this section, I will briefly introduce Annif and how indexing with Annif was implemented. For a general overview concerning machine indexing, see Golub (2019).

### 4.1 Annif

Annif (Suominen et al. 2021) is an open source multi-algorithm automated indexing tool developed at the Finnish National Library (see Suominen 2019 for an overview). Training a local Annif instance for machine indexing is

---

<sup>1</sup>Note that when using the facet by blank on `id_number` in OpenRefine, there are 57'153 matches; this is due to the fact that many items with an ID such as DOI have secondary or tertiary IDs such as ISI or PMID.




Figure 1: The sample data set ( $n = 4'111$ ) is not representative of the raw Edoc data per department. Data field **abstract**:  $\chi^2(df = 9) = 3'160.556$ ,  $p < 0.001$ ; data field **id\_number**:  $\chi^2(df = 9) = 4'209.0285$ ,  $p < 0.001$ ; data field **keywords**:  $\chi^2(df = 9) = 2'314.533$ ,  $p < 0.001$ . The data foundation is available at `/analysis/chi_square_{data field}` and the  $\chi^2$ -statistic can be calculated by calling `Analysis.print_chi_square_fit` on the data foundation files.




Figure 2: The sample data set ( $n = 4'111$ ) is significantly skewed towards English (data field **language**:  $\chi^2(df = 3) = 1'441.414$ ,  $p < 0.001$ ) journal publications (data field **type**:  $\chi^2(df = 10) = 52'519.743$ ,  $p < 0.001$ ) in the sciences, medicine and economics (data field **department**:  $\chi^2(df = 9) = 14'447.276$ ,  $p < 0.001$ ) from the 21st century (data field **date**:  $\chi^2(df = 7) = 35'878.493$ ,  $p < 0.001$ ) as compared to the raw Edoc data. The data foundation is available at `/analysis/chi_square_{data field}` and the  $\chi^2$ -statistic can be calculated by calling `Analysis.print_chi_square_fit` on the data foundation files.

Annif project	Vocabulary	Language	Algorithm(s)
<code>yso-en</code>	YSO	English	NN ensemble
<code>yso-maui-en</code>	YSO	English	Maui
<code>yso-bonsai-en</code>	YSO	English	Omikuji
<code>yso-fasttext-en</code>	YSO	English	fastText
<code>wikidata-en</code>	Wikidata	English	TF-IDF

Table 1: Annif projects used to index the items of the Edoc sample data set.

currently evaluated at different libraries, for example at the German National Library (see Nagelschmidt 12.11.2020). As stated in section “Introduction”, in this project I am interested in using Annif out of the box. This means that instead of training a local Annif instance, I will be relying on the Annif REST-style API (see <https://api.annif.org/>).<sup>2</sup> The advantage of this approach is that it is quick and relatively easy to implement. The disadvantage is that no custom algorithms or vocabularies can be used. The task of constructing a gold standard (see section “Gold standard”) remains the same.

The vocabularies provided by the Annif API are the General Finnish Ontology or YSO in short (see <https://finto.fi/yso/en/>) and Wikidata (see <https://www.wikidata.org/>). Each vocabulary is combined with an algorithm or algorithm ensemble respectively and a specific language to create a so-called Annif “project.” The five projects used in what follows are summarized in Table 1. A high-level description of the algorithm(s) is given by Suominen (2019, 7–10); information on the implementation of the algorithm(s) can be found at the Annif GitHub Wiki (see <https://github.com/NatLibFi/Annif/wiki>).

## 4.2 Implementation

Machine indexing with Annif was implemented using the `annif-client` Python library (see <https://pypi.org/project/annif-client/>). The desired output is that every item in the Edoc sample data set is assigned subject terms by all available Annif API projects (namely, `yso-en`, `yso-maui-en`, `yso-bonsai-en`, `yso-fasttext-en`, `wikidata-en`) based on all available text bases (title or title and abstract). In order to distinguish these assignments, we use a unique ID (called “marker” in what follows) for each Annif configuration. A marker is constructed by the conven-

<sup>2</sup>This API is specifically intended for testing. For integration into a production system, the Finto AI API is available (see <https://ai.finto.fi/v1/ui/>).

tion: `{project_id}-{abstract}-{fulltext}-{n}-{threshold}`, where `project_id` is the Annif project, `abstract` and `fulltext` are boolean variables, `n` is the maximum number of suggestions per item, and `threshold` is a variable for a threshold Annif score.

In order to generate the output, we call `Data.super_enrich_with_annif`, thereby iteratively calling `Data.enrich_with_annif` for all items in `/sample/sample_master.json` for all Annif projects. The output is saved in `/indexed/` as `indexed_master.json`.

## 5 Gold standard

In this section I will construct a derivative gold standard in order to assess the quality of machine indexing the Edoc sample data set with Annif.

### 5.1 Definition

The most common approach for assessing the output of machine indexing is by systematically comparing it with a gold standard (sometimes also referred to as model or reference). Golub et al. (2016, 10) define a gold standard as “a collection in which each document is assigned a set of [subject terms] that is assumed to be complete and correct” where “*complete* means that all subjects that should be assigned to a document are in fact assigned, and *correct* means that there are no subjects assigned that are irrelevant to the content.” Put inversely, if an item in the gold standard lacks subject terms describing its content, the assignment is not complete; and if an item in the gold standard has been assigned subject terms that are not relevant to its content, the assignment is not correct.

A gold standard is usually the product of manual indexing by “information experts, subject experts, or potential or real end users” (Golub et al. 2016, 10). This entails its own host of epistemic problems relating to objectivity and consistency of the assigned subject terms. Most importantly, however, the construction of a gold standard from scratch is very expensive. It is therefore not an option for the project at hand. Rather, I will construct what could be called a “derivative” gold standard by reusing indexing data that is already available.

There are other methods for assessing machine indexing quality besides comparison with a gold standard that are worth mentioning. These include an evaluation in the context of indexing workflows (Golub et al. 2016, 13ff.),

the assessment of retrieval performance (Golub et al. 2016, 15–23.), and so-called model free assessments (Louis and Nenkova 2013).

The construction of the derivative gold standard takes three steps:

1. Extract the keywords from the sample data set.
2. Clean the extracted keywords.
3. Reconcile the extracted keywords with Wikidata and YSO.

These steps are explained in more detail in what follows.

## 5.2 Extract and clean keywords

In a first step, the keywords must be extracted from the Edoc sample data set `/sample/sample_master.json`. Recall that we mandated a non-empty `keywords` data field for an item to be selected from the raw Edoc data (see subsection “Selection”). We can thus simply copy the information in the `keywords` data field on a per item basis. To do this, we call `Keywords.extract_keywords` with the sample data set as argument and save the output as `/keywords/keywords_extracted.json` like so:

```
keywords = Keywords.extract_keywords("/sample/sample_master.json")
Utility.save_json(keywords, "/keywords/keywords_extracted.json")
```

In a second step, a list of all single keywords must be created. In order to do so, let us consider now in more detail the exact information extracted from the `keywords` data fields as per `/keywords/keywords_extracted.json`. In Edoc, the `keywords` data field of an item is a non-mandatory free text field that is filled in by the user (usually one of the authors) who undertakes the data entry of an item to Edoc. Even though the Edoc user manual specifies that keywords must be separated by commas (Universität Basel, n.d., 8), this requirement is neither validated by the input mask nor by an administrator of Edoc. Furthermore, neither the manual nor the input mask provide a definition of the term “keyword.” A vocabulary or a list of vocabularies from which to choose the keywords is also lacking. Taken together, these observations are indicative of very heterogeneous data in the `keywords` data field. To wit, the items of `/keywords/keywords_extracted.json` are strings where single keywords are individuated by any symbols the user saw fit. So, for each item in `/keywords/keywords_extracted.json`, the user input must be parsed into single keywords.

Next the so parsed single keywords must be cleaned or normalized: we want the keywords to follow a uniform format thereby joining mor-

phological duplicates such as “Gene,” “gene,” “gene\_,” “gene/,” and so on. Also, some keywords are in fact keyword chains, for example “Dendrites/metabolism/ultrastructure.” Keyword chains must be broken into their component keywords and then parsed again. The reason for this is that Annif only assigns flat (i.e., non-hierarchical) keywords and not keyword chains.

`Keywords.clean_keywords` is the implementation the parser while the recursive cleaner is implemented by `Keywords.clean_keyword`. To create the desired list of clean keywords, saved as `/keywords/keywords_clean.json`, we call `Keywords.clean_keywords` with the extracted keywords as argument:

```
keywords_extracted = Utility.load_json("/keywords/keywords_extracted.json")
keywords_clean = Keywords.clean_keywords(keywords_extracted)
Utility.save_json(keywords_clean, "/keywords/keywords_clean.json")
```

### 5.3 Analysis

`/keywords/keywords_clean.json` has 36'901 entries many of which are duplicates. We hence deduplicate and count the number of occurrences of each keyword. This is achieved by calling `Keywords.make_histogram` on `/keywords/keywords_clean.json` and saving the output as `/keywords/keywords_clean_histogram.json`:

```
keywords_clean = Utility.load_json("/keywords/keywords_clean.json")
keywords_histogram = Keywords.make_histogram(keywords_clean)
Utility.save_json(keywords_histogram, "/keywords/keywords_clean_histogram.json")
```

An analysis of `/keywords/keywords_clean_histogram.json` shows that the lion’s share of keywords has only one occurrence but that the total occurrences are predominantly made up of keywords with more than one occurrence (see Figure 3 for details).

To analyse the spread of keywords in the sample data set, the keywords per item are counted. To do so, we call `Keywords.make_count` on `/indexed/indexed_master.json` and save the output as `/analysis/keywords_counted.json`:

```
sample_data_set = Utility.load_json("/indexed/indexed_master.json")
keywords_counted = Keywords.make_count(sample_data_set)
Utility.save_json(keywords_counted, "/analysis/keywords_counted.json")
```

The median number of keywords for an item in the sample data set is 6 with an IQR of 4 (min = 0, Q1 = 4, M = 6, Q3 = 8, max = 87). Of course,



Figure 3: In `/keywords/keywords_clean_histogram.json`, the distribution of keywords is strongly skewed right ( $\min = Q1 = M = Q3 = 1$ ,  $\max = 910$ ). However, even though keywords with only one occurrence constitute over 75% of the total keywords, their occurrences constitute less than 35% of the total occurrences. The most common keywords with 50 or more occurrences are extreme outliers but make up almost 20% of the total occurrences.



items in the sample data set with a number of keywords below the first and above the third quartile are highly suspect from a qualitative point of view: when it comes to subject indexing, some terms are required, but more is usually not better but worse. Items with too few or too many keywords will be discussed in more detail in section section “Assessment”

## 5.4 Reconciliation

As explained in section “Machine indexing”, Annif assigns subject terms from a controlled vocabulary. If we want to assess the quality of the indexing via a gold standard, we must therefore ensure that the gold standard makes use of the vocabulary used by Annif. The relevant (English) vocabularies are Wikidata and YSO. The next step in constructing the derivative gold standard is hence to match the extracted and cleaned keywords with keywords from Wikidata and YSO. This process is called “reconciliation” (see <https://docs.openrefine.org/manual/reconciling>) and the tool of choice for this task is OpenRefine).<sup>3</sup>

In what follows, I will describe how the cleaned keywords were reconciled with Wikidata and YSO, and which additional steps for refinement were undertaken. In total, 2’104 data transformation operations were performed; the complete operation history is available as `/keywords/operation_history.json`.

The data from `/keywords/keywords_clean_histogram.json` was imported into OpenRefine. The `keyword` column was then duplicated and reconciled with Wikidata. Here the parameters were chosen as follows: reconcile against no particular type, and auto-match candidates with high confidence.

The reconciliation service API returns automatic matches (call them “suggestions”). A suggestion is correct if and only if the meaning of the keyword from `/keywords/keywords_clean_histogram.json` corresponds to the meaning of the suggested concept from Wikidata. Note that for homonymous or

---

<sup>3</sup>For data refinement I use OpenRefine version 3.4.1 (see <https://openrefine.org/>). Data manipulation in OpenRefine is tracked: the manipulation history of some data can be exported as JSON file and then reproduced (on the same data on a different machine or on different data) by loading said file. I will supply a corresponding manipulation history whenever appropriate. Note that when using OpenRefine with larger files (and there are many such files in this project), the memory allocation to OpenRefine must be manually increased (see <https://docs.openrefine.org/manual/installing/#increasing-memory-allocation> for details). Also note that OpenRefine always counts the number of records by the first column (a fact which caused me many headaches).

polysemous keywords, it is impossible to confirm a correct match without further context; those keywords therefore cannot be reconciled (but see section “Construction” for a possible solution). Unfortunately, random sampling showed that the overall quality of the reconciliation was not satisfactory, that is, there were too many incorrect suggestions. A two-pronged strategy was adopted to ameliorate the quality of the reconciliation.

First, the suggestions to the top 500 keywords were manually verified. These keywords account for 14’996 occurrences or 40.638% of the total occurrences and thus constitute an effective lever.

Second, systematic biases were identified and removed. The most prevalent bias was due to a suggestion’s type. As stated above, the reconciliation service API was not constrained by type but had access to the complete Wikidata database. Since Wikidata is an ontology that encompasses everything, it also features types whose concepts cannot qualify as subject terms (at least in the present context). The most prominent example is the type Q13442814 “scholarly article.” Wikidata contains the metadata of many scholarly articles. Now, for some of our keywords, there is a scholarly article with a title that exactly matches the keyword; and since there is no restriction concerning the type, the scholarly article is suggested with high confidence (see <https://github.com/OpenRefine/OpenRefine/wiki/Reconciliation-Service-API> for details). To generalize, suggestions with types whose concepts are proper names are usually incorrect. Based on this observation, suggestions with types such as “scholarly article,” “clinical trial,” and “scientific journal” were rejected.<sup>4</sup> Suggestions types such as “human,” “album,” and “commune of France” were manually verified (i.e., checked for correctness).<sup>5</sup>

With these improvements in place, each keyword with a suggestion was assigned a QID via the “Add cloumns from reconciled values”-function (and similar for YSO and MeSH identifiers). The data was then exported and saved as `/keywords/keywords_reference.json`. Keywords with a QID now constitute 69% of all keywords and 78% of their total occurrences in

---

<sup>4</sup>The complete list includes “academic journal,” “open access journal,” “thesis,” “doctoral thesis,” and “natural number.”

<sup>5</sup>The complete list includes “film,” “musical group,” “business,” “literary work,” “television series,” “organization,” “family name,” “written work,” “video game,” “single, television series episode,” “painting,” “city of the United States,” “magazine,” “studio album,” “year,” “nonprofit organization,” “border town,” “international organization,” “political party,” “software,” “song,” “website,” “article comic strip,” “collection,” “commune of Italy,” “fictional human,” “film,” “government agency,” “village,” “academic journal article,” “female given name,” and “poem.”

the sample data set, but these numbers are significantly lower for the MeSH identifier (53.6% of all keywords with only 28.8% of all occurrences) and especially low for the YSO identifier (26.9% of all keywords with 11% of all occurrences). In both cases, the problem is due to the fact that Wikidata’s mapping of MeSH respectively YSO is only partial. There can be two reasons for this state of affairs for a given entry: either there is no match between Wikidata and YSO or MeSH (after all, Wikidata is much larger than MeSH and YSO taken together), or there is a match but it has not yet been added to the mapping. In the latter case, at least with respect to YSO, there is a solution: Finto provides a REST-style API to access the YSO vocabulary directly (see <https://api.finto.fi/>). For each keyword in the list of reference keywords that lacks a YSO identifier, the Finto API is queried; if a term turns up, it is added to the keyword. The effect of this second reconciliation is detailed in Figure 4. It is achieved by calling `Keywords.enrich_with_yso` on `/keywords/keywords_reference.json` and saving the output as `/keywords/keywords_reference_master.json` like so:

```
keywords_reference = Utility.load_json("/keywords/keywords_reference.json")
keywords_reference_new = Keywords.enrich_with_yso(keywords_reference)
Utility.save_json(keywords_histogram, "/keywords/keywords_reference_master.json")
```

Finally, consider the distribution of the cleaned and reconciled keywords per item in the Edoc sample data set. The corresponding data is generated with `Keywords.make_count` as described in subsection Analysis above and available as `/analysis/keywords_counted.json`. Figure 5 shows that the median number of keywords from MeSH or YSO might be too low to be adequate. This problem can be amended by imposing further constraints on the Edoc sample data set and such a solution is discussed in section “Conclusion and outlook”.

## 5.5 Discussion

Let us now turn to the evaluation of the reconciliation: how many of the suggestions were correct? This question was answered via random sampling (following Roth and Heidenreich 1993, 204–25). The random sample ( $n = 500$ ) was created by calling `Analysis.make_random_sample` on `/keywords/reference_keywords_master.json`; it is available at `/analysis/random_keywords.json`. The sample was then imported into OpenRefine and the judgement (1 for correct, 0 for incorrect) of the manual verification was recorded in the column `verification`. The data was then




Figure 4: The coverage of `/keywords/keywords_reference_master.json` by the controlled vocabularies of Wikidata (QID), Medical Subject Headings (MeSH), and YSO (General Finnish Ontology). Both MeSH and YSO are dependent on QID but independent of each other. YSO enriched is the superset of YSO created by reconciling keywords that lack a YSO identifier directly with the YSO database provided by the Finto API; it is hence independent of Wikidata.




Figure 5: The distribution of keywords per item in the Edoc sample data set. The leftmost boxplot shows the distribution of cleaned keywords (min = 0, Q1 = 4, M = 6, Q3 = 8, max = 87); the other boxplots show the distribution of cleaned keywords with reconciled QID (min = 0, Q1 = 2, M = 4, Q3 = 6, max = 80), MeSH ID (min = Q1 = 0, M = 2, Q3 = 4, max = 63), and YSO ID respectively (min = Q1 = 0, M = 1, Q3 = 2, max = 46). All four distributions are similarly consistent, but there is a linear decrease of the distribution’s center leaving MeSH and YSO with potentially too few descriptors to represent an adequate indexing.

exported and is available at `/analysis/random_keywords_verified.csv`.

An analysis of this data shows that 53% of the suggestions in the random sample were correct with a 95% confidence interval of 48.8% to 57.3%. We can therefore conclude that  $8'507 \pm 692.1$  of the 16'050 keywords in `/keywords/reference_keywords.json` have correct suggestions. Note that of the 235 incorrect suggestions in the random sample, 188 were incorrect by default because they were missing a QID; the share of non-empty yet incorrect suggestions is only 9.4% in the random sample meaning that the quality of the reconciliation is not as disappointing as it might seem at first glance.

## 6 Assessment

In this section I will assess the quality of the sample data set's indexing by Annif based on the derivative gold standard.

### 6.1 Precision, recall, F1-score

The metrics used for the assessment are precision, recall and F1-score. Precision and recall are standard metrics for indexing quality (e.g., Gantert 2016, 197) whereby the F1-score plays a more prominent role in the assessment of machine indexing (e.g., Suominen 2019, 11–14; Toepfer and Kempf 2016, 93f.). Of course, there is a host of alternative metrics (such as indexing consistency, transparency, reproducibility) that are neglected here.

Let us briefly look at the definitions and motivations of the chosen metrics. Remember that a suggestion of a subject term is correct if and only if the subject term is in the derivative gold standard. The possible outcomes are summarized in Table 2.

		Suggested by Annif?	
		No	Yes
In gold standard?	No	True negative	False positive
	Yes	False negative	True positive

Table 2: Annif confusion matrix.

“Precision” is the fraction of the correctly suggested subject terms; a suggestion is correct if and only if it is in the derivative gold standard:

$$\text{Precision} = \frac{\text{True positive}}{\text{True positive} + \text{False positive}}$$

Or put as question: what fraction of the subject terms suggested by Annif are also in the derivative gold standard?

“Recall” is the fraction of correct subject terms out of all correct subject terms:

$$\text{Recall} = \frac{\text{True positive}}{\text{True positive} + \text{False negative}}$$

Put as question: what fraction of the subject terms in the gold standard were suggested by Annif?

The F1-score is the harmonic mean between precision and recall:

$$\text{F1} = 2 * \frac{\text{Precision} * \text{Recall}}{\text{Precision} + \text{Recall}}$$

The above scoring metrics were implemented using the scikit-learn Python machine learning library (Pedregosa et al. 2011).

## 6.2 Creating the data foundation

I will now describe how the data foundation for the assessment was created. There are three parameters that need to be distinguished (see section “Annif”):

1. The Annif project (algorithm plus vocabulary) responsible for the indexing of the sample data set. As per the Annif REST API, these are `yso-en`, `yso-maui-en`, `yso-bonsai-en`, `yso-fasttext-en`, and `wikidata-en`.
2. The text base per item, namely title versus title and abstract.
3. The maximum number of suggestions per item. Since we required 10 suggestions per item, we can choose between 1 to 10 suggestions.

Combining these parameters, we really have 100 Annif configurations whose performance we want to compare and assess: Annif project \* text base \* maximum number of suggestions =  $5 * 2 * 10 = 100$ . Remember the convention for constructing the marker that identifies a configuration (see section “Annif”): `{project_id}-{abstract}-{fulltext}-{n}-{threshold}`.

For each configuration, the F1-score was then computed. It is important to note that each metric comes in three different flavors dubbed “macro,” “micro,” and “weighted” respectively (see Sokolova and Lapalme 2009). In the macro flavor, the metric represents simply the mean per class (i.e., correct or incorrect suggestion). The weighted metric is the macro metric but each class

is weighted by its true positives. By contrast, a metric with the micro flavor is computed globally over all true positives and false positives respectively negatives. So the “macro” and “weighted” flavors are useful for assessing the performance of a configuration with respect to individual cases of assigning subject terms (call them “samples”) whereas the “micro” flavor is most suitable to assess the overall performance of a configuration with respect to assigning subject terms.

To compute the F1-score, we call `Analysis.super_make_metrics` on `/indexed/indexed_master_mesh_enriched`. The 100 output files are saved as `/metrics/metrics_{marker}.json` where `marker` specifies the Annif configuration; a single file for analysis is saved as `/analysis/metrics.json`:

```
Analysis.super_make_metrics("/indexed/indexed_master.json")
```

Note that the data foundation includes additional information, namely the sample size and the raw values for the confusion matrix. The sample size is a histogram of each instance in which a value in the confusion matrix was computed, that is, each case in which either Annif or the derivative gold standard assigned a subject term. Finally, note that if an item in the Edoc sample data set had an empty derivative gold standard, no score was computed; this is the case exactly if none of the cleaned keywords had been matched to Wikidata or YSO respectively. Configurations with a Wikidata vocabulary had a scoring coverage of 94.38% of the items in the sample data set as compared to only 62.84% for configurations with a YSO vocabulary.

### 6.3 General results

In what follows I will discuss the general results of assessing the performance of the 100 Annif configurations versus the derivative gold standard with respect to the Edoc sample data set. The data foundation is available at `/analysis/metrics.json`.

Let us first consider overall performance. Here the most striking result is that Wikidata configurations outperformed YSO configurations (see Figure 6, left). However, the explanation of this effect is not evident. The two main explanatory hypotheses are 1. that the suggestions by the Wikidata configurations are more salient, or 2. that the derivative gold standard is biased towards Wikidata due to its higher coverage of QIDs as compared to YSO IDs. By contrast, the Wikidata configurations are more productive than the YSO configurations, and the reason for this effect is the higher coverage of QIDs as compared to YSO IDs (see Figure 7). By “productivity”






Figure 6: Distribution of weighted F1-scores per class of project of Annif configuration (left), and per class of text basis of Annif configuration (right). **wikidata-en** (min = 0.239, Q1 = 0.355, M = 0.415, Q3 = 0.492, max = 0.517) outperforms any YSO configuration. **yso-bonsai-en**, **yso-en** and **yso-fasttext-en** are on par (min = 0.169, Q1 = 0.218, M = 0.312, Q3 = 0.414, max = 0.496) and slightly outperformed by the more consistent **yso-maui-en** (min = 0.171, Q1 = 0.250, M = 0.327, Q3 = 0.407, max = 0.496). Surprisingly, the performance of configurations based on titles (min = 0.169, Q1 = 0.250, M = 0.345, Q3 = 0.424, max = 0.517) was marginally better than the performance of configurations based on titles and abstracts (min = 0.169, Q1 = 0.242, M = 0.337, Q3 = 0.424, max = 0.517).

	n=1	n=2	n=3	n=4	n=5	n=6	n=7	n=8	n=9	n=10
min	0.239	0.403	0.454	0.391	0.336	0.289	0.250	0.218	0.192	0.169
Q1	0.407	0.491	0.454	0.391	0.336	0.289	0.250	0.218	0.192	0.169
M	0.414	0.496	0.454	0.391	0.336	0.289	0.250	0.218	0.192	0.169
Q3	0.414	0.496	0.456	0.400	0.351	0.309	0.277	0.251	0.231	0.215
max	0.414	0.496	0.492	0.517	0.503	0.467	0.427	0.389	0.355	0.324

Table 3: Distribution of weighted F1-scores per maximum number of suggestions  $1 \leq n \leq 10$ .

I mean that the absolute number of assigned subject terms. So Wikidata configurations are not only qualitatively but also quantitatively superior to YSO configurations.

Furthermore, the four YSO configurations are more or less on par: the `yso-bonsai-en`, `yso-en`, and `yso-fasttext-en` configurations perform very similarly and are slightly outperformed by `yso-maui-en` (see Figure 6, left). This result is consistent with other assessments reporting that “[o]f the individual algorithms, Maui performed best on all corpora” (Suominen 2019, 13).

A surprising result is that there was no performance gain achieved by increasing the text basis from titles to titles and abstracts (see section “Creating the data foundation”): if anything, the performance for the extended text basis was slightly worse (see Figure 6, right). There is again no easy explanation for this find since there are multiple plausible causes which cannot be distangled here. For example, the abstract of an item in the Edoc sample data set might be less representative of the item’s content than its title. In that case, the observed worse performance of the Annif configurations based on title and abstracts would even be expected. Alternatively, it might be the case that the problem lies with Annif: a larger text basis introduces more confounding factors and might make it harder to extract the subject terms required. An experimentum crucis to decide between the two discussed explanations would be to further extend the text basis to include full texts in addition to titles and abstracts.

Let us turn to the parameter of the maximum number of suggestions per item in the Edoc sample data set (see Figure 8). Here the best performance was achieved by a token  $n = 4$  configuration. However, the type  $n = 4$  configuration performed on average significantly worse than the type  $n = 3$  and type  $n = 2$  configurations. So with respect to the maximum number




Figure 7: The distribution of cumulative sample size per project class of Annif configuration. Wikidata configurations (min = 28'618, Q1 = 29'912, M = 35'121, Q3 = 42'439, max = 48'776) are more productive than YSO configurations (min = 9'878, Q1 = 12'546, M = 16'710, Q3 = 22'694, max = 27'354).




Figure 8: Distribution of weighted F1-scores per maximum number of suggestions  $1 \leq n \leq 10$ . See Table 3 for numeric values.  $n = 2$  is the best performing type of configuration. However, it is outperformed by  $n = 4$  and  $n = 5$  token configurations. The distribution of the distributions is skewed left. Types of configurations with a smaller maximum number of suggestions display a more consistent performance.

of suggestions, there is a discrepancy between the best performing token configuration and the best performing type of configuration. This distinction is important: when choosing a configuration for the purpose of a production system, we are usually interested in the best token configuration. The top 20 token configurations are summarized in Figure 9. The best performing configuration with a weighted F1-score of 0.517 is **wikidata-en** with a maximum number of 4 suggestions per item; its text basis (title or abstract and title) does not matter.




Figure 9: 20 best performing Annif configurations (according to F1-score).

## 6.4 Departmental results

In subsection “General results” I have identified and discussed the overall best Annif configurations. However, in section “Sample data set”, I had noted the caveat that the performance of Annif might vary according to department due to systematic biases in constructing the Edoc sample data set. In this section I will therefore assess the performance of the various Annif configurations per department.

We begin again by constructing the data foundation. Since the Edoc `department` data field is mandatory, the sample data set is partitioned into blocks of departments by default. We can thus create a data foundation for each such block by calling `Analysis.super_make_metrics` with a departmental parameter:

```
for dept in Data.get_departments():  
    Analysis.super_make_metrics("/indexed/indexed_master.json", dept)
```

This yields 1000 files in `/metrics/metrics_{department}_{marker}.json` (100 configurations \* 10 departments) where `department` specifies the department according to the Edoc convention. The data foundation is summarized in `/analysis/metrics.json`.

Let us now look at the results. First consider the distribution of the performance scores across departments as shown in Figure 10. We can see that there are striking differences in variability between departments. The departments with the most consistent weighted F1-scores are Medicine and Central Services. However, these two departments have also the lowest maximum weighted F1-scores. It is noteworthy that all other departments have maximum weighted F1-scores that are well above the weighted F1-score of 0.517 of the best performing general Annif configuration.

Let us now consider the best performing Annif configurations per department as summarized in Figure 11. It is evident that only two of the ten departments (namely Associated and Central Services) have as best performing configuration the configuration that was declared the overall best performing configuration (namely `wikidata-en-F-F-4-N`). More surprisingly, YSO outperforms Wikidata in all other departments except Interdisciplinary. However, the margin is rather slim. The notable exception is the department Economics, where the YSO configuration outperforms the Wikidata configuration by a factor of 3. More importantly, the best performing YSO configurations are significantly less productive than the slightly worse per-




Figure 10: Distribution of weighted F1-scores for all Annif configurations per department.




Figure 11: Best performing Annif configuration (according to weighted F1-score) per department as compared to the overall best performing Annif configuration `wikidata-en-F-F-4-N`.



forming Wikidata configuration, except for `yso-en-F-F-4-N` in the Medicine department.

## 7 Conclusion and outlook

The main take home from this project is that the out of the box Annif API is suitable to index an institutional repository such as Edoc. This is based on the performance of the Annif API in indexing the Edoc sample data set measured against the derivative gold standard constructed from cleaned and reconciled Edoc author keywords. With the prototype in place, the next step now concerns the implementation of a production system. The function `Data.enrich_with_annif` can of course be called to index all Edoc data available at `/raw/`. It would also be relatively straightforward to implement indexing with Annif for items newly added to Edoc respectively the University of Basel’s research database. An alternative and perhaps more sustainable approach would be to improve the data quality by amending the process and requirements for data entry. Generally speaking, authors should be required to choose index terms from a controlled vocabulary or from a set of controlled vocabularies, and the entered data should be automatically validated. One way to implement this would be via the Skosmos recommendations feature of the BARTOC Skomos instance (see Waeber and Ledl 2019).

Apart from implementing a production system as discussed above, natural next steps to improve upon this project include:

1. In response to the result that increasing the text basis to titles and abstracts does not increase performance discussed in section “Assessment”, add full text support and evaluate the performance by increasing the text basis even further. To do this, `Data.enrich_with_annif` must be amended to fetch and parse the full text PDFs. For an item in the sample data set, the link to the full text is constructed from the data fields `official_url` and `documents - main`. Initial tests using the Tika Python library for parsing were promising.
2. Originally I had intended to undertake an additional performance test based on a gold standard distinct from the derivative gold standard constructed in section “Gold standard”. In order to do so, items in the Edoc sample data set were enriched with MeSH terms (see <https://www.nlm.nih.gov/mesh/meshhome.html>) retrieved from PubMed (if they had a PubMed ID). This was achieved by calling `Data.enrich_with_mesh` on `/indexed/indexed_master.json`. How-

ever, the Annif API does not include a configuration with a MeSH vocabulary, and there is no concordance between MeSH and either Wikidata or YSO (see <https://coli-conc.gbv.de/cocoda/app/concordances.html>). Therefore, the MeSH terms obtained from PubMed would have to be reconciled with Wikidata and YSO in a very time-consuming manner, yielding again only a derivative gold standard. As a way forward, it would be more effective to train a local instance of Annif on the already obtained MeSH data.

3. As shown in section “Assessment”, the performance of Annif configurations varies with department. It is hence plausible that some (subsets of) items in Edoc require domain-specific vocabularies that are not available in Annif. These vocabularies can be identified using BARTOC FAST (Hindermann and Ledl 2020); the implementation is straightforward with my `bartocsuggest` Python library that already includes an Annif wrapper (see <https://pypi.org/project/bartocsuggest/>).
4. An issue that has been neglected in this project is the fact that Edoc is a multilingual repository containing more than 3’324 items in German (roughly 5% of Edoc) and 273 items in other languages (less than 0.5% of Edoc).<sup>6</sup> Here it would be interesting to train a local instance of Annif with GND similar in spirit to Nagelschmidt (12.11.2020) and compare its performance to other machine indexing tools such as DA-3 (Beckmann et al. 2019) which are currently informally evaluated at the University Library Basel.

## Bibliography

- Beckmann, Regine, Imma Hinrichs, Melanie Janßen, Gérard Milmeister, and Peter Schäuble. 2019. “Digitale Assistent DA-3.” *O-Bib. Das Offene Bibliotheksjournal* 6 (3): 1–20. <https://doi.org/10.5282/O-BIB/2019H3S1-20>.
- Gantert, Klaus. 2016. *Bibliothekarisches Grundwissen*. 9., vollständig neu bearbeitete und erweiterte Auflage. Berlin: De Gruyter Saur. <https://doi.org/10.1515/9783110321500>.
- Golub, Koraljka. 2019. “Automatic Subject Indexing of Text.” *Knowledge Organization* 46 (2): 104–21. <https://doi.org/10.5771/0943-7444-2019-2->

---

<sup>6</sup>The Edoc sample data set only contains 53 non-English (including 48 German) items; the negligence is hence well justified.

- Golub, Koraljka, Dagobert Soergel, George Buchanan, Douglas Tudhope, Marianne Lykke, and Debra Hiom. 2016. “A Framework for Evaluating Automatic Indexing or Classification in the Context of Retrieval.” *Journal of the Association for Information Science and Technology* 67 (1): 3–16. <https://doi.org/10.1002/asi.23600>.
- Hindermann, Maximilian, and Andreas Ledl. 2020. “BARTOC FAST: A Federated Asynchronous Search Tool for Remote Vocabulary Access.” In *Knowledge Organization at the Interface*, edited by Marianne Lykke, Tanja Svarre, Mette Skov, Daniel Martínez-Ávila, and International Society for Knowledge Organization International Society for Knowledge Organization, 200–206. Advances in Knowledge Organization. Baden-Baden: Ergon – ein Verlag in der Nomos Verlagsgesellschaft. <https://doi.org/10.5771/9783956507762-200>.
- Louis, Annie, and Ani Nenkova. 2013. “Automatically Assessing Machine Summary Content Without a Gold Standard.” *Computational Linguistics* 39 (2): 267–300. <https://doi.org/10.1162/COLI%7B/textunderscore%20%7Da%7B/textunderscore%20%7D00123>.
- Nagelschmidt, Matthias. 12.11.2020. “Evaluation von Annif für Die Maschinelle Inhaltserschließung an Der Deutschen Nationalbibliothek.” <https://wiki.dnb.de/download/attachments/181735291/07-EvaluationVonAnnif.pdf?version=1&modificationDate=1605778295000&api=v2>.
- Parke, Carol. 2013. *Essential First Steps to Data Analysis: Scenario-Based Examples Using SPSS*. Thousand Oaks: SAGE Publications. <https://doi.org/10.4135/9781506335148>.
- Pedregosa, F., G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, et al. 2011. “Scikit-Learn: Machine Learning in Python.” *Journal of Machine Learning Research*, no. 12: 2825–30. <https://www.jmlr.org/papers/volume12/pedregosa11a/pedregosa11a.pdf>.
- Roth, Erwin, and Klaus Heidenreich. 1993. *Sozialwissenschaftliche Methoden: Lehr- Und Handbuch für Forschung Und Praxis*. 3., völlig überarbeitete und erweiterte Auflage. München: R. Oldenbourg Verlag.
- Sokolova, Marina, and Guy Lapalme. 2009. “A Systematic Analysis of Performance Measures for Classification Tasks.” *Information Processing & Management* 45 (4): 427–37. <https://doi.org/10.1016/j.ipm.2009.03.002>.

- Stokhof, Martin, and Michiel van Lambalgen. 2011. “Abstractions and Idealisations: The Construction of Modern Linguistics.” *Theoretical Linguistics* 37 (1-2): 1–26. <https://doi.org/10.1515/thli.2011.001>.
- Suominen, Osmo. 2019. “Annif: DIY Automated Subject Indexing Using Multiple Algorithms.” *LIBER Quarterly* 29 (1): 1–25. <https://doi.org/10.18352/lq.10285>.
- Suominen, Osmo, Juho Inkinen, Tuomo Virolainen, Moritz Fürneisen, Bruno P. Kinoshita, Sara Veldhoen, Mats Sjöberg, Philipp Zumstein, Robin Neatherway, and monalehtinen. 2021. “NatLibFi/Annif: Annif 0.51.” <https://doi.org/10.5281/zenodo.4521923>.
- Toepfer, Martin, and Andreas Oskar Kempf. 2016. “Automatische Indexierung Auf Basis von Titeln Und Autoren-Keywords – Ein Werkstattbericht.” *027.7 Zeitschrift für Bibliothekskultur / Journal for Library Culture* 4 (2): 84–97. [https://0277.ch/ojs/index.php/cdrs\\_0277/article/view/156/354](https://0277.ch/ojs/index.php/cdrs_0277/article/view/156/354).
- Universität Basel. n.d. “Research Database of the University of Basel User Manual.” Edited by Universität Basel.
- Waeber, Jonas, and Andreas Ledl. 2019. “A Semantic Web SKOS Vocabulary Service for Open Knowledge Organization Systems.” In *Metadata and Semantic Research*, edited by Emmanouel Garoufallou, Fabio Sartori, Rania Siatiri, and Marios Zervas, 846:3–12. Communications in Computer and Information Science, 1865-0929. Cham, Switzerland: Springer. <https://doi.org/10.1007/978-3-030-14401-2%7B/textunderscore%20%7D1>.

## 8 Appendix

See <https://github.com/MHindermann/mas>.