

Boundary loss for highly unbalanced segmentation

MIDL 2019, London

Hoel Kervadec*, Jihene Bouchtiba*, Christian Desrosiers, Éric Granger, Jose Dolz, Ismail Ben Ayed

ÉTS Montréal

*Contributed equally

`hoel.kervadec.1@etsmtl.net`

`https://github.com/LIVIAETS/surface-loss`

- Difficulty of highly-imbalanced segmentation

Presentation overview

- Difficulty of highly-imbalanced segmentation
- Formulation: inspired from curve/level-set evolution/differentiation

Presentation overview


- Difficulty of highly-imbalanced segmentation
- Formulation: inspired from curve/level-set evolution/differentiation
- Evaluation

Presentation overview


- Difficulty of highly-imbalanced segmentation
- Formulation: inspired from curve/level-set evolution/differentiation
- Evaluation
- Future works on other applications

Problem statement & motivations


Regional losses (cross-entropy, dice loss, ...) are sensitive to high class-imbalance



Ground truth



Regional loss



Our **boundary** loss

$$\mathcal{L}_R(\theta) = \int_{\Omega} -g(p) \log s_{\theta}(p) dp + \int_{\Omega} -(1 - g(p)) \log (1 - s_{\theta}(p)) dp$$

Ω : image set, θ : network parameters, S_{θ} : softmax predictions, G : ground truth.

$$\mathcal{L}_R(\theta) = \int_{\Omega} -g(p) \log s_{\theta}(p) dp + \int_{\Omega} -(1 - g(p)) \log (1 - s_{\theta}(p)) dp$$

Ω : image set, θ : network parameters, S_{θ} : softmax predictions, G : ground truth.

$$\mathcal{L}_R(\theta) = \int_{\Omega} -g(p) \log s_{\theta}(p) dp + \int_{\Omega} -(1 - g(p)) \log (1 - s_{\theta}(p)) dp$$

Ω : image set, θ : network parameters, S_{θ} : softmax predictions, G : ground truth.

$$\mathcal{L}_R(\theta) = \int_{\Omega} -g(p) \log s_{\theta}(p) dp + \int_{\Omega} -(1 - g(p)) \log (1 - s_{\theta}(p)) dp$$

Ω : image set, θ : network parameters, s_{θ} : softmax predictions, G : ground truth.

$$\mathcal{L}_R(\theta) = \int_{\Omega} -g(p) \log s_{\theta}(p) dp + \int_{\Omega} -(1 - g(p)) \log (1 - s_{\theta}(p)) dp$$


Ω : image set, θ : network parameters, S_{θ} : softmax predictions, G : ground truth.

$$\begin{aligned}\mathcal{L}_R(\theta) &= \int_{\Omega} -g(p) \log s_{\theta}(p) dp + \int_{\Omega} -(1 - g(p)) \log (1 - s_{\theta}(p)) dp \\ &= \int_G -\log s_{\theta}(p) dp + \int_{\Omega \setminus G} -\log (1 - s_{\theta}(p)) dp\end{aligned}$$

Ω : image set, θ : network parameters, S_{θ} : softmax predictions, G : ground truth.

Several orders of magnitude of difference.


Regional losses discard spatial/boundary information:



A boundary loss?

A loss minimizing the distance between two boundaries could:


- Use that extra spatial information
- Be less sensitive to the class imbalance



A boundary loss?

A loss minimizing the distance between two boundaries could:

- Use that extra spatial information
- Be less sensitive to the class imbalance



But challenging to represent the boundary of S_θ

Formulation

Formulation


Inspired by discrete optimization techniques in curve evolution.

Formulation

Inspired by discrete optimization techniques in curve evolution.

When two boundaries are **are close enough** [Boykov et al., 2006], their distance can be written as:


$$\text{Dist}(\partial G, \partial S) \approx \int_{\partial G} \|y_{\partial S}(p) - p\|^2 dp$$



Formulation

Switch to an integral over ΔS

$$\text{Dist}(\partial G, \partial S) \approx 2 \int_{\Delta S} D_G(q) dq$$



$D_G(q)$: distance map corresponding to ∂G

$$\frac{1}{2} \text{Dist}(\partial G, \partial S) \approx \int_{\Delta_S} D_G(q) dq$$

$$\begin{aligned}\frac{1}{2}\text{Dist}(\partial G, \partial S) &\approx \int_{\Delta S} D_G(q) dq \\ \Delta S &= (S \setminus G) \cup (G \setminus S)\end{aligned}$$

$$\begin{aligned}\frac{1}{2}\text{Dist}(\partial G, \partial S) &\approx \int_{\Delta S} D_G(q) dq \\ \Delta S &= (S \setminus G) \cup (G \setminus S) \\ \phi_G(q) &= \begin{cases} -D_G(q) & \text{if } q \in G \\ D_G(q) & \text{otherwise} \end{cases}\end{aligned}$$

$$\left\{ \begin{array}{l} \frac{1}{2} \text{Dist}(\partial G, \partial S) \approx \int_{\Delta S} D_G(q) dq \\ \Delta S = (S \setminus G) \cup (G \setminus S) \\ \phi_G(q) = \begin{cases} -D_G(q) & \text{if } q \in G \\ D_G(q) & \text{otherwise} \end{cases} \end{array} \right.$$

Can rewrite $\text{Dist}(\partial G, \partial S)$ as **regional** integrals of **level-set** functions:

$$\frac{1}{2} \text{Dist}(\partial G, \partial S) \approx \int_S \phi_G(q) dq - \int_G \phi_G(q) dq$$

$$\left\{ \begin{array}{l} \frac{1}{2} \text{Dist}(\partial G, \partial S) \approx \int_{\Delta S} D_G(q) dq \\ \Delta S = (S \setminus G) \cup (G \setminus S) \\ \phi_G(q) = \begin{cases} -D_G(q) & \text{if } q \in G \\ D_G(q) & \text{otherwise} \end{cases} \end{array} \right.$$

Can rewrite $\text{Dist}(\partial G, \partial S)$ as **regional** integrals of **level-set** functions:

$$\begin{aligned} \frac{1}{2} \text{Dist}(\partial G, \partial S) &\approx \int_S \phi_G(q) dq - \int_G \phi_G(q) dq \\ &\approx \int_{\Omega} \phi_G(q) s(q) dq - \int_{\Omega} \phi_G(q) g(q) dq \end{aligned}$$


$$\text{Dist}(\partial G, \partial S_\theta) \approx \int_{\Omega} \phi_G(q) s_\theta(q) dq - \int_{\Omega} \phi_G(q) g(q) dq$$

$$\min_{\theta} \text{Dist}(\partial G, \partial S_{\theta}) \approx \int_{\Omega} \phi_G(q) s_{\theta}(q) dq - \int_{\Omega} \phi_G(q) g(q) dq$$

$$\min_{\theta} \text{Dist}(\partial G, \partial S_{\theta}) \approx \int_{\Omega} \phi_G(q) s_{\theta}(q) dq - \int_{\Omega} \phi_G(q) g(q) dq$$
$$\mathcal{L}_B(\theta) = \int_{\Omega} \phi_G(q) s_{\theta}(q) dq$$

Formulation

$$\min_{\theta} \text{Dist}(\partial G, \partial S_{\theta}) \approx \int_{\Omega} \phi_G(q) s_{\theta}(q) dq - \int_{\Omega} \phi_G(q) g(q) dq$$
$$\mathcal{L}_B(\theta) = \int_{\Omega} \phi_G(q) s_{\theta}(q) dq$$



ϕ_G can be efficiently pre-computed

Experiments

Experiments on two dataset:

- White Matter Hyperintensities (WMH)¹
- Ischemic stroke lesion (ISLES)²

¹<http://wmh.isi.uu.nl>

²<http://www.isles-challenge.org>

Experiments on two dataset:

- White Matter Hyperintensities (WMH)¹
- Ischemic stroke lesion (ISLES)²

Combine with a GDL for the initial predictions:


$$\alpha \mathcal{L}_{GD}(\theta) + (1 - \alpha) \mathcal{L}_B(\theta)$$

We decrease α over time, with the boundary loss taking over.

¹<http://wmh.isi.uu.nl>

²<http://www.isles-challenge.org>

Results







Results

Loss	ISLES		WMH	
	DSC	HD (mm)	DSC	HD (mm)
\mathcal{L}_B	0.321 (0.000)	NA	0.569 (0.000)	NA
\mathcal{L}_{GD}	0.575 (0.028)	4.009 (0.016)	0.727 (0.006)	1.045 (0.014)
$\mathcal{L}_{GD} + \mathcal{L}_B$	0.656 (0.023)	3.562 (0.009)	0.748 (0.005)	0.987 (0.010)


Figure 4: Mean performance (and standard deviation) of 2 runs for each setting.

Results




Other applications

Preliminary results on ACDC (4 classes): might work as stand-alone loss.




Ground truth




Boundary loss alone

Other applications

Preliminary results on ACDC (4 classes): might work as stand-alone loss.



Ground truth



Boundary loss alone


Already several feedbacks of improved performances in various applications:
<https://github.com/LIVIAETS/surface-loss>

Take home message

- New, computationally efficient loss that uses boundary information
- Can be used for any standard regional network
- Improve results and stabilize training on 2 highly-imbalanced datasets
- Many more potential applications to evaluate

- New, computationally efficient loss that uses boundary information
- Can be used for any standard regional network
- Improve results and stabilize training on 2 highly-imbalanced datasets
- Many more potential applications to evaluate

<https://github.com/LIVIAETS/surface-loss>

-  Boykov, Y., Kolmogorov, V., Cremers, D., and Delong, A. (2006).
An integral solution to surface evolution PDEs via geo-cuts.
In *European Conference on Computer Vision*, pages 409–422. Springer.