

# Dueling Network

**Shusen Wang**

<http://wangshusen.github.io/>

# Advantage Function

# Return

**Definition:** Discounted return.

- $U_t = R_t + \gamma \cdot R_{t+1} + \gamma^2 \cdot R_{t+2} + \gamma^3 \cdot R_{t+3} + \dots$

# Value Functions

**Definition:** Discounted return.

- $U_t = R_t + \gamma \cdot R_{t+1} + \gamma^2 \cdot R_{t+2} + \gamma^3 \cdot R_{t+3} + \dots$

**Definition:** Action-value function.

- $Q_\pi(s_t, a_t) = \mathbb{E} [U_t | S_t = s_t, A_t = a_t].$

# Value Functions

**Definition:** Discounted return.

- $U_t = R_t + \gamma \cdot R_{t+1} + \gamma^2 \cdot R_{t+2} + \gamma^3 \cdot R_{t+3} + \dots$

**Definition:** Action-value function.

- $Q_\pi(s_t, a_t) = \mathbb{E} [U_t | S_t = s_t, A_t = a_t].$

**Definition:** State-value function.

- $V_\pi(s_t) = \mathbb{E}_{A_t} [Q_\pi(s_t, A_t)]$

# Optimal Value Functions

**Definition:** Optimal action-value function.

- $Q^*(s, a) = \max_{\pi} Q_{\pi}(s, a).$

# Optimal Value Functions

**Definition:** Optimal action-value function.

- $Q^*(s, a) = \max_{\pi} Q_{\pi}(s, a).$

**Definition:** Optimal state-value function.

- $V^*(s) = \max_{\pi} V_{\pi}(s).$

# Optimal Value Functions

**Definition:** Optimal action-value function.

- $Q^*(s, a) = \max_{\pi} Q_{\pi}(s, a).$

**Definition:** Optimal state-value function.

- $V^*(s) = \max_{\pi} V_{\pi}(s).$

**Definition:** Optimal advantage function.

- $A^*(s, a) = Q^*(s, a) - V^*(s).$



# Properties of Advantage Function

**Theorem 1:**  $V^*(s) = \max_a Q^*(s, a)$ .

# Properties of Advantage Function

**Theorem 1:**  $V^*(s) = \max_a Q^*(s, a)$ .

- Recall the definition of the optimal advantage function:

$$A^*(s, a) = Q^*(s, a) - V^*(s).$$

# Properties of Advantage Function

**Theorem 1:**  $V^*(s) = \max_a Q^*(s, a)$ .

- Recall the definition of the optimal advantage function:

$$A^*(s, a) = Q^*(s, a) - V^*(s).$$

- It follows that

$$\max_a A^*(s, a) = \max_a Q^*(s, a) - V^*(s) = 0$$

# Properties of Advantage Function

**Theorem 1:**  $V^*(s) = \max_a Q^*(s, a)$ .

- Recall the definition of the optimal advantage function:

$$A^*(s, a) = Q^*(s, a) - V^*(s).$$

- It follows that

$$\max_a A^*(s, a) = 0$$

# Properties of Advantage Function

Definition of advantage:  $A^*(s, a) = Q^*(s, a) - V^*(s)$ .



$$Q^*(s, a) = V^*(s) + A^*(s, a)$$

# Properties of Advantage Function

Definition of advantage:  $A^*(s, a) = Q^*(s, a) - V^*(s)$ .



$$Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$$

= 0

# Properties of Advantage Function

Definition of advantage:  $A^*(s, a) = Q^*(s, a) - V^*(s)$ .



**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$   
 $= 0$

# Dueling Network


## Reference:

1. Wang et al. [Dueling network architectures for deep reinforcement learning](#). In *ICML*, 2016.




# Revisiting DQN

- Approximate  $Q^*(s, a)$  by a neural network,  $Q(s, a; \mathbf{w})$ .




# Approximating Advantage Function

- Approximate  $A^*(s, a)$  by a neural network,  $A(s, a; \mathbf{w}^A)$ .



# Approximating State-Value Function

- Approximate  $V^*(s)$  by a neural network,  $V(s; \mathbf{w}^V)$ .



# Dueling Network: Formulation

**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$

# Dueling Network: Formulation

**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$

- Approximate  $V^*(s)$  by a neural network,  $V(s; \mathbf{w}^V)$ .

# Dueling Network: Formulation

**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$

- Approximate  $V^*(s)$  by a neural network,  $V(s; \mathbf{w}^V)$ .
- Approximate  $A^*(s, a)$  by a neural network,  $A(s, a; \mathbf{w}^A)$ .

# Dueling Network: Formulation

**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$

- Approximate  $V^*(s)$  by a neural network,  $V(s; \mathbf{w}^V)$ .
- Approximate  $A^*(s, a)$  by a neural network,  $A(s, a; \mathbf{w}^A)$ .
- Thus, approximate  $Q^*(s, a)$  by the dueling network:

$$Q(s, a; \mathbf{w}^A, \mathbf{w}^V) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$

# Dueling Network: Formulation

**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$

- Approximate  $V^*(s)$  by a neural network,  $V(s; \mathbf{w}^V)$ .
- Approximate  $A^*(s, a)$  by a neural network,  $A(s, a; \mathbf{w}^A)$ .
- Thus, approximate  $Q^*(s, a)$  by the dueling network:

$$Q(s, a; \mathbf{w}^A, \mathbf{w}^V) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$



# Dueling Network: Formulation

**Theorem 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a).$

- Approximate  $V^*(s)$  by a neural network,  $V(s; \mathbf{w}^V)$ .
- Approximate  $A^*(s, a)$  by a neural network,  $A(s, a; \mathbf{w}^A)$ .
- Thus, approximate  $Q^*(s, a)$  by the dueling network:

$$Q(s, a; \mathbf{w}^A, \mathbf{w}^V) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$


$$\mathbf{w} = (\mathbf{w}^A, \mathbf{w}^V)$$

# Dueling Network

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$


# Dueling Network

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$




# Dueling Network

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$



# Dueling Network

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$



# Training

- Dueling network,  $Q(s, a; \mathbf{w})$ , is an approximation to  $Q^*(s, a)$ .
- Learn the parameter,  $\mathbf{w} = (\mathbf{w}^A, \mathbf{w}^V)$ , in the same way as the other DQNs.
- Tricks can be used in the same way.
  - Prioritized experience replay.
  - Double DQN.
  - Multi-step TD target.

**Overcome Non-identifiability**

# Problem of Non-identifiability

- **Equation 1:**  $Q^*(s, a) = V^*(s) + A^*(s, a).$
- **Equation 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a)$

**Question:** Why is the zero term necessary?



# Problem of Non-identifiability

- **Equation 1:**  $Q^*(s, a) = V^*(s) + A^*(s, a)$ .
- Equation 1 has the problem of *non-identifiability*.

# Problem of Non-identifiability

- **Equation 1:**  $Q^*(s, a) = V^*(s) + A^*(s, a)$ .
- Equation 1 has the problem of *non-identifiability*.
  - Let  $V' = V^* + 10$  and  $A' = A^* - 10$ .

# Problem of Non-identifiability

- **Equation 1:**  $Q^*(s, a) = V^*(s) + A^*(s, a)$ .
- Equation 1 has the problem of *non-identifiability*.
  - Let  $V' = V^* + 10$  and  $A' = A^* - 10$ .
  - Then  $Q^*(s, a) = V^*(s) + A^*(s, a) = V'(s) + A'(s, a)$ .

# Problem of Non-identifiability

- **Equation 1:**  $Q^*(s, a) = V^*(s) + A^*(s, a)$ .
- Equation 1 has the problem of *non-identifiability*.
  - Let  $V' = V^* + 10$  and  $A' = A^* - 10$ .
  - Then  $Q^*(s, a) = V^*(s) + A^*(s, a) = V'(s) + A'(s, a)$ .
- Why is non-identifiability a problem?

# Problem of Non-identifiability

- **Equation 2:**  $Q^*(s, a) = V^*(s) + A^*(s, a) - \max_a A^*(s, a)$ .
- Equation 2 does not have the problem.

# Dueling Network

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \max_a A(s, a; \mathbf{w}^A).$$

**Alternative:**

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \text{mean}_a A(s, a; \mathbf{w}^A).$$

# Summary

- **Dueling network:**

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \underset{a}{\text{mean}} A(s, a; \mathbf{w}^A).$$

# Summary

- **Dueling network:**

$$Q(s, a; \mathbf{w}) = V(s; \mathbf{w}^V) + A(s, a; \mathbf{w}^A) - \underset{a}{\text{mean}} A(s, a; \mathbf{w}^A).$$

- Dueling network controls the agent in the same way as DQN.
- Train dueling network by TD in the same way as DQN.
- (Do not train  $V$  and  $A$  separately.)



**Thank you!**