Contents

1 Introduction to Web Design and HTML **4**

1.1 Core Concepts in Web Design . . . 4

1.1.1 Basic Components of the Web . . . 4

1.1.2 Basic Relationship . . . 5

1.1.3 Advantages of Website . . . 5

1.2 Website . . . 5

1.2.1 Website Structure . . . 5

1.2.1.1 Common Pages in a Website . . . 5

1.2.1.2 Types of Website Structure . . . 5

1.2.2 Web Portal . . . 6

1.2.3 Types of Website . . . 6

1.2.3.1 Static Website . . . 6

1.2.3.2 Dynamic Website . . . 7

1.2.3.3 Comparison between Static and Dynamic Website . . . 8

1.2.4 Types of Webpage Based on Location . . . 8

1.2.5 Website Classification by Purpose . . . 8

1.3 Web Browser and Search Engine . . . 9

1.3.1 Web Browser . . . 9

1.3.1.1 Functions of Web Browser . . . 9

1.3.2 Web Browsing . . . 9

1.3.2.1 Methods of Web Browsing . . . 9

1.3.3 Search Engine . . . 9

1.3.3.1 Functions of Search Engine . . . 10

1.3.4 Difference Between Browser and Search Engine . . . 10

1.4 IP Address . . . 10

1.4.1 Purpose of IP Address . . . 10

1.4.2 Types of IP Address . . . 11

1.4.2.1 Network ID and Host ID . . . 11

1.5 Domain Name and Domain Name System (DNS) . . . 11

1.5.1 Some Technical Terms . . . 12

1.5.2 Domain Registration and ICANN . . . 12

1.5.3 Types of Domain . . . 12

1.5.4 Common Top Level Domains / Generic TLDs . . . 12

1.5.5 Country Code Top Level Domains . . . 13

1.6 Web Hosting . . . 13

1.6.1 Types of Web Hosting . . . 13

1.6.1.1 Based on Platform or Operating System . . . 14

1.6.1.2 Based on Facilities . . . 14

1.6.1.3 Email Services with Hosting . . . 14

1.6.2 Difference between Domain Name and Web Hosting . . . 14

1.7 URL (Uniform Resource Locator) . . . 15

1.7.1 Components of URL . . . 15

1.8 Protocol . . . 16

1.8.1 Common Internet Protocols . . . 16
1.8.2 HTTP . . . 16
1.8.2.1 Functions of HTTP . . . 16
1.8.3 FTP . . . 16
1.8.3.1 Functions of FTP . . . 16
1.8.3.2 Types of FTP Access . . . 17
1.9 Web Communication . . . 17
1.9.1 Correct Overall Idea . . . 17
1.9.2 Client-Server System . . . 17
1.9.3 Website Creation Side . . . 17
1.9.4 User Access Side . . . 18
1.10 Difference between IP Address, Domain Name, DNS and URL . . . 18
1.11 HTML (HyperText Markup Language) . . . 19
1.11.1 Concept of HTML . . . 19
1.11.2 Markup Language vs Programming Language . . . 19
1.11.3 Short History of HTML . . . 19
1.11.4 Advantages of HTML . . . 20
1.11.5 Limitations of HTML . . . 20
1.12 HTML Building Blocks . . . 20
1.12.1 HTML Tag . . . 20
1.12.2 Classification of HTML Tags . . . 21
1.12.3 HTML Element . . . 21
1.12.4 HTML Attribute . . . 21
1.12.5 HTML Comments . . . 22
1.13 HTML Document Structure . . . 22
1.13.1 Basic Skeleton . . . 22
1.13.2 Head Section . . . 22
1.13.3 Body Section . . . 23
1.13.4 Block-Level and Inline Elements . . . 23
1.13.5 Body Tag Attributes . . . 23
1.14 Creating and Running an HTML File . . . 24
1.15 Headings, Paragraphs and Line Breaks . . . 24
1.15.1 Heading Elements . . . 24
1.15.2 Paragraph, Break and Horizontal Rule . . . 24
1.16 Text Formatting Tags . . . 25
1.17 Font, Color, Style and Bangla Text . . . 26
1.17.1 Font Tag . . . 26
1.17.2 Color Values . . . 26
1.17.3 Style Attribute . . . 26
1.17.4 Bangla Text in HTML . . . 27
1.18 HTML Lists . . . 27
1.18.1 Ordered List . . . 27
1.18.2 Unordered List . . . 27
1.18.3 Description List . . . 28
1.18.4 Nested List . . . 28
1.19 Hyperlinks in HTML . . . 28

1.19.1 Anchor Tag . . . 28
1.19.2 Internal and External Links . . . 29
1.19.3 Relative and Absolute Paths . . . 29
1.19.4 Hyperlink Attributes . . . 29
1.19.5 Advantages of Hyperlink . . . 29
1.20 Images, Audio and Video . . . 29
1.20.1 Adding Images . . . 30
1.20.2 Advantages and Disadvantages of Web Graphics . . . 30
1.20.3 Inline and External Images . . . 30
1.20.4 Image Syntax and Attributes . . . 30
1.20.5 Clickable Image . . . 31
1.20.6 Audio and Video . . . 31
1.21 HTML Tables . . . 31
1.21.1 Parts of a Table . . . 31
1.21.2 Table Elements . . . 31
1.21.3 Basic Table . . . 32
1.21.4 Table Attributes . . . 32
1.21.5 Cellspacing and Cellpadding . . . 33
1.21.6 Colspan and Rowspan . . . 33
1.21.7 Table Background Color . . . 33
1.22 HTML Layout and Containers . . . 34
1.22.1 Webpage Layout . . . 34
1.22.2 Methods of Creating Layout . . . 34
1.22.3 Div and Span . . . 34
1.22.4 Semantic Layout Tags . . . 35
1.23 HTML Forms . . . 35
1.23.1 Form Element and Attributes . . . 35
1.23.2 Form Tags . . . 35
1.23.3 Input Types . . . 36
1.23.4 Form Example . . . 36
1.24 Designing and Publishing a Website . . . 37
1.24.1 Designing a Webpage . . . 37
1.24.2 Steps for Better Website Design . . . 37
1.24.3 Publishing a Website . . . 37
1.25 Final Summary of the Chapter . . . 38

Chapter – 1

Introduction to Web Design and HTML

1.1 Core Concepts in Web Design

Internet

Internet is the connection of millions of computers worldwide that allows them to communicate and share information.

World Wide Web

World Wide Web is a system of sharing information over the Internet by using hypertext documents, which are linked together and can be accessed through a web browser.

Note: The Internet is the hardware, wires and protocols: the global infrastructure. The World Wide Web is a service, like email or online gaming, that runs on top of that infrastructure.

1.1.1 Basic Components of the Web

The web works through the combined use of three main components:

1. **HTML**: A markup language used to write and structure webpages.
2. **HTTP**: The protocol used to transfer webpages between web server and browser.
3. **Web Browser**: The software that receives, interprets and displays webpage content for the user.

Hypertext document file

A hypertext document is a type of document that contains links to other documents, allowing users to navigate between them easily.

- Like images this is a file type with extension .html or .htm.
- It is made by using HTML (HyperText Markup Language).

Webpage

A webpage is a single hypertext document or page that is displayed in a web browser. It is also called a web document. It can contain text, audio, video, still images, animation, links of other webpages and other multimedia content.

Website

A website is a collection of related webpages stored under a common domain name and connected through hyperlinks.

Web design

Web design is the process of planning, creating, arranging and presenting information on the World Wide Web. It includes the design of webpages, navigation system, content layout, links, images, and user interaction.

1.1.2 Basic Relationship

- A webpage is one single page.
- A website contains multiple related webpages.
- The first page shown after entering a website is called the **homepage**.
- Webpages are connected using hyperlinks.
- A web browser is used to view webpages.

Core Idea

HTML → Hypertext document files → Webpage $\xrightarrow{\text{Web Design}}$ Website → World Wide Web → Internet

1.1.3 Advantages of Website

- Information can be published and accessed easily.
- A website can be accessed from anywhere in the world.
- It is available twenty-four hours a day.
- It reduces the need for physical communication.
- It supports text, images, audio, video and links.
- Information can be updated more easily than printed documents.
- It is useful for education, business, news, communication and entertainment.

1.2 Website

1.2.1 Website Structure

Website Structure

Website structure refers to the way webpages are organized, designed and interconnected within a website.

1.2.1.1 Common Pages in a Website

- **Home Page**: The first page displayed after entering a website. It works as the entry page or index page of the website and gives the main idea, purpose and links to important sections.
- **Main Section Page**: A page that represents a major topic or section of the website. It works like a menu or site index and links users to related subsection pages.
- **Subsection Page**: A page placed under a main section to present specific information. It should contain relevant content and navigation links to move through the website.

1.2.1.2 Types of Website Structure

1.2.1.2.1 Hierarchical Structure

- Pages are arranged like a tree.
- Starts from the homepage and branches into main sections and subsections.
- It is easy to manage and most commonly used.
- Users can easily understand their current position in the website.

1.2.1.2.2 Linear Structure

- Pages are connected in a fixed sequence.
- Users move step-by-step using links such as Next, Previous or Last.
- Suitable for tutorials, forms, sign-up pages or small documents.

1.2.1.2.3 Network Structure

- Each page is connected with many other pages.
- Users can move from one page to another without a fixed path.
- It gives flexibility, but may confuse users if navigation is not clear.

1.2.1.2.4 Hybrid Structure

- Combination of multiple structures.
- Usually combines hierarchical and linear or network structure.
- Most modern websites follow this model.
- Navigation tools such as menu, button and links should be clear and consistent.

1.2.2 Web Portal

Web Portal

A web portal is a website that collects important links, content and services from different sources in one place.

- It helps users access different information and services easily.
- Example: a government portal, education portal or service portal.

1.2.3 Types of Website

There are two main types of websites based on how their content works:

- Static Website
- Dynamic Website

1.2.3.1 Static Website

Static Website

A static website displays fixed content that does not change unless the source files are manually updated.

- Built mainly using HTML and CSS.

Intermediate-Higher Secondary

- Content remains fixed for all users.
- Users cannot directly input or update information.
- No database connection is normally required.
- Communication is mainly one-way: server to client.
- Loads quickly because pages are already prepared.

1.2.3.1.1 Advantages of Static Website

- Low development and hosting cost.
- Easy to develop, test and maintain.
- Loads quickly, even on slower connections.
- More secure because there is usually no database or server-side processing.
- Easier for search engines to index.

1.2.3.1.2 Disadvantages of Static Website

- Content cannot change automatically.
- User input or update is not supported.
- Updating content requires manual editing and re-uploading.
- Large static websites become difficult to control.
- Quality design can be time-consuming.

1.2.3.2 Dynamic Website

Dynamic Website

A dynamic website generates or changes content at runtime based on user input, request or database.

- Uses server-side scripting such as PHP, ASP.NET, JSP or similar technologies.
- Usually uses a database such as SQL or MySQL.
- Content can change for different users.
- Users can provide input and update information.
- Suitable for interactive services such as login, search, comment, online exam or e-commerce.

1.2.3.2.1 Advantages of Dynamic Website

- Content can be updated quickly.
- Can display specific pages or information for specific users.
- Handles large amounts of information using database.
- Supports user input and interactive features.
- Attractive and interactive layouts can be prepared.

1.2.3.2.2 Disadvantages of Dynamic Website

- Development and maintenance are more complex.
- Cost is higher than static websites.
- Loading may be slower because database and server processing are used.
- Security management is more important because input and database are involved.

1.2.3.3 Comparison between Static and Dynamic Website

Feature	Static Website	Dynamic Website
Content	Fixed content.	Content can change at runtime.
Loading Speed	Loads faster because pages are already prepared.	Loads slower because content may be generated dynamically.
Database	Does not usually use a database.	Usually uses a database to store data.
Security	More secure because there is less server-side processing.	Less secure than static if input and database are not properly protected.
User Input	User input or update is not supported.	User input and update are supported.
Technology	HTML and CSS are enough.	Requires HTML, CSS, server-side language and database.
Development	Easy to create and maintain.	Requires skilled developers and more control.
Update	Source files must be edited and uploaded again.	Content can be modified through server application or database.
Pages	Usually has a fixed number of pages.	Many pages can be generated dynamically.
Example Use	Simple information website.	E-commerce, online exam, login system or database website.

Table 1.1: Comparison between Static and Dynamic Website

1.2.4 Types of Webpage Based on Location

- **Local Webpage**: A webpage stored and opened from the user's own computer or local storage. It can be viewed without internet connection and without uploading it to a web server.
- **Remote Webpage**: A webpage stored on another computer or remote web server. It requires internet connection and a URL to access.

1.2.5 Website Classification by Purpose

- **Archive Site**: Stores old or important information for later use.
- **Business Site**: Presents information about a business, product or service.
- **E-commerce Site**: Supports buying and selling products or services online.
- **Community Site**: Connects people with common interests.
- **Database Site**: Provides searchable or organized data from a database.
- **Development Site**: Shares software, tools, documentation or project resources.
- **Directory Site**: Lists links, organizations, services or resources by category.
- **Download Site**: Provides files, software, documents or media for download.
- **Game Site**: Provides online games or gaming-related content.
- **Information Site**: Publishes subject-based information for readers.

- **News Site**: Publishes current news and updates.

Summary

Static websites are simple and fast, whereas dynamic websites are flexible and interactive.

1.3 Web Browser and Search Engine

1.3.1 Web Browser

Web Browser

A web browser is application software used to access, retrieve, interpret and display webpages.

A browser works like an interpreter. It receives webpage code from the web server, converts it into visual output and shows the webpage on the screen.

1.3.1.1 Functions of Web Browser

- Opens websites and webpages using a URL.
- Interprets HTML and other webpage code.
- Displays text, images, links, forms and other webpage contents.
- Helps users move from one webpage to another through hyperlinks.
- Can download information or files from websites.
- Can upload information through forms or file upload systems.
- Can use search engines when the exact web address is not known.
- Example: Google Chrome, Mozilla Firefox, Microsoft Edge, Safari, Opera.

1.3.2 Web Browsing

Web Browsing

Web browsing is the process of visiting and viewing webpages stored on different web servers through a web browser.

1.3.2.1 Methods of Web Browsing

- **Direct Browsing by URL**: The user types the known website address in the browser address bar and opens the webpage directly.
- **Browsing through Search Engine**: The user searches with keywords when the exact website address is not known.

1.3.3 Search Engine

Search Engine

A search engine is a tool that helps users find information on the internet by searching indexed webpages and showing relevant results.

A search engine collects and organizes webpage information. When a user searches with a word or phrase, it shows a list of related webpages.

1.3.3.1 Functions of Search Engine

- Helps users find information when the exact website address is unknown.
- Searches indexed webpages using keywords.
- Displays related webpage links as search results.
- Helps users reach websites quickly through the result list.
- Example: Google, Bing, Yahoo, DuckDuckGo, Ask, Yandex, Baidu, WolframAlpha (computational information-based search tool).

1.3.4 Difference Between Browser and Search Engine

Aspect	Web Browser	Search Engine
Meaning	Software used to open and display webpages.	Tool used to find information and webpages on the internet.
Main Work	Reads webpage code and shows the webpage visually.	Searches indexed webpages and shows related results.
Use	Used when opening a website or viewing a webpage.	Used when the needed website or exact address is not known.
Input	URL or website address.	Keyword, phrase or question.
Examples	Google Chrome, Mozilla Firefox, Microsoft Edge, Safari, Opera.	Google, Bing, Yahoo, DuckDuckGo, Ask.

Table 1.2: Difference between Web Browser and Search Engine

Summary

A web browser opens and displays webpages, while a search engine helps find webpages and information.

1.4 IP Address

IP Address

IP Address stands for Internet Protocol Address. It is a unique numerical address used to identify a device connected to a network on the internet.

Note: An IP address works like the digital address of a device. When sender sends data to a receiver, the receiver's IP address is used to ensure that the data reaches the correct destination.

1.4.1 Purpose of IP Address

- It identifies a device in a network.
- It helps send data to the correct destination.

- It allows communication between client and server.
- It is necessary for internet-based communication.

1.4.2 Types of IP Address

There are two main types of IP addresses:

- **IPv4**: 32-bit address, with four 8-bit octets, 1 octet = 8 bits, usually written in four decimal parts.
  Example: `11000000.10101000.00000001.00000001` $\xrightarrow{\text{in decimal}}$ `192.168.1.1`
- **IPv6**: 128-bit address, with eight 16-bit words, usually written in hexadecimal format.
  Example: `2001:0db8:85a3:0000:0000:8a2e:0370:7334`

1.4.2.1 Network ID and Host ID

- The internet is a network of many networks.
- Each network has many hosts (computers, mobiles, servers etc.) in it.
- So each network and each device needs an unique identifier for communication.
- This is done by dividing the IP address into two parts: Network ID and Host ID.
  - → **Network ID**: identifies the network the device is connected to.
    Example: in `192.168.1.1`, the network ID is `192.168.1.`.
  - → **Host ID**: identifies the specific device inside that network.
    Example: in `192.168.1.1`, the host ID is `1`.

Example 1.1

Q: Why is IP address required?

A: IP address is required because every device in a network must be uniquely identified. It helps data packets travel from the sender to the correct receiver.

Conclusion: Without IP addresses, devices on the internet could not communicate properly.

1.5 Domain Name and Domain Name System (DNS)

Domain Name

A **domain name** is a human-readable name used to identify a website on the internet.

Note: IP addresses are difficult for humans to remember. For this reason, domain names act as an alias for the numeric IP address.

DNS

DNS (Domain Name System) is the system that converts a readable domain name into its corresponding numeric IP address so the browser can load the resource.

The Bridge

- **IP Address** (192.168.1.1): used by computers in numeric form.
- **Domain Name** (*google.com*): used by humans in readable form.

- **DNS**: works like a phonebook that connects the readable name with the numeric address.

1.5.1 Some Technical Terms

- **FQDN** (Fully Qualified Domain Name): The complete domain name that identifies a specific host on the internet.
- **Subdomain**: An additional name placed before the main domain name, such as `www`.
- **Web Hosting**: The server space where website files are stored so users can access them through the internet.
- **Difference**: The *Domain* is your address; *Hosting* is the house where your data lives.

1.5.2 Domain Registration and ICANN

- **Domain Registration** is the process of reserving a domain name for use on the internet. It involves choosing a unique name and registering it with a domain registrar.
- Every registered domain name must be unique. If the same name could be registered by many people, users would not know which website to visit.
- For this reason, domain names are controlled through registration authorities.
- **ICANN** stands for "Internet Corporation for Assigned Names and Numbers".
- ICANN coordinates the global domain name and IP address system.
- Domain names are usually registered through domain registrars approved under this system.
- A registered domain gives a website a unique identity on the internet.

1.5.3 Types of Domain

- **Top Level Domain (TLD)** → The last part of a domain name. It shows the highest level/category of the domain.

  → **gTLD (Generic TLD)** → General TLD, not tied to a country. Examples: `.com`, `.org`, `.net`

  → **ccTLD (Country Code TLD)** → Country-based TLD. Examples: `.bd`, `.uk`, `.in`
- **Second Level Domain (SLD) / Main Domain Name** → The unique name chosen by the owner. It identifies the website or organization. Examples: `google`, `bbc`
- **Subdomain / Host Name** → A name placed before the main domain to identify a service or section. Examples: `www`, `mail`, `blog`

Example: Domain Structure

$$\underbrace{\texttt{mail}}_{\substack{\text{Subdomain}\\ \text{/ Host Name}}} \;.\; \underbrace{\texttt{google}}_{\substack{\text{Main Domain}\\ \text{/ SLD}}} \; \underbrace{\texttt{.com}}_{\substack{\text{TLD}\\ \text{gTLD}}}$$

$$\underbrace{\texttt{www}}_{\substack{\text{Subdomain}\\ \text{/ Host Name}}} \;.\; \underbrace{\texttt{bbc}}_{\substack{\text{Main Domain}\\ \text{/ SLD}}} \; \underbrace{\texttt{.co}}_{\substack{\text{Commercial}\\ \text{category}}} \; \underbrace{\texttt{.uk}}_{\substack{\text{TLD}\\ \text{ccTLD}}}$$

1.5.4 Common Top Level Domains / Generic TLDs

Domain	Used For
.com	Commercial organizations
.net	Network-related services
.edu	Educational institutions
.gov	Government organizations
.org	Non-profit organizations
.mil	Military organizations
.int	International organizations
.biz	Business organizations
.info	Information-based websites

Table 1.3: Common Top Level Domains

1.5.5 Country Code Top Level Domains

Code	Country	Code	Country
.bd	Bangladesh	.cn	China
.au	Australia	.fi	Finland
.in	India	.fr	France
.br	Brazil	.hk	Hong Kong
.uk	United Kingdom	.us	United States

Table 1.4: Common Country Code Top Level Domains

1.6 Web Hosting

Web Hosting

Web hosting means storing website files on an internet-connected server so that the website can be uploaded and accessed online.

- Hosting space is usually provided by an ISP or hosting company.
- Hosting cost depends on storage space, bandwidth, server resources and support.
- Different hosting services can be obtained from hosting providers by paying rent or service charge.
- Without hosting, a website's files cannot be publicly accessed through the internet.

1.6.1 Types of Web Hosting

1.6.1.1 Based on Platform or Operating System

- **Windows Hosting**: Hosting on a Windows server. It is mainly used for websites made with ASP/ASP.NET and Microsoft SQL Server.
- **Linux Hosting**: Hosting on a Linux server. It is mainly used for websites made with PHP and MySQL.

1.6.1.2 Based on Facilities

- **Free Hosting**: Basic hosting for small personal websites. It costs little or nothing, but bandwidth, security and domain facilities are limited.
- **Shared Hosting**: Many websites share the same server resources. It is cheaper, but speed, security, email, database and bandwidth are limited.
- **Dedicated Hosting**: One website or user gets a full server. It gives better speed, security, bandwidth, database support and control, so it is suitable for large websites.
  - → **Managed Hosting**: The hosting company manages setup, software, security, maintenance and control panel support. It is easier but more costly.
  - → **Unmanaged Hosting**: The website owner manages setup, software, security and maintenance. It is cheaper but needs technical skill.
- **Collocated Hosting**: The owner keeps their own server in the hosting company's data center and uses the company's power, network and support.

1.6.1.3 Email Services with Hosting

Hosting providers may also provide domain-based email accounts, such as `info@example.com`.

- **POP** (Post Office Protocol): downloads email from the server to a client device.
- **IMAP** (Internet Message Access Protocol): keeps email on the server and synchronizes it across devices.
- **Web-based Email / Webmail**: allows users to read and send email through a web browser.

1.6.2 Difference between Domain Name and Web Hosting

Domain Name	Web Hosting
The unique readable name of a website.	The server space where website files are stored.
Must be registered with a domain registrar.	Must be rented or configured from a hosting provider.
One domain name identifies one main web address.	One hosting account may contain one or many websites, depending on the plan.
Users cannot easily reach a website without a domain name or URL.	A website cannot be publicly available without hosting.
Domain registration does not require server configuration.	Hosting requires server configuration, storage, bandwidth and control panel settings.
Bandwidth is not the main issue in domain registration.	Bandwidth is an important issue in hosting.
The quality of the domain registrar is less visible to normal visitors.	The quality of the hosting provider affects speed, uptime, security and support.

Domain Name	Web Hosting

Table 1.5: Difference between Domain Name and Web Hosting

1.7 URL (Uniform Resource Locator)

URL

A URL (Uniform Resource Locator) is the complete web address used to locate a resource on the internet.

Note: A URL identifies where a webpage or file is located and also tells the browser which protocol should be used to access it.

1.7.1 Components of URL

- **Protocol**: Defines the communication rule used to access the resource. Examples: `http://`, `https://`, `ftp://`
- **Domain Name**: Identifies the website or server. Example: `www.example.com`
- **Path**: Specifies the exact location of a file or page inside the server. Example: `/folder/page.html`

Structure of URL

$$\text{URL} = \text{Protocol} + \text{Domain Name} + \text{Path}$$

$$\text{URL} = \underbrace{\texttt{https://}}_{\text{Protocol}}\underbrace{\texttt{www.example.com}}_{\text{Domain Name}}\underbrace{\texttt{/folder/page.html}}_{\text{Path}}$$

Example: URL Structure

$$\underbrace{\texttt{https://}}_{\text{Protocol}}\ \underbrace{\texttt{www}}_{\substack{\text{Subdomain}\\ \text{/ Host Name}}}\ .\ \underbrace{\texttt{example}}_{\substack{\text{Main Domain}\\ \text{/ SLD}}}\ \underbrace{\texttt{.com}}_{\text{TLD}}\underbrace{\texttt{/folder/page.html}}_{\text{Path}}$$

$$\underbrace{\texttt{http://}}_{\text{Protocol}}\ \underbrace{\texttt{www}}_{\substack{\text{Subdomain}\\ \text{/ Host Name}}}\ .\underbrace{\texttt{corneliusenterprises}}_{\substack{\text{Main Domain}\\ \text{/ SLD}}}\ \underbrace{\texttt{.co}}_{\substack{\text{Commercial}\\ \text{category}}}\ \underbrace{\texttt{.uk}}_{\substack{\text{Country Code}\\ \text{TLD}}}$$

Summary

A URL gives both the access method and the location of a web resource.

1.8 Protocol

Protocol

A protocol is a set of rules that controls how data is transmitted between computers on the internet.

1.8.1 Common Internet Protocols

- **HTTP** (Hyper Text Transfer Protocol): Used to transfer webpages between browser and web server.
- **FTP** (File Transfer Protocol): Used to upload and download files through the internet.
- **IP** (Internet Protocol): Handles addressing and routing so data packets reach the correct destination.
- **TCP/IP** (Transmission Control Protocol / Internet Protocol): Main protocol system used for internet communication.
- **SMTP** (Simple Mail Transfer Protocol): Used for sending email.
- **POP** (Post Office Protocol): Used for receiving or downloading email from a mail server.
- **VoIP** (Voice over Internet Protocol): Used for voice communication through the internet.

1.8.2 HTTP

HTTP

HTTP stands for Hyper Text Transfer Protocol. It is the web protocol used to exchange data between a browser and a web server.

Note: HTTP is used when a user visits or browses a webpage. The browser sends a request to the web server, and the server sends the requested webpage or resource back to the browser.

1.8.2.1 Functions of HTTP

- Creates a connection between the browser and the server.
- Sends the browser's request to the server.
- Brings the requested webpage or resource from the server to the browser.
- Disconnects the browser and server after the request-response process.

1.8.3 FTP

FTP

FTP stands for File Transfer Protocol. It is a protocol used to exchange files between computers through the internet.

Note: FTP is mainly used to upload and download files between a local computer and a remote computer or server. It is commonly used to upload website files to a hosting server.

1.8.3.1 Functions of FTP

- Transfers website files, documents, books, images, software and other normal files.
- **Download**: Receives a file from a remote computer or server to the local computer.

- **Upload**: Sends a file from the local computer to a remote computer or server.
- FTP software such as **WS-FTP** and **Fetch** can be used for upload and download.

1.8.3.2 Types of FTP Access

- **Private Access**: Requires username and password to access server files.
- **Public Access**: Allows users to access selected files without private login.

HTTP vs FTP

HTTP is used to transfer hypertext/webpage files between browser and web server. FTP is used to transfer normal files such as documents, images, software and website files between computers.

1.9 Web Communication

Web Communication

Web communication is the process of exchanging data between a client browser and a web server through the internet.

Note: The World Wide Web works on top of the internet using a client-server system. The browser works as the client, and the web server stores and sends the requested webpage or resource.

1.9.1 Correct Overall Idea

- **Internet**: The global network infrastructure that connects computers and servers.
- **World Wide Web**: A service that runs on the internet and uses webpages, hyperlinks, browsers and web servers.
- **Website Developer**: Creates website files using HTML, CSS, images, scripts and other resources.
- **Web Hosting**: Stores the website files on an internet-connected server.
- **IP Address**: The numerical address of the hosting server.
- **Domain Name**: The human-readable name registered through a domain registrar.
- **DNS**: Connects the domain name with the hosting server's IP address.
- **URL**: The complete address used by the browser to request a specific webpage or file.
- **Protocol**: The rule used for communication, such as HTTP or HTTPS.

1.9.2 Client-Server System

- A website works using two main parts: **client** and **server**.
- **Client**: The user's computer or browser that requests a webpage.
- **Server**: The computer where webpages or website files are stored and protected.
- The client needs an internet connection and a web browser to request webpages.
- The web server uses HTTP/HTTPS to respond to the client's request and supply webpages.

1.9.3 Website Creation Side

1. The developer creates hypertext documents using **HTML**.

2. Other files such as CSS, images, audio, video and scripts may also be added.
3. These files are organized together as a website project or website folder.
4. The website folder is uploaded to a web hosting server.
5. The hosting server has an IP address.
6. A domain name is registered through a domain registrar.
7. DNS records connect the domain name with the hosting server's IP address.

1.9.4 User Access Side

1. The user enters a URL in the web browser.
2. The browser reads the protocol, domain name and path from the URL.
3. DNS converts the domain name into the server's IP address.
4. The browser connects to the correct web server using HTTP or HTTPS.
5. The browser sends an HTTP request for the specific webpage or file.
6. The server searches for the requested HTML document or resource.
7. The server sends the requested data back as an HTTP response.
8. The browser interprets the HTML and related files.
9. The webpage is displayed on the screen.

Web Working Flow

Developer creates website files → files are uploaded to hosting server → domain name is connected to server IP through DNS → user enters URL → browser requests the file → server responds → browser displays the webpage.

1.10 Difference between IP Address, Domain Name, DNS and URL

Aspect	IP Address	Domain Name	DNS	URL
Meaning	A unique numeric address used to identify a device or server on a network.	A human-readable name used to identify a website.	A system that converts a domain name into its corresponding IP address.	A complete web address used to locate a specific resource on the internet.
Main User	Computers and network devices.	Humans.	Browser and network system.	Browser and user.
Main Work	Finds the actual destination server or device.	Gives an easy readable name for a website.	Connects the domain name with the correct IP address.	Gives the access method and exact resource location.
Points To	A device or server.	A website name.	The IP address of a domain.	A webpage, file, image or resource.

Aspect	IP Address	Domain Name	DNS	URL
Form	Numeric form.	Readable word form.	Background lookup system.	Full address with protocol, domain and path.
Example	`142.250.190.78`	`google.com`	`google.com` → `142.250.190.78`	`https://www.example.com/folder/page.html`

Table 1.6: Difference between IP Address, Domain Name, DNS and URL

1.11 HTML (HyperText Markup Language)

HTML

HTML (HyperText Markup Language) is a markup language used to create webpages and web applications by describing how text, images, links, tables, forms and other contents should be organized and displayed in a browser.

HTML is not a programming language. It cannot process data, make decisions, or create a dynamic website by itself. It marks content with tags so that a browser can present that content as a webpage.

1.11.1 Concept of HTML

- HTML files are usually saved with the `.html` or `.htm` extension.
- A file created with HTML is generally known as a webpage or web document.
- HTML is platform independent; the same page can be opened in different operating systems and browsers.
- HTML can present text, audio, video, graphics, animation, hyperlinks, tables and attached contents.
- A conventional static webpage can be created with HTML, but dynamic or interactive behavior needs CSS, JavaScript, server-side scripts or databases.

1.11.2 Markup Language vs Programming Language

Markup Language	Programming Language
Uses tags to describe how content should be displayed.	Uses logic, variables, conditions and instructions to process data.
Cannot process data by itself.	Can process data and produce calculated results.
Cannot take and handle user input by itself.	Can take input, process it and produce output.
Example: HTML.	Example: C, JavaScript, Python, PHP.

Table 1.7: Difference between markup language and programming language

1.11.3 Short History of HTML

- Tim Berners-Lee invented HTML in 1990 while working at CERN in Geneva, Switzerland.
- HTML became widely known through the Mosaic browser developed by NCSA.

- HTML 2.0 was released in 1995.
- HTML 3.2 was released in January 1997.
- HTML 4.0 was released in December 1997.
- HTML5 is the modern major version; HTML 5.2 was released in December 2017.

1.11.4 Advantages of HTML

- It is a user-friendly open technology.
- It is used all over the world.
- Almost every web browser supports HTML documents.
- Its syntax is easy to learn and use.
- It can be written in any text editor.
- It is lightweight; normal HTML pages require less hosting space.
- It is not expensive and does not require a special license.

1.11.5 Limitations of HTML

- It can create static webpages but cannot create dynamic webpages by itself.
- It cannot process data or interact with a database.
- Large pages may require many lines of code.
- Security is limited because processing and validation are not handled by HTML alone.
- Complex websites require CSS, JavaScript and server-side technologies in addition to HTML.

Summary

HTML defines webpage structure. CSS controls presentation, JavaScript controls browser-side behavior, and server-side languages handle dynamic processing.

1.12 HTML Building Blocks

1.12.1 HTML Tag

HTML Tag

An HTML tag is a keyword enclosed in angle brackets that gives direction to the browser about how a content item should be structured or displayed.

Basic HTML Tag Syntax

```
<TagName> Content </TagName>
```

- The opening tag is also called the start tag. Example: `<p>`.
- The closing tag is also called the end tag. Example: `</p>`.
- The slash `/` is used in the closing tag.
- HTML tags are not case-sensitive, but lowercase tags are recommended by W3C.

1.12.2 Classification of HTML Tags

Tag Type	Meaning	Examples
Container tag	Has both opening and closing tags and contains content between them.	`<html>...</html>`, `<p>...</p>`
Empty tag	Has only an opening tag and no content between opening and closing tags.	` `, `<hr>`, `<img>`

Table 1.8: Container and empty HTML tags

In modern HTML examples, empty elements may be written with a closing slash, such as `<br/>` and `<hr/>`. Closing paired tags properly is important because missing end tags can produce unexpected output.

1.12.3 HTML Element

HTML Element

An HTML element is the complete unit formed by a start tag, element content and an end tag.

Element Structure

$$\text{Element} = \text{Start Tag} + \text{Content} + \text{End Tag}$$

For example, in `<p align="left">This is HTML class</p>`, the start tag is `<p align="left">`, the content is `This is HTML class`, and the end tag is `</p>`.

1.12.4 HTML Attribute

Attribute

An attribute is a special word written inside the start tag to give extra information or control the behavior, appearance or value of an HTML element.

Attribute Syntax

```
<TagName AttributeName="Attribute Value"> Content </TagName>
```

- An attribute has two parts: attribute name and attribute value.
- Attributes are written in the start tag, not in the end tag.
- Multiple attributes can be used in one tag.
- Lowercase attribute names are preferred.
- Attribute values are usually written inside double quotation marks.
- If an attribute value contains spaces, quotation marks are required.
- Single quotation marks can also be used when needed.

```
<p align="left">This is HTML class</p>
```

Listing 1.1: Element and Attribute Parts

What to notice

- `align` is the attribute name.
- `left` is the attribute value.
- The attribute is written in the opening `p` tag.

1.12.5 HTML Comments

Comments are written for explanation inside source code. Browsers ignore comments, so they are not displayed on the webpage.

```
<!-- This is a comment -->
```

Listing 1.2: HTML Comment

1.13 HTML Document Structure

HTML Document Structure

An HTML document is mainly formed with two sections inside the `html` element: the `head` section and the `body` section.

1.13.1 Basic Skeleton

This example shows the minimum structure of a valid HTML page. The `head` section stores information about the page, while the `body` section stores visible content.

```
<!DOCTYPE html>
<html>
<head>
    <title>Page Title</title>
</head>
<body>
    Content goes here
</body>
</html>
```

Listing 1.3: Basic HTML Document Structure

Rendered output

Content goes here

1.13.2 Head Section

The head section contains document-related information such as document title, metadata, keywords, stylesheet links and scripts. This information is important for the browser and search engines, but most of it is not displayed as body content.

Element	Type	Use
`title`	Container	Sets the page title shown in the browser tab. A short useful title is preferred; no HTML tag should be written inside `title`.
`meta`	Empty	Stores document information such as charset, author, description or keywords.
`link`	Empty	Connects an external file such as a CSS stylesheet.
`base`	Empty	Sets a base URL for relative links in a document.
`style`	Container	Stores internal CSS rules.
`script`	Container	Stores or connects script commands.

Table 1.9: Common elements used in the HTML head section

1.13.3 Body Section

- The body section starts with `<body>` and ends with `</body>`.
- Text, headings, paragraphs, lists, tables, images, links and forms are placed inside `body`.
- Browsers display the visible content written inside the body section.

1.13.4 Block-Level and Inline Elements

Element Type	Behavior	Examples
Block-level element	Starts on a new line and usually takes the full available width.	`div`, `p`, `h1`, `ul`, `li`
Inline element	Does not start a new line; it stays inside the flow of text.	`a`, `b`, `span`, `strong`

Table 1.10: Block-level and inline HTML elements

1.13.5 Body Tag Attributes

The following old body attributes are important for exam/reference recognition. Modern webpages should use CSS instead.

Attribute	Use
`bgcolor`	Sets the page background color. Example: `<body bgcolor="green">`.
`background`	Sets an image as the page background. Example: `<body background="watermark.jpg">`.
`text`	Sets the color of normal page text.
`link`	Sets the color of unvisited hyperlinks.
`vlink`	Sets the color of visited hyperlinks.
`alink`	Sets the color of the active link while the mouse/cursor is on it.

Attribute	Use

Table 1.11: Old body attributes used in HTML

1.14 Creating and Running an HTML File

1. Open a simple text editor such as Notepad.
2. Write the HTML code.
3. Save the file using the `.html` or `.htm` extension.
4. Open the saved file in a web browser.
5. Edit the source file again when changes are needed, then refresh the browser.

Summary

HTML source code is written in a text editor, saved as an HTML file, and interpreted by a browser to display the webpage.

1.15 Headings, Paragraphs and Line Breaks

1.15.1 Heading Elements

HTML provides six heading levels from `h1` to `h6`. Headings are container elements and should be used to show document structure.

Tag	Use
`<h1>`	Largest and most important heading.
`<h2>`	Second-level heading.
`<h3>`	Third-level heading.
`<h4>`	Fourth-level heading.
`<h5>`	Fifth-level heading.
`<h6>`	Smallest heading.

Table 1.12: Heading elements in HTML

```
<h1>Dhaka Govt. College</h1>
<p>This is normal text</p>
<h6>Dhaka, Bangladesh</h6>
```

Listing 1.4: Heading Levels

1.15.2 Paragraph, Break and Horizontal Rule

- `<p>...</p>` creates a paragraph.
- `<br>` or `<br/>` creates a line break.
- `<hr>` or `<hr/>` creates a horizontal line.

▷ Browsers collapse extra spaces and normal source-code line breaks unless specific tags are used.

```
<p>This is the first paragraph.</p>
<p>This line has<br/>a manual break.</p>
<hr/>
<p>This is another paragraph.</p>
```

Listing 1.5: Paragraph, Break and Horizontal Rule

1.16 Text Formatting Tags

Formatting means giving proper shape and appearance to text on a webpage. Text formatting includes bold, italic, underline, big/small text, subscript, superscript, deleted text, inserted text, quotation and preformatted text.

Tag	Use	Example
`<b>`	Makes text bold.	`<b>Welcome</b>`
`<strong>`	Marks important text, usually shown bold.	`<strong>ICT</strong>`
`<i>`	Makes text italic.	`<i>Text</i>`
`<em>`	Emphasizes text, usually shown italic.	`<em>Text</em>`
`<u>`	Underlines text.	`<u>Text</u>`
`<ins>`	Shows inserted text, usually underlined.	`<ins>New</ins>`
`<big>`	Makes text bigger; exam/reference only.	`<big>Text</big>`
`<small>`	Makes text smaller.	`<small>Text</small>`
`<del>`	Shows deleted text.	`<del>Old</del>`
`<strike>`	Shows strikethrough text; exam/reference only.	`<strike>Old</strike>`
`<s>`	Shows text no longer correct; exam/reference recognition.	`<s>Old</s>`
`<sub>`	Shows subscript text.	`H<sub>2</sub>O`
`<sup>`	Shows superscript text.	`x<sup>2</sup>`
`<q>`	Shows inline quotation.	`<q>ICT</q>`
`<mark>`	Highlights/marks text.	`<mark>Important</mark>`
`<pre>`	Preserves spaces and line breaks.	`<pre>Text</pre>`

Table 1.13: Common text formatting tags

```
<p><b>Bold</b> and <i>italic</i> text</p>
<p>H<sub>2</sub>O and x<sup>2</sup></p>
<p><del>2017</del> <ins>2018</ins></p>
<pre>
This text keeps
spaces and line breaks.
</pre>
```

Listing 1.6: Text Formatting Example

1.17 Font, Color, Style and Bangla Text

1.17.1 Font Tag

The old `font` tag was used to control font face, color and size. It is exam/reference only, not modern practice. Modern webpages should use CSS.

Old Font Tag Syntax

```
<font face="fontname" color="fontcolor" size="number">Text</font>
```

Attribute	Use
`face`	Sets font type or font family. Example: `face="Verdana"`.
`color`	Sets font color using name, RGB or hexadecimal color.
`size`	Sets font size. Old HTML size values are usually from `1` to `7`; default is `3`. Relative values such as `+1` and `-1` may also appear.

Table 1.14: Attributes of the old font tag

1.17.2 Color Values

- **Named colors**: black, gray, silver, white, yellow, lime, aqua, fuchsia, red, green, blue, purple, maroon, olive, navy, teal.
- **RGB colors**: Written as `rgb(red, green, blue)`, where each value is from 0 to 255. Example: `rgb(255,0,0)` means red.
- **Hexadecimal colors**: Written as `#RRGGBB`. Example: `#FF0000` means red and `#000000` means black.

Color	HEX	RGB
White	`#FFFFFF`	`rgb(255,255,255)`
Black	`#000000`	`rgb(0,0,0)`
Red	`#FF0000`	`rgb(255,0,0)`
Green	`#00FF00`	`rgb(0,255,0)`
Blue	`#0000FF`	`rgb(0,0,255)`
Yellow	`#FFFF00`	`rgb(255,255,0)`
Orange	`#FFA500`	`rgb(255,165,0)`
Violet	`#EE82EE`	`rgb(238,130,238)`

Table 1.15: Common HTML color values

1.17.3 Style Attribute

The `style` attribute is used for inline CSS. It can control exact font family, font size, font style and color.

```
<p style="font-family: Arial; font-size: 18px; color: red;">
    This is styled text.
</p>
```

Listing 1.7: Font Styling with CSS

1.17.4 Bangla Text in HTML

Bangla text may appear in older books using old font names such as `SutonnyMJ`. This is exam/reference only. The modern method is Unicode with UTF-8 encoding.

- Bangla can be written using old `font face` values, but this is not portable.
- Bangla can be shown using CSS `font-family`, but the font must exist on the user device.
- Unicode Bangla text with UTF-8 is the correct modern method.
- File names, image paths and link paths should be written in English characters for better compatibility.

```
<!DOCTYPE html>
<html>
<head>
    <meta charset="UTF-8">
    <title>Bangla Text</title>
</head>
<body>
    <p>Bangla Unicode text can be written here.</p>
</body>
</html>
```

Listing 1.8: UTF-8 and Unicode Bangla

1.18 HTML Lists

HTML lists organize related items. The main list types are ordered list, unordered list and description list.

1.18.1 Ordered List

```
<ol>
    <li>Bangla</li>
    <li>English</li>
    <li>ICT</li>
</ol>
```

Listing 1.9: Ordered List

1.18.2 Unordered List

```
<ul>
    <li>Physics</li>
    <li>Chemistry</li>
    <li>Biology</li>
</ul>
```

Listing 1.10: Unordered List

1.18.3 Description List

```
<dl>
    <dt>HTML</dt>
    <dd>HyperText Markup Language</dd>
    <dt>HTTP</dt>
    <dd>HyperText Transfer Protocol</dd>
</dl>
```

Listing 1.11: Description List

1.18.4 Nested List

```
<ol>
    <li>Science
        <ul>
            <li>Physics</li>
            <li>Chemistry</li>
        </ul>
    </li>
    <li>Business Studies</li>
</ol>
```

Listing 1.12: Nested List

Summary

Use `ol` for sequence, `ul` for bullets, and `dl` for term-description pairs.

1.19 Hyperlinks in HTML

Hyperlink

A hyperlink is a connection that allows a user to move from one webpage, file or resource to another.

Hyperlinks create bridges between pages. A website homepage can connect to other pages through hyperlinks. HTML pages, images, sound files, videos and documents can be referenced by hyperlinks.

1.19.1 Anchor Tag

Hyperlink Syntax

```
<a href="url"> Link Text </a>
```

Two things are necessary to create a link: the destination address and the visible clickable text or object.

```
<a href="https://www.example.com">Visit Website</a>
```

Listing 1.13: Basic Anchor Link

1.19.2 Internal and External Links

- **Internal link**: Connects one page of a website with another page of the same website. Example: `studentinfo.html`.
- **External link**: Connects to a webpage or resource on another server or website. Example: `https://www.du.ac.bd/`.

1.19.3 Relative and Absolute Paths

Path Type	Meaning
Relative path	Gives a file location relative to the current HTML document. Example: `address.html` or `images/logo.jpg`.
Absolute path	Gives the complete address or fixed location. Example: `https://www.example.com/page.html`.

Table 1.16: Types of paths used in hyperlinks

1.19.4 Hyperlink Attributes

Attribute	Use
`href`	Determines the destination address of the hyperlink.
`title`	Shows tooltip text when the mouse is placed over the link.
`target`	Controls where the link opens. Common values are `_self` and `_blank`.
`name`	Used in older HTML to create a bookmark/anchor point inside a page. Modern HTML commonly uses `id`.

Table 1.17: Common hyperlink attributes

1.19.5 Advantages of Hyperlink

- Connects different pages of a website.
- Connects websites stored on different servers.
- Helps users find related information quickly.
- Saves time by allowing direct navigation.

```html
<p><a href="address.html">Our Address</a></p>
<p><a href="https://www.example.com" target="_blank">External Site</a></p>
<p><a href="#top">Go to Top</a></p>
```

Listing 1.14: Internal and External Links

1.20 Images, Audio and Video

1.20.1 Adding Images

Image Tag

The `img` tag is an empty element used to add an image to a webpage.

Images, diagrams, charts, maps and graphics make webpages more attractive and can reduce the amount of text needed for explanation.

1.20.2 Advantages and Disadvantages of Web Graphics

Advantages	Disadvantages
Can reduce the amount of text.	Images take longer to download than text.
Attracts user attention.	Some browsers or devices may not support all graphics properly.
Can be used as graphical navigation links.	Too many images can make a page slow or heavy.

Table 1.18: Advantages and disadvantages of web graphics

1.20.3 Inline and External Images

- **Inline image**: Loads and displays directly with the webpage.
- **External image**: May not load immediately with the page and may require downloading or a separate source.

1.20.4 Image Syntax and Attributes

Image Syntax

```
<img src="url" alt="text">
```

Attribute	Use
`src`	Specifies the image file path or URL.
`alt`	Shows alternate text if the image fails to load; also helps accessibility.
`width`	Sets image width.
`height`	Sets image height.
`title`	Shows tooltip text when the mouse is placed over the image.
`align`	Old/exam-reference attribute for image placement: top, middle, bottom, left or right. Modern CSS is preferred.
`hspace`	Old/exam-reference attribute for horizontal space around an image.
`vspace`	Old/exam-reference attribute for vertical space around an image.

Attribute	Use
`border`	Old/exam-reference attribute for image border size.

Table 1.19: Common image attributes

```
<img src="campus.jpg" alt="College campus"
     width="400" height="250" title="Campus Image">
```

Listing 1.15: Image with Size and Tooltip

1.20.5 Clickable Image

```
<a href="https://www.educationboard.gov.bd">
    <img src="logo.jpg" alt="Education Board" width="200">
</a>
```

Listing 1.16: Image Link

1.20.6 Audio and Video

Modern HTML uses `audio`, `video` and `source` tags to add media.

```
<audio controls>
    <source src="lecture.mp3" type="audio/mpeg">
</audio>

<video controls width="400">
    <source src="lesson.mp4" type="video/mp4">
</video>
```

Listing 1.17: Audio and Video Example

1.21 HTML Tables

HTML Table

An HTML table presents information in rows and columns using the `table` element.

1.21.1 Parts of a Table

- **Caption**: title of the table.
- **Row**: horizontal line of cells.
- **Column**: vertical line of cells.
- **Cell**: box formed by the intersection of a row and a column.
- **Heading**: row or column title, usually shown in bold and centered.

1.21.2 Table Elements

Element	Use
`table`	Defines the table.
`caption`	Displays a title for the table.
`tr`	Creates a table row. It should contain `td` or `th` cells.
`td`	Creates a normal table data cell.
`th`	Creates a table heading cell; browsers usually show it bold and centered.

Table 1.20: Main HTML table elements

1.21.3 Basic Table

```html
<table border="1">
    <caption>Student Info</caption>
    <tr>
        <th>Name</th>
        <th>Result</th>
    </tr>
    <tr>
        <td>Raza</td>
        <td>A-</td>
    </tr>
</table>
```

Listing 1.18: Basic HTML Table

1.21.4 Table Attributes

Attribute	Use
`border`	Sets table border width. `border="1"` shows a border; `border="0"` shows no border.
`width`	Sets table width in pixels or percentage.
`height`	Sets table or cell height.
`align`	Aligns table, row or cell content horizontally.
`valign`	Aligns cell content vertically: top, middle or bottom.
`cellspacing`	Sets the space between table cells.
`cellpadding`	Sets the space between cell border and cell content.
`colspan`	Merges cells across columns.
`rowspan`	Merges cells across rows.
`bgcolor`	Sets background color of table, row or cell; exam/reference only, CSS preferred.

Table 1.21: Important table attributes

1.21.5 Cellspacing and Cellpadding

```
<table border="1" cellspacing="7" cellpadding="10">
    <tr>
        <td>First</td>
        <td>Row</td>
    </tr>
    <tr>
        <td>Second</td>
        <td>Row</td>
    </tr>
</table>
```

Listing 1.19: Cellspacing and Cellpadding

1.21.6 Colspan and Rowspan

```
<table border="1">
    <tr>
        <th colspan="2">Test Result</th>
    </tr>
    <tr>
        <td rowspan="2">Science</td>
        <td>Physics</td>
    </tr>
    <tr>
        <td>Chemistry</td>
    </tr>
</table>
```

Listing 1.20: Colspan and Rowspan

1.21.7 Table Background Color

```
<table border="1" width="300">
    <tr bgcolor="green">
        <th>Roll</th>
        <th>Name</th>
        <th>District</th>
    </tr>
    <tr>
        <td>1</td>
        <td>Abrar Dip</td>
        <td bgcolor="blue">Dhaka</td>
    </tr>
</table>
```

Listing 1.21: Table Background Color

Summary

For exams, know `table`, `tr`, `td`, `th`, `caption`, `border`, `cellspacing`, `cellpadding`, `colspan`, `rowspan`, `align`, `valign` and `bgcolor`.

1.22 HTML Layout and Containers

1.22.1 Webpage Layout

Layout means the planned arrangement of webpage parts such as header, navigation, main content, sidebar and footer. A good layout should be planned before making the website.

Part	Purpose
Header	Contains page title, logo or main heading.
Navigation	Contains links to different pages or sections.
Main content	Contains the main information of the webpage.
Sidebar	Contains supporting links or helping elements.
Footer	Contains footer information such as copyright, contact or lower navigation.

Table 1.22: Common parts of a webpage layout

1.22.2 Methods of Creating Layout

- **Using table**: Old method; only HTML can create the structure, but it is not modern practice.
- **Using div**: Uses `div` with CSS; common for layout learning.
- **Using frameset/frame**: Old method; exam/reference only, not significant in modern webpages.
- **Using semantic HTML**: Modern method using tags such as `header`, `nav`, `main`, `section`, `article` and `footer`.

1.22.3 Div and Span

- `div` is a block-level container used to divide a webpage into sections.
- `span` is an inline container used to mark a small part of text.
- Common `div` attributes in examples include `id`, `class`, `style`, `align`, `width`, `height` and `title`.

```html
<div class="container" style="width:100%;">
    <div class="header" style="background-color:gray;">
        <h1 align="center">Header</h1>
    </div>
    <div class="sidebar" style="float:left; width:25%;">
        Sidebar
    </div>
    <div class="content" style="float:left; width:75%;">
        Main Content
    </div>
    <div class="footer" style="clear:left;">
        Footer
    </div>
</div>
```

Listing 1.22: Simple Div Layout

1.22.4 Semantic Layout Tags

```
<header>Site Title</header>
<nav>Navigation Links</nav>
<main>
    <section>
        <article>Main Article</article>
    </section>
</main>
<footer>Footer Information</footer>
```

Listing 1.23: Semantic Layout

1.23 HTML Forms

HTML Form

An HTML form is an area of a webpage that allows users to enter or select data.

Forms are useful for understanding dynamic websites because users submit data through forms. A form can contain many controls, but one `form` element should not contain another `form` element.

1.23.1 Form Element and Attributes

Attribute	Use
`action`	Specifies where the submitted form data will be sent.
`method`	Specifies how form data will be sent, commonly `get` or `post`.

Table 1.23: Main attributes of the form tag

1.23.2 Form Tags

Tag	Use
`form`	Defines a form area.
`input`	Creates input fields such as text box, password field, radio button, checkbox and button.
`textarea`	Creates a multi-line text input area. Default examples often use rows and columns.
`select`	Creates a drop-down list.
`option`	Defines an option inside a drop-down list.
`button`	Creates a clickable button.

Tag	Use
`label`	Gives a text label for an input control.
`fieldset`	Groups related form controls.
`legend`	Gives a title to a fieldset.

Table 1.24: Common HTML form tags

1.23.3 Input Types

Input Type	Use
`text`	Single-line text field.
`password`	Password field; browsers show bullets or asterisks instead of typed characters.
`radio`	Selects one option from a group.
`checkbox`	Selects one or more options.
`submit`	Submits form data.
`button`	Creates a normal command button.

Table 1.25: Common input types in HTML forms

1.23.4 Form Example

```html
<form action="form_action.asp" method="get">
    <fieldset>
        <legend>Student Information</legend>

        <label>Name:</label>
        <input type="text" name="student_name"><br>

        <label>Password:</label>
        <input type="password" name="password"><br>

        <label>Group:</label>
        <input type="radio" name="group" value="science"> Science
        <input type="radio" name="group" value="business"> Business<br>

        <label>Subjects:</label>
        <input type="checkbox" name="subject" value="ict"> ICT
        <input type="checkbox" name="subject" value="english"> English<br>

        <label>District:</label>
        <select name="district">
            <option>Dhaka</option>
            <option>Chattogram</option>
        </select><br>

        <textarea name="comment" rows="4" cols="30">
```

```
Write your comment here.
        </textarea><br>

        <input type="submit" value="Submit">
        <input type="button" value="Please Click Me!">
    </fieldset>
</form>
```

Listing 1.24: Complete Form Example

> **Summary**
>
> Forms collect user input. HTML creates the form controls, but server-side processing is needed to store or process submitted data.

1.24 Designing and Publishing a Website

1.24.1 Designing a Webpage

Web design is the creation of the external structure and front-end presentation of a website. A good website depends on layout, useful information, interface, linking, and up-to-date correct content.

1.24.2 Steps for Better Website Design

1. **Planning**: decide the objective of the website, target users, topics to publish and quality standard.
2. **Information architecture**: organize the website structure, page relationships and navigation.
3. **Layout design**: plan header, navigation, content, sidebar and footer.
4. **Content preparation**: prepare text, images, links, tables, forms and other materials.
5. **Implementation**: write HTML and CSS, then test the pages in a browser.
6. **Publishing**: upload the website files to hosting so users can access the website online.

1.24.3 Publishing a Website

Publishing means making the completed website available on the internet. To publish a website, the files are uploaded to a web hosting server and connected with a domain name.

- HTML, CSS, images and other files should be kept in organized folders.
- File names and folder paths should be correct because links and images depend on them.
- FTP or hosting control panels can be used to upload website files.
- After publishing, the website should be tested from a browser using its URL.

> **Summary**
>
> Design prepares the website plan and structure; publishing uploads the finished website so it can be accessed through the internet.

1.25 Final Summary of the Chapter

Chapter Overview

- Web design deals with creating and structuring websites.
- Websites are collections of interconnected webpages.
- IP address uniquely identifies devices on a network.
- Domain name provides a human-readable address.
- URL specifies the location of resources.
- HTTP controls browser-server webpage communication.
- FTP is used for uploading and downloading files.
- Website structure affects navigation and usability.
- Websites may be static, dynamic, local or remote.
- Browsers interpret webpage code, while search engines help find webpages.
- HTML is a markup language used to create webpages.
- HTML uses tags, elements and attributes to organize content.
- HTML documents contain head and body sections.
- Headings, paragraphs, formatting tags, lists, links, images, media, tables, layout containers and forms are essential HTML topics.
- Deprecated tags and attributes may appear in exams, but modern practice prefers CSS and semantic HTML.