



Keep going. Keep growing.
Get Creative Cloud All Apps.

[Learn more](#)

Python For Loops

[< Previous](#)[Next >](#)

Python For Loops

A `for` loop is used for iterating over a sequence (that is either a list, a tuple, a dictionary, a set, or a string).

This is less like the `for` keyword in other programming languages, and works more like an iterator method as found in other object-orientated programming languages.

With the `for` loop we can execute a set of statements, once for each item in a list, tuple, set etc.

Example

[Get your own Python Server](#)

Print each fruit in a fruit list:

```
fruits = ["apple", "banana", "cherry"]  
for x in fruits:  
    print(x)
```

[Try it Yourself »](#)

The `for` loop does not require an indexing variable to set beforehand.

[Dark mode](#)



HTML

CSS



Looping Through a String

ADVERTISEMENT

Even strings are iterable objects, they contain a sequence of characters:

Example

[Get your own Python Server](#)

Loop through the letters in the word "banana":

```
for x in "banana":  
    print(x)
```

[Try it Yourself »](#)

The break Statement

With the `break` statement we can stop the loop before it has looped through all the items:

Example

[Get your own Python Server](#)

Exit the loop when `x` is "banana":

```
fruits = ["apple", "banana", "cherry"]  
for x in fruits:  
    print(x)  
    if x == "banana":  
        break
```

[Try it Yourself »](#)

Example

[Get your own Python Server](#)
[Dark mode](#)




```
fruits = ["apple", "banana", "cherry"]  
for x in fruits:  
    if x == "banana":  
        break  
    print(x)
```

[Try it Yourself »](#)

ADVERTISEMENT

ADVERTISEMENT



The continue Statement

With the `continue` statement we can stop the current iteration of the loop, and continue with the next:

Example

Do not print banana:

```
fruits = ["apple", "banana", "cherry"]  
for x in fruits:  
    if x == "banana":  
        continue  
    print(x)
```

[Get your own Python Server](#)[Dark mode](#)



HTML

CSS



ADVERTISEMENT

[Try it Yourself »](#)

The range() Function

To loop through a set of code a specified number of times, we can use the `range()` function,

The `range()` function returns a sequence of numbers, starting from 0 by default, and increments by 1 (by default), and ends at a specified number.

Example

[Get your own Python Server](#)

Using the range() function:

```
for x in range(6):  
    print(x)
```

[Try it Yourself »](#)

Note that `range(6)` is not the values of 0 to 6, but the values 0 to 5.

The `range()` function defaults to 0 as a starting value, however it is possible to specify the starting value by adding a parameter: `range(2, 6)`, which means values from 2 to 6 (but not including 6):

Example

[Get your own Python Server](#)

Using the start parameter:

[Dark mode](#)

`print(x)`

ADVERTISEMENT

Try it Yourself »

The `range()` function defaults to increment the sequence by 1, however it is possible to specify the increment value by adding a third parameter: `range(2, 30, 3)`:

Example

Get your own Python Server

Increment the sequence with 3 (default is 1):

```
for x in range(2, 30, 3):  
    print(x)
```

Try it Yourself »

Else in For Loop

The `else` keyword in a `for` loop specifies a block of code to be executed when the loop is finished:

Example

Get your own Python Server

Print all numbers from 0 to 5, and print a message when the loop has ended:

```
for x in range(6):  
    print(x)  
else:  
    print("Finally finished!")
```

Try it Yourself »

Dark mode



HTML

CSS



Note: The `else` block will NOT be executed if the loop is stopped by a `break` statement. ADVERTISEMENT

Example

[Get your own Python Server](#)

Break the loop when `x` is 3, and see what happens with the `else` block:

```
for x in range(6):  
    if x == 3: break  
    print(x)  
else:  
    print("Finally finished!")
```

[Try it Yourself »](#)

Nested Loops

A nested loop is a loop inside a loop.

The "inner loop" will be executed one time for each iteration of the "outer loop":

Example

[Get your own Python Server](#)

Print each adjective for every fruit:

```
adj = ["red", "big", "tasty"]  
fruits = ["apple", "banana", "cherry"]  
  
for x in adj:  
    for y in fruits:  
        print(x, y)
```

[Dark mode](#)



HTML

CSS



ADVERTISEMENT

The pass Statement

`for` loops cannot be empty, but if you for some reason have a `for` loop with no content, put in the `pass` statement to avoid getting an error.

Example

[Get your own Python Server](#)

```
for x in [0, 1, 2]:  
    pass
```

[Try it Yourself »](#)

Test Yourself With Exercises

Exercise:

Loop through the items in the `fruits` list.

```
fruits = ["apple", "banana", "cherry"]  
    x    fruits  
    print(x)
```

[Submit Answer »](#)[Dark mode](#)



HTML

CSS



ADVERTISEMENT

< Previous

Next >

ADVERTISEMENT

Adobe

**Keep going.
Keep growing.**

Get Creative Cloud All Apps.

[Learn more](#)

The advertisement features a light orange background. At the top left is the Adobe logo. Below it, the text 'Keep going. Keep growing.' is written in a bold, black, sans-serif font, followed by 'Get Creative Cloud All Apps.' in a smaller font. A rounded rectangular button with the text 'Learn more' is positioned below the text. The bottom half of the ad shows a collage of images: a smartphone displaying a social media post for 'unwrp' (Unwrap), a laptop with the 'unwrp' logo on its lid, and a hand typing on a keyboard. The collage is decorated with various colorful geometric shapes like squares and rectangles.

Dark mode



HTML

CSS



ADVERTISEMENT



COLOR PICKER




Dark mode


ADVERTISEMENT



ADVERTISEMENT



ADVERTISEMENT

[Report Error](#)[Spaces](#)[Upgrade](#)[Newsletter](#)[Get Certified](#)[Dark mode](#)

[HTML](#)[CSS](#)

ADVERTISEMENT

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)

Dark mode

[HTML](#)[CSS](#)[C# Certificate](#)[XML Certificate](#)[ADVERTISEMENT](#)[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

