MINTECH INTERNSHIP REPORT

STUDENT ENGINEERING PORTFOLIO

Mintech internship Engineering and AI

A record-validation project

Supervised manufacturing support and
AI-assisted follow-up design and software checks.

Software fixtures and synthetic data | Student follow-up project

01 My role and the follow-up project

Supervised manufacturing support

I spent one month as a manufacturing technology intern at Mintech. I began with factory assistance and then joined OLED deposition-equipment manufacturing work under my supervisor's direction.

My contribution after the internship

After the internship, I described the work I had carried out and set the goal of connecting it with engineering and AI in a report and portfolio. I used AI tools to develop the technical documents and software. My contribution included supplying a reference design and directing revisions to the presentation and explanation of my role.

Part of the work	My contribution	Supporting material
Internship	Assisted with factory work and carried out tasks under supervision	Internship account
Project purpose	Provided the manufacturing context and requested an engineering-and-AI follow-up	Record-validation project and separate 4M analysis
Development and revision	Used AI tools for documents, code and checks; directed revisions to the report's scope and presentation	Design files, executable code, test outputs and reports

AI tools drafted the technical design, implemented the code and ran the automated checks described in this report.

What the project produced

The main deliverable is a record-validation tool, supported by a checklist, a proposed paired comparison and an analysis workbook. The design uses a carrier, the supporting fixture, and a witness coupon, a sample used to assess a deposited film. The proposed record links their identities to preparation conditions and measurement points.

The follow-up work was completed after the internship. Its results concern software behaviour and a separate synthetic-data classification exercise. The package contains no field A/B observations, and the record schema is a proposed design rather than a company-approved specification.

02 Record structure and comparison rules

Choose a change that can be specified

A contact stop could constrain sample placement, but specifying one would require actual equipment dimensions, permitted contact surfaces, contamination requirements and clearance checks. With the available information, the project specifies a non-contact layout, checklist and record-matching rules.

The record contains 26 columns, including 25 required fields and optional notes. Each row identifies one measurement point within one method run. A pair ID connects an A run and a B run. Repeated run information must agree across the point-level rows.



Figure 1. Proposed record flow. The checks establish whether the inputs meet the comparison rules; they do not authenticate the origin of a measurement.

Separate the two outcomes

The proposed A method uses the existing approved preparation procedure. B adds the checklist. Preparation errors are counted once per run. Film thickness is recorded at fixed points, and its range is the maximum minus the minimum across the same point set.

An omitted preparation check and a wider film-thickness range can occur together without establishing a causal relationship. Preparation errors and thickness ranges are therefore recorded separately.

Design decision	Reason
Match block, recipe and measurement tool	Reduce differences in recorded comparison conditions
Require the same point set, with at least two points	Make the spatial ranges refer to the same sampling layout
Balance AB and BA order in the proposed trial	Allow order-related differences to be examined
Review repeated measurements separately	Examine measurement repeatability before pooling results
Keep missing values distinct from zero	Prevent absent observations from becoming numerical results

03 Three cases that explain the validator

A valid software fixture

The baseline fixture contains 12 constructed rows: an AB pair and a BA pair, each with three measurement points per method. Its TEST-prefixed IDs, fixed date of 2000-01-01 and thickness constants identify it as SOFTWARE_TEST input. The validator accepts two comparable pairs.

The worked numerical example lists the point values and calculates the two range differences.

Case 1: an incomplete recipe record

The missing_recipe_id test removes one required recipe value from a six-row fixture. The saved result includes MISSING_FIELD, and the accepted-pair count becomes zero. A numerical thickness value on that row cannot compensate for the missing comparison condition.

Case 2: a different measurement-point set

The measurement_point_mismatch test changes a point identifier to P4. The saved result includes POINT_SET, and the pair is withheld. Equal numbers of measurements are insufficient when the measurements refer to different locations.

Case 3: one error repeated across several rows

Preparation-error counts belong to a run, while thickness values belong to individual points. A constructed test repeats A's two preparation errors and B's one error across their three point rows. The validator reports two and one respectively. Summing every row would incorrectly produce six and three.

What the 55 tests establish

All 55 configured cases passed: each contained the expected issue codes and produced the expected number of accepted pairs. The cases cover required-field omissions, invalid values, duplicate IDs, mismatched conditions, evidence categories and boundary inputs. The result verifies the specified behaviours. A general error-detection rate was not measured.

The saved evidence is in outputs/software_validation/test_results.json and test_cases.csv. Source hashes in the result file connect the test run to the validator and test script versions.

04 From validated records to model evaluation

Connecting records to labels

The validator decides whether records meet declared rules for comparison. A classifier estimates a label from chosen features. Both require a defined unit of observation, consistent identifiers and clear timing.

The current 4M example is a separate synthetic dataset. Its human, machine, material and method fields are not populated from the carrier checklist. A future connection would require a run-level dataset with independently observed quality labels, an agreed prediction time and traceable joins between preparation records and outcomes.

Model errors at the saved threshold

The pipeline generates 4,000 rows with 240 positive labels. A stratified 75/25 split produces 3,000 training rows and 1,000 evaluation rows. The evaluation set contains 60 positives and 940 negatives. The seed is 42 and the decision threshold is 0.5.

Model	Positives found / 60	False alarms / 940	Recall	Precision
LogisticRegression	50	119	83.3%	29.6%
LightGBM	26	29	43.3%	47.3%

At this threshold, LogisticRegression finds 24 more positives and produces 90 more false alarms. LightGBM misses 34 positives, while LogisticRegression misses 10. A model choice must account for the relative costs of missed defects and unnecessary inspections. These outputs alone do not establish either model as the preferred production system.

What changes for a real prediction task

The generated label uses lot, shift, rework, waiting time and noise. Some of these variables also appear as inputs, and rework may only be known after the outcome of interest. The exercise therefore evaluates classification of generated, completed-work records. Future-defect prediction would require features available at the prediction time and labels collected independently. Evaluation by time or lot would also be needed to examine performance on future work or unseen groups.

05 Completed checks and proposed field trial

Completed outputs

The package contains the proposed record structure, comparison plan, CSV validator and synthetic-data classification pipeline. The portfolio workbook is included with empty field inputs and separately labelled examples. Software-test fixtures and model evaluation outputs accompany the code.

The workbook was previously checked through 47 recalculation assertions in Artifact Tool, including statistics and invalid-input handling. Four Streamlit AppTest scenarios checked dashboard filters and sample conditions. These checks did not cover native Excel behaviour or a browser layout review.

A field trial would test a different claim

The next engineering step is a supervised trial of the proposed checklist. It requires review of equipment and contamination constraints, a measurement-repeatability check, matched A/B conditions and recorded order and block information. Measurement time, instrument and calibration information, reviewer identity, corrections and excluded runs need to remain traceable in the source record.

The trial would assess preparation errors and thickness-range differences. The completed software tests cover specified input conditions and calculations. Field effectiveness still requires measurement.

Reproduce the core result

```
python code/verify_records.py --out outputs/software_validation
python code/record_validation.py templates/field_records.csv
python code/pipeline.py --n 4000 --defect-rate 0.06 --seed 42 --out outputs
streamlit run code/app/dashboard.py
```

The validator and its test script use Python's standard library. The model pipeline and dashboard require code/requirements.txt. The execution environment for the saved model outputs is recorded in outputs/run_metadata.json. The field CSV is a blank template and should return EMPTY before observations are entered.

References and supporting files

Evidence index

- Software-test results: case-level outcomes and source hashes.
- Constructed test inputs: SOFTWARE_TEST fixtures.
- Model results and execution metadata: confusion matrices and run conditions.
- Detailed comparison plan: Korean technical supporting document.
- Checklist and workbook: proposed recording and calculation tools.
- OLED literature notes: published context, separate from company measurements.

Measurement references

The range definition follows NIST Measures of Scale. Measurement-repeatability terminology is discussed in NIST TN 1297, Appendix D.1.

The OLED literature notes include Yun et al., 2016 and Lee et al., 2024. Their specimen-specific values provide literature context, not company acceptance limits or evidence of this checklist's effects.