



**packetvideo**<sup>TM</sup>

OSCL API

Build Version: CORE\_8.507.1.1

March 27, 2010

# Contents

<b>1 oscl Module Index</b>	<b>1</b>
1.1 oscl Modules . . . . .	1
<b>2 oscl Hierarchical Index</b>	<b>2</b>
2.1 oscl Class Hierarchy . . . . .	2
<b>3 oscl Data Structure Index</b>	<b>9</b>
3.1 oscl Data Structures . . . . .	9
<b>4 oscl File Index</b>	<b>15</b>
4.1 oscl File List . . . . .	15
<b>5 oscl Page Index</b>	<b>20</b>
5.1 oscl Related Pages . . . . .	20
<b>6 oscl Module Documentation</b>	<b>21</b>
6.1 OSCL config . . . . .	21
6.2 OSCL Base . . . . .	25
6.3 OSCL Memory . . . . .	46
6.4 OSCL Util . . . . .	62
6.5 OSCL Error . . . . .	84
6.6 OSCL IO . . . . .	94
6.7 OSCL Proc . . . . .	102
6.8 OSCL Init . . . . .	106
<b>7 oscl Data Structure Documentation</b>	<b>107</b>
7.1 _OsclBasicAllocator Class Reference . . . . .	107
7.2 _OsclHeapBase Class Reference . . . . .	109
7.3 AcceptParam Class Reference . . . . .	111
7.4 allocator Class Reference . . . . .	112

7.5	AllPassFilter Class Reference . . . . .	113
7.6	BindParam Class Reference . . . . .	115
7.7	BufferFragment Class Reference . . . . .	116
7.8	BufferMgr Class Reference . . . . .	117
7.9	BufferState Class Reference . . . . .	118
7.10	BuFragGroup< ChainClass, max_frags > Class Template Reference . . . . .	119
7.11	BuffFragStatusClass Class Reference . . . . .	122
7.12	CallbackTimer< Alloc > Class Template Reference . . . . .	123
7.13	CallbackTimerObserver Class Reference . . . . .	125
7.14	CFastRep Class Reference . . . . .	126
7.15	CHheapRep Class Reference . . . . .	128
7.16	ConnectParam Class Reference . . . . .	130
7.17	CStackRep Class Reference . . . . .	131
7.18	DNSRequestParam Class Reference . . . . .	132
7.19	GetHostByNameParam Class Reference . . . . .	134
7.20	HeapBase Class Reference . . . . .	136
7.21	internalLeave Class Reference . . . . .	138
7.22	LinkedListElement< LLClass > Class Template Reference . . . . .	139
7.23	ListenParam Class Reference . . . . .	140
7.24	MediaData< ChainClass, max_frags, local_bufsize > Class Template Reference . . . . .	141
7.25	MediaStatusClass Class Reference . . . . .	144
7.26	MemAllocator< T > Class Template Reference . . . . .	145
7.27	MM_AllocBlockFence Struct Reference . . . . .	146
7.28	MM_AllocBlockHdr Struct Reference . . . . .	147
7.29	MM_AllocInfo Struct Reference . . . . .	148
7.30	MM_AllocNode Struct Reference . . . . .	150
7.31	MM_AllocQueryInfo Struct Reference . . . . .	151
7.32	MM_Audit_Imp Class Reference . . . . .	152
7.33	MM_AuditOverheadStats Struct Reference . . . . .	160
7.34	MM_FailInsertParam Struct Reference . . . . .	161
7.35	MM_Stats_CB Struct Reference . . . . .	162
7.36	MM_Stats_t Struct Reference . . . . .	163
7.37	NTPTTime Class Reference . . . . .	165
7.38	Oscl_Alloc Class Reference . . . . .	169
7.39	Oscl_Dealloc Class Reference . . . . .	170
7.40	Oscl_DefAlloc Class Reference . . . . .	171

7.41 Oscl_DefAllocWithRefCounter< DefAlloc > Class Template Reference . . . . .	172
7.42 OSCL_FastString Class Reference . . . . .	174
7.43 Oscl_File Class Reference . . . . .	178
7.44 Oscl_File::OsclCacheObserver Class Reference . . . . .	186
7.45 Oscl_File::OsclFixedCacheParam Class Reference . . . . .	187
7.46 Oscl_FileFind Class Reference . . . . .	188
7.47 Oscl_FileServer Class Reference . . . . .	192
7.48 oscl_fsstat Struct Reference . . . . .	194
7.49 OSCL_HeapString< Alloc > Class Template Reference . . . . .	195
7.50 OSCL_HeapStringA Class Reference . . . . .	197
7.51 Oscl_Int64_Utils Class Reference . . . . .	202
7.52 Oscl_Less< T > Struct Template Reference . . . . .	204
7.53 Oscl_Linked_List< LLClass, Alloc > Class Template Reference . . . . .	205
7.54 Oscl_Linked_List_Base Class Reference . . . . .	210
7.55 Oscl_Map< Key, T, Alloc, Compare > Class Template Reference . . . . .	215
7.56 Oscl_Map< Key, T, Alloc, Compare >::value_compare Class Reference . . . . .	222
7.57 Oscl_MTLinked_List< LLClass, Alloc, TheLock > Class Template Reference . . . . .	224
7.58 Oscl_Opaque_Type_Alloc Class Reference . . . . .	228
7.59 Oscl_Opaque_Type_Alloc_LL Class Reference . . . . .	230
7.60 Oscl_Opaque_Type_Compare Class Reference . . . . .	232
7.61 Oscl_Pair< T1, T2 > Struct Template Reference . . . . .	234
7.62 Oscl_Queue< T, Alloc > Class Template Reference . . . . .	235
7.63 Oscl_Queue_Base Class Reference . . . . .	238
7.64 Oscl_Rb_Tree< Key, Value, KeyOfValue, Compare, Alloc > Class Template Reference . . . . .	241
7.65 Oscl_Rb_Tree_Base Class Reference . . . . .	245
7.66 Oscl_Rb_Tree_Const_Iterator< Value > Struct Template Reference . . . . .	246
7.67 Oscl_Rb_Tree_Iterator< Value > Struct Template Reference . . . . .	249
7.68 Oscl_Rb_Tree_Node< Value > Struct Template Reference . . . . .	252
7.69 Oscl_Rb_Tree_Node_Base Struct Reference . . . . .	253
7.70 Oscl_Select1st< V, U > Struct Template Reference . . . . .	255
7.71 OSCL_StackString< MaxBufSize > Class Template Reference . . . . .	256
7.72 oscl_stat_buf Struct Reference . . . . .	258
7.73 OSCL_String Class Reference . . . . .	259
7.74 Oscl_Tag< Alloc > Struct Template Reference . . . . .	264
7.75 Oscl_Tag_Base Struct Reference . . . . .	266
7.76 Oscl_TagTree< T, Alloc > Class Template Reference . . . . .	268

7.77 Oscl_TagTree< T, Alloc >::const_iterator Struct Reference . . . . .	272
7.78 Oscl_TagTree< T, Alloc >::iterator Struct Reference . . . . .	275
7.79 Oscl_TagTree< T, Alloc >::Node Struct Reference . . . . .	278
7.80 Oscl_TAlloc< T, Alloc > Class Template Reference . . . . .	280
7.81 Oscl_TAlloc< T, Alloc >::rebind< U, V > Struct Template Reference . . . . .	283
7.82 Oscl_Vector< T, Alloc > Class Template Reference . . . . .	284
7.83 Oscl_Vector_Base Class Reference . . . . .	289
7.84 OSCL_wFastString Class Reference . . . . .	293
7.85 OSCL_wHeapString< Alloc > Class Template Reference . . . . .	296
7.86 OSCL_wHeapStringA Class Reference . . . . .	298
7.87 OSCL_wStackString< MaxBufSize > Class Template Reference . . . . .	301
7.88 OSCL_wString Class Reference . . . . .	303
7.89 OsclAcceptMethod Class Reference . . . . .	307
7.90 OsclAcceptRequest Class Reference . . . . .	308
7.91 OsclActiveObject Class Reference . . . . .	309
7.92 OsclAllocDestructDealloc Class Reference . . . . .	313
7.93 OsclAOStatus Class Reference . . . . .	314
7.94 OsclAsyncFile Class Reference . . . . .	315
7.95 OsclAsyncFileBuffer Class Reference . . . . .	318
7.96 OsclAuditCB Class Reference . . . . .	320
7.97 OsclBindMethod Class Reference . . . . .	321
7.98 OsclBindRequest Class Reference . . . . .	322
7.99 OsclBinIStream Class Reference . . . . .	323
7.100 OsclBinIStreamBigEndian Class Reference . . . . .	325
7.101 OsclBinIStreamLittleEndian Class Reference . . . . .	328
7.102 OsclBinOStream Class Reference . . . . .	330
7.103 OsclBinOStreamBigEndian Class Reference . . . . .	331
7.104 OsclBinOStreamLittleEndian Class Reference . . . . .	333
7.105 OsclBinStream Class Reference . . . . .	335
7.106 OsclBuf Class Reference . . . . .	339
7.107 OsclCompareLess< T > Class Template Reference . . . . .	341
7.108 OsclComponentRegistry Class Reference . . . . .	342
7.109 OsclComponentRegistryData Class Reference . . . . .	344
7.110 OsclComponentRegistryElement Class Reference . . . . .	345
7.111 OsclConnectMethod Class Reference . . . . .	347
7.112 OsclConnectRequest Class Reference . . . . .	348

7.113OsclDestructDealloc Class Reference . . . . .	349
7.114OsclDNS Class Reference . . . . .	350
7.115OsclDNSI Class Reference . . . . .	352
7.116OsclDNSIBase Class Reference . . . . .	354
7.117OsclDNSMethod Class Reference . . . . .	357
7.118OsclDNSObserver Class Reference . . . . .	360
7.119OsclDNSRequest Class Reference . . . . .	361
7.120OsclDNSRequestAO Class Reference . . . . .	362
7.121OsclDoubleLink Class Reference . . . . .	365
7.122OsclDoubleList< T > Class Template Reference . . . . .	366
7.123OsclDoubleListBase Class Reference . . . . .	367
7.124OsclDoubleRunner< T > Class Template Reference . . . . .	369
7.125OsclError Class Reference . . . . .	371
7.126OsclErrorAllocator Class Reference . . . . .	373
7.127OsclErrorTrap Class Reference . . . . .	375
7.128OsclErrorTrapImp Class Reference . . . . .	376
7.129OsclException< LeaveCode > Class Template Reference . . . . .	378
7.130OsclExclusiveArrayPtr< T > Class Template Reference . . . . .	379
7.131OsclExclusivePtr< T > Class Template Reference . . . . .	382
7.132OsclExclusivePtrA< T, Alloc > Class Template Reference . . . . .	385
7.133OsclExecScheduler Class Reference . . . . .	388
7.134OsclExecSchedulerBase Class Reference . . . . .	390
7.135OsclExecSchedulerCommonBase Class Reference . . . . .	391
7.136OsclFileCache Class Reference . . . . .	400
7.137OsclFileCacheBuffer Class Reference . . . . .	402
7.138OsclFileHandle Class Reference . . . . .	404
7.139OsclFileManager Class Reference . . . . .	405
7.140OsclFileStats Class Reference . . . . .	410
7.141OsclFileStatsItem Class Reference . . . . .	411
7.142OsclGetHostByNameMethod Class Reference . . . . .	412
7.143OsclGetHostByNameRequest Class Reference . . . . .	413
7.144OsclInit Class Reference . . . . .	414
7.145OsclInteger64Transport Struct Reference . . . . .	415
7.146OsclIpMReq Class Reference . . . . .	416
7.147OsclIPSocketI Class Reference . . . . .	417
7.148OsclJump Class Reference . . . . .	420

7.149OsclListenMethod Class Reference . . . . .	421
7.150OsclListenRequest Class Reference . . . . .	422
7.151OsclLockBase Class Reference . . . . .	423
7.152OsclMem Class Reference . . . . .	424
7.153OsclMemAllocator Class Reference . . . . .	425
7.154OsclMemAllocDestructDealloc< T > Class Template Reference . . . . .	426
7.155OsclMemAudit Class Reference . . . . .	428
7.156OSCLMemAutoPtr< T, _Allocator > Class Template Reference . . . . .	434
7.157OsclMemBasicAllocator Class Reference . . . . .	438
7.158OsclMemBasicAllocDestructDealloc< T > Class Template Reference . . . . .	439
7.159OsclMemGlobalAuditObject Class Reference . . . . .	440
7.160OsclMemoryFragment Struct Reference . . . . .	441
7.161OsclMemPoolFixedChunkAllocator Class Reference . . . . .	442
7.162OsclMemPoolFixedChunkAllocatorObserver Class Reference . . . . .	446
7.163OsclMemPoolResizableAllocator Class Reference . . . . .	447
7.164OsclMemPoolResizableAllocator::MemPoolBlockInfo Struct Reference . . . . .	453
7.165OsclMemPoolResizableAllocator::MemPoolBufferInfo Struct Reference . . . . .	454
7.166OsclMemPoolResizableAllocatorMemoryObserver Class Reference . . . . .	455
7.167OsclMemPoolResizableAllocatorObserver Class Reference . . . . .	456
7.168OsclMemStatsNode Class Reference . . . . .	457
7.169OsclMutex Class Reference . . . . .	458
7.170OsclNameString< __len > Class Template Reference . . . . .	460
7.171OsclNativeFile Class Reference . . . . .	461
7.172OsclNativeFileParams Class Reference . . . . .	464
7.173OsclNetworkAddress Class Reference . . . . .	465
7.174OsclNullLock Class Reference . . . . .	466
7.175OsclPriorityLink Class Reference . . . . .	467
7.176OsclPriorityList< T > Class Template Reference . . . . .	468
7.177OsclPriorityQueue< Qelem, Alloc, Container, Compare > Class Template Reference . . . . .	469
7.178OsclPriorityQueueBase Class Reference . . . . .	473
7.179OsclProcStatus Class Reference . . . . .	474
7.180OsclPtr Class Reference . . . . .	476
7.181OsclPtrC Class Reference . . . . .	478
7.182OsclRand Class Reference . . . . .	480
7.183OsclReadyAlloc Class Reference . . . . .	481
7.184OsclReadyCompare Class Reference . . . . .	482

7.185OsclReadyQ Class Reference . . . . .	483
7.186OsclRecvFromMethod Class Reference . . . . .	485
7.187OsclRecvFromRequest Class Reference . . . . .	487
7.188OsclRecvMethod Class Reference . . . . .	489
7.189OsclRecvRequest Class Reference . . . . .	490
7.190OsclRefCounter Class Reference . . . . .	491
7.191OsclRefCounterDA Class Reference . . . . .	493
7.192OsclRefCounterMemFrag Class Reference . . . . .	495
7.193OsclRefCounterMTDA< LockType > Class Template Reference . . . . .	497
7.194OsclRefCounterMTSA< DeallocType, LockType > Class Template Reference . . . . .	499
7.195OsclRefCounterSA< DeallocType > Class Template Reference . . . . .	501
7.196OsclRegistryAccessClient Class Reference . . . . .	503
7.197OsclRegistryAccessClientImpl Class Reference . . . . .	505
7.198OsclRegistryAccessClientTlsImpl Class Reference . . . . .	506
7.199OsclRegistryAccessElement Class Reference . . . . .	507
7.200OsclRegistryClient Class Reference . . . . .	508
7.201OsclRegistryClientImpl Class Reference . . . . .	510
7.202OsclRegistryClientTlsImpl Class Reference . . . . .	512
7.203OsclRegistryServTlsImpl Class Reference . . . . .	513
7.204OsclScheduler Class Reference . . . . .	515
7.205OsclSchedulerObserver Class Reference . . . . .	516
7.206OsclScopedLock< LockClass > Class Template Reference . . . . .	517
7.207OsclSelect Class Reference . . . . .	518
7.208OsclSemaphore Class Reference . . . . .	520
7.209OsclSendMethod Class Reference . . . . .	522
7.210OsclSendRequest Class Reference . . . . .	523
7.211OsclSendToMethod Class Reference . . . . .	524
7.212OsclSendToRequest Class Reference . . . . .	525
7.213OsclSharedPtr< TheClass > Class Template Reference . . . . .	526
7.214OsclShutdownMethod Class Reference . . . . .	529
7.215OsclShutdownRequest Class Reference . . . . .	530
7.216OsclSingleton< T, ID, Registry > Class Template Reference . . . . .	531
7.217OsclSingletonRegistry Class Reference . . . . .	533
7.218OsclSocketI Class Reference . . . . .	534
7.219OsclSocketIBase Class Reference . . . . .	539
7.220OsclSocketMethod Class Reference . . . . .	544

7.221 OsclSocketObserver Class Reference . . . . .	547
7.222 OsclSocketRequest Class Reference . . . . .	548
7.223 OsclSocketRequestAO Class Reference . . . . .	549
7.224 OsclSocketServ Class Reference . . . . .	553
7.225 OsclSocketServI Class Reference . . . . .	555
7.226 OsclSocketServIBase Class Reference . . . . .	557
7.227 OsclSocketServRequestList Class Reference . . . . .	559
7.228 OsclSocketServRequestQElem Class Reference . . . . .	561
7.229 OsclSocketTOS Class Reference . . . . .	562
7.230 OsclTCPSocket Class Reference . . . . .	564
7.231 OsclTCPSocketI Class Reference . . . . .	571
7.232 OsclThread Class Reference . . . . .	574
7.233 OsclThreadLock Class Reference . . . . .	578
7.234 OsclTickCount Class Reference . . . . .	579
7.235 OsclTimer< Alloc > Class Template Reference . . . . .	581
7.236 OsclTimerCompare Class Reference . . . . .	584
7.237 OsclTimerObject Class Reference . . . . .	585
7.238 OsclTimerObserver Class Reference . . . . .	589
7.239 OsclTimerQ Class Reference . . . . .	590
7.240 OsclTLS< T, ID, Registry > Class Template Reference . . . . .	591
7.241 OsclTLSE< T, ID, Registry > Class Template Reference . . . . .	593
7.242 OsclTLSRegistry Class Reference . . . . .	595
7.243 OsclTLSRegistryEx Class Reference . . . . .	596
7.244 OsclTrapItem Class Reference . . . . .	597
7.245 OsclTrapStack Class Reference . . . . .	598
7.246 OsclTrapStackItem Class Reference . . . . .	599
7.247 OsclUDPSocket Class Reference . . . . .	600
7.248 OsclUDPSocketI Class Reference . . . . .	606
7.249 OsclUuid Struct Reference . . . . .	609
7.250 PVActiveBase Class Reference . . . . .	611
7.251 PVActiveStats Class Reference . . . . .	615
7.252 PVLogger Class Reference . . . . .	616
7.253 PVLoggerAppender Class Reference . . . . .	622
7.254 PVLoggerFilter Class Reference . . . . .	623
7.255 PVLoggerLayout Class Reference . . . . .	625
7.256 PVLoggerRegistry Class Reference . . . . .	627

7.257PVSchedulerStopper Class Reference . . . . .	630
7.258PVSockBufRecv Class Reference . . . . .	631
7.259PVSockBufSend Class Reference . . . . .	632
7.260PVThreadContext Class Reference . . . . .	633
7.261RecvFromParam Class Reference . . . . .	635
7.262RecvParam Class Reference . . . . .	637
7.263SendParam Class Reference . . . . .	638
7.264SendToParam Class Reference . . . . .	639
7.265ShutdownParam Class Reference . . . . .	640
7.266SocketRequestParam Class Reference . . . . .	641
7.267StrCSumPtrLen Struct Reference . . . . .	643
7.268StrPtrLen Struct Reference . . . . .	646
7.269TimeValue Class Reference . . . . .	648
7.270TLSStorageOps Class Reference . . . . .	655
7.271TReadyQueLink Class Reference . . . . .	656
7.272WStrPtrLen Struct Reference . . . . .	657
<b>8 oscl File Documentation . . . . .</b>	<b>659</b>
8.1 oscl_aostatus.h File Reference . . . . .	659
8.2 oscl_assert.h File Reference . . . . .	660
8.3 oscl_base.h File Reference . . . . .	661
8.4 oscl_base_alloc.h File Reference . . . . .	662
8.5 oscl_base_macros.h File Reference . . . . .	663
8.6 oscl_bin_stream.h File Reference . . . . .	664
8.7 oscl_byte_order.h File Reference . . . . .	665
8.8 oscl_defalloc.h File Reference . . . . .	666
8.9 oscl_dll.h File Reference . . . . .	667
8.10 oscl_dns.h File Reference . . . . .	668
8.11 oscl_dns_gethostname.h File Reference . . . . .	669
8.12 oscl_dns_imp.h File Reference . . . . .	670
8.13 oscl_dns_imp_base.h File Reference . . . . .	671
8.14 oscl_dns_imp_pv.h File Reference . . . . .	672
8.15 oscl_dns_method.h File Reference . . . . .	673
8.16 oscl_dns_param.h File Reference . . . . .	674
8.17 oscl_dns_request.h File Reference . . . . .	675
8.18 oscl_dns_tuneables.h File Reference . . . . .	676
8.19 oscl_double_list.h File Reference . . . . .	677

8.20 oscl_errno.h File Reference . . . . .	678
8.21 oscl_error.h File Reference . . . . .	679
8.22 oscl_error_allocator.h File Reference . . . . .	680
8.23 oscl_error_codes.h File Reference . . . . .	681
8.24 oscl_error_imp.h File Reference . . . . .	682
8.25 oscl_error_imp_cppexceptions.h File Reference . . . . .	683
8.26 oscl_error_imp_fatalerror.h File Reference . . . . .	684
8.27 oscl_error_imp_jumps.h File Reference . . . . .	685
8.28 oscl_error_trapcleanup.h File Reference . . . . .	687
8.29 oscl_exception.h File Reference . . . . .	688
8.30 oscl_exclusive_ptr.h File Reference . . . . .	689
8.31 oscl_file_async_read.h File Reference . . . . .	690
8.32 oscl_file_cache.h File Reference . . . . .	691
8.33 oscl_file_dir_utils.h File Reference . . . . .	692
8.34 oscl_file_find.h File Reference . . . . .	694
8.35 oscl_file_handle.h File Reference . . . . .	695
8.36 oscl_file_io.h File Reference . . . . .	696
8.37 oscl_file_manager.h File Reference . . . . .	697
8.38 oscl_file_native.h File Reference . . . . .	698
8.39 oscl_file_server.h File Reference . . . . .	699
8.40 oscl_file_stats.h File Reference . . . . .	700
8.41 oscl_file_types.h File Reference . . . . .	701
8.42 oscl_heapbase.h File Reference . . . . .	702
8.43 oscl_init.h File Reference . . . . .	703
8.44 oscl_int64_utils.h File Reference . . . . .	704
8.45 oscl_ip_socket.h File Reference . . . . .	705
8.46 oscl_linked_list.h File Reference . . . . .	706
8.47 oscl_lock_base.h File Reference . . . . .	707
8.48 oscl_map.h File Reference . . . . .	708
8.49 oscl_math.h File Reference . . . . .	709
8.50 oscl_media_data.h File Reference . . . . .	710
8.51 oscl_media_status.h File Reference . . . . .	711
8.52 oscl_mem.h File Reference . . . . .	712
8.53 oscl_mem_align.h File Reference . . . . .	715
8.54 oscl_mem_audit.h File Reference . . . . .	716
8.55 oscl_mem_audit_internals.h File Reference . . . . .	718

8.56 oscl_mem_auto_ptr.h File Reference . . . . .	719
8.57 oscl_mem_basic_functions.h File Reference . . . . .	720
8.58 oscl_mem_inst.h File Reference . . . . .	721
8.59 oscl_mem_mempool.h File Reference . . . . .	722
8.60 oscl_mutex.h File Reference . . . . .	723
8.61 oscl_namestring.h File Reference . . . . .	724
8.62 oscl_opaque_type.h File Reference . . . . .	725
8.63 oscl_pqueue.h File Reference . . . . .	726
8.64 oscl_proctstatus.h File Reference . . . . .	727
8.65 oscl_queue.h File Reference . . . . .	728
8.66 oscl_rand.h File Reference . . . . .	729
8.67 oscl_refcounter.h File Reference . . . . .	730
8.68 oscl_refcounter_memfrag.h File Reference . . . . .	731
8.69 oscl_registry_access_client.h File Reference . . . . .	732
8.70 oscl_registry_client.h File Reference . . . . .	733
8.71 oscl_registry_client_impl.h File Reference . . . . .	734
8.72 oscl_registry_serv_impl.h File Reference . . . . .	735
8.73 oscl_registry_serv_impl_global.h File Reference . . . . .	736
8.74 oscl_registry_serv_impl_tls.h File Reference . . . . .	737
8.75 oscl_registry_types.h File Reference . . . . .	738
8.76 oscl_scheduler.h File Reference . . . . .	739
8.77 oscl_scheduler_ao.h File Reference . . . . .	740
8.78 oscl_scheduler_aobase.h File Reference . . . . .	741
8.79 oscl_scheduler_readyq.h File Reference . . . . .	742
8.80 oscl_scheduler_threadcontext.h File Reference . . . . .	743
8.81 oscl_scheduler_tuneables.h File Reference . . . . .	744
8.82 oscl_scheduler_types.h File Reference . . . . .	745
8.83 oscl_semaphore.h File Reference . . . . .	746
8.84 oscl_shared_ptr.h File Reference . . . . .	747
8.85 oscl_singleton.h File Reference . . . . .	748
8.86 oscl_snprintf.h File Reference . . . . .	750
8.87 oscl_socket.h File Reference . . . . .	751
8.88 oscl_socket_accept.h File Reference . . . . .	752
8.89 oscl_socket_bind.h File Reference . . . . .	753
8.90 oscl_socket_connect.h File Reference . . . . .	754
8.91 oscl_socket_imp.h File Reference . . . . .	755

8.92 oscl_socket_imp_base.h File Reference . . . . .	756
8.93 oscl_socket_imp_pv.h File Reference . . . . .	757
8.94 oscl_socket_listen.h File Reference . . . . .	758
8.95 oscl_socket_method.h File Reference . . . . .	759
8.96 oscl_socket_recv.h File Reference . . . . .	760
8.97 oscl_socket_recv_from.h File Reference . . . . .	761
8.98 oscl_socket_request.h File Reference . . . . .	762
8.99 oscl_socket_send.h File Reference . . . . .	763
8.100oscl_socket_send_to.h File Reference . . . . .	764
8.101oscl_socket_serv_imp.h File Reference . . . . .	765
8.102oscl_socket_serv_imp_base.h File Reference . . . . .	766
8.103oscl_socket_serv_imp_pv.h File Reference . . . . .	767
8.104oscl_socket_serv_imp_reqlist.h File Reference . . . . .	768
8.105oscl_socket_shutdown.h File Reference . . . . .	769
8.106oscl_socket_stats.h File Reference . . . . .	770
8.107oscl_socket_tuneables.h File Reference . . . . .	772
8.108oscl_socket_types.h File Reference . . . . .	774
8.109oscl_stdstring.h File Reference . . . . .	776
8.110oscl_str_ptr_len.h File Reference . . . . .	778
8.111oscl_string.h File Reference . . . . .	779
8.112oscl_string_containers.h File Reference . . . . .	780
8.113oscl_string_rep.h File Reference . . . . .	781
8.114oscl_string_uri.h File Reference . . . . .	782
8.115oscl_string_utf8.h File Reference . . . . .	783
8.116oscl_string_utils.h File Reference . . . . .	784
8.117oscl_string_xml.h File Reference . . . . .	785
8.118oscl_tagtree.h File Reference . . . . .	786
8.119oscl_tcp_socket.h File Reference . . . . .	787
8.120oscl_thread.h File Reference . . . . .	788
8.121oscl_tickcount.h File Reference . . . . .	790
8.122oscl_time.h File Reference . . . . .	791
8.123oscl_timer.h File Reference . . . . .	793
8.124oscl_tls.h File Reference . . . . .	794
8.125oscl_tree.h File Reference . . . . .	795
8.126oscl_types.h File Reference . . . . .	796
8.127oscl_udp_socket.h File Reference . . . . .	797

8.128oscl_utf8conv.h File Reference . . . . .	798
8.129oscl_uuid.h File Reference . . . . .	799
8.130oscl_uuid_utils.h File Reference . . . . .	800
8.131oscl_vector.h File Reference . . . . .	801
8.132osclconfig.h File Reference . . . . .	802
8.133osclconfig_ansi_memory.h File Reference . . . . .	804
8.134osclconfig_check.h File Reference . . . . .	805
8.135osclconfig_compiler_warnings.h File Reference . . . . .	806
8.136osclconfig_error.h File Reference . . . . .	807
8.137osclconfig_error_check.h File Reference . . . . .	808
8.138osclconfig_global_new_delete.h File Reference . . . . .	809
8.139osclconfig_global_placement_new.h File Reference . . . . .	810
8.140osclconfig_io.h File Reference . . . . .	811
8.141osclconfig_io_check.h File Reference . . . . .	822
8.142osclconfig_ix86.h File Reference . . . . .	823
8.143osclconfig_lib.h File Reference . . . . .	824
8.144osclconfig_lib_check.h File Reference . . . . .	825
8.145osclconfig_limits_typedefs.h File Reference . . . . .	826
8.146osclconfig_memory.h File Reference . . . . .	827
8.147osclconfig_memory_check.h File Reference . . . . .	828
8.148osclconfig_no_os.h File Reference . . . . .	829
8.149osclconfig_proc.h File Reference . . . . .	830
8.150osclconfig_proc_check.h File Reference . . . . .	831
8.151osclconfig_proc_unix_android.h File Reference . . . . .	833
8.152osclconfig_proc_unix_common.h File Reference . . . . .	835
8.153osclconfig_time.h File Reference . . . . .	837
8.154osclconfig_time_check.h File Reference . . . . .	838
8.155osclconfig_unix_android.h File Reference . . . . .	839
8.156osclconfig_unix_common.h File Reference . . . . .	843
8.157osclconfig_util.h File Reference . . . . .	847
8.158osclconfig_util_check.h File Reference . . . . .	848
8.159pvlogger.h File Reference . . . . .	849
8.160pvlogger_accessories.h File Reference . . . . .	857
8.161pvlogger_c.h File Reference . . . . .	858
8.162pvlogger_registry.h File Reference . . . . .	860

---

9.1 Todo List . . . . .	861
-------------------------	-----

# Chapter 1

## oscl Module Index

### 1.1 oscl Modules

Here is a list of all modules:

OSCL config . . . . .	21
OSCL Base . . . . .	25
OSCL Memory . . . . .	46
OSCL Util . . . . .	62
OSCL Error . . . . .	84
OSCL IO . . . . .	94
OSCL Proc . . . . .	102
OSCL Init . . . . .	106

# Chapter 2

## oscl Hierarchical Index

### 2.1 oscl Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

_OscIHeapBase . . . . .	109
HeapBase . . . . .	136
Oscl_File . . . . .	178
OSCL_String . . . . .	259
OSCL_FastString . . . . .	174
OSCL_HeapString< Alloc > . . . . .	195
OSCL_HeapStringA . . . . .	197
OSCL_StackString< MaxBufSize > . . . . .	256
OsclActiveObject . . . . .	309
OsclAsyncFile . . . . .	315
OsclDNSRequestAO . . . . .	362
OsclGetHostNameRequest . . . . .	413
OsclSocketRequestAO . . . . .	549
OsclAcceptRequest . . . . .	308
OsclBindRequest . . . . .	322
OsclConnectRequest . . . . .	348
OsclListenRequest . . . . .	422
OsclRecvFromRequest . . . . .	487
OsclRecvRequest . . . . .	490
OsclSendRequest . . . . .	523
OsclSendToRequest . . . . .	525
OsclShutdownRequest . . . . .	530
PVSchedulerStopper . . . . .	630
OsclAsyncFileBuffer . . . . .	318
OsclBuf . . . . .	339
OsclDNS . . . . .	350
OsclFileCache . . . . .	400
OsclNativeFile . . . . .	461
OsclPtr . . . . .	476
OsclPtrC . . . . .	478
OsclRegistryClient . . . . .	508
OsclSocketServ . . . . .	553
OsclTCPSocket . . . . .	564

OsclTimerObject . . . . .	585
CallbackTimer< Alloc > . . . . .	123
OsclDNSMethod . . . . .	357
OsclGetHostByNameMethod . . . . .	412
OsclSocketMethod . . . . .	544
OsclAcceptMethod . . . . .	307
OsclBindMethod . . . . .	321
OsclConnectMethod . . . . .	347
OsclListenMethod . . . . .	421
OsclRecvFromMethod . . . . .	485
OsclRecvMethod . . . . .	489
OsclSendMethod . . . . .	522
OsclSendToMethod . . . . .	524
OsclShutdownMethod . . . . .	529
OsclSocketServI . . . . .	555
OsclUDPSocket . . . . .	600
OsclExecSchedulerBase . . . . .	390
OsclExecScheduler . . . . .	388
allocator . . . . .	112
BufferMgr . . . . .	117
BufferState . . . . .	118
BufFragGroup< ChainClass, max_frags > . . . . .	119
MediaData< ChainClass, max_frags, local_bufsize > . . . . .	141
BufFragStatusClass . . . . .	122
MediaStatusClass . . . . .	144
CallbackTimerObserver . . . . .	125
OsclTimer< Alloc > . . . . .	581
CFastRep . . . . .	126
CHheapRep . . . . .	128
CStackRep . . . . .	131
DNSRequestParam . . . . .	132
GetHostByNameParam . . . . .	134
internalLeave . . . . .	138
LinkedListElement< LLClass > . . . . .	139
MemAllocator< T > . . . . .	145
MM_AllocBlockFence . . . . .	146
MM_AllocBlockHdr . . . . .	147
MM_AllocInfo . . . . .	148
MM_AllocNode . . . . .	150
MM_AllocQueryInfo . . . . .	151
MM_Audit_Imp . . . . .	152
MM_AuditOverheadStats . . . . .	160
MM_FailInsertParam . . . . .	161
MM_Stats_CB . . . . .	162
MM_Stats_t . . . . .	163
NTPTime . . . . .	165
Oscl_Alloc . . . . .	169
Oscl_DefAlloc . . . . .	171
_OsclBasicAllocator . . . . .	107
OsclAllocDestructDealloc . . . . .	313
OsclMemAllocDestructDealloc< T > . . . . .	426
OsclMemBasicAllocDestructDealloc< T > . . . . .	439

OsclMemAllocator . . . . .	425
OsclMemBasicAllocator . . . . .	438
OsclMemPoolFixedChunkAllocator . . . . .	442
OsclMemPoolResizableAllocator . . . . .	447
OsclReadyAlloc . . . . .	481
<b>Oscl_Dealloc . . . . .</b>	<b>170</b>
<b>Oscl_DefAlloc . . . . .</b>	<b>171</b>
<b>Oscl_File::OsclCacheObserver . . . . .</b>	<b>186</b>
<b>Oscl_File::OsclFixedCacheParam . . . . .</b>	<b>187</b>
<b>Oscl_FileFind . . . . .</b>	<b>188</b>
<b>Oscl_FileServer . . . . .</b>	<b>192</b>
<b>oscl_fsstat . . . . .</b>	<b>194</b>
<b>Oscl_Int64_Utils . . . . .</b>	<b>202</b>
<b>Oscl_Less&lt; T &gt; . . . . .</b>	<b>204</b>
<b>Oscl_Linked_List_Base . . . . .</b>	<b>210</b>
<b>Oscl_Linked_List&lt; LLClass, Alloc &gt; . . . . .</b>	<b>205</b>
<b>Oscl_Map&lt; Key, T, Alloc, Compare &gt; . . . . .</b>	<b>215</b>
<b>Oscl_Map&lt; Key, T, Alloc, Compare &gt;::value_compare . . . . .</b>	<b>222</b>
<b>Oscl_MTLinked_List&lt; LLClass, Alloc, TheLock &gt; . . . . .</b>	<b>224</b>
<b>Oscl_Opaque_Type_Alloc . . . . .</b>	<b>228</b>
<b>Oscl_Queue&lt; T, Alloc &gt; . . . . .</b>	<b>235</b>
<b>Oscl_Vector&lt; T, Alloc &gt; . . . . .</b>	<b>284</b>
<b>Oscl_Vector&lt; TOsclReady, OsclReadyAlloc &gt; . . . . .</b>	<b>284</b>
<b>Oscl_Opaque_Type_Alloc_LL . . . . .</b>	<b>230</b>
<b>Oscl_Linked_List&lt; LLClass, Alloc &gt; . . . . .</b>	<b>205</b>
<b>Oscl_Opaque_Type_Compare . . . . .</b>	<b>232</b>
<b>OsclPriorityQueue&lt; Qelem, Alloc, Container, Compare &gt; . . . . .</b>	<b>469</b>
<b>OsclPriorityQueue&lt; TOsclReady, OsclReadyAlloc, Oscl_Vector&lt; TOsclReady, OsclReady-Alloc &gt;, OsclReadyCompare &gt; . . . . .</b>	<b>469</b>
<b>OsclReadyQ . . . . .</b>	<b>483</b>
<b>OsclPriorityQueue&lt; TOsclReady, OsclReadyAlloc, Oscl_Vector&lt; TOsclReady, OsclReady-Alloc &gt;, OsclTimerCompare &gt; . . . . .</b>	<b>469</b>
<b>OsclTimerQ . . . . .</b>	<b>590</b>
<b>Oscl_Pair&lt; T1, T2 &gt; . . . . .</b>	<b>234</b>
<b>Oscl_Queue_Base . . . . .</b>	<b>238</b>
<b>Oscl_Queue&lt; T, Alloc &gt; . . . . .</b>	<b>235</b>
<b>Oscl_Rb_Tree_Base . . . . .</b>	<b>245</b>
<b>Oscl_Rb_Tree&lt; Key, Value, KeyOfValue, Compare, Alloc &gt; . . . . .</b>	<b>241</b>
<b>Oscl_Rb_Tree_Const_Iterator&lt; Value &gt; . . . . .</b>	<b>246</b>
<b>Oscl_Rb_Tree_Iterator&lt; Value &gt; . . . . .</b>	<b>249</b>
<b>Oscl_Rb_Tree_Node_Base . . . . .</b>	<b>253</b>
<b>Oscl_Rb_Tree_Node&lt; Value &gt; . . . . .</b>	<b>252</b>
<b>Oscl_Select1st&lt; V, U &gt; . . . . .</b>	<b>255</b>
<b>oscl_stat_buf . . . . .</b>	<b>258</b>
<b>Oscl_Tag_Base . . . . .</b>	<b>266</b>
<b>Oscl_Tag&lt; Alloc &gt; . . . . .</b>	<b>264</b>
<b>Oscl_TagTree&lt; T, Alloc &gt; . . . . .</b>	<b>268</b>
<b>Oscl_TagTree&lt; T, Alloc &gt;::const_iterator . . . . .</b>	<b>272</b>
<b>Oscl_TagTree&lt; T, Alloc &gt;::iterator . . . . .</b>	<b>275</b>
<b>Oscl_TagTree&lt; T, Alloc &gt;::Node . . . . .</b>	<b>278</b>
<b>Oscl_TAlloc&lt; T, Alloc &gt;::rebind&lt; U, V &gt; . . . . .</b>	<b>283</b>

Oscl_Vector_Base . . . . .	289
Oscl_Vector< T, Alloc > . . . . .	284
Oscl_Vector< TOsclReady, OsclReadyAlloc > . . . . .	284
OSCL_wString . . . . .	303
OSCL_wFastString . . . . .	293
OSCL_wHeapString< Alloc > . . . . .	296
OSCL_wHeapStringA . . . . .	298
OSCL_wStackString< MaxBufSize > . . . . .	301
OsclAOStatus . . . . .	314
OsclAuditCB . . . . .	320
OsclBinStream . . . . .	335
OsclBinIStream . . . . .	323
OsclBinIStreamBigEndian . . . . .	325
OsclBinIStreamLittleEndian . . . . .	328
OsclBinOStream . . . . .	330
OsclBinOStreamBigEndian . . . . .	331
OsclBinOStreamLittleEndian . . . . .	333
OsclCompareLess< T > . . . . .	341
OsclComponentRegistry . . . . .	342
OsclComponentRegistryData . . . . .	344
OsclComponentRegistryElement . . . . .	345
OsclDestructDealloc . . . . .	349
Oscl_TAlloc< T, Alloc > . . . . .	280
OsclAllocDestructDealloc . . . . .	313
OsclDNSIBase . . . . .	354
OsclDNSI . . . . .	352
OsclDNSObserver . . . . .	360
OsclDNSRequest . . . . .	361
OsclDoubleLink . . . . .	365
OsclPriorityLink . . . . .	467
OsclDoubleListBase . . . . .	367
OsclDoubleList< T > . . . . .	366
OsclPriorityList< T > . . . . .	468
OsclDoubleRunner< T > . . . . .	369
OsclError . . . . .	371
OsclErrorAllocator . . . . .	373
OsclErrorTrap . . . . .	375
OsclErrorTrapImp . . . . .	376
OsclException< LeaveCode > . . . . .	378
OsclExclusiveArrayPtr< T > . . . . .	379
OsclExclusivePtr< T > . . . . .	382
OsclExclusivePtrA< T, Alloc > . . . . .	385
OsclExecSchedulerCommonBase . . . . .	391
OsclExecScheduler . . . . .	388
OsclFileCacheBuffer . . . . .	402
OsclFileHandle . . . . .	404
OsclFileManager . . . . .	405
OsclFileStats . . . . .	410
OsclFileStatsItem . . . . .	411
OsclInit . . . . .	414
OsclInteger64Transport . . . . .	415

OsclIpMReq . . . . .	416
OsclIPSocketI . . . . .	417
OsclTCPSocketI . . . . .	571
OsclUDPSocketI . . . . .	606
OsclJump . . . . .	420
OsclLockBase . . . . .	423
OsclMutex . . . . .	458
OsclNullLock . . . . .	466
OsclThreadLock . . . . .	578
OsclMem . . . . .	424
OsclMemAudit . . . . .	428
OSCLMemAutoPtr< T, _Allocator > . . . . .	434
OsclMemGlobalAuditObject . . . . .	440
OsclMemoryFragment . . . . .	441
BufferFragment . . . . .	116
OsclMemPoolFixedChunkAllocatorObserver . . . . .	446
OsclMemPoolResizableAllocator::MemPoolBlockInfo . . . . .	453
OsclMemPoolResizableAllocator::MemPoolBufferInfo . . . . .	454
OsclMemPoolResizableAllocatorMemoryObserver . . . . .	455
OsclMemPoolResizableAllocatorObserver . . . . .	456
OsclMemStatsNode . . . . .	457
OsclNameString< __len > . . . . .	460
OsclNativeFileParams . . . . .	464
OsclNetworkAddress . . . . .	465
OsclPriorityQueueBase . . . . .	473
OsclPriorityQueue< Qelem, Alloc, Container, Compare > . . . . .	469
OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl_Vector< TOsclReady, OsclReady-Alloc >, OsclReadyCompare > . . . . .	469
OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl_Vector< TOsclReady, OsclReady-Alloc >, OsclTimerCompare > . . . . .	469
OsclProcStatus . . . . .	474
OsclRand . . . . .	480
OsclReadyCompare . . . . .	482
OsclRefCounter . . . . .	491
Oscl_DefAllocWithRefCounter< DefAlloc > . . . . .	172
OsclRefCounterDA . . . . .	493
OsclRefCounterMTDA< LockType > . . . . .	497
OsclRefCounterMTSA< DeallocType, LockType > . . . . .	499
OsclRefCounterSA< DeallocType > . . . . .	501
OsclRefCounterMemFrag . . . . .	495
OsclRegistryAccessClient . . . . .	503
OsclRegistryAccessElement . . . . .	507
OsclRegistryClientImpl . . . . .	510
OsclRegistryAccessClientImpl . . . . .	505
OsclRegistryServTlsImpl . . . . .	513
OsclRegistryAccessClientTlsImpl . . . . .	506
OsclRegistryClientTlsImpl . . . . .	512
OsclScheduler . . . . .	515
OsclSchedulerObserver . . . . .	516
OsclScopedLock< LockClass > . . . . .	517
OsclSelect . . . . .	518
OsclSemaphore . . . . .	520

OsclSharedPtr< TheClass > . . . . .	526
OsclSingleton< T, ID, Registry > . . . . .	531
OsclSingletonRegistry . . . . .	533
OsclSocketIBase . . . . .	539
OsclSocketI . . . . .	534
OsclSocketObserver . . . . .	547
OsclSocketRequest . . . . .	548
OsclSocketServIBase . . . . .	557
OsclSocketServI . . . . .	555
OsclSocketServRequestList . . . . .	559
OsclSocketServRequestQElem . . . . .	561
OsclSocketTOS . . . . .	562
OsclThread . . . . .	574
OsclTickCount . . . . .	579
OsclTimerCompare . . . . .	584
OsclTimerObserver . . . . .	589
OsclTLS< T, ID, Registry > . . . . .	591
OsclTLSE< T, ID, Registry > . . . . .	593
OsclTLSRegistry . . . . .	595
OsclTLSRegistryEx . . . . .	596
OsclTrapItem . . . . .	597
OsclTrapStack . . . . .	598
OsclTrapStackItem . . . . .	599
OsclUuid . . . . .	609
PVActiveBase . . . . .	611
OsclActiveObject . . . . .	309
OsclTimerObject . . . . .	585
PVActiveStats . . . . .	615
PVLogger . . . . .	616
PVLoggerAppender . . . . .	622
PVLoggerFilter . . . . .	623
AllPassFilter . . . . .	113
PVLoggerLayout . . . . .	625
PVLoggerRegistry . . . . .	627
PVSockBufRecv . . . . .	631
PVSockBufSend . . . . .	632
PVThreadContext . . . . .	633
SocketRequestParam . . . . .	641
AcceptParam . . . . .	111
BindParam . . . . .	115
ConnectParam . . . . .	130
ListenParam . . . . .	140
RecvFromParam . . . . .	635
RecvParam . . . . .	637
SendParam . . . . .	638
SendToParam . . . . .	639
ShutdownParam . . . . .	640
StrPtrLen . . . . .	646
StrCSumPtrLen . . . . .	643
TimeValue . . . . .	648
TLSStorageOps . . . . .	655
TReadyQueLink . . . . .	656

WStrPtrLen . . . . . [657](#)

# Chapter 3

## oscl Data Structure Index

### 3.1 oscl Data Structures

Here are the data structures with brief descriptions:

_OsclBasicAllocator . . . . .	107
_OsclHeapBase . . . . .	109
AcceptParam . . . . .	111
allocator . . . . .	112
AllPassFilter . . . . .	113
BindParam . . . . .	115
BufferFragment . . . . .	116
BufferMgr . . . . .	117
BufferState . . . . .	118
BufFragGroup< ChainClass, max_frags >	119
BufFragStatusClass . . . . .	122
CallbackTimer< Alloc > . . . . .	123
CallbackTimerObserver . . . . .	125
CFastRep . . . . .	126
CHheapRep . . . . .	128
ConnectParam . . . . .	130
CStackRep . . . . .	131
DNSRequestParam . . . . .	132
GetHostNameParam . . . . .	134
HeapBase . . . . .	136
internalLeave . . . . .	138
LinkedListElement< LLClass > . . . . .	139
ListenParam . . . . .	140
MediaData< ChainClass, max_frags, local_bufsize >	141
MediaStatusClass . . . . .	144
MemAllocator< T > . . . . .	145
MM_AllocBlockFence . . . . .	146
MM_AllocBlockHdr . . . . .	147
MM_AllocInfo . . . . .	148
MM_AllocNode . . . . .	150
MM_AllocQueryInfo . . . . .	151
MM_Audit_Imp . . . . .	152
MM_AuditOverheadStats . . . . .	160

MM_FailInsertParam . . . . .	161
MM_Stats_CB . . . . .	162
MM_Stats_t . . . . .	163
NTPTime (Time value as the number of seconds since 0h (UTC) Jan. 1, 1900) . . . . .	165
OscI_Alloc . . . . .	169
OscI_Dealloc . . . . .	170
OscI_DefAlloc . . . . .	171
OscI_DefAllocWithRefCounter< DefAlloc > . . . . .	172
OSCL_FastString . . . . .	174
OscI_File . . . . .	178
OscI_File::OsclCacheObserver . . . . .	186
OscI_File::OsclFixedCacheParam . . . . .	187
OscI_FileFind . . . . .	188
OscI_FileServer . . . . .	192
oscl_fstat . . . . .	194
OSCL_HeapString< Alloc > . . . . .	195
OSCL_HeapStringA . . . . .	197
OscI_Int64_Utils (Wrapper for commonly used int64/uint64 operations) . . . . .	202
OscI_Less< T > . . . . .	204
OscI_Linked_List< LLClass, Alloc > . . . . .	205
OscI_Linked_List_Base . . . . .	210
OscI_Map< Key, T, Alloc, Compare > . . . . .	215
OscI_Map< Key, T, Alloc, Compare >::value_compare . . . . .	222
OscI_MTLinked_List< LLClass, Alloc, TheLock > . . . . .	224
OscI_Opaque_Type_Alloc . . . . .	228
OscI_Opaque_Type_Alloc_LL . . . . .	230
OscI_Opaque_Type_Compare . . . . .	232
OscI_Pair< T1, T2 > . . . . .	234
OscI_Queue< T, Alloc > . . . . .	235
OscI_Queue_Base . . . . .	238
OscI_Rb_Tree< Key, Value, KeyOfValue, Compare, Alloc > . . . . .	241
OscI_Rb_Tree_Base . . . . .	245
OscI_Rb_Tree_Const_Iterator< Value > . . . . .	246
OscI_Rb_Tree_Iterator< Value > . . . . .	249
OscI_Rb_Tree_Node< Value > . . . . .	252
OscI_Rb_Tree_Node_Base . . . . .	253
OscI_Select1st< V, U > . . . . .	255
OSCL_StackString< MaxBufSize > . . . . .	256
oscl_stat_buf . . . . .	258
OSCL_String . . . . .	259
OscI_Tag< Alloc > . . . . .	264
OscI_Tag_Base . . . . .	266
OscI_TagTree< T, Alloc > . . . . .	268
OscI_TagTree< T, Alloc >::const_iterator . . . . .	272
OscI_TagTree< T, Alloc >::iterator . . . . .	275
OscI_TagTree< T, Alloc >::Node . . . . .	278
OscI_TAlloc< T, Alloc > . . . . .	280
OscI_TAlloc< T, Alloc >::rebind< U, V > . . . . .	283
OscI_Vector< T, Alloc > . . . . .	284
OscI_Vector_Base . . . . .	289
OSCL_wFastString . . . . .	293
OSCL_wHeapString< Alloc > . . . . .	296
OSCL_wHeapStringA . . . . .	298
OSCL_wStackString< MaxBufSize > . . . . .	301

<b>OSCL_wString</b>	303
<b>OsclAcceptMethod</b>	307
<b>OsclAcceptRequest</b>	308
<b>OsclActiveObject</b>	309
<b>OsclAllocDestructDealloc</b>	313
<b>OsclAOStatus</b>	314
<b>OsclAsyncFile</b>	315
<b>OsclAsyncFileBuffer</b>	318
<b>OsclAuditCB</b>	320
<b>OsclBindMethod</b>	321
<b>OsclBindRequest</b>	322
<b>OsclBinIStream</b>	323
<b>OsclBinIStreamBigEndian</b>	325
<b>OsclBinIStreamLittleEndian</b>	328
<b>OsclBinOStream</b> (Class OsclBinOStream implements the basic stream functions for an output stream)	330
<b>OsclBinOStreamBigEndian</b> (Class OsclBinOStreamBigEndian implements a binary output stream using big endian byte ordering)	331
<b>OsclBinOStreamLittleEndian</b> (Class OsclBinOStreamLittleEndian implements a binary output stream using little endian byte ordering)	333
<b>OsclBinStream</b>	335
<b>OsclBuf</b>	339
<b>OsclCompareLess&lt; T &gt;</b>	341
<b>OsclComponentRegistry</b>	342
<b>OsclComponentRegistryData</b>	344
<b>OsclComponentRegistryElement</b>	345
<b>OsclConnectMethod</b>	347
<b>OsclConnectRequest</b>	348
<b>OsclDestructDealloc</b>	349
<b>OsclDNS</b>	350
<b>OsclDNSI</b>	352
<b>OsclDNSIBase</b>	354
<b>OsclDNSMethod</b>	357
<b>OsclDNSObserver</b>	360
<b>OsclDNSRequest</b>	361
<b>OsclDNSRequestAO</b>	362
<b>OsclDoubleLink</b>	365
<b>OsclDoubleList&lt; T &gt;</b>	366
<b>OsclDoubleListBase</b>	367
<b>OsclDoubleRunner&lt; T &gt;</b>	369
<b>OsclError</b>	371
<b>OsclErrorAllocator</b> (This class provides static methods to invoke the user defined memory allocation routines)	373
<b>OsclErrorTrap</b>	375
<b>OsclErrorTrapImp</b>	376
<b>OsclException&lt; LeaveCode &gt;</b> (Oscl_exception.h contains all the exception handling macros and classes This template class provides the base exception class that all exceptions derive from)	378
<b>OsclExclusiveArrayPtr&lt; T &gt;</b> (Template class that defines an array pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the OsclExclusiveArrayPtr expires, its destructor uses delete to free the memory)	379
<b>OsclExclusivePtr&lt; T &gt;</b> (Template class that defines a pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the OsclExclusivePtr expires, its destructor uses delete to free the memory)	382

<b>OsclExclusivePtrA&lt; T, Alloc &gt;</b> (Template class that defines any pointer like object intended to be assigned an address obtained (directly or or indirectly) through Alloc. When the OsclExclusivePtrA expires, Alloc is used to free the memory) . . . . .	385
<b>OsclExecScheduler</b> . . . . .	388
<b>OsclExecSchedulerBase</b> . . . . .	390
<b>OsclExecSchedulerCommonBase</b> . . . . .	391
<b>OsclFileCache</b> . . . . .	400
<b>OsclFileCacheBuffer</b> . . . . .	402
<b>OsclFileHandle</b> . . . . .	404
<b>OsclFileManager</b> . . . . .	405
<b>OsclFileStats</b> . . . . .	410
<b>OsclFileStatsItem</b> . . . . .	411
<b>OsclGetHostNameMethod</b> . . . . .	412
<b>OsclGetHostNameRequest</b> . . . . .	413
<b>OsclInit</b> . . . . .	414
<b>OsclInteger64Transport</b> . . . . .	415
<b>OsclIpMReq</b> . . . . .	416
<b>OsclIPSocketI</b> . . . . .	417
<b>OsclJump</b> . . . . .	420
<b>OsclListenMethod</b> . . . . .	421
<b>OsclListenRequest</b> . . . . .	422
<b>OsclLockBase</b> . . . . .	423
<b>OsclMem</b> . . . . .	424
<b>OsclMemAllocator</b> . . . . .	425
<b>OsclMemAllocDestructDealloc&lt; T &gt;</b> . . . . .	426
<b>OsclMemAudit</b> . . . . .	428
<b>OSCLMemAutoPtr&lt; T, _Allocator &gt;</b> (The oscl_auto_ptr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the oscl_auto_ptr expires, its destructor uses delete to free the memory) . . . . .	434
<b>OsclMemBasicAllocator</b> . . . . .	438
<b>OsclMemBasicAllocDestructDealloc&lt; T &gt;</b> . . . . .	439
<b>OsclMemGlobalAuditObject</b> . . . . .	440
<b>OsclMemoryFragment</b> . . . . .	441
<b>OsclMemPoolFixedChunkAllocator</b> . . . . .	442
<b>OsclMemPoolFixedChunkAllocatorObserver</b> . . . . .	446
<b>OsclMemPoolResizableAllocator</b> . . . . .	447
<b>OsclMemPoolResizableAllocator::MemPoolBlockInfo</b> . . . . .	453
<b>OsclMemPoolResizableAllocator::MemPoolBufferInfo</b> . . . . .	454
<b>OsclMemPoolResizableAllocatorMemoryObserver</b> . . . . .	455
<b>OsclMemPoolResizableAllocatorObserver</b> . . . . .	456
<b>OsclMemStatsNode</b> . . . . .	457
<b>OsclMutex</b> . . . . .	458
<b>OsclNameString&lt; __len &gt;</b> . . . . .	460
<b>OsclNativeFile</b> . . . . .	461
<b>OsclNativeFileParams</b> . . . . .	464
<b>OsclNetworkAddress</b> . . . . .	465
<b>OsclNullLock</b> . . . . .	466
<b>OsclPriorityLink</b> . . . . .	467
<b>OsclPriorityList&lt; T &gt;</b> . . . . .	468
<b>OsclPriorityQueue&lt; Qelem, Alloc, Container, Compare &gt;</b> . . . . .	469
<b>OsclPriorityQueueBase</b> . . . . .	473
<b>OsclProcStatus</b> . . . . .	474
<b>OsclPtr</b> . . . . .	476

OsclPtrC . . . . .	478
OsclRand . . . . .	480
OsclReadyAlloc . . . . .	481
OsclReadyCompare . . . . .	482
OsclReadyQ . . . . .	483
OsclRecvFromMethod . . . . .	485
OsclRecvFromRequest . . . . .	487
OsclRecvMethod . . . . .	489
OsclRecvRequest . . . . .	490
OsclRefCounter . . . . .	491
OsclRefCounterDA . . . . .	493
OsclRefCounterMemFrag . . . . .	495
OsclRefCounterMTDA< LockType > . . . . .	497
OsclRefCounterMTSA< DeallocType, LockType > . . . . .	499
OsclRefCounterSA< DeallocType > . . . . .	501
OsclRegistryAccessClient . . . . .	503
OsclRegistryAccessClientImpl . . . . .	505
OsclRegistryAccessClientTlsImpl . . . . .	506
OsclRegistryAccessElement . . . . .	507
OsclRegistryClient . . . . .	508
OsclRegistryClientImpl . . . . .	510
OsclRegistryClientTlsImpl . . . . .	512
OsclRegistryServTlsImpl . . . . .	513
OsclScheduler . . . . .	515
OsclSchedulerObserver . . . . .	516
OsclScopedLock< LockClass > (Template class that handles unlocking an abstract class on destruction. This is very useful for ensuring that the lock is released when the OsclScopedLock goes out of scope) . . . . .	517
OsclSelect . . . . .	518
OsclSemaphore . . . . .	520
OsclSendMethod . . . . .	522
OsclSendRequest . . . . .	523
OsclSendToMethod . . . . .	524
OsclSendToRequest . . . . .	525
OsclSharedPtr< TheClass > (A parameterized smart pointer class) . . . . .	526
OsclShutdownMethod . . . . .	529
OsclShutdownRequest . . . . .	530
OsclSingleton< T, ID, Registry > . . . . .	531
OsclSingletonRegistry . . . . .	533
OsclSocketI . . . . .	534
OsclSocketIBase . . . . .	539
OsclSocketMethod . . . . .	544
OsclSocketObserver . . . . .	547
OsclSocketRequest . . . . .	548
OsclSocketRequestAO . . . . .	549
OsclSocketServ . . . . .	553
OsclSocketServI . . . . .	555
OsclSocketServIBase . . . . .	557
OsclSocketServRequestList . . . . .	559
OsclSocketServRequestQElem . . . . .	561
OsclSocketTOS . . . . .	562
OsclTCPSocket . . . . .	564
OsclTCPSocketI . . . . .	571
OsclThread . . . . .	574

OsclThreadLock	578
OsclTickCount	579
OsclTimer< Alloc >	581
OsclTimerCompare	584
OsclTimerObject	585
OsclTimerObserver	589
OsclTimerQ	590
OsclTLS< T, ID, Registry >	591
OsclTLSE< T, ID, Registry >	593
OsclTLSRegistry	595
OsclTLSRegistryEx	596
OsclTrapItem	597
OsclTrapStack	598
OsclTrapStackItem	599
OsclUDPSocket	600
OsclUDPSocketI	606
OsclUuid	609
PVActiveBase	611
PVActiveStats	615
PVLogger	616
PVLoggerAppender	622
PVLoggerFilter	623
PVLoggerLayout	625
PVLoggerRegistry	627
PVSchedulerStopper	630
PVSockBufRecv	631
PVSockBufSend	632
PVThreadContext	633
RecvFromParam	635
RecvParam	637
SendParam	638
SendToParam	639
ShutdownParam	640
SocketRequestParam	641
StrCSumPtrLen (Same as StrPtrLen, but includes checksum field and method to speed up querying)	643
StrPtrLen (This data structure encapsulates a set of functions used to perform)	646
TimeValue (Time value in a format native to the system)	648
TLSStorageOps	655
TReadyQueLink	656
WStrPtrLen (This data structure encapsulates a set of functions used to perform)	657

# Chapter 4

## oscl File Index

### 4.1 oscl File List

Here is a list of all files with brief descriptions:

<code>oscl_aostatus.h</code> (Some basic types used with active objects) . . . . .	659
<code>oscl_assert.h</code> (The file <code>oscl_assert.h</code> provides an OSCL_ASSERT macro to document assumptions and test them during development) . . . . .	660
<code>oscl_base.h</code> (The file <code>oscl_base.h</code> is the public header that should be included to pick up the platform configuration, basic type definitions, and common macros) . . . . .	661
<code>oscl_base_alloc.h</code> (A basic allocator that does not rely on other modules) . . . . .	662
<code>oscl_base_macros.h</code> (This file defines common macros and constants for basic compilation support)	663
<code>oscl_bin_stream.h</code> (Defines a set of binary stream classes which handle portable input / output of binary data regardless of the native byte order) . . . . .	664
<code>oscl_byte_order.h</code> (This file defines functions providing byte ordering utility (e.g., switching between big and little endian orders)) . . . . .	665
<code>oscl_defalloc.h</code> (The file defines simple default memory allocator classes. These allocators are used by the <code>Oscl_Vector</code> and <code>Oscl_Map</code> class, etc) . . . . .	666
<code>oscl_dll.h</code> (Defines a DLL entry point) . . . . .	667
<code>oscl_dns.h</code> (The file <code>oscl_socket.h</code> defines the OSCL DNS APIs) . . . . .	668
<code>oscl_dns_gethostbyname.h</code> . . . . .	669
<code>oscl_dns_imp.h</code> . . . . .	670
<code>oscl_dns_imp_base.h</code> . . . . .	671
<code>oscl_dns_imp_pv.h</code> . . . . .	672
<code>oscl_dns_method.h</code> . . . . .	673
<code>oscl_dns_param.h</code> . . . . .	674
<code>oscl_dns_request.h</code> . . . . .	675
<code>oscl_dns_tuneables.h</code> . . . . .	676
<code>oscl_double_list.h</code> (Internal use types for scheduler) . . . . .	677
<code>oscl_errno.h</code> (Defines functions to access additional information on errors where supported through an errno or similar service) . . . . .	678
<code>oscl_error.h</code> (OSCL Error trap and cleanup include file) . . . . .	679
<code>oscl_error_allocator.h</code> (Defines a memory allocation class used by the oscl error layer) . . . . .	680
<code>oscl_error_codes.h</code> (Defines basic error and leave codes) . . . . .	681
<code>oscl_error_imp.h</code> (Internal error implementation support) . . . . .	682
<code>oscl_error_imp_cppexceptions.h</code> (Implementation File for Leave using C++ exceptions) . . . . .	683
<code>oscl_error_imp_fatalerror.h</code> (Implementation File for Leave using system fatal error) . . . . .	684
<code>oscl_error_imp_jumps.h</code> (Implemenation of using Setjmp / Longjmp) . . . . .	685

<code>oscl_error_trapcleanup.h</code> (OSCL Error trap and cleanup implementation include file) . . . . .	687
<code>oscl_exception.h</code> (Contains all the exception handling macros and classes) . . . . .	688
<code>oscl_exclusive_ptr.h</code> (This file defines the <code>OsclExclusivePtr</code> template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error) . . . . .	689
<code>oscl_file_async_read.h</code> . . . . .	690
<code>oscl_file_cache.h</code> (The file <code>oscl_file_cache.h</code> defines the class <code>OsclFileCache</code> ) . . . . .	691
<code>oscl_file_dir_utils.h</code> (The file <code>oscl_file_dir_utils.h</code> defines some unix-style directory ops) . . . . .	692
<code>oscl_file_find.h</code> (The file <code>oscl_file_find.h</code> defines the class <code>Oscl_FileFind</code> ) . . . . .	694
<code>oscl_file_handle.h</code> (The file <code>oscl_file_handle.h</code> defines the class <code>OsclFileHandle</code> ) . . . . .	695
<code>oscl_file_io.h</code> (The file <code>oscl_file_io.h</code> defines the class <code>Oscl_File</code> . This is the public API to the basic file I/O operations) . . . . .	696
<code>oscl_file_manager.h</code> (File management class) . . . . .	697
<code>oscl_file_native.h</code> (The file <code>oscl_file_native.h</code> defines the class <code>OsclNativeFile</code> . This is the porting layer for basic file I/O operations) . . . . .	698
<code>oscl_file_server.h</code> (The file <code>oscl_file_server.h</code> defines the class <code>Oscl_FileServer</code> . This is the porting layer for file server implementations) . . . . .	699
<code>oscl_file_stats.h</code> (File stats class) . . . . .	700
<code>oscl_file_types.h</code> (The file <code>oscl_file_types.h</code> defines some constants and types for file I/O implementations. Anything that needs to be shared across implementation modules can go here) . . . . .	701
<code>oscl_heapbase.h</code> (OSCL Heap Base include file) . . . . .	702
<code>oscl_init.h</code> (Global oscl initialization) . . . . .	703
<code>oscl_int64_utils.h</code> . . . . .	704
<code>oscl_ip_socket.h</code> . . . . .	705
<code>oscl_linked_list.h</code> (The file <code>oscl_linked_list.h</code> defines the template class <code>Oscl_Linked_List</code> which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter) . . . . .	706
<code>oscl_lock_base.h</code> (This file defines an abstract lock class, <code>OsclLockBase</code> , that is used for APIs potentially requiring multi-thread safety. A null-lock implementation, <code>OsclNullLock</code> , is also provided for single-thread configurations (basically a noop for lock/unlock). Also provides the <code>OsclScopedLock</code> class which is template class takes care of freeing the lock when the class goes out of scope) . . . . .	707
<code>oscl_map.h</code> (The file <code>oscl_map.h</code> defines the template class <code>Oscl_Map</code> which has a very similar API as the STL Map class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter) . . . . .	708
<code>oscl_math.h</code> (Provides math functions) . . . . .	709
<code>oscl_media_data.h</code> (Defines a container class for media data made up of a collection of memory fragments) . . . . .	710
<code>oscl_media_status.h</code> (Defines a status values for the <code>MediaData</code> containers) . . . . .	711
<code>oscl_mem.h</code> (This file contains basic memory definitions for common use across platforms) . . . . .	712
<code>oscl_mem_align.h</code> . . . . .	715
<code>oscl_mem_audit.h</code> (This file contains the definition and partial implementation of MM_Audit class) . . . . .	716
<code>oscl_mem_audit_internals.h</code> (This file contains the internal definitions for the mem audit library) . . . . .	718
<code>oscl_mem_auto_ptr.h</code> (This file defines the <code>oscl_mem_auto_ptr</code> template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error) . . . . .	719
<code>oscl_mem_basic_functions.h</code> (This file contains prototypes for the basic memory functions) . . . . .	720
<code>oscl_mem_inst.h</code> (The file defines default memory instrumentation level) . . . . .	721
<code>oscl_mem_mempool.h</code> (This file contains the definition of memory pool allocators) . . . . .	722
<code>oscl_mutex.h</code> (This file provides implementation of mutex) . . . . .	723
<code>oscl_namestring.h</code> (Name string class include file) . . . . .	724

<code>oscl_opaque_type.h</code> (The file <code>oscl_opaque_type.h</code> defines pure virtual classes for working with opaque types) . . . . .	725
<code>oscl_pqueue.h</code> (Implements a priority queue data structure similar to STL) . . . . .	726
<code>oscl_proctstatus.h</code> . . . . .	727
<code>oscl_queue.h</code> (The file <code>oscl_queue.h</code> defines the template class <code>Oscl_Queue</code> . It is similar to the <code>STL::queue</code> class, with some differences: - less complete - based on array rather than a deque - some interfaces modeled on <code>oscl_vector</code> , for ease of transition Memory allocation is abstracted through the use of an allocator template parameter) . . . . .	728
<code>oscl_rand.h</code> (Provides pseudo-random number generation) . . . . .	729
<code>oscl_refcounter.h</code> (A general purpose reference counter to object lifetimes) . . . . .	730
<code>oscl_refcounter_memfrag.h</code> (This file provides the definition of reference counted memory fragment, which provides access to a buffer and helps manage its lifetime through the refcount) . . . . .	731
<code>oscl_registry_access_client.h</code> (Client-side implementation Registry Access implementation) . . . . .	732
<code>oscl_registry_client.h</code> (Client-side implementation of <code>OsclRegistry</code> ) . . . . .	733
<code>oscl_registry_client_impl.h</code> (Client-side implementation of <code>OsclRegistryInterface</code> ) . . . . .	734
<code>oscl_registry_serv_impl.h</code> (Server-side implementation of <code>OsclRegistry</code> interfaces) . . . . .	735
<code>oscl_registry_serv_impl_global.h</code> . . . . .	736
<code>oscl_registry_serv_impl_tls.h</code> . . . . .	737
<code>oscl_registry_types.h</code> (Common types used in <code>Oscl registry</code> interfaces) . . . . .	738
<code>oscl_scheduler.h</code> . . . . .	739
<code>oscl_scheduler_ao.h</code> ( <code>Oscl Scheduler</code> user execution object classes) . . . . .	740
<code>oscl_scheduler_aobase.h</code> ( <code>Oscl Scheduler</code> internal active object classes) . . . . .	741
<code>oscl_scheduler_readyq.h</code> (Ready q types for <code>oscl scheduler</code> ) . . . . .	742
<code>oscl_scheduler_threadcontext.h</code> (Thread context functions needed by <code>oscl scheduler</code> ) . . . . .	743
<code>oscl_scheduler_tuneables.h</code> (Tunable settings for <code>Oscl Scheduler</code> ) . . . . .	744
<code>oscl_scheduler_types.h</code> (Scheduler common types include file) . . . . .	745
<code>oscl_semaphore.h</code> (This file provides implementation of mutex) . . . . .	746
<code>oscl_shared_ptr.h</code> (This file defines a template class <code>OsclSharedPtr</code> which is a "smart pointer" to the parameterized type) . . . . .	747
<code>oscl_singleton.h</code> (This file defines the <code>OsclSingleton</code> class. This class provides a container which used to give access to a set of process-level singleton objects. Each object is indexed by an integer ID, listed below. There can only be one instance of each object per process at a given time) . . . . .	748
<code>oscl_snprintf.h</code> (Provides a portable implementation of <code>snprintf</code> ) . . . . .	750
<code>oscl_socket.h</code> (The file <code>oscl_socket.h</code> defines the OSCL Socket APIs) . . . . .	751
<code>oscl_socket_accept.h</code> . . . . .	752
<code>oscl_socket_bind.h</code> . . . . .	753
<code>oscl_socket_connect.h</code> . . . . .	754
<code>oscl_socket_imp.h</code> . . . . .	755
<code>oscl_socket_imp_base.h</code> . . . . .	756
<code>oscl_socket_imp_pv.h</code> . . . . .	757
<code>oscl_socket_listen.h</code> . . . . .	758
<code>oscl_socket_method.h</code> . . . . .	759
<code>oscl_socket_recv.h</code> . . . . .	760
<code>oscl_socket_recv_from.h</code> . . . . .	761
<code>oscl_socket_request.h</code> . . . . .	762
<code>oscl_socket_send.h</code> . . . . .	763
<code>oscl_socket_send_to.h</code> . . . . .	764
<code>oscl_socket_serv_imp.h</code> . . . . .	765
<code>oscl_socket_serv_imp_base.h</code> . . . . .	766
<code>oscl_socket_serv_imp_pv.h</code> . . . . .	767
<code>oscl_socket_serv_imp_reqlist.h</code> . . . . .	768
<code>oscl_socket_shutdown.h</code> . . . . .	769

<a href="#">oscl_socket_stats.h</a>	770
<a href="#">oscl_socket_tunables.h</a>	772
<a href="#">oscl_socket_types.h</a>	774
<a href="#">oscl_stdstring.h</a> (This file provides standard string operations such as strlen, strncpy, etc. ANSI defines undefined behavior when the destination pointer is null for operations such as strncpy, strncat, etc. But, we chose to define one. In such cases, we return the destination as null)	776
<a href="#">oscl_str_ptr_len.h</a> (Defines a data structure for string containment/manipulations where the storage for the string is maintained externally)	778
<a href="#">oscl_string.h</a> (Provides a standardized set of string containers that can be used in place of character arrays)	779
<a href="#">oscl_string_containers.h</a> (Provides a standardized set of string containers that can be used in place of character arrays)	780
<a href="#">oscl_string_rep.h</a> (Contains some internal implementation for string containers)	781
<a href="#">oscl_string_uri.h</a> (Utilities to unescape URIs)	782
<a href="#">oscl_string_utf8.h</a> (Utilities to validate and truncate UTF-8 encoded strings)	783
<a href="#">oscl_string_utils.h</a> (Utilities to parse and convert strings)	784
<a href="#">oscl_string_xml.h</a> (Utilities to escape special characters in XML strings)	785
<a href="#">oscl_tagtree.h</a> (The file <a href="#">oscl_tagtree.h</a> ..)	786
<a href="#">oscl_tcp_socket.h</a>	787
<a href="#">oscl_thread.h</a>	788
<a href="#">oscl_tickcount.h</a> (Defines a data structure for string containment/manipulations where the storage for the string is maintained externally)	790
<a href="#">oscl_time.h</a> (The file <a href="#">oscl_time.h</a> defines two classes <a href="#">NTPTime</a> and <a href="#">TimeValue</a> for getting, manipulating, and formatting time values. The <a href="#">TimeValue</a> class is based on the native system time format while <a href="#">NTPTime</a> is used for the standard Network Time Protocol format)	791
<a href="#">oscl_timer.h</a>	793
<a href="#">oscl_tls.h</a>	794
<a href="#">oscl_tree.h</a> (The file <a href="#">oscl_tree.h</a> defines the template class <a href="#">Oscl_Rb_Tree</a> which has a very similar API as the STL Tree class. It is an implementation of a Red-Black Tree for use by the <a href="#">Oscl_Map</a> class. Memory allocation is abstracted through the use of an allocator template parameter)	795
<a href="#">oscl_types.h</a> (This file contains basic type definitions for common use across platforms)	796
<a href="#">oscl_udp_socket.h</a>	797
<a href="#">oscl_utf8conv.h</a> (Utilities to convert unicode to utf8 and vice versa)	798
<a href="#">oscl_uuid.h</a> (This file defines the OSCL UUID structure used for unique identifiers as well as the short (32-bit) identifiers OsclUuid32)	799
<a href="#">oscl_uuid_utils.h</a>	800
<a href="#">oscl_vector.h</a> (The file <a href="#">oscl_vector.h</a> defines the template class <a href="#">Oscl_Vector</a> which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter)	801
<a href="#">osclconfig.h</a> (This file contains configuration information for the linux platform)	802
<a href="#">osclconfig_ansi_memory.h</a> (This file contains common typedefs based on the ANSI C limits.h header)	804
<a href="#">osclconfig_check.h</a>	805
<a href="#">osclconfig_compiler_warnings.h</a> (This file contains the ability to turn off/on compiler warnings)	806
<a href="#">osclconfig_error.h</a> (This file contains the common typedefs and header files needed to compile osclerror)	807
<a href="#">osclconfig_error_check.h</a>	808
<a href="#">osclconfig_global_new_delete.h</a>	809
<a href="#">osclconfig_global_placement_new.h</a>	810
<a href="#">osclconfig_io.h</a> (This file contains common typedefs based on the ANSI C limits.h header)	811
<a href="#">osclconfig_io_check.h</a>	822

<a href="#">osclconfig_ix86.h</a> (This file contains configuration information for the ix86 processor family) . . .	823
<a href="#">osclconfig_lib.h</a> (This file contains configuration information for the ANSI build) . . . . .	824
<a href="#">osclconfig_lib_check.h</a> . . . . .	825
<a href="#">osclconfig_limits_typedefs.h</a> (This file contains common typedefs based on the ANSI C limits.h header) . . . . .	826
<a href="#">osclconfig_memory.h</a> . . . . .	827
<a href="#">osclconfig_memory_check.h</a> . . . . .	828
<a href="#">osclconfig_no_os.h</a> . . . . .	829
<a href="#">osclconfig_proc.h</a> (This file contains configuration information for the linux platform) . . . . .	830
<a href="#">osclconfig_proc_check.h</a> . . . . .	831
<a href="#">osclconfig_proc_unix_android.h</a> . . . . .	833
<a href="#">osclconfig_proc_unix_common.h</a> . . . . .	835
<a href="#">osclconfig_time.h</a> . . . . .	837
<a href="#">osclconfig_time_check.h</a> . . . . .	838
<a href="#">osclconfig_unix_android.h</a> . . . . .	839
<a href="#">osclconfig_unix_common.h</a> . . . . .	843
<a href="#">osclconfig_util.h</a> . . . . .	847
<a href="#">osclconfig_util_check.h</a> . . . . .	848
<a href="#">pvlogger.h</a> (This file contains basic logger interfaces for common use across platforms) . . . . .	849
<a href="#">pvlogger_accessories.h</a> . . . . .	857
<a href="#">pvlogger_c.h</a> (This file contains basic logger interfaces for common use across platforms. C-callable version) . . . . .	858
<a href="#">pvlogger_registry.h</a> . . . . .	860

# **Chapter 5**

## **oscl Page Index**

### **5.1 oscl Related Pages**

Here is a list of all related documentation pages:

Todo List . . . . .	861
---------------------	-----

# Chapter 6

## oscl Module Documentation

### 6.1 OSCL config

#### Defines

- #define OSCL\_ASSERT\_ALWAYS 0
- #define OSCL\_INTEGERS\_WORD\_ALIGNED 1
- #define OSCL\_BYTE\_ORDER\_BIG\_ENDIAN 0
- #define OSCL\_BYTE\_ORDER\_LITTLE\_ENDIAN 1
- #define OSCL\_HAS\_PRAGMA\_PACK 0
- #define OSCL\_HAS\_UNIX\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_PARTIAL\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_SUPPORT 0
- #define OSCL\_HAS\_SAVAJE\_SUPPORT 0
- #define OSCL\_HAS\_PV\_C\_OS\_SUPPORT 0
- #define OSCL\_HAS\_ANDROID\_SUPPORT 0
- #define OSCL\_HAS\_IPHONE\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_ERRORTRAP 0
- #define OSCL\_HAS\_SYMBIAN\_MEMORY\_FUNCS 0
- #define OSCL\_HAS\_PV\_C\_OS\_API\_MEMORY\_FUNCS 0
- #define OSCL\_HAS\_PV\_C\_OS\_TIME\_FUNCS 0
- #define OSCL\_HAS\_UNIX\_TIME\_FUNCS 0
- #define OSCL\_HAS\_SYMBIAN\_TIMERS 0
- #define OSCL\_HAS\_SYMBIAN\_MATH 0
- #define OSCL\_HAS\_SYMBIAN\_SCHEDULER 0
- #define OSCL\_HAS\_SEM\_TIMEDWAIT\_SUPPORT 0
- #define OSCL\_HAS\_PTHREAD\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_COMPATIBLE\_IO\_FUNCTION 0
- #define OSCL\_HAS\_SAVAJE\_IO\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_SOCKET\_SERVER 0
- #define OSCL\_HAS\_SYMBIAN\_DNS\_SERVER 0
- #define OSCL\_HAS\_BERKELEY\_SOCKETS 0

## Typedefs

- `typedef int8 __int8_check__`
- `typedef uint8 __uint8_check__`
- `typedef int16 __int16_check__`
- `typedef uint16 __uint16_check__`
- `typedef int32 __int32_check__`
- `typedef uint32 __uint32_check__`

### 6.1.1 Define Documentation

#### 6.1.1.1 `#define OSCL_ASSERT_ALWAYS 0`

macro should be set to 0 or 1. When set to 1, OSCL\_ASSERT will be compiled in release mode as well as debug mode.

#### 6.1.1.2 `#define OSCL_BYTE_ORDER_BIG_ENDIAN 0`

macro should be set to 1 if the target platform uses big-endian byte order in memory. Otherwise it should be set to 0.

#### 6.1.1.3 `#define OSCL_BYTE_ORDER_LITTLE_ENDIAN 1`

macro should be set to 1 if the target platform uses little-endian byte order in memory. Otherwise it should be set to 0.

#### 6.1.1.4 `#define OSCL_HAS_ANDROID_SUPPORT 0`

#### 6.1.1.5 `#define OSCL_HAS_BERKELEY_SOCKETS 0`

#### 6.1.1.6 `#define OSCL_HAS_IPHONE_SUPPORT 0`

#### 6.1.1.7 `#define OSCL_HAS_MSWIN_PARTIAL_SUPPORT 0`

#### 6.1.1.8 `#define OSCL_HAS_MSWIN_SUPPORT 0`

#### 6.1.1.9 `#define OSCL_HAS_PRAGMA_PACK 0`

macro should be set to 1 if the compiler supports pragma pack, 0 if it does not.

- 6.1.1.10 #define OSCL\_HAS\_PTHREAD\_SUPPORT 0
- 6.1.1.11 #define OSCL\_HAS\_PV\_C\_OS\_API\_MEMORY\_FUNCS 0
- 6.1.1.12 #define OSCL\_HAS\_PV\_C\_OS\_SUPPORT 0
- 6.1.1.13 #define OSCL\_HAS\_PV\_C\_OS\_TIME\_FUNCS 0
- 6.1.1.14 #define OSCL\_HAS\_SAVAJE\_IO\_SUPPORT 0
- 6.1.1.15 #define OSCL\_HAS\_SAVAJE\_SUPPORT 0
- 6.1.1.16 #define OSCL\_HAS\_SEM\_TIMEDWAIT\_SUPPORT 0
- 6.1.1.17 #define OSCL\_HAS\_SYMBIAN\_COMPATIBLE\_IO\_FUNCTION 0
- 6.1.1.18 #define OSCL\_HAS\_SYMBIAN\_DNS\_SERVER 0
- 6.1.1.19 #define OSCL\_HAS\_SYMBIAN\_ERRORTRAP 0
- 6.1.1.20 #define OSCL\_HAS\_SYMBIAN\_MATH 0
- 6.1.1.21 #define OSCL\_HAS\_SYMBIAN\_MEMORY\_FUNCS 0
- 6.1.1.22 #define OSCL\_HAS\_SYMBIAN\_SCHEDULER 0
- 6.1.1.23 #define OSCL\_HAS\_SYMBIAN\_SOCKET\_SERVER 0
- 6.1.1.24 #define OSCL\_HAS\_SYMBIAN\_SUPPORT 0
- 6.1.1.25 #define OSCL\_HAS\_SYMBIAN\_TIMERS 0
- 6.1.1.26 #define OSCL\_HAS\_UNIX\_SUPPORT 0
- 6.1.1.27 #define OSCL\_HAS\_UNIX\_TIME\_FUNCS 0
- 6.1.1.28 #define OSCL\_INTEGERS\_WORD\_ALIGNED 1

macro should be set to 1 if the target platform requires integers to be word-aligned in memory. Otherwise it should be set to 0.

## **6.1.2 Typedef Documentation**

- 6.1.2.1 `typedef int16 __int16__check__`**
- 6.1.2.2 `typedef int32 __int32__check__`**
- 6.1.2.3 `typedef int8 __int8__check__`**
- 6.1.2.4 `typedef uint16 __uint16__check__`**
- 6.1.2.5 `typedef uint32 __uint32__check__`**
- 6.1.2.6 `typedef uint8 __uint8__check__`**

## 6.2 OSCL Base

### Files

- file [oscl\\_assert.h](#)

*The file [oscl\\_assert.h](#) provides an OSCL\_ASSERT macro to document assumptions and test them during development.*

- file [oscl\\_base.h](#)

*The file [oscl\\_base.h](#) is the public header that should be included to pick up the platform configuration, basic type definitions, and common macros.*

- file [oscl\\_base\\_alloc.h](#)

*A basic allocator that does not rely on other modules.*

- file [oscl\\_base\\_macros.h](#)

*This file defines common macros and constants for basic compilation support.*

- file [oscl\\_byte\\_order.h](#)

*This file defines functions providing byte ordering utility (e.g., switching between big and little endian orders).*

- file [oscl\\_defalloc.h](#)

*The file defines simple default memory allocator classes. These allocators are used by the [Oscl\\_Vector](#) and [Oscl\\_Map](#) class, etc.*

- file [oscl\\_dll.h](#)

*Defines a DLL entry point.*

- file [oscl\\_exclusive\\_ptr.h](#)

*This file defines the [OsclExclusivePtr](#) template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error.*

- file [oscl\\_linked\\_list.h](#)

*The file [oscl\\_linked\\_list.h](#) defines the template class [Oscl\\_Linked\\_List](#) which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.*

- file [oscl\\_lock\\_base.h](#)

*This file defines an abstract lock class, [OsclLockBase](#), that is used for APIs potentially requiring multi-thread safety. A null-lock implementation, [OsclNullLock](#), is also provided for single-thread configurations (basically a noop for lock/unlock). Also provides the [OsclScopedLock](#) class which is template class takes care of freeing the lock when the class goes out of scope.*

- file [oscl\\_map.h](#)

*The file [oscl\\_map.h](#) defines the template class [Oscl\\_Map](#) which has a very similar API as the STL Map class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.*

- file [oscl\\_mem\\_inst.h](#)

*The file defines default memory instrumentation level.*

- file [oscl\\_opaque\\_type.h](#)

*The file [oscl\\_opaque\\_type.h](#) defines pure virtual classes for working with opaque types.*

- file [oscl\\_queue.h](#)

*The file [oscl\\_queue.h](#) defines the template class [Oscl\\_Queue](#). It is similar to the `STL::queue` class, with some differences: - less complete - based on array rather than a deque - some interfaces modeled on `oscl_vector`, for ease of transition Memory allocation is abstracted through the use of an allocator template parameter.*

- file [oscl\\_refcounter.h](#)

*A general purpose reference counter to object lifetimes.*

- file [oscl\\_refcounter\\_memfrag.h](#)

*This file provides the definition of reference counted memory fragment, which provides access to a buffer and helps manage its lifetime through the refcount.*

- file [oscl\\_shared\\_ptr.h](#)

*This file defines a template class [OsclSharedPtr](#) which is a "smart pointer" to the parameterized type.*

- file [oscl\\_stdstring.h](#)

*This file provides standard string operations such as `strlen`, `strncpy`, etc. ANSI defines undefined behavior when the destination pointer is null for operations such as `strncpy`, `strncat`, etc. But, we chose to define one. In such cases, we return the destination as null.*

- file [oscl\\_tagtree.h](#)

*The file [oscl\\_tagtree.h](#) ...*

- file [oscl\\_time.h](#)

*The file [oscl\\_time.h](#) defines two classes [NTPTime](#) and [TimeValue](#) for getting, manipulating, and formatting time values. The [TimeValue](#) class is based on the native system time format while [NTPTime](#) is used for the standard Network Time Protocol format.*

- file [oscl\\_tree.h](#)

*The file [oscl\\_tree.h](#) defines the template class [Oscl\\_Rb\\_Tree](#) which has a very similar API as the `STL Tree` class. It is an implementation of a Red-Black Tree for use by the [Oscl\\_Map](#) class. Memory allocation is abstracted through the use of an allocator template parameter.*

- file [oscl\\_types.h](#)

*This file contains basic type definitions for common use across platforms.*

- file [oscl\\_vector.h](#)

*The file [oscl\\_vector.h](#) defines the template class [Oscl\\_Vector](#) which has a very similar API as the `STL Vector` class (it basically provides a subset of the `STL` functionality). Memory allocation is abstracted through the use of an allocator template parameter.*

## Data Structures

- class [\\_OsclBasicAllocator](#)
- class [LinkedListElement](#)
- class [NTPTime](#)

*The [NTPTime](#) class represents a time value as the number of seconds since 0h (UTC) Jan. 1, 1900.*

- class [Oscl\\_Alloc](#)
- class [Oscl\\_Dealloc](#)
- class [Oscl\\_DefAlloc](#)
- class [Oscl\\_DefAllocWithRefCounter](#)
- struct [Oscl\\_Less](#)
- class [Oscl\\_Linked\\_List](#)
- class [Oscl\\_Linked\\_List\\_Base](#)
- class [Oscl\\_Map](#)
- class [Oscl\\_MTLinked\\_List](#)
- class [Oscl\\_Opaque\\_Type\\_Alloc](#)
- class [Oscl\\_Opaque\\_Type\\_Alloc\\_LL](#)
- class [Oscl\\_Opaque\\_Type\\_Compare](#)
- struct [Oscl\\_Pair](#)
- class [Oscl\\_Queue](#)
- class [Oscl\\_Queue\\_Base](#)
- class [Oscl\\_Rb\\_Tree](#)
- class [Oscl\\_Rb\\_Tree\\_Base](#)
- struct [Oscl\\_Rb\\_Tree\\_Const\\_Iterator](#)
- struct [Oscl\\_Rb\\_Tree\\_Iterator](#)
- struct [Oscl\\_Rb\\_Tree\\_Node](#)
- struct [Oscl\\_Rb\\_Tree\\_Node\\_Base](#)
- struct [Oscl\\_Select1st](#)
- struct [Oscl\\_Tag](#)
- struct [Oscl\\_Tag\\_Base](#)
- class [Oscl\\_TagTree](#)
- class [Oscl\\_TAlloc](#)
- class [Oscl\\_Vector](#)
- class [Oscl\\_Vector\\_Base](#)
- class [OsclAllocDestructDealloc](#)
- class [OsclDestructDealloc](#)
- class [OsclExclusiveArrayPtr](#)

The `OsclExclusiveArrayPtr` class is a template class that defines an array pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the `OsclExclusiveArrayPtr` expires, its destructor uses delete to free the memory.

- class [OsclExclusivePtr](#)

The `OsclExclusivePtr` class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the `OsclExclusivePtr` expires, its destructor uses delete to free the memory.

- class [OsclExclusivePtrA](#)

The `OsclExclusivePtrA` class is a template class that defines any pointer like object intended to be assigned an address obtained (directly or or indirectly) through Alloc. When the `OsclExclusivePtrA` expires, Alloc is used to free the memory.

- class [OsclLockBase](#)
- struct [OsclMemoryFragment](#)
- class [OsclNullLock](#)
- class [OsclRefCounter](#)
- class [OsclRefCounterDA](#)

- class [OsclRefCounterMemFrag](#)
- class [OsclRefCounterMTDA](#)
- class [OsclRefCounterMTSA](#)
- class [OsclRefCounterSA](#)
- class [OsclScopedLock](#)

*The OsclScopedLock class is a template class that handles unlocking an abstract class on destruction. This is very useful for ensuring that the lock is released when the OsclScopedLock goes out of scope.*

- class [OsclSharedPtr](#)

*A parameterized smart pointer class.*

- class [OsclTLS](#)
- class [OsclTLSRegistry](#)
- class [TimeValue](#)

*The TimeValue class represents a time value in a format native to the system.*

- class [TLSStorageOps](#)

## Defines

- #define [OSCL\\_ASSERT](#)(*\_expr*) ((*\_expr*)?((void)0):OSCL Assert(# *\_expr*, \_\_FILE\_\_, \_\_LINE\_\_))
- #define [OSCL\\_HAS\\_SINGLETON\\_SUPPORT](#) 1
- #define [NULL\\_TERM\\_CHAR](#) '\0'

*The NULL\_TERM\_CHAR is used to terminate c-style strings.*

- #define [NULL](#) (0)

*if the NULL macro isn't already defined, then define it as zero.*

- #define [OSCL\\_INLINE](#) inline
- #define [OSCL\\_COND\\_EXPORT\\_REF](#)
- #define [OSCL\\_COND\\_IMPORT\\_REF](#)
- #define [OSCL\\_CONST\\_CAST](#)(*type*, *exp*) ((*type*)(*exp*))

*Type casting macros.*

- #define [OSCL\\_STATIC\\_CAST](#)(*type*, *exp*) ((*type*)(*exp*))
- #define [OSCL\\_REINTERPRET\\_CAST](#)(*type*, *exp*) ((*type*)(*exp*))
- #define [OSCL\\_DYNAMIC\\_CAST](#)(*type*, *exp*) ((*type*)(*exp*))
- #define [OSCL\\_VIRTUAL\\_BASE](#)(*type*) *type*
- #define [OSCL\\_UNUSED\\_ARG](#)(*vbl*) (void)(*vbl*)
- #define [OSCL\\_UNUSED\\_RETURN](#)(*value*) return *value*
- #define [OSCL\\_MIN](#)(*a*, *b*) ((*a*) < (*b*) ? (*a*) : (*b*))
- #define [OSCL\\_MAX](#)(*a*, *b*) ((*a*) > (*b*) ? (*a*) : (*b*))
- #define [OSCL\\_ABS](#)(*a*) ((*a*) > (0) ? (*a*) : -(*a*))
- #define [OSCL\\_TEMPLATED\\_DESTRUCTOR\\_CALL](#)(*type*, *simple\_type*) *type* :: ~*simple\_type* ()
- #define [OSCL\\_UNSIGNED\\_CONST](#)(*x*) *x*
- #define [OSCL\\_PACKED\\_VAR](#) "error"
- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)
- #define [ALLOCATE](#)(*n*) *allocate\_fl*(*n*, \_\_FILE\_\_, \_\_LINE\_\_)
- #define [ALLOC\\_AND\\_CONSTRUCT](#)(*n*) *alloc\_and\_construct\_fl*(*n*, \_\_FILE\_\_, \_\_LINE\_\_)
- #define [OSCL\\_DLL\\_ENTRY\\_POINT](#)() void *oscl\_dll\_entry\_point*() {}

- #define **OSCL\_DLL\_ENTRY\_POINT\_DEFAULT()**
- #define **PVMEM\_INST\_LEVEL** 1
- #define **OSCL\_DISABLE\_WARNING\_RETURN\_TYPE\_NOT\_UDT**
- #define **OSCL\_TLS\_BASE\_SLOTS** **OSCL\_TLS\_ID\_BASE\_LAST** +1
- #define **OSCL\_TLS\_EXTERNAL\_SLOTS** 0
- #define **OSCL\_TLS\_MAX\_SLOTS** ( **OSCL\_TLS\_BASE\_SLOTS** + **OSCL\_TLS\_EXTERNAL\_SLOTS** )

## Typedefs

- typedef char **CtimeStrBuf** [**CTIME\_BUFFER\_SIZE**]
- typedef char **PV8601timeStrBuf** [**PV8601TIME\_BUFFER\_SIZE**]
- typedef char **ISO8601timeStrBuf** [**ISO8601TIME\_BUFFER\_SIZE**]
- typedef **OsclAny** **TOsclTlsKey**
- typedef int **c\_bool**

*The c\_bool type is mapped to an integer to provide a bool type for C interfaces.*

- typedef void **OsclAny**

*The OsclAny is meant to be used the context of a generic pointer (i.e., no specific type).*

- typedef char **mbchar**

*mbchar is multi-byte char (e.g., UTF-8) with null termination.*

- typedef unsigned int **uint**

*The uint type is a convenient abbreviation for unsigned int.*

- typedef uint8 **octet**

*The octet type is meant to be used for referring to a byte or collection bytes without suggesting anything about the underlying meaning of the bytes.*

- typedef float **OsclFloat**

*The Float type defined as OsclFloat.*

- typedef **OSCL\_NATIVE\_INT64\_TYPE** **int64**

- typedef **OSCL\_NATIVE\_UINT64\_TYPE** **uint64**

- typedef **OSCL\_NATIVE\_WCHAR\_TYPE** **oscl\_wchar**

- typedef **oscl\_wchar** **OSCL\_TCHAR**

*define OSCL\_TCHAR*

## Enumerations

- enum **TimeUnits** { **SECONDS** = 0, **MILLISECONDS** = 1, **MICROSECONDS** = 2 }

*The TimeUnits enum can be used when constructing a TimeValue class.*

## Functions

- OSCL\_COND\_IMPORT\_REF void [\\_OSCL\\_Abort\(\)](#)  
*This function terminates the current process abnormally.*
- OSCL\_IMPORT\_REF void [OSCL\\_Assert](#) (const char \*expr, const char \*filename, int line\_number)  
*OSCL\_ASSERT macro evaluates an expression and when the result is false, prints a diagnostic message and aborts the program.*
- void [PVOsclBase\\_Init\(\)](#)
- void [PVOsclBase\\_Cleanup\(\)](#)
- void [little\\_endian\\_to\\_host](#) (char \*data, uint32 size)  
*Convert little endian to host format.*
- void [host\\_to\\_little\\_endian](#) (char \*data, unsigned int size)  
*Convert host to little endian format.*
- void [big\\_endian\\_to\\_host](#) (char \*data, unsigned int size)  
*Convert big endian to host format.*
- void [host\\_to\\_big\\_endian](#) (char \*data, unsigned int size)  
*Convert host to big endian format.*
- OSCL\_IMPORT\_REF uint32 [oscl\\_strlen](#) (const char \*str)
- OSCL\_IMPORT\_REF uint32 [oscl\\_strlen](#) (const [oscl\\_wchar](#) \*str)
- OSCL\_IMPORT\_REF char \* [oscl\\_strncpy](#) (char \*dest, const char \*src, uint32 count)
- OSCL\_IMPORT\_REF [oscl\\_wchar](#) \* [oscl\\_strncpy](#) ([oscl\\_wchar](#) \*dest, const [oscl\\_wchar](#) \*src, uint32 count)
- OSCL\_IMPORT\_REF int32 [oscl\\_strcmp](#) (const char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF int32 [oscl\\_strcmp](#) (const [oscl\\_wchar](#) \*str1, const [oscl\\_wchar](#) \*str2)
- OSCL\_IMPORT\_REF int32 [oscl\\_strncmp](#) (const char \*str1, const char \*str2, uint32 count)
- OSCL\_IMPORT\_REF int32 [oscl\\_strncmp](#) (const [oscl\\_wchar](#) \*str1, const [oscl\\_wchar](#) \*str2, uint32 count)
- OSCL\_IMPORT\_REF char \* [oscl\\_strncat](#) (char \*dest, const char \*src, uint32 count)
- OSCL\_IMPORT\_REF [oscl\\_wchar](#) \* [oscl\\_strncat](#) ([oscl\\_wchar](#) \*dest, const [oscl\\_wchar](#) \*src, uint32 count)
- OSCL\_IMPORT\_REF const char \* [oscl\\_strchr](#) (const char \*str, int32 c)
- OSCL\_IMPORT\_REF char \* [oscl\\_strchr](#) (char \*str, int32 c)
- OSCL\_IMPORT\_REF const [oscl\\_wchar](#) \* [oscl\\_strchr](#) (const [oscl\\_wchar](#) \*str, int32 c)
- OSCL\_IMPORT\_REF [oscl\\_wchar](#) \* [oscl\\_strchr](#) ([oscl\\_wchar](#) \*str, int32 c)
- OSCL\_IMPORT\_REF const char \* [oscl strrchr](#) (const char \*str, int32 c)
- OSCL\_IMPORT\_REF char \* [oscl strrchr](#) (char \*str, int32 c)
- OSCL\_IMPORT\_REF const [oscl\\_wchar](#) \* [oscl strrchr](#) (const [oscl\\_wchar](#) \*str, int32 c)
- OSCL\_IMPORT\_REF [oscl\\_wchar](#) \* [oscl strrchr](#) ([oscl\\_wchar](#) \*str, int32 c)
- OSCL\_IMPORT\_REF char \* [oscl\\_strset](#) (char \*dest, char val, uint32 count)
- OSCL\_IMPORT\_REF [oscl\\_wchar](#) \* [oscl\\_strset](#) ([oscl\\_wchar](#) \*dest, [oscl\\_wchar](#) val, uint32 count)
- OSCL\_IMPORT\_REF int32 [oscl\\_CIstrcmp](#) (const char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF int32 [oscl\\_CIstrcmp](#) (const [oscl\\_wchar](#) \*str1, const [oscl\\_wchar](#) \*str2)
- OSCL\_IMPORT\_REF int32 [oscl\\_CIstrncmp](#) (const char \*str1, const char \*str2, uint32 count)

- OSCL\_IMPORT\_REF int32 `oscl_Clstrncmp` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2, uint32 count)
- OSCL\_IMPORT\_REF char `oscl_tolower` (const char car)
- OSCL\_IMPORT\_REF `oscl_wchar` `oscl_tolower` (const `oscl_wchar` car)
- OSCL\_IMPORT\_REF bool `oscl_isLetter` (const char car)
- OSCL\_IMPORT\_REF const char \* `oscl_strstr` (const char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF char \* `oscl_strstr` (char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF const `oscl_wchar` \* `oscl_strstr` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strstr` (`oscl_wchar` \*str1, const `oscl_wchar` \*str2)
- OSCL\_IMPORT\_REF char \* `oscl_strcat` (char \*dest, const char \*src)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strcat` (`oscl_wchar` \*dest, const `oscl_wchar` \*src)
- OSCL\_IMPORT\_REF void `PV8601ToRFC822` (`PV8601timeStrBuf` pv8601\_buffer, `CtimeStrBuf` ctime\_buffer)
- OSCL\_IMPORT\_REF void `ISO8601ToRFC822` (`ISO8601timeStrBuf` iso8601\_buffer, `CtimeStrBuf` ctime\_buffer)
- OSCL\_IMPORT\_REF void `RFC822ToPV8601` (`CtimeStrBuf` ctime\_buffer, `PV8601timeStrBuf`)
- OSCL\_COND\_IMPORT\_REF `TimeValue` operator- (const `TimeValue` &a, const `TimeValue` &b)
- OSCL\_COND\_IMPORT\_REF `TimeValue` operator+ (const `TimeValue` &a, const int32 bSeconds)
- OSCL\_COND\_IMPORT\_REF `TimeValue` operator+ (const int32 aSeconds, const `TimeValue` &b)
- OSCL\_COND\_IMPORT\_REF `TimeValue` operator- (const `TimeValue` &a, const int32 bSeconds)
- OSCL\_COND\_IMPORT\_REF `TimeValue` operator- (const int32 aSeconds, const `TimeValue` &b)
- bool `operator==` (const `OsclSharedPtr` &b) const

*Test for equality to see if two PVHandles wrap the same object.*

- void `Bind` (const `OsclSharedPtr` &inHandle)

*Use this function to bind an existing `OsclSharedPtr` to a already-wrapped object.*

- void `Bind` (TheClass \*ptr, `OsclRefCounter` \*in\_refcnt)

*Use this function to bind an existing `OsclSharedPtr` to a new (unwrapped) object.*

## Variables

- const int `CTIME_BUFFER_SIZE` = 26
- const int `PV8601TIME_BUFFER_SIZE` = 21
- const int `ISO8601TIME_BUFFER_SIZE` = 21
- const long `USEC_PER_SEC` = 1000000
- const long `MSEC_PER_SEC` = 1000
- const uint32 `unix_ntp_offset` = 2208988800U
- const uint32 `OSCL_TLS_ID_MAGICNUM` = 0
- const uint32 `OSCL_TLS_ID_ERRORHOOK` = 1
- const uint32 `OSCL_TLS_ID_PVLOGGER` = 2
- const uint32 `OSCL_TLS_ID_TEST` = 3
- const uint32 `OSCL_TLS_ID_PVSCHEDULER` = 4
- const uint32 `OSCL_TLS_ID_PVERRORTRAP` = 5
- const uint32 `OSCL_TLS_ID_SDPMEDIAPARSER` = 6
- const uint32 `OSCL_TLS_ID_PAYLOADPARSER` = 7
- const uint32 `OSCL_TLS_ID_PVMFRECOGNIZER` = 8
- const uint32 `OSCL_TLS_ID_WMDRM` = 9
- const uint32 `OSCL_TLS_ID_OSCLREGISTRY` = 10
- const uint32 `OSCL_TLS_ID_SQLITE3` = 11
- const uint32 `OSCL_TLS_ID_BASE_LAST` = 11

## 6.2.1 Detailed Description

Additional osclbase comment

Additional osclbase comment

Additional osclbase comment

## 6.2.2 Define Documentation

**6.2.2.1 #define ALLOC\_AND\_CONSTRUCT(n) alloc\_and\_construct\_fl(n,\_\_FILE\_\_,\_\_LINE\_\_)**

**6.2.2.2 #define ALLOCATE(n) allocate\_fl(n,\_\_FILE\_\_,\_\_LINE\_\_)**

**6.2.2.3 #define NULL (0)**

if the NULL macro isn't already defined, then define it as zero.

**6.2.2.4 #define NULL\_TERM\_CHAR '\0'**

The NULL\_TERM\_CHAR is used to terminate c-style strings.

**6.2.2.5 #define OSCL\_ABS(a) ((a) > (0) ? (a) : -(a))**

**6.2.2.6 #define OSCL\_ASSERT(\_expr) ((\_expr)?((void)0):OSCLAssert#\_expr,\_\_FILE\_\_,\_\_LINE\_\_))**

**6.2.2.7 #define OSCL\_COND\_EXPORT\_REF**

**6.2.2.8 #define OSCL\_COND\_IMPORT\_REF**

**6.2.2.9 #define OSCL\_CONST\_CAST(type, exp) ((type)(exp))**

Type casting macros.

### Parameters:

*type* Destination type of cast

*exp* Expression to cast

**6.2.2.10 #define OSCL\_DISABLE\_WARNING\_RETURN\_TYPE\_NOT\_UDT**

**6.2.2.11 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE**

**6.2.2.12 #define OSCL\_DLL\_ENTRY\_POINT() void oscl\_dll\_entry\_point() {}**

DLL entry/exit point.

Allows you to define custom operations at the entry and exit of the DLL. Place this macro within one source file for each DLL.

Functions with the custom commands for the DLL entry and exit point must also be defined. The entry point custom function is LocalDllEntry(), and the exit point custom function is LocalDllExit().

These functions will be called as a result of executing this macro.

Usage :

```
LocalDliEntry() { custom operations... }  
LocalDliExit() { custom operations... }  
OSCL_DLL_ENTRY_POINT()
```

#### **6.2.2.13 #define OSCL\_DLL\_ENTRY\_POINT\_DEFAULT()**

Default DLL entry/exit point function.

The body of the DLL entry point is given. The macro only needs to be declared within the source file.

Usage :

```
OSCL_DLL_ENTRY_POINT_DEFAULT()
```

#### **6.2.2.14 #define OSCL\_DYNAMIC\_CAST(type, exp) ((type)(exp))**

#### **6.2.2.15 #define OSCL\_HAS\_SINGLETON\_SUPPORT 1**

#### **6.2.2.16 #define OSCL\_INLINE inline**

#### **6.2.2.17 #define OSCL\_MAX(a, b) ((a) > (b) ? (a) : (b))**

#### **6.2.2.18 #define OSCL\_MIN(a, b) ((a) < (b) ? (a) : (b))**

#### **6.2.2.19 #define OSCL\_PACKED\_VAR "error"**

#### **6.2.2.20 #define OSCL\_REINTERPRET\_CAST(type, exp) ((type)(exp))**

#### **6.2.2.21 #define OSCL\_STATIC\_CAST(type, exp) ((type)(exp))**

#### **6.2.2.22 #define OSCL\_TEMPLATED\_DESTRUCTOR\_CALL(type, simple\_type) type :: ~simple\_type ()**

#### **6.2.2.23 #define OSCL\_TLS\_BASE\_SLOTS OSCL\_TLS\_ID\_BASE\_LAST +1**

#### **6.2.2.24 #define OSCL\_TLS\_EXTERNAL\_SLOTS 0**

#### **6.2.2.25 #define OSCL\_TLS\_MAX\_SLOTS ( OSCL\_TLS\_BASE\_SLOTS + OSCL\_TLS\_EXTERNAL\_SLOTS )**

#### **6.2.2.26 #define OSCL\_UNSIGNED\_CONST(x) x**

#### **6.2.2.27 #define OSCL\_UNUSED\_ARG(vbl) (void)(vbl)**

The following two macros are used to avoid compiler warnings.

**OSCL\_UNUSED\_ARG(vbl)** is used to "reference" an otherwise unused parameter or variable, often one which is used only in an OSCL\_ASSERT and thus unreferenced in release mode **OSCL\_UNUSED\_RETURN(val)** provides a "return" of a value, in places which will not actually be executed, such as after an OSCL\_LEAVE or Thread::exit or abort. The value needs to be of an appropriate type for the current

function, though zero will usually suffice. Note that OSCL\_UNUSED\_RETURN will not be necessary for 'void' functions, as there is no requirement for a value-return operation.

#### 6.2.2.28 #define OSCL\_UNUSED\_RETURN(value) return value

#### 6.2.2.29 #define OSCL\_VIRTUAL\_BASE(type) type

#### 6.2.2.30 #define PVMEM\_INST\_LEVEL 1

### 6.2.3 Typedef Documentation

#### 6.2.3.1 typedef int c\_bool

The c\_bool type is mapped to an integer to provide a bool type for C interfaces.

#### 6.2.3.2 typedef char CtimeStrBuf[CTIME\_BUFFER\_SIZE]

#### 6.2.3.3 typedef OSCL\_NATIVE\_INT64\_TYPE int64

#### 6.2.3.4 typedef char ISO8601timeStrBuf[ISO8601TIME\_BUFFER\_SIZE]

#### 6.2.3.5 typedef char mbchar

mbchar is multi-byte char (e.g., UTF-8) with null termination.

#### 6.2.3.6 typedef uint8 octet

The octet type is meant to be used for referring to a byte or collection bytes without suggesting anything about the underlying meaning of the bytes.

#### 6.2.3.7 typedef oscl\_wchar OSCL\_TCHAR

define OSCL\_TCHAR

#### 6.2.3.8 typedef OSCL\_NATIVE\_WCHAR\_TYPE oscl\_wchar

#### 6.2.3.9 typedef void OsclAny

The OsclAny is meant to be used the context of a generic pointer (i.e., no specific type).

#### 6.2.3.10 typedef float OsclFloat

The Float type defined as OsclFloat.

**6.2.3.11 `typedef char PV8601timeStrBuf[PV8601TIME_BUFFER_SIZE]`**

**6.2.3.12 `typedef OsclAny TOsclTlsKey`**

**6.2.3.13 `typedef unsigned int uint`**

The uint type is a convenient abbreviation for unsigned int.

**6.2.3.14 `typedef OSCL_NATIVE_UINT64_TYPE uint64`**

## 6.2.4 Enumeration Type Documentation

**6.2.4.1 `enum TimeUnits`**

The TimeUnits enum can be used when constructing a [TimeValue](#) class.

**Enumeration values:**

**SECONDS**

**MILLISECONDS**

**MICROSECONDS**

## 6.2.5 Function Documentation

**6.2.5.1 `OSCL_COND_IMPORT_REF void _OSCL_Abort()`**

This function terminates the current process abnormally.

**6.2.5.2 `void big_endian_to_host (char * data, unsigned int size)`**

Convert big endian to host format.

This function takes a buffer of data which is assumed to be in big endian order and rearranges it to the native order of the machine running the code. If the machine is a big endian machine, nothing is done.

**Parameters:**

*data* A pointer to the input/output buffer

*size* The number of bytes in the buffer.

**6.2.5.3 `template<class TheClass> void OsclSharedPtr< TheClass >::Bind (TheClass * ptr, OsclRefCounter * in_refcnt) [inline, inherited]`**

Use this function to bind an existing OsclSharedPtr to a new (unwrapped) object.

**6.2.5.4 `template<class TheClass> void OsclSharedPtr< TheClass >::Bind (const OsclSharedPtr< TheClass > & inHandle) [inline, inherited]`**

Use this function to bind an existing OsclSharedPtr to a already-wrapped object.

#### 6.2.5.5 void host\_to\_big\_endian (char \* *data*, unsigned int *size*)

Convert host to big endian format.

This function takes a buffer of data which is assumed to be in native host order and rearranges it to big endian format. If the machine is a big endian machine, nothing is done.

**Parameters:**

- data* A pointer to the input/output buffer
- size* The number of bytes in the buffer.

#### 6.2.5.6 void host\_to\_little\_endian (char \* *data*, unsigned int *size*)

Convert host to little endian format.

This function takes a buffer of data which is assumed to be in the host's native order and rearranges it to the little endian format. If the machine is a little endian machine, nothing is done.

**Parameters:**

- data* A pointer to the input/output buffer
- size* The number of bytes in the buffer.

#### 6.2.5.7 OSCL\_IMPORT\_REF void ISO8601ToRFC822 ([ISO8601timeStrBuf iso8601\\_buffer](#), [CtimeStrBuf ctime\\_buffer](#))

#### 6.2.5.8 void little\_endian\_to\_host (char \* *data*, uint32 *size*)

Convert little endian to host format.

This function takes a buffer of data which is assumed to be in little endian order and rearranges it to the native order of the machine running the code. If the machine is a little endian machine, nothing is done.

**Parameters:**

- data* A pointer to the input/output buffer
- size* The number of bytes in the buffer.

- 6.2.5.9 OSCL\_COND\_IMPORT\_REF TimeValue operator+ (const int32 *aSeconds*, const TimeValue & *b*)**
- 6.2.5.10 OSCL\_COND\_IMPORT\_REF TimeValue operator+ (const TimeValue & *a*, const int32 *bSeconds*)**
- 6.2.5.11 OSCL\_COND\_IMPORT\_REF TimeValue operator- (const int32 *aSeconds*, const TimeValue & *b*)**
- 6.2.5.12 OSCL\_COND\_IMPORT\_REF TimeValue operator- (const TimeValue & *a*, const int32 *bSeconds*)**
- 6.2.5.13 OSCL\_COND\_IMPORT\_REF TimeValue operator- (const TimeValue & *a*, const TimeValue & *b*)**
- 6.2.5.14 template<class TheClass> bool OsclSharedPtr<TheClass>::operator== (const OsclSharedPtr<TheClass> & *b*) const [inline, inherited]**

Test for equality to see if two PVHandles wrap the same object.

- 6.2.5.15 OSCL\_IMPORT\_REF void OSCL\_Assert (const char \* *expr*, const char \* *filename*, int *line\_number*)**

OSCL\_ASSERT macro evaluates an expression and when the result is false, prints a diagnostic message and aborts the program.

**Parameters:**

- expr* is the expression to be evaluated
- filename* is the name of the current source file
- line\_number* is the line number in the current source file

- 6.2.5.16 OSCL\_IMPORT\_REF int32 oscl\_CIstrcmp (const oscl\_wchar \* *str1*, const oscl\_wchar \* *str2*)**

Case in-sensitive string comparision.

**Parameters:**

- str1* string to compare
- str2* string to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

- 6.2.5.17 OSCL\_IMPORT\_REF int32 oscl\_CIstrcmp (const char \* *str1*, const char \* *str2*)**

Case in-sensitive string comparision.

**Parameters:**

- str1* string to compare

*str2* string to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

#### 6.2.5.18 OSCL\_IMPORT\_REF int32 oscl\_Clstrncmp (const oscl\_wchar \* *str1*, const oscl\_wchar \* *str2*, uint32 *count*)

Lexicographically compares(case in-sensitive), at most, the first count characters in str1 and str2 and returns a value indicating the relationship between the substrings.

**Parameters:**

*str1* string to compare

*str2* string to compare

*count* Number of characters to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

#### 6.2.5.19 OSCL\_IMPORT\_REF int32 oscl\_Clstrncmp (const char \* *str1*, const char \* *str2*, uint32 *count*)

Lexicographically compares(case in-sensitive), at most, the first count characters in str1 and str2 and returns a value indicating the relationship between the substrings.

**Parameters:**

*str1* string to compare

*str2* string to compare

*count* Number of characters to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

#### 6.2.5.20 OSCL\_IMPORT\_REF bool oscl\_isLetter (const char *car*)

check if supplied parameter is an alphabet (ASCII only).

**Parameters:**

*car*

**Returns:**

1 if car is an alphabet 0 if car is not an alphabet.

**6.2.5.21 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_streat (oscl\_wchar \* dest, const oscl\_wchar \* src)**

Appends up to count characters from string src to string dest, and then appends a terminating null character. The initial character of src overwrites the null character at the end of dest. Subsequent characters in src are appended to dest until either the end of src is reached or count characters have been copied. If copying takes place between objects that overlap, the behavior is undefined.

**Parameters:**

*dest* null terminated destination string

*src* source string

*count* number of characters to append.

**Returns:**

dest

**6.2.5.22 OSCL\_IMPORT\_REF char\* oscl\_streat (char \* dest, const char \* src)**

Appends string src to string dest, and then appends a terminating null character. The initial character of src overwrites the null character at the end of dest. Subsequent characters in src are appended to dest until the end of src is reached. If copying takes place between objects that overlap, the behavior is undefined.

**Parameters:**

*dest* null terminated destination string

*src* source string

**Returns:**

dest

**6.2.5.23 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_strchr (oscl\_wchar \* str, int32 c)****6.2.5.24 OSCL\_IMPORT\_REF const oscl\_wchar\* oscl\_strchr (const oscl\_wchar \* str, int32 c)**

Finds the first occurrence of c in string, or it returns NULL if c is not found. The null-terminating character is included in the search.

**Parameters:**

*str* null terminated source string

*c* character to search for

**Returns:****6.2.5.25 OSCL\_IMPORT\_REF char\* oscl\_strchr (char \* str, int32 c)****6.2.5.26 OSCL\_IMPORT\_REF const char\* oscl\_strchr (const char \* str, int32 c)**

Finds the first occurrence of c in string, or it returns NULL if c is not found. The null-terminating character is included in the search.

**Parameters:**

*str* null terminated source string

*c* character to search for

**Returns:****6.2.5.27 OSCL\_IMPORT\_REF int32 oscl\_strcmp (const oscl\_wchar \* str1, const oscl\_wchar \* str2)**

Lexicographically compares two NULL terminated strings, str1 and str2, and returns a value indicating the relationship between them.

**Parameters:**

*str1* String to compare

*str2* String to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

**6.2.5.28 OSCL\_IMPORT\_REF int32 oscl\_strcmp (const char \* str1, const char \* str2)**

Lexicographically compares two NULL terminated strings, str1 and str2, and returns a value indicating the relationship between them.

**Parameters:**

*str1* String to compare

*str2* String to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

**6.2.5.29 OSCL\_IMPORT\_REF uint32 oscl\_strlen (const oscl\_wchar \* str)**

Gets the length of a wide char string

**Parameters:**

*str* NULL terminated string.

**Returns:**

Returns the number of characters in string, excluding the terminal NULL.

**6.2.5.30 OSCL\_IMPORT\_REF uint32 oscl\_strlen (const char \* str)**

Gets the length of a string

**Parameters:**

*str* NULL terminated string.

**Returns:**

Returns the number of characters in string, excluding the terminal NULL.

**6.2.5.31 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_strncat (oscl\_wchar \* dest, const oscl\_wchar \* src, uint32 count)**

Appends up to count characters from string src to string dest, and then appends a terminating null character. The initial character of src overwrites the null character at the end of dest. Subsequent characters in src are appended to dest until either the end of src is reached or count characters have been copied. If copying takes place between objects that overlap, the behavior is undefined.

**Parameters:**

*dest* null terminated destination string

*src* source string

*count* number of characters to append.

**Returns:**

dest

**6.2.5.32 OSCL\_IMPORT\_REF char\* oscl\_strncat (char \* dest, const char \* src, uint32 count)**

Appends up to count characters from string src to string dest, and then appends a terminating null character. The initial character of src overwrites the null character at the end of dest. Subsequent characters in src are appended to dest until either the end of src is reached or count characters have been copied. If copying takes place between objects that overlap, the behavior is undefined.

**Parameters:**

*dest* null terminated destination string

*src* source string

*count* number of characters to append.

**Returns:**

dest

**6.2.5.33 OSCL\_IMPORT\_REF int32 oscl\_strcmp (const oscl\_wchar \* str1, const oscl\_wchar \* str2, uint32 count)**

Lexicographically compares, at most, the first count characters in str1 and str2 and returns a value indicating the relationship between the substrings.

**Parameters:**

*str1* String to compare

*str2* String to compare

*count* Number of characters to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

**6.2.5.34 OSCL\_IMPORT\_REF int32 oscl\_strncmp (const char \* str1, const char \* str2, uint32 count)**

Lexicographically compares, at most, the first count characters in str1 and str2 and returns a value indicating the relationship between the substrings.

**Parameters:**

- str1* String to compare
- str2* String to compare
- count* Number of characters to compare

**Returns:**

Negative if str1 < str2 Positive if str1 > str2 Zero if equal

**6.2.5.35 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_strncpy (oscl\_wchar \* dest, const oscl\_wchar \* src, uint32 count)**

Copies the chars of one string to another.

Copies the initial count characters of src to dest and returns dest. If count is less than or equal to the length of src, a null character is not appended automatically to the copied string. If count is greater than the length of src, the destination string is padded with null characters up to length count. The behavior of strncpy is undefined if the source and destination strings overlap.

**Parameters:**

- dest* Destination string
- src* NULL terminated source string
- count* Number of chars to copy

**Returns:**

Returns dest.

**6.2.5.36 OSCL\_IMPORT\_REF char\* oscl\_strncpy (char \* dest, const char \* src, uint32 count)**

Copies the chars of one string to another.

Copies the initial count characters of src to dest and returns dest. If count is less than or equal to the length of src, a null character is not appended automatically to the copied string. If count is greater than the length of src, the destination string is padded with null characters up to length count. The behavior of strncpy is undefined if the source and destination strings overlap.

**Parameters:**

- dest* Destination string
- src* NULL terminated source string
- count* Number of chars to copy

**Returns:**

Returns dest.

**6.2.5.37 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_strrchr (oscl\_wchar \* str, int32 c)**

**6.2.5.38 OSCL\_IMPORT\_REF const oscl\_wchar\* oscl\_strrchr (const oscl\_wchar \* str, int32 c)**

**6.2.5.39 OSCL\_IMPORT\_REF char\* oscl\_strrchr (char \* str, int32 c)**

**6.2.5.40 OSCL\_IMPORT\_REF const char\* oscl\_strrchr (const char \* str, int32 c)**

Finds the last occurrence of c in string, or it returns NULL if c is not found. The null-terminating character is included in the search.

**Parameters:**

*str* null terminated source string

*c* character to search for

**Returns:**

**6.2.5.41 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_strset (oscl\_wchar \* dest, oscl\_wchar val, uint32 count)**

Sets the characters of a string to a specified character

**Parameters:**

*dest* buffer to modify

*val* character to set

*count* number of chars to set

**Returns:**

the value of dest

**6.2.5.42 OSCL\_IMPORT\_REF char\* oscl\_strset (char \* dest, char val, uint32 count)**

Sets the characters of a string to a specified character

**Parameters:**

*dest* buffer to modify

*val* character to set

*count* number of chars to set

**Returns:**

the value of dest

**6.2.5.43 OSCL\_IMPORT\_REF oscl\_wchar\* oscl\_strstr (oscl\_wchar \* str1, const oscl\_wchar \* str2)**

**6.2.5.44 OSCL\_IMPORT\_REF const oscl\_wchar\* oscl\_strstr (const oscl\_wchar \* str1, const oscl\_wchar \* str2)**

find the occurrence of sub-string in a string.

**Parameters:**

*str1* string.

*str2* sub-string

**Returns:**

pointer to the begining of sub-string.

**6.2.5.45 OSCL\_IMPORT\_REF char\* oscl\_strstr (char \* str1, const char \* str2)****6.2.5.46 OSCL\_IMPORT\_REF const char\* oscl\_strstr (const char \* str1, const char \* str2)**

find the occurrence of sub-string in a string.

**Parameters:**

*str1* string.

*str2* sub-string

**Returns:**

pointer to the begining of sub-string.

**6.2.5.47 OSCL\_IMPORT\_REF oscl\_wchar oscl\_tolower (const oscl\_wchar car)**

convert upper case ASCII character to lower case. behaviour of this function for non-ASCII characters is not defined.

**Parameters:**

*car* upper case character.

**Returns:**

lower case character.

**6.2.5.48 OSCL\_IMPORT\_REF char oscl\_tolower (const char car)**

convert upper case ASCII character to lower case. behaviour of this function for non-ASCII characters is not defined.

**Parameters:**

*car* upper case character.

**Returns:**

lower case character.

**6.2.5.49 OSCL\_IMPORT\_REF void PV8601ToRFC822 (PV8601timeStrBuf *pv8601\_buffer*, CtimeStrBuf *ctime\_buffer*)****6.2.5.50 void PVOsclBase\_Cleanup ()**

Cleanup OsclBase functionality OsclBase should be cleaned once OsclBase functions are no longer needed

### 6.2.5.51 void PVosclBase\_Init ()

Initializes OsclBase functionality. OsclBase must be initialized before any OsclBase functionality can be used.

**Exceptions:**

*leaves* if out-of-memory

### 6.2.5.52 OSCL\_IMPORT\_REF void RFC822ToPV8601 (**CtimeStrBuf** *ctime\_buffer*, **PV8601timeStrBuf**)

## 6.2.6 Variable Documentation

6.2.6.1 const int CTIME\_BUFFER\_SIZE = 26

6.2.6.2 const int ISO8601TIME\_BUFFER\_SIZE = 21

6.2.6.3 const long MSEC\_PER\_SEC = 1000

6.2.6.4 const uint32 OSCL\_TLS\_ID\_BASE\_LAST = 11

6.2.6.5 const uint32 OSCL\_TLS\_ID\_ERRORHOOK = 1

6.2.6.6 const uint32 OSCL\_TLS\_ID\_MAGICNUM = 0

6.2.6.7 const uint32 OSCL\_TLS\_ID\_OSCLREGISTRY = 10

6.2.6.8 const uint32 OSCL\_TLS\_ID\_PAYLOADPARSER = 7

6.2.6.9 const uint32 OSCL\_TLS\_ID\_PVERRORTRAP = 5

6.2.6.10 const uint32 OSCL\_TLS\_ID\_PVLOGGER = 2

6.2.6.11 const uint32 OSCL\_TLS\_ID\_PVMFRECOGNIZER = 8

6.2.6.12 const uint32 OSCL\_TLS\_ID\_PVSCHEDULER = 4

6.2.6.13 const uint32 OSCL\_TLS\_ID\_SDPMEDIAPARSER = 6

6.2.6.14 const uint32 OSCL\_TLS\_ID\_SQLITE3 = 11

6.2.6.15 const uint32 OSCL\_TLS\_ID\_TEST = 3

6.2.6.16 const uint32 OSCL\_TLS\_ID\_WMDRM = 9

6.2.6.17 const int PV8601TIME\_BUFFER\_SIZE = 21

6.2.6.18 const uint32 unix\_ntp\_offset = 2208988800U

6.2.6.19 const long USEC\_PER\_SEC = 1000000

## 6.3 OSCL Memory

### Files

- file [oscl\\_mem.h](#)

*This file contains basic memory definitions for common use across platforms.*

- file [oscl\\_mem\\_audit.h](#)

*This file contains the definition and partial implementation of MM\_Audit class.*

- file [oscl\\_mem\\_audit\\_internals.h](#)

*This file contains the internal definitions for the mem audit library.*

- file [oscl\\_mem\\_auto\\_ptr.h](#)

*This file defines the oscl\_mem\_auto\_ptr template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error.*

- file [oscl\\_mem\\_basic\\_functions.h](#)

*This file contains prototypes for the basic memory functions.*

- file [oscl\\_mem\\_mempool.h](#)

*This file contains the definition of memory pool allocators.*

### Data Structures

- class [allocator](#)
- class [allocator](#)
- class [HeapBase](#)
- struct [MM\\_AllocBlockFence](#)
- struct [MM\\_AllocBlockHdr](#)
- struct [MM\\_AllocInfo](#)
- struct [MM\\_AllocNode](#)
- struct [MM\\_AllocQueryInfo](#)
- class [MM\\_Audit\\_Imp](#)
- struct [MM\\_AuditOverheadStats](#)
- struct [MM\\_FailInsertParam](#)
- struct [MM\\_Stats\\_CB](#)
- struct [MM\\_Stats\\_t](#)
- class [OsclAuditCB](#)
- class [OsclMem](#)
- class [OsclMemAllocator](#)
- class [OsclMemAllocator](#)
- class [OsclMemAllocDestructDealloc](#)
- class [OsclMemAllocDestructDealloc](#)
- class [OsclMemAudit](#)
- class [OSCLMemAutoPtr](#)

*The oscl\_auto\_ptr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the oscl\_auto\_ptr expires, its destructor uses delete to free the memory.*

- class OsclMemBasicAllocator
- class OsclMemBasicAllocator
- class OsclMemBasicAllocDestructDealloc
- class OsclMemBasicAllocDestructDealloc
- class OsclMemGlobalAuditObject
- class OsclMemPoolFixedChunkAllocator
- class OsclMemPoolFixedChunkAllocatorObserver
- class OsclMemPoolResizableAllocator
- class OsclMemPoolResizableAllocatorMemoryObserver
- class OsclMemPoolResizableAllocatorObserver
- class OsclMemStatsNode

## Defines

- #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE
- #define OSCL\_HAS\_GLOBAL\_NEW\_DELETE 1
- #define OSCL\_CLEANUP\_BASE\_CLASS(T) \_OSCL\_CLEANUP\_BASE\_CLASS(T)
- #define OSCL\_ALLOC\_NEW(T\_allocator, T, params) new(T\_allocator.allocate(1)) T params
- #define OSCL\_TRAP\_ALLOC\_NEW(T\_ptr, T\_allocator, T, params) \_OSCL\_TRAP\_NEW(T\_allocator.allocate(1),T\_allocator.deallocate,T\_ptr,T,params)
- #define OSCL\_ALLOC\_DELETE(ptr, T\_allocator, T)
- #define OSCL\_MALLOC(count) \_oscl\_default\_audit\_malloc(count)
- #define oscl\_malloc(a) OSCL\_MALLOC(a)
- #define OSCL\_DEFAULT\_MALLOC(x) OSCL\_MALLOC(x)
- #define OSCL\_AUDIT\_MALLOC(auditCB, count) \_oscl\_audit\_malloc(count, auditCB)
- #define OSCL\_CALLOC(num, size) \_oscl\_default\_audit\_calloc(num,size)
- #define oscl\_calloc(a, b) OSCL\_CALLOC(a,b)
- #define OSCL\_AUDIT\_CALLOC(auditCB, num, size) \_oscl\_audit\_calloc(num,size, auditCB)
- #define OSCL\_REALLOC(ptr, new\_size) \_oscl\_default\_audit\_realloc(ptr,new\_size)
- #define oscl\_realloc(a, b) OSCL\_REALLOC(a,b)
- #define OSCL\_AUDIT\_REALLOC(auditCB, ptr, new\_size) \_oscl\_audit\_realloc(ptr,new\_size, auditCB)
- #define OSCL\_FREE(ptr) \_oscl\_audit\_free(ptr)
- #define oscl\_free(x) OSCL\_FREE(x)
- #define OSCL\_DEFAULT\_FREE(x) OSCL\_FREE(x)
- #define OSCL\_NEW(T, params) new T params
- #define OSCL\_PLACEMENT\_NEW(ptr, constructor) new(ptr) constructor
- #define OSCL\_TRAP\_NEW(T\_ptr, T, params) \_OSCL\_TRAP\_NEW(\_oscl\_default\_audit\_new(sizeof(T)),\_oscl\_audit\_free,T\_ptr,T,params)
- #define OSCL\_AUDIT\_NEW(auditCB, T, params) new(\_oscl\_audit\_new(sizeof(T),auditCB)) T params
- #define OSCL\_TRAP\_AUDIT\_NEW(T\_ptr, auditCB, T, params) \_OSCL\_TRAP\_NEW(\_oscl\_audit\_new(sizeof(T),auditCB),\_oscl\_audit\_free,T\_ptr,T,params)
- #define OSCL\_DELETE(ptr)
- #define OSCL\_AUDIT\_ARRAY\_NEW(auditCB, T, count) new(\_oscl\_audit\_new(sizeof(T)\*(count),auditCB)) T
- #define OSCL\_ARRAY\_NEW(T, count) new T[count]
- #define OSCL\_ARRAY\_DELETE(ptr) delete [ ] ptr
- #define OSCL\_TRAP\_NEW(exp, freeFunc, T\_ptr, T, params)

- #define `_OSCL_CLEANUP_BASE_CLASS(T)` this → T::~T()
- #define `MM_ALLOC_MAX_QUERY_FILENAME_LEN` 128
- #define `MM_ALLOC_MAX_QUERY_TAG_LEN` 64
- #define `MM_AUDIT_VALIDATE_BLOCK` 1
- #define `MM_AUDIT_PREFILL_FLAG` 0x1
- #define `MM_AUDIT_POSTFILL_FLAG` 0x2
- #define `MM_AUDIT_VALIDATE_ALL_HEAP_FLAG` 0x4
- #define `MM_AUDIT_VALIDATE_ON_FREE_FLAG` 0x8
- #define `MM_AUDIT_ALLOC_NODE_ENABLE_FLAG` 0x10
- #define `MM_AUDIT_SUPPRESS_FILENAME_FLAG` 0x20
- #define `DEFAULT_MM_AUDIT_MODE` 0
- #define `MM_AUDIT_ALLOC_NODE_SUPPORT` 1
- #define `MM_AUDIT_FENCE_SUPPORT` 0
- #define `MM_AUDIT_INCLUDE_ALL_HEAP_VALIDATION` 1
- #define `MM_AUDIT_FILL_SUPPORT` 0
- #define `MM_AUDIT_FAILURE_SIMULATION_SUPPORT` 1
- #define `FENCE_PATTERN` 0xAA
- #define `MIN_FENCE_SIZE` 4
- #define `MEM_ALIGN_SIZE` 8
- #define `COMPUTE_MEM_ALIGN_SIZE`(x, y, z) (y+((x+y)%z) ? (z - (x+y)%z) : 0))
- #define `DEFAULT_PREFILL_PATTERN` 0x96
- #define `DEFAULT_POSTFILL_PATTERN` 0x5A
- #define `OSCL_DISABLE_WARNING_RETURN_TYPE_NOT_UDT`

## Typedefs

- typedef `OSCLMemAutoPtr< char, Oscl_TAlloc< char, OsclMemBasicAllocator > >` `MMAudit_CharAutoPtr`
- typedef `OSCLMemAutoPtr< uint8, Oscl_TAlloc< uint8, _OsclBasicAllocator > >` `MMAudit_Uint8AutoPtr`
- typedef `OSCLMemAutoPtr< MM_AllocNode, Oscl_TAlloc< MM_AllocNode, OsclMemBasicAllocator > >` `MM_AllocNodeAutoPtr`
- typedef `OSCLMemAutoPtr< OsclMemStatsNode, Oscl_TAlloc< OsclMemStatsNode, OsclMemBasicAllocator > >` `MM_StatsNodeTagTreeType`
- typedef `OSCLMemAutoPtr< OsclMemStatsNode, Oscl_TAlloc< OsclMemStatsNode, OsclMemBasicAllocator > >` `OsclMemStatsNodeAutoPtr`
- typedef `Oscl_TAlloc< MM_StatsNodeTagTreeType, OsclMemBasicAllocator >` `TagTreeAllocator`
- typedef `Oscl_TagTree< MM_StatsNodeTagTreeType, TagTreeAllocator >` `OsclTagTreeType`

## Functions

- `OSCL_COND_IMPORT_REF void * _oscl_malloc (int32 count)`
- `OSCL_COND_IMPORT_REF void * _oscl_calloc (int32 nelems, int32 size)`
- `OSCL_COND_IMPORT_REF void * _oscl_realloc (void *src, int32 count)`
- `OSCL_COND_IMPORT_REF void _oscl_free (void *src)`
- `OSCL_COND_IMPORT_REF void * oscl_memcpy (void *dest, const void *src, uint32 count)`
- `OSCL_COND_IMPORT_REF void * oscl_memmove (void *dest, const void *src, uint32 count)`
- `OSCL_COND_IMPORT_REF void * oscl_memmove32 (void *dest, const void *src, uint32 count)`
- `OSCL_COND_IMPORT_REF void * oscl_memset (void *dest, uint8 val, uint32 count)`

- OSCL\_COND\_IMPORT\_REF int `oscl_memcmp` (const void \*buf1, const void \*buf2, uint32 count)
- OSCL\_COND\_IMPORT\_REF uint `oscl_mem_aligned_size` (uint size)
- OSCL\_IMPORT\_REF void `OsclMemInit` (OsclAuditCB &auditCB)
- OSCL\_IMPORT\_REF void \* `_oscl_audit_malloc` (size\_t, OsclAuditCB &, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_audit_calloc` (size\_t, size\_t, OsclAuditCB &, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_audit_realloc` (void \*, size\_t, OsclAuditCB &, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_audit_new` (size\_t, OsclAuditCB &, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_default_audit_malloc` (size\_t, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_default_audit_calloc` (size\_t, size\_t, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_default_audit_realloc` (void \*, size\_t, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void \* `_oscl_default_audit_new` (size\_t, const char \*f=NULL, const int l=0)
- OSCL\_IMPORT\_REF void `_oscl_audit_free` (void \*)
- void \* `operator new` (size\_t aSize, const char \*aFile, int aLine)
- void \* `operator new` (size\_t)
- void `operator delete` (void \*)
- void \* `operator new[]` (size\_t aSize, const char \*aFile, int aLine)
- void \* `operator new[]` (size\_t aSize)
- void `operator delete[]` (void \*aPtr)

## Variables

- const uint32 `ALLOC_NODE_FLAG` = 0x80000000

### 6.3.1 Define Documentation

#### 6.3.1.1 #define \_OSCL\_CLEANUP\_BASE\_CLASS(T) this → T::~T()

This macro is used to cleanup the base class in a derived-class constructor just before a leave occurs.

**Parameters:**

*T*: base class name.

#### 6.3.1.2 #define \_OSCL\_TRAP\_NEW(exp, freeFunc, T\_ptr, T, params)

**Value:**

```
{
    int32 __err; \
    OsclAny* __ptr=exp; \
    OSCL_TRY(__err,T_ptr=new(__ptr) T params); \
    if(__err){ \
        freeFunc(__ptr); \
        T_ptr=NULL; \
        OsclError::Leave(__err); \
    } \
}
```

Internal-use macro to catch leaves in constructors. If the constructor leaves, this will free the memory before allowing the leave to propagate to the next level. It is the constructor's responsibility to cleanup any memory in the partially constructed object before leaving. This cleanup may include cleaning up the base class using the OSCL\_CLEANUP\_BASE\_CLASS macro.

**Parameters:**

*exp*: expression to allocate memory.

*Tptr:variable* to hold result.

*T*: type

*params*: constructor arg list

*freeFunc*: delete or free function.

- 6.3.1.3 #define COMPUTE\_MEM\_ALIGN\_SIZE(x, y, z) (y+((x+y)%z) ? (z - (x+y)%z) : 0))
- 6.3.1.4 #define DEFAULT\_MM\_AUDIT\_MODE 0
- 6.3.1.5 #define DEFAULT\_POSTFILL\_PATTERN 0x5A
- 6.3.1.6 #define DEFAULT\_PREFILL\_PATTERN 0x96
- 6.3.1.7 #define FENCE\_PATTERN 0xAA
- 6.3.1.8 #define MEM\_ALIGN\_SIZE 8
- 6.3.1.9 #define MIN\_FENCE\_SIZE 4
- 6.3.1.10 #define MM\_ALLOC\_MAX\_QUERY\_FILENAME\_LEN 128
- 6.3.1.11 #define MM\_ALLOC\_MAX\_QUERY\_TAG\_LEN 64
- 6.3.1.12 #define MM\_AUDIT\_ALLOC\_NODE\_ENABLE\_FLAG 0x10
- 6.3.1.13 #define MM\_AUDIT\_ALLOC\_NODE\_SUPPORT 1
- 6.3.1.14 #define MM\_AUDIT\_FAILURE\_SIMULATION\_SUPPORT 1
- 6.3.1.15 #define MM\_AUDIT\_FENCE\_SUPPORT 0
- 6.3.1.16 #define MM\_AUDIT\_FILL\_SUPPORT 0
- 6.3.1.17 #define MM\_AUDIT\_INCLUDE\_ALL\_HEAP\_VALIDATION 1
- 6.3.1.18 #define MM\_AUDIT\_POSTFILL\_FLAG 0x2
- 6.3.1.19 #define MM\_AUDIT\_PREFILL\_FLAG 0x1
- 6.3.1.20 #define MM\_AUDIT\_SUPPRESS\_FILENAME\_FLAG 0x20
- 6.3.1.21 #define MM\_AUDIT\_VALIDATE\_ALL\_HEAP\_FLAG 0x4
- 6.3.1.22 #define MM\_AUDIT\_VALIDATE\_BLOCK 1
- 6.3.1.23 #define MM\_AUDIT\_VALIDATE\_ON\_FREE\_FLAG 0x8
- 6.3.1.24 #define OSCL\_ALLOC\_DELETE(ptr, T\_allocator, T)

**Value:**

```
{\
  ptr->~T();\
  T_allocator.deallocate(ptr);\
}
```

Deletes the object of type T using the given allocator

**Parameters:**

*T\_allocator* allocator for objects of type T

*T* type of object to delete

*ptr* pointer to previously created object

**Exceptions:**

*none* , unless thrown by the given allocator

**6.3.1.25 #define OSCL\_ALLOC\_NEW(T\_allocator, T, params) new(T\_allocator.allocate(1)) T  
params**

Creates an object of type T using the given allocator to acquire the memory needed.

**Parameters:**

*T\_allocator* allocator for objects of type T, must be an [Oscl\\_TAlloc<T, Allocator>](#), where Allocator is an [Oscl\\_DefAlloc](#)

*T* type of object to create

*params* object initialization parameters

**Returns:**

pointer to created object

**Exceptions:**

*none* , unless thrown by the given allocator

**6.3.1.26 #define OSCL\_ARRAY\_DELETE(ptr) delete [] ptr**

Oscl array delete operator..

**Parameters:**

*ptr* pointer to memory block previously allocated with OSCL\_ARRAY\_NEW

**Returns:**

void

**6.3.1.27 #define OSCL\_ARRAY\_NEW(T, count) new T[count]**

Oscl array "new" operator. This uses the global memory audit object.

**Parameters:**

*T* data type for 'new' operation

*count* number of elements to create

**Returns:**

pointer to the newly created object array of type T

**Exceptions:**

*may* leave with code = bad alloc

**6.3.1.28 #define OSCL\_AUDIT\_ARRAY\_NEW(auditCB, T, count)**  
`new(_oscl_audit_new(sizeof(T)*(count),auditCB)) T`

Oscl array "new" operator. This uses the input memory audit object.

**Parameters:**

*auditCB* input memory management audit object  
*T* data type for 'new' operation  
*count* number of elements to create

**Returns:**

pointer to the newly created object array of type T

**Exceptions:**

*may* leave with code = bad alloc

**6.3.1.29 #define OSCL\_AUDIT\_CALLOC(auditCB, num, size) \_oscl\_audit\_calloc(num,size, auditCB)**

Allocates a memory block using the specified audit object. The block is initialized to zero.

**Parameters:**

*auditCB* input memory management audit object  
*num* number of elements  
*size* number of bytes to allocate for each element

**Returns:**

a void pointer to the allocated space, or NULL if there is insufficient memory available.

**Exceptions:**

*none*

**6.3.1.30 #define OSCL\_AUDIT\_MALLOC(auditCB, count) \_oscl\_audit\_malloc(count, auditCB)**

Allocates a memory block using the given audit object.

**Parameters:**

*auditCB* input memory management audit object  
*count* number of bytes to allocate

**Returns:**

a void pointer to the allocated space, or NULL if there is insufficient memory available.

**Exceptions:**

*none*

**6.3.1.31 #define OSCL\_AUDIT\_NEW(auditCB, T, params) new(\_oscl\_audit\_new(sizeof(T),audit-CB)) T params**

Oscl "new" operator. This uses the specified memory audit object.

**Parameters:**

*auditCB* input memory management audit object  
*T* data type for 'new' operation  
*params* object initialization parameters

**Returns:**

pointer to the newly created object of type *T*

**Exceptions:**

*may* leave with code = bad alloc

**6.3.1.32 #define OSCL\_AUDIT\_REALLOC(auditCB, ptr, new\_size)  
\_oscl\_audit\_realloc(ptr,new\_size,auditCB)**

Re-Allocates a memory block using the specified audit object.

**Parameters:**

*auditCB* input memory management audit object  
*ptr* original memory block  
*new\_size* New size of the block

**Returns:**

a void pointer to the allocated space, or NULL if there is insufficient memory available.

**Exceptions:**

*none*

**6.3.1.33 #define oscl\_calloc(a, b) OSCL\_CALLOC(a,b)****6.3.1.34 #define OSCL\_CALLOC(num, size) \_oscl\_default\_audit\_calloc(num,size)**

Allocates a memory block using the memory management's global audit object. The block is initialized to zero.

**Parameters:**

*num* number of elements  
*size* number of bytes to allocate for each element

**Returns:**

a void pointer to the allocated space, or NULL if there is insufficient memory available.

**Exceptions:**

*none*

**6.3.1.35 #define OSCL\_CLEANUP\_BASE\_CLASS(T) \_OSCL\_CLEANUP\_BASE\_CLASS(T)**

Cleans up the base class of a partially-constructed derived class. This macro will call the destructor if necessary, based on the error-handling implementation.

**Parameters:**

*T*: name of the base class.

**6.3.1.36 #define OSCL\_DEFAULT\_FREE(x) OSCL\_FREE(x)**

Another back-compatibility definition.

**6.3.1.37 #define OSCL\_DEFAULT\_MALLOC(x) OSCL\_MALLOC(x)**

Another back-compatibility definition.

**6.3.1.38 #define OSCL\_DELETE(ptr)****Value:**

```
{ \
    if(ptr){delete(ptr);} \
}
```

Oscl "delete" operator.

**Parameters:**

*ptr* pointer to memory block previously allocated with OSCL\_NEW

**Returns:**

void

**6.3.1.39 #define OSCL\_DISABLE\_WARNING\_RETURN\_TYPE\_NOT\_UDT****6.3.1.40 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE**

Previously this was in oscl\_mem\_imp.h

**6.3.1.41 #define oscl\_free(x) OSCL\_FREE(x)****6.3.1.42 #define OSCL\_FREE(ptr) \_oscl\_audit\_free(ptr)**

Deallocates or frees a memory block.

**Parameters:**

*ptr* pointer to previously allocated memory block using the given audit object

**6.3.1.43 #define OSCL\_HAS\_GLOBAL\_NEW\_DELETE 1**

**6.3.1.44 #define oscl\_malloc(a) OSCL\_MALLOC(a)**

**6.3.1.45 #define OSCL\_MALLOC(count) \_oscl\_default\_audit\_malloc(count)**

Allocates a memory block using the memory management's global audit object.

**Parameters:**

*count* number of bytes to allocate

**Returns:**

a void pointer to the allocated space, or NULL if there is insufficient memory available.

**Exceptions:**

*none*

**6.3.1.46 #define OSCL\_NEW(T, params) new T params**

Oscl "new" operator. This uses the global memory audit object.

**Parameters:**

*T* data type for 'new' operation

*params* object initialization parameters

**Returns:**

pointer to the newly created object of type T

**Exceptions:**

*may* leave with code = bad alloc

**6.3.1.47 #define OSCL\_PLACEMENT\_NEW(ptr, constructor) new(ptr) constructor**

**6.3.1.48 #define oscl\_realloc(a, b) OSCL\_REALLOC(a,b)**

**6.3.1.49 #define OSCL\_REALLOC(ptr, new\_size) \_oscl\_default\_audit\_realloc(ptr,new\_size)**

Re-Allocates a memory block using the memory management's global audit object.

**Parameters:**

*ptr* original memory block

*new\_size* New size of the block

**Returns:**

a void pointer to the allocated space, or NULL if there is insufficient memory available.

**Exceptions:**

*none*

---

**6.3.1.50 #define OSCL\_TRAP\_ALLOC\_NEW(T\_ptr, T\_allocator, T, params)**  
**\_OSCL\_TRAP\_NEW(T\_allocator.allocate(1),T\_allocator.deallocate,T\_ptr,T,params)**

Creates an object of type T using the given allocator to acquire the memory needed. This macro is similar to OSCL\_ALLOC\_NEW except that it handles constructors that leave. If the constructor leaves, the destructor will be called, and allocated memory will be freed before allowing the leave to propagate to the next level.

**Parameters:**

*T\_ptr* variable to hold return value— pointer to new object of type T.

*T\_allocator* allocator for objects of type T, must be an [Oscl\\_TAlloc<T, Allocator>](#), where Allocator is an [Oscl\\_DefAlloc](#)

*T* type of object to create

*params* object initialization parameters

**Returns:**

pointer to created object

**Exceptions:**

*none* , unless thrown by the given allocator

---

**6.3.1.51 #define OSCL\_TRAP\_AUDIT\_NEW(T\_ptr, auditCB, T, params) \_OSCL\_TRAP\_-  
 NEW(\_oscl\_audit\_new(sizeof(T),auditCB),\_oscl\_audit\_free,T\_ptr,T,params)**

Oscl "new" operator. This uses the specified memory audit object. This macro is similar to OSCL\_AUDIT\_NEW except that it will handle constructors that leave. If the constructor leaves, the destructor will be called, and allocated memory will be freed before allowing the leave to propagate to the next level.

**Parameters:**

*T\_ptr* variable to hold return value— pointer to new object of type T.

*auditCB* input memory management audit object

*T* data type for 'new' operation

*params* object initialization parameters

**Returns:**

pointer to the newly created object of type T

**Exceptions:**

*may* leave with code = bad alloc

---

**6.3.1.52 #define OSCL\_TRAP\_NEW(T\_ptr, T, params) \_OSCL\_TRAP\_NEW(\_oscl\_default\_-  
 audit\_new(sizeof(T)),\_oscl\_audit\_free,T\_ptr,T,params)**

Oscl "new" operator. This uses the global memory audit object. This operator is similar to OSCL\_NEW except that it will handle constructors that leave. If the constructor leaves, the destructor will be called, and allocated memory will be freed before allowing the leave to propagate to the next level.

**Parameters:**

*T\_ptr* variable to hold return value— pointer to new object of type T.

*T* data type for 'new' operation

*params* object initialization parameters

**Returns:**

pointer to the newly created object of type T

**Exceptions:**

*may* leave with code = bad alloc

### 6.3.2 Typedef Documentation

- 6.3.2.1 `typedef OSCLMemAutoPtr<MM_AllocNode, Oscl_TAlloc<MM_AllocNode, OsclMemBasicAllocator> > MM_AllocNodeAutoPtr`
- 6.3.2.2 `typedef OSCLMemAutoPtr<OsclMemStatsNode, Oscl_TAlloc<OsclMemStatsNode, OsclMemBasicAllocator> > MM_StatsNodeTagTreeType`
- 6.3.2.3 `typedef OSCLMemAutoPtr<char, Oscl_TAlloc<char, OsclMemBasicAllocator> > MMAuditCharAutoPtr`
- 6.3.2.4 `typedef OSCLMemAutoPtr<uint8, Oscl_TAlloc<uint8, _OsclBasicAllocator> > MMAuditUInt8AutoPtr`
- 6.3.2.5 `typedef OSCLMemAutoPtr<OsclMemStatsNode, Oscl_TAlloc<OsclMemStatsNode, OsclMemBasicAllocator> > OsclMemStatsNodeAutoPtr`
- 6.3.2.6 `typedef Oscl_TagTree<MM_StatsNodeTagTreeType, TagTree_Allocator> OsclTagTreeType`
- 6.3.2.7 `typedef Oscl_TAlloc<MM_StatsNodeTagTreeType, OsclMemBasicAllocator> TagTree_Allocator`

### 6.3.3 Function Documentation

- 6.3.3.1 `OSCL_IMPORT_REF void* _oscl_audit_calloc (size_t, size_t, OsclAuditCB &, const char *f = NULL, const int l = 0)`
- 6.3.3.2 `OSCL_IMPORT_REF void _oscl_audit_free (void *)`
- 6.3.3.3 `OSCL_IMPORT_REF void* _oscl_audit_malloc (size_t, OsclAuditCB &, const char *f = NULL, const int l = 0)`

\*\*\*\*\* Macros for malloc/free with memory management.

- 6.3.3.4 OSCL\_IMPORT\_REF void\* \_oscl\_audit\_new (size\_t, OsclAuditCB &, const char \**f*=NULL, const int *l*=0)**
- 6.3.3.5 OSCL\_IMPORT\_REF void\* \_oscl\_audit\_realloc (void \*, size\_t, OsclAuditCB &, const char \**f*=NULL, const int *l*=0)**
- 6.3.3.6 OSCL\_COND\_IMPORT\_REF void\* \_oscl\_calloc (int32 *nelems*, int32 *size*)**
- 6.3.3.7 OSCL\_IMPORT\_REF void\* \_oscl\_default\_audit\_calloc (size\_t, size\_t, const char \**f*=NULL, const int *l*=0)**
- 6.3.3.8 OSCL\_IMPORT\_REF void\* \_oscl\_default\_audit\_malloc (size\_t, const char \**f*=NULL, const int *l*=0)**
- 6.3.3.9 OSCL\_IMPORT\_REF void\* \_oscl\_default\_audit\_new (size\_t, const char \**f*=NULL, const int *l*=0)**
- 6.3.3.10 OSCL\_IMPORT\_REF void\* \_oscl\_default\_audit\_realloc (void \*, size\_t, const char \**f*=NULL, const int *l*=0)**
- 6.3.3.11 OSCL\_COND\_IMPORT\_REF void \_oscl\_free (void \**src*)**
- 6.3.3.12 OSCL\_COND\_IMPORT\_REF void\* \_oscl\_malloc (int32 *count*)**
- 6.3.3.13 OSCL\_COND\_IMPORT\_REF void\* \_oscl\_realloc (void \**src*, int32 *count*)**
- 6.3.3.14 void operator delete (void \*) [inline]**
- 6.3.3.15 ]**
- void operator delete[] (void \**aPtr*) [inline]
- 6.3.3.16 void\* operator new (size\_t) [inline]**
- 6.3.3.17 void\* operator new (size\_t *aSize*, const char \**aFile*, int *aLine*) [inline]**
- 6.3.3.18 ]**
- void\* operator new[] (size\_t *aSize*) [inline]
- 6.3.3.19 ]**
- void\* operator new[] (size\_t *aSize*, const char \**aFile*, int *aLine*) [inline]
- 6.3.3.20 OSCL\_COND\_IMPORT\_REF uint oscl\_mem\_aligned\_size (uint *size*)**

Get memory-aligned size of an object.

**Parameters:**

*size* size of object

**Returns:**

memory-aligned size

**6.3.3.21 OSCL\_COND\_IMPORT\_REF int oscl\_memcmp (const void \* buf1, const void \* buf2, uint32 count)**

Compare characters in two buffers

**Parameters:**

*buf1* first buffer

*buf2* second buffer

*count* number of bytes to compare

**Returns:**

<0 buf1 less than buf2 0 buf1 equal to buf2 >0 buf1 greater than buf2

**6.3.3.22 OSCL\_COND\_IMPORT\_REF void\* oscl\_memcpy (void \* dest, const void \* src, uint32 count)**

Copies characters between buffers The oscl\_memcpy function copies count bytes of src to dest. If the source and destination overlap, this function does not ensure that the original source bytes in the overlapping region are copied before being overwritten. Use oscl\_memmove to handle overlapping regions

**Parameters:**

*dest* new buffer

*src* buffer to copy

*count* number of bytes to copy

**Returns:**

the value of dest

**6.3.3.23 OSCL\_COND\_IMPORT\_REF void\* oscl\_memmove (void \* dest, const void \* src, uint32 count)**

Moves chars from one buffer to another The memmove function copies count bytes of characters from src to dest. If some regions of the source area and the destination overlap, memmove ensures that the original source bytes in the overlapping region are copied before being overwritten.

**Parameters:**

*dest* new buffer

*src* buffer to copy

*count* number of bytes to copy

**Returns:**

the value of dest

**6.3.3.24 OSCL\_COND\_IMPORT\_REF void\* oscl\_memmove32 (void \* dest, const void \* src, uint32 count)**

Same functionality as oscl\_memmove, yet optimized for memory aligned on 32-bit boundary

**Parameters:**

*dest* new buffer  
*src* buffer to copy  
*count* number of bytes to copy

**Returns:**

the value of dest

**6.3.3.25 OSCL\_COND\_IMPORT\_REF void\* oscl\_memset (void \* dest, uint8 val, uint32 count)**

Sets the bytes of a buffer to a specified character

**Parameters:**

*dest* buffer to modify  
*val* character to set  
*count* number of bytes to set

**Returns:**

the value of dest

**6.3.3.26 OSCL\_IMPORT\_REF void OsclMemInit ([OsclAuditCB](#) & auditCB)**

Initialize an [OsclAuditCB](#) object. Sets the stats node pointer to null, and sets the audit pointer to the global audit object.

**Parameters:**

*auditCB* memory management audit object

## 6.3.4 Variable Documentation

**6.3.4.1 const uint32 MM\_AllocBlockHdr::ALLOC\_NODE\_FLAG = 0x80000000 [static, inherited]**

## 6.4 OSCL Util

### Files

- file [oscl\\_bin\\_stream.h](#)  
*Defines a set of binary stream classes which handle portable input / output of binary data regardless of the native byte order.*
- file [oscl\\_math.h](#)  
*Provides math functions.*
- file [oscl\\_media\\_data.h](#)  
*Defines a container class for media data made up of a collection of memory fragments.*
- file [oscl\\_media\\_status.h](#)  
*Defines a status values for the [MediaData](#) containers.*
- file [oscl\\_pqueue.h](#)  
*Implements a priority queue data structure similar to STL.*
- file [oscl\\_rand.h](#)  
*Provides pseudo-random number generation.*
- file [oscl\\_registry\\_access\\_client.h](#)  
*Client-side implementation Registry Access implementation.*
- file [oscl\\_registry\\_client.h](#)  
*Client-side implementation of OsclRegistry.*
- file [oscl\\_registry\\_client\\_impl.h](#)  
*Client-side implementation of OsclRegistryInterface.*
- file [oscl\\_registry\\_serv\\_impl.h](#)  
*Server-side implementation of OsclRegistry interfaces.*
- file [oscl\\_registry\\_types.h](#)  
*Common types used in Oscl registry interfaces.*
- file [oscl\\_snprintf.h](#)  
*Provides a portable implementation of sprintf.*
- file [oscl\\_str\\_ptr\\_len.h](#)  
*Defines a data structure for string containment/manipulations where the storage for the string is maintained externally.*
- file [oscl\\_string.h](#)  
*Provides a standardized set of string containers that can be used in place of character arrays.*
- file [oscl\\_string\\_containers.h](#)  
*Provides a standardized set of string containers that can be used in place of character arrays.*

- file [oscl\\_string\\_rep.h](#)  
*Contains some internal implementation for string containers.*
- file [oscl\\_string\\_uri.h](#)  
*Utilities to unescape URIs.*
- file [oscl\\_string\\_utf8.h](#)  
*Utilities to validate and truncate UTF-8 encoded strings.*
- file [oscl\\_string\\_utils.h](#)  
*Utilities to parse and convert strings.*
- file [oscl\\_string\\_xml.h](#)  
*Utilities to escape special characters in XML strings.*
- file [oscl\\_tickcount.h](#)  
*Defines a data structure for string containment/manipulations where the storage for the string is maintained externally.*
- file [oscl\\_utf8conv.h](#)  
*Utilities to convert unicode to utf8 and vice versa.*

## Data Structures

- class [BufferFragment](#)
- class [BufferMgr](#)
- class [BufferState](#)
- class [BufFragGroup](#)
- class [BufFragStatusClass](#)
- class [CFastRep](#)
- class [CHheapRep](#)
- class [CStackRep](#)
- class [MediaData](#)
- class [MediaStatusClass](#)
- class [MemAllocator](#)
- class [OSCL\\_FastString](#)
- class [OSCL\\_HeapString](#)
- class [OSCL\\_HeapStringA](#)
- class [OSCL\\_StackString](#)
- class [OSCL\\_String](#)
- class [OSCL\\_wFastString](#)
- class [OSCL\\_wHeapString](#)
- class [OSCL\\_wHeapStringA](#)
- class [OSCL\\_wStackString](#)
- class [OSCL\\_wString](#)
- class [OsclBinIStream](#)
- class [OsclBinIStreamBigEndian](#)
- class [OsclBinIStreamLittleEndian](#)

- class [OsclBinOStream](#)

*Class OsclBinOStream implements the basic stream functions for an output stream.*

- class [OsclBinOStreamBigEndian](#)

*Class OsclBinOStreamBigEndian implements a binary output stream using big endian byte ordering.*

- class [OsclBinOStreamLittleEndian](#)

*Class OsclBinOStreamLittleEndian implements a binary output stream using little endian byte ordering.*

- class [OsclBinStream](#)

- class [OsclCompareLess](#)

- class [OsclComponentRegistry](#)

- class [OsclComponentRegistryData](#)

- class [OsclComponentRegistryElement](#)

- class [OsclPriorityQueue](#)

- class [OsclPriorityQueueBase](#)

- class [OsclRand](#)

- class [OsclRegistryAccessClient](#)

- class [OsclRegistryAccessClientImpl](#)

- class [OsclRegistryAccessClientTlsImpl](#)

- class [OsclRegistryAccessElement](#)

- class [OsclRegistryClient](#)

- class [OsclRegistryClientImpl](#)

- class [OsclRegistryClientTlsImpl](#)

- class [OsclRegistryServTlsImpl](#)

- class [OsclTickCount](#)

- struct [StrCSumPtrLen](#)

*same as [StrPtrLen](#), but includes checksum field and method to speed up querying*

- struct [StrPtrLen](#)

*This data structure encapsulates a set of functions used to perform.*

- struct [WStrPtrLen](#)

*This data structure encapsulates a set of functions used to perform.*

## Defines

- #define [oscl\\_isdigit](#)(c) ((c) >= '0' && (c) <= '9')
- #define [OSCLTICKCOUNT\\_MAX\\_TICKS](#) 0xffffffff
- #define [MAX\\_NUMBER\\_OF\\_BYTE\\_PER\\_UTF8](#) 3

## Typedefs

- typedef [OsclAny](#) \* [OsclComponentFactory](#)
- typedef void(\* [BufferFreeFuncPtr](#) )(void \*)
- typedef uint32 [MediaTimestamp](#)
- typedef [StrPtrLen](#) [StrPtrLen](#)

*This data structure encapsulates a set of functions used to perform.*

- **typedef WStrPtrLen WStrPtrLen**  
*This data structure encapsulates a set of functions used to perform.*
- **typedef StrCSumPtrLen StrCSumPtrLen**  
*same as [StrPtrLen](#), but includes checksum field and method to speed up querying*
- **typedef WStrPtrLen OSCL\_TStrPtrLen**

## Enumerations

- enum **TOSCL\_StringOp** { [EOSCL\\_StringOp\\_CompressASCII](#), [EOSCL\\_StringOp\\_UTF16ToUTF8](#) }
- enum **TOSCL\_wStringOp** { [EOSCL\\_wStringOp\\_ExpandASCII](#), [EOSCL\\_wStringOp\\_UTF8ToUTF16](#) }

## Functions

- **OSCL\_IMPORT\_REF const char \* skip\_whitespace** (const char \*ptr)
- **OSCL\_IMPORT\_REF char \* skip\_whitespace** (char \*ptr)
- **OSCL\_IMPORT\_REF const char \* skip\_whitespace** (const char \*start, const char \*end)
- **OSCL\_IMPORT\_REF const char \* skip\_to\_whitespace** (const char \*start, const char \*end)
- **OSCL\_IMPORT\_REF const char \* skip\_to\_line\_term** (const char \*start\_ptr, const char \*end\_ptr)
- **OSCL\_IMPORT\_REF const char \* skip\_whitespace\_and\_line\_term** (const char \*start, const char \*end)
- **OSCL\_IMPORT\_REF int extract\_string** (const char \*in\_ptr, char \*outstring, int maxsize)
- **OSCL\_IMPORT\_REF int extract\_string** (const char \*start, const char \*end, char \*outstring, int maxsize)
- **OSCL\_IMPORT\_REF bool PV\_atoi** (const char \*buf, const char new\_format, uint32 &value)
- **OSCL\_IMPORT\_REF bool PV\_atoi** (const char \*buf, const char new\_format, int length, uint32 &value)
- **OSCL\_IMPORT\_REF bool PV\_atoi** (const char \*buf, const char new\_format, int length, [uint64](#) &value)
- **OSCL\_IMPORT\_REF bool PV\_atof** (const char \*buf, [OsclFloat](#) &value)
- **OSCL\_IMPORT\_REF bool PV\_atof** (const char \*buf, int length, [OsclFloat](#) &value)
- **OSCL\_IMPORT\_REF int oscl\_abs** (int aVal)
- **OSCL\_COND\_IMPORT\_REF double oscl\_log** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_log10** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_sqrt** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_pow** (double x, double y)
- **OSCL\_COND\_IMPORT\_REF double oscl\_exp** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_sin** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_cos** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_tan** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_asin** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_atan** (double value)
- **OSCL\_COND\_IMPORT\_REF double oscl\_floor** (double value)
- **OSCL\_IMPORT\_REF int32 oscl\_snprintf** (char \*str, uint32 count, const char \*fmt,...)
- **OSCL\_IMPORT\_REF int32 oscl\_snprintf** ([oscl\\_wchar](#) \*str, uint32 count, const [oscl\\_wchar](#) \*fmt,...)
- **OSCL\_IMPORT\_REF int32 oscl\_vsnprintf** (char \*str, uint32 count, const char \*fmt, va\_list args)

- OSCL\_IMPORT\_REF int32 `oscl_vsnprintf` (oscl\_wchar \*str, uint32 count, const oscl\_wchar \*fmt, va\_list args)
- OSCL\_IMPORT\_REF bool `oscl_str_unescape_uri` (const char \*str\_buf\_in, char \*str\_buf\_out, uint32 max\_out\_buf\_bytes, uint32 max\_bytes, uint32 &out\_buf\_len)
 

*unescape any of the special escape sequence in the uri string*
- OSCL\_IMPORT\_REF bool `oscl_str_unescape_uri` (const OSCL\_String &oscl\_str\_in, OSCL\_String &oscl\_str\_out, uint32 &out\_buf\_len)
 

*unescape any of the special escape sequence in the uri string*
- OSCL\_IMPORT\_REF bool `oscl_str_is_valid_utf8` (const uint8 \*str\_buf, uint32 &num\_valid\_characters, uint32 max\_bytes=0, uint32 max\_char\_2\_valid=0, uint32 \*num\_byte\_4\_char=NULL)
 

*Check if the input string contains any illegal UTF-8 character. The function scans the string and validate that each character is a valid utf-8. It stops at the first NULL character, invalid character or the max\_byte value. The string is valid if and only if every character is a valid utf-8 character and the scanning stopped on a character boundary.*
- OSCL\_IMPORT\_REF int32 `oscl_str_truncate_utf8` (uint8 \*str\_buf, uint32 max\_char, uint32 max\_bytes=0)
 

*Truncates the UTF-8 string upto the required size.*
- OSCL\_IMPORT\_REF bool `oscl_str_need_escape_xml` (const char \*str\_buf, uint32 &num\_escape\_bytes, uint32 max\_bytes=0)
 

*Check if the input string contains any special ASCII character like &, <, >, ', ". The function scans the string and check if each character is a special character. It stops at the first NULL character (if max\_bytes = 0), or the max\_byte value.*
- OSCL\_IMPORT\_REF int32 `oscl_str_escape_xml` (const char \*str\_buf\_in, char \*str\_buf\_out, uint32 max\_out\_buf\_bytes, uint32 max\_bytes=0, uint32 \*num\_bytes\_written=NULL)
 

*Escape any of the following special characters in the string Special ASCII characters: &, <, >, ', ".*
- OSCL\_IMPORT\_REF int32 `oscl_UTF8ToUnicode` (const char \*input, int32 inLength, oscl\_wchar \*output, int32 outLength)
 

*Convert UTF8 byte sequence to Unicode string.*
- OSCL\_IMPORT\_REF int32 `oscl_UnicodeToUTF8` (const oscl\_wchar \*input, int32 inLength, char \*output, int32 outLength)
 

*Convert Unicode string to UTF8 byte sequence.*
- `BufferFragment * GetFragment` (const int32 idx)
- `BufferState * GetBufferState` (const int32 idx)
- uint32 `get_size` () const
- uint32 `get_size` () const
- uint32 `get_maxsize` () const
- uint32 `get_maxsize` () const
- const chartype \* `get_cstr` () const
- const chartype \* `get_cstr` () const
- chartype \* `get_str` () const
- chartype \* `get_str` () const
- `OSCL_HeapString` ()
- `OSCL_wHeapString` ()

- `OSCL_HeapString` (const chartype \*cstr)
- `OSCL_wHeapString` (const chartype \*cstr)
- void `set` (const chartype \*buf, uint32 length)
- void `set` (const chartype \*buf, uint32 length)
- void `set` (const other\_chartype \*buf, optype op)
- void `set` (const other\_chartype \*buf, optype op)
- void `set` (const other\_chartype \*buf, uint32 length, optype op)
- void `set` (const other\_chartype \*buf, uint32 length, optype op)
- `OSCL_HeapString` (const chartype \*buf, uint32 length)
- `OSCL_wHeapString` (const chartype \*buf, uint32 length)
- `OSCL_HeapString` (const OSCL\_HeapString &src)
- `OSCL_wHeapString` (const OSCL\_wHeapString &src)
- `OSCL_HeapString` (const `OSCL_String` &src)
- `OSCL_wHeapString` (const `OSCL_wString` &src)
- `~OSCL_HeapString` ()
- `~OSCL_wHeapString` ()
- `OSCL_HeapString & operator=` (const `OSCL_HeapString` &src)
- `OSCL_wHeapString & operator=` (const `OSCL_wHeapString` &src)
- `OSCL_HeapString & operator=` (const `OSCL_String` &src)
- `OSCL_wHeapString & operator=` (const `OSCL_wString` &src)
- `OSCL_HeapString & operator=` (const chartype \*cstr)
- `OSCL_wHeapString & operator=` (const chartype \*cstr)
- uint32 `get_size` () const
- uint32 `get_size` () const
- uint32 `get_maxsize` () const
- uint32 `get_maxsize` () const
- const chartype \* `get_cstr` () const
- const chartype \* `get_cstr` () const
- chartype \* `get_str` () const
- chartype \* `get_str` () const
- `OSCL_StackString` ()
- `OSCL_wStackString` ()
- `OSCL_StackString` (const chartype \*cstr)
- `OSCL_wStackString` (const chartype \*cstr)
- void `set` (const chartype \*buf, uint32 length)
- void `set` (const chartype \*buf, uint32 length)
- void `set` (const other\_chartype \*buf, optype op)
- void `set` (const other\_chartype \*buf, optype op)
- void `set` (const other\_chartype \*buf, uint32 length, optype op)
- void `set` (const other\_chartype \*buf, uint32 length, optype op)
- `OSCL_StackString` (const chartype \*buf, uint32 length)
- `OSCL_wStackString` (const chartype \*buf, uint32 length)
- `OSCL_StackString` (const OSCL\_StackString &src)
- `OSCL_wStackString` (const OSCL\_wStackString &src)
- `OSCL_StackString` (const `OSCL_String` &src)
- `OSCL_wStackString` (const `OSCL_wString` &src)
- `~OSCL_StackString` ()
- `~OSCL_wStackString` ()
- `OSCL_StackString & operator=` (const `OSCL_StackString` &src)
- `OSCL_wStackString & operator=` (const `OSCL_wStackString` &src)

- `OSCL_StackString & operator= (const OSCL_String &src)`
- `OSCL_wStackString & operator= (const OSCL_wString &src)`
- `OSCL_StackString & operator= (const chartype *cstr)`
- `OSCL_wStackString & operator= (const chartype *cstr)`

## Variables

- `const int32 APPEND_MEDIA_AT_END = -1`
- `const uint8 OSCL_ASCII_CASE_MAGIC_BIT = 0x20`

### 6.4.1 Define Documentation

#### 6.4.1.1 #define MAX\_NUMBER\_OF\_BYTE\_PER\_UTF8 3

Define the maximum UTF8 representation in bytes.

**Todo:**

Handle 4-byte surrogate pair representation

#### 6.4.1.2 #define oscl\_isdigit(c) ((c) >= '0' && (c) <= '9')

#### 6.4.1.3 #define OSCLTICKCOUNT\_MAX\_TICKS 0xffffffff

### 6.4.2 Typedef Documentation

#### 6.4.2.1 typedef void(\* BufferFreeFuncPtr)(void \*)

#### 6.4.2.2 typedef uint32 MediaTimestamp

#### 6.4.2.3 typedef WStrPtrLen OSCL\_TStrPtrLen

#### 6.4.2.4 typedef OsclAny\* OsclComponentFactory

OsclComponentFactory is an opaque pointer.

#### 6.4.2.5 typedef StrCSumPtrLen StrCSumPtrLen

same as `StrPtrLen`, but includes checksum field and method to speed up querying

#### 6.4.2.6 typedef struct StrPtrLen StrPtrLen

This data structure encapsulates a set of functions used to perform.

standard string operations. It should be used for null-terminated constant (non-modifiable) strings of char type.

#### 6.4.2.7 `typedef struct WStrPtrLen WStrPtrLen`

This data structure encapsulates a set of functions used to perform standard string operations. It should be used for null-terminated constant strings (non-modifiable) of wchar type.

### 6.4.3 Enumeration Type Documentation

#### 6.4.3.1 `enum TOSCL_StringOp`

Conversion operations for [OSCL\\_String](#) classes

Enumeration values:

`EOSCL_StringOp_CompressASCII`  
`EOSCL_StringOp_UTF16ToUTF8`

#### 6.4.3.2 `enum TOSCL_wStringOp`

Conversion operations for [OSCL\\_wString](#) classes

Enumeration values:

`EOSCL_wStringOp_ExpandASCII`  
`EOSCL_wStringOp_UTF8ToUTF16`

### 6.4.4 Function Documentation

**6.4.4.1 `OSCL_IMPORT_REF int extract_string (const char * start, const char * end, char * outstring, int maxsize)`**

**6.4.4.2 `OSCL_IMPORT_REF int extract_string (const char * in_ptr, char * outstring, int maxsize)`**

**6.4.4.3 `template<uint32 MaxBufSize> const OSCL_wStackString< MaxBufSize >::chartype * OSCL_wStackString< MaxBufSize >::get_cstr () [virtual, inherited]`**

Implements [OSCL\\_wString](#).

**6.4.4.4 `template<uint32 MaxBufSize> const OSCL_StackString< MaxBufSize >::chartype * OSCL_StackString< MaxBufSize >::get_cstr () [virtual, inherited]`**

This function returns the C-style string for read access.

Implements [OSCL\\_String](#).

**6.4.4.5 `template<class Alloc> const OSCL_wHeapString< Alloc >::chartype * OSCL_wHeapString< Alloc >::get_cstr () [virtual, inherited]`**

Implements [OSCL\\_wString](#).

**6.4.4.6 template<class Alloc> const OSCL\_HeapString< Alloc >::chartype \* OSCL\_HeapString< Alloc >::get\_cstr () [virtual, inherited]**

This function returns the C-style string for read access.

Implements [OSCL\\_String](#).

**6.4.4.7 template<uint32 MaxBufSize> uint32 OSCL\_wStackString< MaxBufSize >::get\_maxsize () [virtual, inherited]**

Implements [OSCL\\_wString](#).

**6.4.4.8 template<uint32 MaxBufSize> uint32 OSCL\_StackString< MaxBufSize >::get\_maxsize () [virtual, inherited]**

This function returns the maximum available storage size, not including null terminator. The maximum size may be larger than the current string size.

Implements [OSCL\\_String](#).

**6.4.4.9 template<class Alloc> uint32 OSCL\_wHeapString< Alloc >::get\_maxsize () [virtual, inherited]**

Implements [OSCL\\_wString](#).

**6.4.4.10 template<class Alloc> uint32 OSCL\_HeapString< Alloc >::get\_maxsize () [virtual, inherited]**

This function returns the maximum available storage size, not including null terminator. The maximum size may be larger than the current string size.

Implements [OSCL\\_String](#).

**6.4.4.11 template<uint32 MaxBufSize> uint32 OSCL\_wStackString< MaxBufSize >::get\_size () [virtual, inherited]**

Implements [OSCL\\_wString](#).

**6.4.4.12 template<uint32 MaxBufSize> uint32 OSCL\_StackString< MaxBufSize >::get\_size () [virtual, inherited]**

Pure virtuals from [OSCL\\_String](#)

Implements [OSCL\\_String](#).

**6.4.4.13 template<class Alloc> uint32 OSCL\_wHeapString< Alloc >::get\_size () [virtual, inherited]**

Implements [OSCL\\_wString](#).

---

**6.4.4.14 template<class Alloc> uint32 OSCL\_HeapString< Alloc >::get\_size () [virtual, inherited]**

Pure virtuals from [OSCL\\_String](#)

Implements [OSCL\\_String](#).

**6.4.4.15 template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize >::chartype \* OSCL\_wStackString< MaxBufSize >::get\_str () [virtual, inherited]**

Implements [OSCL\\_wString](#).

**6.4.4.16 template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize >::chartype \* OSCL\_StackString< MaxBufSize >::get\_str () [virtual, inherited]**

This function returns the C-style string for write access. If the string is not writable it returns NULL.

Implements [OSCL\\_String](#).

**6.4.4.17 template<class Alloc> OSCL\_wHeapString< Alloc >::chartype \* OSCL\_wHeapString< Alloc >::get\_str () [virtual, inherited]**

Implements [OSCL\\_wString](#).

**6.4.4.18 template<class Alloc> OSCL\_HeapString< Alloc >::chartype \* OSCL\_HeapString< Alloc >::get\_str () [virtual, inherited]**

This function returns the C-style string for write access. If the string is not writable it returns NULL.

Implements [OSCL\\_String](#).

**6.4.4.19 template<class ChainClass, uint32 max\_frags> BufferState \* BuffFragGroup< ChainClass, max\_frags >::GetBufferState (const int32 idx) [inline, inherited]**

**6.4.4.20 template<class ChainClass, uint32 max\_frags> BufferFragment \* BuffFragGroup< ChainClass, max\_frags >::GetFragment (const int32 idx) [inline, inherited]**

**6.4.4.21 template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize > & OSCL\_wStackString< MaxBufSize >::operator= (const chartype \* cstr) [inherited]**

Reimplemented from [OSCL\\_wString](#).

**6.4.4.22 template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize > & OSCL\_StackString< MaxBufSize >::operator= (const chartype \* cstr) [inherited]**

Assignment operator

**am: null-terminated string**

Reimplemented from [OSCL\\_String](#).

---

**6.4.4.23** template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize > &  
 OSCL\_wStackString< MaxBufSize >::operator= (const OSCL\_wString & src)  
 [inherited]

Reimplemented from [OSCL\\_wString](#).

**6.4.4.24** template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize > &  
 OSCL\_StackString< MaxBufSize >::operator= (const OSCL\_String & src)  
 [inherited]

Assignment operator

Reimplemented from [OSCL\\_String](#).

**6.4.4.25** template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize > &  
 OSCL\_wStackString< MaxBufSize >::operator= (const OSCL\_wStackString<  
 MaxBufSize > & src) [inherited]

**6.4.4.26** template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize > &  
 OSCL\_StackString< MaxBufSize >::operator= (const OSCL\_StackString< MaxBufSize  
 > & src) [inherited]

Assignment operators

**6.4.4.27** template<class Alloc> OSCL\_wHeapString< Alloc > & OSCL\_wHeapString< Alloc  
 >::operator= (const chartype \* cstr) [inherited]

Reimplemented from [OSCL\\_wString](#).

**6.4.4.28** template<class Alloc> OSCL\_HeapString< Alloc > & OSCL\_HeapString< Alloc  
 >::operator= (const chartype \* cstr) [inherited]

Assignment operator

**am:** null-terminated string

Reimplemented from [OSCL\\_String](#).

**6.4.4.29** template<class Alloc> OSCL\_wHeapString< Alloc > & OSCL\_wHeapString< Alloc  
 >::operator= (const OSCL\_wString & src) [inherited]

Reimplemented from [OSCL\\_wString](#).

**6.4.4.30** template<class Alloc> OSCL\_HeapString< Alloc > & OSCL\_HeapString< Alloc  
 >::operator= (const OSCL\_String & src) [inherited]

Assignment operator

Reimplemented from [OSCL\\_String](#).

**6.4.4.31 template<class Alloc> OSCL\_wHeapString< Alloc > & OSCL\_wHeapString< Alloc >::operator= (const OSCL\_wHeapString< Alloc > & src) [inherited]**

**6.4.4.32 template<class Alloc> OSCL\_HeapString< Alloc > & OSCL\_HeapString< Alloc >::operator= (const OSCL\_HeapString< Alloc > & src) [inherited]**

Assignment operators

**6.4.4.33 OSCL\_IMPORT\_REF int oscl\_abs (int aVal)**

**6.4.4.34 OSCL\_COND\_IMPORT\_REF double oscl\_asin (double value)**

Calculates the arc sine of a number

**Parameters:**

*value* source value

**6.4.4.35 OSCL\_COND\_IMPORT\_REF double oscl\_atan (double value)**

Calculates the arc tangent of a number

**Parameters:**

*value* source value

**6.4.4.36 OSCL\_COND\_IMPORT\_REF double oscl\_cos (double value)**

Calculates the cosine of a number

**Parameters:**

*value* source value

**6.4.4.37 OSCL\_COND\_IMPORT\_REF double oscl\_exp (double value)**

Calculates the exponential of e for a number

**Parameters:**

*value* source value

**6.4.4.38 OSCL\_COND\_IMPORT\_REF double oscl\_floor (double value)**

Calculates the floor of a number

**Parameters:**

*value* source value

**6.4.4.39 template<class Alloc> OSCL\_HeapString< Alloc >::OSCL\_HeapString (const OSCL\_String & src) [inherited]**

**6.4.4.40 template<class Alloc> OSCL\_HeapString< Alloc >::OSCL\_HeapString (const OSCL\_HeapString< Alloc > & src) [inherited]**

Creates a heap string that contains a copy of the input string.

**Parameters:**

*src*: input string.

**6.4.4.41 template<class Alloc> OSCL\_HeapString< Alloc >::OSCL\_HeapString (const chartype \* buf, uint32 length) [inherited]**

Creates a heap string that contains a copy of the input string or character array.

**Parameters:**

*src*: character array, not necessarily null-terminated.

*length*: number of characters to copy.

**6.4.4.42 template<class Alloc> OSCL\_HeapString< Alloc >::OSCL\_HeapString (const chartype \* cstr) [inherited]**

Creates a heap string that contains a copy of the input string.

**Parameters:**

*cp*: null-terminated string.

**6.4.4.43 template<class Alloc> OSCL\_HeapString< Alloc >::OSCL\_HeapString () [inherited]**

The default constructor creates an empty string.

**6.4.4.44 OSCL\_COND\_IMPORT\_REF double oscl\_log (double value)**

Calculates the natural log of a number

**Parameters:**

*value* source value

**6.4.4.45 OSCL\_COND\_IMPORT\_REF double oscl\_log10 (double value)**

Calculates the logarithm to base 10 of a number

**Parameters:**

*value* source value

**6.4.4.46 OSCL\_COND\_IMPORT\_REF double oscl\_pow (double x, double y)**

Calculates the value of x to the power of y

**Parameters:**

*x* base value

*y* power

**6.4.4.47 OSCL\_COND\_IMPORT\_REF double oscl\_sin (double *value*)**

Calculates the sine of a number

**Parameters:**

*value* source value

**6.4.4.48 OSCL\_IMPORT\_REF int32 oscl\_snprintf (*oscl\_wchar* \* *str*, uint32 *count*, const *oscl\_wchar* \* *fmt*, ...)****6.4.4.49 OSCL\_IMPORT\_REF int32 oscl\_snprintf (char \* *str*, uint32 *count*, const char \* *fmt*, ...)****6.4.4.50 OSCL\_COND\_IMPORT\_REF double oscl\_sqrt (double *value*)**

Calculates the square root of a number

**Parameters:**

*value* source value

**6.4.4.51 template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize >::OSCL\_StackString (const OSCL\_String & *src*) [inherited]****6.4.4.52 template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize >::OSCL\_StackString (const OSCL\_StackString< MaxBufSize > & *src*) [inherited]**

Creates an OSCL\_StackString with a copy of the input string. The string may be truncated to fit the available storage.

**Parameters:**

*src*: input string.

**6.4.4.53 template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize >::OSCL\_StackString (const *chartype* \* *buf*, uint32 *length*) [inherited]**

Creates an OSCL\_StackString with a copy of the input string. The string may be truncated to fit the available storage.

**Parameters:**

*src*: a character array, not necessarily null-terminated.

*length*: the number of characters to copy.

**6.4.4.54 template<uint32 MaxBufSize> OSCL\_StackString<MaxBufSize>::OSCL\_StackString  
(const chartype \* *cstr*) [inherited]**

Creates an OSCL\_StackString with a copy of the input string. The string may be truncated to fit the available storage.

**Parameters:**

*cp*: a null-terminated string.

**6.4.4.55 template<uint32 MaxBufSize> OSCL\_StackString<MaxBufSize>::OSCL\_StackString  
() [inherited]**

Creates an OSCL\_StackString initialized with an empty string.

**6.4.4.56 OSCL\_IMPORT\_REF int32 oscl\_str\_escape\_xml (const char \* *str\_buf\_in*, char \*  
*str\_buf\_out*, uint32 *max\_out\_buf\_bytes*, uint32 *max\_bytes* = 0, uint32 \* *num\_bytes\_written*  
= NULL)**

Escape any of the following special characters in the string Special ASCII characters: &, <, >, ', ".

The function scans the string and replaces each special character with its corresponding escape sequence. It stops at the first NULL character, the max\_byte value.

**Parameters:**

*str\_buf\_in* Ptr to an input string

*str\_buf\_out* Ptr to an output buffer which stores the modified string

*max\_out\_buf\_bytes* The size of str\_buf\_out.

*max\_bytes* The maximum number of bytes to read (a zero value means read to the first NULL character). It is the length of str\_buf\_in.

*num\_bytes\_written* Number of bytes written in the output buffer, str\_buf\_out

**Returns:**

It returns the number of bytes in the str\_buf\_outring if succeeded. It returns negative number if failed, and its absolute value indicates the total number bytes written to the output buffer, str\_buf\_out, if str\_buf\_out != null.

**6.4.4.57 OSCL\_IMPORT\_REF bool oscl\_str\_is\_valid\_utf8 (const uint8 \* *str\_buf*, uint32 &  
*num\_valid\_characters*, uint32 *max\_bytes* = 0, uint32 *max\_char\_2\_valid* = 0, uint32 \*  
*num\_byte\_4\_char* = NULL)**

Check if the input string contains any illegal UTF-8 character. The function scans the string and validate that each character is a valid utf-8. It stops at the first NULL character, invalid character or the max\_byte value. The string is valid if and only if every character is a valid utf-8 character and the scanning stopped on a character boundary.

**Parameters:**

*str\_buf* Ptr to an input string, which may not terminate with null, to be checked

*num\_valid\_chars* This is an output parameter which is the number of valid utf-8 characters actually read.

***max\_bytes*** The maximum number of bytes to read (a zero value means read to the first NULL character).

***max\_char\_2\_valid*** This is an input parameter. Specify the number of utf-8 characters the caller wants to validate.

***num\_byte\_4\_char*** This is an output parameter. The number of bytes used by the max\_char characters

**Returns:**

True if the string is valid and false otherwise.

#### 6.4.4.58 OSCL\_IMPORT\_REF bool oscl\_str\_need\_escape\_xml (const char \* str\_buf, uint32 & num\_escape\_bytes, uint32 max\_bytes = 0)

Check if the input string contains any special ASCII character like &, <, >, ', ". The function scans the string and check if each character is a special character. It stops at the first NULL character (if max\_bytes = 0), or the max\_byte value.

**Parameters:**

***str\_buf*** Ptr to an input string, which may not terminate with null, to be checked

***num\_escape\_bytes*** This is an output parameter which is the number of bytes needed to hold the result string. Value 0 indicates that there is no special character found. If max\_bytes = 0, the return value does not include the null character.

***max\_bytes*** The maximum number of bytes to read (a zero value means read to the first NULL character).

**Returns:**

True if the function succeeds, and num\_escape\_bytes = 0 means that no special character is found, num\_escape\_bytes >0 means the number of bytes of the result string. False if there is any error occurred.

#### 6.4.4.59 OSCL\_IMPORT\_REF int32 oscl\_str\_truncate\_utf8 (uint8 \* str\_buf, uint32 max\_char, uint32 max\_bytes = 0)

Truncates the UTF-8 string upto the required size.

The function will modify the str\_buf so that it contains AT MOST len valid utf-8 characters. If a NULL character is found before reading len utf-8 characters, then the function does not modify the string and simply returns the number of characters. If an invalid character is found, then it will insert a NULL character after the last valid character and return the length. Otherwise, it will insert a NULL character after len valid utf-8 characters and return the length.

**Parameters:**

***str\_buf*** Ptr to an input string which may not terminate with null

***max\_char*** The max number of the UTF-8 CHARACTERS

***max\_bytes*** The maximum number of bytes to read (a zero value means read to the first NULL character).

**Returns:**

It returns the length of the truncated string in utf-8 characters.

**6.4.4.60 OSCL\_IMPORT\_REF bool oscl\_str\_unescape\_uri (const OSCL\_String & *oscl\_str\_in*, OSCL\_String & *oscl\_str\_out*, uint32 & *out\_buf\_len*)**

unescape any of the special escape sequence in the uri string

The function scans the string and replaces each escape sequence with its corresponding character. It stops at the first null character, or the max\_byte value. It returns false if the string contains any illegal escape sequence or the output buffer is not big enough. The out\_buf\_len value indicates the needed buffer length or the index of the byte that causes the error respectively.

**Parameters:**

*oscl\_str\_in* Ptr to an input OSCL\_String

*oscl\_str\_out* Ptr to an output OSCL\_String which stores the modified string

*out\_buf\_len* The length of the result string (not including the null character)

**Returns:**

It returns true if succeeds, otherwise false.

**6.4.4.61 OSCL\_IMPORT\_REF bool oscl\_str\_unescape\_uri (const char \* *str\_buf\_in*, char \* *str\_buf\_out*, uint32 *max\_out\_buf\_bytes*, uint32 *max\_bytes*, uint32 & *out\_buf\_len*)**

unescape any of the special escape sequence in the uri string

The function scans the string and replaces each escape sequence with its corresponding character. It stops at the first null character, or the max\_byte value. It returns false if the string contains any illegal escape sequence or the output buffer is not big enough. The out\_buf\_len value indicates the needed buffer length or the index of the byte that causes the error respectively.

**Parameters:**

*str\_buf\_in* Ptr to an input string

*str\_buf\_out* Ptr to an output buffer which stores the modified string

*max\_out\_buf\_bytes* The size of str\_buf\_out.

*max\_bytes* The maximum number of bytes to read. It is the length of str\_buf\_in.

*out\_buf\_len* The length of the result string (not including the null character)

**Returns:**

It returns true if succeeds, otherwise false.

**6.4.4.62 OSCL\_COND\_IMPORT\_REF double oscl\_tan (double *value*)**

Calculates the tangential of a number

**Parameters:**

*value* source value

#### 6.4.4.63 OSCL\_IMPORT\_REF int32 oscl\_UnicodeToUTF8 (const oscl\_wchar \* *input*, int32 *inLength*, char \* *output*, int32 *outLength*)

Convert Unicode string to UTF8 byte sequence.

The function converts Unicode string to UTF8 byte sequence. The length of input Unicode string is specified. It stops at two conditions: (A) Whole input Unicode string is successfully converted. (B) Destination buferr is not enough for output. In case of (A), it adds a terminated '\0' at the end of the output UTF8 byte sequence, and returns length of the output UTF8 byte sequence (without counting terminated '\0'). In case of (B), it converts as much as possible to the output buffer and adds a terminated '\0' at the end of the output UTF8 byte sequence "(no '\0' added if outLength is less than or equal to 0, return 0)", and returns 0.

**Parameters:**

*input* Ptr to an input Unicode string. '\0' termination is not necessary.

*inLength* The length of the input Unicode string, without counting terminated '\0' (if any).

*output* Ptr to an output buffer which output UTF8 byte sequence is written in.

*outLength* The size of output buffer, also the maximum number of char could be written in.

**Returns:**

length of output (excludes '\0') : completely converts all input string and appends '\0' to output; 0 : insufficient buffer or error in conversion

#### 6.4.4.64 OSCL\_IMPORT\_REF int32 oscl\_UTF8ToUnicode (const char \* *input*, int32 *inLength*, oscl\_wchar \* *output*, int32 *outLength*)

Convert UTF8 byte sequence to Unicode string.

The function converts UTF8 byte sequence (or ASCII sequence) to Unicode string. The length of input UTF8 byte sequence is specified. It stops at two conditions: (A) Whole input UTF8 byte sequence is successfully converted. (B) Output buferr is not enough for output, or parse error. In case of (A), it adds a terminated '\0' at the end of the output Unicode string, and returns length of the output Unicode string (without counting terminated '\0'). In case of (B), it converts as much as possible to the output buffer and adds a terminated '\0' at the end of the output Unicode string "(no '\0' added if outLength is less than or equal to 0, return 0)", and returns 0.

**Parameters:**

*input* Ptr to an input UTF8 byte sequence. '\0' termination is not necessary.

*inLength* The length of the input UTF8 byte sequence, without counting terminated '\0' (if any).

*output* Ptr to an output buffer which output Unicode string is written in.

*outLength* The size of output buffer, also the maximum number of oscl\_wchar could be written in.

**Returns:**

Length of output (excludes '\0') : completely converts all input string and appends '\0' to output; 0 : insufficient buffer or error in conversion



- 6.4.4.65 **OSCL\_IMPORT\_REF int32 oscl\_vsnprintf (oscl\_wchar \* str, uint32 count, const oscl\_wchar \* fmt, va\_list args)**
- 6.4.4.66 **OSCL\_IMPORT\_REF int32 oscl\_vsnprintf (char \* str, uint32 count, const char \* fmt, va\_list args)**
- 6.4.4.67 **template<class Alloc> OSCL\_wHeapString< Alloc >::OSCL\_wHeapString (const OSCL\_wString & src) [inherited]**
- 6.4.4.68 **template<class Alloc> OSCL\_wHeapString< Alloc >::OSCL\_wHeapString (const OSCL\_wHeapString< Alloc > & src) [inherited]**
- 6.4.4.69 **template<class Alloc> OSCL\_wHeapString< Alloc >::OSCL\_wHeapString (const chartype \* buf, uint32 length) [inherited]**
- 6.4.4.70 **template<class Alloc> OSCL\_wHeapString< Alloc >::OSCL\_wHeapString (const chartype \* cstr) [inherited]**
- 6.4.4.71 **template<class Alloc> OSCL\_wHeapString< Alloc >::OSCL\_wHeapString () [inherited]**
- 6.4.4.72 **template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize >::OSCL\_wStackString (const OSCL\_wString & src) [inherited]**
- 6.4.4.73 **template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize >::OSCL\_wStackString (const OSCL\_wStackString< MaxBufSize > & src) [inherited]**
- 6.4.4.74 **template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize >::OSCL\_wStackString (const chartype \* buf, uint32 length) [inherited]**
- 6.4.4.75 **template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize >::OSCL\_wStackString (const chartype \* cstr) [inherited]**
- 6.4.4.76 **template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize >::OSCL\_wStackString () [inherited]**
- 6.4.4.77 **OSCL\_IMPORT\_REF bool PV\_atof (const char \* buf, int length, OsclFloat & value)**
- 6.4.4.78 **OSCL\_IMPORT\_REF bool PV\_atof (const char \* buf, OsclFloat & value)**
- 6.4.4.79 **OSCL\_IMPORT\_REF bool PV\_atoi (const char \* buf, const char new\_format, int length, uint64 & value)**
- 6.4.4.80 **OSCL\_IMPORT\_REF bool PV\_atoi (const char \* buf, const char new\_format, int length, uint32 & value)**
- 6.4.4.81 **OSCL\_IMPORT\_REF bool PV\_atoi (const char \* buf, const char new\_format, uint32 & value)**
- 6.4.4.82 **template<uint32 MaxBufSize> void OSCL\_wStackString< MaxBufSize >::set (const other\_chartype \* buf, uint32 length, optype op) [inherited]**
- 6.4.4.83 **template<uint32 MaxBufSize> void OSCL\_StackString< MaxBufSize >::set (const other\_chartype \* buf, uint32 length, optype op) [inherited]**

**Parameters:**

- buf*: string or character array.
- length*: number of characters to copy.
- op*: conversion operation to apply

**6.4.4.84 template<uint32 MaxBufSize> void OSCL\_wStackString< MaxBufSize >::set (const other\_chartype \* *buf*, *otype op*) [inherited]**

**6.4.4.85 template<uint32 MaxBufSize> void OSCL\_StackString< MaxBufSize >::set (const other\_chartype \* *buf*, *otype op*) [inherited]**

Set the contents of this string to a new string, with conversion operation.

**Parameters:**

- buf*: NULL-terminated wide string.
- op*: conversion operation to apply

**6.4.4.86 template<uint32 MaxBufSize> void OSCL\_wStackString< MaxBufSize >::set (const chartype \* *buf*, uint32 *length*) [inherited]**

**6.4.4.87 template<uint32 MaxBufSize> void OSCL\_StackString< MaxBufSize >::set (const chartype \* *buf*, uint32 *length*) [inherited]**

Set the contents of this string to a new string or character array.

**Parameters:**

- buf*: string or character array.
- length*: number of characters to copy.

**6.4.4.88 template<class Alloc> void OSCL\_wHeapString< Alloc >::set (const other\_chartype \* *buf*, uint32 *length*, *otype op*) [inherited]**

**6.4.4.89 template<class Alloc> void OSCL\_HeapString< Alloc >::set (const other\_chartype \* *buf*, uint32 *length*, *otype op*) [inherited]**

Set the contents of this string to a new string or character array, with conversion operation.

**Parameters:**

- buf*: string or character array.
- length*: number of characters to copy.
- op*: conversion operation to apply

**6.4.4.90 template<class Alloc> void OSCL\_wHeapString< Alloc >::set (const other\_chartype \* *buf*, *otype op*) [inherited]**

**6.4.4.91 template<class Alloc> void OSCL\_HeapString< Alloc >::set (const other\_chartype \* *buf*, *otype op*) [inherited]**

Set the contents of this string to a new string, with conversion operation.

**Parameters:**

*buf*: NULL-terminated wide string.

*op*: conversion operation to apply

**6.4.4.92 template<class Alloc> void OSCL\_wHeapString< Alloc >::set (const chartype \* *buf*,  
                  uint32 *length*) [inherited]**

**6.4.4.93 template<class Alloc> void OSCL\_HeapString< Alloc >::set (const chartype \* *buf*,  
                  uint32 *length*) [inherited]**

Set the contents of this string to a new string or character array.

**Parameters:**

*buf*: string or character array.

*length*: number of characters to copy.

**6.4.4.94 OSCL\_IMPORT\_REF const char\* skip\_to\_line\_term (const char \* *start\_ptr*, const char \*  
                  *end\_ptr*)**

**6.4.4.95 OSCL\_IMPORT\_REF const char\* skip\_to\_whitespace (const char \* *start*, const char \*  
                  *end*)**

**6.4.4.96 OSCL\_IMPORT\_REF const char\* skip\_whitespace (const char \* *start*, const char \* *end*)**

**6.4.4.97 OSCL\_IMPORT\_REF char\* skip\_whitespace (char \* *ptr*)**

**6.4.4.98 OSCL\_IMPORT\_REF const char\* skip\_whitespace (const char \* *ptr*)**

**6.4.4.99 OSCL\_IMPORT\_REF const char\* skip\_whitespace\_and\_line\_term (const char \* *start*,  
                  const char \* *end*)**

**6.4.4.100 template<class Alloc> OSCL\_HeapString< Alloc >::~OSCL\_HeapString ()  
                  [inherited]**

**6.4.4.101 template<uint32 MaxBufSize> OSCL\_StackString< MaxBufSize  
                  >::~OSCL\_StackString () [inherited]**

**6.4.4.102 template<class Alloc> OSCL\_wHeapString< Alloc >::~OSCL\_wHeapString ()  
                  [inherited]**

**6.4.4.103 template<uint32 MaxBufSize> OSCL\_wStackString< MaxBufSize  
                  >::~OSCL\_wStackString () [inherited]**

## 6.4.5 Variable Documentation

**6.4.5.1 const int32 APPEND\_MEDIA\_AT\_END = -1**

**6.4.5.2 const uint8 OSCL\_ASCII\_CASE\_MAGIC\_BIT = 0x20**

## 6.5 OSCL Error

### Files

- file [oscl\\_errno.h](#)  
*Defines functions to access additional information on errors where supported through an errno or similar service.*
- file [oscl\\_error.h](#)  
*OSCL Error trap and cleanup include file.*
- file [oscl\\_error\\_allocator.h](#)  
*Defines a memory allocation class used by the oscl error layer.*
- file [oscl\\_error\\_codes.h](#)  
*Defines basic error and leave codes.*
- file [oscl\\_error\\_imp.h](#)  
*Internal error implementation support.*
- file [oscl\\_error\\_imp\\_cppexceptions.h](#)  
*Implementation File for Leave using C++ exceptions.*
- file [oscl\\_error\\_imp\\_fatalerror.h](#)  
*Implementation File for Leave using system fatal error.*
- file [oscl\\_error\\_imp\\_jumps.h](#)  
*Implementation of using Setjmp / Longjmp.*
- file [oscl\\_error\\_trapcleanup.h](#)  
*OSCL Error trap and cleanup implementation include file.*
- file [oscl\\_exception.h](#)  
*contains all the exception handling macros and classes*
- file [oscl\\_heapbase.h](#)  
*OSCL Heap Base include file.*
- file [oscl\\_namestring.h](#)  
*Name string class include file.*

### Data Structures

- class [\\_OsclHeapBase](#)
- class [internalLeave](#)
- class [OsclError](#)
- class [OsclErrorAllocator](#)

*This class provides static methods to invoke the user defined memory allocation routines.*

- class OsclErrorTrap
- class OsclErrorTrapImp
- class OsclException

*oscl\_exception.h* contains all the exception handling macros and classes This template class provides the base exception class that all exceptions derive from

- class OsclJump
- class OsclNameString
- class OsclTLSEx
- class OsclTLSRegistryEx
- class OsclTrapItem
- class OsclTrapStack
- class OsclTrapStackItem

## Defines

- #define OSCL\_TRAPSTACK\_PUSH(a) OsclError::PushL(a)
- #define OSCL\_TRAPSTACK\_POP() OsclError::Pop()
- #define OSCL\_TRAPSTACK\_POPDEALLOC() OsclError::PopDealloc()
- #define OsclErrNone 0
- #define OsclErrGeneral 100
- #define OsclErrNoMemory 101
- #define OsclErrCancelled 102
- #define OsclErrNotSupported 103
- #define OsclErrArgument 104
- #define OsclErrBadHandle 105
- #define OsclErrAlreadyExists 106
- #define OsclErrBusy 107
- #define OsclErrNotReady 108
- #define OsclErrCorrupt 109
- #define OsclErrTimeout 110
- #define OsclErrOverflow 111
- #define OsclErrUnderflow 112
- #define OsclErrInvalidState 113
- #define OsclErrNoResources 114
- #define OsclErrNotInstalled 115
- #define OsclErrAlreadyInstalled 116
- #define OsclErrSystemCallFailed 117
- #define OsclErrNoHandler 118
- #define OsclErrThreadContextIncorrect 119
- #define OSCL\_ERR\_NONE OsclErrNone
- #define OSCL\_BAD\_ALLOC\_EXCEPTION\_CODE OsclErrNoMemory
- #define OsclSuccess 0
- #define OsclPending 1
- #define OsclFailure -1
- #define PVERROR\_IMP\_JUMPS
- #define PVERROR\_DoLeave() internalLeave \_\_ilv; \_\_ilv.a=0; throw(\_\_ilv)
- #define \_PV\_TRAP(\_\_r, \_\_s)
- #define \_PV\_TRAP\_NO\_TLS(\_\_trapimp, \_\_r, \_\_s)
- #define OSCL\_JUMP\_MAX\_JUMP\_MARKS OSCL\_MAX\_TRAP\_LEVELS

- #define **internalLeave** (-1)
- #define **OSCL\_MAX\_TRAP\_LEVELS** 20
- #define **PVERRORTRAP\_REGISTRY\_ID** OSCL\_TLS\_ID\_PVERRORTRAP
- #define **PVERRORTRAP\_REGISTRY** OsclTLSRegistry
- #define **OSCL\_LEAVE**(\_leave\_status) OsclError::Leave(\_leave\_status)
 

*Use this macro to cause a Leave. It terminates the execution of the current active function.*
- #define **OSCL\_TRY**(\_leave\_status, \_statements) \_PV\_TRAP(\_leave\_status,\_statements)
 

*This macro will be used to set up a try block.*
- #define **OSCL\_TRY\_NO\_TLS**(\_trapimp, \_leave\_status, \_statements) \_PV\_TRAP\_NO\_TLS(\_-trapimp,\_leave\_status,\_statements)
- #define **OSCL\_FIRST\_CATCH\_ANY**(\_leave\_status, \_statements) if (\_leave\_status!=OsclErrNone){ \_statements; }
 

*This section defines the macros to be used in the catch block following the try block. Use this macro to call a function that handles all exception types thrown in the preceding try block.*
- #define **OSCL\_FIRST\_CATCH**(\_leave\_status, \_catch\_value, \_statements) if (\_leave\_status!=OsclErrNone && \_leave\_status == \_catch\_value){\_statements;}
 

*Use this macro to define a block of code that catches the first exception type thrown in the preceding try block.*
- #define **OSCL\_CATCH**(\_leave\_status, \_catch\_value, \_statements) else if (\_leave\_status!=OsclErrNone && \_leave\_status == \_catch\_value){\_statements;}
 

*Use this macro to define a block of code for catching additional exception types.*
- #define **OSCL\_CATCH\_ANY**(\_leave\_status, \_statements) else if (\_leave\_status!=OsclErrNone){ \_-statements;}
 

*Use this macro to call a function that will catch all remaining exception types.*
- #define **OSCL\_LAST\_CATCH**(\_leave\_status) else if (\_leave\_status!=OsclErrNone){OSCL\_-LEAVE(\_leave\_status);}
 

*Use this macro if OSCL\_CATCH\_ANY has not been used. It will mark the end of the catch block.*

## Typedefs

- typedef int32 **OsclLeaveCode**
- typedef int32 **OsclReturnCode**
- typedef void(\*) **OsclTrapOperation** )(OsclAny \*)

## Functions

- OSCL\_IMPORT\_REF bool **OSCL\_IsErrnoSupported** ()
 

*This function determines if a particular system saves the error number that occurs on a system call.*
- OSCL\_IMPORT\_REF int **OSCL\_GetLastError** ()
 

*This function returns the value of the system's global error number variable.*
- OSCL\_IMPORT\_REF bool **OSCL\_SetLastError** (int newVal)

*This function sets the last error code for the system.*

- OSCL\_IMPORT\_REF char \* **OSCL\_StrError** (int errnum)

*This function maps an error number to an error-message string.*

## 6.5.1 Define Documentation

### 6.5.1.1 #define \_PV\_TRAP(\_\_r, \_\_s)

**Value:**

```
__r=OsclErrNone; \
{ \
    OsclErrorTrapImp* __tr=OsclErrorTrapImp::Trap(); \
    if(!__tr){__s;}else{ \
        try{__s;} \
        catch(internalLeave __lv){ \
            __lv.a=__r=__tr->iLeave; } \
            __tr->UnTrap(); } \
    } 
```

### 6.5.1.2 #define \_PV\_TRAP\_NO\_TLS(\_\_trapimp, \_\_r, \_\_s)

**Value:**

```
__r=OsclErrNone; \
{ \
    OsclErrorTrapImp* __tr=OsclErrorTrapImp::TrapNoTls(__trapimp); \
    if(!__tr){__s;}else{ \
        try{__s;} \
        catch(internalLeave __lv){ \
            __lv.a=__r=__tr->iLeave; } \
            __tr->UnTrap(); } \
    } 
```

### 6.5.1.3 #define internalLeave (-1)

### 6.5.1.4 #define OSCL\_BAD\_ALLOC\_EXCEPTION\_CODE OsclErrNoMemory

### 6.5.1.5 #define OSCL\_CATCH(\_leave\_status, \_catch\_value, \_statements) else if (\_leave\_status!=OsclErrNone && \_leave\_status == \_catch\_value){\_statements;}

Use this macro to define a block of code for catching additional exception types.

OSCL\_FIRST\_CATCH can be used to catch one exception type. Then the OSCL\_CATCH macro can be used to catch each subsequent type. The catch block must end with OSCL\_LAST\_CATCH or OSCL\_CATCH\_ANY

**Parameters:**

*oscl\_leave\_status* is the result of any OSCL\_THROW

*exceptiontype* is the exception handled by this catch block

**6.5.1.6 #define OSCL\_CATCH\_ANY(\_leave\_status, \_statements) else if  
(\_leave\_status!=OsclErrNone){ \_statements;}**

Use this macro to call a function that will catch all remaining exception types.

**Parameters:**

*\_leave\_status*

*\_statements* is a statement or block of statements to handle all remaining exception types. This macro ends the try block.

**6.5.1.7 #define OSCL\_ERR\_NONE OsclErrNone**

For backward compatibility with old definitions

**6.5.1.8 #define OSCL\_FIRST\_CATCH(\_leave\_status, \_catch\_value, \_statements) if  
(\_leave\_status!=OsclErrNone && \_leave\_status == \_catch\_value){\_statements;}**

Use this macro to define a block of code that catches the first exception type thrown in the preceding try block.

**Parameters:**

*oscl\_leave\_status* is the leave code that was returned by OSCL\_THROW

*exceptiontype* is the exception handled by this catch block. This macro MUST be used in conjunction with either OSCL\_LAST\_CATCH or OSCL\_CATCH\_ANY

**6.5.1.9 #define OSCL\_FIRST\_CATCH\_ANY(\_leave\_status, \_statements) if  
(\_leave\_status!=OsclErrNone) { \_statements; }**

This section defines the macros to be used in the catch block following the try block. Use this macro to call a function that handles all exception types thrown in the preceding try block.

**Parameters:**

*\_leave\_status*

*\_statements* is a statement or block of statements that will catch all the exception types thrown by the preceding try block. This is a standalone macro and should not be used with any of the macros above

**6.5.1.10 #define OSCL\_JUMP\_MAX\_JUMP\_MARKS OSCL\_MAX\_TRAP\_LEVELS****6.5.1.11 #define OSCL\_LAST\_CATCH(\_leave\_status) else if (\_leave\_status!=OsclErrNone){OSCL\_LEAVE(\_leave\_status);}**

Use this macro if OSCL\_CATCH\_ANY has not been used. It will mark the end of the catch block.

**Parameters:**

*\_leave\_status* will be propagated up the call stack. This macro will do an OSCL\_LEAVE if the leave has not been handled by the calls above. This macro ends the try block.

**6.5.1.12 #define OSCL\_LEAVE(\_leave\_status) OsclError::Leave(\_leave\_status)**

Use this macro to cause a Leave. It terminates the execution of the current active function.

It also tries to cleanup the items on the cleanup stack.

**Parameters:**

*oscl\_leave\_status* tells the cause for the Leave

**6.5.1.13 #define OSCL\_MAX\_TRAP\_LEVELS 20****6.5.1.14 #define OSCL\_TRAPSTACK\_POP() OsclError::Pop()****6.5.1.15 #define OSCL\_TRAPSTACK\_POPDEALLOC() OsclError::PopDealloc()****6.5.1.16 #define OSCL\_TRAPSTACK\_PUSH(a) OsclError::PushL(a)**

Cleanup Stack user macros

**6.5.1.17 #define OSCL\_TRY(\_leave\_status, \_statements) \_PV\_TRAP(\_leave\_status, \_statements)**

This macro will be used to set up a try block.

The try block identifies a block of code that might throw exceptions (or leave)

**Parameters:**

*oscl\_leave\_status* oscl\_leave\_status will receive the result of any OSCL\_LEAVE (which will get called from a OSCL\_THROW) on systems that do not support exception handling. This is unused on systems that do support exception handling

*statements* is a statement or block of statements that could throw exceptions and will be executed in the try block



6.5.1.18 #define OSCL\_TRY\_NO\_TLS(\_\_trapimp, \_leave\_status, \_statements)  
  \_\_PV\_TRAP\_NO\_TLS(\_\_trapimp,\_leave\_status,\_statements)

6.5.1.19 #define OsclErrAlreadyExists 106

6.5.1.20 #define OsclErrAlreadyInstalled 116

6.5.1.21 #define OsclErrArgument 104

6.5.1.22 #define OsclErrBadHandle 105

6.5.1.23 #define OsclErrBusy 107

6.5.1.24 #define OsclErrCancelled 102

6.5.1.25 #define OsclErrCorrupt 109

6.5.1.26 #define OsclErrGeneral 100

6.5.1.27 #define OsclErrInvalidState 113

6.5.1.28 #define OsclErrNoHandler 118

6.5.1.29 #define OsclErrNoMemory 101

6.5.1.30 #define OsclErrNone 0

6.5.1.31 #define OsclErrNoResources 114

6.5.1.32 #define OsclErrNotInstalled 115

6.5.1.33 #define OsclErrNotReady 108

6.5.1.34 #define OsclErrNotSupported 103

6.5.1.35 #define OsclErrOverflow 111

6.5.1.36 #define OsclErrSystemCallFailed 117

6.5.1.37 #define OsclErrThreadContextIncorrect 119

6.5.1.38 #define OsclErrTimeout 110

6.5.1.39 #define OsclErrUnderflow 112

6.5.1.40 #define OsclFailure -1

6.5.1.41 #define OsclPending 1

6.5.1.42 #define OsclSuccess 0

6.5.1.43 #define PVError\_DoLeave() internalLeave \_\_ilv; \_\_ilv.a=0; throw(\_\_ilv)

6.5.1.44 #define PVERROR\_IMP\_JUMPS

**6.5.1.45 #define PVERRORTRAP\_REGISTRY OsclTLSRegistry**

**6.5.1.46 #define PVERRORTRAP\_REGISTRY\_ID OSCL\_TLS\_ID\_PVERRORTRAP**

## 6.5.2 Typedef Documentation

**6.5.2.1 typedef int32 OsclLeaveCode**

Leave Codes

**6.5.2.2 typedef int32 OsclReturnCode**

Return Codes

**6.5.2.3 typedef void(\* OsclTrapOperation)(OsclAny\*)**

**OsclTrapItem** may be used in the cleanup stack when a custom cleanup operation is needed.

## 6.5.3 Function Documentation

**6.5.3.1 OSCL\_IMPORT\_REF int OSCL\_GetLastError ()**

This function returns the value of the system's global error number variable.

**Returns:**

Returns 0 for system's that do not have this functionality The value of the error number variable does not change until the user calls SetLastError or if another system call occurs that changes the value

Supported Platforms: Win32/wince, Unix Unsupported Platforms : Symbian

**6.5.3.2 OSCL\_IMPORT\_REF bool OSCL\_IsErrnoSupported ()**

This function determines if a particular system saves the error number that occurs on a system call.

**Returns:**

This method returns false on systems that do not save the error number that occurs on a system call in a global variable. Returns true for systems that do save the error number

**6.5.3.3 OSCL\_IMPORT\_REF bool OSCL\_SetLastError (int *newVal*)**

This function sets the last error code for the system.

**Parameters:**

***newVal*** This value represents the new value for the global error number This method can be used to reset the error number after having retrieved it using GetLastError. Supported Platforms: Win32/wince, Unix Unsupported Platforms : Symbian

#### 6.5.3.4 OSCL\_IMPORT\_REF char\* OSCL\_StrError (int *errnum*)

This function maps an error number to an error-message string.

**Parameters:**

*errnum* This value represents the error number to map

**Returns:**

This method returns a pointer to a string containing the system error-message. It returns NULL for systems that do not have this functionality Supported Platforms: Win32/wince, Unix Unsupported Platforms : Symbian

## 6.6 OSCL IO

### Files

- file `oscl_dns.h`  
*The file `oscl_socket.h` defines the OSCL DNS APIs.*
- file `oscl_file_cache.h`  
*The file `oscl_file_cache.h` defines the class `OsclFileCache`.*
- file `oscl_file_dir_utils.h`  
*The file `oscl_file_dir_utils.h` defines some unix-style directory ops.*
- file `oscl_file_find.h`  
*The file `oscl_file_find.h` defines the class `Oscl_FileFind`.*
- file `oscl_file_handle.h`  
*The file `oscl_file_handle.h` defines the class `Oscl_FileHandle`.*
- file `oscl_file_io.h`  
*The file `oscl_file_io.h` defines the class `Oscl_File`. This is the public API to the basic file I/O operations.*
- file `oscl_file_manager.h`  
*File management class.*
- file `oscl_file_native.h`  
*The file `oscl_file_native.h` defines the class `OsclNativeFile`. This is the porting layer for basic file I/O operations.*
- file `oscl_file_server.h`  
*The file `oscl_file_server.h` defines the class `Oscl_FileServer`. This is the porting layer for file server implementations.*
- file `oscl_file_stats.h`  
*File stats class.*
- file `oscl_file_types.h`  
*The file `oscl_file_types.h` defines some constants and types for file I/O implementations. Anything that needs to be shared across implementation modules can go here.*
- file `oscl_socket.h`  
*The file `oscl_socket.h` defines the OSCL Socket APIs.*

### Data Structures

- class `Oscl_File`
- class `Oscl_FileFind`
- class `Oscl_FileServer`
- struct `oscl_fsstat`

- struct `oscl_stat_buf`
- class `OsclIDNS`
- class `OsclDNSObserver`
- class `OsclFileCache`
- class `OsclFileCacheBuffer`
- class `OsclFileHandle`
- class `OsclFileManager`
- class `OsclFileStats`
- class `OsclFileStatsItem`
- class `OsclNativeFile`
- class `OsclNativeFileParams`
- class `OsclSocketServ`
- class `OsclTCPSocket`
- class `OsclUDPSocket`

## Defines

- #define `TOsclFileOffsetInt32` int32
- #define `OSCL_FILE_STATS_LOGGER_NODE` "OsclFileStats"
- #define `OSCL_IO_FILENAME_MAXLEN` 512
- #define `OSCL_IO_EXTENSION_MAXLEN` 512
- #define `OSCL_FILE_WCHAR_PATH_DELIMITER` \_STRLIT("/")
- #define `OSCL_FILE_CHAR_PATH_DELIMITER` \_STRLIT\_CHAR("/")

## Typedefs

- typedef `oscl_fsstat` `OSCL_FSSTAT`
- typedef `oscl_stat_buf` `OSCL_STAT_BUF`
- typedef FILE \* `TOsclFileHandle`

## Enumerations

- enum `TPVDNSFxn` { `EPVDNSGetHostByName` }
- enum `TPVDNSEvent` { `EPVDNSSuccess`, `EPVDNSPending`, `EPVDNSTimeout`, `EPVDNSFailure`, `EPVDNSCancel` }
- enum `OSCL_FILEMGMT_PERMS` { `OSCL_FILEMGMT_PERMS_READ` = 0x1, `OSCL_FILEMGMT_PERMS_WRITE` = 0x2, `OSCL_FILEMGMT_PERMS_EXECUTE` = 0x4 }
- enum `OSCL_FILEMGMT_MODES` { `OSCL_FILEMGMT_MODE_DIR` = 0x1 }
- enum `OSCL_FILEMGMT_ERR_TYPE` { `OSCL_FILEMGMT_E_OK` = 0, `OSCL_FILEMGMT_E_PATH_TOO_LONG`, `OSCL_FILEMGMT_E_PATH_NOT_FOUND`, `OSCL_FILEMGMT_E_ALREADY_EXISTS`, `OSCL_FILEMGMT_E_NOT_EMPTY`, `OSCL_FILEMGMT_E_PERMISSION_DENIED`, `OSCL_FILEMGMT_E_NO_MATCH`, `OSCL_FILEMGMT_E_UNKNOWN`, `OSCL_FILEMGMT_E_SYS_SPECIFIC`, `OSCL_FILEMGMT_E_NOT_IMPLEMENTED` }
- enum `TOsclFileOp` { `EOsclFileOp_Open`, `EOsclFileOp_Close`, `EOsclFileOp_Read`, `EOsclFileOp_Write`, `EOsclFileOp_Seek`, `EOsclFileOp_Tell`, `EOsclFileOp_Size`, `EOsclFileOp_Flush`, `EOsclFileOp_EndOfFile`, `EOsclFileOp_SetSize`, `EOsclFileOp_NativeOpen`, `EOsclFileOp_NativeClose`, `EOsclFileOp_NativeRead`, `EOsclFileOp_NativeWrite`, `EOsclFileOp_NativeSeek`, `EOsclFileOp_NativeTell`, `EOsclFileOp_NativeSize`, `EOsclFileOp_NativeFlush`, `EOsclFileOp_NativeEndOfFile`, `EOsclFileOp_NativeSetSize`, `EOsclFileOp_Last` }

## Functions

- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_getcwd (oscl\_wchar \*path, uint32 size)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_getcwd (char \*path, uint32 size)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_stat (const oscl\_wchar \*path, OSCL\_STAT\_BUF \*statbuf)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_stat (const char \*path, OSCL\_STAT\_BUF \*statbuf)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_mkdir (const oscl\_wchar \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_mkdir (const char \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rmdir (const oscl\_wchar \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rmdir (const char \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_chdir (const oscl\_wchar \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_chdir (const char \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rename (const oscl\_wchar \*oldpath, const oscl\_wchar \*newpath)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rename (const char \*oldpath, const char \*newpath)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_statsfs (OSCL\_FSSTAT \*stats, const char \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_statsfs (OSCL\_FSSTAT \*stats, const oscl\_wchar \*path)

### 6.6.1 Define Documentation

6.6.1.1 #define OSCL\_FILE\_CHAR\_PATH\_DELIMITER \_STRLIT\_CHAR("/")

6.6.1.2 #define OSCL\_FILE\_STATS\_LOGGER\_NODE "OsclFileStats"

6.6.1.3 #define OSCL\_FILE\_WCHAR\_PATH\_DELIMITER \_STRLIT("/")

6.6.1.4 #define OSCL\_IO\_EXTENSION\_MAXLEN 512

6.6.1.5 #define OSCL\_IO\_FILENAME\_MAXLEN 512

6.6.1.6 #define TOsclFileOffsetInt32 int32

### 6.6.2 Typedef Documentation

6.6.2.1 typedef struct oscl\_fsstat OSCL\_FSSTAT

6.6.2.2 typedef struct oscl\_stat\_buf OSCL\_STAT\_BUF

6.6.2.3 typedef FILE\* TOsclFileHandle

TOsclFileHandle is an OS-native file handle type. With a class-based file API such as Symbian, a class ref is used as a file handle. For most ANSI-style file APIs, a file pointer is used as a file handle.

### 6.6.3 Enumeration Type Documentation

#### 6.6.3.1 enum OSCL\_FILEMGMT\_ERR\_TYPE

Enumeration values:

- `OSCL_FILEMGMT_E_OK`
- `OSCL_FILEMGMT_E_PATH_TOO_LONG`
- `OSCL_FILEMGMT_E_PATH_NOT_FOUND`
- `OSCL_FILEMGMT_E_ALREADY_EXISTS`
- `OSCL_FILEMGMT_E_NOT_EMPTY`
- `OSCL_FILEMGMT_E_PERMISSION_DENIED`
- `OSCL_FILEMGMT_E_NO_MATCH`
- `OSCL_FILEMGMT_E_UNKNOWN`
- `OSCL_FILEMGMT_E_SYS_SPECIFIC`
- `OSCL_FILEMGMT_E_NOT_IMPLEMENTED`

#### 6.6.3.2 enum OSCL\_FILEMGMT\_MODES

Enumeration values:

- `OSCL_FILEMGMT_MODE_DIR`

#### 6.6.3.3 enum OSCL\_FILEMGMT\_PERMS

Enumeration values:

- `OSCL_FILEMGMT_PERMS_READ`
- `OSCL_FILEMGMT_PERMS_WRITE`
- `OSCL_FILEMGMT_PERMS_EXECUTE`

#### 6.6.3.4 enum TOsclFileOp

Enumeration values:

- `EOsclFileOp_Open`
- `EOsclFileOp_Close`
- `EOsclFileOp_Read`
- `EOsclFileOp_Write`
- `EOsclFileOp_Seek`
- `EOsclFileOp_Tell`
- `EOsclFileOp_Size`
- `EOsclFileOp_Flush`
- `EOsclFileOp_EndOfFile`
- `EOsclFileOp_SetSize`
- `EOsclFileOp_NativeOpen`
- `EOsclFileOp_NativeClose`

```
EOsclFileOp_NativeRead
EOsclFileOp_NativeWrite
EOsclFileOp_NativeSeek
EOsclFileOp_NativeTell
EOsclFileOp_NativeSize
EOsclFileOp_NativeFlush
EOsclFileOp_NativeEndOfFile
EOsclFileOp_NativeSetSize
EOsclFileOp_Last
```

#### 6.6.3.5 enum TPVDNSEvent

Enumeration values:

```
EPVDNSSuccess
EPVDNSPending
EPVDNSTimeout
EPVDNSFailure
EPVDNSCancel
```

#### 6.6.3.6 enum TPVDNSFxn

Enumeration values:

```
EPVDNSGetHostByName
```

### 6.6.4 Function Documentation

#### 6.6.4.1 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_chdir (const char \**path*)

oscl\_chdir changes the current directory to the path given

**Parameters:**

*character* path the full path of the directory to change to.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.2 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_chdir (const oscl\_wchar \**path*)

oscl\_chdir changes the current directory to the path given

**Parameters:**

*wide* character path the full path of the directory to change to.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.3 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_getcwd (char \*path, uint32 size)

oscl\_getcwd function can be used to determine the full path name of the current directory.

**Parameters:**

*pointer* to character buffer to receive the current directory  
*size* size of buffer in characters

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.4 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_getcwd (oscl\_wchar \*path, uint32 size)

oscl\_getcwd function can be used to determine the full path name of the current directory.

**Parameters:**

*pointer* to wide character buffer to receive the current directory  
*size* size of buffer in wide characters

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.5 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_mkdir (const char \*path)

oscl\_mkdir function creates a directory in the path given

**Parameters:**

*character* path the full path of the directory to create. if parts of the path do not exist the function will fail

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.6 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_mkdir (const oscl\_wchar \*path)

oscl\_mkdir function creates a directory in the path given

**Parameters:**

*wide* character path the full path of the directory to create. if parts of the path do not exist the function will fail

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

**6.6.4.7 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rename (const char \*  
*oldpath*, const char \**newpath*)**

oscl\_rmdir removes an empty directory in the path given

**Parameters:**

*character* path the full path of the directory to remove.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

**6.6.4.8 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rename (const oscl\_wchar  
*\* oldpath*, const oscl\_wchar \**newpath*)**

oscl\_rename function renames a file or directory

**Parameters:**

*wide* character path the full path of the file or directory to rename.

*wide* character path the full path the new name for the directory

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

**6.6.4.9 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rmdir (const char \**path*)**

oscl\_rmdir removes an empty directory in the path given

**Parameters:**

*character* path the full path of the directory to remove.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

**6.6.4.10 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_rmdir (const oscl\_wchar \*  
*path*)**

oscl\_rmdir function removes and empty directory in the path given

**Parameters:**

*wide* character path the full path of the directory to remove.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.11 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_stat (const char \*path, OSCL\_STAT\_BUF \*statbuf)

oscl\_stat function can be used to determine the attributes of a file in addition to whether the file exists or not

**Parameters:**

*character* path the full path of the file to stat.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.12 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_stat (const oscl\_wchar \* path, OSCL\_STAT\_BUF \*statbuf)

oscl\_stat function can be used to determine the attributes of a file in addition to whether the file exists or not

**Parameters:**

*wide* character path the full path of the file to stat.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.13 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_statsfs (OSCL\_FSSTAT \* stats, const oscl\_wchar \*path)

Oscl\_StatFS function populates a general structure describing free space available on a filesystem

**Parameters:**

*stats* pointer to structure to hold information

*path* located in desired filesystem (utf8) Note: If the OS does not support a particular field in the structure, it is set to -1.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

#### 6.6.4.14 OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_statsfs (OSCL\_FSSTAT \* stats, const char \*path)

Oscl\_StatFS function populates a general structure describing free space available on a filesystem

**Parameters:**

*stats* pointer to structure to hold information

*path* located in desired filesystem (utf8) Note: If the OS does not support a particular field in the structure, it is set to -1.

**Returns:**

OSCL\_FILEMGMT\_ERR\_TYPE, see enumeration for this type.

## 6.7 OSCL Proc

### Files

- file [oscl\\_aostatus.h](#)  
*Some basic types used with active objects.*
- file [oscl\\_double\\_list.h](#)  
*Internal use types for scheduler.*
- file [oscl\\_scheduler\\_ao.h](#)  
*Oscl Scheduler user execution object classes.*
- file [oscl\\_scheduler\\_aobase.h](#)  
*Oscl Scheduler internal active object classes.*
- file [oscl\\_scheduler\\_readyq.h](#)  
*ready q types for oscl scheduler*
- file [oscl\\_scheduler\\_threadcontext.h](#)  
*Thread context functions needed by oscl scheduler.*
- file [oscl\\_scheduler\\_tuneables.h](#)  
*Tuneable settings for Oscl Scheduler.*
- file [oscl\\_scheduler\\_types.h](#)  
*Scheduler common types include file.*

### Data Structures

- class [OsclActiveObject](#)
- class [OsclAOStatus](#)
- class [OsclDoubleLink](#)
- class [OsclDoubleList](#)
- class [OsclDoubleListBase](#)
- class [OsclDoubleRunner](#)
- class [OsclExecScheduler](#)
- class [OsclExecSchedulerBase](#)
- class [OsclExecSchedulerCommonBase](#)
- class [OsclPriorityLink](#)
- class [OsclPriorityList](#)
- class [OsclReadyAlloc](#)
- class [OsclReadyCompare](#)
- class [OsclReadyQ](#)
- class [OsclScheduler](#)
- class [OsclSchedulerObserver](#)
- class [OsclTimerCompare](#)
- class [OsclTimerObject](#)

- class OsclTimerQ
- class PVActiveBase
- class PVActiveStats
- class PVSchedulerStopper
- class PVThreadContext
- class TReadyQueLink

## Defines

- #define QUE\_ITER\_BEGIN(\_type, \_qname)
- #define QUE\_ITER\_END(\_qname)
- #define PVSCHEDNAMELEN 30
- #define OSCL\_ZEROIZE(ptr, size) oscl\_memset(ptr, 0, size)
- #define PVEXECNAMELEN 30
- #define PV\_SCHED\_ENABLE\_AO\_STATS 1
- #define PV\_SCHED\_ENABLE\_LOOP\_STATS 0
- #define PV\_SCHED\_ENABLE\_PERF\_LOGGING 1
- #define PV\_SCHED\_ENABLE\_THREAD\_CONTEXT\_CHECKS 1
- #define PV\_SCHED\_LOG\_Q 0
- #define PV\_SCHED\_CHECK\_Q 0
- #define PV\_SCHED\_FAIR\_SCHEDULING 1
- #define OSCL\_PERF\_SUMMARY\_LOGGING 0

## Typedefs

- typedef PVActiveBase \* TOsclReady

## Enumerations

- enum TPVThreadContext { EPVThreadContext\_InThread, EPVThreadContext\_OsclThread, EPVThreadContext\_NonOsclThread, EPVThreadContext\_Undetermined }

## Functions

- template<class T, class S> T \* OsclPtrAdd (T \*aPtr, S aVal)
- template<class T, class S> T \* OsclPtrSub (T \*aPtr, S aVal)

## Variables

- const int32 OSCL\_REQUEST\_ERR\_NONE = 0
- const int32 OSCL\_REQUEST\_PENDING = (-0x7fffffff)
- const int32 OSCL\_REQUEST\_ERR\_CANCEL = (-1)
- const int32 OSCL\_REQUEST\_ERR\_GENERAL = (-2)

## 6.7.1 Define Documentation

**6.7.1.1 #define OSCL\_PERF\_SUMMARY\_LOGGING 0**

**6.7.1.2 #define OSCL\_ZEROIZE(ptr, size) oscl\_memset(ptr, 0, size)**

This file defines the [PVActiveBase](#) class, which is a common base for All PV ExecObjs on all platforms.

**6.7.1.3 #define PV\_SCHED\_CHECK\_Q 0**

**6.7.1.4 #define PV\_SCHED\_ENABLE\_AO\_STATS 1**

**6.7.1.5 #define PV\_SCHED\_ENABLE\_LOOP\_STATS 0**

**6.7.1.6 #define PV\_SCHED\_ENABLE\_PERF\_LOGGING 1**

**6.7.1.7 #define PV\_SCHED\_ENABLE\_THREAD\_CONTEXT\_CHECKS 1**

**6.7.1.8 #define PV\_SCHED\_FAIR\_SCHEDULING 1**

**6.7.1.9 #define PV\_SCHED\_LOG\_Q 0**

**6.7.1.10 #define PVEEXECNAMELEN 30**

**6.7.1.11 #define PVSCEDNAMELEN 30**

PV Scheduler class

**6.7.1.12 #define QUE\_ITER\_BEGIN(\_type, \_qname)**

**Value:**

```
if (!_qname.IsEmpty())\
{\
    OsclDoubleRunner <_type> iter(_qname);\
    _type *item;\
    for (iter.SetToHead(); ;iter++)\
    {\
        item=iter;\
```

**6.7.1.13 #define QUE\_ITER\_END(\_qname)**

**Value:**

```
if (_qname.IsTail(item))\
    break;\
}\
```

## 6.7.2 Typedef Documentation

### 6.7.2.1 `typedef PVActiveBase* TOsclReady`

## 6.7.3 Enumeration Type Documentation

### 6.7.3.1 `enum TPVThreadContext`

Thread context type

Enumeration values:

- `EPVThreadContext_InThread`
- `EPVThreadContext_OsclThread`
- `EPVThreadContext_NonOsclThread`
- `EPVThreadContext_Undetermined`

## 6.7.4 Function Documentation

### 6.7.4.1 `template<class T, class S> T* OsclPtrAdd (T * aPtr, S aVal) [inline]`

### 6.7.4.2 `template<class T, class S> T* OsclPtrSub (T * aPtr, S aVal) [inline]`

## 6.7.5 Variable Documentation

### 6.7.5.1 `const int32 OSCL_REQUEST_ERR_CANCEL = (-1)`

### 6.7.5.2 `const int32 OSCL_REQUEST_ERR_GENERAL = (-2)`

### 6.7.5.3 `const int32 OSCL_REQUEST_ERR_NONE = 0`

### 6.7.5.4 `const int32 OSCL_REQUEST_PENDING = (-0x7fffffff)`

## **6.8 OSCL Init**

### **Files**

- file [oscl\\_init.h](#)

*Global oscl initialization.*

### **Data Structures**

- class [OsclInit](#)
- class [OsclSelect](#)


# Chapter 7

## oscl Data Structure Documentation

### 7.1 \_OsclBasicAllocator Class Reference

```
#include <oscl_base_alloc.h>
```

Inheritance diagram for \_OsclBasicAllocator::



#### Public Methods

- [OsclAny \\* allocate \(const uint32 size\)](#)
- [void deallocate \(OsclAny \\*p\)](#)
- [virtual ~\\_OsclBasicAllocator \(\)](#)

#### 7.1.1 Detailed Description

A basic allocator that does not rely on other modules. There is no memory auditing or exception generation.

Note: this allocator is for internal use by Oscl code only. Higher level code should use [OsclMemAllocator](#) defined in "oscl\_mem.h".

## 7.1.2 Constructor & Destructor Documentation

7.1.2.1 `virtual _OsclBasicAllocator::~_OsclBasicAllocator () [inline, virtual]`

## 7.1.3 Member Function Documentation

7.1.3.1 `OsclAny* _OsclBasicAllocator::allocate (const uint32 size) [inline, virtual]`

Implements [Oscl\\_DefAlloc](#).

7.1.3.2 `void _OsclBasicAllocator::deallocate (OsclAny *p) [inline, virtual]`

Implements [Oscl\\_DefAlloc](#).


The documentation for this class was generated from the following file:

- [oscl\\_base\\_alloc.h](#)

## 7.2 \_OsclHeapBase Class Reference

```
#include <oscl_heapbase.h>
```

Inheritance diagram for \_OsclHeapBase::



### Public Methods

- virtual ~\_OsclHeapBase ()

### Protected Methods

- \_OsclHeapBase ()
- \_OsclHeapBase (const \_OsclHeapBase &)

### Friends

- class PVCleanupStack

### 7.2.1 Detailed Description

\_OsclHeapBase is used as the base for cleanup stack items with virtual destructor.

### 7.2.2 Constructor & Destructor Documentation

7.2.2.1 `virtual _OsclHeapBase::~_OsclHeapBase () [inline, virtual]`

7.2.2.2 `_OsclHeapBase::_OsclHeapBase () [inline, protected]`

7.2.2.3 `_OsclHeapBase::_OsclHeapBase (const _OsclHeapBase &) [inline, protected]`

### 7.2.3 Friends And Related Function Documentation

7.2.3.1 `friend class PVCleanupStack [friend]`


The documentation for this class was generated from the following file:

- [oscl\\_heapbase.h](#)

## 7.3 AcceptParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for AcceptParam::



### Public Methods

- [AcceptParam \(OsclSocketI &aBlankSocket\)](#)

### Data Fields

- [OsclSocketI \\* iBlankSocket](#)

#### 7.3.1 Constructor & Destructor Documentation

7.3.1.1 [AcceptParam::AcceptParam \(OsclSocketI & aBlankSocket\) \[inline\]](#)

#### 7.3.2 Field Documentation

7.3.2.1 [OsclSocketI\\* AcceptParam::iBlankSocket](#)

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.4 allocator Class Reference

```
#include <oscl_mem_mempool.h>
```

### 7.4.1 Detailed Description

A memory allocator class which allocates and deallocates from a fixed size memory pool; The memory pool is a multiple of fixed chunk size and does not grow. All allocation size must be the same as this chunk size.


The documentation for this class was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.5 AllPassFilter Class Reference

```
#include <pvlogger_accessories.h>
```

Inheritance diagram for AllPassFilter::



### Public Types

- [typedef PVLoggerFilter::message\\_id\\_type message\\_id\\_type](#)
- [typedef PVLoggerFilter::log\\_level\\_type log\\_level\\_type](#)
- [typedef PVLoggerFilter::filter\\_status\\_type filter\\_status\\_type](#)

### Public Methods

- [AllPassFilter \(\)](#)
- [virtual ~AllPassFilter \(\)](#)
- [filter\\_status\\_type FilterString \(char \\*tag, message\\_id\\_type msgID, log\\_level\\_type level\)](#)
- [filter\\_status\\_type FilterOpaqueMessge \(char \\*tag, message\\_id\\_type msgID, log\\_level\\_type level\)](#)

#### 7.5.1 Detailed Description

Example filter that allows all messages to be logged.

#### 7.5.2 Member Typedef Documentation

##### 7.5.2.1 [typedef PVLoggerFilter::filter\\_status\\_type AllPassFilter::filter\\_status\\_type](#)

Reimplemented from [PVLoggerFilter](#).

##### 7.5.2.2 [typedef PVLoggerFilter::log\\_level\\_type AllPassFilter::log\\_level\\_type](#)

Reimplemented from [PVLoggerFilter](#).

##### 7.5.2.3 [typedef PVLoggerFilter::message\\_id\\_type AllPassFilter::message\\_id\\_type](#)

Reimplemented from [PVLoggerFilter](#).

### 7.5.3 Constructor & Destructor Documentation

**7.5.3.1** `AllPassFilter::AllPassFilter () [inline]`

**7.5.3.2** `virtual AllPassFilter::~AllPassFilter () [inline, virtual]`

### 7.5.4 Member Function Documentation

**7.5.4.1** `filter_status_type AllPassFilter::FilterOpaqueMessge (char * tag, message_id_type msgID, log_level_type level) [inline, virtual]`

Implements [PVLoggerFilter](#).

**7.5.4.2** `filter_status_type AllPassFilter::FilterString (char * tag, message_id_type msgID, log_level_type level) [inline, virtual]`

Implements [PVLoggerFilter](#).


The documentation for this class was generated from the following file:

- [pvlogger\\_accessories.h](#)

## 7.6 BindParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for BindParam::



### Public Methods

- [BindParam \(OsclNetworkAddress &anAddr\)](#)

### Data Fields

- [OsclNetworkAddress iAddr](#)

#### 7.6.1 Constructor & Destructor Documentation

7.6.1.1 [BindParam::BindParam \(OsclNetworkAddress & anAddr\) \[inline\]](#)

#### 7.6.2 Field Documentation

7.6.2.1 [OsclNetworkAddress BindParam::iAddr](#)


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.7 BufferFragment Class Reference

```
#include <oscl_media_data.h>
```

Inheritance diagram for BufferFragment::



The documentation for this class was generated from the following file:

- [oscl\\_media\\_data.h](#)

## 7.8 BufferMgr Class Reference

```
#include <oscl_media_data.h>
```

### Public Methods

- virtual void [BufferReleased](#) (void \*ptr, [BufferState](#) \*state=NULL)=0
- virtual [~BufferMgr](#) ()

#### 7.8.1 Constructor & Destructor Documentation

**7.8.1.1 virtual BufferMgr::~BufferMgr () [inline, virtual]**

#### 7.8.2 Member Function Documentation

**7.8.2.1 virtual void BufferMgr::BufferReleased (void \*ptr, BufferState \* state = NULL) [pure virtual]**

The documentation for this class was generated from the following file:

- [oscl\\_media\\_data.h](#)

## 7.9 BufferState Class Reference

```
#include <oscl_media_data.h>
```

### Public Methods

- `BufferState (BufferFreeFuncPtr the_free_function, void *bufptr=0)`
- `BufferState (BufferMgr *the_buf_mgr=0, void *bufptr=0)`
- `void increment_refcnt ()`
- `void decrement_refcnt ()`
- `void bind (void *in_ptr, BufferFreeFuncPtr in_free_function)`
- `void bind (void *in_ptr, BufferMgr *in_buf_mgr)`
- `void * get_ptr ()`
- `int32 getRefCount ()`
- `BufferFreeFuncPtr get_free_function ()`
- `BufferMgr * get_buf_mgr ()`
- `void reset ()`

#### 7.9.1 Constructor & Destructor Documentation

**7.9.1.1 `BufferState::BufferState (BufferFreeFuncPtr the_free_function, void * bufptr = 0)` [inline]**

**7.9.1.2 `BufferState::BufferState (BufferMgr * the_buf_mgr = 0, void * bufptr = 0)` [inline]**

#### 7.9.2 Member Function Documentation

**7.9.2.1 `void BufferState::bind (void * in_ptr, BufferMgr * in_buf_mgr)` [inline]**

**7.9.2.2 `void BufferState::bind (void * in_ptr, BufferFreeFuncPtr in_free_function)` [inline]**

**7.9.2.3 `void BufferState::decrement_refcnt ()` [inline]**

**7.9.2.4 `BufferMgr* BufferState::get_buf_mgr ()` [inline]**

**7.9.2.5 `BufferFreeFuncPtr BufferState::get_free_function ()` [inline]**

**7.9.2.6 `void* BufferState::get_ptr ()` [inline]**

**7.9.2.7 `int32 BufferState::getRefCount ()` [inline]**

**7.9.2.8 `void BufferState::increment_refcnt ()` [inline]**

**7.9.2.9 `void BufferState::reset ()` [inline]**


The documentation for this class was generated from the following file:

- `oscl_media_data.h`

## 7.10 BufFragGroup< ChainClass, max\_frags > Class Template Reference

```
#include <oscl_media_data.h>
```

Inheritance diagram for BufFragGroup< ChainClass, max\_frags >::



### Public Methods

- [BufFragGroup \(\)](#)
- virtual [~BufFragGroup \(\)](#)
- int32 [GetMaxFrags \(\) const](#)
- int32 [GetNumFrags \(\) const](#)
- uint32 [GetLength \(\) const](#)
- [BufferFragment \\* GetFragment \(const int32 idx\)](#)
- [BufferState \\* GetBufferState \(const int32 idx\)](#)
- void [AppendNext \(ChainClass \\*next\\_ptr\)](#)
- ChainClass \* [GetNext \(\) const](#)

### Protected Methods

- virtual void [Clear \(\)](#)
- [BufFragStatusClass::status\\_t AddFragment \(const BufferFragment &frag, BufferState \\*in\\_buffer\\_state, int32 location\\_offset=max\\_frags\)](#)

### Protected Attributes

- [BufferFragment fragments \[max\\_frags\]](#)
- [BufferState \\* buffer\\_states \[max\\_frags\]](#)
- [ChainClass \\* next](#)
- uint32 [num.fragments](#)
- uint32 [length](#)

```
template<class ChainClass, uint32 max_frags> class BufFragGroup< ChainClass, max_frags >
```

### 7.10.1 Constructor & Destructor Documentation

**7.10.1.1** `template<class ChainClass, uint32 max_frags> BufFragGroup< ChainClass, max_frags >::BufFragGroup () [inline]`

**7.10.1.2** `template<class ChainClass, uint32 max_frags> virtual BufFragGroup< ChainClass, max_frags >::~BufFragGroup () [inline, virtual]`

### 7.10.2 Member Function Documentation

**7.10.2.1** `template<class ChainClass, uint32 max_frags> BufFragStatusClass::status\_t BufFragGroup< ChainClass, max_frags >::AddFragment (const BufferFragment & frag, BufferState * in_buffer_state, int32 location_offset = max_frags) [inline, protected]`

**7.10.2.2** `template<class ChainClass, uint32 max_frags> void BufFragGroup< ChainClass, max_frags >::AppendNext (ChainClass * next_ptr) [inline]`

**7.10.2.3** `template<class ChainClass, uint32 max_frags> virtual void BufFragGroup< ChainClass, max_frags >::Clear () [inline, protected, virtual]`

Reimplemented in [MediaData< ChainClass, max\\_frags, local\\_bufsize >](#).

**7.10.2.4** template<class ChainClass, uint32 max\_frags> uint32 BufFragGroup< ChainClass, max\_frags >::GetLength () const [inline]

**7.10.2.5** template<class ChainClass, uint32 max\_frags> int32 BufFragGroup< ChainClass, max\_frags >::GetMaxFrags () const [inline]

**7.10.2.6** template<class ChainClass, uint32 max\_frags> ChainClass\* BufFragGroup< ChainClass, max\_frags >::GetNext () const [inline]

**7.10.2.7** template<class ChainClass, uint32 max\_frags> int32 BufFragGroup< ChainClass, max\_frags >::GetNumFrags () const [inline]

### 7.10.3 Field Documentation

**7.10.3.1** template<class ChainClass, uint32 max\_frags> BufferState\* BufFragGroup< ChainClass, max\_frags >::buffer\_states[max\_frags] [protected]

**7.10.3.2** template<class ChainClass, uint32 max\_frags> BufferFragment BufFragGroup< ChainClass, max\_frags >::fragments[max\_frags] [protected]

**7.10.3.3** template<class ChainClass, uint32 max\_frags> uint32 BufFragGroup< ChainClass, max\_frags >::length [protected]

**7.10.3.4** template<class ChainClass, uint32 max\_frags> ChainClass\* BufFragGroup< ChainClass, max\_frags >::next [protected]

**7.10.3.5** template<class ChainClass, uint32 max\_frags> uint32 BufFragGroup< ChainClass, max\_frags >::num\_fragments [protected]


The documentation for this class was generated from the following file:

- [oscl\\_media\\_data.h](#)

## 7.11 BufFragStatusClass Class Reference

```
#include <oscl_media_status.h>
```

Inheritance diagram for BufFragStatusClass::



### Public Types

- enum `status_t` { `BFG_SUCCESS` = 0, `TOO_MANY_FRAGS` = 1, `NOT_ENOUGH_SPACE` = 2, `EMPTY_FRAGMENT` = 3, `NULL_INPUT` = 4, `FIXED_FRAG_LOC_FULL` = 5, `INTERNAL_ERROR`, `INVALID_ID` }

#### 7.11.1 Member Enumeration Documentation

##### 7.11.1.1 enum BufFragStatusClass::status\_t

Enumeration values:

`BFG_SUCCESS`  
`TOO_MANY_FRAGS`  
`NOT_ENOUGH_SPACE`  
`EMPTY_FRAGMENT`  
`NULL_INPUT`  
`FIXED_FRAG_LOC_FULL`  
`INTERNAL_ERROR`  
`INVALID_ID`


The documentation for this class was generated from the following file:

- [oscl\\_media\\_status.h](#)

## 7.12 CallbackTimer< Alloc > Class Template Reference

```
#include <oscl_timer.h>
```

Inheritance diagram for CallbackTimer< Alloc >::



### Public Methods

- [CallbackTimer \(CallbackTimerObserver &aContainer, const char \\*name, int32 aPriority=OsclActiveObject::EPriorityNominal\)](#)
- [~CallbackTimer \(\)](#)
- [void Run \(\)](#)

```
template<class Alloc> class CallbackTimer< Alloc >
```

#### 7.12.1 Constructor & Destructor Documentation

**7.12.1.1 template<class Alloc> CallbackTimer< Alloc >::CallbackTimer (CallbackTimerObserver & aContainer, const char \* name, int32 aPriority = OsclActiveObject::EPriorityNominal) [inline]**

**7.12.1.2 template<class Alloc> CallbackTimer< Alloc >::~CallbackTimer () [inline]**

#### 7.12.2 Member Function Documentation

**7.12.2.1 template<class Alloc> void CallbackTimer< Alloc >::Run () [inline, virtual]**

Handles an active object's request completion event.

A derived class must provide an implementation to handle the completed request. If appropriate, it may issue another request.

The function is called by the active scheduler when a request completion event occurs, i.e. after the active scheduler's WaitForAnyRequest() function completes.

Before calling this active object's [Run\(\)](#) function, the active scheduler has:

1. decided that this is the highest priority active object with a completed request
2. marked this active object's request as complete (i.e. the request is no longer outstanding)

[Run\(\)](#) runs under a trap harness in the active scheduler. If it leaves, then the active scheduler calls ExecError() to handle the leave.

Note that once the active scheduler's Start() function has been called, all user code is run under one of the program's active object's [Run\(\)](#) or [RunError\(\)](#) functions.

Implements [PVActiveBase](#).


The documentation for this class was generated from the following file:

- [oscl\\_timer.h](#)

## 7.13 CallbackTimerObserver Class Reference

```
#include <oscl_timer.h>
```

Inheritance diagram for CallbackTimerObserver::



### Public Methods

- virtual void [TimerBaseElapsed \(\)=0](#)
- virtual [~CallbackTimerObserver \(\)](#)

#### 7.13.1 Constructor & Destructor Documentation

**7.13.1.1 virtual CallbackTimerObserver::~CallbackTimerObserver () [inline, virtual]**

#### 7.13.2 Member Function Documentation

**7.13.2.1 virtual void CallbackTimerObserver::TimerBaseElapsed () [pure virtual]**

Implemented in [OsclTimer< Alloc >](#).

The documentation for this class was generated from the following file:

- [oscl\\_timer.h](#)

## 7.14 CFastRep Class Reference

```
#include <oscl_string_rep.h>
```

### Public Methods

- [CFastRep \(\)](#)
- OSCL\_IMPORT\_REF void [set\\_w](#) (char \*cp, uint32 len, uint32 maxlen)
- OSCL\_IMPORT\_REF void [set\\_w \(oscl\\_wchar](#) \*cp, uint32 len, uint32 maxlen)
- OSCL\_IMPORT\_REF void [set\\_r](#) (const char \*cp, uint32 len)
- OSCL\_IMPORT\_REF void [set\\_r \(const oscl\\_wchar](#) \*cp, uint32 len)
- OSCL\_IMPORT\_REF void [append](#) (const char \*cp, uint32 len)
- OSCL\_IMPORT\_REF void [append \(const oscl\\_wchar](#) \*cp, uint32 len)

### Data Fields

- uint32 [maxsize](#)
- uint32 [size](#)
- [OsclAny](#) \* [buffer](#)
- bool [writable](#)
- bool [overwrite](#)

#### 7.14.1 Detailed Description

For internal use only– fast string representation

## 7.14.2 Constructor & Destructor Documentation

7.14.2.1 `CFastRep::CFastRep () [inline]`

## 7.14.3 Member Function Documentation

7.14.3.1 `OSCL_IMPORT_REF void CFastRep::append (const oscl_wchar * cp, uint32 len)`

7.14.3.2 `OSCL_IMPORT_REF void CFastRep::append (const char * cp, uint32 len)`

7.14.3.3 `OSCL_IMPORT_REF void CFastRep::set_r (const oscl_wchar * cp, uint32 len)`

7.14.3.4 `OSCL_IMPORT_REF void CFastRep::set_r (const char * cp, uint32 len)`

7.14.3.5 `OSCL_IMPORT_REF void CFastRep::set_w (oscl_wchar * cp, uint32 len, uint32 maxlen)`

7.14.3.6 `OSCL_IMPORT_REF void CFastRep::set_w (char * cp, uint32 len, uint32 maxlen)`

## 7.14.4 Field Documentation

7.14.4.1 `OsclAny* CFastRep::buffer`

7.14.4.2 `uint32 CFastRep::maxsize`

7.14.4.3 `bool CFastRep::overwrite`

7.14.4.4 `uint32 CFastRep::size`

7.14.4.5 `bool CFastRep::writable`

The documentation for this class was generated from the following file:

- `oscl_string_rep.h`

## 7.15 CHeapRep Class Reference

```
#include <oscl_string_rep.h>
```

### Public Methods

- [CHeapRep \(\)](#)
- OSCL\_IMPORT\_REF bool [set](#) (uint32, const char \*, [Oscl\\_DefAlloc](#) &)
- OSCL\_IMPORT\_REF bool [set](#) (uint32, const [oscl\\_wchar](#) \*, [Oscl\\_DefAlloc](#) &)
- OSCL\_IMPORT\_REF bool [append](#) (uint32, const char \*, uint32, const char \*, [Oscl\\_DefAlloc](#) &)
- OSCL\_IMPORT\_REF bool [append](#) (uint32, const [oscl\\_wchar](#) \*, uint32, const [oscl\\_wchar](#) \*, [Oscl\\_DefAlloc](#) &)
- OSCL\_IMPORT\_REF void [add\\_ref](#) ()
- OSCL\_IMPORT\_REF void [remove\\_ref](#) ([Oscl\\_DefAlloc](#) &)

### Static Public Methods

- OSCL\_IMPORT\_REF void [set\\_rep](#) (CHheapRep \*&, [Oscl\\_DefAlloc](#) &, const char \*, uint32)
- OSCL\_IMPORT\_REF void [set\\_rep](#) (CHheapRep \*&, [Oscl\\_DefAlloc](#) &, const [oscl\\_wchar](#) \*, uint32)
- OSCL\_IMPORT\_REF void [append\\_rep](#) (CHheapRep \*&, [Oscl\\_DefAlloc](#) &, const char \*, uint32)
- OSCL\_IMPORT\_REF void [append\\_rep](#) (CHheapRep \*&, [Oscl\\_DefAlloc](#) &, const [oscl\\_wchar](#) \*, uint32)
- OSCL\_IMPORT\_REF void [assign](#) (CHheapRep \*&, CHheapRep \*, [Oscl\\_DefAlloc](#) &)

### Data Fields

- uint32 [refcount](#)
- [OsclAny](#) \* [buffer](#)
- uint32 [maxsize](#)
- uint32 [size](#)

#### 7.15.1 Detailed Description

For internal use only– heap string representation

## 7.15.2 Constructor & Destructor Documentation

7.15.2.1 `OSCL_IMPORT_REF CHeapRep::CHeapRep () [inline]`

## 7.15.3 Member Function Documentation

7.15.3.1 `OSCL_IMPORT_REF void CHeapRep::add_ref ()`

7.15.3.2 `OSCL_IMPORT_REF bool CHeapRep::append (uint32, const oscl_wchar *, uint32, const oscl_wchar *, Oscl_DefAlloc &)`

7.15.3.3 `OSCL_IMPORT_REF bool CHeapRep::append (uint32, const char *, uint32, const char *, Oscl_DefAlloc &)`

7.15.3.4 `OSCL_IMPORT_REF void CHeapRep::append_rep (CHeapRep *&, Oscl_DefAlloc &, const oscl_wchar *, uint32) [static]`

7.15.3.5 `OSCL_IMPORT_REF void CHeapRep::append_rep (CHeapRep *&, Oscl_DefAlloc &, const char *, uint32) [static]`

7.15.3.6 `OSCL_IMPORT_REF void CHeapRep::assign (CHeapRep *&, CHeapRep *, Oscl_DefAlloc &) [static]`

7.15.3.7 `OSCL_IMPORT_REF void CHeapRep::remove_ref (Oscl_DefAlloc &)`

7.15.3.8 `OSCL_IMPORT_REF bool CHeapRep::set (uint32, const oscl_wchar *, Oscl_DefAlloc &)`

7.15.3.9 `OSCL_IMPORT_REF bool CHeapRep::set (uint32, const char *, Oscl_DefAlloc &)`

7.15.3.10 `OSCL_IMPORT_REF void CHeapRep::set_rep (CHeapRep *&, Oscl_DefAlloc &, const oscl_wchar *, uint32) [static]`

7.15.3.11 `OSCL_IMPORT_REF void CHeapRep::set_rep (CHeapRep *&, Oscl_DefAlloc &, const char *, uint32) [static]`

## 7.15.4 Field Documentation

7.15.4.1 `OsclAny* CHeapRep::buffer`

7.15.4.2 `uint32 CHeapRep::maxsize`

7.15.4.3 `uint32 CHeapRep::refcount`

7.15.4.4 `uint32 CHeapRep::size`


The documentation for this class was generated from the following file:

- `oscl_string_rep.h`

## 7.16 ConnectParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for ConnectParam::



### Public Methods

- [ConnectParam \(OsclNetworkAddress &anAddr\)](#)

### Data Fields

- [OsclNetworkAddress iAddr](#)

#### 7.16.1 Constructor & Destructor Documentation

**7.16.1.1 ConnectParam::ConnectParam (OsclNetworkAddress & *anAddr*) [inline]**

#### 7.16.2 Field Documentation

**7.16.2.1 OsclNetworkAddress ConnectParam::iAddr**

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.17 CStackRep Class Reference

```
#include <oscl_string_rep.h>
```

### Public Methods

- [CStackRep \(\)](#)
- [OSCL\\_IMPORT\\_REF void set \(const char \\*cp, uint32 len\)](#)
- [OSCL\\_IMPORT\\_REF void set \(const oscl\\_wchar \\*cp, uint32 len\)](#)
- [OSCL\\_IMPORT\\_REF void append \(const char \\*cp, uint32 len\)](#)
- [OSCL\\_IMPORT\\_REF void append \(const oscl\\_wchar \\*cp, uint32 len\)](#)

### Data Fields

- [uint32 maxsize](#)
- [uint32 size](#)
- [OsclAny \\* buffer](#)

#### 7.17.1 Detailed Description

For internal use only– stack string representation

#### 7.17.2 Constructor & Destructor Documentation

##### 7.17.2.1 CStackRep::CStackRep () [inline]

#### 7.17.3 Member Function Documentation

##### 7.17.3.1 OSCL\_IMPORT\_REF void CStackRep::append (const oscl\_wchar \* cp, uint32 len)

##### 7.17.3.2 OSCL\_IMPORT\_REF void CStackRep::append (const char \* cp, uint32 len)

##### 7.17.3.3 OSCL\_IMPORT\_REF void CStackRep::set (const oscl\_wchar \* cp, uint32 len)

##### 7.17.3.4 OSCL\_IMPORT\_REF void CStackRep::set (const char \* cp, uint32 len)

#### 7.17.4 Field Documentation

##### 7.17.4.1 OsclAny\* CStackRep::buffer

##### 7.17.4.2 uint32 CStackRep::maxsize

##### 7.17.4.3 uint32 CStackRep::size


The documentation for this class was generated from the following file:

- [oscl\\_string\\_rep.h](#)

## 7.18 DNSRequestParam Class Reference

```
#include <oscl_dns_param.h>
```

Inheritance diagram for DNSRequestParam::



### Public Methods

- virtual ~DNSRequestParam ()
- void RemoveRef ()
- void InThread ()
- virtual void Destroy ()=0

### Data Fields

- TPVDNSFx<sub>n</sub> iFx<sub>n</sub>
- OsclDNSRequest \* iDNSRequest

### Protected Methods

- DNSRequestParam (TPVDNSFx<sub>n</sub> aFx<sub>n</sub>)

### Protected Attributes

- uint32 iRefCount

#### 7.18.1 Constructor & Destructor Documentation

7.18.1.1 virtual DNSRequestParam::~DNSRequestParam () [inline, virtual]

7.18.1.2 DNSRequestParam::DNSRequestParam (TPVDNSFx<sub>n</sub> aFx<sub>n</sub>) [protected]

#### 7.18.2 Member Function Documentation

7.18.2.1 virtual void DNSRequestParam::Destroy () [pure virtual]

Implemented in [GetHostByNameParam](#).

**7.18.2.2 void DNSRequestParam::InThread ()**

**7.18.2.3 void DNSRequestParam::RemoveRef ()**

### **7.18.3 Field Documentation**

**7.18.3.1 OsclDNSRequest\* DNSRequestParam::iDNSRequest**

**7.18.3.2 TPVDNSFxn DNSRequestParam::iFxn**

**7.18.3.3 uint32 DNSRequestParam::iRefCount [protected]**


The documentation for this class was generated from the following file:

- [oscl\\_dns\\_param.h](#)

## 7.19 GetHostByNameParam Class Reference

```
#include <oscl_dns_param.h>
```

Inheritance diagram for GetHostByNameParam::



### Public Types

- enum { `addressListCapacity` = 10 }

### Public Methods

- void `Destroy` ()
- `~GetHostByNameParam` ()
- void `PersistHostAddress` (const `OsclNetworkAddress` &`addr`)
- bool `canPersistMoreHostAddresses` ()

### Static Public Methods

- `GetHostByNameParam * Create` (const char \*`name`, `OsclNetworkAddress` \*&`addr`, `Oscl_Vector<OsclNetworkAddress, OsclMemAllocator>` \*`aAddressList`)

### Data Fields

- `char * iName`
- `OsclNetworkAddress * iAddr`
- `Oscl_Vector<OsclNetworkAddress, OsclMemAllocator> * iAddressList`

#### 7.19.1 Member Enumeration Documentation

##### 7.19.1.1 anonymous enum

Enumeration values:

`addressListCapacity`

## 7.19.2 Constructor & Destructor Documentation

7.19.2.1 `GetHostByNameParam::~GetHostByNameParam ()`

## 7.19.3 Member Function Documentation

7.19.3.1 `bool GetHostByNameParam::canPersistMoreHostAddresses () [inline]`

7.19.3.2 `GetHostByNameParam* GetHostByNameParam::Create (const char * name, OsclNetworkAddress *& addr, Oscl_Vector< OsclNetworkAddress, OsclMemAllocator > * aAddressList) [static]`

7.19.3.3 `void GetHostByNameParam::Destroy () [virtual]`

Implements [DNSRequestParam](#).

7.19.3.4 `void GetHostByNameParam::PersistHostAddress (const OsclNetworkAddress & addr) [inline]`

## 7.19.4 Field Documentation

7.19.4.1 `OsclNetworkAddress* GetHostByNameParam::iAddr`

7.19.4.2 `Oscl_Vector<OsclNetworkAddress, OsclMemAllocator>* GetHostByNameParam::i-AddressList`

7.19.4.3 `char* GetHostByNameParam::iName`


The documentation for this class was generated from the following file:

- [oscl\\_dns\\_param.h](#)

## 7.20 HeapBase Class Reference

```
#include <oscl_mem.h>
```

Inheritance diagram for HeapBase::



### Public Methods

- [HeapBase \(\)](#)
- virtual [~HeapBase \(\)](#)

#### 7.20.1 Detailed Description

HeapBase is the base class for all classes that allocates memory.

HeapBase has overloaded new and delete operators.

Derived from [\\_OsclHeapBase](#) providing CBase\* alike pointer and virtual destructor for cleanupstack to Push and Pop for cleanup when leave occurs.

HeapBase has a virtual destructor which calls the destructor of all the derived classes.

## 7.20.2 Constructor & Destructor Documentation

**7.20.2.1 `HeapBase::HeapBase () [inline]`**

**7.20.2.2 `virtual HeapBase::~HeapBase () [inline, virtual]`**

The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.21 internalLeave Class Reference

```
#include <oscl_error_imp_cppexceptions.h>
```

### Data Fields

- int a

#### 7.21.1 Field Documentation

##### 7.21.1.1 int internalLeave::a

The documentation for this class was generated from the following file:

- [oscl\\_error\\_imp\\_cppexceptions.h](#)

## 7.22 LinkedListElement< LLClass > Class Template Reference

```
#include <oscl_linked_list.h>
```

### Public Methods

- [LinkedListElement \(LLClass in\\_data\)](#)

### Data Fields

- [LinkedListElement< LLClass > \\* next](#)
- [LLClass data](#)

#### 7.22.1 Detailed Description

```
template<class LLClass> class LinkedListElement< LLClass >
```

Linked List Element Class

#### 7.22.2 Constructor & Destructor Documentation

```
7.22.2.1 template<class LLClass> LinkedListElement< LLClass >::LinkedListElement  
(LLClass in_data) [inline]
```

#### 7.22.3 Field Documentation

```
7.22.3.1 template<class LLClass> LLClass LinkedListElement< LLClass >::data
```

```
7.22.3.2 template<class LLClass> LinkedListElement<LLClass>*>* LinkedListElement<  
LLClass >::next
```


The documentation for this class was generated from the following file:

- [oscl\\_linked\\_list.h](#)

## 7.23 ListenParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for ListenParam::



### Public Methods

- [ListenParam \(uint32 aSize\)](#)

### Data Fields

- uint32 [iQSize](#)

#### 7.23.1 Constructor & Destructor Documentation

7.23.1.1 [ListenParam::ListenParam \(uint32 aSize\) \[inline\]](#)

#### 7.23.2 Field Documentation

##### 7.23.2.1 [uint32 ListenParam::iQSize](#)


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.24 MediaData< ChainClass, max\_frags, local\_bufsize > Class Template Reference

```
#include <oscl_media_data.h>
```

Inheritance diagram for MediaData< ChainClass, max\_frags, local\_bufsize >::



### Public Methods

- [MediaData \(\)](#)
- virtual [~MediaData \(\)](#)
- uint32 [GetLocalBufsize \(\) const](#)
- [MediaTimestamp GetTimestamp \(\) const](#)
- void [SetTimestamp \(MediaTimestamp in\\_timestamp\)](#)
- uint32 [GetAvailableBufferSize \(\) const](#)
- [MediaStatusClass::status\\_t GetLocalFragment \(BufferFragment &fragment\)](#)
- virtual void [Clear \(\)](#)
- bool [IsLocalData \(const OsclMemoryFragment &frag\) const](#)
- int [GetMediaSize \(\) const](#)
- [BufferFragment \\* GetMediaFragment \(const uint32 idx\)](#)
- uint32 [GetNumMediaFrags \(const uint32 idx\) const](#)

### Protected Methods

- [MediaStatusClass::status\\_t AddLocalFragment \(const BufferFragment &frag, int32 location\\_offset\)](#)

### Protected Attributes

- [MediaTimestamp timestamp](#)
- uint8 [localbuf \[local\\_bufsize\]](#)
- uint32 [available\\_localbuf](#)
- int [num\\_reserved\\_fragments](#)

template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> class MediaData< ChainClass, max\_frags, local\_bufsize >

### 7.24.1 Constructor & Destructor Documentation

- 7.24.1.1 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> MediaData< ChainClass, max\_frags, local\_bufsize >::MediaData () [inline]
- 7.24.1.2 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> virtual MediaData< ChainClass, max\_frags, local\_bufsize >::~MediaData () [inline, virtual]

### 7.24.2 Member Function Documentation

- 7.24.2.1 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> MediaStatusClass::status\_t MediaData< ChainClass, max\_frags, local\_bufsize >::AddLocalFragment (const BufferFragment &frag, int32 location\_offset) [inline, protected]
- 7.24.2.2 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> virtual void MediaData< ChainClass, max\_frags, local\_bufsize >::Clear () [inline, virtual]

Reimplemented from [BufFragGroup< ChainClass, max\\_frags >](#).

- 7.24.2.3 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> uint32 MediaData<ChainClass, max\_frags, local\_bufsize >::GetAvailableBufferSize () const [inline]
- 7.24.2.4 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> uint32 MediaData<ChainClass, max\_frags, local\_bufsize >::GetLocalBufsize () const [inline]
- 7.24.2.5 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize>  
**MediaStatusClass::status\_t** MediaData<ChainClass, max\_frags, local\_bufsize >::GetLocalFragment (**BufferFragment** & *fragment*) [inline]
- 7.24.2.6 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> **BufferFragment\*** MediaData<ChainClass, max\_frags, local\_bufsize >::GetMediaFragment (const uint32 *idx*) [inline]
- 7.24.2.7 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> int MediaData<ChainClass, max\_frags, local\_bufsize >::GetMediaSize () const [inline]
- 7.24.2.8 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> uint32 MediaData<ChainClass, max\_frags, local\_bufsize >::GetNumMediaFrags (const uint32 *idx*) const [inline]
- 7.24.2.9 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> **MediaTimestamp** MediaData<ChainClass, max\_frags, local\_bufsize >::GetTimestamp () const [inline]
- 7.24.2.10 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> bool MediaData<ChainClass, max\_frags, local\_bufsize >::IsLocalData (const **OsclMemoryFragment** & *frag*) const [inline]
- 7.24.2.11 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> void MediaData<ChainClass, max\_frags, local\_bufsize >::SetTimestamp (**MediaTimestamp** *in\_timestamp*) [inline]

### 7.24.3 Field Documentation

- 7.24.3.1 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> uint32 MediaData<ChainClass, max\_frags, local\_bufsize >::available\_localbuf [protected]
- 7.24.3.2 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> uint8 MediaData<ChainClass, max\_frags, local\_bufsize >::localbuf[local\_bufsize] [protected]
- 7.24.3.3 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> int MediaData<ChainClass, max\_frags, local\_bufsize >::num\_reserved.fragments [protected]
- 7.24.3.4 template<class ChainClass, uint32 max\_frags, uint32 local\_bufsize> **MediaTimestamp** MediaData<ChainClass, max\_frags, local\_bufsize >::timestamp [protected]


The documentation for this class was generated from the following file:

- [oscl\\_media\\_data.h](#)

## 7.25 MediaStatusClass Class Reference

```
#include <oscl_media_status.h>
```

Inheritance diagram for MediaStatusClass::



The documentation for this class was generated from the following file:

- [oscl\\_media\\_status.h](#)

## 7.26 MemAllocator< T > Class Template Reference

```
#include <oscl_media_data.h>
```

### Public Types

- `typedef T * pointer`

### Public Methods

- `virtual pointer allocate (void *hint=0, const int num_reserved_frags=1)=0`
- `virtual void deallocate (pointer p)=0`
- `virtual ~MemAllocator ()`

```
template<class T> class MemAllocator< T >
```

#### 7.26.1 Member Typedef Documentation

##### 7.26.1.1 template<class T> `typedef T* MemAllocator< T >::pointer`

#### 7.26.2 Constructor & Destructor Documentation

##### 7.26.2.1 template<class T> `virtual MemAllocator< T >::~MemAllocator () [inline, virtual]`

#### 7.26.3 Member Function Documentation

##### 7.26.3.1 template<class T> `virtual pointer MemAllocator< T >::allocate (void * hint = 0, const int num_reserved_frags = 1) [pure virtual]`

##### 7.26.3.2 template<class T> `virtual void MemAllocator< T >::deallocate (pointer p) [pure virtual]`

The documentation for this class was generated from the following file:

- [oscl\\_media\\_data.h](#)

## 7.27 MM\_AllocBlockFence Struct Reference

```
#include <oscl_mem_audit_internals.h>
```

### Public Methods

- [MM\\_AllocBlockFence \(\)](#)
- [void fill\\_fence \(\)](#)
- [bool check\\_fence \(\)](#)

### Data Fields

- [uint8 pad \[COMPUTE\\_MEM\\_ALIGN\\_SIZE\(sizeof\(MM\\_AllocBlockHdr\), MIN\\_FENCE\\_SIZE, MEM\\_ALIGN\\_SIZE\)\]](#)

#### 7.27.1 Constructor & Destructor Documentation

[7.27.1.1 MM\\_AllocBlockFence::MM\\_AllocBlockFence \(\) \[inline\]](#)

#### 7.27.2 Member Function Documentation

[7.27.2.1 bool MM\\_AllocBlockFence::check\\_fence \(\) \[inline\]](#)

[7.27.2.2 void MM\\_AllocBlockFence::fill\\_fence \(\) \[inline\]](#)

#### 7.27.3 Field Documentation

[7.27.3.1 uint8 MM\\_AllocBlockFence::pad\[COMPUTE\\_MEM\\_ALIGN\\_SIZE\(sizeof\(MM\\_AllocBlockHdr\), MIN\\_FENCE\\_SIZE, MEM\\_ALIGN\\_SIZE\)\]](#)

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit\\_internals.h](#)

## 7.28 MM\_AllocBlockHdr Struct Reference

```
#include <oscl_mem_audit_internals.h>
```

### Public Methods

- bool [isAllocNodePtr \(\)](#)
- void [setAllocNodeFlag \(\)](#)
- [MM\\_AllocBlockHdr \(\)](#)
- [MM\\_AllocBlockHdr \(void \\*ptr, uint32 inSize\)](#)

### Data Fields

- void \* [pNode](#)
- uint32 [size](#)
- void \* [pRootNode](#)
- uint32 [pad](#)

### Static Public Attributes

- const uint32 [ALLOC\\_NODE\\_FLAG](#) = 0x80000000

#### 7.28.1 Constructor & Destructor Documentation

[7.28.1.1 MM\\_AllocBlockHdr::MM\\_AllocBlockHdr \(\) \[inline\]](#)

[7.28.1.2 MM\\_AllocBlockHdr::MM\\_AllocBlockHdr \(void \\*ptr, uint32 inSize\) \[inline\]](#)

#### 7.28.2 Member Function Documentation

[7.28.2.1 bool MM\\_AllocBlockHdr::isAllocNodePtr \(\) \[inline\]](#)

[7.28.2.2 void MM\\_AllocBlockHdr::setAllocNodeFlag \(\) \[inline\]](#)

#### 7.28.3 Field Documentation

[7.28.3.1 uint32 MM\\_AllocBlockHdr::pad](#)

[7.28.3.2 void\\* MM\\_AllocBlockHdr::pNode](#)

[7.28.3.3 void\\* MM\\_AllocBlockHdr::pRootNode](#)

[7.28.3.4 uint32 MM\\_AllocBlockHdr::size](#)

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit\\_internals.h](#)

## 7.29 MM\_AllocInfo Struct Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [MM\\_AllocInfo \(\)](#)
- [~MM\\_AllocInfo \(\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size, MM\\_AllocInfo \\*ptr\)](#)
- [void operator delete \(void \\*ptr\) throw \(\)](#)

### Data Fields

- [uint32 allocNum](#)
- [char \\* pFileName](#)
- [uint32 lineNo](#)
- [uint32 size](#)
- [void \\* pMemBlock](#)
- [OsclMemStatsNode \\* pStatsNode](#)
- [bool bSetFailure](#)

## 7.29.1 Constructor & Destructor Documentation

7.29.1.1 `MM_AllocInfo::MM_AllocInfo () [inline]`

7.29.1.2 `MM_AllocInfo::~MM_AllocInfo () [inline]`

## 7.29.2 Member Function Documentation

7.29.2.1 `void MM_AllocInfo::operator delete (void *ptr) throw () [inline]`

7.29.2.2 `void* MM_AllocInfo::operator new (oscl_memsize_t size, MM_AllocInfo *ptr) [inline]`

7.29.2.3 `void* MM_AllocInfo::operator new (oscl_memsize_t size) [inline]`

## 7.29.3 Field Documentation

7.29.3.1 `uint32 MM_AllocInfo::allocNum`

7.29.3.2 `bool MM_AllocInfo::bSetFailure`

7.29.3.3 `uint32 MM_AllocInfo::lineNo`

7.29.3.4 `char* MM_AllocInfo::pFileName`

7.29.3.5 `void* MM_AllocInfo::pMemBlock`

7.29.3.6 `OsclMemStatsNode* MM_AllocInfo::pStatsNode`

7.29.3.7 `uint32 MM_AllocInfo::size`

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.30 MM\_AllocNode Struct Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [MM\\_AllocNode \(\)](#)
- [~MM\\_AllocNode \(\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size, MM\\_AllocNode \\*ptr\)](#)
- [void operator delete \(void \\*ptr\) throw \(\)](#)

### Data Fields

- [MM\\_AllocInfo \\* pAllocInfo](#)
- [MM\\_AllocNode \\* pPrev](#)
- [MM\\_AllocNode \\* pNext](#)

#### 7.30.1 Constructor & Destructor Documentation

[7.30.1.1 MM\\_AllocNode::MM\\_AllocNode \(\) \[inline\]](#)

[7.30.1.2 MM\\_AllocNode::~MM\\_AllocNode \(\) \[inline\]](#)

#### 7.30.2 Member Function Documentation

[7.30.2.1 void MM\\_AllocNode::operator delete \(void \\*ptr\) throw \(\) \[inline\]](#)

[7.30.2.2 void\\* MM\\_AllocNode::operator new \(oscl\\_memsize\\_t size, MM\\_AllocNode \\*ptr\) \[inline\]](#)

[7.30.2.3 void\\* MM\\_AllocNode::operator new \(oscl\\_memsize\\_t size\) \[inline\]](#)

#### 7.30.3 Field Documentation

[7.30.3.1 MM\\_AllocInfo\\* MM\\_AllocNode::pAllocInfo](#)

[7.30.3.2 MM\\_AllocNode\\* MM\\_AllocNode::pNext](#)

[7.30.3.3 MM\\_AllocNode\\* MM\\_AllocNode::pPrev](#)

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.31 MM\_AllocQueryInfo Struct Reference

```
#include <oscl_mem_audit.h>
```

### Data Fields

- uint32 [allocNum](#)
- char [fileName](#) [MM\_ALLOC\_MAX\_QUERY\_FILENAME\_LEN]
- uint32 [lineNo](#)
- uint32 [size](#)
- const void \* [pMemBlock](#)
- char [tag](#) [MM\_ALLOC\_MAX\_QUERY\_TAG\_LEN]

#### 7.31.1 Field Documentation

**7.31.1.1 uint32 MM\_AllocQueryInfo::allocNum**

**7.31.1.2 char MM\_AllocQueryInfo::fileName[MM\_ALLOC\_MAX\_QUERY\_FILENAME\_LEN]**

**7.31.1.3 uint32 MM\_AllocQueryInfo::lineNo**

**7.31.1.4 const void\* MM\_AllocQueryInfo::pMemBlock**

**7.31.1.5 uint32 MM\_AllocQueryInfo::size**

**7.31.1.6 char MM\_AllocQueryInfo::tag[MM\_ALLOC\_MAX\_QUERY\_TAG\_LEN]**

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.32 MM\_Audit\_Imp Class Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [MM\\_Audit\\_Imp \(\)](#)
- [~MM\\_Audit\\_Imp \(\)](#)
- [OSCL\\_IMPORT\\_REF void \\* MM\\_allocate \(const OsclMemStatsNode \\*statsNode, uint32 sizeIn, const char \\*pFileName, uint32 lineNumber, bool allocNodeTracking=false\)](#)
- [OSCL\\_IMPORT\\_REF bool MM\\_deallocate \(void \\*pMemBlockIn\)](#)
- [OSCL\\_IMPORT\\_REF MM\\_Stats\\_t \\* MM\\_GetStats \(const char \\*const tagIn\)](#)
- [OSCL\\_IMPORT\\_REF uint32 MM\\_GetStatsInDepth \(const char \\*tagIn, MM\\_Stats\\_CB \\*array\\_ptr, uint32 max\\_nodes\)](#)
- [OSCL\\_IMPORT\\_REF uint32 MM\\_GetTreeNodes \(const char \\*tagIn\)](#)
- [OSCL\\_IMPORT\\_REF bool MM\\_AddTag \(const char \\*tagIn\)](#)
- [OSCL\\_IMPORT\\_REF const OsclMemStatsNode \\* MM\\_GetTagName \(const char \\*tagIn\)](#)
- [OSCL\\_IMPORT\\_REF const OsclMemStatsNode \\* MM\\_GetExistingTag \(const char \\*tagIn\)](#)
- [OSCL\\_IMPORT\\_REF const OsclMemStatsNode \\* MM\\_GetRootNode \(\)](#)
- [OSCL\\_IMPORT\\_REF MM\\_AllocQueryInfo \\* MM\\_CreateAllocNodeInfo \(uint32 max\\_array\\_size\)](#)
- [OSCL\\_IMPORT\\_REF void MM\\_ReleaseAllocNodeInfo \(MM\\_AllocQueryInfo \\*info\)](#)
- [OSCL\\_IMPORT\\_REF uint32 MM\\_GetAllocNodeInfo \(MM\\_AllocQueryInfo \\*output\\_array, uint32 max\\_array\\_size, uint32 offset\)](#)
- [OSCL\\_IMPORT\\_REF bool MM\\_Validate \(const void \\*ptrIn\)](#)
- [uint32 MM\\_GetAllocNo \(void\)](#)
- [void MM\\_GetOverheadStats \(MM\\_AuditOverheadStats &stats\)](#)
- [uint32 MM\\_GetNumAllocNodes \(\)](#)
- [uint32 MM\\_GetMode \(void\)](#)
- [uint8 MM\\_GetPrefillPattern \(void\)](#)
- [uint32 MM\\_GetPostfillPattern \(void\)](#)
- [OSCL\\_IMPORT\\_REF void MM\\_SetMode \(uint32 inMode\)](#)
- [OSCL\\_IMPORT\\_REF void MM\\_SetPrefillPattern \(uint8 pattern\)](#)
- [OSCL\\_IMPORT\\_REF void MM\\_SetPostfillPattern \(uint8 pattern\)](#)
- [OSCL\\_IMPORT\\_REF void MM\\_SetTagLevel \(uint32 level\)](#)
- [OSCL\\_IMPORT\\_REF bool MM\\_SetFailurePoint \(const char \\*tagIn, uint32 alloc\\_number\)](#)
- [OSCL\\_IMPORT\\_REF void MM\\_UnsetFailurePoint \(const char \\*tagIn\)](#)
- [MM\\_AllocNode \\* addAllocNode \(void \\*pMem, uint32 sizeIn, OsclMemStatsNode \\*pStatsNode, const char \\*pFileName, uint32 lineNumber\)](#)
- [OsclMemStatsNode \\* removeAllocNode \(void \\*pMemBlockIn, uint32 &size\)](#)
- [void removeALLAllocNodes \(\)](#)
- [OsclMemStatsNode \\* createStatsNode \(const char \\*tagIn\)](#)
- [bool updateStatsNode \(OsclMemStatsNode \\*pCurrStatsNode, const MM\\_Stats\\_t &pDelta, bool bAdd\)](#)
- [bool updateStatsNodeInFailure \(const char \\*tagIn\)](#)
- [bool updateStatsNodeInFailure \(OsclMemStatsNode \\*pStatsNode\)](#)
- [bool pruneSubtree \(OsclMemStatsNode \\*pNode\)](#)
- [bool pruneSubtree \(const char \\*tagIn\)](#)
- [void retrieveParentTag \(char \\*tag\)](#)
- [int32 retrieveParentTagLength \(const char \\*tag, int32 bound\)](#)
- [void makeValidTag \(const char \\*tagIn, MMAuditCharAutoPtr &autoPtr\)](#)

- uint32 [getTagActualSize](#) (const char \*tagIn)
- bool [isSetFailure](#) (const char \*tagIn)
- bool [isSetFailure](#) (OsclMemStatsNode \*statsNode)
- bool [validate\\_all\\_heap](#) ()

## Static Public Methods

- bool [validate](#) (void \*ptrIn)
- OsclMemAudit \* [getAuditRoot](#) (void \*ptrIn)
- uint32 [getSize](#) (void \*ptrIn)

### 7.32.1 Constructor & Destructor Documentation

#### 7.32.1.1 MM\_Audit\_Imp::MM\_Audit\_Imp ()

Constructor, create the root node in statistics table

#### 7.32.1.2 MM\_Audit\_Imp::~MM\_Audit\_Imp ()

A destructor, remove all the nodes in allocation and statistics table

### 7.32.2 Member Function Documentation

#### 7.32.2.1 MM\_AllocNode\* MM\_Audit\_Imp::addAllocNode (void \* pMem, uint32 sizeIn, OsclMemStatsNode \* pStatsNode, const char \* pFileName, uint32 lineNumber)

##### Returns:

true if operation succeeds;

#### 7.32.2.2 OsclMemStatsNode\* MM\_Audit\_Imp::createStatsNode (const char \* tagIn)

##### Returns:

true if operation succeeds;

#### 7.32.2.3 OsclMemAudit\* MM\_Audit\_Imp::getAuditRoot (void \* ptrIn) [static]

##### Returns:

audit root pointer.

#### 7.32.2.4 uint32 MM\_Audit\_Imp::getSize (void \* ptrIn) [static]

##### Returns:

original block size. leaves if bad pointer.

**7.32.2.5 uint32 MM\_Audit\_Imp::getTagActualSize (const char \* tagIn)****Returns:**

the size of the truncated tag; 0 means NO truncation

**7.32.2.6 bool MM\_Audit\_Imp::isSetFailure (OsclMemStatsNode \* statsNode)****7.32.2.7 bool MM\_Audit\_Imp::isSetFailure (const char \* tagIn)****Returns:**

true if operation succeeds;

**7.32.2.8 void MM\_Audit\_Imp::makeValidTag (const char \* tagIn, MMAuditCharAutoPtr & autoptr)****Returns:**

a valid tag; NULL will be converted into root tag

**7.32.2.9 OSCL\_IMPORT\_REF bool MM\_Audit\_Imp::MM\_AddTag (const char \* tagIn) [inline]**

API to add a node and zero out its counters; Note that this tag should be re-used

**Parameters:**

*tagIn* input tag

**Returns:**

true if operation succeeds;

**7.32.2.10 OSCL\_IMPORT\_REF void\* MM\_Audit\_Imp::MM\_allocate (const OsclMemStatsNode \* statsNode, uint32 sizeIn, const char \* pFileName, uint32 lineNumber, bool allocNodeTracking = false)**

The following are APIs t \_\_nothrow\_ / const \_\_nothrow\_

**Returns:**

the memory pointer if operation succeeds.

**7.32.2.11 OSCL\_IMPORT\_REF MM\_AllocQueryInfo\* MM\_Audit\_Imp::MM\_CreateAllocNode-Info (uint32 max\_array\_size)**

These APIs will allocate and release space for alloc node info, to be used with the MM\_GetAllocNodeInfo API.

**7.32.2.12 OSCL\_IMPORT\_REF bool MM\_Audit\_Imp::MM\_deallocate (void \* pMemBlockIn)****Returns:**

true if operation succeeds;

**7.32.2.13 uint32 MM\_Audit\_Imp::MM\_GetAllocNo (void) [inline]**

API to get the current allocation number

**Returns:**

the current allocation number

**7.32.2.14 OSCL\_IMPORT\_REF uint32 MM\_Audit\_Imp::MM\_GetAllocNodeInfo  
(MM\_AllocQueryInfo \* output\_array, uint32 max\_array\_size, uint32 offset)**

API to query the list of alloc nodes. It copies the information into the provided output array.

**Parameters:**

*output\_array* the array where the data will be written

*max\_array\_size* the max number of output array elements

*offset* the offset into the alloc node list from which the data should begin.

**Returns:**

the number of valid nodes in the output array

**7.32.2.15 OSCL\_IMPORT\_REF const OsclMemStatsNode\* MM\_Audit\_Imp::MM\_GetExisting-  
Tag (const char \* tagIn)**

API to add a node and zero out its counters; Note that this tag should be re-used

**Parameters:**

*tagIn* input tag

**Returns:**

true if operation succeeds;

**7.32.2.16 uint32 MM\_Audit\_Imp::MM\_GetMode (void) [inline]**

API to get the operating mode of the mm\_audit class.

**7.32.2.17 uint32 MM\_Audit\_Imp::MM\_GetNumAllocNodes () [inline]**

API to get the number of allocation nodes (records) for allocations that are being tracked individually.

**7.32.2.18 void MM\_Audit\_Imp::MM\_GetOverheadStats (MM\_AuditOverheadStats & stats)  
[inline]**

API to get the overhead statistics for the memory used by the mm\_audit class.

**7.32.2.19 uint32 MM\_Audit\_Imp::MM\_GetPostfillPattern (void) [inline]**

API to get the postfill pattern. The pattern is used to fill the memory before freeing it.

**7.32.2.20 uint8 MM\_Audit\_Imp::MM\_GetPrefillPattern (void) [inline]**

API to get the prefill pattern. The pattern is used to fill the memory before returning it to the caller.

**7.32.2.21 OSCL\_IMPORT\_REF const OsclMemStatsNode\* MM\_Audit\_Imp::MM\_GetRootNode () [inline]****7.32.2.22 OSCL\_IMPORT\_REF MM\_Stats\_t\* MM\_Audit\_Imp::MM\_GetStats (const char \*const tagIn)**

API to get memory statistics through context string(tag)

**Returns:**

statistics pointer if operation succeeds

**7.32.2.23 OSCL\_IMPORT\_REF uint32 MM\_Audit\_Imp::MM\_GetStatsInDepth (const char \* tagIn, MM\_Stats\_CB \* array\_ptr, uint32 max\_nodes)**

API to get memory statistics in detail through context string(tag) including its subtree

**Returns:**

statistics pointer array and actual number of nodes if operation succeeds

**7.32.2.24 OSCL\_IMPORT\_REF const OsclMemStatsNode\* MM\_Audit\_Imp::MM\_GetTagName (const char \* tagIn)**

API to add a node and zero out its counters; Note that this tag should be re-used

**Parameters:**

*tagIn* input tag

**Returns:**

pointer to [OsclMemStatsNode](#) which should be passed to MM\_allocate

**7.32.2.25 OSCL\_IMPORT\_REF uint32 MM\_Audit\_Imp::MM\_GetTreeNodes (const char \* tagIn)**

API to get the number of tree nodes including the tag node and its subtree

**Parameters:**

*tagIn* input tag

**Returns:**

the number of tree nodes ; 0 means no tag node

**7.32.2.26 OSCL\_IMPORT\_REF void MM\_Audit\_Imp::MM\_ReleaseAllocNodeInfo  
([MM\\_AllocQueryInfo](#) \* *info*)**

**7.32.2.27 OSCL\_IMPORT\_REF bool MM\_Audit\_Imp::MM\_SetFailurePoint (const char \* *tagIn*,  
uint32 *alloc\_number*)**

API to insert allocation failure deterministically according to allocation number associated with tag

**Parameters:**

*tagIn* input tag

*alloc\_number* allocation number associated with tag

**Returns:**

true if operation succeeds;

**7.32.2.28 OSCL\_IMPORT\_REF void MM\_Audit\_Imp::MM\_SetMode (uint32 *inMode*)**

API to set the operating mode of the mm\_audit class.

**7.32.2.29 OSCL\_IMPORT\_REF void MM\_Audit\_Imp::MM\_SetPostfillPattern (uint8 *pattern*)**

API to set the postfill pattern.

**7.32.2.30 OSCL\_IMPORT\_REF void MM\_Audit\_Imp::MM\_SetPrefillPattern (uint8 *pattern*)**

API to set the prefill pattern.

**7.32.2.31 OSCL\_IMPORT\_REF void MM\_Audit\_Imp::MM\_SetTagLevel (uint32 *level*)**

API to set the maximum tag level,i.e. tag level for a.b.c.d = 4

**Parameters:**

*level* input tag level to be set

**7.32.2.32 OSCL\_IMPORT\_REF void MM\_Audit\_Imp::MM\_UnsetFailurePoint (const char \*  
*tagIn*)**

API to cancel the allocation failure point associated with tag

**Parameters:**

*tagIn* input tag

**7.32.2.33 OSCL\_IMPORT\_REF bool MM\_Audit\_Imp::MM\_Validate (const void \* *ptrIn*)**

API to check the input pointer is a valid pointer to a chunk of memory

**Parameters:**

*ptrIn* input pointer to be validated

**Returns:**

true if operation succeeds;

**7.32.2.34** `bool MM_Audit_Imp::pruneSubtree (const char * tagIn)`

**7.32.2.35** `bool MM_Audit_Imp::pruneSubtree (OsclMemStatsNode * pNode)`

**Returns:**

true if operation succeeds;

**7.32.2.36** `void MM_Audit_Imp::removeALLAllocNodes ()`

**7.32.2.37** `OsclMemStatsNode* MM_Audit_Imp::removeAllocNode (void * pMemBlockIn, uint32 & size)`

**Returns:**

true if operation succeeds;

**7.32.2.38** `void MM_Audit_Imp::retrieveParentTag (char * tag)`

**7.32.2.39** `int32 MM_Audit_Imp::retrieveParentTagLength (const char * tag, int32 bound)`

**Returns:**

the length of a immediate parent tag for the input tag

**7.32.2.40** `bool MM_Audit_Imp::updateStatsNode (OsclMemStatsNode * pCurrStatsNode, const MM_Stats_t & pDelta, bool bAdd)`

**Returns:**

true if operation succeeds;

**7.32.2.41** `bool MM_Audit_Imp::updateStatsNodeInFailure (OsclMemStatsNode * pStatsNode)`

**7.32.2.42** `bool MM_Audit_Imp::updateStatsNodeInFailure (const char * tagIn)`

**Returns:**

true if operation succeeds;

**7.32.2.43** `bool MM_Audit_Imp::validate (void * ptrIn) [static]`

**Returns:**

true if operation succeeds;

**7.32.2.44 bool MM\_Audit\_Imp::validate\_all\_heap ()****Returns:**

true if operation succeeds;

The documentation for this class was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.33 MM\_AuditOverheadStats Struct Reference

```
#include <oscl_mem_audit.h>
```

### Data Fields

- uint32 [per\\_allocation\\_overhead](#)
- uint32 [stats\\_overhead](#)

#### 7.33.1 Field Documentation

**7.33.1.1 uint32 MM\_AuditOverheadStats::per\_allocation\_overhead**

**7.33.1.2 uint32 MM\_AuditOverheadStats::stats\_overhead**

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.34 MM\_FailInsertParam Struct Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [MM\\_FailInsertParam \(\)](#)
- [void reset \(\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size, MM\\_FailInsertParam \\*ptr\)](#)
- [void operator delete \(void \\*ptr\) throw \(\)](#)

### Data Fields

- [uint32 nAllocNum](#)
- [uint16 xsubi \[3\]](#)

#### 7.34.1 Constructor & Destructor Documentation

[7.34.1.1 MM\\_FailInsertParam::MM\\_FailInsertParam \(\) \[inline\]](#)

#### 7.34.2 Member Function Documentation

[7.34.2.1 void MM\\_FailInsertParam::operator delete \(void \\*ptr\) throw \(\) \[inline\]](#)

[7.34.2.2 void\\* MM\\_FailInsertParam::operator new \(oscl\\_memsize\\_t size, MM\\_FailInsertParam \\*ptr\) \[inline\]](#)

[7.34.2.3 void\\* MM\\_FailInsertParam::operator new \(oscl\\_memsize\\_t size\) \[inline\]](#)

[7.34.2.4 void MM\\_FailInsertParam::reset \(\) \[inline\]](#)

#### 7.34.3 Field Documentation

[7.34.3.1 uint32 MM\\_FailInsertParam::nAllocNum](#)

[7.34.3.2 uint16 MM\\_FailInsertParam::xsubi\[3\]](#)

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.35 MM\_Stats\_CB Struct Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [MM\\_Stats\\_CB \(\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size, MM\\_Stats\\_CB \\*ptr\)](#)
- [void operator delete \(void \\*ptr\) throw \(\)](#)

### Data Fields

- [const char \\* tag](#)
- [const MM\\_Stats\\_t \\* pStats](#)
- [uint32 num\\_child\\_nodes](#)

#### 7.35.1 Constructor & Destructor Documentation

[7.35.1.1 MM\\_Stats\\_CB::MM\\_Stats\\_CB \(\) \[inline\]](#)

#### 7.35.2 Member Function Documentation

[7.35.2.1 void MM\\_Stats\\_CB::operator delete \(void \\*ptr\) throw \(\) \[inline\]](#)

[7.35.2.2 void\\* MM\\_Stats\\_CB::operator new \(oscl\\_memsize\\_t size, MM\\_Stats\\_CB \\*ptr\) \[inline\]](#)

[7.35.2.3 void\\* MM\\_Stats\\_CB::operator new \(oscl\\_memsize\\_t size\) \[inline\]](#)

#### 7.35.3 Field Documentation

[7.35.3.1 uint32 MM\\_Stats\\_CB::num\\_child\\_nodes](#)

[7.35.3.2 const MM\\_Stats\\_t\\* MM\\_Stats\\_CB::pStats](#)

[7.35.3.3 const char\\* MM\\_Stats\\_CB::tag](#)

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.36 MM\_Stats\_t Struct Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [MM\\_Stats\\_t \(\)](#)
- [MM\\_Stats\\_t \(uint32 sizeIn\)](#)
- [void reset \(\)](#)
- [void update \(const MM\\_Stats\\_t &delta, bool add\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size, MM\\_Stats\\_t \\*ptr\)](#)
- [void operator delete \(void \\*ptr\) throw \(\)](#)

### Data Fields

- [uint32 numBytes](#)
- [uint32 peakNumBytes](#)
- [uint32 numAllocs](#)
- [uint32 peakNumAllocs](#)
- [uint32 numAllocFails](#)
- [uint32 totalNumAllocs](#)
- [uint32 totalNumBytes](#)

### 7.36.1 Constructor & Destructor Documentation

7.36.1.1 `MM_Stats_t::MM_Stats_t () [inline]`

7.36.1.2 `MM_Stats_t::MM_Stats_t (uint32 sizeIn) [inline]`

### 7.36.2 Member Function Documentation

7.36.2.1 `void MM_Stats_t::operator delete (void *ptr) throw () [inline]`

7.36.2.2 `void* MM_Stats_t::operator new (oscl_memsize_t size, MM_Stats_t *ptr) [inline]`

7.36.2.3 `void* MM_Stats_t::operator new (oscl_memsize_t size) [inline]`

7.36.2.4 `void MM_Stats_t::reset () [inline]`

7.36.2.5 `void MM_Stats_t::update (const MM_Stats_t & delta, bool add) [inline]`

### 7.36.3 Field Documentation

7.36.3.1 `uint32 MM_Stats_t::numAllocFails`

7.36.3.2 `uint32 MM_Stats_t::numAllocs`

7.36.3.3 `uint32 MM_Stats_t::numBytes`

7.36.3.4 `uint32 MM_Stats_t::peakNumAllocs`

7.36.3.5 `uint32 MM_Stats_t::peakNumBytes`

7.36.3.6 `uint32 MM_Stats_t::totalNumAllocs`

7.36.3.7 `uint32 MM_Stats_t::totalNumBytes`

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.37 NTPTime Class Reference

The NTPTime class represents a time value as the number of seconds since 0h (UTC) Jan. 1, 1900.

```
#include <oscl_time.h>
```

### Public Methods

- **OSCL\_COND\_IMPORT\_REF NTPTime ()**  
*The default constructor creates an NTPTime instance representing the current system time.*
- **OSCL\_COND\_IMPORT\_REF NTPTime (const NTPTime &src)**  
*Copy constructor to create a new NTPTime from an existing one.*
- **OSCL\_COND\_IMPORT\_REF NTPTime (const uint32 seconds)**  
*Construct an NTPTime from a uint32.*
- **OSCL\_COND\_IMPORT\_REF NTPTime (const int32 seconds)**  
*Construct an NTPTime from a int.*
- **OSCL\_COND\_IMPORT\_REF NTPTime (const TimeValue &t)**  
*Construct a NTPTime instance from a TimeValue instance.*
- **OSCL\_COND\_IMPORT\_REF NTPTime (const uint64 value)**  
*Construct a NTPTime instance from a uint64 value.*
- **OSCL\_COND\_IMPORT\_REF NTPTime & operator= (uint32 newval)**  
*The assignment operator for a 32 bit integer.*
- **OSCL\_COND\_IMPORT\_REF NTPTime & operator= (uint64 newval)**  
*The assignment operator for a 64 bit integer.*
- **OSCL\_COND\_IMPORT\_REF NTPTime & operator+= (uint64 val)**  
*The += operator is used to add a 64 bit 32.32 value to an existing NTPTime value.*
- **OSCL\_COND\_IMPORT\_REF NTPTime operator- (const NTPTime &npt) const**  
*The - operator allows subtraction of one NTPTime value from another. This is useful to measure an interval.*
- **void set\_from\_system\_time (const uint32 systemtime)**  
*This method converts a 32-bit system time to NTP time.*
- **OSCL\_COND\_IMPORT\_REF uint32 get\_middle32 () const**  
*Grab the middle 32 bits of the 64 bit 32.32 representation.*
- **OSCL\_COND\_IMPORT\_REF uint32 get\_upper32 () const**  
*This method returns the upper 32 bits of the 32.32 representation.*
- **OSCL\_COND\_IMPORT\_REF uint32 get\_lower32 () const**  
*This method returns the lower 32 bits of the 32.32 representation.*

- int32 [to\\_system\\_time \(\) const](#)

*This method converts the ntp time value to system time.*

- OSCL\_COND\_IMPORT\_REF [uint64 get\\_value \(\) const](#)

*This method returns the 32.32 ntp representation.*

- OSCL\_IMPORT\_REF int [set\\_to\\_current\\_time \(\)](#)

*This method sets the 32.32 representation to the current system time value.*

### 7.37.1 Detailed Description

The NTPTime class represents a time value as the number of seconds since 0h (UTC) Jan. 1, 1900.

The NTPTime class: Conversion to/from Unix (epoch at 0h Jan. 1, 1970) amount to addition/subtraction of 2208988800. A single 64 bit value is used to represent the time. This value represents the number of seconds since 0h (UTC) Jan. 1, 1900. There is an implied binary point between the upper 32 bits and lower 32 bits (this is referred to as a 32.32 fractional representation). For example a binary value of 00000000 00000000 00000011 10000000 00000000 00000000 00000000 represents 3.5 seconds since Jan 1, 1900.

### 7.37.2 Constructor & Destructor Documentation

#### 7.37.2.1 OSCL\_COND\_IMPORT\_REF NTPTime::NTPTime ()

The default constructor creates an NTPTime instance representing the current system time.

#### 7.37.2.2 OSCL\_COND\_IMPORT\_REF NTPTime::NTPTime (const NTPTime & src)

Copy constructor to create a new NTPTime from an existing one.

#### 7.37.2.3 OSCL\_COND\_IMPORT\_REF NTPTime::NTPTime (const uint32 seconds)

Construct an NTPTime from a uint32.

##### Parameters:

**seconds** The uint32 input represents the number of seconds since Jan. 1, 1900.

#### 7.37.2.4 OSCL\_COND\_IMPORT\_REF NTPTime::NTPTime (const int32 seconds)

Construct an NTPTime from a int.

##### Parameters:

**seconds** The int input represents the number of seconds since Jan. 1, 1900.

### 7.37.2.5 OSCL\_COND\_IMPORT\_REF NTPTime::NTPTime (const TimeValue & t)

Construct a NTPTime instance from a TimeValue instance.

This constructor creates an NTPTime value representing the same absolute time as the TimeValue parameter.

**Parameters:**

*t* A reference to a TimeValue object.

### 7.37.2.6 OSCL\_COND\_IMPORT\_REF NTPTime::NTPTime (const uint64 value)

Construct a NTPTime instance from a uint64 value.

**Parameters:**

*value* A 64 bit integer argument which is used as the ntp 32.32 fractional representation.

## 7.37.3 Member Function Documentation

### 7.37.3.1 OSCL\_COND\_IMPORT\_REF uint32 NTPTime::get\_lower32 ()

This method returns the lower 32 bits of the 32.32 representation.

### 7.37.3.2 OSCL\_COND\_IMPORT\_REF uint32 NTPTime::get\_middle32 ()

Grab the middle 32 bits of the 64 bit 32.32 representation.

### 7.37.3.3 OSCL\_COND\_IMPORT\_REF uint32 NTPTime::get\_upper32 ()

This method returns the upper 32 bits of the 32.32 representation.

### 7.37.3.4 OSCL\_COND\_IMPORT\_REF uint64 NTPTime::get\_value ()

This method returns the 32.32 ntp representation.

### 7.37.3.5 OSCL\_COND\_IMPORT\_REF NTPTime& NTPTime::operator+= (uint64 val)

The += operator is used to add a 64 bit 32.32 value to an existing NTPTime value.

**Parameters:**

*val* The 64 bit 32.32 value to add to this object's value.

### 7.37.3.6 OSCL\_COND\_IMPORT\_REF NTPTime NTPTime::operator- (const NTPTime & npt) const

The - operator allows subtraction of one NTPTime value from another. This is useful to measure an interval.

**Parameters:**

*npt* A reference to the NTPTime object to be subtracted from this one.

**7.37.3.7 OSCL\_COND\_IMPORT\_REF NTPTime& NTPTime::operator= (*uint64 newval*)**

The assignment operator for a 64 bit integer.

**Parameters:**

*newval* A 64 bit value which represents the 32.32 fractional representation of the ntp time.

**7.37.3.8 OSCL\_COND\_IMPORT\_REF NTPTime& NTPTime::operator= (*uint32 newval*)**

The assignment operator for a 32 bit integer.

**Parameters:**

*newval* A 32 bit integer representing the upper 32 bits of the 32.32 NTP time (e.g. the number of whole seconds since Jan 1, 1900 UTC).

**7.37.3.9 void NTPTime::set\_from\_system\_time (*const uint32 systemtime*)**

This method converts a 32-bit system time to NTP time.

This method sets the value of the NTPTime instance to the absolute time represented by the 32 bit input argument.

**Parameters:**

*systemtime* This 32-bit value is interpreted as the number of seconds since the unix epoch Jan. 1 1970.

**7.37.3.10 OSCL\_IMPORT\_REF int NTPTime::set\_to\_current\_time ()**

This method sets the 32.32 representation to the current system time value.

**7.37.3.11 int32 NTPTime::to\_system\_time ()**

This method converts the ntp time value to system time.

This method returns a 32 bit value representing the same absolute time as the NTP time value, but expressed as whole seconds since the unix epoch. The fractional part of the ntp value is discarded.


The documentation for this class was generated from the following file:

- [oscl\\_time.h](#)

## 7.38 Oscl\_Alloc Class Reference

```
#include <oscl_defalloc.h>
```

Inheritance diagram for Oscl\_Alloc::



### Public Methods

- virtual `~Oscl_Alloc ()`
- virtual `OsclAny * allocate (const uint32 size)=0`
- virtual `OsclAny * allocate_fl (const uint32 size, const char *file_name, const int line_num)`

#### 7.38.1 Constructor & Destructor Documentation

**7.38.1.1 virtual Oscl\_Alloc::~Oscl\_Alloc () [inline, virtual]**

#### 7.38.2 Member Function Documentation

**7.38.2.1 virtual OsclAny\* Oscl\_Alloc::allocate (const uint32 size) [pure virtual]**

Implemented in `_OsclBasicAllocator`, `Oscl_DefAlloc`, `OsclMemAllocator`, `OsclMemBasicAllocator`, `OsclMemAllocDestructDealloc< T >`, `OsclMemBasicAllocDestructDealloc< T >`, `OsclMemPoolFixedChunkAllocator`, `OsclMemPoolResizableAllocator`, and `OsclReadyAlloc`.

**7.38.2.2 virtual OsclAny\* Oscl\_Alloc::allocate\_fl (const uint32 size, const char \*file\_name, const int line\_num) [inline, virtual]**

Reimplemented in `Oscl_DefAlloc`, `OsclMemAllocator`, `OsclMemAllocDestructDealloc< T >`, and `OsclReadyAlloc`.


The documentation for this class was generated from the following file:

- `oscl_defalloc.h`

## 7.39 Oscl\_Dealloc Class Reference

```
#include <oscl_defalloc.h>
```

Inheritance diagram for Oscl\_Dealloc::



### Public Methods

- virtual void [deallocate \(OsclAny \\*p\)=0](#)
- virtual [~Oscl\\_Dealloc \(\)](#)

#### 7.39.1 Constructor & Destructor Documentation

**7.39.1.1 virtual Oscl\_Dealloc::~Oscl\_Dealloc () [inline, virtual]**

#### 7.39.2 Member Function Documentation

**7.39.2.1 virtual void Oscl\_Dealloc::deallocate (OsclAny \*p) [pure virtual]**

Implemented in [\\_OsclBasicAllocator](#), [Oscl\\_DefAlloc](#), [OsclMemAllocator](#), [OsclMemBasicAllocator](#), [OsclMemAllocDestructDealloc< T >](#), [OsclMemBasicAllocDestructDealloc< T >](#), [OsclMemPoolFixedChunkAllocator](#), [OsclMemPoolResizableAllocator](#), and [OsclReadyAlloc](#).


The documentation for this class was generated from the following file:

- [oscl\\_defalloc.h](#)

## 7.40 Oscl\_DefAlloc Class Reference

```
#include <oscl_defalloc.h>
```

Inheritance diagram for Oscl\_DefAlloc::



### Public Methods

- virtual [OsclAny \\* allocate \(const uint32 size\)=0](#)
- virtual [OsclAny \\* allocate\\_fl \(const uint32 size, const char \\*file\\_name, const int line\\_num\)](#)
- virtual void [deallocate \(OsclAny \\*p\)=0](#)

#### 7.40.1 Member Function Documentation

##### 7.40.1.1 virtual [OsclAny\\* Oscl\\_DefAlloc::allocate \(const uint32 size\)](#) [pure virtual]

Implements [Oscl\\_Alloc](#).

Implemented in [\\_OsclBasicAllocator](#), [OsclMemAllocator](#), [OsclMemBasicAllocator](#), [OsclMemAllocDestructDealloc< T >](#), [OsclMemBasicAllocDestructDealloc< T >](#), [OsclMemPoolFixedChunkAllocator](#), [OsclMemPoolResizableAllocator](#), and [OsclReadyAlloc](#).

##### 7.40.1.2 virtual [OsclAny\\* Oscl\\_DefAlloc::allocate\\_fl \(const uint32 size, const char \\*file\\_name, const int line\\_num\)](#) [inline, virtual]

Reimplemented from [Oscl\\_Alloc](#).

Reimplemented in [OsclMemAllocator](#), [OsclMemAllocDestructDealloc< T >](#), and [OsclReadyAlloc](#).

##### 7.40.1.3 virtual void [Oscl\\_DefAlloc::deallocate \(OsclAny \\*p\)](#) [pure virtual]

Implements [Oscl\\_Dealloc](#).

Implemented in [\\_OsclBasicAllocator](#), [OsclMemAllocator](#), [OsclMemBasicAllocator](#), [OsclMemAllocDestructDealloc< T >](#), [OsclMemBasicAllocDestructDealloc< T >](#), [OsclMemPoolFixedChunkAllocator](#), [OsclMemPoolResizableAllocator](#), and [OsclReadyAlloc](#).


The documentation for this class was generated from the following file:

- [oscl\\_defalloc.h](#)

## 7.41 Oscl\_DefAllocWithRefCounter< DefAlloc > Class Template Reference

```
#include <oscl_refcounter.h>
```

Inheritance diagram for Oscl\_DefAllocWithRefCounter< DefAlloc >::



### Public Methods

- void [Delete](#) ()
- void [addRef](#) ()
- void [removeRef](#) ()
- uint32 [getCount](#) ()

### Static Public Methods

- Oscl\_DefAllocWithRefCounter \* [New](#) ()

#### 7.41.1 Detailed Description

**template<class DefAlloc> class Oscl\_DefAllocWithRefCounter< DefAlloc >**

Implementation of an [Oscl\\_DefAlloc](#) class with a built-in ref counter.

#### 7.41.2 Member Function Documentation

**7.41.2.1 template<class DefAlloc> void Oscl\_DefAllocWithRefCounter< DefAlloc >::addRef () [inline, virtual]**

Add to the reference count

Implements [OsclRefCounter](#).

**7.41.2.2 template<class DefAlloc> void Oscl\_DefAllocWithRefCounter< DefAlloc >::Delete () [inline]**

Delete object

**7.41.2.3 template<class DefAlloc> uint32 Oscl\_DefAllocWithRefCounter< DefAlloc >::getCount () [inline, virtual]**

Gets the current number of references

Implements [OsclRefCounter](#).

**7.41.2.4 template<class DefAlloc> Oscl\_DefAllocWithRefCounter\*<br/>Oscl\_DefAllocWithRefCounter< DefAlloc >::New () [inline, static]**

Create object

**7.41.2.5 template<class DefAlloc> void Oscl\_DefAllocWithRefCounter< DefAlloc >::removeRef<br/>() [inline, virtual]**

Delete from reference count

Implements [OsclRefCounter](#).


The documentation for this class was generated from the following file:

- [oscl\\_refcounter.h](#)

## 7.42 OSCL\_FastString Class Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_FastString::



### Public Types

- `typedef OSCL_String::chartype chartype`
- `typedef TOSCL_StringOp optype`
- `typedef OSCL_wString::chartype other_chartype`

### Public Methods

- `OSCL_IMPORT_REF OSCL_FastString()`
- `OSCL_IMPORT_REF OSCL_FastString(const OSCL_FastString &src)`
- `OSCL_IMPORT_REF OSCL_FastString(const chartype *cstr)`
- `OSCL_IMPORT_REF OSCL_FastString(chartype *buf, uint32 maxlen)`
- `OSCL_IMPORT_REF ~OSCL_FastString()`
- `OSCL_IMPORT_REF uint32 get_size() const`
- `OSCL_IMPORT_REF uint32 get_maxsize() const`
- `OSCL_IMPORT_REF const chartype * get_cstr() const`
- `OSCL_IMPORT_REF chartype * get_str() const`
- `OSCL_IMPORT_REF OSCL_FastString & operator=(const OSCL_FastString &src)`
- `OSCL_IMPORT_REF OSCL_FastString & operator=(const chartype *cstr)`
- `OSCL_IMPORT_REF void set(chartype *cstr, uint32 maxlen)`
- `OSCL_IMPORT_REF void set(const other_chartype *buf, uint32 numofbyte, optype op)`
- `OSCL_IMPORT_REF void set_length()`

### Friends

- class `OSCL_String`

#### 7.42.1 Detailed Description

`OSCL_FastString` is a simple string class, compatible with regular character array strings.

This class does not allocate internal memory for the string but acts as a container for a user-defined buffer. This means no copying of the string is done and provides a faster way of manipulating strings. Depending on initialization, this container provides either read-only or read-write access to the string.

Implementation assumes the input string is null-terminated.

**Parameters:**

*C*: type of character.

## 7.42.2 Member Typedef Documentation

### 7.42.2.1 `typedef OSCL_String::chartype OSCL_FastString::chartype`

Reimplemented from [OSCL\\_String](#).

### 7.42.2.2 `typedef TOSCL_StringOp OSCL_FastString::optype`

### 7.42.2.3 `typedef OSCL_wString::chartype OSCL_FastString::other_chartype`

## 7.42.3 Constructor & Destructor Documentation

### 7.42.3.1 `OSCL_IMPORT_REF OSCL_FastString::OSCL_FastString()`

Default constructor.

### 7.42.3.2 `OSCL_IMPORT_REF OSCL_FastString::OSCL_FastString(const OSCL_FastString &src)`

Creates a fast string that contains a copy of the input string. The string inherits the writable-ness of the source string.

**Parameters:**

*src*: input string.

### 7.42.3.3 `OSCL_IMPORT_REF OSCL_FastString::OSCL_FastString(const chartype *cstr)`

Create the string and initialize it to contain the input string. The string is not writable.

**am:** **null-terminated string.**

### 7.42.3.4 `OSCL_IMPORT_REF OSCL_FastString::OSCL_FastString(chartype *buf, uint32 maxlen)`

Create the string and initialize it to contain the input string. The string is writable.

**Parameters:**

*cp*: null-terminated string.

**maxlen:** maximum size of storage at *cp*, not incl null terminator. If input string is not null-terminated, the function leaves.

**7.42.3.5 OSCL\_IMPORT\_REF OSCL\_FastString::~OSCL\_FastString ()****7.42.4 Member Function Documentation****7.42.4.1 OSCL\_IMPORT\_REF const chartype\* OSCL\_FastString::get\_cstr () [virtual]**

This function returns the C-style string for read access.

Implements [OSCL\\_String](#).

**7.42.4.2 OSCL\_IMPORT\_REF uint32 OSCL\_FastString::get\_maxsize () [virtual]**

This function returns the maximum available storage size, not including null terminator. The maximum size may be larger than the current string size.

Implements [OSCL\\_String](#).

**7.42.4.3 OSCL\_IMPORT\_REF uint32 OSCL\_FastString::get\_size () [virtual]**

Pure virtuals from [OSCL\\_String](#)

Implements [OSCL\\_String](#).

**7.42.4.4 OSCL\_IMPORT\_REF chartype\* OSCL\_FastString::get\_str () [virtual]**

This function returns the C-style string for write access. If the string is not writable it returns NULL.

Implements [OSCL\\_String](#).

**7.42.4.5 OSCL\_IMPORT\_REF OSCL\_FastString& OSCL\_FastString::operator= (const chartype \* cstr)**

Assignment operator

**am:** null-terminated string

Reimplemented from [OSCL\\_String](#).

**7.42.4.6 OSCL\_IMPORT\_REF OSCL\_FastString& OSCL\_FastString::operator= (const OSCL\_FastString & src)**

Assignment operators

**7.42.4.7 OSCL\_IMPORT\_REF void OSCL\_FastString::set (const other\_chartype \* buf, uint32 numofbyte, optype op)**

Set the contents of this string to a new string or character array, with conversion operation.

**Parameters:**

**buf:** string or character array.

*numofbyte*: number of bytes available in the buffer. There must be enough space available for the converted string including its NULL terminator. The converted string may be smaller or larger than the original string.

*op*: conversion operation to apply If numofbyte is not large enough for conversion, the function leaves. If input string is not null-terminated, the function leaves.

#### 7.42.4.8 OSCL\_IMPORT\_REF void OSCL\_FastString::set ([chartype](#) \* *cstr*, uint32 *maxlen*)

This function can be used to reassign the string to a new writable string. If input string is not null-terminated, the function leaves.

#### 7.42.4.9 OSCL\_IMPORT\_REF void OSCL\_FastString::set\_length ()

This function can be used to refresh the string size in case the contents of the string buffer have been modified since the container was created.

### 7.42.5 Friends And Related Function Documentation

#### 7.42.5.1 friend class OSCL\_String [friend]


The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.43 Oscl\_File Class Reference

```
#include <oscl_file_io.h>
```

Inheritance diagram for Oscl\_File::



### Public Types

- enum `seek_type` { `SEEKSET`, `SEEKCUR`, `SEEKEND` }
- enum `mode_type` { `MODE_READ` = 0x0001, `MODE_READWRITE` = 0x0002, `MODE_APPEND` = 0x0004, `MODE_BINARY` = 0x0008, `MODE_TEXT` = 0x0010, `MODE_READ_PLUS` = 0x0020 }
- enum `TSymbianAccessMode` { `ESymbianAccessMode_Rfile` = 0, `ESymbianAccessMode_RfileBuf` = 1 }

### Public Methods

- `OSCL_IMPORT_REF Oscl_File()`
- `OSCL_IMPORT_REF Oscl_File(uint32 aCacheSize)`
- `OSCL_IMPORT_REF Oscl_File(uint32 aCacheSize, OsclFileHandle *aFileHandle)`
- `OSCL_IMPORT_REF ~Oscl_File()`
- `OSCL_IMPORT_REF void SetPVCacheSize(uint32 aSize)`
- `void AddFixedCache(const OsclFixedCacheParam &aParam)`
- `void RemoveFixedCache(const TOsclFileOffset &aPos)`
- `void SetCacheObserver(OsclCacheObserver *aObs)`
- `OSCL_IMPORT_REF void SetNativeAccessMode(uint32 aMode)`
- `OSCL_IMPORT_REF void SetNativeBufferSize(int32 aSize)`
- `OSCL_IMPORT_REF void SetAsyncReadBufferSize(uint32 aSize)`
- `OSCL_IMPORT_REF int32 SetFileHandle(OsclFileHandle *aHandle)`
- `OSCL_IMPORT_REF int32 Open(const char *filename, uint32 mode, Oscl_FileServer &fileserv)`
- `OSCL_IMPORT_REF int32 Open(const oscl_wchar *filename, uint32 mode, Oscl_FileServer &fileserv)`
- `OSCL_IMPORT_REF uint32 Read(OsclAny *buffer, uint32 size, uint32 numelements)`
- `OSCL_IMPORT_REF uint32 Write(const OsclAny *buffer, uint32 size, uint32 numelements)`
- `OSCL_IMPORT_REF int32 Seek(TOscOfFileOffset offset, seek_type origin)`
- `OSCL_IMPORT_REF TOscOfFileOffset Tell()`
- `OSCL_IMPORT_REF int32 Close()`
- `OSCL_IMPORT_REF int32 Flush()`
- `OSCL_IMPORT_REF int32 SetSize(uint32 size)`
- `OSCL_IMPORT_REF int32 EndOfFile()`
- `OSCL_IMPORT_REF int32 GetError()`

- [OsclFileHandle \\* Handle \(\)](#)
- [OSCL\\_IMPORT\\_REF TOsclFileOffset Size \(\)](#)
- [OSCL\\_IMPORT\\_REF void SetLoggingEnable \(bool aEnable\)](#)
- [OSCL\\_IMPORT\\_REF void SetSummaryStatsLoggingEnable \(bool aEnable\)](#)

## Friends

- class [OsclFileCache](#)
- class [OsclFileCacheBuffer](#)
- class [asyncfilereadwrite\\_test](#)
- class [largeasyncfilereadwrite\\_test](#)
- class [asyncfilereadcancel\\_test](#)

### 7.43.1 Member Enumeration Documentation

#### 7.43.1.1 enum Oscl\_File::mode\_type

**Enumeration values:**

**MODE\_READ** Opens a file for reading. The file must exist.

**MODE\_READWRITE** Opens the file for reading and writing. If the file exists, its contents will be overwritten unless APPEND mode is specified. If the file does not exist, it will be created.

**MODE\_APPEND** Specifies all write operations to occur at the end of the file. The file pointer can be moved with the Seek command, but will always be moved to the end of the file for write commands.

**MODE\_BINARY** Opens the file in 'binary' mode. This is the default.

**MODE\_TEXT** Opens the file in 'text' mode. The default mode is 'binary'.

**MODE\_READ\_PLUS** Open a file for reading and writing. The file must exist. The default mode is 'binary'.

#### 7.43.1.2 enum Oscl\_File::seek\_type

**Enumeration values:**

**SEEKSET** Beginning of file

**SEEKCUR** Current position of file pointer

**SEEKEND** End of file

#### 7.43.1.3 enum Oscl\_File::TSymbianAccessMode

Defines mode options for SetNativeAccessMode on Symbian.

**Enumeration values:**

**ESymbianAccessMode\_Rfile**

**ESymbianAccessMode\_RfileBuf**

### 7.43.2 Constructor & Destructor Documentation

#### 7.43.2.1 OSCL\_IMPORT\_REF Oscl\_File::Oscl\_File ()

Constructor

#### 7.43.2.2 OSCL\_IMPORT\_REF Oscl\_File::Oscl\_File (uint32 *aCacheSize*)

Deprecated Constructor, present for back-compatibility.

**Parameters:**

*aCacheSize*: sets native buffer size, and when pv cache is enabled, also sets pv cache size.

#### 7.43.2.3 OSCL\_IMPORT\_REF Oscl\_File::Oscl\_File (uint32 *aCacheSize*, **OsclFileHandle** \* *aFileHandle*)

Deprecated Constructor, present for back-compatibility.

**Parameters:**

*aCacheSize*: sets native buffer size, and when pv cache is enabled, also sets pv cache size.

*aFileHandle*: open file handle.

#### 7.43.2.4 OSCL\_IMPORT\_REF Oscl\_File::~Oscl\_File ()

Destructor

### 7.43.3 Member Function Documentation

#### 7.43.3.1 void Oscl\_File::AddFixedCache (const **OsclFixedCacheParam** & *aParam*) [inline]

AddFixedCache adds a fixed cache. The fixed cache will be used on the next opportunity. The fixed cache must not overlap with any other fixed cache.

**Parameters:**

*aParam*: Cache location and size.

#### 7.43.3.2 OSCL\_IMPORT\_REF int32 Oscl\_File::Close ()

The File Close operation Closes the file after flushing any remaining data in the buffers.

Note: If the file object was opened with an external file handle, then Close will simply flush the file. The file will remain open.

**Returns:**

returns 0 if successful, and a non-zero value otherwise

**7.43.3.3 OSCL\_IMPORT\_REF int32 Oscl\_File::EndOfFile ()**

The File EOF(end of file) operation returns a nonzero value after the first read operation that attempts to read past the end of the file

**Returns:****7.43.3.4 OSCL\_IMPORT\_REF int32 Oscl\_File::Flush ()**

The File Flush operation On an output stream OSCL\_FileFlush causes any buffered but unwritten data to be written to the file. Flush is meant for writable files. The behavior when calling it on read-only files is OS-dependent.

**Returns:**

returns 0 if successful, and a non-zero value otherwise

**7.43.3.5 OSCL\_IMPORT\_REF int32 Oscl\_File::GetError ()**

The File Error operation If no error has occurred on stream, returns 0. Otherwise, it returns a nonzero value

**Returns:****7.43.3.6 OsclFileHandle\* Oscl\_File::Handle () [inline]**

Retrieve the file handle.

**Returns:**

file handle

**7.43.3.7 OSCL\_IMPORT\_REF int32 Oscl\_File::Open (const oscl\_wchar \*filename, uint32 mode, Oscl\_FileServer &fileserv)**

Opens a file.

Note: when an external file handle is used, Open will attach to the file handle and initialize cacheing features, but will not do a native file open.

**Parameters:**

*filename* name of file to open (Unicode)

*mode* combination of open mode flags

*fileserv* fileserv to use

**Returns:**

returns 0 if successful and a non-zero value otherwise

#### 7.43.3.8 OSCL\_IMPORT\_REF int32 Oscl\_File::Open (const char \*filename, uint32 mode, Oscl\_FileServer &fileserv)

Opens a file.

Note: when an external file handle is used, Open will attach to the file handle and initialize cacheing features, but will not do a native file open.

**Parameters:**

*filename* name of file to open (Utf8)  
*mode* combination of open mode flags  
*fileserv* fileserv to use

**Returns:**

returns 0 if successful and a non-zero value otherwise

#### 7.43.3.9 OSCL\_IMPORT\_REF uint32 Oscl\_File::Read (OsclAny \*buffer, uint32 size, uint32 numelements)

The File Read operation Reads from the file into the buffer a maximum of 'numelements' of size 'size'.

**Parameters:**

*buffer* pointer to buffer of type void  
*size* element size in bytes  
*numelements* max number of elements to read

**Returns:**

returns the number of full elements actually read, which may be less than count if an error occurs or if the end of the file is encountered before reaching count. Use the CheckEndOfFile or GetError function to distinguish a read error from an end-of-file condition.

#### 7.43.3.10 void Oscl\_File::RemoveFixedCache (const TOsclFileOffset &aPos) [ inline ]

RemoveFixedCache removes a fixed cache.

**Parameters:**

*aPos*: Cache location and size.

#### 7.43.3.11 OSCL\_IMPORT\_REF int32 Oscl\_File::Seek (TOsclFileOffset offset, seek\_type origin)

The File Seek operation Sets the position for file pointer

**Parameters:**

*offset* offset from the specified origin.  
*origin* starting point

**Returns:**

returns 0 on success, and a non-zero value otherwise

**7.43.3.12 OSCL\_IMPORT\_REF void Oscl\_File::SetAsyncReadBufferSize (uint32 *aSize*)**

SetAsyncReadBufferSize configures the asynchronous background read function. May not be available on all platforms.

This should be called before opening the file. If used when the file is open, the option will not take effect until the next Open.

Note: if asynchronous read is not available on the platform, this call will have no effect.

**Parameters:**

*aSize*: buffer size in bytes. Zero disables the feature.

**7.43.3.13 void Oscl\_File::SetCacheObserver ([OsclCacheObserver](#) \* *aObs*) [inline]****7.43.3.14 OSCL\_IMPORT\_REF int32 Oscl\_File::SetFileHandle ([OsclFileHandle](#) \* *aHandle*)**

SetFileHandle adds an open file handle to the Oscl\_File object. The Oscl\_File object will use that handle to access the file.

This call is not available when the Oscl\_File object is already open.

Note: This feature is used in Symbian with the MMF framework. The MMF framework provides an open RFile handle to access content. When using RFileBuf access mode with an RFile handle, the RFileBuf will be attached to the open RFile handle.

To use the external file handle, the caller starts with a native file handle to an open file. The caller must wrap the native file handle in an [OsclFileHandle](#) object, pass the [OsclFileHandle](#) pointer to SetFileHandle, call [Oscl\\_File::Open](#), then proceed to use the Oscl\_File object, finally calling [Oscl\\_File::Close](#). In this usage mode, [Oscl\\_File::Open](#) and [Oscl\\_File::Close](#) do not actually call native file open and close. It is assumed that the caller will close the original native file handle after usage is complete.

**Parameters:**

*aHandle*: container for an open file handle.

**Returns:**

returns 0 if successful, non-zero if error.

**7.43.3.15 OSCL\_IMPORT\_REF void Oscl\_File::SetLoggingEnable (bool *aEnable*)**

SetLoggingEnable configures the [PVLogger](#) output for this file. This will enable full logging of each API entry and exit using the logger object "Oscl\_File", plus full logging of native operation entry & exit using logger object "OsclNativeFile".

**Parameters:**

*aEnable*: true to enable, false to disable logging.

**7.43.3.16 OSCL\_IMPORT\_REF void Oscl\_File::SetNativeAccessMode (uint32 *aMode*)**

SetNativeAccessMode allows switching between different native file access modes, when available.

Note: for Symbian, use the TSymbianAccessMode values to choose the mode. If multiple access modes are not available on the platform, this call will have no effect.

**Parameters:**

*aMode*: access mode.

**7.43.3.17 OSCL\_IMPORT\_REF void Oscl\_File::SetNativeBufferSize (int32 *aSize*)**

SetNativeBufferSize configures the native file buffering feature, when available.

This should be called before opening the file. If used when the file is open, the option will not take effect until the next Open.

Note: For Symbian, this sets the RFileBuf cache size. If native buffering is not available on the platform, this call will have no effect.

**Parameters:**

*aSize*: native buffer size in bytes. Zero disables the feature.

**7.43.3.18 OSCL\_IMPORT\_REF void Oscl\_File::SetPVCacheSize (uint32 *aSize*)**

SetPVCacheSize configures the read/write cache.

This should be called before opening the file. If used when the file is open, the option will not take effect until the next Open.

**Parameters:**

*aSize*: cache size in bytes. Zero disables the cache.

**7.43.3.19 OSCL\_IMPORT\_REF int32 Oscl\_File::SetSize (uint32 *size*)**

The File SetSize operation If the file has been opened for writing this will set the size of the file. The file pointer position is undefined after calling SetSize. If file size is increased the contents of the new section are undefined.

**Returns:**

returns 0 if successful, and a non-zero value otherwise

**7.43.3.20 OSCL\_IMPORT\_REF void Oscl\_File::SetSummaryStatsLoggingEnable (bool *aEnable*)**

SetSummaryStatsLoggingEnable configures the [PVLogger](#) output for this file. This will enable summary statistics logging only, using the logger object "[OsclFileStats](#)".

**Parameters:**

*aEnable*: true to enable, false to disable stats logging.

**7.43.3.21 OSCL\_IMPORT\_REF [TOsclFileOffset](#) Oscl\_File::Size ()**

Get the file size in bytes.

**Returns:**

- The size of the file, or -1 on error.

#### 7.43.3.22 OSCL\_IMPORT\_REF [TOsclFileOffset](#) Oscl\_File::Tell ()

The File Tell operation Returns the current file position for file specified by fp

#### 7.43.3.23 OSCL\_IMPORT\_REF uint32 Oscl\_File::Write (const [OsclAny](#) \* *buffer*, uint32 *size*, uint32 *numelements*)

The File Write operation Writes from the buffer '*numelements*' objects of size '*size*'

**Parameters:**

*buffer* pointer to buffer of type void

*size* element size in bytes

*numelements* number of elements to write

**Returns:**

The number of elements written

### 7.43.4 Friends And Related Function Documentation

#### 7.43.4.1 friend class [asyncfilereadcancel\\_test](#) [friend]

#### 7.43.4.2 friend class [asyncfilereadwrite\\_test](#) [friend]

#### 7.43.4.3 friend class [largeasynccfilereadwrite\\_test](#) [friend]

#### 7.43.4.4 friend class [OsclFileCache](#) [friend]

#### 7.43.4.5 friend class [OsclFileCacheBuffer](#) [friend]

The documentation for this class was generated from the following file:

- [oscl\\_file\\_io.h](#)

## 7.44 Oscl\_File::OsclCacheObserver Class Reference

```
#include <oscl_file_io.h>
```

### Public Methods

- virtual ~OsclCacheObserver ()
- virtual OsclFileCacheBuffer \* ChooseCurCache (OsclFileCache &aContext, TOsclFileOffset aPos)=0

#### 7.44.1 Detailed Description

For defining a cache observer. Cache observer can implement customized cache schemes by replacing the SetCachePosition routine.

#### 7.44.2 Constructor & Destructor Documentation

**7.44.2.1 virtual Oscl\_File::OsclCacheObserver::~OsclCacheObserver () [inline, virtual]**

#### 7.44.3 Member Function Documentation

**7.44.3.1 virtual OsclFileCacheBuffer\* Oscl\_File::OsclCacheObserver::ChooseCurCache (OsclFileCache & aContext, TOsclFileOffset aPos) [pure virtual]**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_io.h](#)

## 7.45 Oscl\_File::OsclFixedCacheParam Class Reference

```
#include <oscl_file_io.h>
```

### Public Methods

- bool [Contains \(TOsclFileOffset pos\) const](#)

### Data Fields

- [TOsclFileOffset iFilePosition](#)
- [uint32 iSize](#)

#### 7.45.1 Detailed Description

Parameters for defining a fixed cache

#### 7.45.2 Member Function Documentation

**7.45.2.1 bool Oscl\_File::OsclFixedCacheParam::Contains (TOsclFileOffset *pos*) const  
[inline]**

#### 7.45.3 Field Documentation

**7.45.3.1 TOsclFileOffset Oscl\_File::OsclFixedCacheParam::iFilePosition**

**7.45.3.2 uint32 Oscl\_File::OsclFixedCacheParam::iSize**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_io.h](#)

## 7.46 Oscl\_FileFind Class Reference

```
#include <oscl_file_find.h>
```

### Public Types

- enum `error_type` { `E_OK` = 0, `E_INVALID_STATE`, `E_INVALID_ARG`, `E_PATH_TOO_LONG`, `E_PATH_NOT_FOUND`, `E_NO_MATCH`, `E_BUFFER_TOO_SMALL`, `E_NOT_IMPLEMENTED`, `E_MEMORY_ERROR`, `E_OTHER` }
- enum `element_type` { `FILE_TYPE` = 0, `DIR_TYPE`, `INVALID_TYPE` }

### Public Methods

- OSCL\_IMPORT\_REF const char \* `FindFirst` (const char \*directory, const char \*pattern, char \*buf, uint32 buflen)
- OSCL\_IMPORT\_REF const `oscl_wchar` \* `FindFirst` (const `oscl_wchar` \*directory, const `oscl_wchar` \*pattern, `oscl_wchar` \*buf, uint32 buflen)
- OSCL\_IMPORT\_REF char \* `FindNext` (char \*buf, uint32 buflen)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `FindNext` (`oscl_wchar` \*buf, uint32 buflen)
- OSCL\_IMPORT\_REF void `Close` ()
- OSCL\_IMPORT\_REF `element_type` `GetElementType` ()
- OSCL\_IMPORT\_REF `error_type` `GetLastError` ()
- OSCL\_IMPORT\_REF `Oscl_FileFind` ()
- OSCL\_IMPORT\_REF `~Oscl_FileFind` ()

### 7.46.1 Detailed Description

`Oscl_FileFind` class defines the generic way of finding filesystem elements that match a pattern within a directory

### 7.46.2 Member Enumeration Documentation

#### 7.46.2.1 enum Oscl\_FileFind::element\_type

Enumeration values:

`FILE_TYPE`

`DIR_TYPE`

`INVALID_TYPE`

#### 7.46.2.2 enum Oscl\_FileFind::error\_type

Enumeration values:

`E_OK`

`E_INVALID_STATE`

`E_INVALID_ARG`

`E_PATH_TOO_LONG`

**E\_PATH\_NOT\_FOUND**  
**E\_NO\_MATCH**  
**E\_BUFFER\_TOO\_SMALL**  
**E\_NOT\_IMPLEMENTED**  
**E\_MEMORY\_ERROR**  
**E\_OTHER**

### 7.46.3 Constructor & Destructor Documentation

#### 7.46.3.1 OSCL\_IMPORT\_REF Oscl\_FileFind::Oscl\_FileFind ()

constructor.

**Returns:**

none

#### 7.46.3.2 OSCL\_IMPORT\_REF Oscl\_FileFind::~Oscl\_FileFind ()

destructor. will deallocate open handles if necessary

**Returns:**

none

### 7.46.4 Member Function Documentation

#### 7.46.4.1 OSCL\_IMPORT\_REF void Oscl\_FileFind::Close ()

closes the handle to directory.

**Returns:**

none

#### 7.46.4.2 OSCL\_IMPORT\_REF const oscl\_wchar\* Oscl\_FileFind::FindFirst (const oscl\_wchar \* directory, const oscl\_wchar \* pattern, oscl\_wchar \* buf, uint32 buflen)

Opens a directory for reading.

**Parameters:**

*directory* directory to search (utf16).

*pattern* wildcard pattern filter (utf16). passing NULL, results in a universal match.

*buf* buffer for returned pathname (utf16).

*buflen* size in wide characters of buf. If buf is not large enough to hold the returned string, NULL is returned, and GetLastError is set to E\_BUFFER\_TOO\_SMALL.

**Returns:**

returns a pointer to buffer supplied, which contains the pathname of the first found element, or NULL otherwise. On a NULL return value, [GetLastError\(\)](#) returns a more detailed error.

#### 7.46.4.3 OSCL\_IMPORT\_REF const char\* Oscl\_FileFind::FindFirst (const char \* *directory*, const char \* *pattern*, char \* *buf*, uint32 *buflen*)

Finds first element matching the pattern.

**Parameters:**

*directory* directory to search (utf8).

*pattern* wildcard pattern filter (utf8). passing NULL, results in a universal match.

*buf* buffer for returned pathname (utf8).

*buflen* size in wide characters of buf. If buf is not large enough to hold the returned string, NULL is returned, and GetLastError is set to E\_BUFFER\_TOO\_SMALL.

**Returns:**

returns a pointer to buffer supplied, which contains the pathname of the first found element, or NULL otherwise. On a NULL return value, [GetLastError\(\)](#) returns a more detailed error.

#### 7.46.4.4 OSCL\_IMPORT\_REF oscl\_wchar\* Oscl\_FileFind::FindNext (oscl\_wchar \* *buf*, uint32 *buflen*)

Reads the next element in a directory. Note: the pointer returned by this function is not persistent and should be stored. Its scope is limited to the lifetime of the class.

**Parameters:**

*buf* buffer to hold directory name(utf16)

*buflen* size in wide characters of buf. If buf is not large enough to hold the returned string, NULL is returned, and GetLastError is set to E\_BUFFER\_TOO\_SMALL.

**Returns:**

returns a pointer to buffer supplied, which contains the pathname of the next found element, or NULL otherwise. On a NULL return value, [GetLastError\(\)](#) returns a more detailed error.

#### 7.46.4.5 OSCL\_IMPORT\_REF char\* Oscl\_FileFind::FindNext (char \* *buf*, uint32 *buflen*)

Reads the next element in the directory. Note: the pointer returned by this function is not persistent and should be stored. Its scope is limited to the lifetime of the class.

**Parameters:**

*buf* buffer to hold directory name(utf8)

*buflen* size in wide characters of buf. If buf is not large enough to hold the returned string, NULL is returned, and GetLastError is set to E\_BUFFER\_TOO\_SMALL.

**Returns:**

returns a pointer to buffer supplied, which contains the pathname of the next found element, or NULL otherwise. On a NULL return value, [GetLastError\(\)](#) returns a more detailed error.

#### 7.46.4.6 OSCL\_IMPORT\_REF *element\_type* Oscl\_FileFind::GetElementType ()

Returns the element type for the last element returned

**Returns:**

see enumeration above for more info.

#### 7.46.4.7 OSCL\_IMPORT\_REF [error\\_type](#) Oscl\_FileFind::GetLastError ()

Returns the error code for the last operation.

**Returns:**

see enumeration above for more info.

The documentation for this class was generated from the following file:

- [oscl\\_file\\_find.h](#)

## 7.47 Oscl\_FileServer Class Reference

```
#include <oscl_file_server.h>
```

### Public Methods

- OSCL\_IMPORT\_REF [Oscl\\_FileServer \(\)](#)
- OSCL\_IMPORT\_REF [~Oscl\\_FileServer \(\)](#)
- OSCL\_IMPORT\_REF int32 [Connect \(bool aShareSession=false\)](#)
- OSCL\_IMPORT\_REF int32 [Close \(\)](#)
- OSCL\_IMPORT\_REF int32 [Oscl\\_DeleteFile \(const char \\*filename\)](#)
- OSCL\_IMPORT\_REF int32 [Oscl\\_DeleteFile \(const oscl\\_wchar \\*filename\)](#)

### Friends

- class [Oscl\\_File](#)
- class [OsclNativeFile](#)

#### 7.47.1 Constructor & Destructor Documentation

##### 7.47.1.1 OSCL\_IMPORT\_REF Oscl\_FileServer::Oscl\_FileServer ()

Constructor

##### 7.47.1.2 OSCL\_IMPORT\_REF Oscl\_FileServer::~Oscl\_FileServer ()

Destructor

#### 7.47.2 Member Function Documentation

##### 7.47.2.1 OSCL\_IMPORT\_REF int32 Oscl\_FileServer::Close ()

Closes a file server.

**Returns:**

returns 0 on success and a non-zero value otherwise

##### 7.47.2.2 OSCL\_IMPORT\_REF int32 Oscl\_FileServer::Connect (bool *aShareSession = false*)

Connects the server. This must be called before a file server can be used.

**Returns:**

returns 0 on success and a non-zero value otherwise

**7.47.2.3 OSCL\_IMPORT\_REF int32 Oscl\_FileServer::Oscl\_DeleteFile (const oscl\_wchar \*  
*filename*)**

Deletes a file from the filesystem

**Parameters:**

*filename* name of the file to delete (Unicode)

**Returns:**

returns 0 if successful, and a non-zero value otherwise.

**7.47.2.4 OSCL\_IMPORT\_REF int32 Oscl\_FileServer::Oscl\_DeleteFile (const char \**filename*)**

Deletes a file from the filesystem \*

**Parameters:**

*filename* name of the file to delete (Utf8)

**Returns:**

returns 0 if successful, and a non-zero value otherwise.

**7.47.3 Friends And Related Function Documentation****7.47.3.1 friend class Oscl\_File [friend]****7.47.3.2 friend class OsclNativeFile [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_server.h](#)

## 7.48 oscl\_fsstat Struct Reference

```
#include <oscl_file_dir_utils.h>
```

### Data Fields

- [uint64 freebytes](#)
- [uint64 totalbytes](#)

#### 7.48.1 Field Documentation

##### 7.48.1.1 [uint64 oscl\\_fsstat::freebytes](#)

##### 7.48.1.2 [uint64 oscl\\_fsstat::totalbytes](#)


The documentation for this struct was generated from the following file:

- [oscl\\_file\\_dir\\_utils.h](#)

## 7.49 OSCL\_HeapString< Alloc > Class Template Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_HeapString< Alloc >::



### Public Types

- `typedef OSCL_String::chartype chartype`
- `typedef TOSCL_StringOp optype`
- `typedef OSCL_wString::chartype other_chartype`

### Public Methods

- `OSCL_HeapString()`
- `OSCL_HeapString(const OSCL_HeapString &src)`
- `OSCL_HeapString(const OSCL_String &src)`
- `OSCL_HeapString(const chartype *cstr)`
- `OSCL_HeapString(const chartype *buf, uint32 length)`
- `~OSCL_HeapString()`
- `uint32 get_size() const`
- `uint32 get_maxsize() const`
- `const chartype * get_cstr() const`
- `chartype * get_str() const`
- `OSCL_HeapString & operator=(const OSCL_HeapString &src)`
- `OSCL_HeapString & operator=(const OSCL_String &src)`
- `OSCL_HeapString & operator=(const chartype *cstr)`
- `void set(const chartype *buf, uint32 length)`
- `void set(const other_chartype *buf, optype op)`
- `void set(const other_chartype *buf, uint32 length, optype op)`

### Friends

- `class OSCL_String`

### 7.49.1 Detailed Description

```
template<class Alloc> class OSCL_HeapString< Alloc >
```

OSCL\_HeapString is a simple string class, compatible with regular character array strings.

The string array is variable length, is allocated from the heap, and is modifiable. A copy-on-write mechanism is used to minimize unnecessary copying when multiple instances of a string are created for reading. Allocated memory is automatically freed by the class destructor when the last string referencing the memory is destroyed.

The class HAS NO thread synchronization built-in, so it is NOT MT-SAFE. External locks should be used if the class is to be shared across threads.

**Parameters:**

*Alloc*: memory allocator, derived from [Oscl\\_DefAlloc](#).

### 7.49.2 Member Typedef Documentation

**7.49.2.1 template<class Alloc> typedef OSCL\_String::chartype OSCL\_HeapString< Alloc >::chartype**

Reimplemented from [OSCL\\_String](#).

**7.49.2.2 template<class Alloc> typedef TOSCL\_StringOp OSCL\_HeapString< Alloc >::optype**

**7.49.2.3 template<class Alloc> typedef OSCL\_wString::chartype OSCL\_HeapString< Alloc >::other\_chartype**

### 7.49.3 Friends And Related Function Documentation

**7.49.3.1 template<class Alloc> friend class OSCL\_String [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.50 OSCL\_HeapStringA Class Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_HeapStringA::



### Public Types

- `typedef OSCL_String::chartype chartype`
- `typedef TOSCL_StringOp optype`
- `typedef OSCL_wString::chartype other_chartype`

### Public Methods

- `OSCL_IMPORT_REF OSCL_HeapStringA()`
- `OSCL_IMPORT_REF OSCL_HeapStringA(Oscl_DefAlloc *alloc, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_HeapStringA(const OSCL_HeapStringA &src)`
- `OSCL_IMPORT_REF OSCL_HeapStringA(const OSCL_HeapStringA &src, Oscl_DefAlloc *alloc, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_HeapStringA(const OSCL_String &src, Oscl_DefAlloc *alloc=NULL, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_HeapStringA(const chartype *cstr, Oscl_DefAlloc *alloc=NULL, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_HeapStringA(const chartype *buf, uint32 length, Oscl_DefAlloc *alloc=NULL, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF ~OSCL_HeapStringA()`
- `OSCL_IMPORT_REF uint32 get_size() const`
- `OSCL_IMPORT_REF uint32 get_maxsize() const`
- `OSCL_IMPORT_REF const chartype * get_cstr() const`
- `OSCL_IMPORT_REF chartype * get_str() const`
- `OSCL_IMPORT_REF OSCL_HeapStringA & operator=(const OSCL_HeapStringA &src)`
- `OSCL_IMPORT_REF OSCL_HeapStringA & operator=(const OSCL_String &src)`
- `OSCL_IMPORT_REF OSCL_HeapStringA & operator=(const chartype *cstr)`
- `OSCL_IMPORT_REF void set(const chartype *buf, uint32 length)`
- `OSCL_IMPORT_REF void set(const other_chartype *buf, optype op)`
- `OSCL_IMPORT_REF void set(const other_chartype *buf, uint32 length, optype op)`

### Friends

- class `OSCL_String`

### 7.50.1 Detailed Description

OSCL\_HeapStringA is a simple string class, compatible with regular character array strings. It is similar to [OSCL\\_HeapString](#), except that the allocator is passed at run-time instead of compile-time. The allocator pointer is passed in the constructor, and may be a reference-counted object. If the allocator is not a reference-counted object then it must persist over the lifetime of all OSCL\_HeapStringA objects that use it. If no allocator is provided, then an [OsclMemAllocator](#) will be used.

The string array is variable length, is allocated from the heap, and is modifiable. A copy-on-write mechanism is used to minimize unnecessary copying when multiple instances of a string are created for reading. Allocated memory is automatically freed by the class destructor when the last string referencing the memory is destroyed.

The class HAS NO thread synchronization built-in, so it is NOT MT-SAFE. External locks should be used if the class is to be shared across threads.

### 7.50.2 Member Typedef Documentation

#### 7.50.2.1 `typedef OSCL_String::chartype OSCL_HeapStringA::chartype`

Reimplemented from [OSCL\\_String](#).

#### 7.50.2.2 `typedef TOSCL_StringOp OSCL_HeapStringA::optype`

#### 7.50.2.3 `typedef OSCL_wString::chartype OSCL_HeapStringA::other_chartype`

### 7.50.3 Constructor & Destructor Documentation

#### 7.50.3.1 `OSCL_IMPORT_REF OSCL_HeapStringA::OSCL_HeapStringA()`

The default constructor creates an empty string.

**am:** (optional) allocator or reference-counted allocator.

**am:** (optional) reference counter associated with allocator object.

If no allocator is provided, this object will use an [OsclMemAllocator](#).

#### 7.50.3.2 `OSCL_IMPORT_REF OSCL_HeapStringA::OSCL_HeapStringA (Oscl_DefAlloc *alloc, OsclRefCounter *ref = NULL)`

#### 7.50.3.3 `OSCL_IMPORT_REF OSCL_HeapStringA::OSCL_HeapStringA (const OSCL_HeapStringA & src)`

Creates a heap string that contains a copy of the input string.

**Parameters:**

*src*: input string.

**am:** (optional) allocator or reference-counted allocator.

**am:** (optional) reference counter associated with allocator object.

If no allocator is provided, this this object will use an [OsclMemAllocator](#).

**7.50.3.4 OSCL\_IMPORT\_REF OSCL\_HeapStringA::OSCL\_HeapStringA (const OSCL\_HeapStringA & src, Oscl\_DefAlloc \* alloc, OsclRefCounter \* ref = NULL)**

**7.50.3.5 OSCL\_IMPORT\_REF OSCL\_HeapStringA::OSCL\_HeapStringA (const OSCL\_String & src, Oscl\_DefAlloc \* alloc = NULL, OsclRefCounter \* ref = NULL)**

**7.50.3.6 OSCL\_IMPORT\_REF OSCL\_HeapStringA::OSCL\_HeapStringA (const chartype \* cstr, Oscl\_DefAlloc \* alloc = NULL, OsclRefCounter \* ref = NULL)**

Creates a heap string that contains a copy of the input string.

**Parameters:**

*cp*: null-terminated string.

**am: (optional) allocator or reference-counted allocator.**

**am: (optional) reference counter associated with allocator object.**

If no allocator is provided, this this object will use an [OsclMemAllocator](#).

**7.50.3.7 OSCL\_IMPORT\_REF OSCL\_HeapStringA::OSCL\_HeapStringA (const chartype \* buf, uint32 length, Oscl\_DefAlloc \* alloc = NULL, OsclRefCounter \* ref = NULL)**

Creates a heap string that contains a copy of the input string or character array.

**Parameters:**

*src*: character array, not necessarily null-terminated.

*length*: number of characters to copy.

**am: (optional) allocator or reference-counted allocator.**

**am: (optional) reference counter associated with allocator object.**

If no allocator is provided, this this object will use an [OsclMemAllocator](#).

**7.50.3.8 OSCL\_IMPORT\_REF OSCL\_HeapStringA::~OSCL\_HeapStringA ()**

## 7.50.4 Member Function Documentation

**7.50.4.1 OSCL\_IMPORT\_REF const chartype\* OSCL\_HeapStringA::get\_cstr () [virtual]**

This function returns the C-style string for read access.

Implements [OSCL\\_String](#).

**7.50.4.2 OSCL\_IMPORT\_REF uint32 OSCL\_HeapStringA::get\_maxsize () [virtual]**

This function returns the maximum available storage size, not including null terminator. The maximum size may be larger than the current string size.

Implements [OSCL\\_String](#).

**7.50.4.3 OSCL\_IMPORT\_REF uint32 OSCL\_HeapStringA::get\_size () [virtual]**

Pure virtuals from [OSCL\\_String](#)

Implements [OSCL\\_String](#).

**7.50.4.4 OSCL\_IMPORT\_REF chartype\* OSCL\_HeapStringA::get\_str () [virtual]**

This function returns the C-style string for write access. If the string is not writable it returns NULL.

Implements [OSCL\\_String](#).

**7.50.4.5 OSCL\_IMPORT\_REF OSCL\_HeapStringA& OSCL\_HeapStringA::operator= (const chartype \* cstr)**

Assignment operator

**am:** null-terminated string

Reimplemented from [OSCL\\_String](#).

**7.50.4.6 OSCL\_IMPORT\_REF OSCL\_HeapStringA& OSCL\_HeapStringA::operator= (const OSCL\_String & src)**

Assignment operator

Reimplemented from [OSCL\\_String](#).

**7.50.4.7 OSCL\_IMPORT\_REF OSCL\_HeapStringA& OSCL\_HeapStringA::operator= (const OSCL\_HeapStringA & src)**

Assignment operators

**7.50.4.8 OSCL\_IMPORT\_REF void OSCL\_HeapStringA::set (const other\_chartype \* buf, uint32 length, optype op)**

Set the contents of this string to a new string or character array, with conversion operation.

**Parameters:**

*buf*: string or character array.

*length*: number of characters to copy.

*op*: conversion operation to apply

#### 7.50.4.9 OSCL\_IMPORT\_REF void OSCL\_HeapStringA::set (const **other\_chartype** \* *buf*, **optype** *op*)

Set the contents of this string to a new string, with conversion operation.

**Parameters:**

*buf*: NULL-terminated wide string.

*op*: conversion operation to apply

#### 7.50.4.10 OSCL\_IMPORT\_REF void OSCL\_HeapStringA::set (const **chartype** \* *buf*, uint32 *length*)

Set the contents of this string to a new string or character array.

**Parameters:**

*buf*: string or character array.

*length*: number of characters to copy.

### 7.50.5 Friends And Related Function Documentation

#### 7.50.5.1 friend class OSCL\_String [friend]

The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.51 Oscl\_Int64\_Utils Class Reference

The Oscl\_Int64\_Utils class provides a wrapper for commonly used int64/uint64 operations.

```
#include <oscl_int64_utils.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF void `set_int64` (`int64` &`input_value`, const `int32` `upper`, const `uint32` `lower`)
- OSCL\_IMPORT\_REF `int32` `get_int64_upper32` (const `int64` &`input_value`)
- OSCL\_IMPORT\_REF `uint32` `get_int64_lower32` (const `int64` &`input_value`)
- OSCL\_IMPORT\_REF `uint32` `get_int64_middle32` (const `int64` &`input_value`)
- OSCL\_IMPORT\_REF void `set_uint64` (`uint64` &`input_value`, const `uint32` `upper`, const `uint32` `lower`)
- OSCL\_IMPORT\_REF `uint32` `get_uint64_upper32` (const `uint64` &`input_value`)
- OSCL\_IMPORT\_REF `uint32` `get_uint64_lower32` (const `uint64` &`input_value`)
- OSCL\_IMPORT\_REF `uint32` `get_uint64_middle32` (const `uint64` &`input_value`)

### 7.51.1 Detailed Description

The Oscl\_Int64\_Utils class provides a wrapper for commonly used int64/uint64 operations.

The Oscl\_Int64\_Utils class:

Provides a wrapper for commonly used operations to mask the differences between OSes that have an int64/uint64 class instead of a 64-bit integer.

## 7.51.2 Member Function Documentation

- 7.51.2.1 **OSCL\_IMPORT\_REF** **uint32** **Oscl\_Int64\_Utils::get\_int64\_lower32** (**const int64 & input\_value**) [static]
- 7.51.2.2 **OSCL\_IMPORT\_REF** **uint32** **Oscl\_Int64\_Utils::get\_int64\_middle32** (**const int64 & input\_value**) [static]
- 7.51.2.3 **OSCL\_IMPORT\_REF** **int32** **Oscl\_Int64\_Utils::get\_int64\_upper32** (**const int64 & input\_value**) [static]
- 7.51.2.4 **OSCL\_IMPORT\_REF** **uint32** **Oscl\_Int64\_Utils::get\_uint64\_lower32** (**const uint64 & input\_value**) [static]
- 7.51.2.5 **OSCL\_IMPORT\_REF** **uint32** **Oscl\_Int64\_Utils::get\_uint64\_middle32** (**const uint64 & input\_value**) [static]
- 7.51.2.6 **OSCL\_IMPORT\_REF** **uint32** **Oscl\_Int64\_Utils::get\_uint64\_upper32** (**const uint64 & input\_value**) [static]
- 7.51.2.7 **OSCL\_IMPORT\_REF** **void** **Oscl\_Int64\_Utils::set\_int64** (**int64 & input\_value, const int32 upper, const uint32 lower**) [static]
- 7.51.2.8 **OSCL\_IMPORT\_REF** **void** **Oscl\_Int64\_Utils::set\_uint64** (**uint64 & input\_value, const uint32 upper, const uint32 lower**) [static]

The documentation for this class was generated from the following file:

- [oscl\\_int64\\_utils.h](#)

## 7.52 Oscl\_Less< T > Struct Template Reference

```
#include <oscl_map.h>
```

### Public Methods

- bool [operator\(\)](#) (const T &x, const T &y) const

```
template<class T> struct Oscl_Less< T >
```

#### 7.52.1 Member Function Documentation

**7.52.1.1 template<class T> bool Oscl\_Less< T >::operator() (const T & x, const T & y) const [inline]**


The documentation for this struct was generated from the following file:

- [oscl\\_map.h](#)

## 7.53 Oscl\_Linked\_List< LLClass, Alloc > Class Template Reference

```
#include <oscl_linked_list.h>
```

Inheritance diagram for Oscl\_Linked\_List< LLClass, Alloc >::



### Public Methods

- [Oscl\\_Linked\\_List \(\)](#)
- [~Oscl\\_Linked\\_List \(\)](#)
- void [clear \(\)](#)
- int32 [dequeue\\_element \(LLClass &element\)](#)
- int32 [get\\_first \(LLClass &ele\)](#)
- int32 [get\\_next \(LLClass &ele\)](#)
- int32 [check\\_list \(\)](#)
- int32 [get\\_num\\_elements \(\)](#)
- int32 [add\\_element \(LLClass &new\\_element\)](#)
- int32 [add\\_to\\_front \(const LLClass &new\\_element\)](#)
- int32 [insert\\_element \(const LLClass &new\\_element, int index\)](#)
- int32 [get\\_element \(int32 index, LLClass &element\)](#)
- int32 [remove\\_element \(const LLClass &data\\_to\\_remove\)](#)
- int32 [get\\_index \(const LLClass &data\)](#)
- int32 [remove\\_element \(const int32 index\\_to\\_remove\)](#)
- int32 [move\\_to\\_end \(const LLClass &data\\_to\\_move\)](#)
- int32 [move\\_to\\_front \(const LLClass &data\\_to\\_move\)](#)

### 7.53.1 Detailed Description

`template<class LLClass, class Alloc> class Oscl_Linked_List< LLClass, Alloc >`

Oscl Linked List Class

### 7.53.2 Constructor & Destructor Documentation

**7.53.2.1 `template<class LLClass, class Alloc> Oscl_Linked_List< LLClass, Alloc >::Oscl_Linked_List () [inline]`**

Initialized the protected variables of list.

**7.53.2.2 template<class LLClass, class Alloc> Oscl\_Linked\_List< LLClass, Alloc >::~Oscl\_Linked\_List () [inline]**

The destructor.

### 7.53.3 Member Function Documentation

**7.53.3.1 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::add\_element (LLClass & new\_element) [inline]**

Adds new element to the list.if list is already there then it adds element at end of list otherwise it create the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

**7.53.3.2 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::add\_to\_front (const LLClass & new\_element) [inline]**

Adds new element at the start of the list.if list is already exist then it adds element at start of list otherwise it create the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

**7.53.3.3 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::check\_list () [inline]**

Debug routine: Checks the list for elements.

**Returns:**

32-bit integer, if node count is equal to number of node added to the list then returns 1 otherwise returns 0.

Reimplemented from [Oscl\\_Linked\\_List\\_Base](#).

**7.53.3.4 template<class LLClass, class Alloc> void Oscl\_Linked\_List< LLClass, Alloc >::clear () [inline]**

**7.53.3.5 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::dequeue\_element (LLClass & element) [inline]**

**7.53.3.6 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::get\_element (int32 index, LLClass & element) [inline]**

Search and returns the element in the list for passed index.

**Parameters:**

*index, element* The index is the count for the node.

**Returns:**

32-bit integer on success returns 1 otherwise returns 0.

**7.53.3.7 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::get\_first (LLClass & ele) [inline]**

Return the first element of list in passed parameter,

**Parameters:**

*ele* return the value of first element of list in this parameter

**Returns:**

32-bit interger,If first element found, it returns 1 otherwise it returns 0

**7.53.3.8 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::get\_index (const LLClass & data) [inline]**

Returns the index for requested element.

**Parameters:**

*data* the element for which index to be return.

**Returns:**

32-bit integer if data is found in the list it returns index otherwise it returns -1.

**7.53.3.9 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::get\_next (LLClass & ele) [inline]**

Return the next element of list in passed parameter,

**Parameters:**

*ele* return the value of next element of list in this parameter

**Returns:**

32-bit interger ,if next element is found in list,it returns 1 otherwise it returns 0

**7.53.3.10 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::get\_num\_elements () [inline]**

Get number of elements in the list.

**Returns:**

32-bit integer, number of elements in list.

### 7.53.3.11 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::insert\_element (const LLClass & *new\_element*, int *index*) [inline]

Inserts new element in the list. If the index is past the end of the list it creates the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

### 7.53.3.12 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::move\_to\_end (const LLClass & *data\_to\_move*) [inline]

Moves the element to end of the list

**Parameters:**

*data\_to\_move*

**Returns:**

On success returns 1 otherwise returns 0.

### 7.53.3.13 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::move\_to\_front (const LLClass & *data\_to\_move*) [inline]

Moves the element to front of the list

**Parameters:**

*data\_to\_move*

**Returns:**

On success returns 1 otherwise returns 0.

### 7.53.3.14 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::remove\_element (const int32 *index\_to\_remove*) [inline]

Removes the element for requested index.

**Parameters:**

*index\_to\_remove*

**Returns:**

on success return 1 otherwise return 0.

Reimplemented from [Oscl\\_Linked\\_List\\_Base](#).

**7.53.3.15 template<class LLClass, class Alloc> int32 Oscl\_Linked\_List< LLClass, Alloc >::remove\_element (const LLClass & *data\_to\_remove*) [inline]**

Removes the element from the list.

**Parameters:**

*data\_to\_remove*

**Returns:**

32-bit integer on if element fount in the list returns 1 otherwise returns 0.


The documentation for this class was generated from the following file:

- [oscl\\_linked\\_list.h](#)

## 7.54 Oscl\_Linked\_List\_Base Class Reference

```
#include <oscl_linked_list.h>
```

Inheritance diagram for Oscl\_Linked\_List\_Base::



### Protected Methods

- virtual ~[Oscl\\_Linked\\_List\\_Base](#) ()
- OSCL\_IMPORT\_REF void [construct](#) ([Oscl\\_Opaque\\_Type\\_Alloc\\_LL](#) \*op)
- OSCL\_IMPORT\_REF void [destroy](#) ()
- OSCL\_IMPORT\_REF int32 [get\\_first](#) ([OsclAny](#) \*ele)
- OSCL\_IMPORT\_REF int32 [get\\_next](#) ([OsclAny](#) \*ele)
- OSCL\_IMPORT\_REF int32 [check\\_list](#) ()
- OSCL\_IMPORT\_REF int32 [add\\_element](#) (const [OsclAny](#) \*new\_element)
- OSCL\_IMPORT\_REF int32 [add\\_to\\_front](#) (const [OsclAny](#) \*new\_element)
- OSCL\_IMPORT\_REF int32 [insert\\_element](#) (const [OsclAny](#) \*new\_element, int index)
- OSCL\_IMPORT\_REF int32 [get\\_element](#) (int32 index, [OsclAny](#) \*element)
- OSCL\_IMPORT\_REF int32 [remove\\_element](#) (const [OsclAny](#) \*data\_to\_remove)
- OSCL\_IMPORT\_REF int32 [get\\_index](#) (const [OsclAny](#) \*data)
- OSCL\_IMPORT\_REF int32 [remove\\_element](#) (const int32 index\_to\_remove)
- OSCL\_IMPORT\_REF int32 [move\\_to\\_end](#) (const [OsclAny](#) \*data\_to\_move)
- OSCL\_IMPORT\_REF int32 [move\\_to\\_front](#) (const [OsclAny](#) \*data\_to\_move)

### Protected Attributes

- [OsclAny](#) \* head
- [OsclAny](#) \* tail
- [OsclAny](#) \* iterator
- int32 [num\\_elements](#)
- uint32 [sizeof\\_T](#)

#### 7.54.1 Detailed Description

Oscl Linked List Base Class. A non-templated base class is used to avoid large inline functions in the [Oscl\\_Linked\\_List](#) implementation.

## 7.54.2 Constructor & Destructor Documentation

**7.54.2.1** `virtual Oscl_Linked_List_Base::~Oscl_Linked_List_Base ()` [inline, protected, virtual]

## 7.54.3 Member Function Documentation

**7.54.3.1** `OSCL_IMPORT_REF int32 Oscl_Linked_List_Base::add_element (const OsclAny * new_element)` [protected]

Adds new element to the list.if list is already there then it adds element at end of list otherwise it create the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

**7.54.3.2** `OSCL_IMPORT_REF int32 Oscl_Linked_List_Base::add_to_front (const OsclAny * new_element)` [protected]

Adds new element at the start of the list.if list is already exist then it adds element at start of list otherwise it create the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

**7.54.3.3** `OSCL_IMPORT_REF int32 Oscl_Linked_List_Base::check_list ()` [protected]

Debug routine: Checks the list for elements.

**Returns:**

32-bit integer, if node count is equal to number of node added to the list then returns 1 otherwise returns 0.

Reimplemented in [Oscl\\_Linked\\_List< LLClass, Alloc >](#).

**7.54.3.4** `OSCL_IMPORT_REF void Oscl_Linked_List_Base::construct (Oscl_Opaque_Type_Alloc_LL * op)` [protected]

**7.54.3.5** `OSCL_IMPORT_REF void Oscl_Linked_List_Base::destroy ()` [protected]

**7.54.3.6** `OSCL_IMPORT_REF int32 Oscl_Linked_List_Base::get_element (int32 index, OsclAny * element)` [protected]

Search and returns the element in the list for passed index.

**Parameters:**

*index, element* The index is the count for the node.

**Returns:**

32-bit integer on success returns 1 otherwise returns 0.

**7.54.3.7 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::get\_first (OsclAny \* *ele*)  
[protected]**

Return the first element of list in passed parameter,

**Parameters:**

*ele* return the value of first element of list in this parameter

**Returns:**

32-bit interger,If first element found, it returns 1 otherwise it returns 0

**7.54.3.8 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::get\_index (const OsclAny \* *data*)  
[protected]**

Returns the index for requested element.

**Parameters:**

*data* the element for which index to be return.

**Returns:**

32-bit integer if data is found in the list it returns index otherwise it returns -1.

**7.54.3.9 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::get\_next (OsclAny \* *ele*)  
[protected]**

Return the next element of list in passed parameter,

**Parameters:**

*ele* return the value of next element of list in this parameter

**Returns:**

32-bit interger ,if next element is found in list,it returns 1 otherwise it returns 0

**7.54.3.10 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::insert\_element (const OsclAny \*  
*new\_element, int index*) [protected]**

Inserts new element in the list. If the index is past the end of the list it creates the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

**7.54.3.11 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::move\_to\_end (const OsclAny \*  
*data\_to\_move*) [protected]**

Moves the element to end of the list

**Parameters:**

*data\_to\_move*

**Returns:**

On success returns 1 otherwise returns 0.

**7.54.3.12 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::move\_to\_front (const OsclAny \*  
*data\_to\_move*) [protected]**

Moves the element to front of the list

**Parameters:**

*data\_to\_move*

**Returns:**

On success returns 1 otherwise returns 0.

**7.54.3.13 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::remove\_element (const int32  
*index\_to\_remove*) [protected]**

Removes the element for requested index.

**Parameters:**

*index\_to\_remove*

**Returns:**

on success return 1 otherwise return 0.

Reimplemented in [Oscl\\_Linked\\_List< LLClass, Alloc >](#).

**7.54.3.14 OSCL\_IMPORT\_REF int32 Oscl\_Linked\_List\_Base::remove\_element (const OsclAny \*  
*data\_to\_remove*) [protected]**

Removes the element from the list.

**Parameters:**

*data\_to\_remove*

**Returns:**

32-bit integer on if element fount in the list returns 1 otherwise returns 0.

## 7.54.4 Field Documentation

7.54.4.1 **OsclAny\* Oscl\_Linked\_List\_Base::head** [protected]

7.54.4.2 **OsclAny\* Oscl\_Linked\_List\_Base::iterator** [protected]

7.54.4.3 **int32 Oscl\_Linked\_List\_Base::num\_elements** [protected]

7.54.4.4 **uint32 Oscl\_Linked\_List\_Base::sizeof\_T** [protected]

7.54.4.5 **OsclAny\* Oscl\_Linked\_List\_Base::tail** [protected]

The documentation for this class was generated from the following file:

- [oscl\\_linked\\_list.h](#)

## 7.55 Oscl\_Map< Key, T, Alloc, Compare > Class Template Reference

```
#include <oscl_map.h>
```

### Public Types

- `typedef Key key_type`
- `typedef Compare key_compare`
- `typedef Oscl_Pair< const Key, T > value_type`
- `typedef Oscl_Map< Key, T, Alloc, Compare > self`
- `typedef rep_type::pointer pointer`
- `typedef rep_type::reference reference`
- `typedef rep_type::const_reference const_reference`
- `typedef rep_type::iterator iterator`
- `typedef rep_type::const_iterator const_iterator`
- `typedef rep_type::size_type size_type`
- `typedef Oscl_Pair< iterator, bool > pair_iterator_bool`
- `typedef Oscl_Pair< iterator, iterator > pair_iterator_iterator`
- `typedef Oscl_Pair< const_iterator, const_iterator > pair_citerator_citerator`

### Public Methods

- `Oscl_Map (const Compare &comp=Compare())`
- `Oscl_Map (const self &x)`
- `self & operator= (const self &x)`
- `key_compare key_comp () const`
- `value_compare value_comp () const`
- `iterator begin ()`
- `const_iterator begin () const`
- `iterator end ()`
- `const_iterator end () const`
- `bool empty () const`
- `size_type size () const`
- `size_type max_size () const`
- `T & operator[ ] (const key_type &k)`
- `pair_iterator_bool insert (const value_type &x)`
- `iterator insert (iterator position, const value_type &x)`
- `void insert (const value_type *first, const value_type *last)`
- `void erase (iterator position)`
- `size_type erase (const key_type &x)`
- `void erase (iterator first, iterator last)`
- `void clear ()`
- `iterator find (const key_type &x)`
- `const_iterator find (const key_type &x) const`
- `size_type count (const key_type &x) const`
- `iterator lower_bound (const key_type &x)`
- `const_iterator lower_bound (const key_type &x) const`
- `iterator upper_bound (const key_type &x)`

- `const_iterator upper_bound (const key_type &x) const`
- `pair_iterator iterator equal_range (const key_type &x)`
- `pair_citerator citerator equal_range (const key_type &x) const`

### 7.55.1 Detailed Description

```
template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> class Oscl_Map< Key,  
T, Alloc, Compare >
```

Oscl\_Map Class. A subset of STL::Map methods. Oscl\_Map is a sorted associative container that associates objects of type Key with objects of type T. It is also a unique associative container, meaning that no two elements have the same key. Oscl\_Map uses the key to speed lookup, insertion, and deletion of elements. It is often superior to all other containers when you need to lookup an element by key value. Due to the underlying tree structure, inserts and erases can be performed in logarithmic time, where a vector would take linear time in some cases.

### 7.55.2 Member Typedef Documentation

- 7.55.2.1 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef rep_type::const_iterator Oscl_Map< Key, T, Alloc, Compare >::const_iterator`
- 7.55.2.2 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef rep_type::const_reference Oscl_Map< Key, T, Alloc, Compare >::const_reference`
- 7.55.2.3 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef rep_type::iterator Oscl_Map< Key, T, Alloc, Compare >::iterator`
- 7.55.2.4 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Compare Oscl_Map< Key, T, Alloc, Compare >::key_compare`
- 7.55.2.5 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Key Oscl_Map< Key, T, Alloc, Compare >::key_type`
- 7.55.2.6 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Oscl_Pair<const_iterator, const_iterator> Oscl_Map< Key, T, Alloc, Compare >::pair_citerator_citerator`
- 7.55.2.7 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Oscl_Pair<iterator, bool> Oscl_Map< Key, T, Alloc, Compare >::pair_iterator_bool`
- 7.55.2.8 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Oscl_Pair<iterator, iterator> Oscl_Map< Key, T, Alloc, Compare >::pair_iterator_iterator`
- 7.55.2.9 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef rep_type::pointer Oscl_Map< Key, T, Alloc, Compare >::pointer`
- 7.55.2.10 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef rep_type::reference Oscl_Map< Key, T, Alloc, Compare >::reference`
- 7.55.2.11 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Oscl_Map<Key, T, Alloc, Compare> Oscl_Map< Key, T, Alloc, Compare >::self`
- 7.55.2.12 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef rep_type::size_type Oscl_Map< Key, T, Alloc, Compare >::size_type`
- 7.55.2.13 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> typedef Oscl_Pair<const Key, T> Oscl_Map< Key, T, Alloc, Compare >::value_type`

### 7.55.3 Constructor & Destructor Documentation

- 7.55.3.1 `template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> Oscl_Map< Key, T, Alloc, Compare >::Oscl_Map (const Compare & comp = Compare() [inline])`

Creates an empty map using comp as the key compare object

**7.55.3.2 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> Oscl\_Map< Key, T, Alloc, Compare >::Oscl\_Map (const **self** & *x*) [inline]**

Oscl\_Map copy constructor

#### 7.55.4 Member Function Documentation

**7.55.4.1 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> const\_iterator Oscl\_Map< Key, T, Alloc, Compare >::begin () const [inline]**

Returns a const iterator pointing to the beginning of the map

**7.55.4.2 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> iterator Oscl\_Map< Key, T, Alloc, Compare >::begin () [inline]**

Returns an iterator pointing to the beginning of the map

**7.55.4.3 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> void Oscl\_Map< Key, T, Alloc, Compare >::clear () [inline]**

Erases all elements

**7.55.4.4 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> size\_type Oscl\_Map< Key, T, Alloc, Compare >::count (const **key\_type** & *x*) const [inline]**

Returns the number of elements with key *x*. For map this will either be 0 or 1.

**7.55.4.5 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> bool Oscl\_Map< Key, T, Alloc, Compare >::empty () const [inline]**

Returns true if map size is 0

**7.55.4.6 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> const\_iterator Oscl\_Map< Key, T, Alloc, Compare >::end () const [inline]**

Returns a const iterator pointing to the end of the map.

**7.55.4.7 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> iterator Oscl\_Map< Key, T, Alloc, Compare >::end () [inline]**

Returns an iterator pointing to the end of the map.

**7.55.4.8 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> pair\_citerator\_citerator Oscl\_Map< Key, T, Alloc, Compare >::equal\_range (const **key\_type** & *x*) const [inline]**

Finds a range containing all elements whose key is *x*

**7.55.4.9 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
 pair\_iterator\_iterator Oscl\_Map< Key, T, Alloc, Compare >::equal\_range (const  
 key\_type & x) [inline]**

Finds a range containing all elements whose key is x

**7.55.4.10 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> void  
 Oscl\_Map< Key, T, Alloc, Compare >::erase (iterator first, iterator last) [inline]**

Erases all elements in the range [first,last)

**7.55.4.11 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> size\_type  
 Oscl\_Map< Key, T, Alloc, Compare >::erase (const key\_type & x) [inline]**

Erases the element with key x

**7.55.4.12 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> void  
 Oscl\_Map< Key, T, Alloc, Compare >::erase (iterator position) [inline]**

Erases the element pointed to by position

**7.55.4.13 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
 const\_iterator Oscl\_Map< Key, T, Alloc, Compare >::find (const key\_type & x) const  
 [inline]**

Finds an element whose key is x

**7.55.4.14 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> iterator  
 Oscl\_Map< Key, T, Alloc, Compare >::find (const key\_type & x) [inline]**

Finds an element whose key is x

**7.55.4.15 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> void  
 Oscl\_Map< Key, T, Alloc, Compare >::insert (const value\_type \*first, const value\_type  
 \*last) [inline]**

Inserts the range [first,last) into the map

**7.55.4.16 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> iterator  
 Oscl\_Map< Key, T, Alloc, Compare >::insert (iterator position, const value\_type & x)  
 [inline]**

Inserts x into the map using position as a hint as to where it should be inserted

**7.55.4.17 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
`pair_iterator_bool` Oscl\_Map< Key, T, Alloc, Compare >::insert (const `value_type` & x) [inline]**

Inserts x into the map

**7.55.4.18 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
`key_compare` Oscl\_Map< Key, T, Alloc, Compare >::key\_comp () const [inline]**

Returns the key compare object used by the map

**7.55.4.19 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
`const_iterator` Oscl\_Map< Key, T, Alloc, Compare >::lower\_bound (const `key_type` & x) const [inline]**

Finds the first element whose key is not less than x

**7.55.4.20 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> iterator  
`Oscl_Map`< Key, T, Alloc, Compare >::lower\_bound (const `key_type` & x) [inline]**

Finds the first element whose key is not less than x

**7.55.4.21 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> size\_type  
`Oscl_Map`< Key, T, Alloc, Compare >::max\_size () const [inline]**

Returns the maximum possible size of the map

**7.55.4.22 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> self&  
`Oscl_Map`< Key, T, Alloc, Compare >::operator= (const `self` & x) [inline]**

Oscl\_Map assignment operator

**7.55.4.23 ]**

template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> T& Oscl\_Map< Key, T, Alloc, Compare >::operator[] (const `key_type` & k) [inline]

Returns a reference to the object that is associated with a particular key. If the map does not already contain such an object, operator[] inserts the default object `value_type()`.

**7.55.4.24 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> size\_type  
`Oscl_Map`< Key, T, Alloc, Compare >::size () const [inline]**

Returns the size of the map

**7.55.4.25 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
const\_iterator Oscl\_Map< Key, T, Alloc, Compare >::upper\_bound (const key\_type &  
x) const [inline]**

Finds the first element whose key is not greater than x

**7.55.4.26 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>> iterator  
Oscl\_Map< Key, T, Alloc, Compare >::upper\_bound (const key\_type & x) [inline]**

Finds the first element whose key is not greater than x

**7.55.4.27 template<class Key, class T, class Alloc, class Compare = Oscl\_Less<Key>>  
value\_compare Oscl\_Map< Key, T, Alloc, Compare >::value\_comp () const  
[inline]**

Returns the value compare object used by the map

The documentation for this class was generated from the following file:

- [oscl\\_map.h](#)

## 7.56 Oscl\_Map< Key, T, Alloc, Compare >::value\_compare Class Reference

```
#include <oscl_map.h>
```

### Public Methods

- bool [operator\(\)](#) (const [value\\_type](#) &x, const [value\\_type](#) &y) const

### Protected Methods

- [value\\_compare](#) (Compare c)

### Protected Attributes

- Compare [comp](#)

### Friends

- class [Oscl\\_Map< Key, T, Alloc, Compare >](#)

```
template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> class Oscl_Map< Key,  
T, Alloc, Compare >::value_compare
```

#### 7.56.1 Constructor & Destructor Documentation

```
7.56.1.1 template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> Oscl\_Map< Key, T, Alloc, Compare >::value\_compare::value\_compare (Compare c) [inline, protected]
```

#### 7.56.2 Member Function Documentation

```
7.56.2.1 template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> bool  
Oscl\_Map< Key, T, Alloc, Compare >::value\_compare::operator\(\) (const value\_type &  
x, const value\_type &y) const [inline]
```

#### 7.56.3 Friends And Related Function Documentation

```
7.56.3.1 template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> friend class  
Oscl\_Map< Key, T, Alloc, Compare > [friend]
```

#### 7.56.4 Field Documentation

```
7.56.4.1 template<class Key, class T, class Alloc, class Compare = Oscl_Less<Key>> Compare  
Oscl\_Map< Key, T, Alloc, Compare >::value\_compare::comp [protected]
```

The documentation for this class was generated from the following file:

- [oscl\\_map.h](#)

## 7.57 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock > Class Template Reference

```
#include <oscl_linked_list.h>
```

### Public Methods

- [Oscl\\_MTLinked\\_List \(\)](#)
- [~Oscl\\_MTLinked\\_List \(\)](#)
- int32 [dequeue\\_element \(LLClass &element\)](#)
- int32 [add\\_element \(LLClass &new\\_element\)](#)
- int32 [add\\_to\\_front \(LLClass &new\\_element\)](#)
- uint32 [get\\_element \(int32 index, LLClass &element\)](#)
- int32 [remove\\_element \(const LLClass &data\\_to\\_remove\)](#)
- int32 [get\\_index \(const LLClass &data\)](#)
- int32 [remove\\_element \(const int32 index\\_to\\_remove\)](#)
- int32 [move\\_to\\_end \(const LLClass &data\\_to\\_move\)](#)
- int32 [move\\_to\\_front \(const LLClass &data\\_to\\_move\)](#)

### Protected Attributes

- [Oscl\\_Linked\\_List< LLClass, Alloc > the\\_list](#)

#### 7.57.1 Detailed Description

**template<class LLClass, class Alloc, class TheLock> class Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >**

Oscl\_MTLinked\_List is a multi-threaded version of the LinkedList. It has mutex protection to allow access by different threads.

#### 7.57.2 Constructor & Destructor Documentation

**7.57.2.1 template<class LLClass, class Alloc, class TheLock> Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::Oscl\_MTLinked\_List () [inline]**

Constructor for Oscl\_MTLinked\_List

**7.57.2.2 template<class LLClass, class Alloc, class TheLock> Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::~Oscl\_MTLinked\_List () [inline]**

Destructor for Oscl\_MTLinked\_List

### 7.57.3 Member Function Documentation

#### 7.57.3.1 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::add\_element (LLClass & *new\_element*) [inline]

Adds new element to the Multi Threaded Linked list.if list is already there then it adds element at end of list otherwise it create the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

#### 7.57.3.2 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::add\_to\_front (LLClass & *new\_element*) [inline]

Adds new element at the start of the Multi Threaded Linked list. if list is already exist then it adds element at start of list otherwise it create the list and add the element as first element of list.

**Parameters:**

*new\_element* the element to be add in the list.

**Returns:**

32-bit integer on the success returns 1.

#### 7.57.3.3 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::dequeue\_element (LLClass & *element*) [inline]

#### 7.57.3.4 template<class LLClass, class Alloc, class TheLock> uint32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::get\_element (int32 *index*, LLClass & *element*) [inline]

Search and returns the element in the Multi Threaded Linked List for passed index.

**Parameters:**

*index, element* The index is the count for the node.

**Returns:**

32-bit integer on success returns 1 otherwise returns 0.

#### 7.57.3.5 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::get\_index (const LLClass & *data*) [inline]

Returns the index for requested element.

**Parameters:**

*data* the element for which index to be return.

**Returns:**

32-bit integer if data is found in the list it returns index otherwise it returns -1.

**7.57.3.6 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::move\_to\_end (const LLClass & *data\_to\_move*) [inline]**

Moves the element to end of the list

**Parameters:**

*data\_to\_move*

**Returns:**

On success returns 1 otherwise returns 0.

**7.57.3.7 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::move\_to\_front (const LLClass & *data\_to\_move*) [inline]**

Moves the element to front of the list

**Parameters:**

*data\_to\_move*

**Returns:**

On success returns 1 otherwise returns 0.

**7.57.3.8 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::remove\_element (const int32 *index\_to\_remove*) [inline]**

Removes the element for requested index.

**Parameters:**

*index\_to\_remove*

**Returns:**

on success return 1 otherwise return 0.

**7.57.3.9 template<class LLClass, class Alloc, class TheLock> int32 Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::remove\_element (const LLClass & *data\_to\_remove*) [inline]**

Removes the element from the list.

**Parameters:**

*data\_to\_remove*

**Returns:**

32-bit integer on if element fount in the list returns 1 otherwise returns 0.

## 7.57.4 Field Documentation

**7.57.4.1 template<class LLClass, class Alloc, class TheLock> Oscl\_Linked\_List<LLClass, Alloc> Oscl\_MTLinked\_List< LLClass, Alloc, TheLock >::the\_list [protected]**


The documentation for this class was generated from the following file:

- 
- [oscl\\_linked\\_list.h](#)

## 7.58 Oscl\_Opaque\_Type\_Alloc Class Reference

```
#include <oscl_opaque_type.h>
```

Inheritance diagram for Oscl\_Opaque\_Type\_Alloc::



### Public Methods

- virtual ~Oscl\_Opaque\_Type\_Alloc ()
- virtual void construct (OsclAny \*p, const OsclAny \*init\_val)=0
- virtual void destroy (OsclAny \*p)=0
- virtual OsclAny \* allocate (const uint32 size)=0
- virtual void deallocate (OsclAny \*p)=0

#### 7.58.1 Detailed Description

This class combines opaque type operations with memory allocation operations.

#### 7.58.2 Constructor & Destructor Documentation

**7.58.2.1 virtual Oscl\_Opaque\_Type\_Alloc::~Oscl\_Opaque\_Type\_Alloc () [inline, virtual]**

#### 7.58.3 Member Function Documentation

**7.58.3.1 virtual OsclAny\* Oscl\_Opaque\_Type\_Alloc::allocate (const uint32 size) [pure virtual]**

Allocate "size" bytes

**7.58.3.2 virtual void Oscl\_Opaque\_Type\_Alloc::construct (OsclAny \* p, const OsclAny \* init\_val) [pure virtual]**

Construct element at p using element at init\_val as the initial value. Both pointers must be non-NULL.

**7.58.3.3 virtual void Oscl\_Opaque\_Type\_Alloc::deallocate (OsclAny \* p) [pure virtual]**

Deallocate memory previously allocated with "allocate"

**7.58.3.4 virtual void Oscl\_Opaque\_Type\_Alloc::destroy (OsclAny \* p) [pure virtual]**

Destroy element at p.


The documentation for this class was generated from the following file:

- [oscl\\_opaque\\_type.h](#)

## 7.59 Oscl\_Opaque\_Type\_Alloc\_LL Class Reference

```
#include <oscl_opaque_type.h>
```

Inheritance diagram for Oscl\_Opaque\_Type\_Alloc\_LL::



### Public Methods

- virtual ~Oscl\_Opaque\_Type\_Alloc\_LL ()
- virtual void construct (OsclAny \*p, const OsclAny \*init\_val)=0
- virtual void destroy (OsclAny \*p)=0
- virtual OsclAny \* allocate (const uint32 size)=0
- virtual void deallocate (OsclAny \*p)=0
- virtual OsclAny \* get\_next (const OsclAny \*elem) const=0
- virtual void set\_next (OsclAny \*elem, const OsclAny \*nextelem)=0
- virtual void get\_data (OsclAny \*elem, OsclAny \*data\_val)=0
- virtual bool compare\_data (const OsclAny \*elem, const OsclAny \*data\_val) const=0

### 7.59.1 Detailed Description

This class combines opaque type operations with memory allocation operations and linked list support

### 7.59.2 Constructor & Destructor Documentation

**7.59.2.1 virtual Oscl\_Opaque\_Type\_Alloc\_LL::~Oscl\_Opaque\_Type\_Alloc\_LL () [inline, virtual]**

### 7.59.3 Member Function Documentation

**7.59.3.1 virtual OsclAny\* Oscl\_Opaque\_Type\_Alloc\_LL::allocate (const uint32 size) [pure virtual]**

Allocate "size" bytes

**7.59.3.2 virtual bool Oscl\_Opaque\_Type\_Alloc\_LL::compare\_data (const OsclAny \* elem, const OsclAny \* data\_val) const [pure virtual]**

Compare data.

**7.59.3.3 virtual void Oscl\_Opaque\_Type\_Alloc\_LL::construct (OsclAny \* p, const OsclAny \* init\_val) [pure virtual]**

Construct element at p using element at init\_val as the initial value. Both pointers must be non-NULL.

**7.59.3.4 virtual void Oscl\_Opaque\_Type\_Alloc\_LL::deallocate (OsclAny \* *p*) [pure virtual]**

Deallocate memory previously allocated with "allocate"

**7.59.3.5 virtual void Oscl\_Opaque\_Type\_Alloc\_LL::destroy (OsclAny \* *p*) [pure virtual]**

Destroy element at p.

**7.59.3.6 virtual void Oscl\_Opaque\_Type\_Alloc\_LL::get\_data (OsclAny \* *elem*, OsclAny \* *data\_val*) [pure virtual]**

Get data

**7.59.3.7 virtual OsclAny\* Oscl\_Opaque\_Type\_Alloc\_LL::get\_next (const OsclAny \* *elem*) const [pure virtual]**

Get next element in linked list.

**7.59.3.8 virtual void Oscl\_Opaque\_Type\_Alloc\_LL::set\_next (OsclAny \* *elem*, const OsclAny \* *nextelem*) [pure virtual]**

Set next element in linked list.


The documentation for this class was generated from the following file:

- [oscl\\_opaque\\_type.h](#)

## 7.60 Oscl\_Opaque\_Type\_Compare Class Reference

```
#include <oscl_opaque_type.h>
```

Inheritance diagram for Oscl\_Opaque\_Type\_Compare::



### Public Methods

- virtual ~Oscl\_Opaque\_Type\_Compare ()
- virtual void swap (OsclAny \*a, const OsclAny \*b)=0
- virtual int compare\_LT (OsclAny \*a, OsclAny \*b) const=0
- virtual int compare\_EQ (const OsclAny \*a, const OsclAny \*b) const=0

#### 7.60.1 Detailed Description

Opaque type operations with swap & comparisons.

#### 7.60.2 Constructor & Destructor Documentation

**7.60.2.1 virtual Oscl\_Opaque\_Type\_Compare::~Oscl\_Opaque\_Type\_Compare () [inline, virtual]**

#### 7.60.3 Member Function Documentation

**7.60.3.1 virtual int Oscl\_Opaque\_Type\_Compare::compare\_EQ (const OsclAny \* a, const OsclAny \* b) const [pure virtual]**

Return a==b.

Implemented in [OsclPriorityQueue< Qelem, Alloc, Container, Compare >](#), [OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl\\_Vector< TOsclReady, OsclReadyAlloc >, OsclReadyCompare >](#), and [OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl\\_Vector< TOsclReady, OsclReadyAlloc >, OsclTimerCompare >](#).

**7.60.3.2 virtual int Oscl\_Opaque\_Type\_Compare::compare\_LT (OsclAny \* a, OsclAny \* b) const [pure virtual]**

Return a<b.

Implemented in [OsclPriorityQueue< Qelem, Alloc, Container, Compare >](#), [OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl\\_Vector< TOsclReady, OsclReadyAlloc >, OsclReadyCompare >](#), and [OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl\\_Vector< TOsclReady, OsclReadyAlloc >, OsclTimerCompare >](#).

**7.60.3.3 virtual void Oscl\_Opaque\_Type\_Compare::swap (OsclAny \* a, const OsclAny \* b)  
[pure virtual]**

Swap element at "a" with element at "b". Both pointers must be non-NULL.

Implemented in [OsclPriorityQueue< Qelem, Alloc, Container, Compare >](#), [OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl\\_Vector< TOsclReady, OsclReadyAlloc >, OsclReadyCompare >](#), and [OsclPriorityQueue< TOsclReady, OsclReadyAlloc, Oscl\\_Vector< TOsclReady, OsclReadyAlloc >, OsclTimerCompare >](#).

The documentation for this class was generated from the following file:

- [oscl\\_opaque\\_type.h](#)

## 7.61 Oscl\_Pair< T1, T2 > Struct Template Reference

```
#include <oscl_tree.h>
```

### Public Methods

- [Oscl\\_Pair \(\)](#)
- [Oscl\\_Pair \(const T1 &a, const T2 &b\)](#)

### Data Fields

- [T1 first](#)
- [T2 second](#)

```
template<class T1, class T2> struct Oscl_Pair< T1, T2 >
```

#### 7.61.1 Constructor & Destructor Documentation

**7.61.1.1 template<class T1, class T2> Oscl\_Pair< T1, T2 >::Oscl\_Pair () [inline]**

**7.61.1.2 template<class T1, class T2> Oscl\_Pair< T1, T2 >::Oscl\_Pair (const T1 & a, const T2 & b) [inline]**

#### 7.61.2 Field Documentation

**7.61.2.1 template<class T1, class T2> T1 Oscl\_Pair< T1, T2 >::first**

**7.61.2.2 template<class T1, class T2> T2 Oscl\_Pair< T1, T2 >::second**


The documentation for this struct was generated from the following file:

- [oscl\\_tree.h](#)

## 7.62 Oscl\_Queue< T, Alloc > Class Template Reference

```
#include <oscl_queue.h>
```

Inheritance diagram for Oscl\_Queue< T, Alloc >::



### Public Types

- typedef T [value\\_type](#)
- typedef T \* [pointer](#)
- typedef T & [reference](#)
- typedef const T & [const\\_reference](#)
- typedef uint32 [size\\_type](#)

### Public Methods

- [Oscl\\_Queue \(\)](#)
- [Oscl\\_Queue \(uint32 n\)](#)
- virtual [~Oscl\\_Queue \(\)](#)
- void [push \(const T &x\)](#)
- [reference front \(\)](#)
- [const\\_reference front \(\) const](#)
- void [pop \(\)](#)
- [reference back \(\)](#)
- [const\\_reference back \(\) const](#)
- void [clear \(\)](#)

#### 7.62.1 Detailed Description

**template<class T, class Alloc> class Oscl\_Queue< T, Alloc >**

Oscl\_Queue Class. A subset of STL::Queue methods. Oscl\_Queue supports constant time insertion (at the end) and removal of elements at the front of the queue. It does not support insertion or removal of elements at the other ends or middle of the queue, nor random access to elements. \* No iteration capability is [currently] supplied. \* No assignment or copy capability is [currently] supplied. The number of elements in a queue can vary dynamically, and memory management is performed automatically.

## 7.62.2 Member Typedef Documentation

- 7.62.2.1 **template<class T, class Alloc> typedef const T& Oscl\_Queue< T, Alloc >::const\_reference**
- 7.62.2.2 **template<class T, class Alloc> typedef T\* Oscl\_Queue< T, Alloc >::pointer**
- 7.62.2.3 **template<class T, class Alloc> typedef T& Oscl\_Queue< T, Alloc >::reference**
- 7.62.2.4 **template<class T, class Alloc> typedef uint32 Oscl\_Queue< T, Alloc >::size\_type**
- 7.62.2.5 **template<class T, class Alloc> typedef T Oscl\_Queue< T, Alloc >::value\_type**

## 7.62.3 Constructor & Destructor Documentation

- 7.62.3.1 **template<class T, class Alloc> Oscl\_Queue< T, Alloc >::Oscl\_Queue () [inline]**

Creates an empty queue.

- 7.62.3.2 **template<class T, class Alloc> Oscl\_Queue< T, Alloc >::Oscl\_Queue (uint32 n) [inline]**

Creates an empty queue with capacity n.

### Parameters:

*n* creates a queue with n elements. The main reason for specifying n is efficiency. If you know the capacity to which your queue must grow, then it is more efficient to allocate the queue all at once rather than rely on the automatic reallocation scheme.

- 7.62.3.3 **template<class T, class Alloc> virtual Oscl\_Queue< T, Alloc >::~Oscl\_Queue () [inline, virtual]**

The destructor.

## 7.62.4 Member Function Documentation

- 7.62.4.1 **template<class T, class Alloc> const\_reference Oscl\_Queue< T, Alloc >::back () const [inline]**

Returns the last element (const)

- 7.62.4.2 **template<class T, class Alloc> reference Oscl\_Queue< T, Alloc >::back () [inline]**

Returns the last element: "back" (generally not too useful, but some debugging aids might want to find out what was just added)

- 7.62.4.3 **template<class T, class Alloc> void Oscl\_Queue< T, Alloc >::clear () [inline]**

Removes all elements.

Reimplemented from [Oscl\\_Queue\\_Base](#).

**7.62.4.4 template<class T, class Alloc> const\_reference Oscl\_Queue< T, Alloc >::front () const [inline]**

Returns the first element (const)

**7.62.4.5 template<class T, class Alloc> reference Oscl\_Queue< T, Alloc >::front () [inline]**

Returns the first element.

Reimplemented from [Oscl\\_Queue\\_Base](#).

**7.62.4.6 template<class T, class Alloc> void Oscl\_Queue< T, Alloc >::pop () [inline]**

Removes the first element

Reimplemented from [Oscl\\_Queue\\_Base](#).

**7.62.4.7 template<class T, class Alloc> void Oscl\_Queue< T, Alloc >::push (const T & x) [inline]**

Inserts a new element at the end. Queue will be grown if necessary. If allocation fails, an OSCL\_LEAVE will occur

**Parameters:**

*x* new element


The documentation for this class was generated from the following file:

- [oscl\\_queue.h](#)

## 7.63 Oscl\_Queue\_Base Class Reference

```
#include <oscl_queue.h>
```

Inheritance diagram for Oscl\_Queue\_Base::



### Public Methods

- uint32 `size () const`
- uint32 `capacity () const`
- bool `empty () const`
- OSCL\_IMPORT\_REF void `reserve (uint32 n)`

### Protected Methods

- OSCL\_IMPORT\_REF void `construct (Oscl_Opaque_Type_Alloc *aType)`
- OSCL\_IMPORT\_REF void `construct (Oscl_Opaque_Type_Alloc *aType, uint32 n)`
- virtual `~Oscl_Queue_Base ()`
- OSCL\_IMPORT\_REF void `destroy ()`
- OSCL\_IMPORT\_REF void `push (const OsclAny *x)`
- OSCL\_IMPORT\_REF void `pop ()`
- OSCL\_IMPORT\_REF void `clear ()`

### Protected Attributes

- uint32 `numelems`
- uint32 `bufsize`
- `OsclAny * elems`
- uint32 `sizeof_T`
- uint32 `ifront`
- uint32 `irear`

#### 7.63.1 Detailed Description

`Oscl_Queue_Base` is a non-templatized base class for [Oscl\\_Queue](#). The purpose of this base class is to avoid large inline routines in the [Oscl\\_Queue](#) implementation. This class is not intended for direct instantiation except by [Oscl\\_Queue](#).

#### 7.63.2 Constructor & Destructor Documentation

**7.63.2.1 virtual Oscl\_Queue\_Base::~Oscl\_Queue\_Base () [inline, protected, virtual]**

The destructor.

### 7.63.3 Member Function Documentation

#### 7.63.3.1 **uint32 Oscl\_Queue\_Base::capacity () const [inline]**

Returns the allocated memory of the queue.

#### 7.63.3.2 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::clear () [protected]**

Removes all elements.

Reimplemented in [Oscl\\_Queue< T, Alloc >](#).

#### 7.63.3.3 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::construct (Oscl\_Opaque\_Type\_Alloc \* aType, uint32 n) [protected]**

#### 7.63.3.4 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::construct (Oscl\_Opaque\_Type\_Alloc \* aType) [protected]**

#### 7.63.3.5 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::destroy () [protected]**

Like an explicit destructor call.

#### 7.63.3.6 **bool Oscl\_Queue\_Base::empty () const [inline]**

True if there are no elements in the queue

#### 7.63.3.7 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::pop () [protected]**

Removes the first element

Reimplemented in [Oscl\\_Queue< T, Alloc >](#).

#### 7.63.3.8 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::push (const OsclAny \* x) [protected]**

Inserts a new element at the end. Queue will be grown if necessary. If allocation fails, an OSCL\_LEAVE will occur

**Parameters:**

*x* new element

#### 7.63.3.9 **OSCL\_IMPORT\_REF void Oscl\_Queue\_Base::reserve (uint32 n)**

Reallocates memory if necessary to a capacity of *n* elements. The main reason for reserve is efficiency. If you know the capacity to which your vector must grow, then it is more efficient to allocate the vector all at once rather than rely on the automatic reallocation scheme. This also helps control the invalidation of iterators.

**Parameters:**

*n* size of vector

**7.63.3.10 uint32 Oscl\_Queue\_Base::size () const [inline]**

Returns the size of the queue.

#### 7.63.4 Field Documentation

**7.63.4.1 uint32 Oscl\_Queue\_Base::bufsize [protected]****7.63.4.2 OsclAny\* Oscl\_Queue\_Base::elems [protected]****7.63.4.3 uint32 Oscl\_Queue\_Base::ifront [protected]****7.63.4.4 uint32 Oscl\_Queue\_Base::irear [protected]****7.63.4.5 uint32 Oscl\_Queue\_Base::numelems [protected]****7.63.4.6 uint32 Oscl\_Queue\_Base::sizeof\_T [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_queue.h](#)




## 7.64 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc > Class Template Reference

### 7.64 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc > Class Template Reference

```
#include <oscl_tree.h>
```

Inheritance diagram for Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::



#### Public Types

- typedef Key `key_type`
- typedef Value `value_type`
- typedef `value_type * pointer`
- typedef `const value_type * const_pointer`
- typedef `value_type & reference`
- typedef `const value_type & const_reference`
- typedef `Oscl_Rb_Tree_Node< Value >::link_type link_type`
- typedef `Oscl_Rb_Tree_Iterator< value_type > iterator`
- typedef `Oscl_Rb_Tree_Const_Iterator< value_type > const_iterator`
- typedef uint32 `size_type`
- typedef int32 `difference_type`

#### Public Methods

- `Oscl_Rb_Tree (const Compare &comp=Compare())`
- `Oscl_Rb_Tree (const Oscl_Rb_Tree< Key, Value, KeyOfValue, Compare, Alloc > &x)`
- `~Oscl_Rb_Tree ()`
- `Oscl_Rb_Tree< Key, Value, KeyOfValue, Compare, Alloc > & operator= (const Oscl_Rb_Tree< Key, Value, KeyOfValue, Compare, Alloc > &x)`
- `iterator begin ()`
- `const_iterator begin () const`
- `iterator end ()`
- `const_iterator end () const`
- `bool empty () const`
- `size_type size () const`
- `size_type max_size () const`
- `Oscl_Pair< iterator, bool > insert_unique (const value_type &v)`
- `iterator insert_unique (iterator position, const value_type &v)`
- `void insert_unique (const iterator first, const iterator last)`
- `void insert_unique (const value_type *first, const value_type *last)`
- `void erase (iterator position)`
- `size_type erase (const key_type &x)`
- `void erase (iterator first, iterator last)`
- `void erase (const key_type *first, const key_type *last)`



## 7.64 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc > Class Template Reference

- void [clear \(\)](#)
- [iterator find \(const Key &k\)](#)
- [const\\_iterator find \(const Key &k\) const](#)
- [size\\_type count \(const Key &k\) const](#)
- [iterator lower\\_bound \(const Key &k\)](#)
- [const\\_iterator lower\\_bound \(const Key &k\) const](#)
- [iterator upper\\_bound \(const Key &k\)](#)
- [const\\_iterator upper\\_bound \(const Key &k\) const](#)
- [Oscl\\_Pair< iterator, iterator > equal\\_range \(const Key &k\)](#)
- [Oscl\\_Pair< const\\_iterator, const\\_iterator > equal\\_range \(const Key &k\) const](#)



## 7.64 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc > Class Template Reference

template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> class Oscl\_Rb\_-Tree< Key, Value, KeyOfValue, Compare, Alloc >

### 7.64.1 Member Typedef Documentation

7.64.1.1 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef Oscl\_Rb\_Tree\_Const\_Iterator<value\_type> Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::const\_iterator

7.64.1.2 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef const value\_type\* Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::const\_pointer

7.64.1.3 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef const value\_type& Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::const\_reference

7.64.1.4 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef int32 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::difference\_type

7.64.1.5 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef Oscl\_Rb\_Tree\_Iterator<value\_type> Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::iterator

7.64.1.6 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef Key Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::key\_type

7.64.1.7 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef Oscl\_Rb\_Tree\_Node<Value>::link\_type Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::link\_type

7.64.1.8 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef value\_type\* Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::pointer

7.64.1.9 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef value\_type& Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::reference

7.64.1.10 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef uint32 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::size\_type

7.64.1.11 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> typedef Value Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::value\_type

### 7.64.2 Constructor & Destructor Documentation

7.64.2.1 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::Oscl\_Rb\_Tree (const Compare & comp = Compare() ) [inline]

7.64.2.2 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::Oscl\_Rb\_Tree (const Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc > & x) [inline]

7.64.2.3 template<class Key, class Value, class KeyOfValue, class Compare, class Alloc> Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc >::~Oscl\_Rb\_Tree ()




## 7.64 Oscl\_Rb\_Tree< Key, Value, KeyOfValue, Compare, Alloc > Class Template Reference

- [oscl\\_tree.h](#)

## 7.65 Oscl\_Rb\_Tree\_Base Class Reference

```
#include <oscl_tree.h>
```

Inheritance diagram for Oscl\_Rb\_Tree\_Base::



### Public Types

- `typedef Oscl_Rb_Tree_Node_Base::base_link_type base_link_type`

### Public Methods

- `OSCL_IMPORT_REF void rotate_left (base_link_type x, base_link_type &root)`
- `OSCL_IMPORT_REF void rotate_right (base_link_type x, base_link_type &root)`
- `OSCL_IMPORT_REF void rebalance (base_link_type x, base_link_type &root)`
- `OSCL_IMPORT_REF base_link_type rebalance_for_erase (base_link_type z, base_link_type &root, base_link_type &leftmost, base_link_type &rightmost)`

#### 7.65.1 Member Typedef Documentation

##### 7.65.1.1 `typedef Oscl_Rb_Tree_Node_Base::base_link_type Oscl_Rb_Tree_Base::base_link_type`

#### 7.65.2 Member Function Documentation

##### 7.65.2.1 `OSCL_IMPORT_REF void Oscl_Rb_Tree_Base::rebalance (base_link_type x, base_link_type &root)`

##### 7.65.2.2 `OSCL_IMPORT_REF base_link_type Oscl_Rb_Tree_Base::rebalance_for_erase (base_link_type z, base_link_type &root, base_link_type &leftmost, base_link_type &rightmost)`

##### 7.65.2.3 `OSCL_IMPORT_REF void Oscl_Rb_Tree_Base::rotate_left (base_link_type x, base_link_type &root)`

##### 7.65.2.4 `OSCL_IMPORT_REF void Oscl_Rb_Tree_Base::rotate_right (base_link_type x, base_link_type &root)`

The documentation for this class was generated from the following file:

- `oscl_tree.h`

## 7.66 Oscl\_Rb\_Tree\_Const\_Iterator< Value > Struct Template Reference

```
#include <oscl_tree.h>
```

### Public Types

- `typedef Value value_type`
- `typedef const value_type & reference`
- `typedef const value_type * pointer`
- `typedef Oscl_Rb_Tree_Const_Iterator< Value > const_iterator`
- `typedef Oscl_Rb_Tree_Const_Iterator< Value > self`
- `typedef Oscl_Rb_Tree_Node_Base * base_link_type`
- `typedef Oscl_Rb_Tree_Node< Value > * link_type`

### Public Methods

- `Oscl_Rb_Tree_Const_Iterator()`
- `Oscl_Rb_Tree_Const_Iterator(link_type x)`
- `Oscl_Rb_Tree_Const_Iterator(const const_iterator &it)`
- `reference operator * () const`
- `pointer operator → () const`
- `bool operator==(const self &x)`
- `bool operator!=(const self &x)`
- `self & operator++()`
- `self operator++(int)`
- `self & operator--()`
- `self operator--(int)`

### Data Fields

- `base_link_type node`

```
template<class Value> struct Oscl_Rb_Tree_Const_Iterator< Value >
```

### 7.66.1 Member Typedef Documentation

- 7.66.1.1 `template<class Value> typedef Oscl_Rb_Tree_Node_Base* Oscl_Rb_Tree_Const_Iterator< Value >::base_link_type`
- 7.66.1.2 `template<class Value> typedef Oscl_Rb_Tree_Const_Iterator<Value> Oscl_Rb_Tree_Const_Iterator< Value >::const_iterator`
- 7.66.1.3 `template<class Value> typedef Oscl_Rb_Tree_Node<Value>* Oscl_Rb_Tree_Const_Iterator< Value >::link_type`
- 7.66.1.4 `template<class Value> typedef const value_type* Oscl_Rb_Tree_Const_Iterator< Value >::pointer`
- 7.66.1.5 `template<class Value> typedef const value_type& Oscl_Rb_Tree_Const_Iterator< Value >::reference`
- 7.66.1.6 `template<class Value> typedef Oscl_Rb_Tree_Const_Iterator<Value> Oscl_Rb_Tree_Const_Iterator< Value >::self`
- 7.66.1.7 `template<class Value> typedef Value Oscl_Rb_Tree_Const_Iterator< Value >::value_type`

### 7.66.2 Constructor & Destructor Documentation

- 7.66.2.1 `template<class Value> Oscl_Rb_Tree_Const_Iterator< Value >::Oscl_Rb_Tree_Const_Iterator () [inline]`
- 7.66.2.2 `template<class Value> Oscl_Rb_Tree_Const_Iterator< Value >::Oscl_Rb_Tree_Const_Iterator (link_type x) [inline]`
- 7.66.2.3 `template<class Value> Oscl_Rb_Tree_Const_Iterator< Value >::Oscl_Rb_Tree_Const_Iterator (const const_iterator & it) [inline]`

### 7.66.3 Member Function Documentation

- 7.66.3.1 `template<class Value> reference Oscl_Rb_Tree_Const_Iterator< Value >::operator * () const [inline]`
- 7.66.3.2 `template<class Value> bool Oscl_Rb_Tree_Const_Iterator< Value >::operator!= (const self & x) [inline]`
- 7.66.3.3 `template<class Value> self Oscl_Rb_Tree_Const_Iterator< Value >::operator++ (int) [inline]`
- 7.66.3.4 `template<class Value> self& Oscl_Rb_Tree_Const_Iterator< Value >::operator++ () [inline]`
- 7.66.3.5 `template<class Value> self Oscl_Rb_Tree_Const_Iterator< Value >::operator- (int) [inline]`
- 7.66.3.6 `template<class Value> self& Oscl_Rb_Tree_Const_Iterator< Value >::operator- () [inline]`

- 
- [oscl\\_tree.h](#)

## 7.67 Oscl\_Rb\_Tree\_Iterator< Value > Struct Template Reference

```
#include <oscl_tree.h>
```

### Public Types

- `typedef Value value_type`
- `typedef value_type & reference`
- `typedef value_type * pointer`
- `typedef Oscl_Rb_Tree_Iterator< Value > iterator`
- `typedef Oscl_Rb_Tree_Iterator< Value > self`
- `typedef Oscl_Rb_Tree_Node_Base * base_link_type`
- `typedef Oscl_Rb_Tree_Node< Value > * link_type`

### Public Methods

- `Oscl_Rb_Tree_Iterator ()`
- `Oscl_Rb_Tree_Iterator (link_type x)`
- `Oscl_Rb_Tree_Iterator (const iterator &it)`
- `reference operator * () const`
- `pointer operator → () const`
- `bool operator== (const self &x)`
- `bool operator!= (const self &x)`
- `self & operator++ ()`
- `self operator++ (int)`
- `self & operator– ()`
- `self operator– (int)`

### Data Fields

- `base_link_type node`

---

```
template<class Value> struct Oscl_Rb_Tree_Iterator< Value >
```

### 7.67.1 Member Typedef Documentation

- 7.67.1.1 template<class Value> typedef Oscl\_Rb\_Tree\_Node\_Base\* Oscl\_Rb\_Tree\_Iterator< Value >::base\_link\_type
- 7.67.1.2 template<class Value> typedef Oscl\_Rb\_Tree\_Iterator<Value> Oscl\_Rb\_Tree\_Iterator< Value >::iterator
- 7.67.1.3 template<class Value> typedef Oscl\_Rb\_Tree\_Node<Value>\* Oscl\_Rb\_Tree\_Iterator< Value >::link\_type
- 7.67.1.4 template<class Value> typedef value\_type\* Oscl\_Rb\_Tree\_Iterator< Value >::pointer
- 7.67.1.5 template<class Value> typedef value\_type& Oscl\_Rb\_Tree\_Iterator< Value >::reference
- 7.67.1.6 template<class Value> typedef Oscl\_Rb\_Tree\_Iterator<Value> Oscl\_Rb\_Tree\_Iterator< Value >::self
- 7.67.1.7 template<class Value> typedef Value Oscl\_Rb\_Tree\_Iterator< Value >::value\_type

### 7.67.2 Constructor & Destructor Documentation

- 7.67.2.1 template<class Value> Oscl\_Rb\_Tree\_Iterator< Value >::Oscl\_Rb\_Tree\_Iterator () [inline]
- 7.67.2.2 template<class Value> Oscl\_Rb\_Tree\_Iterator< Value >::Oscl\_Rb\_Tree\_Iterator (link\_type x) [inline]
- 7.67.2.3 template<class Value> Oscl\_Rb\_Tree\_Iterator< Value >::Oscl\_Rb\_Tree\_Iterator (const iterator & it) [inline]

### 7.67.3 Member Function Documentation


- 7.67.3.1 template<class Value> reference Oscl\_Rb\_Tree\_Iterator< Value >::operator \* () const [inline]
- 7.67.3.2 template<class Value> bool Oscl\_Rb\_Tree\_Iterator< Value >::operator!= (const self & x) [inline]
- 7.67.3.3 template<class Value> self Oscl\_Rb\_Tree\_Iterator< Value >::operator++ (int) [inline]
- 7.67.3.4 template<class Value> self& Oscl\_Rb\_Tree\_Iterator< Value >::operator++ () [inline]
- 7.67.3.5 template<class Value> self Oscl\_Rb\_Tree\_Iterator< Value >::operator- (int) [inline]
- 7.67.3.6 template<class Value> self& Oscl\_Rb\_Tree\_Iterator< Value >::operator- () [inline]
- 7.67.3.7 template<class Value> pointer Oscl\_Rb\_Tree\_Iterator< Value >::operator -> () const [inline]

- [oscl\\_tree.h](#)

## 7.68 Oscl\_Rb\_Tree\_Node< Value > Struct Template Reference

```
#include <oscl_tree.h>
```

Inheritance diagram for Oscl\_Rb\_Tree\_Node< Value >::



### Public Types

- `typedef Value value_type`
- `typedef Oscl_Rb_Tree_Node< Value > * link_type`

### Data Fields

- `value_type value`

```
template<class Value> struct Oscl_Rb_Tree_Node< Value >
```

#### 7.68.1 Member Typedef Documentation

**7.68.1.1 template<class Value> typedef Oscl\_Rb\_Tree\_Node<Value>\* Oscl\_Rb\_Tree\_Node< Value >::link\_type**

**7.68.1.2 template<class Value> typedef Value Oscl\_Rb\_Tree\_Node< Value >::value\_type**

#### 7.68.2 Field Documentation

**7.68.2.1 template<class Value> value\_type Oscl\_Rb\_Tree\_Node< Value >::value**


The documentation for this struct was generated from the following file:

- `oscl_tree.h`

## 7.69 Oscl\_Rb\_Tree\_Node\_Base Struct Reference

```
#include <oscl_tree.h>
```

Inheritance diagram for Oscl\_Rb\_Tree\_Node\_Base::



### Public Types

- `typedef Oscl_Rb_Tree_Node_Base * base_link_type`
- `typedef enum Oscl_Rb_Tree_Node_Base::RedBl color_type`
- `enum RedBl { red, black }`

### Static Public Methods

- `base_link_type minimum (base_link_type x)`
- `base_link_type maximum (base_link_type x)`

### Data Fields

- `color_type color`
- `base_link_type parent`
- `base_link_type left`
- `base_link_type right`

#### 7.69.1 Member Typedef Documentation

7.69.1.1 `typedef Oscl_Rb_Tree_Node_Base* Oscl_Rb_Tree_Node_Base::base_link_type`

7.69.1.2 `typedef enum Oscl_Rb_Tree_Node_Base::RedBl Oscl_Rb_Tree_Node_Base::color_type`

#### 7.69.2 Member Enumeration Documentation

7.69.2.1 `enum Oscl_Rb_Tree_Node_Base::RedBl`

Enumeration values:

`red`

`black`

### 7.69.3 Member Function Documentation

7.69.3.1 **base\_link\_type** Oscl\_Rb\_Tree\_Node\_Base::maximum (**base\_link\_type** *x*) [inline, static]

7.69.3.2 **base\_link\_type** Oscl\_Rb\_Tree\_Node\_Base::minimum (**base\_link\_type** *x*) [inline, static]

### 7.69.4 Field Documentation

7.69.4.1 **color\_type** Oscl\_Rb\_Tree\_Node\_Base::color

7.69.4.2 **base\_link\_type** Oscl\_Rb\_Tree\_Node\_Base::left

7.69.4.3 **base\_link\_type** Oscl\_Rb\_Tree\_Node\_Base::parent

7.69.4.4 **base\_link\_type** Oscl\_Rb\_Tree\_Node\_Base::right

The documentation for this struct was generated from the following file:

- [oscl\\_tree.h](#)

## 7.70 Oscl\_Select1st< V, U > Struct Template Reference

```
#include <oscl_map.h>
```

### Public Methods

- const U & [operator\(\)](#) (const V &x) const

```
template<class V, class U> struct Oscl_Select1st< V, U >
```

#### 7.70.1 Member Function Documentation

**7.70.1.1 template<class V, class U> const U& Oscl\_Select1st< V, U >::operator() (const V & x)  
const [inline]**


The documentation for this struct was generated from the following file:

- [oscl\\_map.h](#)

## 7.71 OSCL\_StackString< MaxBufSize > Class Template Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_StackString< MaxBufSize >::



### Public Types

- `typedef OSCL_String::chartype chartype`
- `typedef TOSCL_StringOp optype`
- `typedef OSCL_wString::chartype other_chartype`

### Public Methods

- `OSCL_StackString()`
- `OSCL_StackString(const OSCL_StackString &src)`
- `OSCL_StackString(const OSCL_String &src)`
- `OSCL_StackString(const chartype *cstr)`
- `OSCL_StackString(const chartype *buf, uint32 length)`
- `~OSCL_StackString()`
- `uint32 get_size() const`
- `uint32 get_maxsize() const`
- `const chartype * get_cstr() const`
- `chartype * get_str() const`
- `OSCL_StackString & operator=(const OSCL_StackString &src)`
- `OSCL_StackString & operator=(const OSCL_String &src)`
- `OSCL_StackString & operator=(const chartype *cstr)`
- `void set(const chartype *buf, uint32 length)`
- `void set(const other_chartype *buf, optype op)`
- `void set(const other_chartype *buf, uint32 length, optype op)`

### Friends

- `class OSCL_String`

### 7.71.1 Detailed Description

```
template<uint32 MaxBufSize> class OSCL_StackString< MaxBufSize >
```

OSCL\_StackString is a simple string class, compatible with regular character array strings.

The string array is fixed length, is allocated from the stack, and is modifiable. Operations that update the string will automatically truncate it to fit the fixed size storage. This is recommended for use for short strings (<255). Use [OSCL\\_HeapString](#) for very large strings to avoid stack overflow.

**Parameters:**

*C*: type of character.

*MaxBufSize*: maximum string length not including null terminator.

### 7.71.2 Member Typedef Documentation

**7.71.2.1 template<uint32 MaxBufSize> typedef OSCL\_String::chartype OSCL\_StackString< MaxBufSize >::chartype**

Reimplemented from [OSCL\\_String](#).

**7.71.2.2 template<uint32 MaxBufSize> typedef TOSCL\_StringOp OSCL\_StackString< MaxBufSize >::optype**

**7.71.2.3 template<uint32 MaxBufSize> typedef OSCL\_wString::chartype OSCL\_StackString< MaxBufSize >::other\_chartype**

### 7.71.3 Friends And Related Function Documentation

**7.71.3.1 template<uint32 MaxBufSize> friend class OSCL\_String [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.72 oscl\_stat\_buf Struct Reference

```
#include <oscl_file_dir_utils.h>
```

### Data Fields

- uint32 [mode](#)
- uint32 [perms](#)

#### 7.72.1 Field Documentation

##### 7.72.1.1 uint32 oscl\_stat\_buf::mode

##### 7.72.1.2 uint32 oscl\_stat\_buf::perms


The documentation for this struct was generated from the following file:

- [oscl\\_file\\_dir\\_utils.h](#)

## 7.73 OSCL\_String Class Reference

```
#include <oscl_string.h>
```

Inheritance diagram for OSCL\_String::



### Public Types

- `typedef char chartype`

### Public Methods

- `virtual uint32 get_size () const=0`
- `virtual uint32 get_maxsize () const=0`
- `virtual const chartype * get_cstr () const=0`
- `virtual bool is_writable () const`
- `virtual chartype * get_str () const=0`
- `OSCL_String & operator=(const OSCL_String &src)`
- `OSCL_String & operator=(const chartype *cstr)`
- `OSCL_String & operator+=(const OSCL_String &src)`
- `OSCL_String & operator+=(const chartype *cstr)`
- `OSCL_String & operator+=(const chartype c)`
- `bool operator==(const OSCL_String &src) const`
- `bool operator!=(const OSCL_String &src) const`
- `bool operator< (const OSCL_String &src) const`
- `bool operator<= (const OSCL_String &src) const`
- `bool operator> (const OSCL_String &src) const`
- `bool operator>= (const OSCL_String &src) const`
- `bool operator==(const chartype *cstr) const`
- `chartype operator[] (uint32 index) const`
- `virtual chartype read (uint32 index) const`
- `virtual uint32 setrep_to_char (const oscl_wchar *src, uint32 len, TOSCL_StringOp op, Oscl_DefAlloc *aAlloc)`
- `virtual int8 hash () const`
- `virtual void write (uint32 index, chartype c)`
- `virtual void write (uint32 offset, uint32 length, const chartype *buf)`

## Protected Methods

- [OSCL\\_String \(\)](#)
- [virtual ~OSCL\\_String \(\)](#)
- [virtual void set\\_rep \(const chartype \\*cstr\)=0](#)
- [virtual void append\\_rep \(const chartype \\*cstr\)=0](#)
- [virtual void set\\_rep \(const OSCL\\_String &src\)=0](#)
- [virtual void append\\_rep \(const OSCL\\_String &src\)=0](#)
- [virtual void set\\_len \(uint32 len\)=0](#)

### 7.73.1 Detailed Description

A common base class for string classes with "char" character format

### 7.73.2 Member Typedef Documentation

#### 7.73.2.1 `typedef char OSCL_String::chartype`

Reimplemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), [OSCL\\_FastString](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

### 7.73.3 Constructor & Destructor Documentation

#### 7.73.3.1 `OSCL_String::OSCL_String () [protected]`

#### 7.73.3.2 `virtual OSCL_String::~OSCL_String () [protected, virtual]`

### 7.73.4 Member Function Documentation

#### 7.73.4.1 `virtual void OSCL_String::append_rep (const OSCL_String & src) [protected, pure virtual]`

Append the input string to the current string. The string may be truncated to fit the available storage.

#### 7.73.4.2 `virtual void OSCL_String::append_rep (const chartype * cstr) [protected, pure virtual]`

Append the input null-terminated string to the current string. The string may be truncated to fit the available storage.

#### 7.73.4.3 `virtual const chartype* OSCL_String::get_cstr () [pure virtual]`

This function returns the C-style string for read access.

Implemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), [OSCL\\_FastString](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

**7.73.4.4 virtual uint32 OSCL\_String::get\_maxsize () [pure virtual]**

This function returns the maximum available storage size, not including null terminator. The maximum size may be larger than the current string size.

Implemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), [OSCL\\_FastString](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

**7.73.4.5 virtual uint32 OSCL\_String::get\_size () [pure virtual]**

This function returns the string size not including the null-terminator.

Implemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), [OSCL\\_FastString](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

**7.73.4.6 virtual chartype\* OSCL\_String::get\_str () [pure virtual]**

This function returns the C-style string for write access. If the string is not writable it returns NULL.

Implemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), [OSCL\\_FastString](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

**7.73.4.7 virtual int8 OSCL\_String::hash () [virtual]**

This function performs a hash operation on the string. If the string is not writable, the function leaves.

**7.73.4.8 virtual bool OSCL\_String::is\_writable () [virtual]**

This function returns true if the string is writable.

**7.73.4.9 bool OSCL\_String::operator!= (const OSCL\_String & src) const****7.73.4.10 OSCL\_String& OSCL\_String::operator+= (const chartype c)**

Append operator. This operator appends the input character to this object. The string may be truncated to fit available storage.

**7.73.4.11 OSCL\_String& OSCL\_String::operator+= (const chartype \* cstr)**

Append operator. This operator appends the input string to this object. The string may be truncated to fit available storage.

**am:** null-terminated string

**7.73.4.12 OSCL\_String& OSCL\_String::operator+= (const OSCL\_String & src)**

Append operator. This operator appends the input string to this object. The string may be truncated to fit available storage.

**7.73.4.13 bool OSCL\_String::operator< (const OSCL\_String & src) const**

**7.73.4.14 bool OSCL\_String::operator<= (const OSCL\_String & src) const**

**7.73.4.15 OSCL\_String& OSCL\_String::operator= (const chartype \* cstr)**

Assignment operator

**am:** null-terminated string

Reimplemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), [OSCL\\_FastString](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

**7.73.4.16 OSCL\_String& OSCL\_String::operator= (const OSCL\_String & src)**

Assignment operator

Reimplemented in [OSCL\\_HeapString< Alloc >](#), [OSCL\\_HeapStringA](#), [OSCL\\_StackString< MaxBufSize >](#), and [OSCL\\_HeapString< OsclMemAllocator >](#).

**7.73.4.17 bool OSCL\_String::operator== (const chartype \* cstr) const**

Comparison operator

**am:** null-terminated string

**7.73.4.18 bool OSCL\_String::operator== (const OSCL\_String & src) const**

Comparison operators

**7.73.4.19 bool OSCL\_String::operator> (const OSCL\_String & src) const**

**7.73.4.20 bool OSCL\_String::operator>= (const OSCL\_String & src) const**

**7.73.4.21 ]**

**chartype OSCL\_String::operator[ ] (uint32 index) const**

This is subscript notation to access a character at the given position. If the index is outside the current size range then the function leaves.

**7.73.4.22 virtual chartype OSCL\_String::read (uint32 index) const [virtual]**

This function returns the character at the given position. If the index is outside the current size range then the function leaves.

**7.73.4.23 virtual void OSCL\_String::set\_len (uint32 len) [protected, pure virtual]**

Update the length of the string. This function will only be called when the string is writable.

**7.73.4.24 virtual void OSCL\_String::set\_rep (const OSCL\_String & src) [protected, pure virtual]**

Set string representation to input string.

**7.73.4.25 virtual void OSCL\_String::set\_rep (const chartype \* cstr) [protected, pure virtual]**

Set string representation to input null-terminated string.

**7.73.4.26 virtual uint32 OSCL\_String::setrep\_to\_char (const oscl\_wchar \* src, uint32 len, TOSCL\_StringOp op, Oscl\_DefAlloc \* aAlloc) [virtual]**

This function allocates a temp storage for performing one of the following operations based on TOSCL\_StringOp

- compress src string from oscl\_wchar to utf8.
- convert src string from oscl\_wchar to utf8. call parent [set\\_rep\(\)](#) to copy resulting string.

**Parameters:**

*src*: reference input string

*len*: length of string to operate on

*op*: type operation mentioned above

*aAlloc*: optional, memory allocator if available

**Returns:**

length of compressed or converted string exclude terminated '\0'.

**7.73.4.27 virtual void OSCL\_String::write (uint32 offset, uint32 length, const chartype \* buf) [virtual]**

This function replaces characters at the specified offset within the current string. If the string is not writable, the function leaves. The characters may be truncated to fit the current storage.

**Parameters:**

*offset*: the offset into the existing string buffer

*length*: number of characters to copy.

*ptr*: character buffer, not necessarily null-terminated.

**7.73.4.28 virtual void OSCL\_String::write (uint32 index, chartype c) [virtual]**

This function stores a character at the specified position. If the string is not writable, the function leaves. If the index is outside the current size range then the function leaves.


The documentation for this class was generated from the following file:

- [oscl\\_string.h](#)

## 7.74 Oscl\_Tag< Alloc > Struct Template Reference

```
#include <oscl_tagtree.h>
```

Inheritance diagram for Oscl\_Tag< Alloc >::



### Public Methods

- [Oscl\\_Tag](#) (const Oscl\_Tag< Alloc > &t)
- [Oscl\\_Tag](#) (const [tag\\_base\\_type](#) &t)
- [~Oscl\\_Tag](#) ()
- bool [operator<](#) (const Oscl\_Tag< Alloc > &x) const

### Data Fields

- [Oscl\\_TAlloc< tag\\_base\\_unit, Alloc > tagAllocator](#)
- [tag\\_base\\_type tag](#)

```
template<class Alloc> struct Oscl_Tag< Alloc >
```

#### 7.74.1 Constructor & Destructor Documentation

**7.74.1.1 template<class Alloc> Oscl\_Tag< Alloc >::Oscl\_Tag (const Oscl\_Tag< Alloc > & t)**  
`[inline]`

**7.74.1.2 template<class Alloc> Oscl\_Tag< Alloc >::Oscl\_Tag (const tag\_base\_type & t)**  
`[inline]`

**7.74.1.3 template<class Alloc> Oscl\_Tag< Alloc >::~Oscl\_Tag ()** `[inline]`

#### 7.74.2 Member Function Documentation

**7.74.2.1 template<class Alloc> bool Oscl\_Tag< Alloc >::operator< (const Oscl\_Tag< Alloc > & x) const** `[inline]`

#### 7.74.3 Field Documentation

**7.74.3.1 template<class Alloc> tag\_base\_type Oscl\_Tag< Alloc >::tag**

**7.74.3.2 template<class Alloc> Oscl\_TAlloc<tag\_base\_unit, Alloc> Oscl\_Tag< Alloc >::tagAllocator**


The documentation for this struct was generated from the following file:

- [oscl\\_tagtree.h](#)

## 7.75 Oscl\_Tag\_Base Struct Reference

```
#include <oscl_tagtree.h>
```

Inheritance diagram for Oscl\_Tag\_Base::



### Public Types

- `typedef char tag_base_unit`
- `typedef tag_base_unit * tag_base_type`
- `typedef uint32 size_type`

### Public Methods

- `bool operator() (const tag_base_type &x, const tag_base_type &y) const`
- `size_type tag_len (const tag_base_type &t) const`
- `tag_base_type tag_copy (tag_base_type &dest, const tag_base_type &src) const`
- `int32 tag_cmp (const tag_base_type &x, const tag_base_type &y) const`
- `OSCL_IMPORT_REF tag_base_type tag_ancestor (tag_base_type &dest, const tag_base_type &src) const`
- `OSCL_IMPORT_REF size_type tag_depth (const tag_base_type &t) const`

### 7.75.1 Member Typedef Documentation

- 7.75.1.1 `typedef uint32 Oscl_Tag_Base::size_type`
- 7.75.1.2 `typedef tag_base_unit* Oscl_Tag_Base::tag_base_type`
- 7.75.1.3 `typedef char Oscl_Tag_Base::tag_base_unit`

### 7.75.2 Member Function Documentation

- 7.75.2.1 `bool Oscl_Tag_Base::operator() (const tag_base_type & x, const tag_base_type & y) const [inline]`
- 7.75.2.2 `OSCL_IMPORT_REF tag_base_type Oscl_Tag_Base::tag_ancestor (tag_base_type & dest, const tag_base_type & src) const`
- 7.75.2.3 `int32 Oscl_Tag_Base::tag_cmp (const tag_base_type & x, const tag_base_type & y) const [inline]`
- 7.75.2.4 `tag_base_type Oscl_Tag_Base::tag_copy (tag_base_type & dest, const tag_base_type & src) const [inline]`
- 7.75.2.5 `OSCL_IMPORT_REF size_type Oscl_Tag_Base::tag_depth (const tag_base_type & t) const`
- 7.75.2.6 `size_type Oscl_Tag_Base::tag_len (const tag_base_type & t) const [inline]`

The documentation for this struct was generated from the following file:

- [oscl\\_tagtree.h](#)

## 7.76 Oscl\_TagTree< T, Alloc > Class Template Reference

```
#include <oscl_tagtree.h>
```

### Public Types

- `typedef Oscl_Tag< Alloc > tag_type`
- `typedef tag_type::tag_base_type tag_base_type`
- `typedef Oscl_Vector< Node *, Alloc > children_type`
- `typedef Node node_type`
- `typedef node_type * node_ptr`
- `typedef Oscl_Map< const tag_base_type, node_ptr, Alloc, Oscl_Tag_Base > map_type`
- `typedef map_type::size_type size_type`
- `typedef map_type::value_type value_type`
- `typedef Oscl_Pair< iterator, bool > pair_iterator_bool`

### Public Methods

- `Oscl_TagTree (size_type max_depth=0)`
- `Oscl_TagTree (const Oscl_TagTree< T, Alloc > &x)`
- `Oscl_TagTree< T, Alloc > & operator= (const Oscl_TagTree< T, Alloc > &x)`
- `~Oscl_TagTree ()`
- `iterator begin ()`
- `const_iterator begin () const`
- `iterator end ()`
- `const_iterator end () const`
- `bool empty () const`
- `size_type size () const`
- `T & operator[ ] (const tag_base_type &t)`
- `pair_iterator_bool insert (const tag_base_type &t, const T &x)`
- `void erase (iterator position)`
- `size_type erase (const tag_base_type &x)`
- `void clear ()`
- `iterator find (const tag_base_type &x)`
- `size_type count (const tag_base_type &x) const`

### 7.76.1 Detailed Description

`template<class T, class Alloc> class Oscl_TagTree< T, Alloc >`

Oscl\_TagTree Class.

## 7.76.2 Member Typedef Documentation

- 7.76.2.1 template<class T, class Alloc> typedef **Oscl\_Vector<Node\*, Alloc>** Oscl\_TagTree< T, Alloc >::children\_type
- 7.76.2.2 template<class T, class Alloc> typedef **Oscl\_Map<const tag\_base\_type, node\_ptr, Alloc, Oscl\_Tag\_Base>** Oscl\_TagTree< T, Alloc >::map\_type
- 7.76.2.3 template<class T, class Alloc> typedef **node\_type\*** Oscl\_TagTree< T, Alloc >::node\_ptr
- 7.76.2.4 template<class T, class Alloc> typedef **Node** Oscl\_TagTree< T, Alloc >::node\_type
- 7.76.2.5 template<class T, class Alloc> typedef **Oscl\_Pair<iterator, bool>** Oscl\_TagTree< T, Alloc >::pair\_iterator\_bool
- 7.76.2.6 template<class T, class Alloc> typedef map\_type::size\_type Oscl\_TagTree< T, Alloc >::size\_type
- 7.76.2.7 template<class T, class Alloc> typedef tag\_type::tag\_base\_type Oscl\_TagTree< T, Alloc >::tag\_base\_type
- 7.76.2.8 template<class T, class Alloc> typedef **Oscl\_Tag<Alloc>** Oscl\_TagTree< T, Alloc >::tag\_type
- 7.76.2.9 template<class T, class Alloc> typedef map\_type::value\_type Oscl\_TagTree< T, Alloc >::value\_type

## 7.76.3 Constructor & Destructor Documentation

- 7.76.3.1 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::Oscl\_TagTree (**size\_type max\_depth = 0**) [inline]

Creates a tag tree with only a root node with tag ""

- 7.76.3.2 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::Oscl\_TagTree (const Oscl\_TagTree< T, Alloc > & x) [inline]

Copy constructor

- 7.76.3.3 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::~Oscl\_TagTree () [inline]

Destructor

## 7.76.4 Member Function Documentation

- 7.76.4.1 template<class T, class Alloc> const\_iterator Oscl\_TagTree< T, Alloc >::begin () const [inline]

Returns an iterator pointing to the first node in the tree.

**7.76.4.2 template<class T, class Alloc> iterator Oscl\_TagTree< T, Alloc >::begin () [inline]**

Returns an iterator pointing to the first node in the tree.

**7.76.4.3 template<class T, class Alloc> void Oscl\_TagTree< T, Alloc >::clear () [inline]**

Erases the entire tag tree.

**7.76.4.4 template<class T, class Alloc> size\_type Oscl\_TagTree< T, Alloc >::count (const tag\_base\_type & x) const [inline]**

Returns the number of elements with key x. This can only be 0 or 1..

**7.76.4.5 template<class T, class Alloc> bool Oscl\_TagTree< T, Alloc >::empty () const [inline]**

Returns true if tree size is 0

**7.76.4.6 template<class T, class Alloc> const\_iterator Oscl\_TagTree< T, Alloc >::end () const [inline]**

Returns a const iterator pointing to the end of the tree.

**7.76.4.7 template<class T, class Alloc> iterator Oscl\_TagTree< T, Alloc >::end () [inline]**

Returns an iterator pointing to the end of the tree.

**7.76.4.8 template<class T, class Alloc> size\_type Oscl\_TagTree< T, Alloc >::erase (const tag\_base\_type & x) [inline]**

Erases the node with tag x. If the node has children, then the node will not be erased from the tree. It will be replaced with the default node value

**Parameters:**

*x* Tag of node to erase

**Returns:**

Returns the number of nodes erased. Since one-to-one mapping between nodes and tags, this will be either 0 or 1

**7.76.4.9 template<class T, class Alloc> void Oscl\_TagTree< T, Alloc >::erase (iterator position) [inline]**

Erases the element pointed to by the iterator. If the node has children, then the node will not be erased from the tree. It will be replaced with the default node value.

**Parameters:**

*position* Iterator pointing to the node to be erased

**7.76.4.10 template<class T, class Alloc> iterator Oscl\_TagTree< T, Alloc >::find (const tag\_base\_type & x) [inline]**

Finds an element whose key is x

**Returns:**

returns an iterator to the element with key x. If no element is found, returns [end\(\)](#)

**7.76.4.11 template<class T, class Alloc> pair\_iterator\_bool Oscl\_TagTree< T, Alloc >::insert (const tag\_base\_type & t, const T & x) [inline]**

Inserts x into the tree and associates it with tag t. If the tag already exists x will not be inserted, and an iterator pointing to the existing node with tag t is returned.

**Parameters:**

*t* tag to use

*x* element to insert

**Returns:**

Returns a pair of parameters, iterator and bool. The iterator points to the inserted node containing x. If the tag t already existed, then the iterator points to the node associated with tag t. The bool is true if x was inserted and false if it was not inserted due to an existing node with tag t.

**7.76.4.12 template<class T, class Alloc> Oscl\_TagTree<T, Alloc>& Oscl\_TagTree< T, Alloc >::operator= (const Oscl\_TagTree< T, Alloc > & x) [inline]**

Assignment operator

**7.76.4.13 ]**

template<class T, class Alloc> T& Oscl\_TagTree< T, Alloc >::operator[] (const tag\_base\_type & t) [inline]

Returns a reference to the object that is associated with a particular tag. If the map does not already contain such an object, operator[] inserts the default object T().

**7.76.4.14 template<class T, class Alloc> size\_type Oscl\_TagTree< T, Alloc >::size () const [inline]**

Returns the number of nodes stored in the tree

The documentation for this class was generated from the following file:

- [oscl\\_tagtree.h](#)

## 7.77 Oscl\_TagTree< T, Alloc >::const\_iterator Struct Reference

```
#include <oscl_tagtree.h>
```

### Public Types

- `typedef const node_type & reference`
- `typedef const node_type * pointer`
- `typedef map_type::const_iterator mapiter`
- `typedef const_iterator self`

### Public Methods

- `const_iterator()`
- `const_iterator(mapiter x)`
- `const_iterator(const const_iterator &it)`
- `reference operator*() const`
- `pointer operator->() const`
- `bool operator==(const self &x)`
- `bool operator!=(const self &x)`
- `self & operator++()`
- `self operator++(int)`
- `self & operator--()`
- `self operator--(int)`

### Data Fields

- `mapiter mapit`

template<class T, class Alloc> struct Oscl\_TagTree< T, Alloc >::const\_iterator

### 7.77.1 Member Typedef Documentation

- 7.77.1.1 template<class T, class Alloc> typedef map\_type::const\_iterator Oscl\_TagTree< T, Alloc >::const\_iterator::mapiter
- 7.77.1.2 template<class T, class Alloc> typedef const node\_type\* Oscl\_TagTree< T, Alloc >::const\_iterator::pointer
- 7.77.1.3 template<class T, class Alloc> typedef const node\_type& Oscl\_TagTree< T, Alloc >::const\_iterator::reference
- 7.77.1.4 template<class T, class Alloc> typedef const\_iterator Oscl\_TagTree< T, Alloc >::const\_iterator::self

### 7.77.2 Constructor & Destructor Documentation

- 7.77.2.1 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::const\_iterator::const\_iterator() [inline]
- 7.77.2.2 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::const\_iterator::const\_iterator(mapiter x) [inline]
- 7.77.2.3 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::const\_iterator::const\_iterator(const const\_iterator & it) [inline]

### 7.77.3 Member Function Documentation

- 7.77.3.1 template<class T, class Alloc> reference Oscl\_TagTree< T, Alloc >::const\_iterator::operator \*() const [inline]
- 7.77.3.2 template<class T, class Alloc> bool Oscl\_TagTree< T, Alloc >::const\_iterator::operator!= (const self & x) [inline]
- 7.77.3.3 template<class T, class Alloc> self Oscl\_TagTree< T, Alloc >::const\_iterator::operator++(int) [inline]
- 7.77.3.4 template<class T, class Alloc> self& Oscl\_TagTree< T, Alloc >::const\_iterator::operator++() [inline]
- 7.77.3.5 template<class T, class Alloc> self Oscl\_TagTree< T, Alloc >::const\_iterator::operator-(int) [inline]
- 7.77.3.6 template<class T, class Alloc> self& Oscl\_TagTree< T, Alloc >::const\_iterator::operator-() [inline]
- 7.77.3.7 template<class T, class Alloc> pointer Oscl\_TagTree< T, Alloc >::const\_iterator::operator -() const [inline]
- 7.77.3.8 template<class T, class Alloc> bool Oscl\_TagTree< T, Alloc >::const\_iterator::operator==(const self & x) [inline]

### 7.77.4 Field Documentation

- [oscl\\_tagtree.h](#)

## 7.78 Oscl\_TagTree< T, Alloc >::iterator Struct Reference

```
#include <oscl_tagtree.h>
```

### Public Types

- `typedef node_type & reference`
- `typedef node_type * pointer`
- `typedef map_type::iterator mapiter`
- `typedef iterator self`

### Public Methods

- `iterator ()`
- `iterator (mapiter x)`
- `iterator (const iterator &it)`
- `reference operator * () const`
- `pointer operator → () const`
- `bool operator== (const self &x)`
- `bool operator!= (const self &x)`
- `self & operator++ ()`
- `self operator++ (int)`
- `self & operator– ()`
- `self operator– (int)`

### Data Fields

- `mapiter mapit`

template<class T, class Alloc> struct Oscl\_TagTree< T, Alloc >::iterator

### 7.78.1 Member Typedef Documentation

- 7.78.1.1 template<class T, class Alloc> typedef map\_type::iterator Oscl\_TagTree< T, Alloc >::iterator::mapiter
- 7.78.1.2 template<class T, class Alloc> typedef node\_type\* Oscl\_TagTree< T, Alloc >::iterator::pointer
- 7.78.1.3 template<class T, class Alloc> typedef node\_type& Oscl\_TagTree< T, Alloc >::iterator::reference
- 7.78.1.4 template<class T, class Alloc> typedef iterator Oscl\_TagTree< T, Alloc >::iterator::self

### 7.78.2 Constructor & Destructor Documentation

- 7.78.2.1 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::iterator::iterator () [inline]
- 7.78.2.2 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::iterator::iterator (mapiter x) [inline]
- 7.78.2.3 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::iterator::iterator (const iterator & it) [inline]

### 7.78.3 Member Function Documentation

- 7.78.3.1 template<class T, class Alloc> reference Oscl\_TagTree< T, Alloc >::iterator::operator \* () const [inline]
- 7.78.3.2 template<class T, class Alloc> bool Oscl\_TagTree< T, Alloc >::iterator::operator!= (const self & x) [inline]
- 7.78.3.3 template<class T, class Alloc> self Oscl\_TagTree< T, Alloc >::iterator::operator++ (int) [inline]
- 7.78.3.4 template<class T, class Alloc> self& Oscl\_TagTree< T, Alloc >::iterator::operator++ () [inline]
- 7.78.3.5 template<class T, class Alloc> self Oscl\_TagTree< T, Alloc >::iterator::operator- (int) [inline]
- 7.78.3.6 template<class T, class Alloc> self& Oscl\_TagTree< T, Alloc >::iterator::operator- () [inline]
- 7.78.3.7 template<class T, class Alloc> pointer Oscl\_TagTree< T, Alloc >::iterator::operator → () const [inline]
- 7.78.3.8 template<class T, class Alloc> bool Oscl\_TagTree< T, Alloc >::iterator::operator== (const self & x) [inline]

### 7.78.4 Field Documentation

- 
- 7.78.4.1 template<class T, class Alloc> mapiter Oscl\_TagTree< T, Alloc >::iterator::mapit

- [oscl\\_tagtree.h](#)

## 7.79 Oscl\_TagTree< T, Alloc >::Node Struct Reference

```
#include <oscl_tagtree.h>
```

### Public Types

- `typedef Oscl_Vector< Node *, Alloc > children_type`

### Public Methods

- `Node()`
- `void sort_children()`
- `tag_type::size_type depth()`

### Data Fields

- `tag_type tag`
- `T value`
- `Node * parent`
- `children_type children`

template<class T, class Alloc> struct Oscl\_TagTree< T, Alloc >::Node

### 7.79.1 Member Typedef Documentation

7.79.1.1 template<class T, class Alloc> typedef Oscl\_Vector<Node\*, Alloc> Oscl\_TagTree< T, Alloc >::Node::children\_type

### 7.79.2 Constructor & Destructor Documentation

7.79.2.1 template<class T, class Alloc> Oscl\_TagTree< T, Alloc >::Node::Node () [inline]

### 7.79.3 Member Function Documentation

7.79.3.1 template<class T, class Alloc> tag\_type::size\_type Oscl\_TagTree< T, Alloc >::Node::depth () [inline]

7.79.3.2 template<class T, class Alloc> void Oscl\_TagTree< T, Alloc >::Node::sort\_children () [inline]

### 7.79.4 Field Documentation

7.79.4.1 template<class T, class Alloc> children\_type Oscl\_TagTree< T, Alloc >::Node::children

7.79.4.2 template<class T, class Alloc> Node\* Oscl\_TagTree< T, Alloc >::Node::parent

7.79.4.3 template<class T, class Alloc> tag\_type Oscl\_TagTree< T, Alloc >::Node::tag

7.79.4.4 template<class T, class Alloc> T Oscl\_TagTree< T, Alloc >::Node::value


The documentation for this struct was generated from the following file:

- [oscl\\_tagtree.h](#)

## 7.80 Oscl\_TAlloc< T, Alloc > Class Template Reference

```
#include <oscl_defalloc.h>
```

Inheritance diagram for Oscl\_TAlloc< T, Alloc >::



### Public Types

- typedef T [value\\_type](#)
- typedef T \* [pointer](#)
- typedef const T \* [const\\_pointer](#)
- typedef uint32 [size\\_type](#)
- typedef T & [reference](#)
- typedef const T & [const\\_reference](#)

### Public Methods

- virtual [~Oscl\\_TAlloc \(\)](#)
- [pointer allocate\\_fl \(uint32 size, const char \\*file\\_name, const int line\\_num\)](#)
- [pointer allocate \(uint32 size\)](#)
- [pointer alloc\\_and\\_construct\\_fl \(const\\_reference val, const char \\*file\\_name, const int line\\_num\)](#)
- [pointer alloc\\_and\\_construct \(const\\_reference val\)](#)
- void [deallocate \(OsclAny \\*p\)](#)
- void [deallocate \(OsclAny \\*p, size\\_type n\)](#)
- void [destruct\\_and\\_dealloc \(OsclAny \\*p\)](#)
- [pointer address \(reference r\)](#)
- [const\\_pointer address \(const\\_reference r\) const](#)
- void [construct \(pointer p, const\\_reference val\)](#)
- void [destroy \(pointer p\)](#)

template<class T, class Alloc> class Oscl\_TAlloc< T, Alloc >

### 7.80.1 Member Typedef Documentation

7.80.1.1 template<class T, class Alloc> **typedef const T\* Oscl\_TAlloc< T, Alloc >::const\_pointer**

7.80.1.2 template<class T, class Alloc> **typedef const T& Oscl\_TAlloc< T, Alloc >::const\_reference**

7.80.1.3 template<class T, class Alloc> **typedef T\* Oscl\_TAlloc< T, Alloc >::pointer**

7.80.1.4 template<class T, class Alloc> **typedef T& Oscl\_TAlloc< T, Alloc >::reference**

7.80.1.5 template<class T, class Alloc> **typedef uint32 Oscl\_TAlloc< T, Alloc >::size\_type**

7.80.1.6 template<class T, class Alloc> **typedef T Oscl\_TAlloc< T, Alloc >::value\_type**

### 7.80.2 Constructor & Destructor Documentation

7.80.2.1 template<class T, class Alloc> **virtual Oscl\_TAlloc< T, Alloc >::~Oscl\_TAlloc ()**  
 [inline, virtual]

### 7.80.3 Member Function Documentation

7.80.3.1 template<class T, class Alloc> **const\_pointer Oscl\_TAlloc< T, Alloc >::address (const\_reference r) const** [inline]

7.80.3.2 template<class T, class Alloc> **pointer Oscl\_TAlloc< T, Alloc >::address (reference r)**  
 [inline]

7.80.3.3 template<class T, class Alloc> **pointer Oscl\_TAlloc< T, Alloc >::alloc\_and\_construct (const\_reference val)** [inline]

7.80.3.4 template<class T, class Alloc> **pointer Oscl\_TAlloc< T, Alloc >::alloc\_and\_construct\_fl (const\_reference val, const char \*file\_name, const int line\_num)** [inline]

7.80.3.5 template<class T, class Alloc> **pointer Oscl\_TAlloc< T, Alloc >::allocate (uint32 size)**  
 [inline]

7.80.3.6 template<class T, class Alloc> **pointer Oscl\_TAlloc< T, Alloc >::allocate\_fl (uint32 size, const char \*file\_name, const int line\_num)** [inline]

7.80.3.7 template<class T, class Alloc> **void Oscl\_TAlloc< T, Alloc >::construct (pointer p, const\_reference val)** [inline]

7.80.3.8 template<class T, class Alloc> **void Oscl\_TAlloc< T, Alloc >::deallocate (OsclAny \*p, size\_type n)** [inline]

7.80.3.9 template<class T, class Alloc> **void Oscl\_TAlloc< T, Alloc >::deallocate (OsclAny \*p)**  
 [inline]

7.80.3.10 template<class T, class Alloc> **void Oscl\_TAlloc< T, Alloc >::destroy (pointer p)**  
 [inline]

7.80.3.11 template<class T, class Alloc> **void Oscl\_TAlloc< T, Alloc >::destruct\_and\_dealloc (OsclAny \*p)** [inline, virtual]

The documentation for this class was generated from the following file:

- [oscl\\_defalloc.h](#)

## 7.81 Oscl\_TAlloc< T, Alloc >::rebind< U, V > Struct Template Reference

```
#include <oscl_defalloc.h>
```

### Public Types

- `typedef Oscl_TAlloc< U, V > other`

```
template<class T, class Alloc>template<class U, class V> struct Oscl_TAlloc< T, Alloc >::rebind< U, V >
```

#### 7.81.1 Member Typedef Documentation

```
7.81.1.1 template<class T, class Alloc> template<class U, class V> typedef Oscl_TAlloc<U, V>  
Oscl_TAlloc< T, Alloc >::rebind< U, V >::other
```


The documentation for this struct was generated from the following file:

- `oscl_defalloc.h`

## 7.82 Oscl\_Vector< T, Alloc > Class Template Reference

```
#include <oscl_vector.h>
```

Inheritance diagram for Oscl\_Vector< T, Alloc >::



### Public Types

- `typedef T value_type`
- `typedef T * pointer`
- `typedef T & reference`
- `typedef const T & const_reference`
- `typedef T * iterator`
- `typedef const T * const_iterator`

### Public Methods

- `Oscl_Vector()`
- `Oscl_Vector(uint32 n)`
- `Oscl_Vector(const Oscl_Vector< T, Alloc > &x)`
- `virtual ~Oscl_Vector()`
- `Oscl_Vector< T, Alloc > & operator=(const Oscl_Vector< T, Alloc > &x)`
- `void push_back(const T &x)`
- `void push_front(const T &x)`
- `iterator insert(iterator pos, const T &x)`
- `T & operator[](uint32 n)`
- `const T & operator[](uint32 n) const`
- `T & front()`
- `const T & front() const`
- `T & back()`
- `const T & back() const`
- `void pop_back()`
- `void clear()`
- `void destroy()`
- `iterator begin() const`
- `iterator end() const`
- `iterator erase(iterator pos)`
- `iterator erase(iterator first, iterator last)`

### 7.82.1 Detailed Description

**template<class T, class Alloc> class Oscl\_Vector< T, Alloc >**

Oscl\_Vector Class. A subset of STL::Vector methods. Oscl\_Vector supports random access to elements, constant time insertion and removal of elements at the end of the vector, and linear time insertion and removal of elements at the beginning or middle of the vector. The number of elements in a vector can vary dynamically, and memory management is performed automatically.

### 7.82.2 Member Typedef Documentation

**7.82.2.1 template<class T, class Alloc> typedef const T\* Oscl\_Vector< T, Alloc >::const\_iterator**

**7.82.2.2 template<class T, class Alloc> typedef const T& Oscl\_Vector< T, Alloc >::const\_reference**

**7.82.2.3 template<class T, class Alloc> typedef T\* Oscl\_Vector< T, Alloc >::iterator**

**7.82.2.4 template<class T, class Alloc> typedef T\* Oscl\_Vector< T, Alloc >::pointer**

**7.82.2.5 template<class T, class Alloc> typedef T& Oscl\_Vector< T, Alloc >::reference**

**7.82.2.6 template<class T, class Alloc> typedef T Oscl\_Vector< T, Alloc >::value\_type**

### 7.82.3 Constructor & Destructor Documentation

**7.82.3.1 template<class T, class Alloc> Oscl\_Vector< T, Alloc >::Oscl\_Vector () [inline]**

Creates an empty vector.

**7.82.3.2 template<class T, class Alloc> Oscl\_Vector< T, Alloc >::Oscl\_Vector (uint32 n) [inline]**

Creates an empty vector with capacity n.

**Parameters:**

*n* creates a vector with n elements. The main reason for specifying n is efficiency. If you know the capacity to which your vector must grow, then it is more efficient to allocate the vector all at once rather than rely on the automatic reallocation scheme. This also helps control the invalidation of iterators.

**7.82.3.3 template<class T, class Alloc> Oscl\_Vector< T, Alloc >::Oscl\_Vector (const Oscl\_Vector< T, Alloc > & x) [inline]**

Copy Constructor.

**Parameters:**

*x* vector class to copy.

**7.82.3.4 template<class T, class Alloc> virtual Oscl\_Vector< T, Alloc >::~Oscl\_Vector ()  
[inline, virtual]**

The destructor.

#### 7.82.4 Member Function Documentation

**7.82.4.1 template<class T, class Alloc> const T& Oscl\_Vector< T, Alloc >::back () const  
[inline]**

Returns the last element.

**7.82.4.2 template<class T, class Alloc> T& Oscl\_Vector< T, Alloc >::back () [inline]**

Returns the last element.

**7.82.4.3 template<class T, class Alloc> iterator Oscl\_Vector< T, Alloc >::begin () const  
[inline]**

Returns an iterator pointing to the beginning of the vector.

Reimplemented from [Oscl\\_Vector\\_Base](#).

**7.82.4.4 template<class T, class Alloc> void Oscl\_Vector< T, Alloc >::clear () [inline]**

Removes all elements.

**7.82.4.5 template<class T, class Alloc> void Oscl\_Vector< T, Alloc >::destroy () [inline]**

Destroy – this is like an explicit destructor call.

Reimplemented from [Oscl\\_Vector\\_Base](#).

**7.82.4.6 template<class T, class Alloc> iterator Oscl\_Vector< T, Alloc >::end () const  
[inline]**

Returns an iterator pointing to the end of the vector..

Reimplemented from [Oscl\\_Vector\\_Base](#).

**7.82.4.7 template<class T, class Alloc> iterator Oscl\_Vector< T, Alloc >::erase (iterator *first*,  
iterator *last*) [inline]**

Erases elements in range [*first*, *last*). Erasing an element invalidates all iterators pointing to elements following the deletion point.

##### Parameters:

*first* starting position

*last* ending position, this position is not erased

**7.82.4.8 template<class T, class Alloc> iterator Oscl\_Vector< T, Alloc >::erase (iterator pos) [inline]**

Erases the element pointed to by iterator pos. Erasing an element invalidates all iterators pointing to elements following the deletion point.

**Parameters:**

*pos* iterator at erase position

**7.82.4.9 template<class T, class Alloc> const T& Oscl\_Vector< T, Alloc >::front () const [inline]**

Returns the first element.

**7.82.4.10 template<class T, class Alloc> T& Oscl\_Vector< T, Alloc >::front () [inline]**

Returns the first element.

**7.82.4.11 template<class T, class Alloc> iterator Oscl\_Vector< T, Alloc >::insert (iterator pos, const T & x) [inline]**

Inserts a new element before the one at pos.

**Parameters:**

*pos* position at which to insert the new element.

*x* new element

**7.82.4.12 template<class T, class Alloc> Oscl\_Vector<T, Alloc>& Oscl\_Vector< T, Alloc >::operator= (const Oscl\_Vector< T, Alloc > & x) [inline]**

The assignment operator

**7.82.4.13 ]**

template<class T, class Alloc> const T& Oscl\_Vector< T, Alloc >::operator[] (uint32 n) const [inline]

Returns the n'th element.

**Parameters:**

*n* element position to return

**7.82.4.14 ]**

template<class T, class Alloc> T& Oscl\_Vector< T, Alloc >::operator[] (uint32 n) [inline]

Returns the n'th element.

**Parameters:**

*n* element position to return

**7.82.4.15 template<class T, class Alloc> void Oscl\_Vector< T, Alloc >::pop\_back () [inline]**

Removes the last element.

Reimplemented from [Oscl\\_Vector\\_Base](#).

**7.82.4.16 template<class T, class Alloc> void Oscl\_Vector< T, Alloc >::push\_back (const T & x) [inline]**

Inserts a new element at the end. Inserting an element invalidates all iterators if memory reallocation occurs as a result of the insertion.

**Parameters:**

*x* new element

**7.82.4.17 template<class T, class Alloc> void Oscl\_Vector< T, Alloc >::push\_front (const T & x) [inline]**

Inserts a new element at the front. Inserting an element invalidates all iterators if memory reallocation occurs as a result of the insertion.

**Parameters:**

*x* new element


The documentation for this class was generated from the following file:

- [oscl\\_vector.h](#)

## 7.83 Oscl\_Vector\_Base Class Reference

```
#include <oscl_vector.h>
```

Inheritance diagram for Oscl\_Vector\_Base::



### Public Methods

- uint32 [size \(\) const](#)
- uint32 [capacity \(\) const](#)
- bool [empty \(\) const](#)
- OSCL\_IMPORT\_REF void [reserve \(uint32 n\)](#)

### Protected Methods

- OSCL\_IMPORT\_REF void [construct \(Oscl\\_Opaque\\_Type\\_Alloc \\*aType\)](#)
- OSCL\_IMPORT\_REF void [construct \(Oscl\\_Opaque\\_Type\\_Alloc \\*aType, uint32 n\)](#)
- OSCL\_IMPORT\_REF void [construct \(Oscl\\_Opaque\\_Type\\_Alloc \\*aType, const Oscl\\_Vector\\_Base &x\)](#)
- virtual [~Oscl\\_Vector\\_Base \(\)](#)
- OSCL\_IMPORT\_REF void [push\\_back \(const OsclAny \\*x\)](#)
- OSCL\_IMPORT\_REF void [pop\\_back \(\)](#)
- OSCL\_IMPORT\_REF void [push\\_front \(const OsclAny \\*x\)](#)
- OSCL\_IMPORT\_REF OsclAny \* [insert \(OsclAny \\*pos, const OsclAny \\*x\)](#)
- OSCL\_IMPORT\_REF OsclAny \* [erase \(OsclAny \\*pos\)](#)
- OSCL\_IMPORT\_REF OsclAny \* [erase \(OsclAny \\*first, OsclAny \\*last\)](#)
- OSCL\_IMPORT\_REF void [assign\\_vector \(const Oscl\\_Vector\\_Base &x\)](#)
- OSCL\_IMPORT\_REF void [destroy \(\)](#)

### Protected Attributes

- uint32 [numelems](#)
- uint32 [bufsize](#)
- [OsclAny \\* elems](#)
- uint32 [sizeof\\_T](#)

### Friends

- class [OsclPriorityQueueBase](#)

### 7.83.1 Detailed Description

Oscl\_Vector\_Base is a non-templatized base class for [Oscl\\_Vector](#). The purpose of this base class is to avoid large inline routines in the [Oscl\\_Vector](#) implementation. This class is not intended for direct instantiation except by [Oscl\\_Vector](#).

### 7.83.2 Constructor & Destructor Documentation

**7.83.2.1 virtual Oscl\_Vector\_Base::~Oscl\_Vector\_Base () [inline, protected, virtual]**

The destructor.

### 7.83.3 Member Function Documentation

**7.83.3.1 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::assign\_vector (const Oscl\_Vector\_Base & x) [protected]**

**7.83.3.2 uint32 Oscl\_Vector\_Base::capacity () const [inline]**

Returns the allocated memory of the vector in units of number of elements.

**7.83.3.3 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::construct (Oscl\_Opaque\_Type\_Alloc \* aType, const Oscl\_Vector\_Base & x) [protected]**

**7.83.3.4 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::construct (Oscl\_Opaque\_Type\_Alloc \* aType, uint32 n) [protected]**

**7.83.3.5 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::construct (Oscl\_Opaque\_Type\_Alloc \* aType) [protected]**

**7.83.3.6 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::destroy () [protected]**

Reimplemented in [Oscl\\_Vector< T, Alloc >](#), [Oscl\\_Vector< OsclComponentRegistryElement, OsclMemAllocator >](#), [Oscl\\_Vector< uint32, OsclMemAllocator >](#), [Oscl\\_Vector< OsclSocketServRequestQElem, OsclMemAllocator >](#), [Oscl\\_Vector< Node \\*, Alloc >](#), [Oscl\\_Vector< OsclFixedCacheParam, OsclMemAllocator >](#), [Oscl\\_Vector< OsclSocketRequest \\*, OsclMemAllocator >](#), [Oscl\\_Vector< entry\\_type \\*, Alloc >](#), [Oscl\\_Vector< OSCL\\_HeapString< OsclMemAllocator >, OsclMemAllocator >](#), [Oscl\\_Vector< OsclAsyncFileBuffer \\*, OsclMemAllocator >](#), [Oscl\\_Vector< TOsclFileOffset, OsclMemAllocator >](#), [Oscl\\_Vector< MemPoolBufferInfo \\*, OsclMemAllocator >](#), [Oscl\\_Vector< OsclSharedPtr< PVLoggerFilter >, alloc\\_type >](#), [Oscl\\_Vector< TOsclReady, OsclReadyAlloc >](#), [Oscl\\_Vector< OsclFileCacheBuffer, OsclMemAllocator >](#), [Oscl\\_Vector< OsclSharedPtr< PVLoggerAppender >, alloc\\_type >](#), [Oscl\\_Vector< OsclAny \\*, OsclMemAllocator >](#), and [Oscl\\_Vector< OsclNetworkAddress, OsclMemAllocator >](#).

**7.83.3.7 bool Oscl\_Vector\_Base::empty () const [inline]**

True if the vector's size is 0.

**7.83.3.8 OSCL\_IMPORT\_REF `OsclAny*` Oscl\_Vector\_Base::erase (`OsclAny *first, OsclAny *last`) [protected]**

Erases elements in range [first, last). Erasing an element invalidates all iterators pointing to elements following the deletion point.

**Parameters:**

*first* starting position

*last* ending position, this position is not erased

**7.83.3.9 OSCL\_IMPORT\_REF `OsclAny*` Oscl\_Vector\_Base::erase (`OsclAny *pos`) [protected]**

Erases the element pointed to by iterator pos. Erasing an element invalidates all iterators pointing to elements following the deletion point.

**Parameters:**

*pos* iterator at erase position

**7.83.3.10 OSCL\_IMPORT\_REF `OsclAny*` Oscl\_Vector\_Base::insert (`OsclAny *pos, const OsclAny *x`) [protected]**

Inserts a new element at a specific position.

**Parameters:**

*pos* iterator at insert position.

*x* pointer to new element

**7.83.3.11 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::pop\_back () [protected]**

Removes the last element.

Reimplemented in `Oscl_Vector< T, Alloc >`, `Oscl_Vector< OsclComponentRegistryElement, OsclMemAllocator >`, `Oscl_Vector< uint32, OsclMemAllocator >`, `Oscl_Vector< OsclSocketServRequestQElem, OsclMemAllocator >`, `Oscl_Vector< Node *, Alloc >`, `Oscl_Vector< OsclFixedCacheParam, OsclMemAllocator >`, `Oscl_Vector< OsclSocketRequest *, OsclMemAllocator >`, `Oscl_Vector< entry_type *, Alloc >`, `Oscl_Vector< OSCL_HeapString< OsclMemAllocator >, OsclMemAllocator >`, `Oscl_Vector< OsclAsyncFileBuffer *, OsclMemAllocator >`, `Oscl_Vector< TOscFileOffset, OsclMemAllocator >`, `Oscl_Vector< MemPoolBufferInfo *, OsclMemAllocator >`, `Oscl_Vector< OsclSharedPtr< PVLoggerFilter >, alloc_type >`, `Oscl_Vector< TOscReady, OsclReadyAlloc >`, `Oscl_Vector< OsclFileCacheBuffer, OsclMemAllocator >`, `Oscl_Vector< OsclSharedPtr< PVLoggerAppender >, alloc_type >`, `Oscl_Vector< OsclAny *, OsclMemAllocator >`, and `Oscl_Vector< OsclNetworkAddress, OsclMemAllocator >`.

**7.83.3.12 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::push\_back (const `OsclAny *x`) [protected]**

Inserts a new element at the end. Inserting an element invalidates all iterators if memory reallocation occurs as a result of the insertion.

**Parameters:**

*x* pointer to the new element

**7.83.3.13 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::push\_front (const OsclAny \* *x*) [protected]**

Inserts a new element at the front. Inserting an element invalidates all iterators if memory reallocation occurs as a result of the insertion.

**Parameters:**

*x* pointer to new element

**7.83.3.14 OSCL\_IMPORT\_REF void Oscl\_Vector\_Base::reserve (uint32 *n*)**

Reallocates memory if necessary to a capacity of *n* elements. The main reason for reserve is efficiency. If you know the capacity to which your vector must grow, then it is more efficient to allocate the vector all at once rather than rely on the automatic reallocation scheme. This also helps control the invalidation of iterators.

**Parameters:**

*n* size of vector

**7.83.3.15 uint32 Oscl\_Vector\_Base::size () const [inline]**

Returns the size of the vector in units of number of elements.

## 7.83.4 Friends And Related Function Documentation

**7.83.4.1 friend class OsclPriorityQueueBase [friend]**

## 7.83.5 Field Documentation

**7.83.5.1 uint32 Oscl\_Vector\_Base::bufsize [protected]****7.83.5.2 OsclAny\* Oscl\_Vector\_Base::elems [protected]****7.83.5.3 uint32 Oscl\_Vector\_Base::numelems [protected]****7.83.5.4 uint32 Oscl\_Vector\_Base::sizeof\_T [protected]**


The documentation for this class was generated from the following file:

- [oscl\\_vector.h](#)

## 7.84 OSCL\_wFastString Class Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_wFastString::



### Public Types

- `typedef OSCL_wString::chartype chartype`
- `typedef TOSCL_wStringOp optype`
- `typedef OSCL_String::chartype other_chartype`

### Public Methods

- `OSCL_IMPORT_REF OSCL_wFastString()`
- `OSCL_IMPORT_REF OSCL_wFastString(const OSCL_wFastString &src)`
- `OSCL_IMPORT_REF OSCL_wFastString(const chartype *cstr)`
- `OSCL_IMPORT_REF OSCL_wFastString(chartype *buf, uint32 maxlen)`
- `OSCL_IMPORT_REF ~OSCL_wFastString()`
- `OSCL_IMPORT_REF uint32 get_size() const`
- `OSCL_IMPORT_REF uint32 get_maxsize() const`
- `OSCL_IMPORT_REF const chartype * get_cstr() const`
- `OSCL_IMPORT_REF chartype * get_str() const`
- `OSCL_IMPORT_REF OSCL_wFastString & operator=(const OSCL_wFastString &src)`
- `OSCL_IMPORT_REF OSCL_wFastString & operator=(const chartype *cstr)`
- `OSCL_IMPORT_REF void set(chartype *cstr, uint32 maxlen)`
- `OSCL_IMPORT_REF void set(const other_chartype *buf, uint32 numofbyte, optype op)`
- `OSCL_IMPORT_REF void set_length()`

### Friends

- class `OSCL_wString`

#### 7.84.1 Detailed Description

`OSCL_wFastString` is identical to `OSCL_FastString` except that it uses wide-character format. For descriptions, see `OSCL_FastString`.

#### 7.84.2 Member Typedef Documentation

##### 7.84.2.1 `typedef OSCL_wString::chartype OSCL_wFastString::chartype`

Reimplemented from `OSCL_wString`.

7.84.2.2 **typedef TOSCL\_wStringOp OSCL\_wFastString::optype**

7.84.2.3 **typedef OSCL\_String::chartype OSCL\_wFastString::other\_chartype**

### 7.84.3 Constructor & Destructor Documentation

7.84.3.1 **OSCL\_IMPORT\_REF OSCL\_wFastString::OSCL\_wFastString()**

7.84.3.2 **OSCL\_IMPORT\_REF OSCL\_wFastString::OSCL\_wFastString(const OSCL\_wFastString & src)**

7.84.3.3 **OSCL\_IMPORT\_REF OSCL\_wFastString::OSCL\_wFastString(const chartype \* cstr)**

7.84.3.4 **OSCL\_IMPORT\_REF OSCL\_wFastString::OSCL\_wFastString(chartype \* buf, uint32 maxlen)**

7.84.3.5 **OSCL\_IMPORT\_REF OSCL\_wFastString::~OSCL\_wFastString()**

### 7.84.4 Member Function Documentation

7.84.4.1 **OSCL\_IMPORT\_REF const chartype\* OSCL\_wFastString::get\_cstr() [virtual]**

Implements [OSCL\\_wString](#).

7.84.4.2 **OSCL\_IMPORT\_REF uint32 OSCL\_wFastString::get\_maxsize() [virtual]**

Implements [OSCL\\_wString](#).

7.84.4.3 **OSCL\_IMPORT\_REF uint32 OSCL\_wFastString::get\_size() [virtual]**

Implements [OSCL\\_wString](#).

7.84.4.4 **OSCL\_IMPORT\_REF chartype\* OSCL\_wFastString::get\_str() [virtual]**

Implements [OSCL\\_wString](#).

7.84.4.5 **OSCL\_IMPORT\_REF OSCL\_wFastString& OSCL\_wFastString::operator=(const chartype \* cstr)**

Reimplemented from [OSCL\\_wString](#).

- 7.84.4.6 **OSCL\_IMPORT\_REF OSCL\_wFastString& OSCL\_wFastString::operator= (const OSCL\_wFastString & src)**
- 7.84.4.7 **OSCL\_IMPORT\_REF void OSCL\_wFastString::set (const other\_chartype \* buf, uint32 numofbyte, optype op)**
- 7.84.4.8 **OSCL\_IMPORT\_REF void OSCL\_wFastString::set (chartype \* cstr, uint32 maxlen)**
- 7.84.4.9 **OSCL\_IMPORT\_REF void OSCL\_wFastString::set\_length ()**

## 7.84.5 Friends And Related Function Documentation

- 7.84.5.1 **friend class OSCL\_wString [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.85 OSCL\_wHeapString< Alloc > Class Template Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_wHeapString< Alloc >::



### Public Types

- `typedef OSCL_wString::chartype chartype`
- `typedef TOSCL_wStringOp otype`
- `typedef OSCL_String::chartype other_chartype`

### Public Methods

- `OSCL_wHeapString()`
- `OSCL_wHeapString(const OSCL_wHeapString &src)`
- `OSCL_wHeapString(const OSCL_wString &src)`
- `OSCL_wHeapString(const chartype *cstr)`
- `OSCL_wHeapString(const chartype *buf, uint32 length)`
- `~OSCL_wHeapString()`
- `uint32 get_size() const`
- `uint32 get_maxsize() const`
- `const chartype * get_cstr() const`
- `chartype * get_str() const`
- `OSCL_wHeapString & operator=(const OSCL_wHeapString &src)`
- `OSCL_wHeapString & operator=(const OSCL_wString &src)`
- `OSCL_wHeapString & operator=(const chartype *cstr)`
- `void set(const chartype *buf, uint32 length)`
- `void set(const other_chartype *buf, otype op)`
- `void set(const other_chartype *buf, uint32 length, otype op)`

### Friends

- class `OSCL_wString`

#### 7.85.1 Detailed Description

```
template<class Alloc> class OSCL_wHeapString< Alloc >
```

`OSCL_wHeapString` is identical to `OSCL_HeapString` except that it uses wide-character format. For descriptions, see `OSCL_HeapString`.

## 7.85.2 Member Typedef Documentation

**7.85.2.1 template<class Alloc> typedef OSCL\_wString::chartype OSCL\_wHeapString< Alloc >::chartype**

Reimplemented from [OSCL\\_wString](#).

**7.85.2.2 template<class Alloc> typedef TOSCL\_wStringOp OSCL\_wHeapString< Alloc >::optype**

**7.85.2.3 template<class Alloc> typedef OSCL\_String::chartype OSCL\_wHeapString< Alloc >::other\_chartype**

## 7.85.3 Friends And Related Function Documentation

**7.85.3.1 template<class Alloc> friend class OSCL\_wString [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.86 OSCL\_wHeapStringA Class Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_wHeapStringA::



### Public Types

- `typedef OSCL_wString::chartype chartype`
- `typedef TOSCL_wStringOp optype`
- `typedef OSCL_String::chartype other_chartype`

### Public Methods

- `OSCL_IMPORT_REF OSCL_wHeapStringA()`
- `OSCL_IMPORT_REF OSCL_wHeapStringA(Oscl_DefAlloc *alloc, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA(const OSCL_wHeapStringA &src)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA(const OSCL_wHeapStringA &src, Oscl_DefAlloc *alloc, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA(const OSCL_wString &src, Oscl_DefAlloc *alloc=NULL, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA(const chartype *cstr, Oscl_DefAlloc *alloc=NULL, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA(const chartype *buf, uint32 length, Oscl_DefAlloc *alloc=NULL, OsclRefCounter *ref=NULL)`
- `OSCL_IMPORT_REF ~OSCL_wHeapStringA()`
- `OSCL_IMPORT_REF uint32 get_size() const`
- `OSCL_IMPORT_REF uint32 get_maxsize() const`
- `OSCL_IMPORT_REF const chartype * get_cstr() const`
- `OSCL_IMPORT_REF chartype * get_str() const`
- `OSCL_IMPORT_REF OSCL_wHeapStringA & operator=(const OSCL_wHeapStringA &src)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA & operator=(const OSCL_wString &src)`
- `OSCL_IMPORT_REF OSCL_wHeapStringA & operator=(const chartype *cstr)`
- `OSCL_IMPORT_REF void set(const chartype *buf, uint32 length)`
- `OSCL_IMPORT_REF void set(const other_chartype *buf, optype op)`
- `OSCL_IMPORT_REF void set(const other_chartype *buf, uint32 length, optype op)`

### Friends

- class `OSCL_wString`

### 7.86.1 Detailed Description

OSCL\_wHeapStringA is identical to [OSCL\\_HeapStringA](#) except that it uses wide-character format. For descriptions, see [OSCL\\_HeapStringA](#).

### 7.86.2 Member Typedef Documentation

#### 7.86.2.1 `typedef OSCL_wString::chartype OSCL_wHeapStringA::chartype`

Reimplemented from [OSCL\\_wString](#).

#### 7.86.2.2 `typedef TOSCL_wStringOp OSCL_wHeapStringA::optype`

#### 7.86.2.3 `typedef OSCL_String::chartype OSCL_wHeapStringA::other_chartype`

### 7.86.3 Constructor & Destructor Documentation

#### 7.86.3.1 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA()`

#### 7.86.3.2 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA(Oscl_DefAlloc *alloc, OsclRefCounter *ref = NULL)`

#### 7.86.3.3 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA(const OSCL_wHeapStringA &src)`

#### 7.86.3.4 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA(const OSCL_wHeapStringA &src, Oscl_DefAlloc *alloc, OsclRefCounter *ref = NULL)`

#### 7.86.3.5 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA(const OSCL_wString &src, Oscl_DefAlloc *alloc = NULL, OsclRefCounter *ref = NULL)`

#### 7.86.3.6 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA(const chartype *cstr, Oscl_DefAlloc *alloc = NULL, OsclRefCounter *ref = NULL)`

#### 7.86.3.7 `OSCL_IMPORT_REF OSCL_wHeapStringA::OSCL_wHeapStringA(const chartype *buf, uint32 length, Oscl_DefAlloc *alloc = NULL, OsclRefCounter *ref = NULL)`

#### 7.86.3.8 `OSCL_IMPORT_REF OSCL_wHeapStringA::~OSCL_wHeapStringA()`

### 7.86.4 Member Function Documentation

#### 7.86.4.1 `OSCL_IMPORT_REF const chartype* OSCL_wHeapStringA::get_cstr() [virtual]`

Implements [OSCL\\_wString](#).

#### 7.86.4.2 `OSCL_IMPORT_REF uint32 OSCL_wHeapStringA::get_maxsize() [virtual]`

Implements [OSCL\\_wString](#).

**7.86.4.3 OSCL\_IMPORT\_REF uint32 OSCL\_wHeapStringA::get\_size () [virtual]**

Implements [OSCL\\_wString](#).

**7.86.4.4 OSCL\_IMPORT\_REF chartype\* OSCL\_wHeapStringA::get\_str () [virtual]**

Implements [OSCL\\_wString](#).

**7.86.4.5 OSCL\_IMPORT\_REF OSCL\_wHeapStringA& OSCL\_wHeapStringA::operator= (const chartype \* cstr)**

Reimplemented from [OSCL\\_wString](#).

**7.86.4.6 OSCL\_IMPORT\_REF OSCL\_wHeapStringA& OSCL\_wHeapStringA::operator= (const OSCL\_wString & src)**

Reimplemented from [OSCL\\_wString](#).

**7.86.4.7 OSCL\_IMPORT\_REF OSCL\_wHeapStringA& OSCL\_wHeapStringA::operator= (const OSCL\_wHeapStringA & src)****7.86.4.8 OSCL\_IMPORT\_REF void OSCL\_wHeapStringA::set (const other\_chartype \* buf, uint32 length, optype op)****7.86.4.9 OSCL\_IMPORT\_REF void OSCL\_wHeapStringA::set (const other\_chartype \* buf, optype op)****7.86.4.10 OSCL\_IMPORT\_REF void OSCL\_wHeapStringA::set (const chartype \* buf, uint32 length)**

## 7.86.5 Friends And Related Function Documentation

**7.86.5.1 friend class OSCL\_wString [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.87 OSCL\_wStackString< MaxBufSize > Class Template Reference

```
#include <oscl_string_containers.h>
```

Inheritance diagram for OSCL\_wStackString< MaxBufSize >::



### Public Types

- `typedef OSCL_wString::chartype chartype`
- `typedef TOSCL_wStringOp optype`
- `typedef OSCL_String::chartype other_chartype`

### Public Methods

- `OSCL_wStackString()`
- `OSCL_wStackString(const OSCL_wStackString &src)`
- `OSCL_wStackString(const OSCL_wString &src)`
- `OSCL_wStackString(const chartype *cstr)`
- `OSCL_wStackString(const chartype *buf, uint32 length)`
- `~OSCL_wStackString()`
- `uint32 get_size() const`
- `uint32 get_maxsize() const`
- `const chartype *get_cstr() const`
- `chartype *get_str() const`
- `OSCL_wStackString & operator=(const OSCL_wStackString &src)`
- `OSCL_wStackString & operator=(const OSCL_wString &src)`
- `OSCL_wStackString & operator=(const chartype *cstr)`
- `void set(const chartype *buf, uint32 length)`
- `void set(const other_chartype *buf, optype op)`
- `void set(const other_chartype *buf, uint32 length, optype op)`

### Friends

- class `OSCL_wString`

#### 7.87.1 Detailed Description

```
template<uint32 MaxBufSize> class OSCL_wStackString< MaxBufSize >
```

OSCL\_wStackString is identical to `OSCL_StackString` except that it uses wide-character format. For descriptions, see `OSCL_StackString`.

## 7.87.2 Member Typedef Documentation

**7.87.2.1 template<uint32 MaxBufSize> typedef OSCL\_wString::chartype OSCL\_wStackString< MaxBufSize >::chartype**

Reimplemented from [OSCL\\_wString](#).

**7.87.2.2 template<uint32 MaxBufSize> typedef TOSCL\_wStringOp OSCL\_wStackString< MaxBufSize >::optype**

**7.87.2.3 template<uint32 MaxBufSize> typedef OSCL\_String::chartype OSCL\_wStackString< MaxBufSize >::other\_chartype**

## 7.87.3 Friends And Related Function Documentation

**7.87.3.1 template<uint32 MaxBufSize> friend class OSCL\_wString [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_string\\_containers.h](#)

## 7.88 OSCL\_wString Class Reference

```
#include <oscl_string.h>
```

Inheritance diagram for OSCL\_wString::



### Public Types

- `typedef oscl_wchar chartype`

### Public Methods

- `virtual uint32 get_size () const=0`
- `virtual uint32 get_maxsize () const=0`
- `virtual const chartype * get_cstr () const=0`
- `virtual bool is_writable () const`
- `virtual chartype * get_str () const=0`
- `OSCL_wString & operator=(const OSCL_wString &src)`
- `OSCL_wString & operator=(const chartype *cstr)`
- `OSCL_wString & operator+=(const OSCL_wString &src)`
- `OSCL_wString & operator+=(const chartype *cstr)`
- `OSCL_wString & operator+=(const chartype c)`
- `bool operator==(const OSCL_wString &src) const`
- `bool operator!=(const OSCL_wString &src) const`
- `bool operator<(const OSCL_wString &src) const`
- `bool operator<=(const OSCL_wString &src) const`
- `bool operator>(const OSCL_wString &src) const`
- `bool operator>=(const OSCL_wString &src) const`
- `bool operator==(const chartype *cstr) const`
- `chartype operator[](uint32 index) const`
- `virtual chartype read(uint32 index) const`
- `virtual uint32 setrep_to_wide_char(const char *src, uint32 len, TOSCL_wStringOp op, Oscl_DefAlloc *aAlloc)`
- `virtual int8 hash() const`
- `virtual void write(uint32 index, chartype c)`
- `virtual void write(uint32 offset, uint32 length, const chartype *buf)`

### Protected Methods

- `OSCL_wString()`
- `virtual ~OSCL_wString()`
- `virtual void set_rep(const chartype *cstr)=0`
- `virtual void append_rep(const chartype *cstr)=0`
- `virtual void set_rep(const OSCL_wString &src)=0`
- `virtual void append_rep(const OSCL_wString &src)=0`
- `virtual void set_len(uint32 len)=0`

### 7.88.1 Detailed Description

A common base class for string classes with wide character (oscl\_wchar) format. OSCL\_wString and [OSCL\\_String](#) are identical except for the character format. For descriptions, see [OSCL\\_String](#).

### 7.88.2 Member Typedef Documentation

#### 7.88.2.1 `typedef oscl_wchar OSCL_wString::chartype`

Reimplemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), [OSCL\\_wStackString< MaxBufSize >](#), and [OSCL\\_wFastString](#).

### 7.88.3 Constructor & Destructor Documentation

#### 7.88.3.1 `OSCL_wString::OSCL_wString () [protected]`

#### 7.88.3.2 `virtual OSCL_wString::~OSCL_wString () [protected, virtual]`

### 7.88.4 Member Function Documentation

#### 7.88.4.1 `virtual void OSCL_wString::append_rep (const OSCL_wString & src) [protected, pure virtual]`

#### 7.88.4.2 `virtual void OSCL_wString::append_rep (const chartype * cstr) [protected, pure virtual]`

#### 7.88.4.3 `virtual const chartype* OSCL_wString::get_cstr () [pure virtual]`

Implemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), [OSCL\\_wStackString< MaxBufSize >](#), and [OSCL\\_wFastString](#).

#### 7.88.4.4 `virtual uint32 OSCL_wString::get_maxsize () [pure virtual]`

Implemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), [OSCL\\_wStackString< MaxBufSize >](#), and [OSCL\\_wFastString](#).

#### 7.88.4.5 `virtual uint32 OSCL_wString::get_size () [pure virtual]`

Implemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), [OSCL\\_wStackString< MaxBufSize >](#), and [OSCL\\_wFastString](#).

#### 7.88.4.6 `virtual chartype* OSCL_wString::get_str () [pure virtual]`

Implemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), [OSCL\\_wStackString< MaxBufSize >](#), and [OSCL\\_wFastString](#).

**7.88.4.7 virtual int8 OSCL\_wString::hash () [virtual]**

**7.88.4.8 virtual bool OSCL\_wString::is\_writable () [virtual]**

**7.88.4.9 bool OSCL\_wString::operator!= (const OSCL\_wString & src) const**

**7.88.4.10 OSCL\_wString& OSCL\_wString::operator+= (const chartype c)**

**7.88.4.11 OSCL\_wString& OSCL\_wString::operator+= (const chartype \* cstr)**

**7.88.4.12 OSCL\_wString& OSCL\_wString::operator+= (const OSCL\_wString & src)**

**7.88.4.13 bool OSCL\_wString::operator< (const OSCL\_wString & src) const**

**7.88.4.14 bool OSCL\_wString::operator<= (const OSCL\_wString & src) const**

**7.88.4.15 OSCL\_wString& OSCL\_wString::operator= (const chartype \* cstr)**

Reimplemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), [OSCL\\_wStackString< MaxBufSize >](#), and [OSCL\\_wFastString](#).

**7.88.4.16 OSCL\_wString& OSCL\_wString::operator= (const OSCL\_wString & src)**

Reimplemented in [OSCL\\_wHeapString< Alloc >](#), [OSCL\\_wHeapStringA](#), and [OSCL\\_wStackString< MaxBufSize >](#).

**7.88.4.17 bool OSCL\_wString::operator== (const chartype \* cstr) const**

**7.88.4.18 bool OSCL\_wString::operator== (const OSCL\_wString & src) const**

**7.88.4.19 bool OSCL\_wString::operator> (const OSCL\_wString & src) const**

**7.88.4.20 bool OSCL\_wString::operator>= (const OSCL\_wString & src) const**

**7.88.4.21 ]**

**chartype OSCL\_wString::operator[ ] (uint32 index) const**

- 7.88.4.22 **virtual chartype** OSCL\_wString::read (*uint32 index*) const [virtual]
- 7.88.4.23 **virtual void** OSCL\_wString::set\_len (*uint32 len*) [protected, pure virtual]
- 7.88.4.24 **virtual void** OSCL\_wString::set\_rep (*const OSCL\_wString & src*) [protected, pure virtual]
- 7.88.4.25 **virtual void** OSCL\_wString::set\_rep (*const chartype \* cstr*) [protected, pure virtual]
- 7.88.4.26 **virtual uint32** OSCL\_wString::setrep\_to\_wide\_char (*const char \* src, uint32 len, TOSCL\_wStringOp op, Oscl\_DefAlloc \* aAlloc*) [virtual]
- 7.88.4.27 **virtual void** OSCL\_wString::write (*uint32 offset, uint32 length, const chartype \* buf*) [virtual]
- 7.88.4.28 **virtual void** OSCL\_wString::write (*uint32 index, chartype c*) [virtual]


The documentation for this class was generated from the following file:

- [oscl\\_string.h](#)

## 7.89 OsclAcceptMethod Class Reference

```
#include <oscl_socket_accept.h>
```

Inheritance diagram for OsclAcceptMethod::



### Public Methods

- [~OsclAcceptMethod \(\)](#)
- [TPVSocketEvent Accept \(int32 aTimeout\)](#)
- [void DiscardAcceptedSocket \(\)](#)
- [OsclSocketI \\* GetAcceptedSocket \(\)](#)
- [OsclAcceptRequest \\* AcceptRequest \(\)](#)

### Static Public Methods

- [OsclAcceptMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.89.1 Constructor & Destructor Documentation

##### 7.89.1.1 OsclAcceptMethod::~OsclAcceptMethod ()

#### 7.89.2 Member Function Documentation

##### 7.89.2.1 TPVSocketEvent OsclAcceptMethod::Accept (int32 aTimeout)

##### 7.89.2.2 OsclAcceptRequest\* OsclAcceptMethod::AcceptRequest () [inline]

##### 7.89.2.3 void OsclAcceptMethod::DiscardAcceptedSocket ()

##### 7.89.2.4 OsclSocketI\* OsclAcceptMethod::GetAcceptedSocket ()

##### 7.89.2.5 OsclAcceptMethod\* OsclAcceptMethod::NewL (OsclIPSocketI &c) [static]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_accept.h](#)

## 7.90 OsclAcceptRequest Class Reference

```
#include <oscl_socket_accept.h>
```

Inheritance diagram for OsclAcceptRequest::



### Public Methods

- [OsclAcceptRequest \(OsclSocketMethod &c\)](#)
- [void Accept \(OsclSocketI &aSocket\)](#)

#### 7.90.1 Constructor & Destructor Documentation

**7.90.1.1 OsclAcceptRequest::OsclAcceptRequest ([OsclSocketMethod & c](#)) [inline]**

#### 7.90.2 Member Function Documentation

**7.90.2.1 void OsclAcceptRequest::Accept ([OsclSocketI & aSocket](#))**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_accept.h](#)

## 7.91 OsclActiveObject Class Reference

```
#include <oscl_scheduler_ao.h>
```

Inheritance diagram for OsclActiveObject::



### Public Types

- enum **OsclActivePriority** { **EPriorityIdle** = -100, **EPriorityLow** = -20, **EPriorityNominal** = 0, **EPriorityHigh** = 10, **EPriorityHighest** = 20 }

### Public Methods

- OSCL\_IMPORT\_REF **OsclActiveObject** (int32 aPriority, const char name[ ])
- virtual OSCL\_IMPORT\_REF ~**OsclActiveObject** ()
- OSCL\_IMPORT\_REF void **SetBusy** ()
- OSCL\_IMPORT\_REF bool **IsBusy** () const
- OSCL\_IMPORT\_REF void **PendForExec** ()
- OSCL\_IMPORT\_REF void **PendComplete** (int32 aStatus)
- OSCL\_IMPORT\_REF void **AddToScheduler** ()
- OSCL\_IMPORT\_REF void **RemoveFromScheduler** ()
- OSCL\_IMPORT\_REF void **RunIfNotReady** ()
- OSCL\_IMPORT\_REF void **Cancel** ()
- OSCL\_IMPORT\_REF int32 **Priority** () const
- OSCL\_IMPORT\_REF int32 **Status** () const
- OSCL\_IMPORT\_REF void **SetStatus** (int32)
- OSCL\_IMPORT\_REF **OsclAOStatus & StatusRef** ()

## Protected Methods

- virtual OSCL\_IMPORT\_REF void [DoCancel \(\)](#)
- virtual OSCL\_IMPORT\_REF int32 [RunError \(int32 aError\)](#)

### 7.91.1 Detailed Description

User base class for execution objects. OsclActiveObject defines an execution object without any timer. This AO can be used across threads, i.e. the request can be activated in one thread and completed in another.

### 7.91.2 Member Enumeration Documentation

#### 7.91.2.1 enum OsclActiveObject::OsclActivePriority

Scheduling priorities.

##### Enumeration values:

- EPriorityIdle** A low priority, useful for execution objects representing background processing.  
**EPriorityLow** A priority higher than EPriorityIdle but lower than EPriorityNominal.  
**EPriorityNominal** Most exec objects will have this priority.  
**EPriorityHigh** A priority higher than EPriorityNominal; useful for execution objects handling user input.  
**EPriorityHighest** A priority higher than EPriorityHighest.

### 7.91.3 Constructor & Destructor Documentation

#### 7.91.3.1 OSCL\_IMPORT\_REF OsclActiveObject::OsclActiveObject (int32 *aPriority*, const char *name*[])

Constructor.

##### Parameters:

- aPriority* (input param): scheduling priority  
*name* (input param): optional name for this AO.

#### 7.91.3.2 virtual OSCL\_IMPORT\_REF OsclActiveObject::~OsclActiveObject () [virtual]

Destructor.

### 7.91.4 Member Function Documentation

#### 7.91.4.1 OSCL\_IMPORT\_REF void OsclActiveObject::AddToScheduler ()

Add this exec object to the current thread's scheduler.

Reimplemented from [PVActiveBase](#).

#### 7.91.4.2 OSCL\_IMPORT\_REF void OsclActiveObject::Cancel ()

Cancel any pending request. If the request is readied, this will call the DoCancel routine, wait for the request to cancel, then set the request idle. The AO will not run. If the request is not readied, it does nothing. Request must be canceled from the same thread in which it is scheduled.

Reimplemented from [PVActiveBase](#).

#### 7.91.4.3 virtual OSCL\_IMPORT\_REF void OsclActiveObject::DoCancel () [protected, virtual]

Cancel request handler. This gets called by scheduler when the request is cancelled. The default routine will complete the request. If any additional action is needed, the derived class may override this. If the derived class does override DoCancel, it must complete the request.

Implements [PVActiveBase](#).

Reimplemented in [OsclDNSRequestAO](#), and [OsclSocketRequestAO](#).

#### 7.91.4.4 OSCL\_IMPORT\_REF bool OsclActiveObject::IsBusy ()

Return true if this AO is pending, false otherwise.

#### 7.91.4.5 OSCL\_IMPORT\_REF void OsclActiveObject::PendComplete (int32 *aStatus*)

Complete the active request for the AO. This API is thread-safe. If the request is not pending, this call will leave.

**Parameters:**

*aStatus*: request completion status.

#### 7.91.4.6 OSCL\_IMPORT\_REF void OsclActiveObject::PendForExec ()

Set request active for this AO and set the status to pending. PendForExec is identical to SetActive, but it additionally sets the request status to OSCL\_REQUEST\_PENDING.

#### 7.91.4.7 OSCL\_IMPORT\_REF int32 OsclActiveObject::Priority ()

Return scheduling priority of this exec object.

#### 7.91.4.8 OSCL\_IMPORT\_REF void OsclActiveObject::RemoveFromScheduler ()

Remove this AO from its scheduler. Will leave if the calling thread context does not match the scheduling thread. Cancels any readied request before removing.

Reimplemented from [PVActiveBase](#).

**7.91.4.9 virtual OSCL\_IMPORT\_REF int32 OsclActiveObject::RunError (int32 *aError*)  
[protected, virtual]**

Run Error handler. This gets called by scheduler when the Run routine leaves. The default implementation simply returns the leave code. If the derived class wants to handle errors from Run, it may override this. The RunError should return OsclErrNone if it handles the error, otherwise it should return the input error code.

**Parameters:**

*aError*: the leave code generated by the Run.

Implements [PVActiveBase](#).

**7.91.4.10 OSCL\_IMPORT\_REF void OsclActiveObject::RunIfNotReady ()**

Complete this AO's request immediately. If the AO is already active, this will do nothing. Will leave if the AO is not added to any scheduler, or if the calling thread context does not match the scheduling thread.

**7.91.4.11 OSCL\_IMPORT\_REF void OsclActiveObject::SetBusy ()**

Set object ready for this AO, additionally sets the request status to OSCL\_REQUEST\_PENDING. Will leave if the request is already readied, or the execution object is not added to any scheduler, or the calling thread context does not match the scheduler thread.

**7.91.4.12 OSCL\_IMPORT\_REF void OsclActiveObject::SetStatus (int32)****7.91.4.13 OSCL\_IMPORT\_REF int32 OsclActiveObject::Status ()**

Request status access

**7.91.4.14 OSCL\_IMPORT\_REF OsclAOStatus& OsclActiveObject::StatusRef ()**


The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_ao.h](#)

## 7.92 OsclAllocDestructDealloc Class Reference

```
#include <oscl_defalloc.h>
```

Inheritance diagram for OsclAllocDestructDealloc::



### Public Methods

- virtual ~OsclAllocDestructDealloc ()

#### 7.92.1 Constructor & Destructor Documentation

**7.92.1.1 virtual OsclAllocDestructDealloc::~OsclAllocDestructDealloc () [inline, virtual]**

The documentation for this class was generated from the following file:

- [oscl\\_defalloc.h](#)

## 7.93 OsclAOStatus Class Reference

```
#include <oscl_aostatus.h>
```

### Public Methods

- OSCL\_INLINE OsclAOStatus ()
- OSCL\_INLINE OsclAOStatus (int32 aStatus)
- OSCL\_INLINE int32 operator= (int32 aStatus)
- OSCL\_INLINE int32 operator== (int32 aStatus) const
- OSCL\_INLINE int32 operator!= (int32 aStatus) const
- OSCL\_INLINE int32 operator>= (int32 aStatus) const
- OSCL\_INLINE int32 operator<= (int32 aStatus) const
- OSCL\_INLINE int32 operator> (int32 aStatus) const
- OSCL\_INLINE int32 operator< (int32 aStatus) const
- OSCL\_INLINE int32 Value () const

#### 7.93.1 Constructor & Destructor Documentation

7.93.1.1 OSCL\_INLINE OsclAOStatus::OsclAOStatus ()

7.93.1.2 OSCL\_INLINE OsclAOStatus::OsclAOStatus (int32 *aStatus*)

#### 7.93.2 Member Function Documentation

7.93.2.1 OSCL\_INLINE int32 OsclAOStatus::operator!= (int32 *aStatus*) const

7.93.2.2 OSCL\_INLINE int32 OsclAOStatus::operator< (int32 *aStatus*) const

7.93.2.3 OSCL\_INLINE int32 OsclAOStatus::operator<= (int32 *aStatus*) const

7.93.2.4 OSCL\_INLINE int32 OsclAOStatus::operator= (int32 *aStatus*)

7.93.2.5 OSCL\_INLINE int32 OsclAOStatus::operator== (int32 *aStatus*) const

7.93.2.6 OSCL\_INLINE int32 OsclAOStatus::operator> (int32 *aStatus*) const

7.93.2.7 OSCL\_INLINE int32 OsclAOStatus::operator>= (int32 *aStatus*) const

7.93.2.8 OSCL\_INLINE int32 OsclAOStatus::Value ()


The documentation for this class was generated from the following file:

- [oscl\\_aostatus.h](#)

## 7.94 OsclAsyncFile Class Reference

```
#include <oscl_file_async_read.h>
```

Inheritance diagram for OsclAsyncFile::



### Public Methods

- [`~OsclAsyncFile \(\)`](#)
- [`int32 Open \(const oscl\_wchar \*filename, uint32 mode, const OsclNativeFileParams &params, Oscl\_FileServer &fileserv\)`](#)
- [`int32 Open \(const char \*filename, uint32 mode, const OsclNativeFileParams &params, Oscl\_FileServer &fileserv\)`](#)
- [`int32 Seek \(TOsclFileOffset offset, Oscl\_File::seek\_type origin\)`](#)
- [`TOsclFileOffset Tell \(\)`](#)
- [`uint32 Read \(OsclAny \*aBuffer1, uint32 aDataSize, uint32 aNumElements\)`](#)
- [`int32 EndOfFile \(\)`](#)
- [`TOsclFileOffset Size \(\)`](#)
- [`int32 Close \(\)`](#)
- [`uint32 Write \(const OsclAny \*aBuffer1, uint32 aDataSize, uint32 aNumElements\)`](#)
- [`uint32 Flush \(\)`](#)

### Static Public Methods

- [`OsclAsyncFile \* NewL \(OsclNativeFile &aAsyncFile, int32 aCacheSize, PVLogger \*\)`](#)
- [`void Delete \(OsclAsyncFile \*\)`](#)

### Data Fields

- [`uint32 iNumOfRun`](#)
- [`uint32 iNumOfRunErr`](#)

#### 7.94.1 Detailed Description

OsclAsyncFile

## 7.94.2 Constructor & Destructor Documentation

### 7.94.2.1 OsclAsyncFile::~OsclAsyncFile ()

Destructor.

## 7.94.3 Member Function Documentation

### 7.94.3.1 int32 OsclAsyncFile::Close ()

### 7.94.3.2 void OsclAsyncFile::Delete (OsclAsyncFile \*) [static]

### 7.94.3.3 int32 OsclAsyncFile::EndOfFile ()

### 7.94.3.4 uint32 OsclAsyncFile::Flush () [inline]

### 7.94.3.5 OsclAsyncFile\* OsclAsyncFile::NewL (OsclNativeFile & aSyncFile, int32 aCacheSize, PVLogger \*) [static]

Two-phased constructor.

#### Parameters:

*aSyncFile*: open handle for async file read. Note: it is the caller's job to open/close this file handle.

*aSyncFile*: duplicate open handle for sync file read. Note: it is the caller's job to open this file handle, but this class will close the handle.

*aCacheSize*: size of one of the individual cache buffers. The total cached data size will be larger, since multiple buffers are used.

*aStartAsyncRead*: When true, async file read will start immediately. When false, read will not begin until StartAsyncRead is called.

- 7.94.3.6 int32 OsclAsyncFile::Open (const char \**filename*, uint32 *mode*, const OsclNativeFileParams & *params*, Oscl\_FileServer & *fileserv*)
- 7.94.3.7 int32 OsclAsyncFile::Open (const oscl\_wchar \**filename*, uint32 *mode*, const OsclNativeFileParams & *params*, Oscl\_FileServer & *fileserv*)
- 7.94.3.8 uint32 OsclAsyncFile::Read (OsclAny \**aBuffer1*, uint32 *aDataSize*, uint32 *aNumElements*)
- 7.94.3.9 int32 OsclAsyncFile::Seek (TOsclFileOffset *offset*, Oscl\_File::seek\_type *origin*)
- 7.94.3.10 TOsclFileOffset OsclAsyncFile::Size ()
- 7.94.3.11 TOsclFileOffset OsclAsyncFile::Tell ()
- 7.94.3.12 uint32 OsclAsyncFile::Write (const OsclAny \**aBuffer1*, uint32 *aDataSize*, uint32 *aNumElements*) [inline]

#### 7.94.4 Field Documentation

- 7.94.4.1 uint32 OsclAsyncFile::iNumOfRun

- 7.94.4.2 uint32 OsclAsyncFile::iNumOfRunErr


The documentation for this class was generated from the following file:

- [oscl\\_file\\_async\\_read.h](#)

## 7.95 OsclAsyncFileBuffer Class Reference

```
#include <oscl_file_async_read.h>
```

Inheritance diagram for OsclAsyncFileBuffer::



### Public Methods

- `~OsclAsyncFileBuffer ()`
- `void CleanInUse ()`
- `void SetInUse ()`
- `bool IsInUse ()`
- `bool IsValid ()`
- `TOsclFileOffset Offset ()`
- `void SetOffset (TOsclFileOffset aOffset)`
- `int32 Length ()`
- `bool HasThisOffset (TOsclFileOffset aOffset)`
- `int32 Id ()`
- `OsclBuf * Buffer ()`
- `void UpdateData ()`
- `void StartAsyncRead (bool aStartAsyncRead)`

### Static Public Methods

- `OsclAsyncFileBuffer * NewL (int32 aBufferSize, int32 aId)`

#### 7.95.1 Detailed Description

Buffer class used with async read. We keep an array of these, covering consecutive areas of the file. This allows for some seeking without requiring a full flush & refill each time.

## 7.95.2 Constructor & Destructor Documentation

7.95.2.1 `OsclAsyncFileBuffer::~OsclAsyncFileBuffer ()`

## 7.95.3 Member Function Documentation

7.95.3.1 `OsclBuf* OsclAsyncFileBuffer::Buffer ()`

7.95.3.2 `void OsclAsyncFileBuffer::CleanInUse () [inline]`

7.95.3.3 `bool OsclAsyncFileBuffer::HasThisOffset (TOsclFileOffset aOffset)`

7.95.3.4 `int32 OsclAsyncFileBuffer::Id () [inline]`

7.95.3.5 `bool OsclAsyncFileBuffer::IsInUse () [inline]`

7.95.3.6 `bool OsclAsyncFileBuffer::IsValid () [inline]`

7.95.3.7 `int32 OsclAsyncFileBuffer::Length () [inline]`

7.95.3.8 `OsclAsyncFileBuffer* OsclAsyncFileBuffer::NewL (int32 aBufferSize, int32 aId) [static]`

7.95.3.9 `TOsclFileOffset OsclAsyncFileBuffer::Offset () [inline]`

7.95.3.10 `void OsclAsyncFileBuffer::SetInUse () [inline]`

7.95.3.11 `void OsclAsyncFileBuffer::SetOffset (TOsclFileOffset aOffset) [inline]`

7.95.3.12 `void OsclAsyncFileBuffer::StartAsyncRead (bool aStartAsyncRead)`

7.95.3.13 `void OsclAsyncFileBuffer::UpdateData ()`

The documentation for this class was generated from the following file:

- `oscl_file_async_read.h`

## 7.96 OsclAuditCB Class Reference

```
#include <oscl_mem.h>
```

### Public Methods

- [OsclAuditCB \(\)](#)
- [OsclAuditCB \(const OsclMemStatsNode \\*myStatsNode, OsclMemAudit \\*ptr\)](#)

### Data Fields

- [const OsclMemStatsNode \\* pStatsNode](#)
- [OsclMemAudit \\* pAudit](#)

#### 7.96.1 Constructor & Destructor Documentation

**7.96.1.1 OsclAuditCB::OsclAuditCB () [inline]**

**7.96.1.2 OsclAuditCB::OsclAuditCB (const OsclMemStatsNode \* *myStatsNode*, OsclMemAudit \* *ptr*) [inline]**

#### 7.96.2 Field Documentation

**7.96.2.1 OsclMemAudit\* OsclAuditCB::pAudit**

**7.96.2.2 const OsclMemStatsNode\* OsclAuditCB::pStatsNode**


The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.97 OsclBindMethod Class Reference

```
#include <oscl_socket_bind.h>
```

Inheritance diagram for OsclBindMethod::



### Public Methods

- [~OsclBindMethod \(\)](#)
- [TPVSocketEvent Bind \(OsclNetworkAddress &aAddress, int32 aTimeout\)](#)
- [OsclBindRequest \\* BindRequest \(\)](#)

### Static Public Methods

- [OsclBindMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.97.1 Constructor & Destructor Documentation

##### 7.97.1.1 OsclBindMethod::~OsclBindMethod ()

#### 7.97.2 Member Function Documentation

##### 7.97.2.1 TPVSocketEvent OsclBindMethod::Bind (OsclNetworkAddress & aAddress, int32 aTimeout)

##### 7.97.2.2 OsclBindRequest\* OsclBindMethod::BindRequest () [inline]

##### 7.97.2.3 OsclBindMethod\* OsclBindMethod::NewL (OsclIPSocketI &c) [static]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_bind.h](#)

## 7.98 OsclBindRequest Class Reference

```
#include <oscl_socket_bind.h>
```

Inheritance diagram for OsclBindRequest::



### Public Methods

- [OsclBindRequest \(OsclSocketMethod &c\)](#)
- [void Bind \(OsclNetworkAddress &aAddress\)](#)

#### 7.98.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.98.2 Constructor & Destructor Documentation

##### 7.98.2.1 OsclBindRequest::OsclBindRequest ([OsclSocketMethod & c](#)) [inline]

#### 7.98.3 Member Function Documentation

##### 7.98.3.1 void OsclBindRequest::Bind ([OsclNetworkAddress & aAddress](#))


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_bind.h](#)

## 7.99 OsclBinIStream Class Reference

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinIStream::



### Public Methods

- [OsclBinIStream \(\)](#)
- [~OsclBinIStream \(\)](#)
- uint8 [Read\\_uint8 \(\)](#)

*This method reads an unsigned short from the stream.*

- OsclBinIStream & [get \(int8 \\*data, int32 size\)](#)

*This method reads 'length' number of bytes from the stream and places them in 'data'.*

#### 7.99.1 Constructor & Destructor Documentation

**7.99.1.1 OsclBinIStream::OsclBinIStream () [inline]**

**7.99.1.2 OsclBinIStream::~OsclBinIStream () [inline]**

#### 7.99.2 Member Function Documentation

**7.99.2.1 OsclBinIStream& OsclBinIStream::get (int8 \* data, int32 size)**

This method reads 'length' number of bytes from the stream and places them in 'data'.

**Parameters:**

*data* is a pointer to the place to store the bytes read

*size* is the number of bytes to read

**7.99.2.2 uint8 OsclBinIStream::Read\_uint8 ()**

This method reads an unsigned short from the stream.

**Returns:**

Unsigned short read from the stream.


The documentation for this class was generated from the following file:

- [oscl\\_bin\\_stream.h](#)

## 7.100 OsclBinIStreamBigEndian Class Reference

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinIStreamBigEndian::



### Public Methods

- [OsclBinIStreamBigEndian \(\)](#)
- [void Read \(int8 &data\)](#)
- [void Read \(uint8 &data\)](#)
- [void Read \(int16 &data\)](#)
- [void Read \(uint16 &data\)](#)
- [void Read \(int32 &data\)](#)
- [void Read \(uint32 &data\)](#)
- [OsclBinIStreamBigEndian & operator>> \(int8 &data\)](#)

*This method reads a int8 from the stream and stores it in 'data'.*

- [OsclBinIStream & operator>> \(uint8 &data\)](#)

*This method reads a uint8 from the stream and stores it in 'data'.*

- [OsclBinIStreamBigEndian & operator>> \(int16 &data\)](#)

*This method reads a int16 from the stream and stores it in 'data'.*

- [OsclBinIStreamBigEndian & operator>> \(uint16 &data\)](#)

*This method reads a uint16 from the stream and stores it in 'data'.*

- [OsclBinIStreamBigEndian & operator>> \(int32 &data\)](#)

*This method reads a int32 from the stream and stores it in 'data'.*

- [OsclBinIStreamBigEndian & operator>> \(uint32 &data\)](#)

*This method reads a uint32 from the stream and stores it in 'data'.*

- [uint16 Read\\_uint16 \(\)](#)

*This method reads an unsigned short from the stream.*

- [uint32 Read\\_uint32 \(\)](#)

*This method reads an unsigned long from the stream.*

## 7.100.1 Constructor & Destructor Documentation

**7.100.1.1 OsclBinIStreamBigEndian::OsclBinIStreamBigEndian () [inline]**

## 7.100.2 Member Function Documentation

**7.100.2.1 OsclBinIStreamBigEndian& OsclBinIStreamBigEndian::operator>> (uint32 & data)**

This method reads a uint32 from the stream and stores it in 'data'.

**7.100.2.2 OsclBinIStreamBigEndian& OsclBinIStreamBigEndian::operator>> (int32 & data)**

This method reads a int32 from the stream and stores it in 'data'.

**7.100.2.3 OsclBinIStreamBigEndian& OsclBinIStreamBigEndian::operator>> (uint16 & data)**

This method reads a uint16 from the stream and stores it in 'data'.

**7.100.2.4 OsclBinIStreamBigEndian& OsclBinIStreamBigEndian::operator>> (int16 & data)**

This method reads a int16 from the stream and stores it in 'data'.

**7.100.2.5 OsclBinIStream& OsclBinIStreamBigEndian::operator>> (uint8 & data)**

This method reads a uint8 from the stream and stores it in 'data'.

**7.100.2.6 OsclBinIStreamBigEndian& OsclBinIStreamBigEndian::operator>> (int8 & data)**

This method reads a int8 from the stream and stores it in 'data'.

**7.100.2.7 void OsclBinIStreamBigEndian::Read (uint32 & data)**

**7.100.2.8 void OsclBinIStreamBigEndian::Read (int32 & data)**

**7.100.2.9 void OsclBinIStreamBigEndian::Read (uint16 & data)**

**7.100.2.10 void OsclBinIStreamBigEndian::Read (int16 & data)**

**7.100.2.11 void OsclBinIStreamBigEndian::Read (uint8 & data)**

**7.100.2.12 void OsclBinIStreamBigEndian::Read (int8 & data)**

**7.100.2.13 uint16 OsclBinIStreamBigEndian::Read\_uint16 ()**

This method reads an unsigned short from the stream.

### Returns:

Unsigned short read from the stream.

### 7.100.2.14 uint32 OsclBinIStreamBigEndian::Read\_uint32 ()

This method reads an unsigned long from the stream.

**Returns:**

unsigned long read from the stream.


The documentation for this class was generated from the following file:

- [oscl\\_bin\\_stream.h](#)

## 7.101 OsclBinIStreamLittleEndian Class Reference

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinIStreamLittleEndian::



### Public Methods

- [OsclBinIStreamLittleEndian \(\)](#)  
[OsclBinIStreamLittleEndian & operator>> \(int8 &data\)](#)  
*This method reads a int8 from the stream and stores it in 'data'.*
- [OsclBinIStreamLittleEndian & operator>> \(uint8 &data\)](#)  
*This method reads a uint8 from the stream and stores it in 'data'.*
- [OsclBinIStreamLittleEndian & operator>> \(int16 &data\)](#)  
*This method reads a int16 from the stream and stores it in 'data'.*
- [OsclBinIStreamLittleEndian & operator>> \(uint16 &data\)](#)  
*This method reads a uint16 from the stream and stores it in 'data'.*
- [OsclBinIStreamLittleEndian & operator>> \(int32 &data\)](#)  
*This method reads a int32 from the stream and stores it in 'data'.*
- [OsclBinIStreamLittleEndian & operator>> \(uint32 &data\)](#)  
*This method reads a uint32 from the stream and stores it in 'data'.*

### Protected Methods

- uint16 [Read\\_uint16 \(\)](#)
- uint32 [Read\\_uint32 \(\)](#)

### 7.101.1 Constructor & Destructor Documentation

**7.101.1.1 OsclBinIStreamLittleEndian::OsclBinIStreamLittleEndian () [inline]**

### 7.101.2 Member Function Documentation

**7.101.2.1 OsclBinIStreamLittleEndian& OsclBinIStreamLittleEndian::operator>> (uint32 & data)**

This method reads a uint32 from the stream and stores it in 'data'.

**7.101.2.2 OsclBinIStreamLittleEndian& OsclBinIStreamLittleEndian::operator>> (int32 & data)**

This method reads a int32 from the stream and stores it in 'data'.

**7.101.2.3 OsclBinIStreamLittleEndian& OsclBinIStreamLittleEndian::operator>> (uint16 & data)**

This method reads a uint16 from the stream and stores it in 'data'.

**7.101.2.4 OsclBinIStreamLittleEndian& OsclBinIStreamLittleEndian::operator>> (int16 & data)**

This method reads a int16 from the stream and stores it in 'data'.

**7.101.2.5 OsclBinIStreamLittleEndian& OsclBinIStreamLittleEndian::operator>> (uint8 & data)**

This method reads a uint8 from the stream and stores it in 'data'.

**7.101.2.6 OsclBinIStreamLittleEndian& OsclBinIStreamLittleEndian::operator>> (int8 & data)**

This method reads a int8 from the stream and stores it in 'data'.

**7.101.2.7 uint16 OsclBinIStreamLittleEndian::Read\_uint16 () [protected]**

**7.101.2.8 uint32 OsclBinIStreamLittleEndian::Read\_uint32 () [protected]**

The documentation for this class was generated from the following file:


- [oscl\\_bin\\_stream.h](#)

## 7.102 OsclBinOStream Class Reference

Class OsclBinOStream implements the basic stream functions for an output stream.

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinOStream:::



### Public Methods

- [OsclBinOStream \(\)](#)
- virtual [~OsclBinOStream \(\)](#)
- [OsclBinOStream & write \(const int8 \\*data, int32 size\)](#)

*This method writes 'length' number of bytes stored in 'data' to the stream.*

### 7.102.1 Detailed Description

Class OsclBinOStream implements the basic stream functions for an output stream.

### 7.102.2 Constructor & Destructor Documentation

**7.102.2.1 [OsclBinOStream::OsclBinOStream \(\) \[inline\]](#)**

**7.102.2.2 [virtual OsclBinOStream::~OsclBinOStream \(\) \[inline, virtual\]](#)**

### 7.102.3 Member Function Documentation

**7.102.3.1 [OsclBinOStream& OsclBinOStream::write \(const int8 \\* data, int32 size\)](#)**

This method writes 'length' number of bytes stored in 'data' to the stream.

The documentation for this class was generated from the following file:


- [oscl\\_bin\\_stream.h](#)

## 7.103 OsclBinOStreamBigEndian Class Reference

Class OsclBinOStreamBigEndian implements a binary output stream using big endian byte ordering.

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinOStreamBigEndian::



### Public Methods

- [OsclBinOStreamBigEndian \(\)](#)
- OsclBinOStreamBigEndian & [operator<< \(const int8 &data\)](#)  
*This method writes a int8 from 'data' to the stream.*
- OsclBinOStreamBigEndian & [operator<< \(const uint8 &data\)](#)  
*This method writes a uint8 from 'data' to the stream.*
- OsclBinOStreamBigEndian & [operator<< \(const int16 &data\)](#)  
*This method writes a int16 from 'data' to the stream.*
- OsclBinOStreamBigEndian & [operator<< \(const uint16 &data\)](#)  
*This method writes a uint16 from 'data' to the stream.*
- OsclBinOStreamBigEndian & [operator<< \(const int32 &data\)](#)  
*This method writes a int32 from 'data' to the stream.*
- OsclBinOStreamBigEndian & [operator<< \(const uint32 &data\)](#)  
*This method writes a uint32 from 'data' to the stream.*

### Protected Methods

- void [WriteUnsignedShort \(const uint16 data\)](#)
- void [WriteUnsignedLong \(const uint32 data\)](#)

#### 7.103.1 Detailed Description

Class OsclBinOStreamBigEndian implements a binary output stream using big endian byte ordering.

### 7.103.2 Constructor & Destructor Documentation

**7.103.2.1 OsclBinOStreamBigEndian::OsclBinOStreamBigEndian () [inline]**

### 7.103.3 Member Function Documentation

**7.103.3.1 OsclBinOStreamBigEndian& OsclBinOStreamBigEndian::operator<< (const uint32 & data)**

This method writes a uint32 from 'data' to the stream.

**7.103.3.2 OsclBinOStreamBigEndian& OsclBinOStreamBigEndian::operator<< (const int32 & data)**

This method writes a int32 from 'data' to the stream.

**7.103.3.3 OsclBinOStreamBigEndian& OsclBinOStreamBigEndian::operator<< (const uint16 & data)**

This method writes a uint16 from 'data' to the stream.

**7.103.3.4 OsclBinOStreamBigEndian& OsclBinOStreamBigEndian::operator<< (const int16 & data)**

This method writes a int16 from 'data' to the stream.

**7.103.3.5 OsclBinOStreamBigEndian& OsclBinOStreamBigEndian::operator<< (const uint8 & data)**

This method writes a uint8 from 'data' to the stream.

**7.103.3.6 OsclBinOStreamBigEndian& OsclBinOStreamBigEndian::operator<< (const int8 & data)**

This method writes a int8 from 'data' to the stream.

**7.103.3.7 void OsclBinOStreamBigEndian::WriteUnsignedLong (const uint32 data) [protected]**

**7.103.3.8 void OsclBinOStreamBigEndian::WriteUnsignedShort (const uint16 data) [protected]**

The documentation for this class was generated from the following file:


- [oscl\\_bin\\_stream.h](#)

## 7.104 OsclBinOStreamLittleEndian Class Reference

Class OsclBinOStreamLittleEndian implements a binary output stream using little endian byte ordering.

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinOStreamLittleEndian::



### Public Methods

- [OsclBinOStreamLittleEndian \(\)](#)
- [OsclBinOStreamLittleEndian & operator<< \(const int8 &data\)](#)  
*This method writes a int8 from 'data' to the stream.*
- [OsclBinOStreamLittleEndian & operator<< \(const uint8 &data\)](#)  
*This method writes a uint8 from 'data' to the stream.*
- [OsclBinOStreamLittleEndian & operator<< \(const int16 &data\)](#)  
*This method writes a int16 from 'data' to the stream.*
- [OsclBinOStreamLittleEndian & operator<< \(const uint16 &data\)](#)  
*This method writes a uint16 from 'data' to the stream.*
- [OsclBinOStreamLittleEndian & operator<< \(const int32 &data\)](#)  
*This method writes a int32 from 'data' to the stream.*
- [OsclBinOStreamLittleEndian & operator<< \(const uint32 &data\)](#)  
*This method writes a uint32 from 'data' to the stream.*

### Protected Methods

- [void WriteUnsignedShort \(const uint16 data\)](#)  
*This method writes 'data' (unsigned short) to the stream.*
- [void WriteUnsignedLong \(const uint32 data\)](#)  
*This method writes 'data' (unsigned long) to the stream.*

### 7.104.1 Detailed Description

Class OsclBinOStreamLittleEndian implements a binary output stream using little endian byte ordering.

## 7.104.2 Constructor & Destructor Documentation

**7.104.2.1 OsclBinOStreamLittleEndian::OsclBinOStreamLittleEndian () [inline]**

## 7.104.3 Member Function Documentation

**7.104.3.1 OsclBinOStreamLittleEndian& OsclBinOStreamLittleEndian::operator<< (const uint32 & data)**

This method writes a uint32 from 'data' to the stream.

**7.104.3.2 OsclBinOStreamLittleEndian& OsclBinOStreamLittleEndian::operator<< (const int32 & data)**

This method writes a int32 from 'data' to the stream.

**7.104.3.3 OsclBinOStreamLittleEndian& OsclBinOStreamLittleEndian::operator<< (const uint16 & data)**

This method writes a uint16 from 'data' to the stream.

**7.104.3.4 OsclBinOStreamLittleEndian& OsclBinOStreamLittleEndian::operator<< (const int16 & data)**

This method writes a int16 from 'data' to the stream.

**7.104.3.5 OsclBinOStreamLittleEndian& OsclBinOStreamLittleEndian::operator<< (const uint8 & data)**

This method writes a uint8 from 'data' to the stream.

**7.104.3.6 OsclBinOStreamLittleEndian& OsclBinOStreamLittleEndian::operator<< (const int8 & data)**

This method writes a int8 from 'data' to the stream.

**7.104.3.7 void OsclBinOStreamLittleEndian::WriteUnsignedLong (const uint32 data) [protected]**

This method writes 'data' (unsigned long) to the stream.

**7.104.3.8 void OsclBinOStreamLittleEndian::WriteUnsignedShort (const uint16 data) [protected]**

This method writes 'data' (unsigned short) to the stream.


The documentation for this class was generated from the following file:

- [oscl\\_bin\\_stream.h](#)

## 7.105 OsclBinStream Class Reference

```
#include <oscl_bin_stream.h>
```

Inheritance diagram for OsclBinStream::



### Public Methods

- [OsclBinStream \(\)](#)
- [bool good \(\)](#)

*This method determines if the stream is ok.*

- [bool eof \(\)](#)

*This method determines if end of stream has been reached.*

- [bool fail \(\)](#)

*This method determines if an error has occurred in the stream.*

- [void Attach \(void \\*buffer, uint32 l\\_length\)](#)

*This method specifies the data buffer to attach to the stream.*

- [void Attach \(const uint32 numFragments, const OsclMemoryFragment \\*fragPtr\)](#)

*This method specifies the memory fragment array to use for input.*

- [uint32 tellg \(\)](#)

*This method returns the current stream position.*

- [void Seek \(uint32 absPosition\)](#)

*This method seeks to the specified stream position.*

- [uint32 PositionInBlock \(\)](#)

*This method returns the current stream position.*

- [void seekFromCurrentPosition \(int32 offset\)](#)

*This method seeks to the specified offset from the current location.*

### Protected Types

- enum [state\\_t](#) { [GOOD\\_STATE](#), [EOF\\_STATE](#), [FAIL\\_STATE](#) }

## Protected Methods

- bool [ReserveSpace](#) (uint32 size)
- bool [HaveRoomInCurrentBlock](#) (uint32 size)

## Protected Attributes

- [state\\_t state](#)
- uint8 \* [pBasePosition](#)
- uint8 \* [pPosition](#)
- uint32 [length](#)
- const [OsclMemoryFragment](#) \* [nextFragPtr](#)
- int [fragsLeft](#)
- const [OsclMemoryFragment](#) \* [firstFragPtr](#)
- int [numFrags](#)
- [OsclMemoryFragment](#) [specialFragBuffer](#)

### 7.105.1 Member Enumeration Documentation

#### 7.105.1.1 enum OsclBinStream::state\_t [protected]

Enumeration values:

- GOOD\_STATE**
- EOF\_STATE**
- FAIL\_STATE**

### 7.105.2 Constructor & Destructor Documentation

#### 7.105.2.1 OsclBinStream::OsclBinStream () [inline]

### 7.105.3 Member Function Documentation

#### 7.105.3.1 void OsclBinStream::Attach (const uint32 *numFragments*, const [OsclMemoryFragment](#) \**fragPtr*)

This method specifies the memory fragment array to use for input.

This array should remain static while the stream refers to it.

**Parameters:**

*numFragments* is the number of elements in the array

*fragPtr* is the pointer to the MemoryFragment array

#### 7.105.3.2 void OsclBinStream::Attach (void \**buffer*, uint32 *l\_length*)

This methods specifies the data buffer to attach to the stream.

**Parameters:**

*buffer* will provide the input

*length* of the buffer

**7.105.3.3 bool OsclBinStream::eof ()**

This method determines if end of stream has been reached.

**Returns:**

true if end of stream has been reached.

**7.105.3.4 bool OsclBinStream::fail ()**

This method determines if an error has occurred in the stream.

**Returns:**

true if an error occurred in the stream.

**7.105.3.5 bool OsclBinStream::good ()**

This method determines if the stream is ok.

**Returns:**

true if stream is ok.

**7.105.3.6 bool OsclBinStream::HaveRoomInCurrentBlock (uint32 *size*) [protected]****7.105.3.7 uint32 OsclBinStream::PositionInBlock ()**

This method returns the current stream position.

**Returns:**

stream position.

**7.105.3.8 bool OsclBinStream::ReserveSpace (uint32 *size*) [protected]****7.105.3.9 void OsclBinStream::Seek (uint32 *absPosition*)**

This method seeks to the specified stream position.

**Returns:**

Stream position.

**7.105.3.10 void OsclBinStream::seekFromCurrentPosition (int32 *offset*)**

This method seeks to the specified offset from the current location.

**Parameters:**

*offset* from current stream location

### 7.105.3.11 uint32 OsclBinStream::tellg ()

This method returns the current stream position.

This method is to be used if the input stream is a pointer to the MemoryFragment array

**Returns:**

Stream position.

## 7.105.4 Field Documentation

**7.105.4.1 const OsclMemoryFragment\* OsclBinStream::firstFragPtr [protected]**

**7.105.4.2 int OsclBinStream::fragsLeft [protected]**

**7.105.4.3 uint32 OsclBinStream::length [protected]**

**7.105.4.4 const OsclMemoryFragment\* OsclBinStream::nextFragPtr [protected]**

**7.105.4.5 int OsclBinStream::numFrags [protected]**

**7.105.4.6 uint8\* OsclBinStream::pBasePosition [protected]**

**7.105.4.7 uint8\* OsclBinStream::pPosition [protected]**

**7.105.4.8 OsclMemoryFragment OsclBinStream::specialFragBuffer [protected]**

**7.105.4.9 state\_t OsclBinStream::state [protected]**


The documentation for this class was generated from the following file:

- [oscl\\_bin\\_stream.h](#)

## 7.106 OsclBuf Class Reference

```
#include <oscl_file_async_read.h>
```

Inheritance diagram for OsclBuf::



### Public Methods

- [OsclBuf](#) (int32 size)
- int32 [Length](#) ()
- [OsclPtr Des](#) ()
- [OsclPtrC DesC](#) ()

### Static Public Methods

- OsclBuf \* [NewL](#) (int32 size)
- void [Delete](#) (OsclBuf \*a)

### Data Fields

- uint8 \* [iBuffer](#)
- int32 [iMaxLength](#)
- int32 [iLength](#)

## 7.106.1 Constructor & Destructor Documentation

**7.106.1.1** `OsclBuf::OsclBuf (int32 size)` [inline]

## 7.106.2 Member Function Documentation

**7.106.2.1** `void OsclBuf::Delete (OsclBuf * a)` [inline, static]

**7.106.2.2** `OsclPtr OsclBuf::Des ()` [inline]

**7.106.2.3** `OsclPtrC OsclBuf::DesC ()` [inline]

**7.106.2.4** `int32 OsclBuf::Length ()` [inline]

**7.106.2.5** `OsclBuf* OsclBuf::NewL (int32 size)` [inline, static]

## 7.106.3 Field Documentation

**7.106.3.1** `uint8* OsclBuf::iBuffer`

**7.106.3.2** `int32 OsclBuf::iLength`

**7.106.3.3** `int32 OsclBuf::iMaxLength`

The documentation for this class was generated from the following file:

- [oscl\\_file\\_async\\_read.h](#)

## 7.107 OsclCompareLess< T > Class Template Reference

```
#include <oscl_priqueue.h>
```

### Public Methods

- int [compare](#) (T &a, T &b) const

```
template<class T> class OsclCompareLess< T >
```

#### 7.107.1 Member Function Documentation

**7.107.1.1 template<class T> int OsclCompareLess< T >::compare (T & a, T & b) const  
[inline]**

The documentation for this class was generated from the following file:

- [oscl\\_priqueue.h](#)

## 7.108 OsclComponentRegistry Class Reference

```
#include <oscl_registry_serv_impl.h>
```

### Public Methods

- [OsclComponentRegistry \(\)](#)
- [~OsclComponentRegistry \(\)](#)
- [int32 Register \(uint32 &aId, OSCL\\_String &, OsclComponentFactory\)](#)
- [int32 Unregister \(OSCL\\_String &\)](#)
- [int32 Unregister \(uint32\)](#)
- [OsclComponentFactory FindExact \(OSCL\\_String &\)](#)
- [void FindHierarchical \(OSCL\\_String &, Oscl\\_Vector< OsclRegistryAccessElement, OsclMemAllocator > &\)](#)
- [void OpenSession \(\)](#)
- [void CloseSession \(\)](#)

### Data Fields

- [OsclComponentRegistryData iData](#)
- [OsclMutex iMutex](#)
- [uint32 iComponentIdCounter](#)
- [uint32 iNumSessions](#)

#### 7.108.1 Detailed Description

Thread-safe singleton registry object.

## 7.108.2 Constructor & Destructor Documentation

7.108.2.1 `OsclComponentRegistry::OsclComponentRegistry ()`

7.108.2.2 `OsclComponentRegistry::~OsclComponentRegistry ()`

## 7.108.3 Member Function Documentation

7.108.3.1 `void OsclComponentRegistry::CloseSession ()`

7.108.3.2 `OsclComponentFactory OsclComponentRegistry::FindExact (OSCL_String &)`

7.108.3.3 `void OsclComponentRegistry::FindHierarchical (OSCL_String &, Oscl_Vector< OsclRegistryAccessElement, OsclMemAllocator > &)`

7.108.3.4 `void OsclComponentRegistry::OpenSession ()`

7.108.3.5 `int32 OsclComponentRegistry::Register (uint32 & aId, OSCL_String &, OsclComponentFactory)`

7.108.3.6 `int32 OsclComponentRegistry::Unregister (uint32)`

7.108.3.7 `int32 OsclComponentRegistry::Unregister (OSCL_String &)`

## 7.108.4 Field Documentation

7.108.4.1 `uint32 OsclComponentRegistry::iComponentIdCounter`

7.108.4.2 `OsclComponentRegistryData OsclComponentRegistry::iData`

7.108.4.3 `OsclMutex OsclComponentRegistry::iMutex`

7.108.4.4 `uint32 OsclComponentRegistry::iNumSessions`

The documentation for this class was generated from the following file:

- `oscl_registry_serv_impl.h`

## 7.109 OsclComponentRegistryData Class Reference

```
#include <oscl_registry_serv_impl.h>
```

### Public Methods

- [OsclComponentRegistryElement \\* Find \(OSCL\\_String &, bool aExact\)](#)

### Data Fields

- [Oscl\\_Vector< OsclComponentRegistryElement, OsclMemAllocator > iVec](#)

#### 7.109.1 Detailed Description

Registry

#### 7.109.2 Member Function Documentation

##### 7.109.2.1 [OsclComponentRegistryElement\\* OsclComponentRegistryData::Find \(OSCL\\_String &, bool aExact\)](#)

#### 7.109.3 Field Documentation

##### 7.109.3.1 [Oscl\\_Vector<OsclComponentRegistryElement, OsclMemAllocator> OsclComponentRegistryData::iVec](#)

The documentation for this class was generated from the following file:

- [oscl\\_registry\\_serv\\_impl.h](#)

## 7.110 OsclComponentRegistryElement Class Reference

```
#include <oscl_registry_serv_impl.h>
```

### Public Methods

- [OsclComponentRegistryElement \(OSCL\\_String &, OsclComponentFactory\)](#)
- [OsclComponentRegistryElement \(const OsclComponentRegistryElement &\)](#)
- [OsclComponentRegistryElement & operator= \(const OsclComponentRegistryElement &src\)](#)
- [~OsclComponentRegistryElement \(\)](#)
- [bool Match \(OSCL\\_String &aStr, bool aExact\)](#)

### Data Fields

- [OSCL\\_String \\* iId](#)
- [OsclComponentFactory iFactory](#)
- [uint32 iComponentId](#)

#### 7.110.1 Detailed Description

Data for each registered component.

#### 7.110.2 Constructor & Destructor Documentation

**7.110.2.1 OsclComponentRegistryElement::OsclComponentRegistryElement (OSCL\_String &, OsclComponentFactory)**

**7.110.2.2 OsclComponentRegistryElement::OsclComponentRegistryElement (const OsclComponentRegistryElement &)**

**7.110.2.3 OsclComponentRegistryElement::~OsclComponentRegistryElement ()**

#### 7.110.3 Member Function Documentation

**7.110.3.1 bool OsclComponentRegistryElement::Match (OSCL\_String & aStr, bool aExact)**

**7.110.3.2 OsclComponentRegistryElement& OsclComponentRegistryElement::operator= (const OsclComponentRegistryElement & src)**

#### 7.110.4 Field Documentation

**7.110.4.1 uint32 OsclComponentRegistryElement::iComponentId**

**7.110.4.2 OsclComponentFactory OsclComponentRegistryElement::iFactory**

**7.110.4.3 OSCL\_String\* OsclComponentRegistryElement::iId**


The documentation for this class was generated from the following file:

- [oscl\\_registry\\_serv\\_impl.h](#)

## 7.111 OsclConnectMethod Class Reference

```
#include <oscl_socket_connect.h>
```

Inheritance diagram for OsclConnectMethod::



### Public Methods

- [~OsclConnectMethod \(\)](#)
- [TPVSocketEvent Connect \(OsclNetworkAddress &aAddress, int32 aTimeout\)](#)
- [OsclConnectRequest \\* ConnectRequest \(\)](#)

### Static Public Methods

- [OsclConnectMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.111.1 Constructor & Destructor Documentation

##### 7.111.1.1 OsclConnectMethod::~OsclConnectMethod ()

#### 7.111.2 Member Function Documentation

##### 7.111.2.1 TPVSocketEvent OsclConnectMethod::Connect (OsclNetworkAddress & aAddress, int32 aTimeout)

##### 7.111.2.2 OsclConnectRequest\* OsclConnectMethod::ConnectRequest () [inline]

##### 7.111.2.3 OsclConnectMethod\* OsclConnectMethod::NewL (OsclIPSocketI & c) [static]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_connect.h](#)

## 7.112 OsclConnectRequest Class Reference

```
#include <oscl_socket_connect.h>
```

Inheritance diagram for OsclConnectRequest::



### Public Methods

- [OsclConnectRequest \(OsclSocketMethod &c\)](#)
- [void Connect \(OsclNetworkAddress &aAddress\)](#)

#### 7.112.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.112.2 Constructor & Destructor Documentation

**7.112.2.1 OsclConnectRequest::OsclConnectRequest ([OsclSocketMethod & c](#)) [inline]**

#### 7.112.3 Member Function Documentation

**7.112.3.1 void OsclConnectRequest::Connect ([OsclNetworkAddress & aAddress](#))**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_connect.h](#)

## 7.113 OsclDestructDealloc Class Reference

```
#include <oscl_defalloc.h>
```

Inheritance diagram for OsclDestructDealloc::



### Public Methods

- virtual ~OsclDestructDealloc ()
- virtual void [destruct\\_and\\_dealloc \(OsclAny \\*ptr\)=0](#)

#### 7.113.1 Constructor & Destructor Documentation

**7.113.1.1 virtual OsclDestructDealloc::~OsclDestructDealloc () [inline, virtual]**

#### 7.113.2 Member Function Documentation

**7.113.2.1 virtual void OsclDestructDealloc::destruct\_and\_dealloc (OsclAny \* ptr) [pure virtual]**

Implemented in [Oscl\\_TAlloc< T, Alloc >](#), [OsclMemAllocDestructDealloc< T >](#), [OsclMemBasicAllocDestructDealloc< T >](#), [Oscl\\_TAlloc< entry\\_type, Alloc >](#), [Oscl\\_TAlloc< node\\_type, TagTree\\_Allocator >](#), [Oscl\\_TAlloc< node\\_type, alloc\\_type >](#), [Oscl\\_TAlloc< MM\\_StatsNodeTagTreeType, OsclMemBasicAllocator >](#), [Oscl\\_TAlloc< char, alloc\\_type >](#), [Oscl\\_TAlloc< tag\\_base\\_unit, Alloc >](#), [Oscl\\_TAlloc< PVLogger, alloc\\_type >](#), and [Oscl\\_TAlloc< node\\_type, Alloc >](#).


The documentation for this class was generated from the following file:

- [oscl\\_defalloc.h](#)

## 7.114 OsclDNS Class Reference

```
#include <oscl_dns.h>
```

Inheritance diagram for OsclDNS::



### Public Methods

- OSCL\_IMPORT\_REF ~OsclDNS ()
- OSCL\_IMPORT\_REF TPVDNSEvent GetHostByName (char \*name, OsclNetworkAddress &addr, int32 aTimeoutMsec=-1, Oscl\_Vector< OsclNetworkAddress, OsclMemAllocator > \*aAddressList=NULL)
- OSCL\_IMPORT\_REF void CancelGetHostByName ()

### Static Public Methods

- OSCL\_IMPORT\_REF OsclDNS \* NewL (Oscl\_DefAlloc &alloc, OsclSocketServ &aServ, OsclDNSObserver &aObserver, uint32 aId)

### Friends

- class OsclDNSRequestAO

#### 7.114.1 Detailed Description

The DNS class

#### 7.114.2 Constructor & Destructor Documentation

##### 7.114.2.1 OSCL\_IMPORT\_REF OsclDNS::~OsclDNS ()

Destructor.

Note: the application must de-allocate the DNS object using the same allocator that was passed in the NewL object creation call.

#### 7.114.3 Member Function Documentation

##### 7.114.3.1 OSCL\_IMPORT\_REF void OsclDNS::CancelGetHostByName ()

Cancel GetHostByName

This method will cancel any pending GetHostByName operation on the current object, causing the GetHostByName to complete with error EPVDNSCancel. If there is no pending GetHostByName operation, this method will have no effect.

#### 7.114.3.2 OSCL\_IMPORT\_REF TPVDNSEvent OsclDNS::GetHostByName (char \* *name*, OsclNetworkAddress & *addr*, int32 *aTimeoutMsec* = -1, Oscl\_Vector< OsclNetworkAddress, OsclMemAllocator > \* *aAddressList* = NULL)

GetHostByName. This is an asynchronous method.

**Parameters:**

*name*: Null-terminated string containing the host name.

*addr*: The output address corresponding to the host. The ipAddr field will contain the network address of the host in dotted decimal notation.

*aTimeoutMsec*: A timeout for the request in milliseconds, or (-1) to indicate infinite wait.

*aAddressList* : A list of addresses for the host. @returns: EPVDNSPending for success, EPVDNSFailure for failure.

#### 7.114.3.3 OSCL\_IMPORT\_REF OsclDNS\* OsclDNS::NewL (Oscl\_DefAlloc & *alloc*, OsclSocketServ & *aServ*, OsclDNSObserver & *aObserver*, uint32 *aId*) [static]

DNS object creation.

**Parameters:**

*alloc*: Memory allocator

*aServ*: Socket server.

*aObserver*: DNS Event observer

*aId*: Unique ID for this DNS object. This ID will be included in all callbacks associated with this DNS object.

### 7.114.4 Friends And Related Function Documentation

#### 7.114.4.1 friend class OsclDNSRequestAO [friend]


The documentation for this class was generated from the following file:

- [oscl\\_dns.h](#)

## 7.115 OsclDNSI Class Reference

```
#include <oscl_dns_imp_pv.h>
```

Inheritance diagram for OsclDNSI::



### Public Methods

- [~OsclDNSI \(\)](#)
- int32 [Open \(OsclSocketServI &aServer\)](#)
- int32 [Close \(\)](#)
- void [GetHostByName \(GetHostNameParam &, OsclDNSRequestAO &\)](#)
- void [GetHostByNameSuccess \(GetHostNameParam &\)](#)
- void [GetNextHost \(OsclDNSRequestAO &\)](#)
- void [GetNextHostSuccess \(GetHostNameParam &\)](#)
- bool [GetHostByNameResponseContainsAliasInfo \(\)](#)

### Static Public Methods

- OsclDNSI \* [NewL \(Oscl\\_DefAlloc &a\)](#)

### Friends

- class [OsclDNSRequest](#)
- class [OsclGetHostByNameRequest](#)
- class [DNSRequestParam](#)

### 7.115.1 Detailed Description

OsclDNSI, non-Symbian implementation

### 7.115.2 Constructor & Destructor Documentation

#### 7.115.2.1 OsclDNSI::~OsclDNSI ()

### 7.115.3 Member Function Documentation

#### 7.115.3.1 int32 OsclDNSI::Close () [virtual]

Implements [OsclDNSIBase](#).

**7.115.3.2 void OsclDNSI::GetHostByName ([GetHostNameParam](#) &, [OsclDNSRequestAO](#) &)** [virtual]

Implements [OsclDNSIBase](#).

**7.115.3.3 bool OsclDNSI::GetHostNameResponseContainsAliasInfo ()** [virtual]

Implements [OsclDNSIBase](#).

**7.115.3.4 void OsclDNSI::GetHostNameSuccess ([GetHostNameParam](#) &)** [virtual]

Implements [OsclDNSIBase](#).

**7.115.3.5 void OsclDNSI::GetNextHost ([OsclDNSRequestAO](#) &)** [virtual]

Implements [OsclDNSIBase](#).

**7.115.3.6 void OsclDNSI::GetNextHostSuccess ([GetHostNameParam](#) &)** [virtual]

Implements [OsclDNSIBase](#).

**7.115.3.7 OsclDNSI\* OsclDNSI::NewL ([Oscl\\_DefAlloc](#) & *a*)** [static]

**7.115.3.8 int32 OsclDNSI::Open ([OsclSocketServI](#) & *aServer*)** [virtual]

Implements [OsclDNSIBase](#).

## 7.115.4 Friends And Related Function Documentation

**7.115.4.1 friend class DNSRequestParam** [friend]

**7.115.4.2 friend class OsclDNSRequest** [friend]

Reimplemented from [OsclDNSIBase](#).

**7.115.4.3 friend class OsclGetHostNameRequest** [friend]

Reimplemented from [OsclDNSIBase](#).


The documentation for this class was generated from the following file:

- [oscl\\_dns\\_imp\\_pv.h](#)

## 7.116 OsclDNSIBase Class Reference

```
#include <oscl_dns_imp_base.h>
```

Inheritance diagram for OsclDNSIBase::



### Public Methods

- virtual ~OsclDNSIBase ()
- virtual int32 Open (OsclSocketServI &aServer)=0
- virtual int32 Close ()=0
- virtual void GetHostByName (GetHostNameParam &, OsclDNSRequestAO &)=0
- virtual void GetHostByNameSuccess (GetHostNameParam &)=0
- virtual bool GetHostByNameResponseContainsAliasInfo ()=0
- virtual void GetNextHost (OsclDNSRequestAO &)=0
- virtual void GetNextHostSuccess (GetHostNameParam &)=0
- void CancelFxn (TPVDNSFx)

### Protected Methods

- OsclDNSIBase (Oscl\_DefAlloc &a)
- virtual bool IsReady (OsclDNSRequestAO &aObject)=0
- virtual void CancelGetHostByName ()=0

### Protected Attributes

- Oscl\_DefAlloc & iAlloc
- OsclSocketServI \* iSocketServ

### Friends

- class OsclDNSRequest
- class OsclGetHostNameRequest

### 7.116.1 Detailed Description

OsclDNSIBase is a common base class for all implementations.

## 7.116.2 Constructor & Destructor Documentation

**7.116.2.1** `virtual OsclDNSIBase::~OsclDNSIBase () [virtual]`

**7.116.2.2** `OsclDNSIBase::OsclDNSIBase (Oscl_DefAlloc & a) [protected]`

## 7.116.3 Member Function Documentation

**7.116.3.1** `void OsclDNSIBase::CancelFxn (TPVDNSFxn)`

**7.116.3.2** `virtual void OsclDNSIBase::CancelGetHostByName () [protected, pure virtual]`

**7.116.3.3** `virtual int32 OsclDNSIBase::Close () [pure virtual]`

Implemented in [OsclDNSI](#).

**7.116.3.4** `virtual void OsclDNSIBase::GetHostByName (GetHostNameParam &, OsclDNSRequestAO &) [pure virtual]`

Implemented in [OsclDNSI](#).

**7.116.3.5** `virtual bool OsclDNSIBase::GetHostByNameResponseContainsAliasInfo () [pure virtual]`

Implemented in [OsclDNSI](#).

**7.116.3.6** `virtual void OsclDNSIBase::GetHostByNameSuccess (GetHostNameParam &) [pure virtual]`

Implemented in [OsclDNSI](#).

**7.116.3.7** `virtual void OsclDNSIBase::GetNextHost (OsclDNSRequestAO &) [pure virtual]`

Implemented in [OsclDNSI](#).

**7.116.3.8** `virtual void OsclDNSIBase::GetNextHostSuccess (GetHostNameParam &) [pure virtual]`

Implemented in [OsclDNSI](#).

**7.116.3.9** `virtual bool OsclDNSIBase::IsReady (OsclDNSRequestAO & aObject) [protected, pure virtual]`

**7.116.3.10** `virtual int32 OsclDNSIBase::Open (OsclSocketServI & aServer) [pure virtual]`

Implemented in [OsclDNSI](#).

## 7.116.4 Friends And Related Function Documentation

### 7.116.4.1 friend class OsclDNSRequest [friend]

Reimplemented in [OsclDNSI](#).

### 7.116.4.2 friend class OsclGetHostByNameRequest [friend]

Reimplemented in [OsclDNSI](#).

## 7.116.5 Field Documentation

### 7.116.5.1 [Oscl\\_DefAlloc& OsclDNSIBase::iAlloc](#) [protected]

### 7.116.5.2 [OsclSocketServI\\* OsclDNSIBase::iSocketServ](#) [protected]


The documentation for this class was generated from the following file:

- [oscl\\_dns\\_imp\\_base.h](#)

## 7.117 OsclDNSMethod Class Reference

```
#include <oscl_dns_method.h>
```

Inheritance diagram for OsclDNSMethod::



### Public Methods

- [OsclDNSMethod \(Oscl\\_DefAlloc &a, const char \\*name, TPVDNSFxn fxn\)](#)
- void [Abort \(\)](#)
- void [AbortAll \(\)](#)
- void [CancelMethod \(\)](#)
- void [Run \(\)](#)

### Data Fields

- [OsclDNSObserver \\* iDNSObserver](#)
- uint32 [iId](#)
- [Oscl\\_DefAlloc & iAlloc](#)
- [TPVDNSFxn iDNSFxn](#)
- [PVLogger \\* iLogger](#)

### Protected Methods

- void [ConstructL \(OsclDNSObserver \\*aObserver, OsclDNSRequestAO \\*aAO, uint32 aId\)](#)
- bool [StartMethod \(int32 aTimeoutMsec\)](#)
- void [MethodDone \(\)](#)

### Protected Attributes

- [OsclDNSRequestAO \\* iDNSRequestAO](#)

#### 7.117.1 Detailed Description

This is the base class for all socket methods. It provides the timeout on socket requests.

## 7.117.2 Constructor & Destructor Documentation

**7.117.2.1 OsclDNSMethod::OsclDNSMethod ([Oscl\\_DefAlloc](#) & *a*, const char \* *name*, [TPVDNSFxn](#) *fxn*) [inline]**

## 7.117.3 Member Function Documentation

**7.117.3.1 void OsclDNSMethod::Abort ()**

**7.117.3.2 void OsclDNSMethod::AbortAll ()**

**7.117.3.3 void OsclDNSMethod::CancelMethod ()**

**7.117.3.4 void OsclDNSMethod::ConstructL ([OsclDNSObserver](#) \* *aObserver*, [OsclDNSRequestAO](#) \* *aAO*, uint32 *aId*) [protected]**

**7.117.3.5 void OsclDNSMethod::MethodDone () [protected]**

**7.117.3.6 void OsclDNSMethod::Run () [virtual]**

Handles an active object's request completion event.

A derived class must provide an implementation to handle the completed request. If appropriate, it may issue another request.

The function is called by the active scheduler when a request completion event occurs, i.e. after the active scheduler's `WaitForAnyRequest()` function completes.

Before calling this active object's `Run()` function, the active scheduler has:

1. decided that this is the highest priority active object with a completed request

2. marked this active object's request as complete (i.e. the request is no longer outstanding)

`Run()` runs under a trap harness in the active scheduler. If it leaves, then the active scheduler calls `ExecError()` to handle the leave.

Note that once the active scheduler's `Start()` function has been called, all user code is run under one of the program's active object's `Run()` or `RunError()` functions.

Implements [PVActiveBase](#).

7.117.3.7 **bool OsclDNSMethod::StartMethod (int32 *aTimeoutMsec*)** [protected]

#### 7.117.4 Field Documentation

7.117.4.1 **Oscl\_DefAlloc& OsclDNSMethod::iAlloc**

7.117.4.2 **TPVDNSFxn OsclDNSMethod::iDNSFxn**

7.117.4.3 **OsclDNSObserver\* OsclDNSMethod::iDNSObserver**

7.117.4.4 **OsclDNSRequestAO\* OsclDNSMethod::iDNSRequestAO** [protected]

7.117.4.5 **uint32 OsclDNSMethod::iId**

7.117.4.6 **PVLogger\* OsclDNSMethod::iLogger**

The documentation for this class was generated from the following file:

- [oscl\\_dns\\_method.h](#)

## 7.118 OsclDNSObserver Class Reference

```
#include <oscl_dns.h>
```

### Public Methods

- virtual OSCL\_IMPORT\_REF void [HandleDNSEvent](#) (int32 aId, [TPVDNSFxn](#) aFxn, [TPVDNSEvent](#) aEvent, int32 aError)=0
- virtual [~OsclDNSObserver](#) ()

### 7.118.1 Detailed Description

DNS event observer. The client implements this to get asynchronous command completion.

### 7.118.2 Constructor & Destructor Documentation

**7.118.2.1 virtual OsclDNSObserver::~OsclDNSObserver () [inline, virtual]**

### 7.118.3 Member Function Documentation

**7.118.3.1 virtual OSCL\_IMPORT\_REF void OsclDNSObserver::HandleDNSEvent (int32 *aId*,  
[TPVDNSFxn](#) *aFxn*, [TPVDNSEvent](#) *aEvent*, int32 *aError*) [pure virtual]**

DNS Event callback.

#### Parameters:

***aId*:** The ID that was supplied when the DNS object was created.

***aEvent*:** Function completion event. Will be EPVDNSSuccess, EPVDNSTimeout, or EPVDNSFailure.

***aError*:** When the event is EPVDNSFailure, this may contain a platform-specific error code, or zero if none is available.

The documentation for this class was generated from the following file:

- [oscl\\_dns.h](#)

## 7.119 OsclDNSRequest Class Reference

```
#include <oscl_dns_request.h>
```

### Public Methods

- [OsclDNSRequest \(\)](#)
- [~OsclDNSRequest \(\)](#)
- void [CancelRequest \(\)](#)
- void [Complete \(bool, int32 aStatus, int32 aSockErr\)](#)
- void [Activate \(DNSRequestParam \\*iParam, OsclDNSRequestAO &a\)](#)

### Data Fields

- [OsclDNSRequestAO \\* iDNSRequestAO](#)
- [DNSRequestParam \\* iDNSRequestParam](#)
- bool [iActive](#)

#### 7.119.1 Detailed Description

This class defines the interface to the dns implementation threads.

#### 7.119.2 Constructor & Destructor Documentation

**7.119.2.1 OsclDNSRequest::OsclDNSRequest () [inline]**

**7.119.2.2 OsclDNSRequest::~OsclDNSRequest () [inline]**

#### 7.119.3 Member Function Documentation

**7.119.3.1 void OsclDNSRequest::Activate (DNSRequestParam \* iParam, OsclDNSRequestAO & a)**

**7.119.3.2 void OsclDNSRequest::CancelRequest ()**

**7.119.3.3 void OsclDNSRequest::Complete (bool, int32 aStatus, int32 aSockErr)**

#### 7.119.4 Field Documentation

**7.119.4.1 bool OsclDNSRequest::iActive**

**7.119.4.2 OsclDNSRequestAO\* OsclDNSRequest::iDNSRequestAO**

**7.119.4.3 DNSRequestParam\* OsclDNSRequest::iDNSRequestParam**


The documentation for this class was generated from the following file:

- [oscl\\_dns\\_request.h](#)

## 7.120 OsclDNSRequestAO Class Reference

```
#include <oscl_dns_method.h>
```

Inheritance diagram for OsclDNSRequestAO::



### Protected Methods

- [OsclDNSRequestAO](#) (const char \*name)
- void [ConstructL](#) ([OsclDNSI](#) \*aDNS, [OsclDNSMethod](#) \*aMethod)
- void [Abort](#) ()
- void [NewRequest](#) ()
- void [RequestDone](#) ()
- int [GetSocketError](#) ()
- [OsclSocketServI](#) \* [Serv](#) ()
- void [DoCancel](#) ()
- void [Run](#) ()
- virtual void [Success](#) ()
- virtual void [Failure](#) ()
- virtual void [Cancelled](#) ()

### Protected Attributes

- [OsclDNSI](#) \* [iDNSI](#)
- [OsclDNSMethod](#) \* [iDNSMethod](#)
- int32 [iSocketError](#)
- [PVLogger](#) \* [iLogger](#)

### Friends

- class [OsclDNSI](#)
- class [OsclDNSMethod](#)
- class [OsclDNSRequest](#)
- class [GetHostNameParam](#)

### 7.120.1 Detailed Description

This is the base class for all requests to the socket server.

### 7.120.2 Constructor & Destructor Documentation

**7.120.2.1 OsclDNSRequestAO::OsclDNSRequestAO (const char \* *name*)** [inline, protected]

### 7.120.3 Member Function Documentation

**7.120.3.1 void OsclDNSRequestAO::Abort ()** [inline, protected]

**7.120.3.2 virtual void OsclDNSRequestAO::Cancelled ()** [inline, protected, virtual]

**7.120.3.3 void OsclDNSRequestAO::ConstructL (OsclDNSI \* *aDNS*, OsclDNSMethod \* *aMethod*)** [inline, protected]

**7.120.3.4 void OsclDNSRequestAO::DoCancel ()** [protected, virtual]

Cancel request handler. This gets called by scheduler when the request is cancelled. The default routine will complete the request. If any additional action is needed, the derived class may override this. If the derived class does override DoCancel, it must complete the request.

Reimplemented from [OsclActiveObject](#).

**7.120.3.5 virtual void OsclDNSRequestAO::Failure ()** [inline, protected, virtual]

**7.120.3.6 int OsclDNSRequestAO::GetSocketError ()** [protected]

**7.120.3.7 void OsclDNSRequestAO::NewRequest ()** [protected]

**7.120.3.8 void OsclDNSRequestAO::RequestDone ()** [protected]

**7.120.3.9 void OsclDNSRequestAO::Run ()** [protected, virtual]

Handles an active object's request completion event.

A derived class must provide an implementation to handle the completed request. If appropriate, it may issue another request.

The function is called by the active scheduler when a request completion event occurs, i.e. after the active scheduler's `WaitForAnyRequest()` function completes.

Before calling this active object's `Run()` function, the active scheduler has:

1. decided that this is the highest priority active object with a completed request
2. marked this active object's request as complete (i.e. the request is no longer outstanding)

`Run()` runs under a trap harness in the active scheduler. If it leaves, then the active scheduler calls `ExecError()` to handle the leave.

Note that once the active scheduler's `Start()` function has been called, all user code is run under one of the program's active object's `Run()` or `RunError()` functions.

Implements [PVActiveBase](#).

**7.120.3.10** [\*\*OsclSocketServI\\*\*\* OsclDNSRequestAO::Serv \(\)](#) [protected]

**7.120.3.11** [\*\*virtual void OsclDNSRequestAO::Success \(\)\*\*](#) [inline, protected, virtual]

## 7.120.4 Friends And Related Function Documentation

**7.120.4.1** [\*\*friend class GetHostByNameParam\*\*](#) [friend]

**7.120.4.2** [\*\*friend class OsclDNSI\*\*](#) [friend]

**7.120.4.3** [\*\*friend class OsclDNSMethod\*\*](#) [friend]

**7.120.4.4** [\*\*friend class OsclDNSRequest\*\*](#) [friend]

## 7.120.5 Field Documentation

**7.120.5.1** [\*\*OsclDNSI\\* OsclDNSRequestAO::iDNSI\*\*](#) [protected]

**7.120.5.2** [\*\*OsclDNSMethod\\* OsclDNSRequestAO::iDNSMethod\*\*](#) [protected]

**7.120.5.3** [\*\*PVLogger\\* OsclDNSRequestAO::iLogger\*\*](#) [protected]

**7.120.5.4** [\*\*int32 OsclDNSRequestAO::iSocketError\*\*](#) [protected]


The documentation for this class was generated from the following file:

- [oscl\\_dns\\_method.h](#)

## 7.121 OsclDoubleLink Class Reference

```
#include <oscl_double_list.h>
```

Inheritance diagram for OsclDoubleLink::



### Public Methods

- [OsclDoubleLink \(\)](#)
- void [Remove \(\)](#)
- void [InsertAfter \(OsclDoubleLink \\*aLink\)](#)
- void [InsertBefore \(OsclDoubleLink \\*aLink\)](#)

### Data Fields

- OsclDoubleLink \* [iNext](#)
- OsclDoubleLink \* [iPrev](#)

#### 7.121.1 Constructor & Destructor Documentation

##### 7.121.1.1 [OsclDoubleLink::OsclDoubleLink \(\) \[inline\]](#)

#### 7.121.2 Member Function Documentation

##### 7.121.2.1 [void OsclDoubleLink::InsertAfter \(OsclDoubleLink \\* aLink\)](#)

##### 7.121.2.2 [void OsclDoubleLink::InsertBefore \(OsclDoubleLink \\* aLink\)](#)

##### 7.121.2.3 [void OsclDoubleLink::Remove \(\)](#)

#### 7.121.3 Field Documentation

##### 7.121.3.1 [OsclDoubleLink\\* OsclDoubleLink::iNext](#)

##### 7.121.3.2 [OsclDoubleLink\\* OsclDoubleLink::iPrev](#)


The documentation for this class was generated from the following file:

- [oscl\\_double\\_list.h](#)

## 7.122 OsclDoubleList< T > Class Template Reference

```
#include <oscl_double_list.h>
```

Inheritance diagram for OsclDoubleList< T >::



### Public Methods

- OSCL\_INLINE OsclDoubleList()
- OSCL\_INLINE OsclDoubleList(int32 anOffset)
- OSCL\_INLINE void InsertHead(T &aRef)
- OSCL\_INLINE void InsertTail(T &aRef)
- OSCL\_INLINE bool IsHead(const T \*aPtr) const
- OSCL\_INLINE bool IsTail(const T \*aPtr) const
- OSCL\_INLINE T \* Head() const
- OSCL\_INLINE T \* Tail() const

```
template<class T> class OsclDoubleList< T >
```

#### 7.122.1 Constructor & Destructor Documentation

**7.122.1.1 template<class T> OSCL\_INLINE OsclDoubleList< T >::OsclDoubleList()**

**7.122.1.2 template<class T> OSCL\_INLINE OsclDoubleList< T >::OsclDoubleList(int32  
anOffset)**

#### 7.122.2 Member Function Documentation

**7.122.2.1 template<class T> OSCL\_INLINE T\* OsclDoubleList< T >::Head()**

**7.122.2.2 template<class T> OSCL\_INLINE void OsclDoubleList< T >::InsertHead(T & aRef)**

**7.122.2.3 template<class T> OSCL\_INLINE void OsclDoubleList< T >::InsertTail(T & aRef)**

**7.122.2.4 template<class T> OSCL\_INLINE bool OsclDoubleList< T >::IsHead(const T \* aPtr)  
const**

**7.122.2.5 template<class T> OSCL\_INLINE bool OsclDoubleList< T >::IsTail(const T \* aPtr)  
const**

**7.122.2.6 template<class T> OSCL\_INLINE T\* OsclDoubleList< T >::Tail()**


The documentation for this class was generated from the following file:

- [oscl\\_double\\_list.h](#)

## 7.123 OsclDoubleListBase Class Reference

```
#include <oscl_double_list.h>
```

Inheritance diagram for OsclDoubleListBase::



### Public Methods

- `bool IsEmpty () const`
- `void SetOffset (int32 anOffset)`
- `void Reset ()`
- `OsclDoubleLink * getHead ()`
- `int32 getOffset ()`

### Protected Methods

- `OsclDoubleListBase ()`
- `OsclDoubleListBase (int32 anOffset)`
- `void InsertHead (OsclAny *aPtr)`
- `void InsertTail (OsclAny *aPtr)`
- `void Insert (OsclAny *aPtr)`

### Protected Attributes

- `OsclDoubleLink iHead`
- `int32 iOffset`

### 7.123.1 Constructor & Destructor Documentation

7.123.1.1 **OsclDoubleListBase::OsclDoubleListBase ()** [protected]

7.123.1.2 **OsclDoubleListBase::OsclDoubleListBase (int32 *anOffset*)** [protected]

### 7.123.2 Member Function Documentation

7.123.2.1 **OsclDoubleLink\* OsclDoubleListBase::getHead ()** [inline]

7.123.2.2 **int32 OsclDoubleListBase::getOffset ()** [inline]

7.123.2.3 **void OsclDoubleListBase::Insert (OsclAny \* *aPtr*)** [protected]

7.123.2.4 **void OsclDoubleListBase::InsertHead (OsclAny \* *aPtr*)** [protected]

7.123.2.5 **void OsclDoubleListBase::InsertTail (OsclAny \* *aPtr*)** [protected]

7.123.2.6 **bool OsclDoubleListBase::IsEmpty ()**

7.123.2.7 **void OsclDoubleListBase::Reset ()**

7.123.2.8 **void OsclDoubleListBase::SetOffset (int32 *anOffset*)**

### 7.123.3 Field Documentation

7.123.3.1 **OsclDoubleLink OsclDoubleListBase::iHead** [protected]

7.123.3.2 **int32 OsclDoubleListBase::iOffset** [protected]

The documentation for this class was generated from the following file:

- [oscl\\_double\\_list.h](#)

## 7.124 OsclDoubleRunner< T > Class Template Reference

```
#include <oscl_double_list.h>
```

### Public Methods

- [OsclDoubleRunner \(OsclDoubleListBase &aQue\)](#)
- [void Set \(T &aLink\)](#)
- [operator T \\* \(\)](#)
- [T \\* operator++ \(int\)](#)
- [T \\* operator- \(int\)](#)
- [void SetToHead \(\)](#)
- [void SetToTail \(\)](#)

### Protected Attributes

- [int32 iOffset](#)
- [OsclDoubleLink \\* iHead](#)
- [OsclDoubleLink \\* iNext](#)

template<class T> class OsclDoubleRunner< T >

#### 7.124.1 Constructor & Destructor Documentation

7.124.1.1 template<class T> OsclDoubleRunner< T >::OsclDoubleRunner ([OsclDoubleListBase & aQue](#)) [inline]

#### 7.124.2 Member Function Documentation

7.124.2.1 template<class T> OsclDoubleRunner< T >::operator T \* () [inline]

7.124.2.2 template<class T> T\* OsclDoubleRunner< T >::operator++ (int) [inline]

7.124.2.3 template<class T> T\* OsclDoubleRunner< T >::operator- (int)

7.124.2.4 template<class T> void OsclDoubleRunner< T >::Set (T & aLink) [inline]

7.124.2.5 template<class T> void OsclDoubleRunner< T >::SetToHead () [inline]

7.124.2.6 template<class T> void OsclDoubleRunner< T >::SetToTail () [inline]

#### 7.124.3 Field Documentation

7.124.3.1 template<class T> [OsclDoubleLink\\* OsclDoubleRunner< T >::iHead](#) [protected]

7.124.3.2 template<class T> [OsclDoubleLink\\* OsclDoubleRunner< T >::iNext](#) [protected]

7.124.3.3 template<class T> int32 [OsclDoubleRunner< T >::iOffset](#) [protected]

The documentation for this class was generated from the following file:

- 
- [oscl\\_double\\_list.h](#)

## 7.125 OsclError Class Reference

```
#include <oscl_error.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF void [PushL \(\\_OsclHeapBase \\*aPtr\)](#)
- OSCL\_IMPORT\_REF void [PushL \(OsclAny \\*aPtr\)](#)
- OSCL\_IMPORT\_REF void [PushL \(OsclTrapItem anItem\)](#)
- OSCL\_IMPORT\_REF void [Pop \(\)](#)
- OSCL\_IMPORT\_REF void [Pop \(int32 aCount\)](#)
- OSCL\_IMPORT\_REF void [PopDealloc \(\)](#)
- OSCL\_IMPORT\_REF void [PopDealloc \(int32 aCount\)](#)
- OSCL\_IMPORT\_REF void [Leave \(int32 aReason\)](#)
- OSCL\_IMPORT\_REF void [LeaveIfNull \(OsclAny \\*a\)](#)
- OSCL\_IMPORT\_REF void [LeaveIfError \(int32 aReason\)](#)

### 7.125.1 Detailed Description

User Error class

### 7.125.2 Member Function Documentation

#### 7.125.2.1 OSCL\_IMPORT\_REF void OsclError::Leave (int32 *aReason*) [static]

Do a Leave error, with the given reason code. When a leave occurs, all items on the cleanup stack for the current trap level will be destroyed, and execution will jump to the trap handler.

#### 7.125.2.2 OSCL\_IMPORT\_REF void OsclError::LeaveIfError (int32 *aReason*) [static]

Evaluate the input parameter, and if it is an error code (non-zero), then do a Leave with the provided reason code.

#### 7.125.2.3 OSCL\_IMPORT\_REF void OsclError::LeaveIfNull (OsclAny \* *a*) [static]

Evaluate the input parameter, and if it is null, do a Leave with OsclErrNoMemory reason code.

#### 7.125.2.4 OSCL\_IMPORT\_REF void OsclError::Pop (int32 *aCount*) [static]

Pop the cleanup stack N times

#### 7.125.2.5 OSCL\_IMPORT\_REF void OsclError::Pop () [static]

Pop the cleanup stack

**7.125.2.6 OSCL\_IMPORT\_REF void OsclError::PopDealloc (int32 *aCount*) [static]**

PopDealloc N times

**7.125.2.7 OSCL\_IMPORT\_REF void OsclError::PopDealloc () [static]**

Destroy the item on the top of the cleanup stack and pop it

**7.125.2.8 OSCL\_IMPORT\_REF void OsclError::PushL ([OsclTrapItem](#) *anItem*) [static]**

Push an [OsclTrapItem](#) onto the cleanup stack

**7.125.2.9 OSCL\_IMPORT\_REF void OsclError::PushL ([OsclAny](#) \* *aPtr*) [static]**

Push an OsclAny item onto the cleanup stack.

**7.125.2.10 OSCL\_IMPORT\_REF void OsclError::PushL ([\\_OsclHeapBase](#) \* *aPtr*) [static]**

Push an [\\_OsclHeapBase](#) item onto the cleanup stack.

The documentation for this class was generated from the following file:

- [oscl\\_error.h](#)

## 7.126 OsclErrorAllocator Class Reference

This class provides static methods to invoke the user defined memory allocation routines.

```
#include <oscl_error_allocator.h>
```

### Public Methods

- **OsclErrorAllocator (Oscl\_DefAlloc \*allocator)**  
*constructor method*
- **void \* operator new (uint32 size, OsclAny \*aPtr)**  
*placement new operator that allocates memory using the user defined methods*
- **void operator delete (OsclAny \*aPtr, OsclAny \*aPtr2)**  
*delete operator that doesn't do anything, user has to deallocate manually*

### Static Public Methods

- **OsclAny \* allocate (uint32 aSize)**  
*static method to allocate a block of memory on heap*
- **OsclAny deallocate (OsclAny \*aPointer)**  
*static method to deallocate a block of memory on heap*

### 7.126.1 Detailed Description

This class provides static methods to invoke the user defined memory allocation routines.

This class must be instantiated before the static methods are called, else asserts will happen

### 7.126.2 Constructor & Destructor Documentation

#### 7.126.2.1 OsclErrorAllocator::OsclErrorAllocator (**Oscl\_DefAlloc \* allocator**) [inline]

constructor method

**Parameters:**

*allocator* - a pointer to the concrete object that provides the allocator/deallocator

### 7.126.3 Member Function Documentation

#### 7.126.3.1 OsclAny\* OsclErrorAllocator::allocate (uint32 *aSize*) [inline, static]

static method to allocate a block of memory on heap

**Parameters:**

*aSize* - number of bytes to allocate

**7.126.3.2 OsclAny OsclErrorAllocator::deallocate (OsclAny \* aPointer) [inline, static]**

static method to deallocate a block of memory on heap

**Parameters:**

*aPointer* - pointer to block of memory to be deallocated

**7.126.3.3 void OsclErrorAllocator::operator delete (OsclAny \* aPtr, OsclAny \* aPtr2) [inline]**

delete operator that doesn't do anything, user has to deallocate manually

**7.126.3.4 void\* OsclErrorAllocator::operator new (uint32 size, OsclAny \* aPtr) [inline]**

placement new operator that allocates memory using the user defined methods

The documentation for this class was generated from the following file:

- [oscl\\_error\\_allocator.h](#)

## 7.127 OsclErrorTrap Class Reference

```
#include <oscl_error.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF int32 [Init \(Oscl\\_DefAlloc \\*aAlloc=NULL\)](#)
- OSCL\_IMPORT\_REF int32 [Cleanup \(\)](#)
- OSCL\_IMPORT\_REF [OsclErrorTrapImp \\* GetErrorTrapImp \(\)](#)

#### 7.127.1 Member Function Documentation

##### 7.127.1.1 OSCL\_IMPORT\_REF int32 OsclErrorTrap::Cleanup () [static]

Cleanup and destroy error trap for the calling thread.

###### Returns:

0 for success, or an error

##### 7.127.1.2 OSCL\_IMPORT\_REF [OsclErrorTrapImp\\*](#) OsclErrorTrap::GetErrorTrapImp () [static]

Get the ErrorTrapImp for the current thread. Leaves on error.

##### 7.127.1.3 OSCL\_IMPORT\_REF int32 OsclErrorTrap::Init ([Oscl\\_DefAlloc \\* aAlloc = NULL](#)) [static]

Allocate and initialize error trap for the calling thread.

###### Parameters:

*aAlloc*: optional, allocator to use for the internal implementation.

###### Returns:

0 for success, or an error

The documentation for this class was generated from the following file:

- [oscl\\_error.h](#)

## 7.128 OsclErrorTrapImp Class Reference

```
#include <oscl_error_trapcleanup.h>
```

### Public Methods

- OSCL\_IMPORT\_REF void [UnTrap \(\)](#)

### Static Public Methods

- OSCL\_IMPORT\_REF OsclErrorTrapImp \* [Trap \(\)](#)
- OSCL\_IMPORT\_REF OsclErrorTrapImp \* [TrapNoTls \(OsclErrorTrapImp \\*\)](#)

### Data Fields

- [OsclJump \\* iJumpData](#)
- int32 [iLeave](#)
- [OsclTrapStack \\* iTrapStack](#)

### Friends

- class [OsclErrorTrap](#)
- class [OsclError](#)
- class [OsclExecScheduler](#)
- class [OsclExecSchedulerCommonBase](#)
- class [OsclJump](#)
- class [OsclJumpMark](#)
- class [OsclTrapStack](#)
- class [CPVInterfaceProxy](#)
- class [OsclScheduler](#)

### 7.128.1 Detailed Description

A per-thread cleanup stack with nested trap support.

### 7.128.2 Member Function Documentation

#### 7.128.2.1 OSCL\_IMPORT\_REF OsclErrorTrapImp\* OsclErrorTrapImp::Trap () [static]

PV trap cleanup. Public for use in macros only.

#### 7.128.2.2 OSCL\_IMPORT\_REF OsclErrorTrapImp\* OsclErrorTrapImp::TrapNoTls (OsclErrorTrapImp \*) [static]

#### 7.128.2.3 OSCL\_IMPORT\_REF void OsclErrorTrapImp::UnTrap ()

these are used in public macros, but aren't intended as public methods or members.

### 7.128.3 Friends And Related Function Documentation

7.128.3.1 **friend class CPVInterfaceProxy [friend]**

7.128.3.2 **friend class OsclError [friend]**

7.128.3.3 **friend class OsclErrorTrap [friend]**

7.128.3.4 **friend class OsclExecScheduler [friend]**

7.128.3.5 **friend class OsclExecSchedulerCommonBase [friend]**

7.128.3.6 **friend class OsclJump [friend]**

7.128.3.7 **friend class OsclJumpMark [friend]**

7.128.3.8 **friend class OsclScheduler [friend]**

7.128.3.9 **friend class OsclTrapStack [friend]**

### 7.128.4 Field Documentation

7.128.4.1 **OsclJump\* OsclErrorTrapImp::iJumpData**

7.128.4.2 **int32 OsclErrorTrapImp::iLeave**

7.128.4.3 **OsclTrapStack\* OsclErrorTrapImp::iTrapStack**

The documentation for this class was generated from the following file:

- [oscl\\_error\\_trapcleanup.h](#)

## 7.129 OsclException< LeaveCode > Class Template Reference

`oscl_exception.h` contains all the exception handling macros and classes This template class provides the base exception class that all exceptions derive from

```
#include <oscl_exception.h>
```

### Public Methods

- `OsclException ()`

### Static Public Methods

- `int getLeaveCode ()`

#### 7.129.1 Detailed Description

`template<int LeaveCode> class OsclException< LeaveCode >`

`oscl_exception.h` contains all the exception handling macros and classes This template class provides the base exception class that all exceptions derive from

All PacketVideo exception classes will be derived from the OsclException class. Each derived class will have a static function where the leave code can be obtained. This avoids the issue of having static members in a DLL. The function needs to be static so it can be called without an instance of the class

#### 7.129.2 Constructor & Destructor Documentation

**7.129.2.1 `template<int LeaveCode> OsclException< LeaveCode >::OsclException ()`**  
[inline]

#### 7.129.3 Member Function Documentation

**7.129.3.1 `template<int LeaveCode> int OsclException< LeaveCode >::getLeaveCode ()`**  
[inline, static]

The documentation for this class was generated from the following file:

- `oscl_exception.h`

## 7.130 OsclExclusiveArrayPtr< T > Class Template Reference

The OsclExclusiveArrayPtr class is a template class that defines an array pointer like object intended to be assigned an address obtained (directly or indirectly) by new. When the OsclExclusiveArrayPtr expires, its destructor uses delete to free the memory.

```
#include <oscl_exclusive_ptr.h>
```

### Public Methods

- **OsclExclusiveArrayPtr (T \*inPtr=0)**  
*Default constructor Initializes the pointer and takes ownership.*
- **OsclExclusiveArrayPtr (OsclExclusiveArrayPtr< T > &\_Y)**  
*Copy constructor.*
- **OsclExclusiveArrayPtr< T > & operator= (OsclExclusiveArrayPtr< T > &\_Y)**  
*Assignment operator from an another OsclExclusiveArrayPtr.*
- **virtual ~OsclExclusiveArrayPtr ()**  
*Destructor.*
- **T & operator\* () const**  
*The indirection operator (\*) accesses a value indirectly, through a pointer.*
- **T \* operator-> () const**  
*The indirection operator (->) accesses a value indirectly, through a pointer.*
- **T \* get () const**  
*get() method returns the pointer, currently owned by the class.*
- **T \* release ()**  
*release() method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.*
- **bool set (T \*ptr)**  
*set() method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.*

### Protected Attributes

- **T \* \_Ptr**

#### 7.130.1 Detailed Description

**template<class T> class OsclExclusiveArrayPtr< T >**

The OsclExclusiveArrayPtr class is a template class that defines an array pointer like object intended to be assigned an address obtained (directly or indirectly) by new. When the OsclExclusiveArrayPtr expires, its destructor uses delete to free the memory.

The purpose of this class is to provide a way to prevent accidental memory leaks in a class or a method, due to "not remembering to delete" variables allocated on the heap. Thus if you assign an address returned by new to an `OsclExclusivePtr` object, you don't have to remember to free the memory later, it will be freed automatically when the object goes out of scope. The `OsclExclusivePtr` is an example of a smart pointer, an object that acts like a pointer, but with additional features. The class is defined so that it acts like a regular pointer in most respects

### 7.130.2 Constructor & Destructor Documentation

**7.130.2.1 template<class T> OsclExclusiveArrayPtr< T >::OsclExclusiveArrayPtr (T \* *inPtr* = 0) [inline, explicit]**

Default constructor Initializes the pointer and takes ownership.

**7.130.2.2 template<class T> OsclExclusiveArrayPtr< T >::OsclExclusiveArrayPtr (OsclExclusiveArrayPtr< T > & *\_Y*) [inline]**

Copy constructor.

Initializes the pointer and takes ownership from another `OsclExclusiveArrayPtr`. Note that the other class does NOT own the pointer any longer, and hence it is NOT its responsibility to free it.

**7.130.2.3 template<class T> virtual OsclExclusiveArrayPtr< T >::~OsclExclusiveArrayPtr () [inline, virtual]**

Destructor.

The pointer is deleted in case this class still has ownership

### 7.130.3 Member Function Documentation

**7.130.3.1 template<class T> T\* OsclExclusiveArrayPtr< T >::get () const [inline]**

`get()` method returns the pointer, currently owned by the class.

**7.130.3.2 template<class T> T& OsclExclusiveArrayPtr< T >::operator \* () const [inline]**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the `OsclExclusiveArrayPtr` can be used like the regular pointer that it was initialized with.

**7.130.3.3 template<class T> T\* OsclExclusiveArrayPtr< T >::operator -> () const [inline]**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the `OsclExclusiveArrayPtr` can be used like the regular pointer that it was initialized with.

**7.130.3.4 template<class T> OsclExclusiveArrayPtr<T>& OsclExclusiveArrayPtr< T >::operator= (OsclExclusiveArrayPtr< T > & \_Y) [inline]**

Assignment operator from an another OsclExclusiveArrayPtr.

**Parameters:**

*\_Y* The value parameter should be another OsclExclusiveArrayPtr

**Returns:**

Returns a reference to this OsclExclusiveArrayPtr instance with pointer initialized.

**Precondition:**

The input class should be non-null and should point to a valid pointer.

This assignment operator initializes the class to the contents of the OsclExclusiveArrayPtr given as the input parameter. The ownership of the pointer is transferred.

**7.130.3.5 template<class T> T\* OsclExclusiveArrayPtr< T >::release () [inline]**

[release\(\)](#) method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.

**7.130.3.6 template<class T> bool OsclExclusiveArrayPtr< T >::set (T \*ptr) [inline]**

[set\(\)](#) method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.

## 7.130.4 Field Documentation

**7.130.4.1 template<class T> T\* OsclExclusiveArrayPtr< T >::\_Ptr [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_exclusive\\_ptr.h](#)

## 7.131 OsclExclusivePtr< T > Class Template Reference

The OsclExclusivePtr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or indirectly) by new. When the OsclExclusivePtr expires, its destructor uses delete to free the memory.

```
#include <oscl_exclusive_ptr.h>
```

### Public Methods

- **OsclExclusivePtr** (T \*inPtr=0)  
*Default constructor Initializes the pointer and takes ownership.*
- **OsclExclusivePtr** (OsclExclusivePtr< T > &\_Y)  
*Copy constructor.*
- OsclExclusivePtr< T > & **operator=** (OsclExclusivePtr< T > &\_Y)  
*Assignment operator from an another OsclExclusivePtr.*
- virtual ~**OsclExclusivePtr** ()  
*Destructor.*
- T & **operator \*** () const  
*The indirection operator (\*) accesses a value indirectly, through a pointer.*
- T \* **operator ->** () const  
*The indirection operator (->) accesses a value indirectly, through a pointer.*
- T \* **get** () const  
***get()** method returns the pointer, currently owned by the class.*
- T \* **release** ()  
***release()** method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.*
- bool **set** (T \*ptr)  
***set()** method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.*

### Protected Attributes

- T \* **\_Ptr**

#### 7.131.1 Detailed Description

**template<class T> class OsclExclusivePtr< T >**

The OsclExclusivePtr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or indirectly) by new. When the OsclExclusivePtr expires, its destructor uses delete to free the memory.

The purpose of this class is to provide a way to prevent accidental memory leaks in a class or a method, due to "not remembering to delete" variables allocated on the heap. Thus if you assign an address returned by new to an OsclExclusivePtr object, you don't have to remember to free the memory later, it will be freed automatically when the object goes out of scope. The OsclExclusivePtr is an example of a smart pointer, an object that acts like a pointer, but with additional features. The class is defined so that it acts like a regular pointer in most respects

### 7.131.2 Constructor & Destructor Documentation

**7.131.2.1 template<class T> OsclExclusivePtr< T >::OsclExclusivePtr (T \* *inPtr* = 0) [inline, explicit]**

Default constructor Initializes the pointer and takes ownership.

**7.131.2.2 template<class T> OsclExclusivePtr< T >::OsclExclusivePtr (OsclExclusivePtr< T > & *\_Y*) [inline]**

Copy constructor.

Initializes the pointer and takes ownership from another OsclExclusivePtr. Note that the other class does NOT own the pointer any longer, and hence it is NOT its responsibility to free it.

**7.131.2.3 template<class T> virtual OsclExclusivePtr< T >::~OsclExclusivePtr () [inline, virtual]**

Destructor.

The pointer is deleted in case this class still has ownership

### 7.131.3 Member Function Documentation

**7.131.3.1 template<class T> T\* OsclExclusivePtr< T >::get () const [inline]**

[get\(\)](#) method returns the pointer, currently owned by the class.

**7.131.3.2 template<class T> T& OsclExclusivePtr< T >::operator \* () const [inline]**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the OsclExclusivePtr can be used like the regular pointer that it was initialized with.

**7.131.3.3 template<class T> T\* OsclExclusivePtr< T >::operator -> () const [inline]**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the OsclExclusivePtr can be used like the regular pointer that it was initialized with.

**7.131.3.4 template<class T> OsclExclusivePtr<T>& OsclExclusivePtr< T >::operator= (OsclExclusivePtr< T > & \_Y) [inline]**

Assignment operator from an another OsclExclusivePtr.

**Parameters:**

*\_Y* The value parameter should be another OsclExclusivePtr

**Returns:**

Returns a reference to this OsclExclusivePtr instance with pointer initialized.

**Precondition:**

The input class should be non-null and should point to a valid pointer.

This assignment operator initializes the class to the contents of the OsclExclusivePtr given as the input parameter. The ownership of the pointer is transferred.

**7.131.3.5 template<class T> T\* OsclExclusivePtr< T >::release () [inline]**

[release\(\)](#) method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.

**7.131.3.6 template<class T> bool OsclExclusivePtr< T >::set (T \*ptr) [inline]**

[set\(\)](#) method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.

## 7.131.4 Field Documentation

**7.131.4.1 template<class T> T\* OsclExclusivePtr< T >::\_Ptr [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_exclusive\\_ptr.h](#)

## 7.132 OsclExclusivePtrA< T, Alloc > Class Template Reference

The OsclExclusivePtrA class is a template class that defines any pointer like object intended to be assigned an address obtained (directly or indirectly) through Alloc. When the OsclExclusivePtrA expires, Alloc is used to free the memory.

```
#include <oscl_exclusive_ptr.h>
```

### Public Methods

- `OsclExclusivePtrA (T *inPtr=0)`  
*Default constructor Initializes the pointer and takes ownership.*
- `OsclExclusivePtrA (OsclExclusivePtrA< T, Alloc > &_Y)`  
*Copy constructor.*
- `OsclExclusivePtrA< T, Alloc > & operator= (OsclExclusivePtrA< T, Alloc > &_Y)`  
*Assignment operator from an another `OsclExclusiveArrayPtr`.*
- `virtual ~OsclExclusivePtrA ()`  
*Destructor.*
- `T & operator* () const`  
*The indirection operator (\*) accesses a value indirectly, through a pointer.*
- `T * operator-> () const`  
*The indirection operator (->) accesses a value indirectly, through a pointer.*
- `T * get () const`  
*`get()` method returns the pointer, currently owned by the class.*
- `T * release ()`  
*`release()` method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.*
- `bool set (T *ptr)`  
*`set()` method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.*

### Protected Attributes

- `T * _Ptr`

#### 7.132.1 Detailed Description

`template<class T, class Alloc> class OsclExclusivePtrA< T, Alloc >`

The OsclExclusivePtrA class is a template class that defines any pointer like object intended to be assigned an address obtained (directly or indirectly) through Alloc. When the OsclExclusivePtrA expires, Alloc is used to free the memory.

The purpose of this class is to provide a way to prevent accidental memory leaks in a class or a method, due to "not remembering to delete" variables allocated on the heap. Thus if you assign an address returned by new to an [OsclExclusivePtr](#) object, you don't have to remember to free the memory later, it will be freed automatically when the object goes out of scope. The [OsclExclusivePtr](#) is an example of a smart pointer, an object that acts like a pointer, but with additional features. The class is defined so that it acts like a regular pointer in most respects

### 7.132.2 Constructor & Destructor Documentation

**7.132.2.1 template<class T, class Alloc> OsclExclusivePtrA< T, Alloc >::OsclExclusivePtrA (T \* *inPtr* = 0) [inline, explicit]**

Default constructor Initializes the pointer and takes ownership.

**7.132.2.2 template<class T, class Alloc> OsclExclusivePtrA< T, Alloc >::OsclExclusivePtrA (OsclExclusivePtrA< T, Alloc > & *\_Y*) [inline]**

Copy constructor.

Initializes the pointer and takes ownership from another [OsclExclusiveArrayPtr](#). Note that the other class does NOT own the pointer any longer, and hence it is NOT its responsibility to free it.

**7.132.2.3 template<class T, class Alloc> virtual OsclExclusivePtrA< T, Alloc >::~OsclExclusivePtrA () [inline, virtual]**

Destructor.

The pointer is deleted in case this class still has ownership

### 7.132.3 Member Function Documentation

**7.132.3.1 template<class T, class Alloc> T\* OsclExclusivePtrA< T, Alloc >::get () const [inline]**

[get\(\)](#) method returns the pointer, currently owned by the class.

**7.132.3.2 template<class T, class Alloc> T& OsclExclusivePtrA< T, Alloc >::operator \* () const [inline]**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the [OsclExclusiveArrayPtr](#) can be used like the regular pointer that it was initialized with.

**7.132.3.3 template<class T, class Alloc> T\* OsclExclusivePtrA< T, Alloc >::operator -> () const [inline]**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the [OsclExclusiveArrayPtr](#) can be used like the regular pointer that it was initialized with.

**7.132.3.4 template<class T, class Alloc> OsclExclusivePtrA<T, Alloc>& OsclExclusivePtrA< T, Alloc >::operator= (OsclExclusivePtrA< T, Alloc > & \_Y) [inline]**

Assignment operator from an another [OsclExclusiveArrayPtr](#).

**Parameters:**

*\_Y* The value parameter should be another [OsclExclusiveArrayPtr](#)

**Returns:**

Returns a reference to this [OsclExclusiveArrayPtr](#) instance with pointer initialized.

**Precondition:**

The input class should be non-null and should point to a valid pointer.

This assignment operator initializes the class to the contents of the [OsclExclusiveArrayPtr](#) given as the input parameter. The ownership of the pointer is transferred.

**7.132.3.5 template<class T, class Alloc> T\* OsclExclusivePtrA< T, Alloc >::release () [inline]**

[release\(\)](#) method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.

**7.132.3.6 template<class T, class Alloc> bool OsclExclusivePtrA< T, Alloc >::set (T \*ptr) [inline]**

[set\(\)](#) method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.

## 7.132.4 Field Documentation

**7.132.4.1 template<class T, class Alloc> T\* OsclExclusivePtrA< T, Alloc >::\_Ptr [protected]**


The documentation for this class was generated from the following file:

- [oscl\\_exclusive\\_ptr.h](#)

## 7.133 OsclExecScheduler Class Reference

```
#include <oscl_scheduler.h>
```

Inheritance diagram for OsclExecScheduler::



### Public Methods

- OSCL\_IMPORT\_REF void [RunSchedulerNonBlocking](#) (int32 aTargetCount, int32 &aReady, uint32 &aDelayMsec)
- OSCL\_IMPORT\_REF void [RegisterForCallback](#) ([OsclSchedulerObserver](#) \*aCallback, [OsclAny](#) \*aCallbackContext)

### Static Public Methods

- OSCL\_IMPORT\_REF [OsclExecScheduler](#) \* [Current](#) ()

### Friends

- class [OsclScheduler](#)

#### 7.133.1 Member Function Documentation

##### 7.133.1.1 OSCL\_IMPORT\_REF OsclExecScheduler\* OsclExecScheduler::Current () [static]

Get currently installed scheduler for calling thread, or NULL if no scheduler is installed.

##### 7.133.1.2 OSCL\_IMPORT\_REF void OsclExecScheduler::RegisterForCallback ([OsclSchedulerObserver](#) \* aCallback, [OsclAny](#) \* aCallbackContext)

Register for a notification when non-blocking scheduler needs to run again.

Note: On Symbian, non-blocking mode is not supported and this call will leave.

##### 7.133.1.3 OSCL\_IMPORT\_REF void OsclExecScheduler::RunSchedulerNonBlocking (int32 aTargetCount, int32 & aReady, uint32 & aDelayMsec)

Run PV scheduler in non-blocking mode. This call returns when the desired number of Run calls have been made, or when there are no more active objects that are ready to run.

**Parameters:**

*aTargetCount*: (input param) the maximum number of Run calls to make.

*aReady*: (output param) tells the number of active objects that are currently ready to run.

*aDelayMsec*: (output param) If no active objects are ready to run, but one or more active objects are waiting on timers, this parameter will tell the time interval from the current time until the first of the pending timer objects will be ready to run, in milliseconds.

Note: On Symbian, non-blocking mode is not supported and this call will leave.

## 7.133.2 Friends And Related Function Documentation

### 7.133.2.1 friend class OsclScheduler [friend]

Reimplemented from [OsclExecSchedulerCommonBase](#).


The documentation for this class was generated from the following file:

- [oscl\\_scheduler.h](#)

## 7.134 OsclExecSchedulerBase Class Reference

```
#include <oscl_scheduler_types.h>
```

Inheritance diagram for OsclExecSchedulerBase::



### Friends

- class [OsclExecScheduler](#)
- class [OsclCoeActiveScheduler](#)
- class [PVActiveBase](#)

#### 7.134.1 Detailed Description

OsclActiveSchedulerBase is the base for [OsclExecScheduler](#). The non-Symbian OsclActiveSchedulerBase class is functionally similar to a subset of Symbian CActiveScheduler class.

#### 7.134.2 Friends And Related Function Documentation

**7.134.2.1 friend class OsclCoeActiveScheduler [friend]**

**7.134.2.2 friend class OsclExecScheduler [friend]**

**7.134.2.3 friend class PVActiveBase [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_types.h](#)

## 7.135 OsclExecSchedulerCommonBase Class Reference

```
#include <oscl_scheduler.h>
```

Inheritance diagram for OsclExecSchedulerCommonBase::



### Public Methods

- OSCL\_IMPORT\_REF void [StartScheduler](#) (OsclSemaphore \*sem=NULL)
- OSCL\_IMPORT\_REF void [StopScheduler](#) ()
- OSCL\_IMPORT\_REF void [SuspendScheduler](#) ()
- OSCL\_IMPORT\_REF void [ResumeScheduler](#) ()
- OSCL\_IMPORT\_REF void [StartNativeScheduler](#) ()

### Static Public Methods

- OSCL\_IMPORT\_REF [OsclNameString< PVSCHEDNAMELEN > \\*](#) [GetName](#) ()
- OSCL\_IMPORT\_REF uint32 [GetId](#) ()

### Protected Types

- enum [TOtherExecStats](#) { [EOtherExecStats\\_WaitTime](#), [EOtherExecStats\\_QueueTime](#), [EOtherExecStats\\_NativeOS](#), [EOtherExecStats\\_ReleaseTime](#), [EOtherExecStats\\_Last](#) }

### Protected Methods

- virtual ~[OsclExecSchedulerCommonBase](#) ()
- void [InstallScheduler](#) ()
- void [UninstallScheduler](#) ()
- void [Error](#) (int32 anError) const
- [OsclExecSchedulerCommonBase](#) ([Oscl\\_DefAlloc](#) \*)
- virtual void [ConstructL](#) (const char \*name, int)
- void [BeginScheduling](#) (bool blocking, bool native)
- void [EndScheduling](#) ()
- void [BlockingLoopL](#) ()
- bool [IsStarted](#) ()
- bool [IsInstalled](#) ()
- void [AddToExecTimerQ](#) ([PVActiveBase](#) \*active, uint32)
- void [PendComplete](#) ([PVActiveBase](#) \*, int32 aReason, [TPVThreadContext](#) aContext)
- void [RequestCanceled](#) ([PVActiveBase](#) \*)
- [PVActiveBase](#) \* [UpdateTimers](#) (uint32 &aDelay)
- [PVActiveBase](#) \* [UpdateTimersMsec](#) (uint32 &aDelay)
- [PVActiveBase](#) \* [WaitForReadyAO](#) ()

- void [CallRunExec \(PVActiveBase \\*\)](#)
- void [ConstructStatQ \(\)](#)
- void [BeginStats \(\)](#)
- void [EndStats \(\)](#)
- void [CleanupStatQ \(\)](#)
- PVActiveBase \* [FindPVBase \(PVActiveBase \\*active, OsclDoubleList< PVActiveBase > &\)](#)
- void [CleanupExecQ \(\)](#)
- void [InitExecQ \(int\)](#)
- void [ResetLogPerf \(\)](#)
- void [IncLogPerf \(uint32\)](#)

## Static Protected Methods

- OsclExecSchedulerCommonBase \* [GetScheduler \(\)](#)
- OsclExecSchedulerCommonBase \* [SetScheduler \(OsclExecSchedulerCommonBase \\*\)](#)
- void [ShowStats \(PVActiveStats \\*active\)](#)
- void [ShowSummaryStats \(PVActiveStats \\*active, PVLogger \\*, int64, int64 &, float &\)](#)

## Protected Attributes

- bool [iBlockingMode](#)
- bool [iNativeMode](#)
- PVSchedulerStopper \* [iStopper](#)
- OsclNoYieldMutex [iStopperCrit](#)
- PVThreadContext [iThreadContext](#)
- OsclNameString< PVSCHEDNAMELEN > [iName](#)
- bool [iDoStop](#)
- bool [iDoSuspend](#)
- bool [iSuspended](#)
- OsclSemaphore [iResumeSem](#)
- OsclErrorTrapImp \* [iErrorTrapImp](#)
- OsclReadyQ [iReadyQ](#)
- OsclTimerQ [iExecTimerQ](#)
- uint32 [iNumAOAdded](#)
- OsclDoubleList< PVActiveStats > [iPVStatQ](#)
- PVActiveStats \* [iOtherExecStats](#) [EOtherExecStats\_Last]
- uint8 \* [iTTotalTicksTemp](#)
- int64 [iGrandTotalTicks](#)
- float [iTTotalPercent](#)
- uint32 [iTime](#)
- int32 [iDelta](#)
- PVActiveStats \* [iPVStats](#)
- PVLogger \* [iLogger](#)
- PVLogger \* [iDebugLogger](#)
- char \* [iLogPerfIndentStr](#)
- int32 [iLogPerfIndentStrLen](#)
- uint32 [iLogPerfTotal](#)
- Oscl\_DefAlloc \* [iAlloc](#)
- OsclMemAllocator [iDefAlloc](#)

## Static Protected Attributes

- const uint32 [iTTimeCompareThreshold](#)

## Friends

- class [OsclScheduler](#)
- class [PVThreadContext](#)
- class [OsclCoeActiveScheduler](#)
- class [OsclTimerCompare](#)
- class [OsclReadyQ](#)
- class [OsclError](#)
- class [PVActiveStats](#)
- class [OsclActiveObject](#)
- class [OsclTimerObject](#)
- class [PVActiveBase](#)
- class [PVSchedulerStopper](#)
- class [OsclExecScheduler](#)

## 7.135.1 Member Enumeration Documentation

### 7.135.1.1 enum OsclExecSchedulerCommonBase::TOtherExecStats [protected]

Enumeration values:

- EOtherExecStats\_WaitTime**
- EOtherExecStats\_QueueTime**
- EOtherExecStats\_NativeOS**
- EOtherExecStats\_ReleaseTime**
- EOtherExecStats\_Last**

## 7.135.2 Constructor & Destructor Documentation

- 7.135.2.1 **virtual OsclExecSchedulerCommonBase::~OsclExecSchedulerCommonBase ()**  
[protected, virtual]
- 7.135.2.2 **OsclExecSchedulerCommonBase::OsclExecSchedulerCommonBase (Oscl\_DefAlloc \*)**  
[protected]

## 7.135.3 Member Function Documentation

- 7.135.3.1 **void OsclExecSchedulerCommonBase::AddToExecTimerQ (PVActiveBase \* *active*, uint32)** [protected]
- 7.135.3.2 **void OsclExecSchedulerCommonBase::BeginScheduling (bool *blocking*, bool *native*)**  
[protected]
- 7.135.3.3 **void OsclExecSchedulerCommonBase::BeginStats ()** [protected]
- 7.135.3.4 **void OsclExecSchedulerCommonBase::BlockingLoopL ()** [protected]
- 7.135.3.5 **void OsclExecSchedulerCommonBase::CallRunExec (PVActiveBase \*)** [protected]
- 7.135.3.6 **void OsclExecSchedulerCommonBase::CleanupExecQ ()** [protected]
- 7.135.3.7 **void OsclExecSchedulerCommonBase::CleanupStatQ ()** [protected]
- 7.135.3.8 **virtual void OsclExecSchedulerCommonBase::ConstructL (const char \* *name*, int)**  
[protected, virtual]
- 7.135.3.9 **void OsclExecSchedulerCommonBase::ConstructStatQ ()** [protected]
- 7.135.3.10 **void OsclExecSchedulerCommonBase::EndScheduling ()** [protected]
- 7.135.3.11 **void OsclExecSchedulerCommonBase::EndStats ()** [protected]
- 7.135.3.12 **void OsclExecSchedulerCommonBase::Error (int32 *anError*) const** [protected]
- 7.135.3.13 **PVActiveBase\* OsclExecSchedulerCommonBase::FindPVBase (PVActiveBase \* *active*, OsclDoubleList< PVActiveBase > &)** [protected]
- 7.135.3.14 **OSCL\_IMPORT\_REF uint32 OsclExecSchedulerCommonBase::GetId ()** [static]

Get numeric ID of current thread.

- 7.135.3.15 **OSCL\_IMPORT\_REF OsclNameString< PVSCHEDNAMELEN >\* OsclExecSchedulerCommonBase::GetName ()** [static]

Get name of scheduler for current thread.

- 7.135.3.16** `OsclExecSchedulerCommonBase* OsclExecSchedulerCommonBase::GetScheduler ()` [static, protected]
- 7.135.3.17** `void OsclExecSchedulerCommonBase::IncLogPerf (uint32) [protected]`
- 7.135.3.18** `void OsclExecSchedulerCommonBase::InitExecQ (int) [protected]`
- 7.135.3.19** `void OsclExecSchedulerCommonBase::InstallScheduler () [protected]`
- 7.135.3.20** `bool OsclExecSchedulerCommonBase::IsInstalled () [inline, protected]`
- 7.135.3.21** `bool OsclExecSchedulerCommonBase::IsStarted () [protected]`
- 7.135.3.22** `void OsclExecSchedulerCommonBase::PendComplete (PVActiveBase *, int32 aReason, TPVThreadContext aContext) [protected]`
- 7.135.3.23** `void OsclExecSchedulerCommonBase::RequestCanceled (PVActiveBase *) [protected]`
- 7.135.3.24** `void OsclExecSchedulerCommonBase::ResetLogPerf () [protected]`
- 7.135.3.25** `OSCL_IMPORT_REF void OsclExecSchedulerCommonBase::ResumeScheduler ()`

Resume scheduling immediately. This API only applies to a blocking loop scheduler.

- 7.135.3.26** `OsclExecSchedulerCommonBase* OsclExecSchedulerCommonBase::SetScheduler (OsclExecSchedulerCommonBase *) [static, protected]`
- 7.135.3.27** `void OsclExecSchedulerCommonBase::ShowStats (PVActiveStats * active) [static, protected]`
- 7.135.3.28** `void OsclExecSchedulerCommonBase::ShowSummaryStats (PVActiveStats * active, PVLogger *, int64, int64 &, float &) [static, protected]`
- 7.135.3.29** `OSCL_IMPORT_REF void OsclExecSchedulerCommonBase::StartNativeScheduler ()`

Start the OS native scheduling loop. This is an alternative to the PV scheduling loop. To stop the native scheduler, use the StopScheduler API.

- 7.135.3.30** `OSCL_IMPORT_REF void OsclExecSchedulerCommonBase::StartScheduler (OsclSemaphore * sem = NULL)`

Start scheduling. This call blocks until scheduler is stopped or an error occurs.

**Parameters:**

***sem***: optional startup semaphore. If provided, the scheduler will signal this semaphore when the startup has progressed to the point that it's safe to call StopScheduler or SuspendScheduler from another thread.

**7.135.3.31 OSCL\_IMPORT\_REF void OsclExecSchedulerCommonBase::StopScheduler ()**

Stop scheduling. This API may be called from the scheduling thread or some other thread.

**7.135.3.32 OSCL\_IMPORT\_REF void OsclExecSchedulerCommonBase::SuspendScheduler ()**

Suspend scheduling when the current Run is complete. This API only applies to a blocking loop scheduler.

**7.135.3.33 void OsclExecSchedulerCommonBase::UninstallScheduler () [protected]****7.135.3.34 PVActiveBase\* OsclExecSchedulerCommonBase::UpdateTimers (uint32 & aDelay) [protected]****7.135.3.35 PVActiveBase\* OsclExecSchedulerCommonBase::UpdateTimersMsec (uint32 & aDelay) [protected]****7.135.3.36 PVActiveBase\* OsclExecSchedulerCommonBase::WaitForReadyAO () [protected]****7.135.4 Friends And Related Function Documentation****7.135.4.1 friend class OsclActiveObject [friend]****7.135.4.2 friend class OsclCoeActiveScheduler [friend]****7.135.4.3 friend class OsclError [friend]****7.135.4.4 friend class OsclExecScheduler [friend]****7.135.4.5 friend class OsclReadyQ [friend]****7.135.4.6 friend class OsclScheduler [friend]**

Reimplemented in [OsclExecScheduler](#).



- 7.135.4.7 friend class OsclTimerCompare [friend]
- 7.135.4.8 friend class OsclTimerObject [friend]
- 7.135.4.9 friend class PVActiveBase [friend]
- 7.135.4.10 friend class PVActiveStats [friend]
- 7.135.4.11 friend class PVSchedulerStopper [friend]
- 7.135.4.12 friend class PVThreadContext [friend]

## 7.135.5 Field Documentation


- 7.135.5.1 **Oscl\_DefAlloc\*** OsclExecSchedulerCommonBase::iAlloc [protected]
- 7.135.5.2 bool OsclExecSchedulerCommonBase::iBlockingMode [protected]
- 7.135.5.3 **PVLogger\*** OsclExecSchedulerCommonBase::iDebugLogger [protected]
- 7.135.5.4 **OsclMemAllocator** OsclExecSchedulerCommonBase::iDefAlloc [protected]
- 7.135.5.5 int32 OsclExecSchedulerCommonBase::iDelta [protected]
- 7.135.5.6 bool OsclExecSchedulerCommonBase::iDoStop [protected]
- 7.135.5.7 bool OsclExecSchedulerCommonBase::iDoSuspend [protected]
- 7.135.5.8 **OsclErrorTrapImp\*** OsclExecSchedulerCommonBase::iErrorTrapImp [protected]
- 7.135.5.9 **OsclTimerQ** OsclExecSchedulerCommonBase::iExecTimerQ [protected]
- 7.135.5.10 **int64** OsclExecSchedulerCommonBase::iGrandTotalTicks [protected]
- 7.135.5.11 **PVLogger\*** OsclExecSchedulerCommonBase::iLogger [protected]
- 7.135.5.12 char\* OsclExecSchedulerCommonBase::iLogPerfIndentStr [protected]
- 7.135.5.13 int32 OsclExecSchedulerCommonBase::iLogPerfIndentStrLen [protected]
- 7.135.5.14 uint32 OsclExecSchedulerCommonBase::iLogPerfTotal [protected]
- 7.135.5.15 **OsclNameString<PVSCHEDEXNAMELEN>** OsclExecSchedulerCommonBase::iName [protected]
- 7.135.5.16 bool OsclExecSchedulerCommonBase::iNativeMode [protected]
- 7.135.5.17 uint32 OsclExecSchedulerCommonBase::iNumAOAdded [protected]
- 7.135.5.18 **PVActiveStats\*** OsclExecSchedulerCommonBase::iOtherExecStats[EOtherExecStats\_-Last] [protected]
- 7.135.5.19 **OsclDoubleList<PVActiveStats>** OsclExecSchedulerCommonBase::iPVStatQ [protected]

- [oscl\\_scheduler.h](#)

## 7.136 OsclFileCache Class Reference

```
#include <oscl_file_cache.h>
```

Inheritance diagram for OsclFileCache::



### Public Methods

- [OsclFileCache \(Oscl\\_File &aContainer\)](#)
- [~OsclFileCache \(\)](#)
- int32 [Open \(uint32 mode, uint32 cache\\_size\)](#)
- void [Close \(\)](#)
- uint32 [Read \(void \\*outputBuffer, uint32 size, uint32 numelements\)](#)
- uint32 [Write \(const void \\*inputBuffer, uint32 size, uint32 numelements\)](#)
- [TOsclFileOffset FileSize \(\)](#)
- int32 [Seek \(TOsclFileOffset offset, Oscl\\_File::seek\\_type origin\)](#)
- [TOsclFileOffset Tell \(\)](#)
- int32 [Flush \(\)](#)
- int32 [EndOfFile \(\)](#)
- OSCL\_IMPORT\_REF [OsclFileCacheBuffer \\* AddFixedCache \(const Oscl\\_File::OsclFixedCacheParam &\)](#)

### Data Fields

- [OsclFileCacheBuffer \\_movableCache](#)
- [Oscl\\_Vector< OsclFileCacheBuffer, OsclMemAllocator > \\_fixedCaches](#)

### Friends

- class [OsclFileCacheBuffer](#)

### 7.136.1 Constructor & Destructor Documentation

7.136.1.1 **OsclFileCache::OsclFileCache ([Oscl\\_File](#) & *aContainer*)**

7.136.1.2 **OsclFileCache::~OsclFileCache ()**

### 7.136.2 Member Function Documentation

7.136.2.1 **OSCL\_IMPORT\_REF [OsclFileCacheBuffer](#)\* OsclFileCache::AddFixedCache (const [Oscl\\_File::OsclFixedCacheParam](#) &)**

7.136.2.2 **void OsclFileCache::Close ()**

7.136.2.3 **int32 OsclFileCache::EndOfFile () [inline]**

7.136.2.4 **[TOsclFileOffset](#) OsclFileCache::FileSize () [inline]**

7.136.2.5 **int32 OsclFileCache::Flush ()**

7.136.2.6 **int32 OsclFileCache::Open (uint32 *mode*, uint32 *cache\_size*)**

7.136.2.7 **uint32 OsclFileCache::Read (void \* *outputBuffer*, uint32 *size*, uint32 *numelements*)**

7.136.2.8 **int32 OsclFileCache::Seek ([TOsclFileOffset](#) *offset*, [Oscl\\_File::seek\\_type](#) *origin*)**

7.136.2.9 **[TOsclFileOffset](#) OsclFileCache::Tell () [inline]**

7.136.2.10 **uint32 OsclFileCache::Write (const void \* *inputBuffer*, uint32 *size*, uint32 *numelements*)**

### 7.136.3 Friends And Related Function Documentation

7.136.3.1 **friend class OsclFileCacheBuffer [friend]**

### 7.136.4 Field Documentation

7.136.4.1 **[Oscl\\_Vector](#)<[OsclFileCacheBuffer](#), [OsclMemAllocator](#)> OsclFileCache::\_fixedCaches**

7.136.4.2 **[OsclFileCacheBuffer](#) OsclFileCache::\_movableCache**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_cache.h](#)

## 7.137 OsclFileCacheBuffer Class Reference

```
#include <oscl_file_cache.h>
```

### Public Methods

- [OsclFileCacheBuffer \(\)](#)
- int32 [SetPosition \(TOsclFileOffset pos\)](#)
- int32 [PrepRead \(\)](#)
- int32 [PrepWrite \(\)](#)
- int32 [WriteUpdatesToFile \(\)](#)
- int32 [FillFromFile \(uint32, uint32\)](#)
- bool [IsUpdated \(\)](#)
- bool [Contains \(TOsclFileOffset pos\)](#)
- bool [Preceeds \(TOsclFileOffset pos\)](#)

### Data Fields

- [OsclFileCache \\* iContainer](#)
- bool [isFixed](#)
- uint32 [capacity](#)
- uint32 [usableSize](#)
- uint8 \* [pBuffer](#)
- [TOsclFileOffset filePosition](#)
- uint32 [currentPos](#)
- uint32 [endPos](#)
- uint32 [updateStart](#)
- uint32 [updateEnd](#)

### 7.137.1 Constructor & Destructor Documentation

**7.137.1.1** `OsclFileCacheBuffer::OsclFileCacheBuffer () [inline]`

### 7.137.2 Member Function Documentation

**7.137.2.1** `bool OsclFileCacheBuffer::Contains (TOsclFileOffset pos) [inline]`

**7.137.2.2** `int32 OsclFileCacheBuffer::FillFromFile (uint32, uint32)`

**7.137.2.3** `bool OsclFileCacheBuffer::IsUpdated () [inline]`

**7.137.2.4** `bool OsclFileCacheBuffer::Preceeds (TOsclFileOffset pos) [inline]`

**7.137.2.5** `int32 OsclFileCacheBuffer::PreRead ()`

**7.137.2.6** `int32 OsclFileCacheBuffer::PrepWrite ()`

**7.137.2.7** `int32 OsclFileCacheBuffer::SetPosition (TOsclFileOffset pos)`

**7.137.2.8** `int32 OsclFileCacheBuffer::WriteUpdatesToFile ()`

### 7.137.3 Field Documentation

**7.137.3.1** `uint32 OsclFileCacheBuffer::capacity`

**7.137.3.2** `uint32 OsclFileCacheBuffer::currentPos`

**7.137.3.3** `uint32 OsclFileCacheBuffer::endPos`

**7.137.3.4** `TOsclFileOffset OsclFileCacheBuffer::filePosition`

**7.137.3.5** `OsclFileCache* OsclFileCacheBuffer::iContainer`

**7.137.3.6** `bool OsclFileCacheBuffer::isFixed`

**7.137.3.7** `uint8* OsclFileCacheBuffer::pBuffer`

**7.137.3.8** `uint32 OsclFileCacheBuffer::updateEnd`

**7.137.3.9** `uint32 OsclFileCacheBuffer::updateStart`

**7.137.3.10** `uint32 OsclFileCacheBuffer::usableSize`

The documentation for this class was generated from the following file:

- [oscl\\_file\\_cache.h](#)

## 7.138 OsclFileHandle Class Reference

```
#include <oscl_file_handle.h>
```

### Public Methods

- [OsclFileHandle \(TOsclFileHandle aHandle\)](#)
- [OsclFileHandle \(const OsclFileHandle &aHandle\)](#)
- [TOsclFileHandle Handle \(\) const](#)

### Friends

- class [Oscl\\_File](#)

#### 7.138.1 Detailed Description

OsclFileHandle is a container for a handle to a previously-opened file.

#### 7.138.2 Constructor & Destructor Documentation

**7.138.2.1 OsclFileHandle::OsclFileHandle (TOsclFileHandle *aHandle*) [inline]**

**7.138.2.2 OsclFileHandle::OsclFileHandle (const OsclFileHandle & *aHandle*) [inline]**

#### 7.138.3 Member Function Documentation

**7.138.3.1 TOsclFileHandle OsclFileHandle::Handle () const [inline]**

#### 7.138.4 Friends And Related Function Documentation

**7.138.4.1 friend class Oscl\_File [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_handle.h](#)

## 7.139 OsclFileManager Class Reference

```
#include <oscl_file_manager.h>
```

### Public Types

- enum **OSCL\_FILE\_ATTRIBUTE\_TYPE** { **OSCL\_FILE\_ATTRIBUTE\_READONLY** = 0x00000001, **OSCL\_FILE\_ATTRIBUTE\_HIDDEN** = 0x00000002, **OSCL\_FILE\_ATTRIBUTE\_SYSTEM** = 0x00000004, **OSCL\_FILE\_ATTRIBUTE\_DIRECTORY** = 0x00000010, **OSCL\_FILE\_ATTRIBUTE\_ARCHIVE** = 0x00000020, **OSCL\_FILE\_ATTRIBUTE\_NORMAL** = 0x00000080 }

### Static Public Methods

- OSCL\_IMPORT\_REF bool **OsclGetFileSize** (const **oscl\_wchar** \*aFileName, **uint64** &aFileSize)
- OSCL\_IMPORT\_REF bool **OsclGetFileSize** (const char \*aFileName, **uint64** &aFileSize)
- OSCL\_IMPORT\_REF bool **OsclGetFileCreationTime** (const **oscl\_wchar** \*aFileName, **uint64** &aFileCreationTime)
- OSCL\_IMPORT\_REF bool **OsclGetFileCreationTime** (const char \*aFileName, **uint64** &aFileCreationTime)
- OSCL\_IMPORT\_REF bool **OsclGetFileLastAccessTime** (const **oscl\_wchar** \*aFileName, **uint64** &aFileLastAccessTime)
- OSCL\_IMPORT\_REF bool **OsclGetFileLastAccessTime** (const char \*aFileName, **uint64** &aFileLastAccessTime)
- OSCL\_IMPORT\_REF bool **OsclGetFileLastWriteTime** (const **oscl\_wchar** \*aFileName, **uint64** &aFileLastWriteTime)
- OSCL\_IMPORT\_REF bool **OsclGetFileLastWriteTime** (const char \*aFileName, **uint64** &aFileLastWriteTime)
- OSCL\_IMPORT\_REF bool **OsclGetFileAttributes** (const **oscl\_wchar** \*aFileName, **uint32** &aFileAttributes)
- OSCL\_IMPORT\_REF bool **OsclGetFileAttributes** (const char \*aFileName, **uint32** &aFileAttributes)
- OSCL\_IMPORT\_REF void **OsclExtractFilenameFromFullPath** (const char \*aPath, char \*&aFileName)
- OSCL\_IMPORT\_REF void **OsclExtractFilenameFromFullPath** (const **oscl\_wchar** \*aPath, **oscl\_wchar** \*&aFileName)

### 7.139.1 Member Enumeration Documentation

#### 7.139.1.1 enum OsclFileManager::OSCL\_FILE\_ATTRIBUTE\_TYPE

Enumeration values:

- OSCL\_FILE\_ATTRIBUTE\_READONLY**
- OSCL\_FILE\_ATTRIBUTE\_HIDDEN**
- OSCL\_FILE\_ATTRIBUTE\_SYSTEM**
- OSCL\_FILE\_ATTRIBUTE\_DIRECTORY**
- OSCL\_FILE\_ATTRIBUTE\_ARCHIVE**
- OSCL\_FILE\_ATTRIBUTE\_NORMAL**

## 7.139.2 Member Function Documentation

**7.139.2.1 OSCL\_IMPORT\_REF void OsclFileManager::OsclExtractFilenameFromFullPath  
(const oscl\_wchar \* aPath, oscl\_wchar \*& aFileName) [static]**

**7.139.2.2 OSCL\_IMPORT\_REF void OsclFileManager::OsclExtractFilenameFromFullPath  
(const char \* aPath, char \*& aFileName) [static]**

OsclExtractFilenameFromFullPath utility function provide the FileName From Path of a file.

**Parameters:**

*in* ] character path; the full path of the file or directory

*out* ] character FileName :file Name .It is assigned a pointer to file name in path itself.

**Returns:**

void for all condition

**7.139.2.3 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileAttributes (const char \*  
aFileName, uint32 & aFileAttributes) [static]**

OsclGetFileAttributes utility function provides the various attributes of file (or directory) like if it is hidden, read only etc. The uint32 value is to be interpreted as per the enum OSCL\_FILE\_ATTRIBUTE\_TYPE defined in [oscl\\_file\\_manager.h](#)

**Parameters:**

*in* ] character path; the full path of the file or directory

*out* ] file attributes.

**Returns:**

true if successful, otherwise false.

**7.139.2.4 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileAttributes (const oscl\_wchar  
\* aFileName, uint32 & aFileAttributes) [static]**

OsclGetFileAttributes utility function provides the various attributes of file (or directory) like if it is hidden, read only etc. The uint32 value is to be interpreted as per the enum OSCL\_FILE\_ATTRIBUTE\_TYPE defined in [oscl\\_file\\_manager.h](#)

**Parameters:**

*in* ] wide character path; the full path of the file or directory

*out* ] file attributes.

**Returns:**

true if successful, otherwise false.

**7.139.2.5 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileCreationTime (const char \*  
aFileName, uint64 & aFileCreationTime) [static]**

OsclGetFileCreationTime utility function provides the file (or directory) creation time

**Note:**

On symbian platform, this api returns last modified time.

**Parameters:**

*in* ] character path; the full path of the file or directory

*out* ] creation time in microseconds.

**Returns:**

true if successful, otherwise false.

**7.139.2.6 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileCreationTime (const  
oscl\_wchar \* aFileName, uint64 & aFileCreationTime) [static]**

OsclGetFileCreationTime utility function provides the file (or directory) creation time

**Note:**

On symbian platform, this api returns last modified time.

**Parameters:**

*in* ] wide character path; the full path of the file or directory

*out* ] creation time in microseconds

**Returns:**

true if successful, otherwise false.

**7.139.2.7 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileLastAccessTime (const char  
\* aFileName, uint64 & aFileLastAccessTime) [static]**

OsclGetFileLastAccessTime utility function provides the file (or directory) last access time, which might be different from last modified time.

**Note:**

On symbian platform, this api returns last modified time.

**Parameters:**

*in* ] character path; the full path of the file or directory

*out* ] Last access time in microseconds.

**Returns:**

true if successful, otherwise false.

**7.139.2.8 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileLastAccessTime (const oscl\_wchar \* aFileName, uint64 & aFileLastAccessTime) [static]**

OsclGetFileLastAccessTime utility function provides the file (or directory) last access time, which might be different from last modified time.

**Note:**

On symbian platform, this api returns last modified time.

**Parameters:**

*in* ] wide character path; the full path of the file or directory  
*out* ] Last access time in microseconds

**Returns:**

true if successful, otherwise false.

**7.139.2.9 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileLastWriteTime (const char \* aFileName, uint64 & aFileLastWriteTime) [static]**

OsclGetFileLastWriteTime utility function provides the file (or directory) last modified time.

**Parameters:**

*in* ] character path; the full path of the file or directory  
*out* ] last modified time in microseconds

**Returns:**

true if successful, otherwise false.

**7.139.2.10 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileLastWriteTime (const oscl\_wchar \* aFileName, uint64 & aFileLastWriteTime) [static]**

OsclGetFileLastWriteTime utility function provides the file (or directory) last modified time.

**Parameters:**

*in* ] wide character path; the full path of the file or directory  
*out* ] last modified time in microseconds

**Returns:**

true if successful, otherwise false.

**7.139.2.11 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileSize (const char \* aFileName, uint64 & aFileSize) [static]**

OsclGetFileSize utility function provides the file size. For directory, this value is undefined.

**Parameters:**

*in* ] character path; the full path of the file or directory  
*out* ] file size in bytes.

**Returns:**

true if successful, otherwise false.

**7.139.2.12 OSCL\_IMPORT\_REF bool OsclFileManager::OsclGetFileSize (const oscl\_wchar \*  
*aFileName*, uint64 & *aFileSize*) [static]**

OsclGetFileSize utility function provides the file size. For directory, this value is undefined. creation time

**Parameters:**

- in* ] wide character path; the full path of the file or directory
- out* ] file size in bytes

**Returns:**

true if successful, otherwise false.

The documentation for this class was generated from the following file:

- [oscl\\_file\\_manager.h](#)

## 7.140 OsclFileStats Class Reference

```
#include <oscl_file_stats.h>
```

### Public Methods

- [OsclFileStats \(Oscl\\_File \\*c\)](#)
- [void Start \(uint32 &aTicks\)](#)
- [void End \(TOsclFileOp aOp, uint32 aStart, uint32 aParam=0, TOsclFileOffset aParam2=0\)](#)
- [void Log \(TOsclFileOp, PVLogger \\*, uint32\)](#)
- [void LogAll \(PVLogger \\*, uint32\)](#)

#### 7.140.1 Constructor & Destructor Documentation

##### 7.140.1.1 OsclFileStats::OsclFileStats ([Oscl\\_File](#) \* *c*)

#### 7.140.2 Member Function Documentation

##### 7.140.2.1 void OsclFileStats::End ([TOsclFileOp](#) *aOp*, [uint32](#) *aStart*, [uint32](#) *aParam* = 0, [TOsclFileOffset](#) *aParam2* = 0)

##### 7.140.2.2 void OsclFileStats::Log ([TOsclFileOp](#), [PVLogger](#) \*, [uint32](#))

##### 7.140.2.3 void OsclFileStats::LogAll ([PVLogger](#) \*, [uint32](#))

##### 7.140.2.4 void OsclFileStats::Start ([uint32](#) & *aTicks*)

The documentation for this class was generated from the following file:

- [oscl\\_file\\_stats.h](#)

## 7.141 OsclFileStatsItem Class Reference

```
#include <oscl_file_stats.h>
```

### Data Fields

- uint32 [iOpCount](#)
- uint64 [iParam](#)
- [TOsclFileOffset](#) [iParam2](#)
- uint32 [iStartTick](#)
- uint32 [iTTotalTicks](#)

#### 7.141.1 Field Documentation

**7.141.1.1 uint32 OsclFileStatsItem::iOpCount**

**7.141.1.2 uint64 OsclFileStatsItem::iParam**

**7.141.1.3 TOsclFileOffset OsclFileStatsItem::iParam2**

**7.141.1.4 uint32 OsclFileStatsItem::iStartTick**

**7.141.1.5 uint32 OsclFileStatsItem::iTTotalTicks**


The documentation for this class was generated from the following file:

- [oscl\\_file\\_stats.h](#)

## 7.142 OsclGetHostByNameMethod Class Reference

```
#include <oscl_dns_gethostbyname.h>
```

Inheritance diagram for OsclGetHostByNameMethod::



### Public Methods

- `~OsclGetHostByNameMethod ()`
- `TPVDNSEvent GetHostByName (char *name, OsclNetworkAddress *addr, int32 aTimeout, Oscl_-Vector< OsclNetworkAddress, OsclMemAllocator > *aAddressList)`

### Static Public Methods

- `OsclGetHostByNameMethod * NewL (Oscl_DefAlloc &a, OsclDNSI *aDNS, OsclDNSObserver *aObserver, uint32 aId)`

#### 7.142.1 Constructor & Destructor Documentation

##### 7.142.1.1 OsclGetHostByNameMethod::~OsclGetHostByNameMethod ()

#### 7.142.2 Member Function Documentation

##### 7.142.2.1 TPVDNSEvent OsclGetHostByNameMethod::GetHostByName (char \* name, OsclNetworkAddress \* addr, int32 aTimeout, Oscl\_Vector< OsclNetworkAddress, OsclMemAllocator > \* aAddressList)

##### 7.142.2.2 OsclGetHostByNameMethod\* OsclGetHostByNameMethod::NewL (Oscl\_DefAlloc &a, OsclDNSI \*aDNS, OsclDNSObserver \*aObserver, uint32 aId) [static]


The documentation for this class was generated from the following file:

- `oscl_dns_gethostbyname.h`

## 7.143 OsclGetHostByNameRequest Class Reference

```
#include <oscl_dns_gethostbyname.h>
```

Inheritance diagram for OsclGetHostByNameRequest::



### Friends

- class [OsclGetHostByNameMethod](#)

#### 7.143.1 Friends And Related Function Documentation

##### 7.143.1.1 friend class OsclGetHostByNameMethod [friend]

The documentation for this class was generated from the following file:

- [oscl\\_dns\\_gethostbyname.h](#)

## 7.144 OsclInit Class Reference

```
#include <oscl_init.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF void [Init](#) (int32 &aError, const [OsclSelect](#) \*aSelect=NULL)
- OSCL\_IMPORT\_REF void [Cleanup](#) (int32 &aError, const [OsclSelect](#) \*aSelect=NULL)

#### 7.144.1 Detailed Description

Per-thread oscl initialization and cleanup.

#### 7.144.2 Member Function Documentation

##### 7.144.2.1 OSCL\_IMPORT\_REF void OsclInit::Cleanup (int32 & aError, const [OsclSelect](#) \* aSelect = NULL) [static]

This routine cleans up the Oscl modules in the calling thread.

###### Parameters:

*err*: (output) error code of any leave that occurs in initialization.

*config*: (input param) optional set of initialization parameters. If null, then full initialization with default parameters will be performed. For proper cleanup, the parameters should match the ones used during the Init call.

##### 7.144.2.2 OSCL\_IMPORT\_REF void OsclInit::Init (int32 & aError, const [OsclSelect](#) \* aSelect = NULL) [static]

This routine initializes the Oscl modules in the calling thread.

###### Parameters:

*err*: (output) error code of any leave that occurs in initialization.

*config*: (input param) optional set of initialization parameters. If null, then full initialization with default parameters will be performed.

The documentation for this class was generated from the following file:

- [oscl\\_init.h](#)

## 7.145 OsclInteger64Transport Struct Reference

```
#include <oscl_int64_utils.h>
```

### Data Fields

- uint32 [iHigh](#)
- uint32 [iLow](#)

#### 7.145.1 Detailed Description

OsclInteger64Transport Structure

Structure to only transport 64-bit integer values uint64 and int64 could be classes so needed for cases where having a class will not work.

#### 7.145.2 Field Documentation

##### 7.145.2.1 uint32 OsclInteger64Transport::iHigh

##### 7.145.2.2 uint32 OsclInteger64Transport::iLow

The documentation for this struct was generated from the following file:

- [oscl\\_int64\\_utils.h](#)

## 7.146 OsclIpMReq Class Reference

```
#include <oscl_socket_types.h>
```

### Public Methods

- [OsclIpMReq \(const char \\*intrfcAddr, const char \\*multcstAddr\)](#)

### Data Fields

- [OsclNameString< PVNETWORKADDRESS\\_LEN > interfaceAddr](#)
- [OsclNameString< PVNETWORKADDRESS\\_LEN > multicastAddr](#)

#### 7.146.1 Constructor & Destructor Documentation

**7.146.1.1 OsclIpMReq::OsclIpMReq (const char \* *intrfcAddr*, const char \* *multcstAddr*)**  
[inline]

#### 7.146.2 Field Documentation

**7.146.2.1 OsclNameString<PVNETWORKADDRESS\_LEN> OsclIpMReq::interfaceAddr**

**7.146.2.2 OsclNameString<PVNETWORKADDRESS\_LEN> OsclIpMReq::multicastAddr**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_types.h](#)

## 7.147 OsclIPSocketI Class Reference

```
#include <oscl_ip_socket.h>
```

Inheritance diagram for OsclIPSocketI::



### Public Methods

- int32 [Bind \(OsclNetworkAddress &aAddress\)](#)
- int32 [Join \(OsclNetworkAddress &aAddress\)](#)
- int32 [SetRecvBufferSize \(uint32 size\)](#)
- int32 [SetOptionToReuseAddress \(\)](#)
- int32 [SetTOS \(const OsclSocketTOS &aTOS\)](#)
- int32 [GetPeerName \(OsclNetworkAddress &peerName\)](#)
- virtual int32 [Close \(\)=0](#)
- virtual uint8 \* [GetRecvData \(int32 \\*aLength\)=0](#)
- virtual uint8 \* [GetSendData \(int32 \\*aLength\)=0](#)
- virtual ~[OsclIPSocketI \(\)](#)
- void [ThreadLogoff \(\)](#)
- void [ThreadLogon \(OsclSocketObserver \\*aObs, OsclSocketServI \\*aServ\)](#)
- [OsclSocketServI \\* SocketServ \(\)](#)
- [Oscl\\_DefAlloc & Alloc \(\)](#)

### Protected Methods

- [OsclIPSocketI \(Oscl\\_DefAlloc &a\)](#)
- void [ConstructL \(OsclSocketObserver \\*aObs, OsclSocketI \\*aSock, OsclSocketServI \\*aServ, uint32 aId\)](#)

### Protected Attributes

- [Oscl\\_DefAlloc & iAlloc](#)
- [OsclNetworkAddress iAddress](#)
- uint32 [iId](#)
- [OsclSocketObserver \\* iObserver](#)
- [OsclSocketI \\* iSocket](#)
- [OsclSocketServI \\* iSocketServ](#)
- [PVLogger \\* iLogger](#)

### Friends

- class [OsclSocketRequestAO](#)
- class [OsclSocketMethod](#)

### 7.147.1 Constructor & Destructor Documentation

7.147.1.1 `virtual OsclIPSocketI::~OsclIPSocketI () [inline, virtual]`

7.147.1.2 `OsclIPSocketI::OsclIPSocketI (Oscl_DefAlloc & a) [inline, protected]`

### 7.147.2 Member Function Documentation

7.147.2.1 `Oscl_DefAlloc& OsclIPSocketI::Alloc () [inline]`

7.147.2.2 `int32 OsclIPSocketI::Bind (OsclNetworkAddress & aAddress)`

7.147.2.3 `virtual int32 OsclIPSocketI::Close () [pure virtual]`

Implemented in [OsclTCPSocketI](#), and [OsclUDPSocketI](#).

7.147.2.4 `void OsclIPSocketI::ConstructL (OsclSocketObserver * aObs, OsclSocketI * aSock, OsclSocketServI * aServ, uint32 aId) [protected]`

7.147.2.5 `int32 OsclIPSocketI::GetPeerName (OsclNetworkAddress & peerName)`

7.147.2.6 `virtual uint8* OsclIPSocketI::GetRecvData (int32 * aLength) [pure virtual]`

Implemented in [OsclTCPSocketI](#), and [OsclUDPSocketI](#).

7.147.2.7 `virtual uint8* OsclIPSocketI::GetSendData (int32 * aLength) [pure virtual]`

Implemented in [OsclTCPSocketI](#), and [OsclUDPSocketI](#).

7.147.2.8 `int32 OsclIPSocketI::Join (OsclNetworkAddress & aAddress)`

7.147.2.9 `int32 OsclIPSocketI::SetOptionToReuseAddress ()`

7.147.2.10 `int32 OsclIPSocketI::SetRecvBufferSize (uint32 size)`

7.147.2.11 `int32 OsclIPSocketI::SetTOS (const OsclSocketTOS & aTOS)`

7.147.2.12 `OsclSocketServI* OsclIPSocketI::SocketServ () [inline]`

7.147.2.13 `void OsclIPSocketI::ThreadLogoff ()`

Reimplemented in [OsclTCPSocketI](#), and [OsclUDPSocketI](#).

7.147.2.14 void OsclIPSocketI::ThreadLogon ([OsclSocketObserver](#) \* *aObs*, [OsclSocketServI](#) \* *aServ*)

### 7.147.3 Friends And Related Function Documentation

7.147.3.1 friend class [OsclSocketMethod](#) [friend]

7.147.3.2 friend class [OsclSocketRequestAO](#) [friend]

### 7.147.4 Field Documentation

7.147.4.1 [OsclNetworkAddress](#) [OsclIPSocketI::iAddress](#) [protected]

7.147.4.2 [Oscl\\_DefAlloc&](#) [OsclIPSocketI::iAlloc](#) [protected]

7.147.4.3 uint32 [OsclIPSocketI::iId](#) [protected]

7.147.4.4 [PVLogger\\*](#) [OsclIPSocketI::iLogger](#) [protected]

7.147.4.5 [OsclSocketObserver\\*](#) [OsclIPSocketI::iObserver](#) [protected]

7.147.4.6 [OsclSocketI\\*](#) [OsclIPSocketI::iSocket](#) [protected]

7.147.4.7 [OsclSocketServI\\*](#) [OsclIPSocketI::iSocketServ](#) [protected]

The documentation for this class was generated from the following file:

- [oscl\\_ip\\_socket.h](#)

## 7.148 OsclJump Class Reference

```
#include <oscl_error_imp_jumps.h>
```

### Public Methods

- void [Jump](#) (int a)
- jmp\_buf \* [Top](#) ()
- [~OsclJump](#) ()

### Static Public Methods

- OSCL\_IMPORT\_REF void [StaticJump](#) (int a)

### Friends

- class [OsclErrorTrapImp](#)

#### 7.148.1 Constructor & Destructor Documentation

**7.148.1.1 OsclJump::~OsclJump () [inline]**

#### 7.148.2 Member Function Documentation

**7.148.2.1 void OsclJump::Jump (int a) [inline]**

**7.148.2.2 OSCL\_IMPORT\_REF void OsclJump::StaticJump (int a) [static]**

**7.148.2.3 jmp\_buf\* OsclJump::Top () [inline]**

#### 7.148.3 Friends And Related Function Documentation

**7.148.3.1 friend class OsclErrorTrapImp [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_error\\_imp\\_jumps.h](#)

## 7.149 OsclListenMethod Class Reference

```
#include <oscl_socket_listen.h>
```

Inheritance diagram for OsclListenMethod::



### Public Methods

- [~OsclListenMethod \(\)](#)
- [TPVSocketEvent Listen \(uint32 qsize, int32 aTimeout\)](#)
- [OsclListenRequest \\* ListenRequest \(\)](#)

### Static Public Methods

- [OsclListenMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.149.1 Constructor & Destructor Documentation

##### 7.149.1.1 OsclListenMethod::~OsclListenMethod ()

#### 7.149.2 Member Function Documentation

##### 7.149.2.1 TPVSocketEvent OsclListenMethod::Listen (uint32 qsize, int32 aTimeout)

##### 7.149.2.2 OsclListenRequest\* OsclListenMethod::ListenRequest () [inline]

##### 7.149.2.3 OsclListenMethod\* OsclListenMethod::NewL (OsclIPSocketI &c) [static]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_listen.h](#)

## 7.150 OsclListenRequest Class Reference

```
#include <oscl_socket_listen.h>
```

Inheritance diagram for OsclListenRequest::



### Public Methods

- [OsclListenRequest \(OsclSocketMethod &c\)](#)
- void [Listen \(uint32 qsize\)](#)

#### 7.150.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.150.2 Constructor & Destructor Documentation

**7.150.2.1 OsclListenRequest::OsclListenRequest ([OsclSocketMethod & c](#)) [inline]**

#### 7.150.3 Member Function Documentation

**7.150.3.1 void OsclListenRequest::Listen (uint32 *qsize*)**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_listen.h](#)

## 7.151 OsclLockBase Class Reference

```
#include <oscl_lock_base.h>
```

Inheritance diagram for OsclLockBase::



### Public Methods

- virtual void [Lock \(\)=0](#)
- virtual void [Unlock \(\)=0](#)
- virtual [~OsclLockBase \(\)](#)

#### 7.151.1 Constructor & Destructor Documentation

**7.151.1.1 virtual OsclLockBase::~OsclLockBase () [inline, virtual]**

#### 7.151.2 Member Function Documentation

**7.151.2.1 virtual void OsclLockBase::Lock () [pure virtual]**

Implemented in [OsclNullLock](#), [OsclMutex](#), and [OsclThreadLock](#).

**7.151.2.2 virtual void OsclLockBase::Unlock () [pure virtual]**

Implemented in [OsclNullLock](#), [OsclMutex](#), and [OsclThreadLock](#).

The documentation for this class was generated from the following file:

- [oscl\\_lock\\_base.h](#)

## 7.152 OsclMem Class Reference

```
#include <oscl_mem.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF void [Init \(\)](#)
- OSCL\_IMPORT\_REF void [Cleanup \(\)](#)

#### 7.152.1 Member Function Documentation

##### 7.152.1.1 OSCL\_IMPORT\_REF void OsclMem::Cleanup () [static]

Per-thread cleanup of Oscl Memory @exception: Leaves on error;

##### 7.152.1.2 OSCL\_IMPORT\_REF void OsclMem::Init () [static]

Per-thread initialization of Oscl Memory

#### Parameters:

*lock*: A lock class for use with multi-threaded applications. The lock is needed in use cases where memory may be allocated in one thread and freed in another. In this case, there must be a single lock object, and its pointer must be passed to the [OsclMem::Init](#) call in each thread. If no lock is provided, the memory manager will not be thread-safe. @exception: Leaves on error


The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.153 OsclMemAllocator Class Reference

```
#include <oscl_mem.h>
```

Inheritance diagram for OsclMemAllocator::



### Public Methods

- [OsclAny \\* allocate \(const uint32 n\)](#)
- [OsclAny \\* allocate\\_fl \(const uint32 n, const char \\*file\\_name, const int line\\_num\)](#)
- void [deallocate \(OsclAny \\*p\)](#)

#### 7.153.1 Detailed Description

A simple allocator class. Configurable as to whether this goes through the memory manager or not.

#### 7.153.2 Member Function Documentation

##### 7.153.2.1 [OsclAny\\* OsclMemAllocator::allocate \(const uint32 n\)](#) [inline, virtual]

This API throws an exception when malloc returns NULL. n must be greater than 0.

**Returns:**

pointer (or Leave with OsclErrNoMemory )

Implements [Oscl\\_DefAlloc](#).

##### 7.153.2.2 [OsclAny\\* OsclMemAllocator::allocate\\_fl \(const uint32 n, const char \\*file\\_name, const int line\\_num\)](#) [inline, virtual]

Reimplemented from [Oscl\\_DefAlloc](#).

##### 7.153.2.3 [void OsclMemAllocator::deallocate \(OsclAny \\*p\)](#) [inline, virtual]

Implements [Oscl\\_DefAlloc](#).


The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.154 OsclMemAllocDestructDealloc< T > Class Template Reference

```
#include <oscl_mem.h>
```

Inheritance diagram for OsclMemAllocDestructDealloc< T >::



### Public Methods

- [OsclAny \\* allocate\\_f1](#) (const uint32 size, const char \*file\_name, const int line\_num)
- [OsclAny \\* allocate](#) (const uint32 size)
- void [deallocate](#) (OsclAny \*p)
- void [destruct\\_and\\_dealloc](#) (OsclAny \*p)

#### 7.154.1 Detailed Description

`template<class T> class OsclMemAllocDestructDealloc< T >`

An [OsclAllocDestructDealloc](#) class that uses [OsclMemAllocator](#).

#### 7.154.2 Member Function Documentation

**7.154.2.1 `template<class T> OsclAny* OsclMemAllocDestructDealloc< T >::allocate (const uint32 size) [inline, virtual]`**

Implements [Oscl\\_DefAlloc](#).

**7.154.2.2 `template<class T> OsclAny* OsclMemAllocDestructDealloc< T >::allocate_f1 (const uint32 size, const char *file_name, const int line_num) [inline, virtual]`**

Reimplemented from [Oscl\\_DefAlloc](#).

**7.154.2.3 `template<class T> void OsclMemAllocDestructDealloc< T >::deallocate (OsclAny * p) [inline, virtual]`**

Implements [Oscl\\_DefAlloc](#).

**7.154.2.4 template<class T> void OsclMemAllocDestructDealloc< T >::destruct\_and\_dealloc  
(OsclAny \* p) [inline, virtual]**

Implements [OsclDestructDealloc](#).

The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.155 OsclMemAudit Class Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [OsclMemAudit \(\)](#)
- [~OsclMemAudit \(\)](#)
- [void \\* MM\\_allocate \(const OsclMemStatsNode \\*statsNode, uint32 sizeIn, const char \\*pFileName, uint32 lineNumber, bool allocNodeTracking=false\)](#)
- [bool MM\\_deallocate \(void \\*pMemBlockIn\)](#)
- [MM\\_Stats\\_t \\* MM\\_GetStats \(const char \\*const tagIn\)](#)
- [uint32 MM\\_GetStatsInDepth \(const char \\*tagIn, MM\\_Stats\\_CB \\*array\\_ptr, uint32 max\\_nodes\)](#)
- [uint32 MM\\_GetTreeNodes \(const char \\*tagIn\)](#)
- [bool MM\\_AddTag \(const char \\*tagIn\)](#)
- [const OsclMemStatsNode \\* MM\\_GetTagName \(const char \\*tagIn\)](#)
- [const OsclMemStatsNode \\* MM\\_GetExistingTag \(const char \\*tagIn\)](#)
- [const OsclMemStatsNode \\* MM\\_GetRootNode \(\)](#)
- [uint32 MM\\_GetAllocNodeInfo \(MM\\_AllocQueryInfo \\*output\\_array, uint32 max\\_array\\_size, uint32 offset\)](#)
- [MM\\_AllocQueryInfo \\* MM\\_CreateAllocNodeInfo \(uint32 max\\_array\\_size\)](#)
- [void MM\\_ReleaseAllocNodeInfo \(MM\\_AllocQueryInfo \\*info\)](#)
- [bool MM\\_Validate \(const void \\*ptrIn\)](#)
- [uint32 MM\\_GetAllocNo \(void\)](#)
- [void MM\\_GetOverheadStats \(MM\\_AuditOverheadStats &stats\)](#)
- [uint32 MM\\_GetNumAllocNodes \(\)](#)
- [uint32 MM\\_GetMode \(void\)](#)
- [uint8 MM\\_GetPrefillPattern \(void\)](#)
- [uint32 MM\\_GetPostfillPattern \(void\)](#)
- [void MM\\_SetMode \(uint32 inMode\)](#)
- [void MM\\_SetPrefillPattern \(uint8 pattern\)](#)
- [void MM\\_SetPostfillPattern \(uint8 pattern\)](#)
- [void MM\\_SetTagLevel \(uint32 level\)](#)
- [bool MM\\_SetFailurePoint \(const char \\*tagIn, uint32 alloc\\_number\)](#)
- [void MM\\_UnsetFailurePoint \(const char \\*tagIn\)](#)
- [int32 MM\\_GetRefCount \(\)](#)
- [OsclLockBase \\* GetLock \(\)](#)

### Friends

- class [OsclMemGlobalAuditObject](#)

#### 7.155.1 Constructor & Destructor Documentation

##### 7.155.1.1 OsclMemAudit::OsclMemAudit () [inline]

Constructor, create the root node in statistics table

**7.155.1.2 OsclMemAudit::~OsclMemAudit () [inline]**

A destructor, remove all the nodes in allocation andstatistics table

**7.155.2 Member Function Documentation****7.155.2.1 OsclLockBase\* OsclMemAudit::GetLock () [inline]**

API to obtain mem lock ptr

**7.155.2.2 bool OsclMemAudit::MM\_AddTag (const char \* tagIn) [inline]**

API to add a node and zero out its counters; Note that this tag should be re-used

**Parameters:**

*tagIn* input tag

**Returns:**

true if operation succeeds;

**7.155.2.3 void\* OsclMemAudit::MM\_allocate (const OsclMemStatsNode \* statsNode, uint32 sizeIn, const char \* pFileName, uint32 lineNumber, bool allocNodeTracking = false) [inline]**

The following are APIs t \_\_nothrow\_ / const \_\_nothrow\_

**Returns:**

the memory pointer if operation succeeds.

**7.155.2.4 MM\_AllocQueryInfo\* OsclMemAudit::MM\_CreateAllocNodeInfo (uint32 max\_array\_size) [inline]****7.155.2.5 bool OsclMemAudit::MM\_deallocate (void \* pMemBlockIn) [inline]****Returns:**

true if operation succeeds;

**7.155.2.6 uint32 OsclMemAudit::MM\_GetAllocNo (void) [inline]**

API to get the current allocation number

**Returns:**

the current allocation number

**7.155.2.7** `uint32 OsclMemAudit::MM_GetAllocNodeInfo (MM_AllocQueryInfo * output_array, uint32 max_array_size, uint32 offset) [inline]`

API to query the list of alloc nodes. It copies the information into the provided output array.

**Parameters:**

*output\_array* the array where the data will be written

*max\_array\_size* the max number of output array elements

*offset* the offset into the alloc node list from which the data should begin.

**Returns:**

the number of valid nodes in the output array

**7.155.2.8** `const OsclMemStatsNode* OsclMemAudit::MM_GetExistingTag (const char * tagIn) [inline]`

API to add a node and zero out its counters; Note that this tag should be re-used

**Parameters:**

*tagIn* input tag

**Returns:**

true if operation succeeds;

**7.155.2.9** `uint32 OsclMemAudit::MM_GetMode (void) [inline]`

API to get the operating mode of the mm\_audit class.

**7.155.2.10** `uint32 OsclMemAudit::MM_GetNumAllocNodes () [inline]`

API to get the number of allocation nodes (records) for allocations that are being tracked individually.

**7.155.2.11** `void OsclMemAudit::MM_GetOverheadStats (MM_AuditOverheadStats & stats) [inline]`

API to get the overhead statistics for the memory used by the mm\_audit class.

**7.155.2.12** `uint32 OsclMemAudit::MM_GetPostfillPattern (void) [inline]`

API to get the postfill pattern. The pattern is used to fill the memory before freeing it.

**7.155.2.13** `uint8 OsclMemAudit::MM_GetPrefillPattern (void) [inline]`

API to get the prefill pattern. The pattern is used to fill the memory before returning it to the caller.

**7.155.2.14 int32 OsclMemAudit::MM\_GetRefCount () [inline]**

**7.155.2.15 const OsclMemStatsNode\* OsclMemAudit::MM\_GetRootNode () [inline]**

**7.155.2.16 MM\_Stats\_t\* OsclMemAudit::MM\_GetStats (const char \*const tagIn) [inline]**

API to get memory statistics through context string(tag)

**Returns:**

statistics pointer if operation succeeds

**7.155.2.17 uint32 OsclMemAudit::MM\_GetStatsInDepth (const char \* tagIn, MM\_Stats\_CB \* array\_ptr, uint32 max\_nodes) [inline]**

API to get memory statistics in detail through context string(tag) including its subtree

**Returns:**

statistics pointer array and actual number of nodes if operation succeeds

**7.155.2.18 const OsclMemStatsNode\* OsclMemAudit::MM\_GetTagName (const char \* tagIn) [inline]**

API to add a node and zero out its counters; Note that this tag should be re-used

**Parameters:**

*tagIn* input tag

**Returns:**

pointer to [OsclMemStatsNode](#) which should be passed to MM\_allocate

**7.155.2.19 uint32 OsclMemAudit::MM\_GetTreeNodes (const char \* tagIn) [inline]**

API to get the number of tree nodes including the tag node and its subtree

**Parameters:**

*tagIn* input tag

**Returns:**

the number of tree nodes ; 0 means no tag node

**7.155.2.20 void OsclMemAudit::MM\_ReleaseAllocNodeInfo (MM\_AllocQueryInfo \* info) [inline]**

**7.155.2.21 bool OsclMemAudit::MM\_SetFailurePoint (const char \* tagIn, uint32 alloc\_number) [inline]**

API to insert allocation failure deterministically according to allocation number associated with tag

**Parameters:**

*tagIn* input tag  
*alloc\_number* allocation number associated with tag

**Returns:**

true if operation succeeds;

**7.155.2.22 void OsclMemAudit::MM\_SetMode (uint32 *inMode*) [inline]**

API to set the operating mode of the mm\_audit class.

**7.155.2.23 void OsclMemAudit::MM\_SetPostfillPattern (uint8 *pattern*) [inline]**

API to set the postfill pattern.

**7.155.2.24 void OsclMemAudit::MM\_SetPrefillPattern (uint8 *pattern*) [inline]**

API to set the prefill pattern.

**7.155.2.25 void OsclMemAudit::MM\_SetTagLevel (uint32 *level*) [inline]**

API to set the maximum tag level,i.e. tag level for a.b.c.d = 4

**Parameters:**

*level* input tag level to be set

**7.155.2.26 void OsclMemAudit::MM\_UnsetFailurePoint (const char \* *tagIn*) [inline]**

API to cancel the allocation failure point associated with tag

**Parameters:**

*tagIn* input tag

**7.155.2.27 bool OsclMemAudit::MM\_Validate (const void \* *ptrIn*) [inline]**

API to check the input pointer is a valid pointer to a chunk of memory

**Parameters:**

*ptrIn* input pointer to be validated

**Returns:**

true if operation succeeds;

### **7.155.3 Friends And Related Function Documentation**

#### **7.155.3.1 friend class OsclMemGlobalAuditObject [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.156 OSCLMemAutoPtr< T, \_Allocator > Class Template Reference

The oscl\_auto\_ptr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or indirectly) by new. When the oscl\_auto\_ptr expires, its destructor uses delete to free the memory.

```
#include <oscl_mem_auto_ptr.h>
```

### Public Methods

- **OSCLMemAutoPtr** (T \*inPtr=0)  
*Default constructor Initializes the pointer and takes ownership.*
- **OSCLMemAutoPtr** (const OSCLMemAutoPtr< T > &\_Y)  
*Copy constructor.*
- **OSCLMemAutoPtr< T, \_Allocator > & operator=** (const OSCLMemAutoPtr< T, \_Allocator > &\_Y)  
*Assignment operator from an another oscl\_auto\_ptr.*
- **~OSCLMemAutoPtr** ()  
*Destructor.*
- **T & operator \*** () const  
*The indirection operator (\*) accesses a value indirectly, through a pointer.*
- **T \* operator ->** () const  
*The indirection operator (->) accesses a value indirectly, through a pointer.*
- **void takeOwnership** (T \*ptr)  
*The takeOwnership function assigns the value with ownership.*
- **void allocate** (**oscl\_memsize\_t** size)
- **void setWithoutOwnership** (T \*ptr)  
*The takeOwnership function assigns the value with ownership.*
- **T \* get** () const  
*get() method returns the pointer, currently owned by the class.*
- **T \* release** () const  
*release() method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.*

### Static Public Methods

- **void deallocate** (T \*ptr)

## Data Fields

- bool [\\_Ownership](#)

### 7.156.1 Detailed Description

```
template<class T, class _Allocator = Oscl_TAlloc<T, OsclMemAllocator>> class OSCLMemAuto-  
Ptr< T, _Allocator >
```

The oscl\_auto\_ptr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or indirectly) by new. When the oscl\_auto\_ptr expires, its destructor uses delete to free the memory.

The purpose of this class is to provide a way to prevent accidental memory leaks in a class or a method, due to "not remembering to delete" variables allocated on the heap. Thus if you assign an address returned by new to an oscl\_auto\_ptr object, you don't have to remember to free the memory later, it will be freed automatically when the object goes out of scope. The oscl\_auto\_ptr is an example of a smart pointer, an object that acts like a pointer, but with additional features. The class is defined so that it acts like a regular pointer in most respects

### 7.156.2 Constructor & Destructor Documentation

```
7.156.2.1 template<class T, class _Allocator = Oscl_TAlloc<T, OsclMemAllocator>>  
OSCLMemAutoPtr< T, _Allocator >::OSCLMemAutoPtr (T * inPtr = 0) [inline,  
explicit]
```

Default constructor Initializes the pointer and takes ownership.

```
7.156.2.2 template<class T, class _Allocator = Oscl_TAlloc<T, OsclMemAllocator>>  
OSCLMemAutoPtr< T, _Allocator >::OSCLMemAutoPtr (const OSCLMemAutoPtr<  
T > & Y) [inline]
```

Copy constructor.

Initializes the pointer and takes ownership from another oscl\_auto\_ptr. Note that the other class does NOT own the pointer any longer, and hence it is NOT its responsibility to free it.

```
7.156.2.3 template<class T, class _Allocator = Oscl_TAlloc<T, OsclMemAllocator>>  
OSCLMemAutoPtr< T, _Allocator >::~OSCLMemAutoPtr () [inline]
```

Destructor.

The pointer is deleted in case this class still has ownership

### 7.156.3 Member Function Documentation

**7.156.3.1 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> void OSCLMemAutoPtr< T, \_Allocator >::allocate (oscl\_memsize\_t size) [inline]**

**7.156.3.2 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> void OSCLMemAutoPtr< T, \_Allocator >::deallocate (T \*ptr) [inline, static]**

**7.156.3.3 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> T\* OSCLMemAutoPtr< T, \_Allocator >::get () const [inline]**

[get\(\)](#) method returns the pointer, currently owned by the class.

**7.156.3.4 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> T& OSCLMemAutoPtr< T, \_Allocator >::operator \* () const [inline]**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the OSCLMemAutoPtr can be used like the regular pointer that it was initialized with.

**7.156.3.5 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> T\* OSCLMemAutoPtr< T, \_Allocator >::operator -> () const [inline]**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the OSCLMemAutoPtr can be used like the regular pointer that it was initialized with.

**7.156.3.6 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> OSCLMemAutoPtr< T, \_Allocator >& OSCLMemAutoPtr< T, \_Allocator >::operator=(const OSCLMemAutoPtr< T, \_Allocator > & \_Y) [inline]**

Assignment operator from an another oscl\_auto\_ptr.

**Parameters:**

*\_Y* The value parameter should be another oscl\_auto\_ptr

**Returns:**

Returns a reference to this oscl\_auto\_ptr instance with pointer initialized.

**Precondition:**

The input class should be non-null and should point to a valid pointer.

This assignment operator initializes the class to the contents of the oscl\_auto\_ptr given as the input parameter. The ownership of the pointer is transferred.

**7.156.3.7 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> T\* OSCLMemAutoPtr< T, \_Allocator >::release () const [inline]**

[release\(\)](#) method releases ownership of the pointer, currently owned by the class. It returns the pointer as well.

**7.156.3.8 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> void OSCLMemAutoPtr< T, \_Allocator >::setWithoutOwnership (T \*ptr) [inline]**

The takeOwnership function assigns the value with ownership.

**7.156.3.9 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> void OSCLMemAutoPtr< T, \_Allocator >::takeOwnership (T \*ptr) [inline]**

The takeOwnership function assigns the value with ownership.

#### **7.156.4 Field Documentation**

**7.156.4.1 template<class T, class \_Allocator = Oscl\_TAlloc<T, OsclMemAllocator>> bool OSCLMemAutoPtr< T, \_Allocator >::\_Ownership**


The documentation for this class was generated from the following file:

- [oscl\\_mem\\_auto\\_ptr.h](#)

## 7.157 OsclMemBasicAllocator Class Reference

```
#include <oscl_mem.h>
```

Inheritance diagram for OsclMemBasicAllocator::



### Public Methods

- [OsclAny \\* allocate \(const uint32 n\)](#)
- [void deallocate \(OsclAny \\*p\)](#)

#### 7.157.1 Detailed Description

A simple allocator class that does not use the memory management.

Note: this allocator is for internal use by Oscl only. Higher level code should use [OsclMemAllocator](#).

#### 7.157.2 Member Function Documentation

##### 7.157.2.1 [OsclAny\\* OsclMemBasicAllocator::allocate \(const uint32 n\) \[inline, virtual\]](#)

This API throws an exception when malloc returns NULL. n must be greater than 0.

###### Returns:

pointer (or Leave with OsclErrNoMemory )

Implements [Oscl\\_DefAlloc](#).

##### 7.157.2.2 [void OsclMemBasicAllocator::deallocate \(OsclAny \\*p\) \[inline, virtual\]](#)

Implements [Oscl\\_DefAlloc](#).


The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.158 OsclMemBasicAllocDestructDealloc< T > Class Template Reference

```
#include <oscl_mem.h>
```

Inheritance diagram for OsclMemBasicAllocDestructDealloc< T >::



### Public Methods

- [OsclAny \\* allocate \(const uint32 size\)](#)
- [void deallocate \(OsclAny \\*p\)](#)
- [void destruct\\_and\\_dealloc \(OsclAny \\*p\)](#)

#### 7.158.1 Detailed Description

**template<class T> class OsclMemBasicAllocDestructDealloc< T >**

An [OsclAllocDestructDealloc](#) class that uses [OsclMemBasicAllocator](#).

#### 7.158.2 Member Function Documentation

**7.158.2.1 template<class T> [OsclAny\\*](#) OsclMemBasicAllocDestructDealloc< T >::allocate (const uint32 size) [inline, virtual]**

Implements [Oscl\\_DefAlloc](#).

**7.158.2.2 template<class T> void OsclMemBasicAllocDestructDealloc< T >::deallocate ([OsclAny](#) \* p) [inline, virtual]**

Implements [Oscl\\_DefAlloc](#).

**7.158.2.3 template<class T> void OsclMemBasicAllocDestructDealloc< T >::destruct\_and\_dealloc ([OsclAny](#) \* p) [inline, virtual]**

Implements [OsclDestructDealloc](#).

The documentation for this class was generated from the following file:

- [oscl\\_mem.h](#)

## 7.159 OsclMemGlobalAuditObject Class Reference

```
#include <oscl_mem.h>
```

### Public Types

- `typedef OsclMemAudit audit_type`

### Static Public Methods

- `OSCL_IMPORT_REF audit_type * getGlobalMemAuditObject ()`

### Friends

- class `OsclMem`

### 7.159.1 Member Typedef Documentation

#### 7.159.1.1 `typedef OsclMemAudit OsclMemGlobalAuditObject::audit_type`

### 7.159.2 Member Function Documentation

#### 7.159.2.1 `OSCL_IMPORT_REF audit_type* OsclMemGlobalAuditObject::getGlobalMemAuditObject () [static]`

returns the global audit object. For use in macros only– not a public API.

### 7.159.3 Friends And Related Function Documentation

#### 7.159.3.1 `friend class OsclMem [friend]`


The documentation for this class was generated from the following file:

- `oscl_mem.h`

## 7.160 OsclMemoryFragment Struct Reference

```
#include <oscl_types.h>
```

Inheritance diagram for OsclMemoryFragment::



### Data Fields

- uint32 [len](#)
- void \* [ptr](#)

#### 7.160.1 Field Documentation

##### 7.160.1.1 uint32 OsclMemoryFragment::len

##### 7.160.1.2 void\* OsclMemoryFragment::ptr


The documentation for this struct was generated from the following file:

- [oscl\\_types.h](#)

## 7.161 OsclMemPoolFixedChunkAllocator Class Reference

```
#include <oscl_mem_mempool.h>
```

Inheritance diagram for OsclMemPoolFixedChunkAllocator::



### Public Methods

- OSCL\_IMPORT\_REF OsclMemPoolFixedChunkAllocator (const uint32 numchunk=1, const uint32 chunksze=0, Oscl\_DefAlloc \*gen\_alloc=NULL, const uint32 chunkalignment=0)
- virtual OSCL\_IMPORT\_REF void enablenullpointerreturn ()
- virtual ~OsclMemPoolFixedChunkAllocator ()
- virtual OSCL\_IMPORT\_REF OsclAny \* allocate (const uint32 n)
- virtual OSCL\_IMPORT\_REF void deallocate (OsclAny \*p)
- virtual OSCL\_IMPORT\_REF void notifyfreechunkavailable (OsclMemPoolFixedChunkAllocatorObserver &obs, OsclAny \*aContextData=NULL)
- virtual OSCL\_IMPORT\_REF void CancelFreeChunkAvailableCallback ()
- OSCL\_IMPORT\_REF void addRef ()
- OSCL\_IMPORT\_REF void removeRef ()

### Protected Methods

- virtual OSCL\_IMPORT\_REF void createmempool ()
- virtual OSCL\_IMPORT\_REF void destroymempool ()

### Protected Attributes

- uint32 iNumChunk
- uint32 iChunkSize
- uint32 iChunkSizeMemAligned
- uint32 iChunkAlignment
- Oscl\_DefAlloc \* iMemPoolAllocator
- OsclAny \* iMemPool
- OsclAny \* iMemPoolAligned
- Oscl\_Vector< OsclAny \*, OsclMemAllocator > iFreeMemChunkList
- bool iCheckNextAvailableFreeChunk
- OsclMemPoolFixedChunkAllocatorObserver \* iObserver
- OsclAny \* iNextAvailableContextData
- int32 iRefCount
- bool iEnableNullPtrReturn

### 7.161.1 Constructor & Destructor Documentation

**7.161.1.1 OSCL\_IMPORT\_REF OsclMemPoolFixedChunkAllocator::OsclMemPoolFixedChunkAllocator (const uint32 numchunk = 1, const uint32 chunkszie = 0, Oscl\_DefAlloc \* gen\_alloc = NULL, const uint32 chunkalignment = 0)**

This API throws an exception when the memory allocation for pool fails If numchunk and chunkszie parameters are not set, memory pool of 1 chunk will be created in the first call to allocate. The chunk size will be set to the n passed in for [allocate\(\)](#). If numchunk parameter is set to 0, the memory pool will use 1 for numchunk. If chunkalignment is set to 0, memory pool will use default allocator alignment (8-byte) If chunkalignment is > 0, memory pool will align all buffers in the mempool to the specified alignment. Alignment should be a power of 2

**Returns:**

void

**7.161.1.2 virtual OsclMemPoolFixedChunkAllocator::~OsclMemPoolFixedChunkAllocator () [inline, virtual]**

The destructor for the memory pool

### 7.161.2 Member Function Documentation

**7.161.2.1 OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::addRef ()**

Increments the reference count for this memory pool allocator

**Returns:**

void

**7.161.2.2 virtual OSCL\_IMPORT\_REF OsclAny\* OsclMemPoolFixedChunkAllocator::allocate (const uint32 n) [virtual]**

This API throws an exception when n is greater than the fixed chunk size or there are no free chunk available in the pool, if "enablenullpointerreturn" has not been called. If the memory pool hasn't been created yet, the pool will be created with chunk size equal to n so n must be greater than 0. Exception will be thrown if memory allocation for the memory pool fails.

**Returns:**

pointer to available chunk from memory pool

Implements [Oscl\\_DefAlloc](#).

**7.161.2.3 virtual OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::CancelFreeChunkAvailableCallback () [virtual]**

This API will cancel any past callback requests..

**Returns:**

void

**7.161.2.4 virtual OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::createmempool()** [protected, virtual]

**7.161.2.5 virtual OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::deallocate(  
OsclAny \*p)** [virtual]

This API throws an exception when the pointer p passed in is not part of the memory pool. Exception will be thrown if the memory pool is not set up yet.

**Returns:**

void

Implements [Oscl\\_DefAlloc](#).

**7.161.2.6 virtual OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::destroymempool()** [protected, virtual]

**7.161.2.7 virtual OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::enablenullpointerreturn()** [virtual]

This API will disable exceptions in case the memory pool runs out of memory Instead of doing "[OSCL\\_LEAVE\(OsclErrNoResources\)](#)" allocate API will return NULL.

**Returns:**

void

**7.161.2.8 virtual OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::notifyfreechunkavailable(  
OsclMemPoolFixedChunkAllocatorObserver &obs, OsclAny \*aContextData = NULL)** [virtual]

This API will set the flag to send a callback via specified observer object when the next memory chunk is deallocated by [deallocate\(\)](#) call..

**Returns:**

void

**7.161.2.9 OSCL\_IMPORT\_REF void OsclMemPoolFixedChunkAllocator::removeRef()**

Decrements the reference count for this memory pool allocator When the reference count goes to 0, this instance of the memory pool object is deleted

**Returns:**

void

### 7.161.3 Field Documentation

- 7.161.3.1 **bool OsclMemPoolFixedChunkAllocator::iCheckNextAvailableFreeChunk** [protected]
- 7.161.3.2 **uint32 OsclMemPoolFixedChunkAllocator::iChunkAlignment** [protected]
- 7.161.3.3 **uint32 OsclMemPoolFixedChunkAllocator::iChunkSize** [protected]
- 7.161.3.4 **uint32 OsclMemPoolFixedChunkAllocator::iChunkSizeMemAligned** [protected]
- 7.161.3.5 **bool OsclMemPoolFixedChunkAllocator::iEnableNullPtrReturn** [protected]
- 7.161.3.6 **Oscl\_Vector<OsclAny\*, OsclMemAllocator> OsclMemPoolFixedChunkAllocator::iFreeMemChunkList** [protected]
- 7.161.3.7 **OsclAny\* OsclMemPoolFixedChunkAllocator::iMemPool** [protected]
- 7.161.3.8 **OsclAny\* OsclMemPoolFixedChunkAllocator::iMemPoolAligned** [protected]
- 7.161.3.9 **Oscl\_DefAlloc\* OsclMemPoolFixedChunkAllocator::iMemPoolAllocator** [protected]
- 7.161.3.10 **OsclAny\* OsclMemPoolFixedChunkAllocator::iNextAvailableContextData** [protected]
- 7.161.3.11 **uint32 OsclMemPoolFixedChunkAllocator::iNumChunk** [protected]
- 7.161.3.12 **OsclMemPoolFixedChunkAllocatorObserver\* OsclMemPoolFixedChunkAllocator::iObserver** [protected]
- 7.161.3.13 **int32 OsclMemPoolFixedChunkAllocator::iRefCount** [protected]

The documentation for this class was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.162 OsclMemPoolFixedChunkAllocatorObserver Class Reference

```
#include <oscl_mem_mempool.h>
```

### Public Methods

- virtual void [freechunkavailable \(OsclAny \\*aContextData\)=0](#)
- virtual [~OsclMemPoolFixedChunkAllocatorObserver \(\)](#)

#### 7.162.1 Constructor & Destructor Documentation

**7.162.1.1** virtual [OsclMemPoolFixedChunkAllocatorObserver::~OsclMemPoolFixedChunkAllocatorObserver \(\) \[inline, virtual\]](#)

#### 7.162.2 Member Function Documentation

**7.162.2.1** virtual void [OsclMemPoolFixedChunkAllocatorObserver::freechunkavailable \(OsclAny \\* aContextData\) \[pure virtual\]](#)


The documentation for this class was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.163 OsclMemPoolResizableAllocator Class Reference

```
#include <oscl_mem_mempool.h>
```

Inheritance diagram for OsclMemPoolResizableAllocator::



### Public Methods

- OSCL\_IMPORT\_REF [OsclMemPoolResizableAllocator](#) (uint32 aMemPoolBufferSize, uint32 aMemPoolBufferNumLimit=0, uint32 aExpectedNumBlocksPerBuffer=0, [Oscl\\_DefAlloc](#) \*gen\_alloc=NULL)
- virtual OSCL\_IMPORT\_REF void [enablenullpointerreturn](#) ()
- virtual OSCL\_IMPORT\_REF [OsclAny](#) \* [allocate](#) (const uint32 aNumBytes)
- virtual OSCL\_IMPORT\_REF void [deallocate](#) ([OsclAny](#) \*aPtr)
- virtual OSCL\_IMPORT\_REF bool [trim](#) ([OsclAny](#) \*aPtr, uint32 aBytesToFree)
- OSCL\_IMPORT\_REF uint32 [getBufferSize](#) () const
- virtual OSCL\_IMPORT\_REF uint32 [getAllocatedSize](#) () const
- virtual OSCL\_IMPORT\_REF uint32 [getAvailableSize](#) () const
- virtual OSCL\_IMPORT\_REF uint32 [getLargestContiguousFreeBlockSize](#) () const
- virtual OSCL\_IMPORT\_REF bool [setMaxSzForNewMemPoolBuffer](#) (uint32 aMaxNewMemPoolBufferSz)
- virtual OSCL\_IMPORT\_REF void [notifyfreeblockavailable](#) ([OsclMemPoolResizableAllocatorObserver](#) &aObserver, uint32 aRequestedSize=0, [OsclAny](#) \*aContextData=NULL)
- virtual OSCL\_IMPORT\_REF void [CancelFreeChunkAvailableCallback](#) ()
- virtual OSCL\_IMPORT\_REF void [notifyfreememoryavailable](#) ([OsclMemPoolResizableAllocatorMemoryObserver](#) &aObserver, uint32 aRequestedSize=0, [OsclAny](#) \*aContextData=NULL)
- OSCL\_IMPORT\_REF void [CancelFreeMemoryAvailableCallback](#) ()
- OSCL\_IMPORT\_REF void [addRef](#) ()
- OSCL\_IMPORT\_REF void [removeRef](#) ()

### Protected Methods

- virtual ~[OsclMemPoolResizableAllocator](#) ()
- [MemPoolBufferInfo](#) \* [addnewmempoolbuffer](#) (uint32 aBufferSize)
- void [destroyallmempoolbuffers](#) ()
- [MemPoolBlockInfo](#) \* [findfreeblock](#) (uint32 aBlockSize)
- [OsclAny](#) \* [allocateblock](#) ([MemPoolBlockInfo](#) &aBlockPtr, uint32 aNumBytes)
- void [deallocateblock](#) ([MemPoolBlockInfo](#) &aBlockPtr)
- bool [validateblock](#) ([OsclAny](#) \*aBlockBufPtr)
- uint32 [getMemPoolBufferSize](#) ([MemPoolBufferInfo](#) \*aBufferInfo) const
- uint32 [getMemPoolBufferAllocatedSize](#) ([MemPoolBufferInfo](#) \*aBufferInfo) const
- uint32 [memoryPoolBufferMgmtOverhead](#) () const

## Protected Attributes

- uint32 `iMemPoolBufferSize`
- uint32 `iMemPoolBufferNumLimit`
- uint32 `iExpectedNumBlocksPerBuffer`
- uint32 `iMaxNewMemPoolBufferSz`
- `Oscl_DefAlloc * iMemPoolBufferAllocator`
- `Oscl_Vector< MemPoolBufferInfo *, OsclMemAllocator > iMemPoolBufferList`
- uint32 `iBufferInfoAlignedSize`
- uint32 `iBlockInfoAlignedSize`
- bool `iCheckNextAvailable`
- uint32 `iRequestedNextAvailableSize`
- `OsclAny * iNextAvailableContextData`
- `OsclMemPoolResizableAllocatorObserver * iObserver`
- bool `iCheckFreeMemoryAvailable`
- uint32 `iRequestedAvailableFreeMemSize`
- `OsclAny * iFreeMemContextData`
- `OsclMemPoolResizableAllocatorMemoryObserver * iFreeMemPoolObserver`
- int32 `iRefCount`
- bool `iEnableNullPtrReturn`

### 7.163.1 Constructor & Destructor Documentation

**7.163.1.1 OSCL\_IMPORT\_REF OsclMemPoolResizableAllocator::OsclMemPoolResizableAllocator (uint32 *aMemPoolBufferSize*, uint32 *aMemPoolBufferNumLimit* = 0, uint32 *aExpectedNumBlocksPerBuffer* = 0, `Oscl_DefAlloc * gen_alloc` = NULL)**

Create the memory pool allocator with resizing functionality. The size of the memory pool buffer needs to be passed-in. The maximum number of memory pool buffers, expected number of blocks in a memory pool buffer, and outside allocator are optional. This API throws an exception when the memory allocation for the pool buffer fails. If memory pool buffer number limit parameter is not set, the assumption is that there is no limit and memory pool will grow as needed. If the expected number of blocks is not set or not known, the memory pool will use a default value to 10 to allocate extra memory for the block info header.

**Returns:**

`void`

**7.163.1.2 virtual OsclMemPoolResizableAllocator::~OsclMemPoolResizableAllocator () [inline, protected, virtual]**

The destructor for the memory pool. Should not be called directly. Use `removeRef()` instead.

### 7.163.2 Member Function Documentation

**7.163.2.1 `MemPoolBufferInfo* OsclMemPoolResizableAllocator::addnewmempoolbuffer (uint32 aBufferSize)` [protected]**

**7.163.2.2 OSCL\_IMPORT\_REF void OsclMemPoolResizableAllocator::addRef ()**

Increments the reference count for this memory pool allocator

**Returns:**

void

**7.163.2.3 virtual OSCL\_IMPORT\_REF [OsclAny](#)\* OsclMemPoolResizableAllocator::allocate  
(const uint32 aNumBytes) [virtual]**

Allocates a block from the memory pool that is at least in size requested This API throws an exception if there isn't enough memory (if "enablenullpointerreturn" has not been called) for the requested amount in the pool or if the extra pool buffer cannot be allocated.

**Returns:**

Pointer to memory buffer from memory pool

Implements [Oscl\\_DefAlloc](#).

**7.163.2.4 [OsclAny](#)\* OsclMemPoolResizableAllocator::allocateblock ([MemPoolBlockInfo](#) &  
aBlockPtr, uint32 aNumBytes) [protected]****7.163.2.5 virtual OSCL\_IMPORT\_REF void OsclMemPoolResizableAllocator::CancelFree-  
ChunkAvailableCallback () [virtual]**

This API will cancel any past callback requests..

**Returns:**

void

**7.163.2.6 OSCL\_IMPORT\_REF void OsclMemPoolResizableAllocator::CancelFreeMemory-  
AvailableCallback ()****7.163.2.7 virtual OSCL\_IMPORT\_REF void OsclMemPoolResizableAllocator::deallocate  
([OsclAny](#) \* aPtr) [virtual]**

Deallocates and returns a block back to the memory pool This API throws an exception if the pointer passed in is not part of the memory pool, aligned, or has corrupted block header.

**Returns:**

void

Implements [Oscl\\_DefAlloc](#).

**7.163.2.8 void OsclMemPoolResizableAllocator::deallocateblock ([MemPoolBlockInfo](#) &  
aBlockPtr) [protected]****7.163.2.9 void OsclMemPoolResizableAllocator::destroyallmempoolbuffers () [protected]****7.163.2.10 virtual OSCL\_IMPORT\_REF void OsclMemPoolResizable-  
Allocator::enablenullpointerreturn () [virtual]**

This API will disable exceptions in case the memory pool runs out of memory Instead of doing "[OSCL\\_LEAVE\(OsclErrNoResources\)](#)" allocate API will return NULL.

**Returns:**

void

**7.163.2.11** **MemPoolBlockInfo\*** OsclMemPoolResizableAllocator::findfreeblock (**uint32 aBlockSize**) [protected]

**7.163.2.12** **virtual OSCL\_IMPORT\_REF uint32 OsclMemPoolResizableAllocator::getAllocatedSize ()** [virtual]

Returns the number of bytes allocated from the buffer<including the overhead bytes that may be allocated by the allocator to keep track of the chunks allocated>

**7.163.2.13** **virtual OSCL\_IMPORT\_REF uint32 OsclMemPoolResizableAllocator::getAvailableSize ()** [virtual]

Returns the number of bytes available with the buffer

**7.163.2.14** **OSCL\_IMPORT\_REF uint32 OsclMemPoolResizableAllocator::getBufferSize ()**

Returns the size of the buffer <including the overhead bytes that may be allocated by the allocator>

**7.163.2.15** **virtual OSCL\_IMPORT\_REF uint32 OsclMemPoolResizableAllocator::getLargestContiguousFreeBlockSize ()** [virtual]

Returns the size of the largest available chunk in the memory.

**7.163.2.16** **uint32 OsclMemPoolResizableAllocator::getMemPoolBufferAllocatedSize (MemPoolBufferInfo \* aBufferInfo) const** [protected]

**7.163.2.17** **uint32 OsclMemPoolResizableAllocator::getMemPoolBufferSize (MemPoolBufferInfo \* aBufferInfo) const** [protected]

**7.163.2.18** **uint32 OsclMemPoolResizableAllocator::memoryPoolBufferMgmtOverhead ()** [protected]

**7.163.2.19** **virtual OSCL\_IMPORT\_REF void OsclMemPoolResizableAllocator::notifyfreeblockavailable (OsclMemPoolResizableAllocatorObserver & aObserver, uint32 aRequestedSize = 0, OsclAny \* aContextData = NULL)** [virtual]

This API will set the flag to send a callback via specified observer object when the next memory block is deallocated by [deallocate\(\)](#) call. If the optional requested size parameter is set, the callback is sent when a free memory space of requested size becomes available. The optional context data is returned with the callback and can be used by the user to differentiate between different instances of memory pool objects. This memory pool only allows one notify to be queued. Another call to this function will just overwrite the previous call.

**Returns:**

void

**7.163.2.20** `virtual OSCL_IMPORT_REF void OsclMemPoolResizableAllocator::notifyfreememoryavailable (OsclMemPoolResizableAllocatorMemoryObserver & aObserver, uint32 aRequestedSize = 0, OsclAny * aContextData = NULL)`  
[virtual]

**7.163.2.21** `OSCL_IMPORT_REF void OsclMemPoolResizableAllocator::removeRef ()`

Decrements the reference count for this memory pool allocator When the reference count goes to 0, this instance of the memory pool object is deleted

**Returns:**

`void`

**7.163.2.22** `virtual OSCL_IMPORT_REF bool OsclMemPoolResizableAllocator::setMaxSzForNewMemPoolBuffer (uint32 aMaxNewMemPoolBufferSz)`  
[virtual]

**7.163.2.23** `virtual OSCL_IMPORT_REF bool OsclMemPoolResizableAllocator::trim (OsclAny * aPtr, uint32 aBytesToFree)` [virtual]

Returns a tail segment of a previously allocated memory block back to the memory pool. The passed-in pointer to the memory buffer is still valid after the call completes but the buffer size is smaller by by specified amount that was freed. This function allows the user to allocate a larger size block initially when the amount needed is unknown and then return the unused portion of the block when the amount becomes known. This API throws an exception if the pointer passed in is not part of the memory pool or the size to return is bigger than the size of the passed-in block. Exception will be thrown if the memory pool is not set up yet.

**Returns:**

`bool` True if trim operation successful. False if the block wasn't trimmed

7.163.2.24 **bool OsclMemPoolResizableAllocator::validateblock ([OsclAny](#) \* *aBlockBufPtr*)** [protected]

### 7.163.3 Field Documentation

7.163.3.1 **uint32 OsclMemPoolResizableAllocator::iBlockInfoAlignedSize** [protected]

7.163.3.2 **uint32 OsclMemPoolResizableAllocator::iBufferInfoAlignedSize** [protected]

7.163.3.3 **bool OsclMemPoolResizableAllocator::iCheckFreeMemoryAvailable** [protected]

7.163.3.4 **bool OsclMemPoolResizableAllocator::iCheckNextAvailable** [protected]

7.163.3.5 **bool OsclMemPoolResizableAllocator::iEnableNullPtrReturn** [protected]

7.163.3.6 **uint32 OsclMemPoolResizableAllocator::iExpectedNumBlocksPerBuffer** [protected]

7.163.3.7 **[OsclAny](#)\* OsclMemPoolResizableAllocator::iFreeMemContextData** [protected]

7.163.3.8 **[OsclMemPoolResizableAllocatorMemoryObserver](#)\* OsclMemPoolResizableAllocator::iFreeMemPoolObserver** [protected]

7.163.3.9 **uint32 OsclMemPoolResizableAllocator::iMaxNewMemPoolBufferSz** [protected]

7.163.3.10 **[Oscl\\_DefAlloc](#)\* OsclMemPoolResizableAllocator::iMemPoolBufferAllocator** [protected]

7.163.3.11 **[Oscl\\_Vector](#)<[MemPoolBufferInfo](#)\*, [OsclMemAllocator](#)> OsclMemPoolResizableAllocator::iMemPoolBufferList** [protected]

7.163.3.12 **uint32 OsclMemPoolResizableAllocator::iMemPoolBufferNumLimit** [protected]

7.163.3.13 **uint32 OsclMemPoolResizableAllocator::iMemPoolBufferSize** [protected]

7.163.3.14 **[OsclAny](#)\* OsclMemPoolResizableAllocator::iNextAvailableContextData** [protected]

7.163.3.15 **[OsclMemPoolResizableAllocatorObserver](#)\* OsclMemPoolResizableAllocator::iObserver** [protected]

7.163.3.16 **int32 OsclMemPoolResizableAllocator::iRefCount** [protected]

7.163.3.17 **uint32 OsclMemPoolResizableAllocator::iRequestedAvailableFreeMemSize** [protected]

7.163.3.18 **uint32 OsclMemPoolResizableAllocator::iRequestedNextAvailableSize** [protected]

The documentation for this class was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.164 OsclMemPoolResizableAllocator::MemPoolBlockInfo Struct Reference

```
#include <oscl_mem_mempool.h>
```

### Data Fields

- uint32 iBlockPreFence
- MemPoolBlockInfo \* iNextFreeBlock
- MemPoolBlockInfo \* iPrevFreeBlock
- uint32 iBlockSize
- uint8 \* iBlockBuffer
- MemPoolBufferInfo \* iParentBuffer
- uint32 iBlockPostFence

#### 7.164.1 Field Documentation

7.164.1.1 uint8\* OsclMemPoolResizableAllocator::MemPoolBlockInfo::iBlockBuffer

7.164.1.2 uint32 OsclMemPoolResizableAllocator::MemPoolBlockInfo::iBlockPostFence

7.164.1.3 uint32 OsclMemPoolResizableAllocator::MemPoolBlockInfo::iBlockPreFence

7.164.1.4 uint32 OsclMemPoolResizableAllocator::MemPoolBlockInfo::iBlockSize

7.164.1.5 MemPoolBlockInfo\* OsclMemPoolResizableAllocator::MemPoolBlockInfo::iNextFree-Block

7.164.1.6 MemPoolBufferInfo\* OsclMemPoolResizableAllocator::MemPoolBlockInfo::iParent-Buffer

7.164.1.7 MemPoolBlockInfo\* OsclMemPoolResizableAllocator::MemPoolBlockInfo::iPrevFree-Block

The documentation for this struct was generated from the following file:

- oscl\_mem\_mempool.h

## 7.165 OsclMemPoolResizableAllocator::MemPoolBufferInfo Struct Reference

```
#include <oscl_mem_mempool.h>
```

### Data Fields

- uint32 iBufferPreFence
- [OsclAny](#) \* iStartAddr
- [OsclAny](#) \* iEndAddr
- uint32 iBufferSize
- uint32 iNumOutstanding
- [MemPoolBlockInfo](#) \* iNextFreeBlock
- uint32 iAllocatedSz
- uint32 iBufferPostFence

#### 7.165.1 Field Documentation

**7.165.1.1 uint32 OsclMemPoolResizableAllocator::MemPoolBufferInfo::iAllocatedSz**

**7.165.1.2 uint32 OsclMemPoolResizableAllocator::MemPoolBufferInfo::iBufferPostFence**

**7.165.1.3 uint32 OsclMemPoolResizableAllocator::MemPoolBufferInfo::iBufferPreFence**

**7.165.1.4 uint32 OsclMemPoolResizableAllocator::MemPoolBufferInfo::iBufferSize**

**7.165.1.5 [OsclAny](#)\* OsclMemPoolResizableAllocator::MemPoolBufferInfo::iEndAddr**

**7.165.1.6 [MemPoolBlockInfo](#)\* OsclMemPoolResizableAllocator::MemPoolBufferInfo::iNextFree-Block**

**7.165.1.7 uint32 OsclMemPoolResizableAllocator::MemPoolBufferInfo::iNumOutstanding**

**7.165.1.8 [OsclAny](#)\* OsclMemPoolResizableAllocator::MemPoolBufferInfo::iStartAddr**

The documentation for this struct was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.166 OsclMemPoolResizableAllocatorMemoryObserver Class Reference

```
#include <oscl_mem_mempool.h>
```

### Public Methods

- virtual void [freememoryavailable \(OsclAny \\*aContextData\)=0](#)
- virtual [~OsclMemPoolResizableAllocatorMemoryObserver \(\)](#)

#### 7.166.1 Constructor & Destructor Documentation

**7.166.1.1 virtual OsclMemPoolResizableAllocatorMemoryObserver::~OsclMemPoolResizableAllocatorMemoryObserver () [inline, virtual]**

#### 7.166.2 Member Function Documentation

**7.166.2.1 virtual void OsclMemPoolResizableAllocatorMemoryObserver::freememoryavailable (OsclAny \* aContextData) [pure virtual]**

The documentation for this class was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.167 OsclMemPoolResizableAllocatorObserver Class Reference

```
#include <oscl_mem_mempool.h>
```

### Public Methods

- virtual void [freeblockavailable \(OsclAny \\*aContextData\)=0](#)
- virtual [~OsclMemPoolResizableAllocatorObserver \(\)](#)

#### 7.167.1 Constructor & Destructor Documentation

**7.167.1.1** [virtual OsclMemPoolResizableAllocatorObserver::~OsclMemPoolResizableAllocatorObserver \(\) \[inline, virtual\]](#)

#### 7.167.2 Member Function Documentation

**7.167.2.1** [virtual void OsclMemPoolResizableAllocatorObserver::freeblockavailable \(OsclAny \\*\*aContextData\*\) \[pure virtual\]](#)

The documentation for this class was generated from the following file:

- [oscl\\_mem\\_mempool.h](#)

## 7.168 OsclMemStatsNode Class Reference

```
#include <oscl_mem_audit.h>
```

### Public Methods

- [OsclMemStatsNode \(\)](#)
- [void reset \(\)](#)
- [~OsclMemStatsNode \(\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size\)](#)
- [void \\* operator new \(oscl\\_memsize\\_t size, OsclMemStatsNode \\*ptr\)](#)
- [void operator delete \(void \\*ptr\) throw \(\)](#)

### Data Fields

- [MM\\_Stats\\_t \\* pMMStats](#)
- [MM\\_FailInsertParam \\* pMMFIParam](#)
- [char \\* tag](#)

#### 7.168.1 Constructor & Destructor Documentation

**7.168.1.1 OsclMemStatsNode::OsclMemStatsNode () [inline]**

**7.168.1.2 OsclMemStatsNode::~OsclMemStatsNode () [inline]**

#### 7.168.2 Member Function Documentation

**7.168.2.1 void OsclMemStatsNode::operator delete (void \*ptr) throw () [inline]**

**7.168.2.2 void\* OsclMemStatsNode::operator new (oscl\_memsize\_t size, OsclMemStatsNode \*ptr) [inline]**

**7.168.2.3 void\* OsclMemStatsNode::operator new (oscl\_memsize\_t size) [inline]**

**7.168.2.4 void OsclMemStatsNode::reset () [inline]**

#### 7.168.3 Field Documentation

**7.168.3.1 MM\_FailInsertParam\* OsclMemStatsNode::pMMFIParam**

**7.168.3.2 MM\_Stats\_t\* OsclMemStatsNode::pMMStats**

**7.168.3.3 char\* OsclMemStatsNode::tag**


The documentation for this class was generated from the following file:

- [oscl\\_mem\\_audit.h](#)

## 7.169 OsclMutex Class Reference

```
#include <oscl_mutex.h>
```

Inheritance diagram for OsclMutex::



### Public Methods

- OSCL\_IMPORT\_REF OsclMutex ()
- virtual OSCL\_IMPORT\_REF ~OsclMutex ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Create (void)
- OSCL\_IMPORT\_REF void Lock ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError TryLock ()
- OSCL\_IMPORT\_REF void Unlock ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Close (void)

#### 7.169.1 Detailed Description

Class OsclMutex

#### 7.169.2 Constructor & Destructor Documentation

##### 7.169.2.1 OSCL\_IMPORT\_REF OsclMutex::OsclMutex ()

Class constructor

##### 7.169.2.2 virtual OSCL\_IMPORT\_REF OsclMutex::~OsclMutex () [virtual]

Class destructor

#### 7.169.3 Member Function Documentation

##### 7.169.3.1 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclMutex::Close (void)

Closes the Mutex

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns the Error whether it is success or failure. Incase of failure it will return what is the specific error

**7.169.3.2 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclMutex::Create (void)**

Creates the Mutex

**Parameters:**

*No* input arguments

**Returns:**

Returns the Error whether it is success or failure. Incase of failure it will return what is the specific error

**7.169.3.3 OSCL\_IMPORT\_REF void OsclMutex::Lock () [virtual]**

Locks the Mutex

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns nothing

Implements [OsclLockBase](#).

**7.169.3.4 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclMutex::TryLock ()**

Try to lock the mutex,if the Mutex is already locked calling thread immediately returns with out blocking

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns SUCCESS\_ERROR if the mutex was acquired, MUTEX\_LOCKED\_ERROR if the mutex cannot be acquired without waiting, or an error code if the operation failed. Note: this function may not be supported on all platforms, and may return NOT\_IMPLEMENTED.

**7.169.3.5 OSCL\_IMPORT\_REF void OsclMutex::Unlock () [virtual]**

Releases the Mutex

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns nothing

Implements [OsclLockBase](#).

The documentation for this class was generated from the following file:

- [oscl\\_mutex.h](#)

## 7.170 OsclNameString< \_\_len > Class Template Reference

```
#include <oscl_namestring.h>
```

### Public Methods

- [OsclNameString \(\)](#)
- [OsclNameString \(const char a\[ \]\)](#)
- [OsclNameString \(uint8 \\*a\)](#)
- void [Set \(uint8 \\*a\)](#)
- void [Set \(const char a\[ \]\)](#)
- uint8 \* [Str \(\) const](#)
- int32 [MaxLen \(\) const](#)

### 7.170.1 Detailed Description

```
template<int __len> class OsclNameString< __len >
```

Name string class appropriate for passing short constant ASCII strings around. All strings are automatically truncated and null-terminated.

### 7.170.2 Constructor & Destructor Documentation

**7.170.2.1 template<int \_\_len> OsclNameString< \_\_len >::OsclNameString () [inline]**

**7.170.2.2 template<int \_\_len> OsclNameString< \_\_len >::OsclNameString (const char a[ ]) [inline]**

**7.170.2.3 template<int \_\_len> OsclNameString< \_\_len >::OsclNameString (uint8 \* a) [inline]**

### 7.170.3 Member Function Documentation

**7.170.3.1 template<int \_\_len> int32 OsclNameString< \_\_len >::MaxLen () const [inline]**

**7.170.3.2 template<int \_\_len> void OsclNameString< \_\_len >::Set (const char a[ ]) [inline]**

**7.170.3.3 template<int \_\_len> void OsclNameString< \_\_len >::Set (uint8 \* a) [inline]**

Set the string to the input value. The string will be truncated to fit the storage class and automatically null-terminated.

#### Parameters:

*a* (input param): null-terminated character string.

**7.170.3.4 template<int \_\_len> uint8\* OsclNameString< \_\_len >::Str () const [inline]**


The documentation for this class was generated from the following file:

- [oscl\\_namestring.h](#)

## 7.171 OsclNativeFile Class Reference

```
#include <oscl_file_native.h>
```

Inheritance diagram for OsclNativeFile::



### Public Methods

- [OsclNativeFile \(\)](#)
- [~OsclNativeFile \(\)](#)
- [int32 Open \(const OsclFileHandle &, uint32 mode, const OsclNativeFileParams &params, Oscl\\_FileServer &fileserv\)](#)
- [int32 Open \(const oscl\\_wchar \\*filename, uint32 mode, const OsclNativeFileParams &params, Oscl\\_FileServer &fileserv\)](#)
- [int32 Open \(const char \\*filename, uint32 mode, const OsclNativeFileParams &params, Oscl\\_FileServer &fileserv\)](#)
- [uint32 Read \(OsclAny \\*buffer, uint32 size, uint32 numelements\)](#)
- [uint32 Write \(const OsclAny \\*buffer, uint32 size, uint32 numelements\)](#)
- [int32 Seek \(TOsclFileOffset offset, Oscl\\_File::seek\\_type origin\)](#)
- [TOsclFileOffset Tell \(\)](#)
- [int32 Flush \(\)](#)
- [int32 EndOfFile \(\)](#)
- [TOsclFileOffset Size \(\)](#)
- [int32 Close \(\)](#)
- [int32 SetSize \(uint32 size\)](#)
- [uint32 Mode \(\)](#)
- [int32 GetError \(\)](#)
- [int32 ReadAsync \(OsclAny \\*buffer, uint32 size, uint32 numelements, OsclAOStatus &status\)](#)
- [uint32 GetReadAsyncNumElements \(\)](#)
- [bool HasAsyncRead \(\)](#)
- [void ReadAsyncCancel \(\)](#)

### 7.171.1 Constructor & Destructor Documentation

**7.171.1.1 OsclNativeFile::OsclNativeFile ()**

**7.171.1.2 OsclNativeFile::~OsclNativeFile ()**

### 7.171.2 Member Function Documentation

**7.171.2.1 int32 OsclNativeFile::Close ()**

**7.171.2.2 int32 OsclNativeFile::EndOfFile ()**

**7.171.2.3 int32 OsclNativeFile::Flush ()**

**7.171.2.4 int32 OsclNativeFile::GetError ()**

**7.171.2.5 uint32 OsclNativeFile::GetReadAsyncNumElements ()**

Get the number of elements read in the last call to ReadAsync. @returns: number of elements read.

**7.171.2.6 bool OsclNativeFile::HasAsyncRead ()**

@returns: true if async read is supported natively.

**7.171.2.7 uint32 OsclNativeFile::Mode () [inline]**

**7.171.2.8 int32 OsclNativeFile::Open (const char \*filename, uint32 mode, const OsclNativeFileParams &params, Oscl\_FileServer &fileserv)**

**7.171.2.9 int32 OsclNativeFile::Open (const oscl\_wchar \*filename, uint32 mode, const OsclNativeFileParams &params, Oscl\_FileServer &fileserv)**

**7.171.2.10 int32 OsclNativeFile::Open (const OsclFileHandle &, uint32 mode, const OsclNativeFileParams &params, Oscl\_FileServer &fileserv)**

**7.171.2.11 uint32 OsclNativeFile::Read (OsclAny \*buffer, uint32 size, uint32 numelements)**

**7.171.2.12 int32 OsclNativeFile::ReadAsync (OsclAny \*buffer, uint32 size, uint32 numelements, OsclAOStatus &status)**

Asynchronous read.

#### Parameters:

**buffer:** data buffer, must be at least size\*numelements bytes

**size:** size of elements

**numelements:** number of elements to read

**status:** Request status for asynchronous completion @returns: 0 for success.

**7.171.2.13 void OsclNativeFile::ReadAsyncCancel ()**

Cancel any pending async read.

**7.171.2.14 int32 OsclNativeFile::Seek ([TOsclFileOffset offset](#), [Oscl\\_File::seek\\_type origin](#))****7.171.2.15 int32 OsclNativeFile::SetSize (uint32 *size*)****7.171.2.16 [TOsclFileOffset](#) OsclNativeFile::Size ()****7.171.2.17 [TOsclFileOffset](#) OsclNativeFile::Tell ()****7.171.2.18 uint32 OsclNativeFile::Write (const [OsclAny](#) \* *buffer*, uint32 *size*, uint32 *numelements*)**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_native.h](#)

## 7.172 OsclNativeFileParams Class Reference

```
#include <oscl_file_types.h>
```

### Public Methods

- [OsclNativeFileParams \(uint32 mode=0, uint32 bufsize=0, uint32 asyncsize=0\)](#)

### Data Fields

- uint32 [iNativeAccessMode](#)
- uint32 [iNativeBufferSize](#)
- uint32 [iAsyncReadBufferSize](#)

#### 7.172.1 Constructor & Destructor Documentation

7.172.1.1 **OsclNativeFileParams::OsclNativeFileParams (uint32 mode = 0, uint32 bufsize = 0, uint32 asyncsize = 0) [inline]**

#### 7.172.2 Field Documentation

7.172.2.1 **uint32 OsclNativeFileParams::iAsyncReadBufferSize**

7.172.2.2 **uint32 OsclNativeFileParams::iNativeAccessMode**

7.172.2.3 **uint32 OsclNativeFileParams::iNativeBufferSize**

The documentation for this class was generated from the following file:

- [oscl\\_file\\_types.h](#)

## 7.173 OsclNetworkAddress Class Reference

```
#include <oscl_socket_types.h>
```

### Public Methods

- [OsclNetworkAddress \(\)](#)
- [OsclNetworkAddress \(const char \\*addr, int p\)](#)
- [bool operator== \(const OsclNetworkAddress &rhs\) const](#)

### Data Fields

- [OsclNameString< PVNETWORKADDRESS\\_LEN > ipAddr](#)
- [int port](#)

#### 7.173.1 Constructor & Destructor Documentation

7.173.1.1 [OsclNetworkAddress::OsclNetworkAddress \(\) \[inline\]](#)

7.173.1.2 [OsclNetworkAddress::OsclNetworkAddress \(const char \\*addr, int p\) \[inline\]](#)

#### 7.173.2 Member Function Documentation

7.173.2.1 [bool OsclNetworkAddress::operator== \(const OsclNetworkAddress & rhs\) const \[inline\]](#)

#### 7.173.3 Field Documentation

7.173.3.1 [OsclNameString<PVNETWORKADDRESS\\_LEN> OsclNetworkAddress::ipAddr](#)

7.173.3.2 [int OsclNetworkAddress::port](#)


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_types.h](#)

## 7.174 OsclNullLock Class Reference

```
#include <oscl_lock_base.h>
```

Inheritance diagram for OsclNullLock::



### Public Methods

- virtual void [Lock \(\)](#)
- virtual void [Unlock \(\)](#)
- virtual [~OsclNullLock \(\)](#)

#### 7.174.1 Constructor & Destructor Documentation

**7.174.1.1 virtual OsclNullLock::~OsclNullLock () [inline, virtual]**

#### 7.174.2 Member Function Documentation

**7.174.2.1 virtual void OsclNullLock::Lock () [inline, virtual]**

Implements [OsclLockBase](#).

**7.174.2.2 virtual void OsclNullLock::Unlock () [inline, virtual]**

Implements [OsclLockBase](#).


The documentation for this class was generated from the following file:

- [oscl\\_lock\\_base.h](#)

## 7.175 OsclPriorityLink Class Reference

```
#include <oscl_double_list.h>
```

Inheritance diagram for OsclPriorityLink::



### Data Fields

- int32 [iPriority](#)

#### 7.175.1 Field Documentation

##### 7.175.1.1 int32 OsclPriorityLink::iPriority


The documentation for this class was generated from the following file:

- [oscl\\_double\\_list.h](#)

## 7.176 OsclPriorityList< T > Class Template Reference

```
#include <oscl_double_list.h>
```

Inheritance diagram for OsclPriorityList< T >::



### Public Methods

- OSCL\_INLINE OsclPriorityList ()
- OSCL\_INLINE OsclPriorityList (int32 anOffset)
- OSCL\_INLINE void Insert (T &aRef)
- OSCL\_INLINE bool IsHead (const T \*aPtr) const
- OSCL\_INLINE bool IsTail (const T \*aPtr) const
- OSCL\_INLINE T \* Head () const
- OSCL\_INLINE T \* Tail () const

```
template<class T> class OsclPriorityList< T >
```

#### 7.176.1 Constructor & Destructor Documentation

**7.176.1.1 template<class T> OSCL\_INLINE OsclPriorityList< T >::OsclPriorityList ()**

**7.176.1.2 template<class T> OSCL\_INLINE OsclPriorityList< T >::OsclPriorityList (int32 *anOffset*)**

#### 7.176.2 Member Function Documentation

**7.176.2.1 template<class T> OSCL\_INLINE T\* OsclPriorityList< T >::Head ()**

**7.176.2.2 template<class T> OSCL\_INLINE void OsclPriorityList< T >::Insert (T &*aRef*)**

**7.176.2.3 template<class T> OSCL\_INLINE bool OsclPriorityList< T >::IsHead (const T \**aPtr*) const**

**7.176.2.4 template<class T> OSCL\_INLINE bool OsclPriorityList< T >::IsTail (const T \**aPtr*) const**

**7.176.2.5 template<class T> OSCL\_INLINE T\* OsclPriorityList< T >::Tail ()**


The documentation for this class was generated from the following file:

- [oscl\\_double\\_list.h](#)

## 7.177 OsclPriorityQueue< Qelem, Alloc, Container, Compare > Class Template Reference

```
#include <oscl_priqueue.h>
```

Inheritance diagram for OsclPriorityQueue< Qelem, Alloc, Container, Compare >::



### Public Types

- `typedef Container::value_type value_type`
- `typedef Container container_type`
- `typedef Container::iterator iterator`
- `typedef Container::const_reference const_reference`

### Public Methods

- `bool empty () const`
- `uint32 size () const`
- `void reserve (uint32 n)`
- `const_reference top () const`
- `const Container & vec ()`
- `void push (const value_type &input)`
- `void pop ()`
- `int remove (const value_type &input)`
- `OsclPriorityQueue ()`
- `virtual ~OsclPriorityQueue ()`

### Protected Methods

- `void push_heap (iterator first, iterator last)`
- `void pop_heap (iterator first, iterator last)`
- `iterator find_heap (const value_type &input, iterator first, iterator last)`
- `int validate ()`
- `void swap (OsclAny *dest, const OsclAny *src)`
- `int compare_LT (OsclAny *a, OsclAny *b) const`
- `int compare_EQ (const OsclAny *a, const OsclAny *b) const`

### Protected Attributes

- `Container c`
- `Compare comp`

## Friends

- class [oscl\\_priqueue\\_test](#)

```
template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> class OsclPriorityQueue< Qelem, Alloc, Container, Compare >
```

### 7.177.1 Member Typedef Documentation

- 7.177.1.1 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **typedef Container::const\_reference OsclPriorityQueue< Qelem, Alloc, Container, Compare >::const\_reference**
- 7.177.1.2 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **typedef Container OsclPriorityQueue< Qelem, Alloc, Container, Compare >::container\_type**
- 7.177.1.3 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **typedef Container::iterator OsclPriorityQueue< Qelem, Alloc, Container, Compare >::iterator**
- 7.177.1.4 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **typedef Container::value\_type OsclPriorityQueue< Qelem, Alloc, Container, Compare >::value\_type**

### 7.177.2 Constructor & Destructor Documentation

- 7.177.2.1 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **OsclPriorityQueue< Qelem, Alloc, Container, Compare >::OsclPriorityQueue () [inline]**
- 7.177.2.2 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **virtual OsclPriorityQueue< Qelem, Alloc, Container, Compare >::~OsclPriorityQueue () [inline, virtual]**

### 7.177.3 Member Function Documentation

- 7.177.3.1 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **int OsclPriorityQueue< Qelem, Alloc, Container, Compare >::compare\_EQ (const OsclAny \* a, const OsclAny \* b) const [inline, protected, virtual]**

Return a==b.

Implements [Oscl\\_Opaque\\_Type\\_Compare](#).

- 7.177.3.2 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **int OsclPriorityQueue< Qelem, Alloc, Container, Compare >::compare\_LT (OsclAny \* a, OsclAny \* b) const [inline, protected, virtual]**

Return a<b.

Implements [Oscl\\_Opaque\\_Type\\_Compare](#).

- 7.177.3.3 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> bool OsclPriorityQueue< Qelem, Alloc, Container, Compare >::empty () const [inline]`
- 7.177.3.4 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> iterator OsclPriorityQueue< Qelem, Alloc, Container, Compare >::find_heap (const value_type & input, iterator first, iterator last) [inline, protected]`
- 7.177.3.5 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> void OsclPriorityQueue< Qelem, Alloc, Container, Compare >::pop () [inline]`
- 7.177.3.6 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> void OsclPriorityQueue< Qelem, Alloc, Container, Compare >::pop_heap (iterator first, iterator last) [inline, protected]`
- 7.177.3.7 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> void OsclPriorityQueue< Qelem, Alloc, Container, Compare >::push (const value_type & input) [inline]`
- 7.177.3.8 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> void OsclPriorityQueue< Qelem, Alloc, Container, Compare >::push_heap (iterator first, iterator last) [inline, protected]`
- 7.177.3.9 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> int OsclPriorityQueue< Qelem, Alloc, Container, Compare >::remove (const value_type & input) [inline]`
- 7.177.3.10 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> void OsclPriorityQueue< Qelem, Alloc, Container, Compare >::reserve (uint32 n) [inline]`
- 7.177.3.11 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> uint32 OsclPriorityQueue< Qelem, Alloc, Container, Compare >::size () const [inline]`
- 7.177.3.12 `template<class Qelem, class Alloc, class Container = Oscl_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> void OsclPriorityQueue< Qelem, Alloc, Container, Compare >::swap (OsclAny * dest, const OsclAny * src) [inline, protected, virtual]`

Swap element at "a" with element at "b". Both pointers must be non-NULL.

Implements [Oscl\\_Opaque\\_Type\\_Compare](#).

- 7.177.3.13 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **const\_reference** OsclPriorityQueue< Qelem, Alloc, Container, Compare >::top () const [inline]
- 7.177.3.14 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> int OsclPriorityQueue< Qelem, Alloc, Container, Compare >::validate () [inline, protected]
- 7.177.3.15 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> **const Container&** OsclPriorityQueue< Qelem, Alloc, Container, Compare >::vec () [inline]

#### 7.177.4 Friends And Related Function Documentation

- 7.177.4.1 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> friend class oscl\_priqueue\_test [friend]

#### 7.177.5 Field Documentation

- 7.177.5.1 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> Container OsclPriorityQueue< Qelem, Alloc, Container, Compare >::c [protected]
- 7.177.5.2 template<class Qelem, class Alloc, class Container = Oscl\_Vector<Qelem, Alloc>, class Compare = OsclCompareLess<Qelem>> Compare OsclPriorityQueue< Qelem, Alloc, Container, Compare >::comp [protected]


The documentation for this class was generated from the following file:

- [oscl\\_priqueue.h](#)

## 7.178 OsclPriorityQueueBase Class Reference

```
#include <oscl_priqueue.h>
```

Inheritance diagram for OsclPriorityQueueBase::



### Protected Methods

- virtual ~OsclPriorityQueueBase ()
- OSCL\_IMPORT\_REF void [push\\_heap](#) (OsclAny \*first, OsclAny \*last)
- OSCL\_IMPORT\_REF void [pop\\_heap](#) (OsclAny \*first, OsclAny \*last)
- OSCL\_IMPORT\_REF OsclAny \* [find\\_heap](#) (const OsclAny \*input, OsclAny \*first, OsclAny \*last)
- OSCL\_IMPORT\_REF int [remove](#) (const OsclAny \*input)
- void [construct](#) (Oscl\_Opaque\_Type\_Compare \*ot, Oscl\_Vector\_Base \*vec)

#### 7.178.1 Detailed Description

OsclPriorityQueueBase is a non-templatized base class for [OsclPriorityQueue](#). The purpose of this base class is to avoid large inline routines in the [OsclPriorityQueue](#) implementation. This class is not intended for direct instantiation except by [OsclPriorityQueue](#).

#### 7.178.2 Constructor & Destructor Documentation

**7.178.2.1** virtual OsclPriorityQueueBase::~OsclPriorityQueueBase () [inline, protected, virtual]

#### 7.178.3 Member Function Documentation

**7.178.3.1** void OsclPriorityQueueBase::[construct](#) (Oscl\_Opaque\_Type\_Compare \* *ot*, Oscl\_Vector\_Base \* *vec*) [inline, protected]

**7.178.3.2** OSCL\_IMPORT\_REF OsclAny\* OsclPriorityQueueBase::[find\\_heap](#) (const OsclAny \* *input*, OsclAny \* *first*, OsclAny \* *last*) [protected]

**7.178.3.3** OSCL\_IMPORT\_REF void OsclPriorityQueueBase::[pop\\_heap](#) (OsclAny \* *first*, OsclAny \* *last*) [protected]

**7.178.3.4** OSCL\_IMPORT\_REF void OsclPriorityQueueBase::[push\\_heap](#) (OsclAny \* *first*, OsclAny \* *last*) [protected]

**7.178.3.5** OSCL\_IMPORT\_REF int OsclPriorityQueueBase::[remove](#) (const OsclAny \* *input*) [protected]

The documentation for this class was generated from the following file:

- [oscl\\_priqueue.h](#)

## 7.179 OsclProcStatus Class Reference

```
#include <oscl_procstatus.h>
```

### Public Types

- enum `eOsclProcError` { `SUCCESS_ERROR` = 0, `OTHER_ERROR`, `TOO_MANY_THREADS_ERROR`, `BAD_THREADID_ADDR_ERROR`, `MAX_THRDS_REACHED_ERROR`, `INVALID_THREAD_ID_ERROR`, `NOT_ENOUGH_MEMORY_ERROR`, `OUTOFMEMORY_ERROR`, `NOT_ENOUGH_RESOURCES_ERROR`, `THREAD_1_INACTIVE_ERROR`, `ALREADY_SUSPENDED_ERROR`, `NOT_SUSPENDED_ERROR`, `INVALID_THREAD_ERROR`, `INVALID_PARAM_ERROR`, `NO_PERMISSION_ERROR`, `INVALID_PRIORITY_ERROR`, `PSHARED_NOT_ZERO_ERROR`, `EXCEED_MAX_COUNT_VARIABLE_ERROR`, `THREAD_BLOCK_ERROR`, `EXCEED_MAX_SEM_COUNT_ERROR`, `INVALID_HANDLE_ERROR`, `INVALID_OPERATION_ERROR`, `INVALID_FUNCTION_ERROR`, `INVALID_ACCESS_ERROR`, `INVALID_ARGUMENT_ERROR`, `SYSTEM_RESOURCES_UNAVAILABLE_ERROR`, `INVALID_POINTER_ERROR`, `RELOCK_MUTEX_ERROR`, `THREAD_NOT_OWN_MUTEX_ERROR`, `MUTEX_LOCKED_ERROR`, `WAIT_ABANDONED_ERROR`, `WAIT_TIMEOUT_ERROR`, `SEM_NOT_SIGNALED_ERROR`, `PSHARED_ATTRIBUTE_SETTING_ERROR`, `NOT_IMPLEMENTED` }

### 7.179.1 Detailed Description

Class OsclProcStatus

### 7.179.2 Member Enumeration Documentation

#### 7.179.2.1 enum OsclProcStatus::eOsclProcError

List of enums which contain error codes

Enumeration values:

`SUCCESS_ERROR`  
`OTHER_ERROR`  
`TOO_MANY_THREADS_ERROR`  
`BAD_THREADID_ADDR_ERROR`  
`MAX_THRDS_REACHED_ERROR`  
`INVALID_THREAD_ID_ERROR`  
`NOT_ENOUGH_MEMORY_ERROR`  
`OUTOFMEMORY_ERROR`  
`NOT_ENOUGH_RESOURCES_ERROR`  
`THREAD_1_INACTIVE_ERROR`  
`ALREADY_SUSPENDED_ERROR`  
`NOT_SUSPENDED_ERROR`  
`INVALID_THREAD_ERROR`  
`INVALID_PARAM_ERROR`  
`NO_PERMISSION_ERROR`

**INVALID\_PRIORITY\_ERROR**  
**PSHARED\_NOT\_ZERO\_ERROR**  
**EXCEED\_MAX\_COUNT\_VARIABLE\_ERROR**  
**THREAD\_BLOCK\_ERROR**  
**EXCEED\_MAX\_SEM\_COUNT\_ERROR**  
**INVALID\_HANDLE\_ERROR**  
**INVALID\_OPERATION\_ERROR**  
**INVALID\_FUNCTION\_ERROR**  
**INVALID\_ACCESS\_ERROR**  
**INVALID\_ARGUMENT\_ERROR**  
**SYSTEM\_RESOURCES\_UNAVAILABLE\_ERROR**  
**INVALID\_POINTER\_ERROR**  
**RELOCK\_MUTEX\_ERROR**  
**THREAD\_NOT\_OWN\_MUTEX\_ERROR**  
**MUTEX\_LOCKED\_ERROR**  
**WAIT\_ABANDONED\_ERROR**  
**WAIT\_TIMEOUT\_ERROR**  
**SEM\_NOT\_SIGNALED\_ERROR**  
**PSHARED\_ATTRIBUTE\_SETTING\_ERROR**  
**NOT\_IMPLEMENTED**


The documentation for this class was generated from the following file:

- [oscl\\_procstatus.h](#)

## 7.180 OsclPtr Class Reference

```
#include <oscl_file_async_read.h>
```

Inheritance diagram for OsclPtr::



### Public Methods

- [OsclPtr \(uint8 \\*ptr, int32 &len, int32 max\)](#)
- [OsclPtr \(const OsclPtr &d\)](#)
- [uint8 \\* Ptr \(\)](#)
- [void SetLength \(int32 l\)](#)
- [int32 Length \(\)](#)
- [void Zero \(\)](#)
- [void Set \(OsclPtr &v\)](#)
- [void Set \(uint8 \\*ptr, int32 len, int32 max\)](#)
- [void Append \(OsclPtrC &v\)](#)

#### 7.180.1 Constructor & Destructor Documentation

**7.180.1.1 OsclPtr::OsclPtr (uint8 \*ptr, int32 &len, int32 max) [inline]**

**7.180.1.2 OsclPtr::OsclPtr (const OsclPtr &d) [inline]**

#### 7.180.2 Member Function Documentation

**7.180.2.1 void OsclPtr::Append (OsclPtrC &v) [inline]**

**7.180.2.2 int32 OsclPtr::Length () [inline]**

**7.180.2.3 uint8\* OsclPtr::Ptr () [inline]**

**7.180.2.4 void OsclPtr::Set (uint8 \*ptr, int32 len, int32 max) [inline]**

**7.180.2.5 void OsclPtr::Set (OsclPtr &v) [inline]**

**7.180.2.6 void OsclPtr::SetLength (int32 l) [inline]**

**7.180.2.7 void OsclPtr::Zero () [inline]**


The documentation for this class was generated from the following file:

- [oscl\\_file\\_async\\_read.h](#)

## 7.181 OsclPtrC Class Reference

```
#include <oscl_file_async_read.h>
```

Inheritance diagram for OsclPtrC::



### Public Methods

- [OsclPtrC](#) (const uint8 \*ptr, int32 len, int32 max)
- [OsclPtrC](#) (const OsclPtrC &d)
- const uint8 \* [Ptr](#) ()
- void [SetLength](#) (int32 l)
- int32 [Length](#) ()
- void [Zero](#) ()
- void [Set](#) (OsclPtrC \*v)
- void [Set](#) (uint8 \*ptr, int32 len, int32 max)
- OsclPtrC [Right](#) (int32 size)
- OsclPtrC [Left](#) (int32 size)

### 7.181.1 Constructor & Destructor Documentation

**7.181.1.1** `OsclPtrC::OsclPtrC (const uint8 *ptr, int32 len, int32 max)` [inline]

**7.181.1.2** `OsclPtrC::OsclPtrC (const OsclPtrC & d)` [inline]

### 7.181.2 Member Function Documentation

**7.181.2.1** `OsclPtrC OsclPtrC::Left (int32 size)` [inline]

**7.181.2.2** `int32 OsclPtrC::Length ()` [inline]

**7.181.2.3** `const uint8* OsclPtrC::Ptr ()` [inline]

**7.181.2.4** `OsclPtrC OsclPtrC::Right (int32 size)` [inline]

**7.181.2.5** `void OsclPtrC::Set (uint8 *ptr, int32 len, int32 max)` [inline]

**7.181.2.6** `void OsclPtrC::Set (OsclPtrC *v)` [inline]

**7.181.2.7** `void OsclPtrC::SetLength (int32 l)` [inline]

**7.181.2.8** `void OsclPtrC::Zero ()` [inline]

The documentation for this class was generated from the following file:

- [oscl\\_file\\_async\\_read.h](#)

## 7.182 OsclRand Class Reference

```
#include <oscl_rand.h>
```

### Public Methods

- OSCL\_COND\_IMPORT\_REF void [Seed](#) (int32 seed)
- OSCL\_COND\_IMPORT\_REF int32 [Rand](#) ()

#### 7.182.1 Member Function Documentation

**7.182.1.1 OSCL\_COND\_IMPORT\_REF int32 OsclRand::Rand ()**

**7.182.1.2 OSCL\_COND\_IMPORT\_REF void OsclRand::Seed (int32 *seed*)**


The documentation for this class was generated from the following file:

- [oscl\\_rand.h](#)

## 7.183 OsclReadyAlloc Class Reference

```
#include <oscl_scheduler_readyq.h>
```

Inheritance diagram for OsclReadyAlloc::



### Public Methods

- [OsclAny \\* allocate \(const uint32 size\)](#)
- [OsclAny \\* allocate\\_fl \(const uint32 size, const char \\*file\\_name, const int line\\_num\)](#)
- void [deallocate \(OsclAny \\*p\)](#)

#### 7.183.1 Member Function Documentation

##### 7.183.1.1 [OsclAny\\* OsclReadyAlloc::allocate \(const uint32 size\) \[virtual\]](#)

Implements [Oscl\\_DefAlloc](#).

##### 7.183.1.2 [OsclAny\\* OsclReadyAlloc::allocate\\_fl \(const uint32 size, const char \\*file\\_name, const int line\\_num\) \[virtual\]](#)

Reimplemented from [Oscl\\_DefAlloc](#).

##### 7.183.1.3 [void OsclReadyAlloc::deallocate \(OsclAny \\*p\) \[virtual\]](#)

Implements [Oscl\\_DefAlloc](#).

The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_readyq.h](#)

## 7.184 OsclReadyCompare Class Reference

```
#include <oscl_scheduler_readyq.h>
```

### Static Public Methods

- int [compare \(TOsclReady &a, TOsclReady &b\)](#)

#### 7.184.1 Member Function Documentation

##### 7.184.1.1 int OsclReadyCompare::compare (TOsclReady &*a*, TOsclReady &*b*) [static]


The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_readyq.h](#)

## 7.185 OsclReadyQ Class Reference

```
#include <oscl_scheduler_readyq.h>
```

Inheritance diagram for OsclReadyQ::



### Public Methods

- void [Construct](#) (int)
- void [ThreadLogon](#) ()
- void [ThreadLogoff](#) ()
- void [Remove](#) (TOscIReady)
- bool [IsIn](#) (TOscIReady)
- uint32 [Depth](#) ()
- [TOscIReady PopTop](#) ()
- [TOscIReady Top](#) ()
- [TOscIReady WaitAndPopTop](#) ()
- [TOscIReady WaitAndPopTop](#) (uint32)
- int32 [PendComplete](#) (PVActiveBase \*pvbase, int32 aReason)
- int32 [WaitForRequestComplete](#) (PVActiveBase \*)
- void [RegisterForCallback](#) (OsclSchedulerObserver \*aCallback, OsclAny \*aCallbackContext)
- void [TimerCallback](#) (uint32 aDelayMicrosec)
- [OsclSchedulerObserver \\* Callback](#) ()

## 7.185.1 Member Function Documentation

7.185.1.1 **OsclSchedulerObserver\*** OsclReadyQ::Callback () [inline]

7.185.1.2 void OsclReadyQ::Construct (int)

7.185.1.3 uint32 OsclReadyQ::Depth () [inline]

7.185.1.4 bool OsclReadyQ::IsIn (**TOsclReady**)

7.185.1.5 int32 OsclReadyQ::PendComplete (**PVActiveBase** \**pvbase*, int32 *aReason*)

7.185.1.6 **TOsclReady** OsclReadyQ::PopTop ()

7.185.1.7 void OsclReadyQ::RegisterForCallback (**OsclSchedulerObserver** \**aCallback*, **OsclAny** \**aCallbackContext*)

7.185.1.8 void OsclReadyQ::Remove (**TOsclReady**)

7.185.1.9 void OsclReadyQ::ThreadLogoff ()

7.185.1.10 void OsclReadyQ::ThreadLogon ()

7.185.1.11 void OsclReadyQ::TimerCallback (uint32 *aDelayMicrosec*)

7.185.1.12 **TOsclReady** OsclReadyQ::Top ()

7.185.1.13 **TOsclReady** OsclReadyQ::WaitAndPopTop (uint32)

7.185.1.14 **TOsclReady** OsclReadyQ::WaitAndPopTop ()

7.185.1.15 int32 OsclReadyQ::WaitForRequestComplete (**PVActiveBase** \*)


The documentation for this class was generated from the following file:

- `oscl_scheduler_readyq.h`

## 7.186 OsclRecvFromMethod Class Reference

```
#include <oscl_socket_recv_from.h>
```

Inheritance diagram for OsclRecvFromMethod:::



### Public Methods

- [`~OsclRecvFromMethod \(\)`](#)
- [`TPVSocketEvent RecvFrom \(uint8 \*&aPtr, uint32 aMaxLen, OsclNetworkAddress &aAddress, int32 aTimeout, uint32 aMultiMax, Oscl\_Vector< uint32, OsclMemAllocator > \*aPacketLen, Oscl\_Vector< OsclNetworkAddress, OsclMemAllocator > \*aPacketSource\)`](#)
- [`uint8 \* GetRecvData \(int32 \*aLength\)`](#)
- [`OsclRecvFromRequest \* RecvFromRequest \(\)`](#)

### Static Public Methods

- [`OsclRecvFromMethod \* NewL \(OsclIPSocketI &c\)`](#)

#### 7.186.1 Constructor & Destructor Documentation

##### 7.186.1.1 OsclRecvFromMethod::~OsclRecvFromMethod ()

#### 7.186.2 Member Function Documentation

##### 7.186.2.1 `uint8* OsclRecvFromMethod::GetRecvData (int32 * aLength)`

##### 7.186.2.2 `OsclRecvFromMethod* OsclRecvFromMethod::NewL (OsclIPSocketI & c) [static]`

##### 7.186.2.3 `TPVSocketEvent OsclRecvFromMethod::RecvFrom (uint8 *& aPtr, uint32 aMaxLen, OsclNetworkAddress & aAddress, int32 aTimeout, uint32 aMultiMax, Oscl_Vector< uint32, OsclMemAllocator > * aPacketLen, Oscl_Vector< OsclNetworkAddress, OsclMemAllocator > * aPacketSource)`

##### 7.186.2.4 `OsclRecvFromRequest* OsclRecvFromMethod::RecvFromRequest () [inline]`


The documentation for this class was generated from the following file:

- 
- [oscl\\_socket\\_recv\\_from.h](#)

## 7.187 OsclRecvFromRequest Class Reference

```
#include <oscl_socket_recv_from.h>
```

Inheritance diagram for OsclRecvFromRequest::



### Public Methods

- `uint8 * GetRecvData (int32 *aLength)`
- `OsclRecvFromRequest (OsclSocketMethod &c)`
- `void RecvFrom (uint8 *&aPtr, uint32 aMaxLen, OsclNetworkAddress &aAddress, uint32 aMultiMax, Oscl_Vector< uint32, OsclMemAllocator > *aPacketLen, Oscl_Vector< OsclNetworkAddress, OsclMemAllocator > *aPacketSource)`
- `void Success ()`

#### 7.187.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.187.2 Constructor & Destructor Documentation

**7.187.2.1 OsclRecvFromRequest::OsclRecvFromRequest (`OsclSocketMethod &c`) [inline]**

#### 7.187.3 Member Function Documentation

**7.187.3.1 `uint8* OsclRecvFromRequest::GetRecvData (int32 * aLength)`**

**7.187.3.2 `void OsclRecvFromRequest::RecvFrom (uint8 *& aPtr, uint32 aMaxLen, OsclNetworkAddress & aAddress, uint32 aMultiMax, Oscl_Vector< uint32, OsclMemAllocator > * aPacketLen, Oscl_Vector< OsclNetworkAddress, OsclMemAllocator > * aPacketSource)`**

**7.187.3.3 `void OsclRecvFromRequest::Success () [virtual]`**

Reimplemented from `OsclSocketRequestAO`.


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_recv\\_from.h](#)

## 7.188 OsclRecvMethod Class Reference

```
#include <oscl_socket_recv.h>
```

Inheritance diagram for OsclRecvMethod::



### Public Methods

- [~OsclRecvMethod \(\)](#)
- [TPVSocketEvent Recv \(uint8 \\*&aPtr, uint32 aMaxLen, int32 aTimeout\)](#)
- [uint8 \\* GetRecvData \(int32 \\*aLength\)](#)
- [OsclRecvRequest \\* RecvRequest \(\)](#)

### Static Public Methods

- [OsclRecvMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.188.1 Constructor & Destructor Documentation

##### 7.188.1.1 OsclRecvMethod::~OsclRecvMethod ()

#### 7.188.2 Member Function Documentation

##### 7.188.2.1 uint8\* OsclRecvMethod::GetRecvData (int32 \* aLength)

##### 7.188.2.2 OsclRecvMethod\* OsclRecvMethod::NewL (OsclIPSocketI & c) [static]

##### 7.188.2.3 TPVSocketEvent OsclRecvMethod::Recv (uint8 \*& aPtr, uint32 aMaxLen, int32 aTimeout)

##### 7.188.2.4 OsclRecvRequest\* OsclRecvMethod::RecvRequest () [inline]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_recv.h](#)

## 7.189 OsclRecvRequest Class Reference

```
#include <oscl_socket_recv.h>
```

Inheritance diagram for OsclRecvRequest::



### Public Methods

- `uint8 * GetRecvData (int32 *aLength)`
- `OsclRecvRequest (OsclSocketMethod &c)`
- `void Recv (uint8 *&aPtr, uint32 aMaxLen)`
- `void Success ()`

#### 7.189.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.189.2 Constructor & Destructor Documentation

**7.189.2.1 OsclRecvRequest::OsclRecvRequest (`OsclSocketMethod &c`) [inline]**

#### 7.189.3 Member Function Documentation

**7.189.3.1 `uint8* OsclRecvRequest::GetRecvData (int32 * aLength)`**

**7.189.3.2 `void OsclRecvRequest::Recv (uint8 *& aPtr, uint32 aMaxLen)`**

**7.189.3.3 `void OsclRecvRequest::Success () [virtual]`**

Reimplemented from `OsclSocketRequestAO`.


The documentation for this class was generated from the following file:

- `oscl_socket_recv.h`

## 7.190 OsclRefCounter Class Reference

```
#include <oscl_refcounter.h>
```

Inheritance diagram for OsclRefCounter:::



### Public Methods

- virtual void `addRef ()=0`
- virtual void `removeRef ()=0`
- virtual uint32 `getCount ()=0`
- virtual `~OsclRefCounter ()`

#### 7.190.1 Detailed Description

Interface class for OsclRefCounter implementations

#### 7.190.2 Constructor & Destructor Documentation

**7.190.2.1 virtual OsclRefCounter::~OsclRefCounter () [inline, virtual]**

#### 7.190.3 Member Function Documentation

**7.190.3.1 virtual void OsclRefCounter::addRef () [pure virtual]**

Add to the reference count

Implemented in `OsclRefCounterDA`, `OsclRefCounterSA< DeallocType >`, `OsclRefCounterMTDA< LockType >`, `OsclRefCounterMTSA< DeallocType, LockType >`, and `Oscl_DefAllocWithRefCounter< DefAlloc >`.

**7.190.3.2 virtual uint32 OsclRefCounter::getCount () [pure virtual]**

Gets the current number of references

Implemented in `OsclRefCounterDA`, `OsclRefCounterSA< DeallocType >`, `OsclRefCounterMTDA< LockType >`, `OsclRefCounterMTSA< DeallocType, LockType >`, and `Oscl_DefAllocWithRefCounter< DefAlloc >`.

**7.190.3.3 virtual void OsclRefCounter::removeRef () [pure virtual]**

Delete from reference count

Implemented in `OsclRefCounterDA`, `OsclRefCounterSA< DeallocType >`, `OsclRefCounterMTDA< LockType >`, `OsclRefCounterMTSA< DeallocType, LockType >`, and `Oscl_DefAllocWithRefCounter< DefAlloc >`.


The documentation for this class was generated from the following file:

- 
- [oscl\\_refcounter.h](#)

## 7.191 OsclRefCounterDA Class Reference

```
#include <oscl_refcounter.h>
```

Inheritance diagram for OsclRefCounterDA::



### Public Methods

- [OsclRefCounterDA \(OsclAny \\*p, OsclDestructDealloc \\*dealloc\)](#)
- virtual [~OsclRefCounterDA \(\)](#)
- void [addRef \(\)](#)
- void [removeRef \(\)](#)
- uint32 [getCount \(\)](#)

#### 7.191.1 Detailed Description

Implementation of an [OsclRefCounter](#) that uses a dynamically created deallocator.

#### 7.191.2 Constructor & Destructor Documentation

##### 7.191.2.1 OsclRefCounterDA::OsclRefCounterDA ([OsclAny \\*p](#), [OsclDestructDealloc \\*dealloc](#)) [inline]

Constructor Takes a pointer to the buffer to track, and a pointer to the deallocator object which will be used to delete the buffer.

When the reference count reaches zero, the buffer will be deleted by the deallocator. Also, the [OsclRefCounter](#) object (this) will self-destruct when the reference count is zero. In some cases the [OsclRefCounter](#) object will be part of the buffer being deleted. For such cases, the object pointer must be equal to the buffer pointer given at construction. If the object is not part of the buffer being deleted, it will self-destruct with a call to `delete()`.

##### Parameters:

*p* pointer to the buffer to track

*dealloc* pointer to the deallocator to use when deleting the buffer

##### 7.191.2.2 virtual OsclRefCounterDA::~OsclRefCounterDA () [inline, virtual]

Destructor empty

### 7.191.3 Member Function Documentation

#### 7.191.3.1 void OsclRefCounterDA::addRef () [inline, virtual]

Add to the reference count

Implements [OsclRefCounter](#).

#### 7.191.3.2 uint32 OsclRefCounterDA::getCount () [inline, virtual]

Gets the current number of references

Implements [OsclRefCounter](#).

#### 7.191.3.3 void OsclRefCounterDA::removeRef () [inline, virtual]

Remove from the reference count

Implements [OsclRefCounter](#).

The documentation for this class was generated from the following file:

- [oscl\\_refcounter.h](#)

## 7.192 OsclRefCounterMemFrag Class Reference

```
#include <oscl_refcounter_memfrag.h>
```

### Public Methods

- [OsclRefCounterMemFrag \(OsclMemoryFragment &m, OsclRefCounter \\*r, uint32 in\\_capacity\)](#)
- [OsclRefCounterMemFrag \(const OsclRefCounterMemFrag &x\)](#)
- [OsclRefCounterMemFrag \(\)](#)
- [OsclRefCounterMemFrag & operator= \(const OsclRefCounterMemFrag &x\)](#)
- [~OsclRefCounterMemFrag \(\)](#)
- [OsclRefCounter \\* getRefCounter \(\)](#)
- [OsclMemoryFragment & getMemFrag \(\)](#)
- [OsclAny \\* getMemFragPtr \(\)](#)
- [uint32 getMemFragSize \(\)](#)
- [uint32 getCapacity \(\)](#)
- [uint32 getCount \(\)](#)

### 7.192.1 Detailed Description

Class to contain a memory fragment with it's associated reference counter.

### 7.192.2 Constructor & Destructor Documentation

#### 7.192.2.1 OsclRefCounterMemFrag::OsclRefCounterMemFrag ([OsclMemoryFragment & m](#), [OsclRefCounter \\* r](#), [uint32 in\\_capacity](#)) [inline]

Constructor. A valid memory fragment and reference counter are required as input. The memory fragment structure will be copied locally.

##### Parameters:

- m* reference to memory fragment
- r* pointer to the reference counter associated with the memory fragment.

#### 7.192.2.2 OsclRefCounterMemFrag::OsclRefCounterMemFrag ([const OsclRefCounterMemFrag & x](#)) [inline]

Copy constructor.

#### 7.192.2.3 OsclRefCounterMemFrag::OsclRefCounterMemFrag () [inline]

Default constructor.

#### 7.192.2.4 OsclRefCounterMemFrag::~OsclRefCounterMemFrag () [inline]

Destructor. Removes this object's reference from the reference counter. The reference counter will not be deleted. The reference counter is designed to self-delete when it's reference count reaches 0.

### 7.192.3 Member Function Documentation

#### 7.192.3.1 **uint32 OsclRefCounterMemFrag::getCapacity () [inline]**

Returns the capacity of the memory fragment

**Returns:**

#### 7.192.3.2 **uint32 OsclRefCounterMemFrag::getCount () [inline]**

Returns the reference counter's current count.

#### 7.192.3.3 **OsclMemoryFragment& OsclRefCounterMemFrag::getMemFrag () [inline]**

Returns a reference to the contained memory fragment structure.

#### 7.192.3.4 **OsclAny\* OsclRefCounterMemFrag::getMemFragPtr () [inline]**

Returns a pointer to the memory fragment data.

#### 7.192.3.5 **uint32 OsclRefCounterMemFrag::getMemFragSize () [inline]**

Returns the size of the memory fragment data which equals its filled size.

**Returns:**

#### 7.192.3.6 **OsclRefCounter\* OsclRefCounterMemFrag::getRefCounter () [inline]**

Returns a pointer to the contained reference counter object

#### 7.192.3.7 **OsclRefCounterMemFrag& OsclRefCounterMemFrag::operator= (const OsclRefCounterMemFrag & x) [inline]**

Assignment Operator


The documentation for this class was generated from the following file:

- [oscl\\_refcounter\\_memfrag.h](#)

## 7.193 OsclRefCounterMTDA< LockType > Class Template Reference

```
#include <oscl_refcounter.h>
```

Inheritance diagram for OsclRefCounterMTDA< LockType >::



### Public Methods

- [OsclRefCounterMTDA \(OsclAny \\*p, OsclDestructDealloc \\*dealloc\)](#)
- virtual [~OsclRefCounterMTDA \(\)](#)
- void [addRef \(\)](#)
- void [removeRef \(\)](#)
- uint32 [getCount \(\)](#)

#### 7.193.1 Detailed Description

**template<class LockType> class OsclRefCounterMTDA< LockType >**

Implementation of [OsclRefCounterDA](#) for multi-threaded use. A templated lock class must be specified.

#### 7.193.2 Constructor & Destructor Documentation

**7.193.2.1 template<class LockType> OsclRefCounterMTDA< LockType >::OsclRefCounterMTDA (OsclAny \*p, OsclDestructDealloc \*dealloc) [inline]**

Constructor Takes a pointer to the buffer to track, and a pointer to the deallocator object which will be used to delete the buffer.

When the reference count reaches zero, the buffer will be deleted by the deallocator. Also, the [OsclRefCounter](#) object (this) will self-destruct when the reference count is zero. In some cases the [OsclRefCounter](#) object will be part of the buffer being deleted. For such cases, the object pointer must be equal to the buffer pointer given at construction. If the object is not part of the buffer being deleted, it will self-destruct with a call to [delete\(\)](#).

##### Parameters:

*p* pointer to the buffer to track

*dealloc* pointer to the deallocator to use when deleting the buffer

**7.193.2.2 template<class LockType> virtual OsclRefCounterMTDA< LockType >::~OsclRefCounterMTDA () [inline, virtual]**

Destructor empty

### 7.193.3 Member Function Documentation

**7.193.3.1 template<class LockType> void OsclRefCounterMTDA< LockType >::addRef ()  
[inline, virtual]**

Add to the reference count

Implements [OsclRefCounter](#).

**7.193.3.2 template<class LockType> uint32 OsclRefCounterMTDA< LockType >::getCount ()  
[inline, virtual]**

Gets the current number of references

Implements [OsclRefCounter](#).

**7.193.3.3 template<class LockType> void OsclRefCounterMTDA< LockType >::removeRef ()  
[inline, virtual]**

Remove from the reference count

Implements [OsclRefCounter](#).


The documentation for this class was generated from the following file:

- [oscl\\_refcounter.h](#)

## 7.194 OsclRefCounterMTSA< DeallocType, LockType > Class Template Reference

```
#include <oscl_refcounter.h>
```

Inheritance diagram for OsclRefCounterMTSA< DeallocType, LockType >::



### Public Methods

- [OsclRefCounterMTSA \(OsclAny \\*p\)](#)
- virtual [~OsclRefCounterMTSA \(\)](#)
- void [addRef \(\)](#)
- void [removeRef \(\)](#)
- uint32 [getCount \(\)](#)

#### 7.194.1 Detailed Description

```
template<class DeallocType, class LockType> class OsclRefCounterMTSA< DeallocType, LockType >
```

Implementation of [OsclRefCounterSA](#) for multi-threaded use. A templated lock class must be specified.

#### 7.194.2 Constructor & Destructor Documentation

**7.194.2.1 template<class DeallocType, class LockType> OsclRefCounterMTSA< DeallocType, LockType >::OsclRefCounterMTSA (OsclAny \* p) [inline]**

Constructor Takes a pointer to the buffer to track.

When the reference count reaches zero, the buffer will be deleted by the deallocator. Also, the [OsclRefCounter](#) object (this) will self-destruct when the reference count is zero. In some cases the [OsclRefCounter](#) object will be part of the buffer being deleted. For such cases, the object pointer must be equal to the buffer pointer given at construction. If the object is not part of the buffer being deleted, it will self-destruct with a call to `delete()`.

**Parameters:**

*p* pointer to the buffer to track

**7.194.2.2 template<class DeallocType, class LockType> virtual OsclRefCounterMTSA< DeallocType, LockType >::~OsclRefCounterMTSA () [inline, virtual]**

Destructor empty

## 7.194.3 Member Function Documentation

**7.194.3.1 template<class DeallocType, class LockType> void OsclRefCounterMTSA< DeallocType, LockType >::addRef () [inline, virtual]**

Add to the reference count

Implements [OsclRefCounter](#).

**7.194.3.2 template<class DeallocType, class LockType> uint32 OsclRefCounterMTSA< DeallocType, LockType >::getCount () [inline, virtual]**

Gets the current number of references

Implements [OsclRefCounter](#).

**7.194.3.3 template<class DeallocType, class LockType> void OsclRefCounterMTSA< DeallocType, LockType >::removeRef () [inline, virtual]**

Remove from the reference count

Implements [OsclRefCounter](#).


The documentation for this class was generated from the following file:

- [oscl\\_refcounter.h](#)

## 7.195 OsclRefCounterSA< DeallocType > Class Template Reference

```
#include <oscl_refcounter.h>
```

Inheritance diagram for OsclRefCounterSA< DeallocType >::



### Public Methods

- [OsclRefCounterSA \(OsclAny \\*p\)](#)
- virtual [~OsclRefCounterSA \(\)](#)
- void [addRef \(\)](#)
- void [removeRef \(\)](#)
- uint32 [getCount \(\)](#)

#### 7.195.1 Detailed Description

**template<class DeallocType> class OsclRefCounterSA< DeallocType >**

Implementation of an [OsclRefCounter](#) that uses a statically created deallocator.

#### 7.195.2 Constructor & Destructor Documentation

##### 7.195.2.1 template<class DeallocType> OsclRefCounterSA< DeallocType >::OsclRefCounterSA (OsclAny \*p) [inline]

Constructor Takes a pointer to the buffer to track.

When the reference count reaches zero, the buffer will be deleted by the deallocator. Also, the [OsclRefCounter](#) object (this) will self-destruct when the reference count is zero. In some cases the [OsclRefCounter](#) object will be part of the buffer being deleted. For such cases, the object pointer must be equal to the buffer pointer given at construction. If the object is not part of the buffer being deleted, it will self-destruct with a call to [delete\(\)](#).

###### Parameters:

*p* pointer to the buffer to track

##### 7.195.2.2 template<class DeallocType> virtual OsclRefCounterSA< DeallocType >::~OsclRefCounterSA () [inline, virtual]

Destructor empty

### 7.195.3 Member Function Documentation

**7.195.3.1 template<class DeallocType> void OsclRefCounterSA< DeallocType >::addRef () [inline, virtual]**

Add to the reference count

Implements [OsclRefCounter](#).

**7.195.3.2 template<class DeallocType> uint32 OsclRefCounterSA< DeallocType >::getCount () [inline, virtual]**

Gets the current number of references

Implements [OsclRefCounter](#).

**7.195.3.3 template<class DeallocType> void OsclRefCounterSA< DeallocType >::removeRef () [inline, virtual]**

Remove from the reference count

Implements [OsclRefCounter](#).

The documentation for this class was generated from the following file:

- [oscl\\_refcounter.h](#)

## 7.196 OsclRegistryAccessClient Class Reference

```
#include <oscl_registry_access_client.h>
```

### Public Methods

- OSCL\_IMPORT\_REF OsclRegistryAccessClient ()
- OSCL\_IMPORT\_REF ~OsclRegistryAccessClient ()
- OSCL\_IMPORT\_REF int32 Connect ()
- OSCL\_IMPORT\_REF OsclComponentFactory GetFactory (OSCL\_String &aComponent)
- OSCL\_IMPORT\_REF void GetFactories (OSCL\_String &aRegistry, Oscl\_Vector< OsclRegistryAccessElement, OsclMemAllocator > &aVec)
- OSCL\_IMPORT\_REF void Close ()

#### 7.196.1 Constructor & Destructor Documentation

**7.196.1.1 OSCL\_IMPORT\_REF OsclRegistryAccessClient::OsclRegistryAccessClient ()**

**7.196.1.2 OSCL\_IMPORT\_REF OsclRegistryAccessClient::~OsclRegistryAccessClient ()**

#### 7.196.2 Member Function Documentation

**7.196.2.1 OSCL\_IMPORT\_REF void OsclRegistryAccessClient::Close ()**

Close and cleanup session.

**7.196.2.2 OSCL\_IMPORT\_REF int32 OsclRegistryAccessClient::Connect ()**

Create a session.

**Returns:**

OsclErrNone on success.

**7.196.2.3 OSCL\_IMPORT\_REF void OsclRegistryAccessClient::GetFactories (OSCL\_String & aRegistry, Oscl\_Vector< OsclRegistryAccessElement, OsclMemAllocator > & aVec)**

Get all factories for a given registry type.

**Parameters:**

*aRegistry*: registry MIME type

*aVec*: output component factory + mimestring vector.

**7.196.2.4 OSCL\_IMPORT\_REF OsclComponentFactory OsclRegistryAccessClient::GetFactory (OSCL\_String & aComponent)**

Lookup a factory by registry and component mime type.

**Parameters:**

*aComponent*: registry+component MIME type

**Returns:**

Factory. Factory will be NULL if not found.


The documentation for this class was generated from the following file:

- [oscl\\_registry\\_access\\_client.h](#)

## 7.197 OsclRegistryAccessClientImpl Class Reference

```
#include <oscl_registry_client_impl.h>
```

Inheritance diagram for OsclRegistryAccessClientImpl::




The documentation for this class was generated from the following file:

- [oscl\\_registry\\_client\\_impl.h](#)

## 7.198 OsclRegistryAccessClientTlsImpl Class Reference

```
#include <oscl_registry_client_impl.h>
```

Inheritance diagram for OsclRegistryAccessClientTlsImpl::



The documentation for this class was generated from the following file:

- [oscl\\_registry\\_client\\_impl.h](#)

## 7.199 OsclRegistryAccessElement Class Reference

```
#include <oscl_registry_types.h>
```

### Data Fields

- [OsclComponentFactory](#) iFactory
- [OSCL\\_HeapString< OsclMemAllocator >](#) iMimeType

#### 7.199.1 Detailed Description

A class used to access the registry data

#### 7.199.2 Field Documentation

##### 7.199.2.1 [OsclComponentFactory](#) OsclRegistryAccessElement::iFactory

##### 7.199.2.2 [OSCL\\_HeapString<OsclMemAllocator>](#) OsclRegistryAccessElement::iMimeType


The documentation for this class was generated from the following file:

- [oscl\\_registry\\_types.h](#)

## 7.200 OsclRegistryClient Class Reference

```
#include <oscl_registry_client.h>
```

Inheritance diagram for OsclRegistryClient::



### Public Methods

- OSCL\_IMPORT\_REF [OsclRegistryClient \(\)](#)
- OSCL\_IMPORT\_REF [~OsclRegistryClient \(\)](#)
- OSCL\_IMPORT\_REF int32 [Connect \(bool aPerThread=false\)](#)
- OSCL\_IMPORT\_REF int32 [Register \(OSCL\\_String &aComponentID, OsclComponentFactory aFactory\)](#)
- OSCL\_IMPORT\_REF int32 [UnRegister \(OSCL\\_String &aComponentID\)](#)
- OSCL\_IMPORT\_REF void [Close \(\)](#)

#### 7.200.1 Constructor & Destructor Documentation

**7.200.1.1 OSCL\_IMPORT\_REF OsclRegistryClient::OsclRegistryClient ()**

**7.200.1.2 OSCL\_IMPORT\_REF OsclRegistryClient::~OsclRegistryClient ()**

#### 7.200.2 Member Function Documentation

**7.200.2.1 OSCL\_IMPORT\_REF void OsclRegistryClient::Close ()**

Close and cleanup. All components registered in this session are automatically unregistered.

**7.200.2.2 OSCL\_IMPORT\_REF int32 OsclRegistryClient::Connect (bool *aPerThread* = false)**

Create a session.

**Parameters:**

*aPerThread*: Select per-thread registry instead of global registry.

**Returns:**

OsclErrNone on success.

**7.200.2.3 OSCL\_IMPORT\_REF int32 OsclRegistryClient::Register ([OSCL\\_String &](#)  
*aComponentID*, [OsclComponentFactory](#) *aFactory*)**

Register a component factory by registry ID and component ID.

**Parameters:**

*aComponentID*: registry + component mime-string.

*aFactory*: factory function pointer.

*aParam*: component Create param.

**Returns:**

OsclErrNone on success.

**7.200.2.4 OSCL\_IMPORT\_REF int32 OsclRegistryClient::UnRegister ([OSCL\\_String &](#)  
*aComponentID*)**

Unregister a previously registered component.

**Returns:**

OsclErrNone on success.


The documentation for this class was generated from the following file:

- [oscl\\_registry\\_client.h](#)

## 7.201 OsclRegistryClientImpl Class Reference

```
#include <oscl_registry_client_impl.h>
```

Inheritance diagram for OsclRegistryClientImpl:



### Protected Methods

- int32 [Connect \(\)](#)
- void [Close \(\)](#)
- int32 [Register \(OSCL\\_String &, OsclComponentFactory\)](#)
- int32 [UnRegister \(OSCL\\_String &\)](#)
- [OsclComponentFactory GetFactory \(OSCL\\_String &\)](#)
- void [GetFactories \(OSCL\\_String &, Oscl\\_Vector< OsclRegistryAccessElement, OsclMemAllocator > &\)](#)

### Friends

- class [OsclRegistryClient](#)
- class [OsclRegistryAccessClient](#)

## 7.201.1 Member Function Documentation

7.201.1.1 **void OsclRegistryClientImpl::Close (void)** [inline, protected]

7.201.1.2 **int32 OsclRegistryClientImpl::Connect ()** [inline, protected]

7.201.1.3 **void OsclRegistryClientImpl::GetFactories (OSCL\_String &, Oscl\_Vector< OsclRegistryAccessElement, OsclMemAllocator > &)** [inline, protected]

7.201.1.4 **OsclComponentFactory OsclRegistryClientImpl::GetFactory (OSCL\_String &)**  
[inline, protected]

7.201.1.5 **int32 OsclRegistryClientImpl::Register (OSCL\_String &, OsclComponentFactory)**  
[inline, protected]

7.201.1.6 **int32 OsclRegistryClientImpl::UnRegister (OSCL\_String &)** [inline,  
protected]

## 7.201.2 Friends And Related Function Documentation

7.201.2.1 **friend class OsclRegistryAccessClient** [friend]

7.201.2.2 **friend class OsclRegistryClient** [friend]


The documentation for this class was generated from the following file:

- [oscl\\_registry\\_client\\_impl.h](#)

## 7.202 OsclRegistryClientTlsImpl Class Reference

```
#include <oscl_registry_client_impl.h>
```

Inheritance diagram for OsclRegistryClientTlsImpl::




The documentation for this class was generated from the following file:

- [oscl\\_registry\\_client\\_impl.h](#)

## 7.203 OsclRegistryServTlsImpl Class Reference

```
#include <oscl_registry_serv_impl_tls.h>
```

Inheritance diagram for OsclRegistryServTlsImpl::



### Protected Methods

- [OsclRegistryServTlsImpl \(\)](#)
- virtual [~OsclRegistryServTlsImpl \(\)](#)
- int32 [Connect \(\)](#)
- void [Close \(\)](#)
- int32 [Register \(OSCL\\_String &aComponentID, OsclComponentFactory aFactory\)](#)
- int32 [UnRegister \(OSCL\\_String &aComponentID\)](#)
- [OsclComponentFactory GetFactory \(OSCL\\_String &aComponent\)](#)
- void [GetFactories \(OSCL\\_String &aRegistry, Oscl\\_Vector< OsclRegistryAccessElement, OsclMemAllocator > &aVec\)](#)

### Friends

- class [OsclRegistryClient](#)
- class [OsclRegistryAccessClient](#)

### 7.203.1 Constructor & Destructor Documentation

7.203.1.1 `OsclRegistryServTlsImpl::OsclRegistryServTlsImpl ()` [protected]

7.203.1.2 `virtual OsclRegistryServTlsImpl::~OsclRegistryServTlsImpl ()` [protected, virtual]

### 7.203.2 Member Function Documentation

7.203.2.1 `void OsclRegistryServTlsImpl::Close ()` [protected]

7.203.2.2 `int32 OsclRegistryServTlsImpl::Connect ()` [protected]

7.203.2.3 `void OsclRegistryServTlsImpl::GetFactories (OSCL_String & aRegistry, Oscl_Vector< OsclRegistryAccessElement, OsclMemAllocator > & aVec)` [protected]

7.203.2.4 `OsclComponentFactory OsclRegistryServTlsImpl::GetFactory (OSCL_String & aComponent)` [protected]

7.203.2.5 `int32 OsclRegistryServTlsImpl::Register (OSCL_String & aComponentID, OsclComponentFactory aFactory)` [protected]

7.203.2.6 `int32 OsclRegistryServTlsImpl::UnRegister (OSCL_String & aComponentID)` [protected]

### 7.203.3 Friends And Related Function Documentation

7.203.3.1 `friend class OsclRegistryAccessClient` [friend]

7.203.3.2 `friend class OsclRegistryClient` [friend]

The documentation for this class was generated from the following file:

- [oscl\\_registry\\_serv\\_impl\\_tls.h](#)

## 7.204 OsclScheduler Class Reference

```
#include <oscl_scheduler.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF void [Init](#) (const char \*name, [Oscl\\_DefAlloc](#) \*alloc=NULL, int nreserve=20)
- OSCL\_IMPORT\_REF void [Cleanup](#) ()

#### 7.204.1 Detailed Description

Per-thread scheduler initialization and cleanup.

#### 7.204.2 Member Function Documentation

##### 7.204.2.1 OSCL\_IMPORT\_REF void OsclScheduler::Cleanup () [static]

This routine uninstalls and destroys Oscl scheduler for the calling thread.

##### 7.204.2.2 OSCL\_IMPORT\_REF void OsclScheduler::Init (const char \* *name*, [Oscl\\_DefAlloc](#) \* *alloc* = NULL, int *nreserve* = 20) [static]

This routine creates and installs a scheduler in the calling thread.

#### Parameters:

- name*:** (input param) scheduler name.
- alloc*:** (input param) optional allocator to use for the internal implementation.
- nreserve*:** (input param) optional value for ready queue reserve size.

The documentation for this class was generated from the following file:

- [oscl\\_scheduler.h](#)

## 7.205 OsclSchedulerObserver Class Reference

```
#include <oscl_scheduler.h>
```

### Public Methods

- virtual void [OsclSchedulerTimerCallback](#) ([OsclAny](#) \*aContext, uint32 aDelayMsec)=0
- virtual void [OsclSchedulerReadyCallback](#) ([OsclAny](#) \*aContext)=0
- virtual [~OsclSchedulerObserver](#) ()

### 7.205.1 Detailed Description

OsclSchedulerObserver is an observer class for use when running scheduler in non-blocking mode. The scheduler observer can register for callbacks so it will be notified when it is necessary to run scheduler again. Note: non-blocking mode and scheduler callbacks are not supported on Symbian.

### 7.205.2 Constructor & Destructor Documentation

**7.205.2.1** virtual [OsclSchedulerObserver](#)::[~OsclSchedulerObserver](#) () [inline, virtual]

### 7.205.3 Member Function Documentation

**7.205.3.1** virtual void [OsclSchedulerObserver](#)::[OsclSchedulerReadyCallback](#) ([OsclAny](#) \* *aContext*) [pure virtual]

[OsclSchedulerReadyCallback](#) is called when the ready queue is updated, meaning an AO is ready to run. Scheduler needs to be run ASAP. Calling context may be any thread, so be careful!

The current observer is cleared before making the callback, so the observer must call RegisterForCallback again if it wants further notifications.

**7.205.3.2** virtual void [OsclSchedulerObserver](#)::[OsclSchedulerTimerCallback](#) ([OsclAny](#) \* *aContext*, uint32 *aDelayMsec*) [pure virtual]

[OsclSchedulerTimerCallback](#) is called when the front of the timer queue is updated. This means the minimum delay has changed and scheduler needs to be run again after aDelayMsec. Calling context is in-thread.

The current observer is cleared before making the callback, so the observer must call RegisterForCallback again if it wants further notifications.

The documentation for this class was generated from the following file:

- [oscl\\_scheduler.h](#)

## 7.206 OsclScopedLock< LockClass > Class Template Reference

The OsclScopedLock class is a template class that handles unlocking an abstract class on destruction. This is very useful for ensuring that the lock is released when the OsclScopedLock goes out of scope.

```
#include <oscl_lock_base.h>
```

### Public Methods

- [OsclScopedLock \(LockClass &inLock\)](#)  
*Default constructor Initializes the pointer and takes ownership.*
- [~OsclScopedLock \(\)](#)  
*Destructor.*

### 7.206.1 Detailed Description

**template<class LockClass> class OsclScopedLock< LockClass >**

The OsclScopedLock class is a template class that handles unlocking an abstract class on destruction. This is very useful for ensuring that the lock is released when the OsclScopedLock goes out of scope.

The purpose of this class is to provide a way to prevent accidental resource leaks in a class or a method, due to "not remembering to unlock" variables which might lead to deadlock conditions.

### 7.206.2 Constructor & Destructor Documentation

#### 7.206.2.1 **template<class LockClass> OsclScopedLock< LockClass >::OsclScopedLock (LockClass & inLock) [inline, explicit]**

Default constructor Initializes the pointer and takes ownership.

#### 7.206.2.2 **template<class LockClass> OsclScopedLock< LockClass >::~OsclScopedLock () [inline]**

Destructor.

The pointer is deleted in case this class still has ownership

The documentation for this class was generated from the following file:

- [oscl\\_lock\\_base.h](#)

## 7.207 OsclSelect Class Reference

```
#include <oscl_init.h>
```

### Public Methods

- [OsclSelect \(\)](#)
- [OsclSelect \(Oscl\\_DefAlloc \\*erralloc, Oscl\\_DefAlloc \\*schedalloc, const char \\*name, int32 reserve=10, bool heapcheck=false, FILE \\*output=NULL\)](#)

### Data Fields

- bool [iOsclBase](#)
- bool [iOsclMemory](#)
- bool [iOsclErrorTrap](#)
- bool [iOsclLogger](#)
- bool [iOsclScheduler](#)
- [Oscl\\_DefAlloc \\* iErrAlloc](#)
- [Oscl\\_DefAlloc \\* iSchedulerAlloc](#)
- const char \* [iSchedulerName](#)
- int32 [iSchedulerReserve](#)
- bool [iHeapCheck](#)
- FILE \* [iOutputFile](#)

### 7.207.1 Detailed Description

Oscl Module selection and Init/Cleanup options.

## 7.207.2 Constructor & Destructor Documentation

**7.207.2.1 OsclSelect::OsclSelect () [inline]**

**7.207.2.2 OsclSelect::OsclSelect ([Oscl\\_DefAlloc](#) \* *erralloc*, [Oscl\\_DefAlloc](#) \* *schedalloc*, const char \* *name*, int32 *reserve* = 10, bool *heapcheck* = false, FILE \* *output* = NULL) [inline]**

## 7.207.3 Field Documentation

**7.207.3.1 [Oscl\\_DefAlloc](#)\* OsclSelect::iErrAlloc**

**7.207.3.2 bool OsclSelect::iHeapCheck**

**7.207.3.3 bool OsclSelect::iOsclBase**

**7.207.3.4 bool OsclSelect::iOsclErrorTrap**

**7.207.3.5 bool OsclSelect::iOsclLogger**

**7.207.3.6 bool OsclSelect::iOsclMemory**

**7.207.3.7 bool OsclSelect::iOsclScheduler**

**7.207.3.8 FILE\* OsclSelect::iOutputFile**

**7.207.3.9 [Oscl\\_DefAlloc](#)\* OsclSelect::iSchedulerAlloc**

**7.207.3.10 const char\* OsclSelect::iSchedulerName**

**7.207.3.11 int32 OsclSelect::iSchedulerReserve**

The documentation for this class was generated from the following file:

- [oscl\\_init.h](#)

## 7.208 OsclSemaphore Class Reference

```
#include <oscl_semaphore.h>
```

### Public Methods

- OSCL\_IMPORT\_REF OsclSemaphore ()
- OSCL\_IMPORT\_REF ~OsclSemaphore ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Create (uint32 initVal=0)
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Close ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Wait ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Wait (uint32 timeout\_msec)
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError TryWait ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Signal ()

### 7.208.1 Detailed Description

Class Semaphore

### 7.208.2 Constructor & Destructor Documentation

#### 7.208.2.1 OSCL\_IMPORT\_REF OsclSemaphore::OsclSemaphore ()

Class constructor

#### 7.208.2.2 OSCL\_IMPORT\_REF OsclSemaphore::~OsclSemaphore ()

Class destructor

### 7.208.3 Member Function Documentation

#### 7.208.3.1 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclSemaphore::Close ()

Closes the Semaphore

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns the Error whether it is success or failure incase of failure it will return what is the specific error

#### 7.208.3.2 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclSemaphore::Create (uint32 initVal = 0)

Creates the Semaphore

**Parameters:**

*Intialcount*

**Returns:**

Returns the Error whether it is success or failure incase of failure it will return what is the specific error

**7.208.3.3 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclSemaphore::Signal ()**

Signals that the thread is finished with the Semaphore

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns the Error whether it is success or failure incase of failure it will return what is the specific error

**7.208.3.4 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclSemaphore::TryWait ()**

Try to acquire semaphore ,if the semaphore is already acquired by another thread, calling thread immediately returns with out blocking

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns SUCCESS\_ERROR if the semaphore was acquired, SEM\_LOCKED\_ERROR if the semaphore cannot be acquired without waiting, or an error code if the operation failed. Note: this function may not be supported on all platforms, and may return NOT\_IMPLEMENTED.

**7.208.3.5 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclSemaphore::Wait (uint32 timeout\_msec)**

Makes the thread to wait on the Semaphore, with a timeout.

**Parameters:**

*timeout* in milliseconds.

**Returns:**

Returns SUCCESS\_ERROR if the semaphore was aquired, WAIT\_TIMEOUT\_ERROR if the timeout expired without acquiring the semaphore, or an error code if the operation failed. Note: this function may not be supported on all platforms, and may return NOT\_IMPLEMENTED.

**7.208.3.6 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclSemaphore::Wait ()**

Makes the thread to wait on the Semaphore

**Parameters:**

*It* wont take any parameters

**Returns:**

Returns the Error whether it is success or failure incase of failure it will return what is the specific error


The documentation for this class was generated from the following file:

- [oscl\\_semaphore.h](#)

## 7.209 OsclSendMethod Class Reference

```
#include <oscl_socket_send.h>
```

Inheritance diagram for OsclSendMethod::



### Public Methods

- [~OsclSendMethod \(\)](#)
- [TPVSocketEvent Send \(const uint8 \\*aPtr, uint32 aLen, int32 aTimeout\)](#)
- [uint8 \\* GetSendData \(int32 \\*aLength\)](#)
- [OsclSendRequest \\* SendRequest \(\)](#)

### Static Public Methods

- [OsclSendMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.209.1 Constructor & Destructor Documentation

##### 7.209.1.1 OsclSendMethod::~OsclSendMethod ()

#### 7.209.2 Member Function Documentation

##### 7.209.2.1 uint8\* OsclSendMethod::GetSendData (int32 \* aLength)

##### 7.209.2.2 OsclSendMethod\* OsclSendMethod::NewL (OsclIPSocketI & c) [static]

##### 7.209.2.3 TPVSocketEvent OsclSendMethod::Send (const uint8 \*& aPtr, uint32 aLen, int32 aTimeout)

##### 7.209.2.4 OsclSendRequest\* OsclSendMethod::SendRequest () [inline]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_send.h](#)

## 7.210 OsclSendRequest Class Reference

```
#include <oscl_socket_send.h>
```

Inheritance diagram for OsclSendRequest::



### Public Methods

- [OsclSendRequest \(OsclSocketMethod &c\)](#)
- [void Send \(const uint8 \\*&aPtr, uint32 aLen\)](#)
- [void Success \(\)](#)
- [uint8 \\* GetSendData \(int32 \\*aLength\)](#)

#### 7.210.1 Constructor & Destructor Documentation

**7.210.1.1 OsclSendRequest::OsclSendRequest (OsclSocketMethod & c) [inline]**

#### 7.210.2 Member Function Documentation

**7.210.2.1 uint8\* OsclSendRequest::GetSendData (int32 \* aLength)**

**7.210.2.2 void OsclSendRequest::Send (const uint8 \*& aPtr, uint32 aLen)**

**7.210.2.3 void OsclSendRequest::Success () [virtual]**

Reimplemented from [OsclSocketRequestAO](#).


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_send.h](#)

## 7.211 OsclSendToMethod Class Reference

```
#include <oscl_socket_send_to.h>
```

Inheritance diagram for OsclSendToMethod:::



### Public Methods

- [~OsclSendToMethod \(\)](#)
- [TPVSocketEvent SendTo \(const uint8 \\*&aPtr, uint32 aLen, OsclNetworkAddress &aAddress, int32 aTimeout\)](#)
- [uint8 \\* GetSendData \(int32 \\*aLength\)](#)
- [OsclSendToRequest \\* SendToRequest \(\)](#)

### Static Public Methods

- [OsclSendToMethod \\* NewL \(OsclIPSocketI &c\)](#)

#### 7.211.1 Constructor & Destructor Documentation

##### 7.211.1.1 OsclSendToMethod::~OsclSendToMethod ()

#### 7.211.2 Member Function Documentation

##### 7.211.2.1 uint8\* OsclSendToMethod::GetSendData (int32 \* aLength)

##### 7.211.2.2 OsclSendToMethod\* OsclSendToMethod::NewL (OsclIPSocketI & c) [static]

##### 7.211.2.3 TPVSocketEvent OsclSendToMethod::SendTo (const uint8 \*& aPtr, uint32 aLen, OsclNetworkAddress & aAddress, int32 aTimeout)

##### 7.211.2.4 OsclSendToRequest\* OsclSendToMethod::SendToRequest () [inline]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_send\\_to.h](#)

## 7.212 OsclSendToRequest Class Reference

```
#include <oscl_socket_send_to.h>
```

Inheritance diagram for OsclSendToRequest::



### Public Methods

- [OsclSendToRequest \(OsclSocketMethod &c\)](#)
- void [SendTo \(const uint8 \\*&aPtr, uint32 aLen, OsclNetworkAddress &aAddress\)](#)
- void [Success \(\)](#)
- uint8 \* [GetSendData \(int32 \\*aLength\)](#)

#### 7.212.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.212.2 Constructor & Destructor Documentation

##### 7.212.2.1 OsclSendToRequest::OsclSendToRequest ([OsclSocketMethod & c](#)) [inline]

#### 7.212.3 Member Function Documentation

##### 7.212.3.1 uint8\* OsclSendToRequest::GetSendData (int32 \* aLength)

##### 7.212.3.2 void OsclSendToRequest::SendTo (const uint8 \*& aPtr, uint32 aLen, [OsclNetworkAddress & aAddress](#))

##### 7.212.3.3 void OsclSendToRequest::Success () [virtual]

Reimplemented from [OsclSocketRequestAO](#).

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_send\\_to.h](#)

## 7.213 OsclSharedPtr< TheClass > Class Template Reference

A parameterized smart pointer class.

```
#include <oscl_shared_ptr.h>
```

### Public Methods

- **OsclSharedPtr ()**  
*Constructor.*
- **OsclSharedPtr (TheClass \*inClassPtr, OsclRefCounter \*in\_refcnt)**  
*Constructor.*
- **OsclSharedPtr (const OsclSharedPtr &inSharedPtr)**  
*Copy constructor.*
- **virtual ~OsclSharedPtr ()**  
*Destructor.*
- **TheClass \* operator → ()**  
• **TheClass & operator \* ()**  
*The indirection operator returns a reference to an object of the parameterized type.*
- **operator TheClass \* ()**  
*Casting operator.*
- **TheClass \* GetRep ()**  
*Use this function to get a pointer to the wrapped object.*
- **OsclRefCounter \* GetRefCounter ()**  
*Get the refcount pointer. This should primarily be used for conversion operations.*
- **int get\_count ()**  
*Get a count of how many references to the object exist.*
- **void Bind (const OsclSharedPtr &inHandle)**  
*Use this function to bind an existing OsclSharedPtr to a already-wrapped object.*
- **void Bind (TheClass \*ptr, OsclRefCounter \*in\_refcnt)**  
*Use this function to bind an existing OsclSharedPtr to a new (unwrapped) object.*
- **void Unbind ()**  
*Use this function of unbind an existing OsclSharedPtr.*
- **OsclSharedPtr & operator= (const OsclSharedPtr &inSharedPtr)**  
*Assignment operator.*
- **bool operator== (const OsclSharedPtr &b) const**  
*Test for equality to see if two PVHandles wrap the same object.*

### 7.213.1 Detailed Description

**template<class TheClass> class OsclSharedPtr< TheClass >**

A parameterized smart pointer class.

### 7.213.2 Constructor & Destructor Documentation

**7.213.2.1 template<class TheClass> OsclSharedPtr< TheClass >::OsclSharedPtr () [inline]**

Constructor.

**7.213.2.2 template<class TheClass> OsclSharedPtr< TheClass >::OsclSharedPtr (TheClass \* *inClassPtr*, OsclRefCounter \* *in\_refcnt*) [inline]**

Constructor.

**Parameters:**

*inClassPtr* A pointer to an instance of the parameterized type that the new OsclSharedPtr will wrap.

**7.213.2.3 template<class TheClass> OsclSharedPtr< TheClass >::OsclSharedPtr (const OsclSharedPtr< TheClass > & *inSharedPtr*) [inline]**

Copy constructor.

**7.213.2.4 template<class TheClass> virtual OsclSharedPtr< TheClass >::~OsclSharedPtr () [inline, virtual]**

Destructor.

### 7.213.3 Member Function Documentation

**7.213.3.1 template<class TheClass> int OsclSharedPtr< TheClass >::get\_count () [inline]**

Get a count of how many references to the object exist.

**7.213.3.2 template<class TheClass> OsclRefCounter\* OsclSharedPtr< TheClass >::GetRefCounter () [inline]**

Get the refcount pointer. This should primarily be used for conversion operations.

**7.213.3.3 template<class TheClass> TheClass\* OsclSharedPtr< TheClass >::GetRep () [inline]**

Use this function to get a pointer to the wrapped object.

**7.213.3.4 template<class TheClass> TheClass& OsclSharedPtr< TheClass >::operator \* () [inline]**

The indirection operator returns a reference to an object of the parameterized type.

**7.213.3.5 template<class TheClass> OsclSharedPtr< TheClass >::operator TheClass \* () [inline]**

Casting operator.

**7.213.3.6 template<class TheClass> TheClass\* OsclSharedPtr< TheClass >::operator -> () [inline]**

The dereferencing operator returns a pointer to the parameterized type and can be used to access member elements of TheClass.

**7.213.3.7 template<class TheClass> OsclSharedPtr& OsclSharedPtr< TheClass >::operator=(const OsclSharedPtr< TheClass > & *inSharedPtr*) [inline]**

Assignment operator.

**7.213.3.8 template<class TheClass> void OsclSharedPtr< TheClass >::Unbind () [inline]**

Use this function of unbind an existing OsclSharedPtr.


The documentation for this class was generated from the following file:

- [oscl\\_shared\\_ptr.h](#)

## 7.214 OsclShutdownMethod Class Reference

```
#include <oscl_socket_shutdown.h>
```

Inheritance diagram for OsclShutdownMethod::



### Public Methods

- `~OsclShutdownMethod ()`
- `TPVSocketEvent Shutdown (TPVSocketShutdown aHow, int32 aTimeout)`
- `OsclShutdownRequest * ShutdownRequest ()`

### Static Public Methods

- `OsclShutdownMethod * NewL (OsclIPSocketI &c)`

#### 7.214.1 Constructor & Destructor Documentation

##### 7.214.1.1 OsclShutdownMethod::~OsclShutdownMethod ()

#### 7.214.2 Member Function Documentation

##### 7.214.2.1 OsclShutdownMethod\* OsclShutdownMethod::NewL (OsclIPSocketI &c) [static]

##### 7.214.2.2 TPVSocketEvent OsclShutdownMethod::Shutdown (TPVSocketShutdown aHow, int32 aTimeout)

##### 7.214.2.3 OsclShutdownRequest\* OsclShutdownMethod::ShutdownRequest () [inline]


The documentation for this class was generated from the following file:

- `oscl_socket_shutdown.h`

## 7.215 OsclShutdownRequest Class Reference

```
#include <oscl_socket_shutdown.h>
```

Inheritance diagram for OsclShutdownRequest::



### Public Methods

- [OsclShutdownRequest \(OsclSocketMethod &c\)](#)
- [void Shutdown \(TPVSocketShutdown aHow\)](#)

#### 7.215.1 Detailed Description

This is the AO that interacts with the socket server

#### 7.215.2 Constructor & Destructor Documentation

**7.215.2.1 OsclShutdownRequest::OsclShutdownRequest ([OsclSocketMethod & c](#)) [inline]**

#### 7.215.3 Member Function Documentation

**7.215.3.1 void OsclShutdownRequest::Shutdown ([TPVSocketShutdown aHow](#))**

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_shutdown.h](#)

## 7.216 OsclSingleton< T, ID, Registry > Class Template Reference

```
#include <oscl_singleton.h>
```

### Public Methods

- `OsclSingleton ()`
- `~OsclSingleton ()`
- `T & operator * () const`

*The indirection operator (\*) accesses a value indirectly, through a pointer.*

- `T * operator -> () const`

*The indirection operator (->) accesses a value indirectly, through a pointer.*

- `bool set ()`

*set() method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.*

### Protected Attributes

- `T * _Ptr`

```
template<class T, uint32 ID, class Registry = OsclSingletonRegistry> class OsclSingleton< T, ID, Registry >
```

#### 7.216.1 Constructor & Destructor Documentation

**7.216.1.1 template<class T, uint32 ID, class Registry = OsclSingletonRegistry> OsclSingleton< T, ID, Registry >::OsclSingleton () [inline]**

**7.216.1.2 template<class T, uint32 ID, class Registry = OsclSingletonRegistry> OsclSingleton< T, ID, Registry >::~OsclSingleton () [inline]**

#### 7.216.2 Member Function Documentation

**7.216.2.1 template<class T, uint32 ID, class Registry = OsclSingletonRegistry> T& OsclSingleton< T, ID, Registry >::operator \* () const [inline]**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the OsclSingleton can be used like the regular pointer that it was initialized with.

**7.216.2.2 template<class T, uint32 ID, class Registry = OsclSingletonRegistry> T\* OsclSingleton< T, ID, Registry >::operator -> () const [inline]**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the OsclSingleton can be used like the regular pointer that it was initialized with.

**7.216.2.3 template<class T, uint32 ID, class Registry = OsclSingletonRegistry> bool OsclSingleton< T, ID, Registry >::set () [inline]**

[set\(\)](#) method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.

### 7.216.3 Field Documentation

**7.216.3.1 template<class T, uint32 ID, class Registry = OsclSingletonRegistry> T\* OsclSingleton< T, ID, Registry >::\_Ptr [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_singleton.h](#)

## 7.217 OsclSingletonRegistry Class Reference

```
#include <oscl_singleton.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF [OsclAny](#) \* getInstance (uint32 ID, int32 &error)
- OSCL\_IMPORT\_REF void registerInstance ([OsclAny](#) \*ptr, uint32 ID, int32 &error)
- OSCL\_IMPORT\_REF [OsclAny](#) \* lockAndGetInstance (uint32 ID, int32 &error)
- OSCL\_IMPORT\_REF void registerInstanceAndUnlock ([OsclAny](#) \*ptr, uint32 ID, int32 &error)

### Friends

- class [OsclBase](#)

#### 7.217.1 Member Function Documentation

**7.217.1.1 OSCL\_IMPORT\_REF [OsclAny](#)\* OsclSingletonRegistry::getInstance (uint32 *ID*, int32 & *error*) [static]**

**7.217.1.2 OSCL\_IMPORT\_REF [OsclAny](#)\* OsclSingletonRegistry::lockAndGetInstance (uint32 *ID*, int32 & *error*) [static]**

**7.217.1.3 OSCL\_IMPORT\_REF void OsclSingletonRegistry::registerInstance ([OsclAny](#) \* *ptr*, uint32 *ID*, int32 & *error*) [static]**

**7.217.1.4 OSCL\_IMPORT\_REF void OsclSingletonRegistry::registerInstanceAndUnlock ([OsclAny](#) \* *ptr*, uint32 *ID*, int32 & *error*) [static]**

#### 7.217.2 Friends And Related Function Documentation

**7.217.2.1 friend class OsclBase [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_singleton.h](#)

## 7.218 OsclSocketI Class Reference

```
#include <oscl_socket_imp_pv.h>
```

Inheritance diagram for OsclSocketI::



### Public Methods

- `~OsclSocketI ()`
- `int32 Open (OsclSocketServI &aServer, uint32 addrFamily, uint32 sockType, uint32 protocol)`
- `int32 Open (OsclSocketServI &aServer)`
- `int32 Bind (OsclNetworkAddress &anAddr)`
- `int32 SetSockOpt (TPVSocketOptionLevel aOptionLevel, TPVSocketOptionName aOptionName, OsclAny *aOptionValue, int32 aOptionLen)`
- `int32 GetPeerName (OsclNetworkAddress &peerName)`
- `int32 Join (OsclNetworkAddress &anAddr)`
- `int32 Close ()`
- `int32 Listen (uint32 qSize)`
- `int32 SetRecvBufferSize (uint32 size)`
- `TPVSocketEvent ThreadLogoff ()`
- `TPVSocketEvent ThreadLogon (OsclSocketServI *aServ)`
- `void Connect (ConnectParam &, OsclSocketRequestAO &)`
- `void Accept (AcceptParam &, OsclSocketRequestAO &)`
- `void Shutdown (ShutdownParam &, OsclSocketRequestAO &)`
- `void Send (SendParam &, OsclSocketRequestAO &)`
- `void SendSuccess (SendParam &)`
- `void SendTo (SendToParam &, OsclSocketRequestAO &)`
- `void SendToSuccess (SendToParam &)`
- `void Recv (RecvParam &, OsclSocketRequestAO &)`
- `void RecvSuccess (RecvParam &)`
- `void RecvFrom (RecvFromParam &, OsclSocketRequestAO &)`
- `void RecvFromSuccess (RecvFromParam &)`
- `TOsclSocket Socket ()`
- `void ProcessConnect (OsclSocketServRequestQElem *)`
- `void ProcessShutdown (OsclSocketServRequestQElem *)`
- `void ProcessAccept (OsclSocketServRequestQElem *)`
- `void ProcessSendTo (OsclSocketServRequestQElem *)`
- `void ProcessRecvFrom (OsclSocketServRequestQElem *)`
- `void ProcessSend (OsclSocketServRequestQElem *)`
- `void ProcessRecv (OsclSocketServRequestQElem *)`
- `PVLogger * Logger ()`

## Static Public Methods

- `OsclSocketI * NewL (Oscl_DefAlloc &a)`
- `bool MakeAddr (OsclNetworkAddress &in, TOsclSockAddr &addr)`
- `void MakeAddr (TOsclSockAddr &in, OsclNetworkAddress &addr)`
- `bool MakeMulticastGroupInformation (OsclIpMReq &in, TIpMReq &addr)`
- `void MakeMulticastGroupInformation (TIpMReq &in, OsclIpMReq &addr)`

## Friends

- class `OsclAcceptRequest`
- class `OsclConnectRequest`
- class `OsclRecvRequest`
- class `OsclRecvFromRequest`
- class `OsclSendRequest`
- class `OsclSendToRequest`
- class `OsclShutdownRequest`
- class `OsclUDPSocket`
- class `OsclTCPSocket`

### 7.218.1 Detailed Description

Socket implementation class

### 7.218.2 Constructor & Destructor Documentation

#### 7.218.2.1 `OsclSocketI::~OsclSocketI ()`

### 7.218.3 Member Function Documentation

#### 7.218.3.1 `void OsclSocketI::Accept (AcceptParam &, OsclSocketRequestAO &) [virtual]`

Implements `OsclSocketIBase`.

#### 7.218.3.2 `int32 OsclSocketI::Bind (OsclNetworkAddress & anAddr) [virtual]`

Implements `OsclSocketIBase`.

#### 7.218.3.3 `int32 OsclSocketI::Close () [virtual]`

Implements `OsclSocketIBase`.

#### 7.218.3.4 `void OsclSocketI::Connect (ConnectParam &, OsclSocketRequestAO &) [virtual]`

Implements `OsclSocketIBase`.

**7.218.3.5 int32 OsclSocketI::GetPeerName ([OsclNetworkAddress](#) & *peerName*)**

**7.218.3.6 int32 OsclSocketI::Join ([OsclNetworkAddress](#) & *anAddr*) [virtual]**

Implements [OsclSocketIBase](#).

**7.218.3.7 int32 OsclSocketI::Listen (uint32 *qSize*) [virtual]**

Implements [OsclSocketIBase](#).

**7.218.3.8 [PVLogger](#)\* OsclSocketI::Logger () [inline]**

**7.218.3.9 void OsclSocketI::MakeAddr ([TOscI\\_SockAddr](#) & *in*, [OsclNetworkAddress](#) & *addr*) [static]**

**7.218.3.10 bool OsclSocketI::MakeAddr ([OsclNetworkAddress](#) & *in*, [TOscI\\_SockAddr](#) & *addr*) [static]**

**7.218.3.11 void OsclSocketI::MakeMulticastGroupInformation ([TIpMReq](#) & *in*, [OsclIpMReq](#) & *addr*) [static]**

**7.218.3.12 bool OsclSocketI::MakeMulticastGroupInformation ([OsclIpMReq](#) & *in*, [TIpMReq](#) & *addr*) [static]**

**7.218.3.13 OsclSocketI\* OsclSocketI::NewL ([Oscl\\_DefAlloc](#) & *a*) [static]**

**7.218.3.14 int32 OsclSocketI::Open ([OsclSocketServI](#) & *aServer*) [virtual]**

Implements [OsclSocketIBase](#).

**7.218.3.15 int32 OsclSocketI::Open ([OsclSocketServI](#) & *aServer*, uint32 *addrFamily*, uint32 *sockType*, uint32 *protocol*) [virtual]**

Implements [OsclSocketIBase](#).

- 7.218.3.16 void OsclSocketI::ProcessAccept ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.17 void OsclSocketI::ProcessConnect ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.18 void OsclSocketI::ProcessRecv ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.19 void OsclSocketI::ProcessRecvFrom ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.20 void OsclSocketI::ProcessSend ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.21 void OsclSocketI::ProcessSendTo ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.22 void OsclSocketI::ProcessShutdown ([OsclSocketServRequestQElem](#) \*)
- 7.218.3.23 void OsclSocketI::Recv ([RecvParam](#) &, [OsclSocketRequestAO](#) &) [virtual]

Implements [OsclSocketIBase](#).

- 7.218.3.24 void OsclSocketI::RecvFrom ([RecvFromParam](#) &, [OsclSocketRequestAO](#) && [virtual])

Implements [OsclSocketIBase](#).

- 7.218.3.25 void OsclSocketI::RecvFromSuccess ([RecvFromParam](#) &) [virtual]

Implements [OsclSocketIBase](#).

- 7.218.3.26 void OsclSocketI::RecvSuccess ([RecvParam](#) &) [virtual]

Implements [OsclSocketIBase](#).

- 7.218.3.27 void OsclSocketI::Send ([SendParam](#) &, [OsclSocketRequestAO](#) &) [virtual]

Implements [OsclSocketIBase](#).

- 7.218.3.28 void OsclSocketI::SendSuccess ([SendParam](#) &) [virtual]

Implements [OsclSocketIBase](#).

- 7.218.3.29 void OsclSocketI::SendTo ([SendToParam](#) &, [OsclSocketRequestAO](#) &) [virtual]

Implements [OsclSocketIBase](#).

- 7.218.3.30 void OsclSocketI::SendToSuccess ([SendToParam](#) &) [virtual]

Implements [OsclSocketIBase](#).

**7.218.3.31** `int32 OsclSocketI::SetRecvBufferSize (uint32 size)`

**7.218.3.32** `int32 OsclSocketI::SetSockOpt (TPVSocketOptionLevel aOptionLevel,  
TPVSocketOptionName aOptionName, OsclAny * aOptionValue, int32 aOptionLen)`

**7.218.3.33** `void OsclSocketI::Shutdown (ShutdownParam &, OsclSocketRequestAO &)`  
[virtual]

Implements [OsclSocketIBase](#).

**7.218.3.34** `TOsclSocket OsclSocketI::Socket () [inline]`

**7.218.3.35** `TPVSocketEvent OsclSocketI::ThreadLogoff ()`

**7.218.3.36** `TPVSocketEvent OsclSocketI::ThreadLogon (OsclSocketServI * aServ)`

## 7.218.4 Friends And Related Function Documentation

**7.218.4.1** `friend class OsclAcceptRequest [friend]`

**7.218.4.2** `friend class OsclConnectRequest [friend]`

**7.218.4.3** `friend class OsclRecvFromRequest [friend]`

**7.218.4.4** `friend class OsclRecvRequest [friend]`

**7.218.4.5** `friend class OsclSendRequest [friend]`

**7.218.4.6** `friend class OsclSendToRequest [friend]`

**7.218.4.7** `friend class OsclShutdownRequest [friend]`

**7.218.4.8** `friend class OsclTCPSocket [friend]`

Reimplemented from [OsclSocketIBase](#).

**7.218.4.9** `friend class OsclUDPSocket [friend]`

Reimplemented from [OsclSocketIBase](#).


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_imp\\_pv.h](#)

## 7.219 OsclSocketIBase Class Reference

```
#include <oscl_socket_imp_base.h>
```

Inheritance diagram for OsclSocketIBase::



### Public Methods

- virtual ~OsclSocketIBase ()
- virtual int32 Open (OsclSocketServI &aServer, uint32 addrFamily, uint32 sockType, uint32 proto-col)=0
- virtual int32 Open (OsclSocketServI &aServer)=0
- virtual int32 Bind (OsclNetworkAddress &anAddr)=0
- virtual int32 Join (OsclNetworkAddress &anAddr)=0
- virtual int32 Close ()=0
- virtual int32 Listen (uint32 qSize)=0
- virtual void Connect (ConnectParam &, OsclSocketRequestAO &)=0
- virtual void Accept (AcceptParam &, OsclSocketRequestAO &)=0
- virtual void Shutdown (ShutdownParam &, OsclSocketRequestAO &)=0
- virtual void Send (SendParam &, OsclSocketRequestAO &)=0
- virtual void SendSuccess (SendParam &)=0
- virtual void SendTo (SendToParam &, OsclSocketRequestAO &)=0
- virtual void SendToSuccess (SendToParam &)=0
- virtual void Recv (RecvParam &, OsclSocketRequestAO &)=0
- virtual void RecvSuccess (RecvParam &)=0
- virtual void RecvFrom (RecvFromParam &, OsclSocketRequestAO &)=0
- virtual void RecvFromSuccess (RecvFromParam &)=0
- virtual void BindAsync (BindParam &, OsclSocketRequestAO &)
- virtual void ListenAsync (ListenParam &, OsclSocketRequestAO &)
- void CancelFxn (TPVSocketFxn)

### Static Public Methods

- bool HasAsyncBind ()
- bool HasAsyncListen ()

### Protected Methods

- OsclSocketIBase (Oscl\_DefAlloc &a)
- virtual void CancelConnect ()=0
- virtual void CancelAccept ()=0
- virtual void CancelShutdown ()=0
- virtual void CancelSend ()=0

- virtual void [CancelSendTo \(\)=0](#)
- virtual void [CancelRecv \(\)=0](#)
- virtual void [CancelRecvFrom \(\)=0](#)
- virtual void [CancelBind \(\)](#)
- virtual void [CancelListen \(\)](#)
- virtual bool [IsOpen \(\)=0](#)

## Static Protected Methods

- int [GetShutdown \(TPVSocketShutdown aOsclVal\)](#)

## Protected Attributes

- [Oscl\\_DefAlloc & iAlloc](#)
- [OsclSocketServI \\* iSocketServ](#)

## Friends

- class [OsclSocketRequest](#)
- class [OsclSocketMethod](#)
- class [OsclSocketRequestAO](#)
- class [OsclUDPSocket](#)
- class [OsclTCPSocket](#)

### 7.219.1 Detailed Description

Socket implementation base class

### 7.219.2 Constructor & Destructor Documentation

**7.219.2.1** virtual OsclSocketIBase::~OsclSocketIBase () [virtual]

**7.219.2.2** OsclSocketIBase::OsclSocketIBase ([Oscl\\_DefAlloc & a](#)) [protected]

### 7.219.3 Member Function Documentation

**7.219.3.1** virtual void OsclSocketIBase::Accept ([AcceptParam &](#), [OsclSocketRequestAO &](#)) [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.2** virtual int32 OsclSocketIBase::Bind ([OsclNetworkAddress & anAddr](#)) [pure virtual]

Implemented in [OsclSocketI](#).

- 7.219.3.3 **virtual void OsclSocketIBase::BindAsync ([BindParam](#) &, [OsclSocketRequestAO](#) &)**  
[inline, virtual]
- 7.219.3.4 **virtual void OsclSocketIBase::CancelAccept ()** [protected, pure virtual]
- 7.219.3.5 **virtual void OsclSocketIBase::CancelBind ()** [inline, protected, virtual]
- 7.219.3.6 **virtual void OsclSocketIBase::CancelConnect ()** [protected, pure virtual]
- 7.219.3.7 **void OsclSocketIBase::CancelFxn ([TPVSocketFxn](#))**
- 7.219.3.8 **virtual void OsclSocketIBase::CancelListen ()** [inline, protected, virtual]
- 7.219.3.9 **virtual void OsclSocketIBase::CancelRecv ()** [protected, pure virtual]
- 7.219.3.10 **virtual void OsclSocketIBase::CancelRecvFrom ()** [protected, pure virtual]
- 7.219.3.11 **virtual void OsclSocketIBase::CancelSend ()** [protected, pure virtual]
- 7.219.3.12 **virtual void OsclSocketIBase::CancelSendTo ()** [protected, pure virtual]
- 7.219.3.13 **virtual void OsclSocketIBase::CancelShutdown ()** [protected, pure virtual]
- 7.219.3.14 **virtual int32 OsclSocketIBase::Close ()** [pure virtual]

Implemented in [OsclSocketI](#).

- 7.219.3.15 **virtual void OsclSocketIBase::Connect ([ConnectParam](#) &, [OsclSocketRequestAO](#) &)**  
[pure virtual]

Implemented in [OsclSocketI](#).

- 7.219.3.16 **int OsclSocketIBase::GetShutdown ([TPVSocketShutdown](#) aOsclVal)** [static,  
protected]
- 7.219.3.17 **bool OsclSocketIBase::HasAsyncBind ()** [static]
- 7.219.3.18 **bool OsclSocketIBase::HasAsyncListen ()** [static]
- 7.219.3.19 **virtual bool OsclSocketIBase::IsOpen ()** [protected, pure virtual]
- 7.219.3.20 **virtual int32 OsclSocketIBase::Join ([OsclNetworkAddress](#) & anAddr)** [pure  
virtual]

Implemented in [OsclSocketI](#).

- 7.219.3.21 **virtual int32 OsclSocketIBase::Listen (uint32 qSize)** [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.22** `virtual void OsclSocketIBase::ListenAsync (ListenParam &, OsclSocketRequestAO &)`  
[inline, virtual]

**7.219.3.23** `virtual int32 OsclSocketIBase::Open (OsclSocketServI & aServer)` [pure  
virtual]

Implemented in [OsclSocketI](#).

**7.219.3.24** `virtual int32 OsclSocketIBase::Open (OsclSocketServI & aServer, uint32 addrFamily,  
uint32 sockType, uint32 protocol)` [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.25** `virtual void OsclSocketIBase::Recv (RecvParam &, OsclSocketRequestAO &)` [pure  
virtual]

Implemented in [OsclSocketI](#).

**7.219.3.26** `virtual void OsclSocketIBase::RecvFrom (RecvFromParam &, OsclSocketRequestAO  
&)` [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.27** `virtual void OsclSocketIBase::RecvFromSuccess (RecvFromParam &)` [pure  
virtual]

Implemented in [OsclSocketI](#).

**7.219.3.28** `virtual void OsclSocketIBase::RecvSuccess (RecvParam &)` [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.29** `virtual void OsclSocketIBase::Send (SendParam &, OsclSocketRequestAO &)` [pure  
virtual]

Implemented in [OsclSocketI](#).

**7.219.3.30** `virtual void OsclSocketIBase::SendSuccess (SendParam &)` [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.31** `virtual void OsclSocketIBase::SendTo (SendToParam &, OsclSocketRequestAO &)`  
[pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.32 virtual void OsclSocketIBase::SendToSuccess ([SendToParam](#) &)** [pure virtual]

Implemented in [OsclSocketI](#).

**7.219.3.33 virtual void OsclSocketIBase::Shutdown ([ShutdownParam](#) &, [OsclSocketRequestAO](#) &)** [pure virtual]

Implemented in [OsclSocketI](#).

## 7.219.4 Friends And Related Function Documentation

**7.219.4.1 friend class OsclSocketMethod** [friend]

**7.219.4.2 friend class OsclSocketRequest** [friend]

**7.219.4.3 friend class OsclSocketRequestAO** [friend]

**7.219.4.4 friend class OsclTCPSocket** [friend]

Reimplemented in [OsclSocketI](#).

**7.219.4.5 friend class OsclUDPSocket** [friend]

Reimplemented in [OsclSocketI](#).

## 7.219.5 Field Documentation

**7.219.5.1 [Oscl\\_DefAlloc](#)& OsclSocketIBase::iAlloc** [protected]

**7.219.5.2 [OsclSocketServI](#)\* OsclSocketIBase::iSocketServ** [protected]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_imp\\_base.h](#)

## 7.220 OsclSocketMethod Class Reference

```
#include <oscl_socket_method.h>
```

Inheritance diagram for OsclSocketMethod::



### Public Methods

- [OsclSocketMethod \(OsclIPSocketI &aContainer, const char \\*name, TPVSocketFxn fxn\)](#)
- virtual [~OsclSocketMethod \(\)](#)
- void [Abort \(\)](#)
- void [AbortAll \(\)](#)
- void [CancelMethod \(\)](#)
- [Oscl\\_DefAlloc & Alloc \(\)](#)
- [TPVSocketEvent ThreadLogon \(\)](#)
- [TPVSocketEvent ThreadLogoff \(\)](#)

### Data Fields

- [OsclIPSocketI & iContainer](#)
- [TPVSocketFxn iSocketFxn](#)

## Protected Methods

- void [ConstructL \(OsclSocketRequestAO \\*aAO\)](#)
- bool [StartMethod \(int32 aTimeoutMsec\)](#)
- void [MethodDone \(\)](#)
- void [Run \(\)](#)

## Protected Attributes

- [OsclSocketRequestAO \\* iSocketRequestAO](#)

### 7.220.1 Detailed Description

OsclSocketMethod is the base class for all socket methods. Two AOs are required for each socket operation— one to provide a timeout, and one to detect request completion. The OsclSocketMethod class implements the timeout and contains the request completion AO.

### 7.220.2 Constructor & Destructor Documentation

**7.220.2.1 OsclSocketMethod::OsclSocketMethod** ([OsclIPSocketI & aContainer](#), [const char \\* name](#), [TPVSocketFxn ffn](#)) [inline]

**7.220.2.2 virtual OsclSocketMethod::~OsclSocketMethod ()** [inline, virtual]

### 7.220.3 Member Function Documentation

**7.220.3.1 void OsclSocketMethod::Abort ()** [inline]

**7.220.3.2 void OsclSocketMethod::AbortAll ()** [inline]

**7.220.3.3 Oscl\_DefAlloc& OsclSocketMethod::Alloc ()** [inline]

**7.220.3.4 void OsclSocketMethod::CancelMethod ()** [inline]

**7.220.3.5 void OsclSocketMethod::ConstructL (OsclSocketRequestAO \* aAO)** [inline, protected]

**7.220.3.6 void OsclSocketMethod::MethodDone ()** [inline, protected]

**7.220.3.7 void OsclSocketMethod::Run ()** [protected, virtual]

Handles an active object's request completion event.

A derived class must provide an implementation to handle the completed request. If appropriate, it may issue another request.

The function is called by the active scheduler when a request completion event occurs, i.e. after the active scheduler's `WaitForAnyRequest()` function completes.

Before calling this active object's `Run()` function, the active scheduler has:

1. decided that this is the highest priority active object with a completed request

2. marked this active object's request as complete (i.e. the request is no longer outstanding)

[Run\(\)](#) runs under a trap harness in the active scheduler. If it leaves, then the active scheduler calls [ExecError\(\)](#) to handle the leave.

Note that once the active scheduler's [Start\(\)](#) function has been called, all user code is run under one of the program's active object's [Run\(\)](#) or [RunError\(\)](#) functions.

Implements [PVActiveBase](#).

**7.220.3.8 bool OsclSocketMethod::StartMethod (int32 *aTimeoutMsec*) [protected]**

**7.220.3.9 TPVSocketEvent OsclSocketMethod::ThreadLogoff ()**

**7.220.3.10 TPVSocketEvent OsclSocketMethod::ThreadLogon ()**

## 7.220.4 Field Documentation

**7.220.4.1 OsclIPSocketI& OsclSocketMethod::iContainer**

**7.220.4.2 TPVSocketFxn OsclSocketMethod::iSocketFxn**

**7.220.4.3 OsclSocketRequestAO\* OsclSocketMethod::iSocketRequestAO [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_method.h](#)

## 7.221 OsclSocketObserver Class Reference

```
#include <oscl_socket_types.h>
```

### Public Methods

- virtual OSCL\_IMPORT\_REF void [HandleSocketEvent](#) (int32 *aId*, [TPVSocketFxn](#) *aFxn*, [TPVSocketEvent](#) *aEvent*, int32 *aError*)=0
- virtual ~[OsclSocketObserver](#) ()

#### 7.221.1 Detailed Description

Socket event observer. The client implements this to get asynchronous command completion.

#### 7.221.2 Constructor & Destructor Documentation

7.221.2.1 virtual [OsclSocketObserver::~OsclSocketObserver](#) () [inline, virtual]

#### 7.221.3 Member Function Documentation

7.221.3.1 virtual OSCL\_IMPORT\_REF void [OsclSocketObserver::HandleSocketEvent](#) (int32 *aId*, [TPVSocketFxn](#) *aFxn*, [TPVSocketEvent](#) *aEvent*, int32 *aError*) [pure virtual]

Socket Event callback.

##### Parameters:

*aId*: The ID that was supplied when the socket was created.

*aFxn*: Type of socket function call.

*aEvent*: Function completion event. Will be EPVSocketSuccess, EPVSocketTimeout, or EPVSocketFailure.

*aError*: When the event is EPVSocketFailure, this may contain a platform-specific error code, or zero if none is available.

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_types.h](#)

## 7.222 OsclSocketRequest Class Reference

```
#include <oscl_socket_request.h>
```

### Public Methods

- [OsclSocketRequest \(\)](#)
- [TPVSocketFxn Fxn \(\)](#)
- void [CancelRequest \(\)](#)
- void [Activate \(SocketRequestParam \\*iParam, OsclSocketRequestAO &a\)](#)
- void [Complete \(OsclSocketServRequestQElem \\*, int32 aStatus, int32 aSockErr=0\)](#)

### Data Fields

- [OsclSocketRequestAO \\* iSocketRequestAO](#)
- [SocketRequestParam \\* iParam](#)
- [OsclSocketI \\* iSocketI](#)

#### 7.222.1 Detailed Description

This class defines the request interface to the PV socket server.

#### 7.222.2 Constructor & Destructor Documentation

##### 7.222.2.1 [OsclSocketRequest::OsclSocketRequest \(\) \[inline\]](#)

#### 7.222.3 Member Function Documentation

##### 7.222.3.1 [void OsclSocketRequest::Activate \(SocketRequestParam \\* iParam, OsclSocketRequestAO & a\)](#)

##### 7.222.3.2 [void OsclSocketRequest::CancelRequest \(\)](#)

##### 7.222.3.3 [void OsclSocketRequest::Complete \(OsclSocketServRequestQElem \\*, int32 aStatus, int32 aSockErr = 0\)](#)

##### 7.222.3.4 [TPVSocketFxn OsclSocketRequest::Fxn \(\) \[inline\]](#)

#### 7.222.4 Field Documentation

##### 7.222.4.1 [SocketRequestParam\\* OsclSocketRequest::iParam](#)

##### 7.222.4.2 [OsclSocketI\\* OsclSocketRequest::iSocketI](#)

##### 7.222.4.3 [OsclSocketRequestAO\\* OsclSocketRequest::iSocketRequestAO](#)


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.223 OsclSocketRequestAO Class Reference

```
#include <oscl_socket_method.h>
```

Inheritance diagram for OsclSocketRequestAO::



### Public Methods

- void [ConstructL \(\)](#)

### Protected Methods

- [OsclSocketRequestAO \(OsclSocketMethod &aContainer, const char \\*name\)](#)
- virtual [~OsclSocketRequestAO \(\)](#)
- [OsclAny \\* NewRequest \(const uint32 size\)](#)
- void [CleanupParam \(bool deallocate=false\)](#)
- void [Abort \(\)](#)
- void [RequestDone \(\)](#)
- int [GetSocketError \(\)](#)
- void [DoCancel \(\)](#)
- void [Run \(\)](#)

- virtual void [Success \(\)](#)
- [OsclSocketI \\* SocketI \(\)](#)
- [OsclSocketObserver \\* SocketObserver \(\)](#)
- uint32 [Id \(\)](#)
- [Oscl\\_DefAlloc & Alloc \(\)](#)

## Protected Attributes

- [OsclSocketMethod & iContainer](#)
- int32 [iSocketError](#)
- [SocketRequestParam \\* iParam](#)
- uint32 [iParamSize](#)

## Friends

- class [OsclSocketI](#)
- class [OsclSocketMethod](#)
- class [OsclSocketRequest](#)

### 7.223.1 Detailed Description

This is the base class for all the AOs that interact with the socket server. This object is contained within an [OsclSocketMethod](#) object

### 7.223.2 Constructor & Destructor Documentation

**7.223.2.1 OsclSocketRequestAO::OsclSocketRequestAO ([OsclSocketMethod & aContainer](#), const char \* *name*) [inline, protected]**

**7.223.2.2 virtual OsclSocketRequestAO::~OsclSocketRequestAO () [inline, protected, virtual]**

### 7.223.3 Member Function Documentation

**7.223.3.1 void OsclSocketRequestAO::Abort () [inline, protected]**

**7.223.3.2 [Oscl\\_DefAlloc& OsclSocketRequestAO::Alloc \(\) \[inline, protected\]](#)**

**7.223.3.3 void OsclSocketRequestAO::CleanupParam (bool *deallocate* = false) [protected]**

**7.223.3.4 void OsclSocketRequestAO::ConstructL () [inline]**

**7.223.3.5 void OsclSocketRequestAO::DoCancel () [inline, protected, virtual]**

Cancel request handler. This gets called by scheduler when the request is cancelled. The default routine will complete the request. If any additional action is needed, the derived class may override this. If the derived class does override DoCancel, it must complete the request.

Reimplemented from [OsclActiveObject](#).

**7.223.3.6 int OsclSocketRequestAO::GetSocketError () [inline, protected]**

**7.223.3.7 uint32 OsclSocketRequestAO::Id () [inline, protected]**

**7.223.3.8 OsclAny\* OsclSocketRequestAO::NewRequest (const uint32 *size*) [protected]**

**7.223.3.9 void OsclSocketRequestAO::RequestDone () [inline, protected]**

**7.223.3.10 void OsclSocketRequestAO::Run () [protected, virtual]**

Handles an active object's request completion event.

A derived class must provide an implementation to handle the completed request. If appropriate, it may issue another request.

The function is called by the active scheduler when a request completion event occurs, i.e. after the active scheduler's WaitForAnyRequest() function completes.

Before calling this active object's Run() function, the active scheduler has:

1. decided that this is the highest priority active object with a completed request
2. marked this active object's request as complete (i.e. the request is no longer outstanding)

Run() runs under a trap harness in the active scheduler. If it leaves, then the active scheduler calls ExecError() to handle the leave.

Note that once the active scheduler's Start() function has been called, all user code is run under one of the program's active object's Run() or RunError() functions.

Implements [PVActiveBase](#).

**7.223.3.11 OsclSocketI\* OsclSocketRequestAO::SocketI () [inline, protected]**

**7.223.3.12 OsclSocketObserver\* OsclSocketRequestAO::SocketObserver () [inline, protected]**

**7.223.3.13 virtual void OsclSocketRequestAO::Success () [inline, protected, virtual]**

Reimplemented in [OsclRecvRequest](#), [OsclRecvFromRequest](#), [OsclSendRequest](#), and [OsclSendToRequest](#).

## 7.223.4 Friends And Related Function Documentation

7.223.4.1 **friend class OsclSocketI** [friend]

7.223.4.2 **friend class OsclSocketMethod** [friend]

7.223.4.3 **friend class OsclSocketRequest** [friend]

## 7.223.5 Field Documentation

7.223.5.1 **OsclSocketMethod& OsclSocketRequestAO::iContainer** [protected]

7.223.5.2 **SocketRequestParam\* OsclSocketRequestAO::iParam** [protected]

7.223.5.3 **uint32 OsclSocketRequestAO::iParamSize** [protected]

7.223.5.4 **int32 OsclSocketRequestAO::iSocketError** [protected]


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_method.h](#)

## 7.224 OsclSocketServ Class Reference

```
#include <oscl_socket.h>
```

Inheritance diagram for OsclSocketServ::



### Public Methods

- OSCL\_IMPORT\_REF ~OsclSocketServ ()
- OSCL\_IMPORT\_REF int32 Connect (uint32 aMessageSlots=8, bool aShareSession=false)
- OSCL\_IMPORT\_REF void Close (bool aCleanup=true)

### Static Public Methods

- OSCL\_IMPORT\_REF OsclSocketServ \* NewL (Oscl\_DefAlloc &alloc)

### Friends

- class OsclTCPSocket
- class OsclUDPSocket
- class OsclDNS

#### 7.224.1 Constructor & Destructor Documentation

##### 7.224.1.1 OSCL\_IMPORT\_REF OsclSocketServ::~OsclSocketServ ()

Destructor. The server object must be deleted using the same allocator used in the NewL call.

#### 7.224.2 Member Function Documentation

##### 7.224.2.1 OSCL\_IMPORT\_REF void OsclSocketServ::Close (bool aCleanup = true)

Close socket server. This is a synchronous method.

#### Parameters:

*aCleanup*: cleanup the socket system? the socket cleanup should only be done when all parts of the application are done using sockets.

**7.224.2.2 OSCL\_IMPORT\_REF int32 OsclSocketServ::Connect (uint32 *aMessageSlots* = 8, bool *aShareSession* = false)**

Connect to socket server. This is a synchronous method.

**Parameters:**

*Number* of message slots.

**Returns:**

Returns OsclErrNone for success, or a platform-specific code.

**7.224.2.3 OSCL\_IMPORT\_REF OsclSocketServ\* OsclSocketServ::NewL (Oscl\_DefAlloc & *alloc*)  
[static]**

Create a socket server. May leave if failure.

**Parameters:**

*alloc*: Memory allocator.

**Returns:**

Returns pointer to socket server

**7.224.3 Friends And Related Function Documentation****7.224.3.1 friend class OsclDNS [friend]****7.224.3.2 friend class OsclTCPSocket [friend]****7.224.3.3 friend class OsclUDPSocket [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_socket.h](#)

## 7.225 OsclSocketServI Class Reference

```
#include <oscl_socket_serv_imp_pv.h>
```

Inheritance diagram for OsclSocketServI::



### Public Methods

- int32 [Connect](#) (uint32 aMessageSlots, bool aShareSession)
- void [Close](#) (bool)
- bool [IsServerThread](#) ()

### Static Public Methods

- OsclSocketServI \* [NewL](#) (Oscl\_DefAlloc &a)

### Friends

- class [OsclSocketServRequestList](#)
- class [LoopbackSocket](#)
- class [OsclTCPSocketI](#)
- class [OsclUDPSocketI](#)
- class [OsclSocketI](#)
- class [OsclDNSI](#)
- class [OsclSocketRequest](#)
- class [OsclSocketServ](#)

### 7.225.1 Detailed Description

PV socket server implementation

### 7.225.2 Member Function Documentation

#### 7.225.2.1 void OsclSocketServI::Close (bool) [virtual]

Implements [OsclSocketServIBase](#).

**7.225.2.2 int32 OsclSocketServI::Connect (uint32 *aMessageSlots*, bool *aShareSession*)**  
[virtual]

Implements [OsclSocketServIBase](#).

**7.225.2.3 bool OsclSocketServI::IsServerThread ()**

**7.225.2.4 OsclSocketServI\* OsclSocketServI::NewL ([Oscl\\_DefAlloc](#) & *a*) [static]**

### 7.225.3 Friends And Related Function Documentation

**7.225.3.1 friend class LoopbackSocket [friend]**

**7.225.3.2 friend class OsclDNSI [friend]**

**7.225.3.3 friend class OsclSocketI [friend]**

**7.225.3.4 friend class OsclSocketRequest [friend]**

**7.225.3.5 friend class OsclSocketServ [friend]**

**7.225.3.6 friend class OsclSocketServRequestList [friend]**

**7.225.3.7 friend class OsclTCPSocketI [friend]**

**7.225.3.8 friend class OsclUDPSocketI [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_serv\\_imp\\_pv.h](#)

## 7.226 OsclSocketServIBase Class Reference

```
#include <oscl_socket_serv_imp_base.h>
```

Inheritance diagram for OsclSocketServIBase::



### Public Methods

- virtual ~[OsclSocketServIBase](#) ()
- virtual int32 [Connect](#) (uint32 aMessageSlots, bool aShareSession)=0
- virtual void [Close](#) (bool)=0

### Data Fields

- [PVLogger \\* iLogger](#)

### Protected Types

- enum [TSocketServState](#) { [ESocketServ\\_Idle](#), [ESocketServ\\_Connected](#), [ESocketServ\\_Error](#) }

### Protected Methods

- [OsclSocketServIBase \(Oscl\\_DefAlloc &a\)](#)
- [TSocketServState State \(\) const](#)
- [bool IsServConnected \(\) const](#)

### Protected Attributes

- [Oscl\\_DefAlloc & iAlloc](#)
- [TSocketServState iServState](#)
- [int iServError](#)

### 7.226.1 Detailed Description

Base class common to all implementations

### 7.226.2 Member Enumeration Documentation

#### 7.226.2.1 enum OsclSocketServIBase::TSocketServState [protected]

Enumeration values:

[ESocketServ\\_Idle](#)

**ESocketServ\_Connected**

**ESocketServ\_Error**

### 7.226.3 Constructor & Destructor Documentation

**7.226.3.1 virtual OsclSocketServIBase::~OsclSocketServIBase () [inline, virtual]**

**7.226.3.2 OsclSocketServIBase::OsclSocketServIBase ([Oscl\\_DefAlloc](#) & *a*) [inline, protected]**

### 7.226.4 Member Function Documentation

**7.226.4.1 virtual void OsclSocketServIBase::Close (bool) [pure virtual]**

Implemented in [OsclSocketServI](#).

**7.226.4.2 virtual int32 OsclSocketServIBase::Connect (uint32 *aMessageSlots*, bool *aShareSession*) [pure virtual]**

Implemented in [OsclSocketServI](#).

**7.226.4.3 bool OsclSocketServIBase::IsServConnected () const [inline, protected]**

**7.226.4.4 [TSocketServState](#) OsclSocketServIBase::State () const [inline, protected]**

### 7.226.5 Field Documentation

**7.226.5.1 [Oscl\\_DefAlloc](#)& OsclSocketServIBase::iAlloc [protected]**

**7.226.5.2 [PVLogger](#)\* OsclSocketServIBase::iLogger**

**7.226.5.3 int OsclSocketServIBase::iServerError [protected]**

**7.226.5.4 [TSocketServState](#) OsclSocketServIBase::iServState [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_serv\\_imp\\_base.h](#)

## 7.227 OsclSocketServRequestList Class Reference

```
#include <oscl_socket_serv_imp_reqlist.h>
```

### Public Methods

- [OsclSocketServRequestList \(\)](#)
- [void Add \(OsclSocketRequest \\*\)](#)
- [void StartCancel \(OsclSocketRequest \\*\)](#)
- [void Open \(OsclSocketServI \\*s\)](#)
- [void Close \(\)](#)
- [void Wakeup \(\)](#)
- [void WaitOnRequests \(\)](#)
- [void Remove \(OsclSocketServRequestQElem \\*aElem\)](#)

### Friends

- class [OsclSocketServI](#)

### 7.227.1 Detailed Description

PV socket server request queue

### 7.227.2 Constructor & Destructor Documentation

#### 7.227.2.1 OsclSocketServRequestList::OsclSocketServRequestList ()

### 7.227.3 Member Function Documentation

#### 7.227.3.1 void OsclSocketServRequestList::Add ([OsclSocketRequest \\*](#))

#### 7.227.3.2 void OsclSocketServRequestList::Close ()

#### 7.227.3.3 void OsclSocketServRequestList::Open ([OsclSocketServI \\* s](#))

#### 7.227.3.4 void OsclSocketServRequestList::Remove ([OsclSocketServRequestQElem \\* aElem](#)) [inline]

#### 7.227.3.5 void OsclSocketServRequestList::StartCancel ([OsclSocketRequest \\*](#))

#### 7.227.3.6 void OsclSocketServRequestList::WaitOnRequests ()

#### 7.227.3.7 void OsclSocketServRequestList::Wakeup ()

### 7.227.4 Friends And Related Function Documentation

#### 7.227.4.1 friend class OsclSocketServI [friend]

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_serv\\_imp\\_reqlist.h](#)

## 7.228 OsclSocketServRequestQElem Class Reference

```
#include <oscl_socket_serv_imp_reqlist.h>
```

### Public Methods

- [OsclSocketServRequestQElem \(OsclSocketRequest \\*r\)](#)

### Data Fields

- [OsclSocketRequest \\* iSocketRequest](#)
- [uint8 iSelect](#)
- [bool iCancel](#)

#### 7.228.1 Constructor & Destructor Documentation

7.228.1.1 [OsclSocketServRequestQElem::OsclSocketServRequestQElem \(OsclSocketRequest \\* r\)](#)  
[inline]

#### 7.228.2 Field Documentation

7.228.2.1 [bool OsclSocketServRequestQElem::iCancel](#)

7.228.2.2 [uint8 OsclSocketServRequestQElem::iSelect](#)

7.228.2.3 [OsclSocketRequest\\* OsclSocketServRequestQElem::iSocketRequest](#)

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_serv\\_imp\\_reqlist.h](#)

## 7.229 OsclSocketTOS Class Reference

```
#include <oscl_socket_types.h>
```

### Public Types

- enum **TPVServicePrecedence** { **EPVRoutine** = 0, **EPVPriority** = 1, **EPVImmediate** = 2, **EPVFlash** = 3, **EPVOverrideFlash** = 4, **EPVCritic\_Ecp** = 5, **EPVInetControl** = 6, **EPVNetControl** = 7 }
- enum **TPVServicePriority** { **EPVNoTOS** = 0x0, **EPVLDelay** = (1 << 4), **EPVHiThrpt** = (1 << 3), **EPVHiRel** = (1 << 2) }

### Public Methods

- **OsclSocketTOS ()**
- void **SetPrecedence** (**TPVServicePrecedence** aPrecedence)
- void **SetPriority** (bool aMinimizeDelay, bool aMaximizeThroughput, bool MaximizeReliability)
- void **ClearTOS ()**
- uint8 **GetTOS ()** const

### 7.229.1 Member Enumeration Documentation

#### 7.229.1.1 enum OsclSocketTOS::TPVServicePrecedence

Enumeration values:

**EPVRoutine**  
**EPVPriority**  
**EPVImmediate**  
**EPVFlash**  
**EPVOverrideFlash**  
**EPVCritic\_Ecp**  
**EPVInetControl**  
**EPVNetControl**

#### 7.229.1.2 enum OsclSocketTOS::TPVServicePriority

Enumeration values:

**EPVNoTOS**  
**EPVLDelay**  
**EPVHiThrpt**  
**EPVHiRel**

## 7.229.2 Constructor & Destructor Documentation

7.229.2.1 `OsclSocketTOS::OsclSocketTOS () [inline]`

## 7.229.3 Member Function Documentation

7.229.3.1 `void OsclSocketTOS::ClearTOS () [inline]`

7.229.3.2 `uint8 OsclSocketTOS::GetTOS () const [inline]`

7.229.3.3 `void OsclSocketTOS::SetPrecedence (TPVServicePrecedence aPrecedence) [inline]`

7.229.3.4 `void OsclSocketTOS::SetPriority (bool aMinimizeDelay, bool aMaximizeThroughput, bool MaximizeReliability) [inline]`


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_types.h](#)

## 7.230 OsclTCPSocket Class Reference

```
#include <oscl_socket.h>
```

Inheritance diagram for OsclTCPSocket::



### Public Methods

- OSCL\_IMPORT\_REF ~OsclTCPSocket ()
- OSCL\_IMPORT\_REF TPVSocketEvent ThreadLogoff ()
- OSCL\_IMPORT\_REF TPVSocketEvent ThreadLogon (OsclSocketServ &aServ, OsclSocketObserver \*aObserver)
- OSCL\_IMPORT\_REF int32 Close ()
- OSCL\_IMPORT\_REF int32 Bind (OsclNetworkAddress &aAddress)
- OSCL\_IMPORT\_REF TPVSocketEvent BindAsync (OsclNetworkAddress &aAddress, int32 aTimeoutMsec=(-1))
- OSCL\_IMPORT\_REF void CancelBind ()
- OSCL\_IMPORT\_REF int32 SetOptionToReuseAddress ()
- OSCL\_IMPORT\_REF int32 SetTOS (const OsclSocketTOS &aTOS)
- OSCL\_IMPORT\_REF int32 GetPeerName (OsclNetworkAddress &aPeerName)
- OSCL\_IMPORT\_REF int32 Listen (int32 aQueueSize)
- OSCL\_IMPORT\_REF TPVSocketEvent ListenAsync (int32 aQueueSize, int32 aTimeoutMsec=(-1))
- OSCL\_IMPORT\_REF void CancelListen ()
- OSCL\_IMPORT\_REF OsclTCPSocket \* GetAcceptedSocketL (uint32 aId)
- OSCL\_IMPORT\_REF uint8 \* GetRecvData (int32 \*aLength)
- OSCL\_IMPORT\_REF uint8 \* GetSendData (int32 \*aLength)
- OSCL\_IMPORT\_REF TPVSocketEvent Connect (OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1)
- OSCL\_IMPORT\_REF void CancelConnect ()
- OSCL\_IMPORT\_REF TPVSocketEvent Shutdown (TPVSocketShutdown aHow, int32 aTimeoutMsec=-1)
- OSCL\_IMPORT\_REF void CancelShutdown ()
- OSCL\_IMPORT\_REF TPVSocketEvent Accept (int32 aTimeout=-1)
- OSCL\_IMPORT\_REF void CancelAccept ()
- OSCL\_IMPORT\_REF TPVSocketEvent Send (const uint8 \*aPtr, uint32 aLen, int32 aTimeoutMsec=-1)
- OSCL\_IMPORT\_REF void CancelSend ()
- OSCL\_IMPORT\_REF TPVSocketEvent Recv (uint8 \*aPtr, uint32 aMaxLen, int32 aTimeoutMsec=-1)
- OSCL\_IMPORT\_REF void CancelRecv ()

## Static Public Methods

- OSCL\_IMPORT\_REF OsclTCPSocket \* **NewL** (Oscl\_DefAlloc &alloc, OsclSocketServ &aServ, OsclSocketObserver \*aObserver, uint32 aId)

### 7.230.1 Detailed Description

The TCP Socket class

### 7.230.2 Constructor & Destructor Documentation

#### 7.230.2.1 OSCL\_IMPORT\_REF OsclTCPSocket::~OsclTCPSocket ()

Destructor. The object must be deleted using the same allocator used in the NewL call.

### 7.230.3 Member Function Documentation

#### 7.230.3.1 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::Accept (int32 aTimeout = -1)

Accept incoming connections. This is an asynchronous method.

**Parameters:**

*aTimeoutMsec*: Timeout in milliseconds, or (-1) for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

#### 7.230.3.2 OSCL\_IMPORT\_REF int32 OsclTCPSocket::Bind (OsclNetworkAddress & aAddress)

Bind a TCP socket to an address. This is a synchronous method.

**Parameters:**

*aAddress*: Bind address.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code.

#### 7.230.3.3 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::BindAsync (OsclNetworkAddress & aAddress, int32 aTimeoutMsec = (-1))

Bind a TCP socket to an address. This is an asynchronous method.

**Parameters:**

*aAddress*: Bind address.

*aTimeoutMsec*: Optional timeout. Use a negative value for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

**7.230.3.4 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelAccept ()**

Cancel Accept

This method will cancel any pending Accept operation on the current socket, causing the Accept to complete with error EPVSocketCancel. If there is no pending Accept operation, this method will have no effect.

**7.230.3.5 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelBind ()**

Cancel Bind

This method will cancel any pending BindAsync operation on the current socket, causing the BindAsync to complete with error EPVSocketCancel. If there is no pending BindAsync operation, this method will have no effect.

**7.230.3.6 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelConnect ()**

Cancel Connect

This method will cancel any pending Connect operation on the current socket, causing the Connect to complete with error EPVSocketCancel. If there is no pending Connect operation, this method will have no effect.

**7.230.3.7 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelListen ()**

Cancel Async Listen

This method will cancel any pending ListenAsync operation on the current socket, causing the Listen to complete with error EPVSocketCancel. If there is no pending Listen operation, this method will have no effect.

**7.230.3.8 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelRecv ()**

Cancel Recv

This method will cancel any pending Recv operation on the current socket, causing the Recv to complete with error EPVSocketCancel. If there is no pending Recv operation, this method will have no effect.

**7.230.3.9 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelSend ()**

Cancel Send

This method will cancel any pending Send operation on the current socket, causing the Send to complete with error EPVSocketCancel. If there is no pending Send operation, this method will have no effect.

### 7.230.3.10 OSCL\_IMPORT\_REF void OsclTCPSocket::CancelShutdown ()

Cancel Shutdown

This method will cancel any pending Shutdown operation on the current socket, causing the Shutdown to complete with error EPVSocketCancel. If there is no pending Shutdown operation, this method will have no effect.

### 7.230.3.11 OSCL\_IMPORT\_REF int32 OsclTCPSocket::Close ()

Close a TCP socket. This is a synchronous method.

Once it is closed a socket cannot be re-opened. Sockets are automatically closed when they are deleted. This method may be used to see any error code returned from the platform's socket close call.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code.

### 7.230.3.12 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::Connect (OsclNetworkAddress & aAddress, int32 aTimeoutMsec = -1)

Connect to an address. This is an asynchronous method.

**Parameters:**

*aAddress*: a network address.

*aTimeoutMsec*: Timeout in milliseconds, or (-1) for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

### 7.230.3.13 OSCL\_IMPORT\_REF OsclTCPSocket\* OsclTCPSocket::GetAcceptedSocketL (uint32 aId)

Retrieve the accept socket after a successful Accept operation. This is a synchronous method.

**Parameters:**

*aId*: Socket ID. The caller must assign an ID to each socket. The ID is used to identify the socket in observer callbacks.

**Returns:**

Returns pointer to socket, or NULL if error. Note: The caller is responsible for deleting any accepted socket that it retrieves.

### 7.230.3.14 OSCL\_IMPORT\_REF int32 OsclTCPSocket::GetPeerName (OsclNetworkAddress & aPeerName)

Retrieves the peer address of the socket

**Parameters:**

*aPeerName*: This will store the peer address when API returns successfully.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.230.3.15 OSCL\_IMPORT\_REF uint8\* OsclTCPSocket::GetRecvData (int32 \* aLength)**

Retrieve the received data after a successful Recv operation. This is a synchronous method.

**Parameters:**

*aLength*: (output) number of bytes of data received.

**Returns:**

Returns pointer to received data, or NULL if none.

**7.230.3.16 OSCL\_IMPORT\_REF uint8\* OsclTCPSocket::GetSendData (int32 \* aLength)**

Retrieve the sent data after a successful Send operation. This is a synchronous method.

**Parameters:**

*aLength*: (output) number of bytes of data sent.

**Returns:**

Returns pointer to sent data, or NULL if none.

**7.230.3.17 OSCL\_IMPORT\_REF int32 OsclTCPSocket::Listen (int32 aQueueSize)**

Listen. This is a synchronous method.

**Parameters:**

*aQueueSize*: Queue size.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code.

**7.230.3.18 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::ListenAsync (int32 aQueueSize, int32 aTimeoutMsec = (-1))**

ListenAsync This is an asynchronous method.

**Parameters:**

*aQueueSize*: Queue size.

*aTimeoutMsec*: Optional timeout. Use a negative value for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

**7.230.3.19 OSCL\_IMPORT\_REF OsclTCPSocket\* OsclTCPSocket::NewL (Oscl\_DefAlloc  
& alloc, OsclSocketServ & aServ, OsclSocketObserver \* aObserver, uint32 aId)  
[static]**

Create a TCP Socket. May leave if failure.

**Parameters:**

*alloc*: Memory allocator.

*aServ*: Socket server. Must be connected.

*aObserver*: Socket observer.

*aId*: Socket ID. The caller must assign an ID to each socket. The ID is used to identify the socket in observer callbacks.

**Returns:**

Returns pointer to socket.

**7.230.3.20 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::Recv (uint8 \* aPtr, uint32  
aMaxLen, int32 aTimeoutMsec = -1)**

Receive Data. This is an asynchronous method.

**Parameters:**

*aPtr*: Buffer for received data.

*aMaxLen*: Length of buffer.

*aTimeoutMsec*: Timeout in milliseconds, or (-1) for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

**7.230.3.21 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::Send (const uint8 \* aPtr,  
uint32 aLen, int32 aTimeoutMsec = -1)**

Send Data. This is an asynchronous method.

**Parameters:**

*aPtr*: Data to send.

*aLen*: Length of data to send.

*aTimeoutMsec*: Timeout in milliseconds, or (-1) for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

**7.230.3.22 OSCL\_IMPORT\_REF int32 OsclTCPSocket::SetOptionToReuseAddress ()**

Allows the server to bind to an address which is in a TIME\_WAIT state.

**Returns:**

Returns: OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_SUPPORTED, if underlying OS doesn't support joining multicast group PVSOCK\_ERR\_BAD\_PARAM, if config io file is not configured in accordance with underlying OS PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.230.3.23 OSCL\_IMPORT\_REF int32 OsclTCPSocket::SetTOS (const OsclSocketTOS & aTOS)**

Sets the Type of Service field of each outgoing IP datagram.

**Parameters:**

*aTOS*: Specifies the type of service requested.

**Returns:**

Returns: OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_SUPPORTED, if underlying OS doesn't support joining multicast group PVSOCK\_ERR\_BAD\_PARAM, if config io file is not configured in accordance with underlying OS PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.230.3.24 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::Shutdown  
(TPVSocketShutdown aHow, int32 aTimeoutMsec = -1)**

Shutdown a socket. This is an asynchronous method.

**Parameters:**

*aHow*: type of shutdown

*aTimeoutMsec*: Timeout in milliseconds, or (-1) for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

**7.230.3.25 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::ThreadLogoff ()**

Thread logoff routine. This will prepare for transfer and use of the socket in another thread. All socket requests must be complete prior to calling this routine. If any requests are still active, it will return EPVSocketFailure;

**7.230.3.26 OSCL\_IMPORT\_REF TPVSocketEvent OsclTCPSocket::ThreadLogon  
(OsclSocketServ & aServ, OsclSocketObserver \* aObserver)**

Thread logon routine. This will complete the transfer of a socket from another thread for use in the current thread. The ThreadLogoff API must be called in the original thread prior to calling ThreadLogon.


The documentation for this class was generated from the following file:

- [oscl\\_socket.h](#)

## 7.231 OsclTCPSocketI Class Reference

```
#include <oscl_tcp_socket.h>
```

Inheritance diagram for OsclTCPSocketI::



### Public Methods

- virtual ~OsclTCPSocketI ()
- [TPVSocketEvent ThreadLogoff \(\)](#)
- [TPVSocketEvent ThreadLogon \(OsclSocketServI \\*aServ, OsclSocketObserver \\*aObserver\)](#)
- int32 [Close \(\)](#)
- int32 [Listen \(int aQueueSize\)](#)
- OsclTCPSocketI \* [GetAcceptedSocketL \(uint32 aId\)](#)
- uint8 \* [GetRecvData \(int32 \\*aLength\)](#)
- uint8 \* [GetSendData \(int32 \\*aLength\)](#)
- [TPVSocketEvent BindAsync \(OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1\)](#)
- void [CancelBind \(\)](#)
- [TPVSocketEvent ListenAsync \(uint32 qsize, int32 aTimeoutMsec=-1\)](#)
- void [CancelListen \(\)](#)
- [TPVSocketEvent Connect \(OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1\)](#)
- void [CancelConnect \(\)](#)
- [TPVSocketEvent Shutdown \(TPVSocketShutdown aHow, int32 aTimeoutMsec=-1\)](#)
- void [CancelShutdown \(\)](#)
- [TPVSocketEvent Accept \(int32 aTimeout=-1\)](#)
- void [CancelAccept \(\)](#)
- [TPVSocketEvent Send \(const uint8 \\*&aPtr, uint32 aLen, int32 aTimeoutMsec=-1\)](#)
- void [CancelSend \(\)](#)
- [TPVSocketEvent Recv \(uint8 \\*&aPtr, uint32 aMaxLen, int32 aTimeoutMsec=-1\)](#)
- void [CancelRecv \(\)](#)

### Static Public Methods

- OsclTCPSocketI \* [NewL \(Oscl\\_DefAlloc &a, OsclSocketServI \\*aServ, OsclSocketObserver \\*aObserver, uint32 aId\)](#)

#### 7.231.1 Detailed Description

Internal implementation class for [OsclTCPSocket](#)

## 7.231.2 Constructor & Destructor Documentation

7.231.2.1 **virtual OsclTCPSocketI::~OsclTCPSocketI () [virtual]**

## 7.231.3 Member Function Documentation

7.231.3.1 **TPVSocketEvent OsclTCPSocketI::Accept (int32 *aTimeout* = -1) [inline]**

7.231.3.2 **TPVSocketEvent OsclTCPSocketI::BindAsync (OsclNetworkAddress & *aAddress*, int32 *aTimeoutMsec* = -1) [inline]**

7.231.3.3 **void OsclTCPSocketI::CancelAccept () [inline]**

7.231.3.4 **void OsclTCPSocketI::CancelBind () [inline]**

7.231.3.5 **void OsclTCPSocketI::CancelConnect () [inline]**

7.231.3.6 **void OsclTCPSocketI::CancelListen () [inline]**

7.231.3.7 **void OsclTCPSocketI::CancelRecv () [inline]**

7.231.3.8 **void OsclTCPSocketI::CancelSend () [inline]**

7.231.3.9 **void OsclTCPSocketI::CancelShutdown () [inline]**

7.231.3.10 **int32 OsclTCPSocketI::Close () [virtual]**

Implements [OsclIPSocketI](#).

7.231.3.11 **TPVSocketEvent OsclTCPSocketI::Connect (OsclNetworkAddress & *aAddress*, int32 *aTimeoutMsec* = -1) [inline]**

7.231.3.12 **OsclTCPSocketI\* OsclTCPSocketI::GetAcceptedSocketL (uint32 *aId*)**

7.231.3.13 **uint8 \* OsclTCPSocketI::GetRecvData (int32 \* *aLength*) [inline, virtual]**

Implements [OsclIPSocketI](#).

7.231.3.14 **uint8 \* OsclTCPSocketI::GetSendData (int32 \* *aLength*) [inline, virtual]**

Implements [OsclIPSocketI](#).

- 7.231.3.15 **int32** OsclTCPSocketI::Listen (*int aQueueSize*) [inline]
- 7.231.3.16 **TPVSocketEvent** OsclTCPSocketI::ListenAsync (*uint32 qsize, int32 aTimeoutMsec = -1*) [inline]
- 7.231.3.17 OsclTCPSocketI\* OsclTCPSocketI::NewL (**Oscl\_DefAlloc** & *a*, **OsclSocketServI** \* *aServ*, **OsclSocketObserver** \* *aObserver*, *uint32 aId*) [static]
- 7.231.3.18 **TPVSocketEvent** OsclTCPSocketI::Recv (*uint8 \*& aPtr, uint32 aMaxLen, int32 aTimeoutMsec = -1*) [inline]
- 7.231.3.19 **TPVSocketEvent** OsclTCPSocketI::Send (*const uint8 \*& aPtr, uint32 aLen, int32 aTimeoutMsec = -1*) [inline]
- 7.231.3.20 **TPVSocketEvent** OsclTCPSocketI::Shutdown (**TPVSocketShutdown** *aHow, int32 aTimeoutMsec = -1*) [inline]
- 7.231.3.21 **TPVSocketEvent** OsclTCPSocketI::ThreadLogoff ()

Reimplemented from **OsclIPSocketI**.

- 7.231.3.22 **TPVSocketEvent** OsclTCPSocketI::ThreadLogon (**OsclSocketServI** \* *aServ*, **OsclSocketObserver** \* *aObserver*)

The documentation for this class was generated from the following file:

- [oscl\\_tcp\\_socket.h](#)

## 7.232 OsclThread Class Reference

```
#include <oscl_thread.h>
```

### Public Methods

- OSCL\_IMPORT\_REF OsclThread ()
- OSCL\_IMPORT\_REF ~OsclThread ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Create (TOsclThreadFuncPtr func, int32 stack\_size, TOsclThreadFuncArg argument, OsclThread\_State state=Start\_on\_creation, bool oIsJoinable=false)
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError GetPriority (OsclThreadPriority &refThreadPriority)
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError SetPriority (OsclThreadPriority ePriority)
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Suspend ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Resume ()
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError Terminate (OsclAny \*exitcode)
- OSCL\_IMPORT\_REF TOsclThreadTerminate CanTerminate ()

### Static Public Methods

- OSCL\_IMPORT\_REF void Exit (OsclAny \*exitcode)
- OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError GetId (TOsclThreadId &refThreadId)
- OSCL\_IMPORT\_REF bool CompareId (TOsclThreadId &t1, TOsclThreadId &t2)
- OSCL\_IMPORT\_REF void SleepMillisec (const int32 msec)

### 7.232.1 Detailed Description

Thread Class. A subset of Thread APIs. It implements platform independent APIs for thread creation, exiting, suspend, resume, priority and termination. With the use of proper defines it implements the basic thread features. It provides an opaque layer through which user doesn't need to worry about OS specific data.

### 7.232.2 Constructor & Destructor Documentation

#### 7.232.2.1 OSCL\_IMPORT\_REF OsclThread::OsclThread ()

Class constructor

#### 7.232.2.2 OSCL\_IMPORT\_REF OsclThread::~OsclThread ()

Class destructor

### 7.232.3 Member Function Documentation

#### 7.232.3.1 OSCL\_IMPORT\_REF TOsclThreadTerminate OsclThread::CanTerminate ()

Tell if thread terminate will do join, immediate hard kill, or NOP.

**Returns:**

Terminate behavior.

**7.232.3.2 OSCL\_IMPORT\_REF bool OsclThread::CompareId ([TOsclThreadId & t1](#),  
[TOsclThreadId & t2](#)) [static]**

Static routine to compare whether two thread ID's are equal.

**Parameters:**

*t1, t2*: thread ID passed by the application

**Returns:**

true if equal.

**7.232.3.3 OSCL\_IMPORT\_REF [OsclProcStatus::eOsclProcError](#) OsclThread::Create  
([TOsclThreadFuncPtr func](#), [int32 stack\\_size](#), [TOsclThreadFuncArg argument](#),  
[OsclThread\\_State state = Start\\_on\\_creation](#), [bool oIsJoinable = false](#))**

This routine will create a thread. The thread may be launched immediately or may be created in a suspended state and launched with a Resume call.

**Parameters:**

*func* = Name of the thread Function *stack\_size* = Size of the thread stack. If zero, then the platform-specific default stack size will be used. *argument* = Argument to be passed to thread function *state* = Enumeration which specifies the state of the thread on creation with values Running and Suspend. Note: the Suspend option may not be available on all platforms. If it is not supported, the Create call will return INVALID\_PARAM\_ERROR. *oIsJoinable* = A boolean, which when set to true, creates a Joinable thread. The default value for this is false, which creates a Detached thread. Note 1: When a joinable thread is created, it is imperative to call thread Terminate. Otherwise, it would cause a memory leak. Note 2: This is currently available only for platforms that have support for pthreads.

**Returns:**

[eOsclProcError](#)

**7.232.3.4 OSCL\_IMPORT\_REF void OsclThread::Exit ([OsclAny \\* exitcode](#)) [static]**

Exit is a static function which is used to end the current thread. When called it just ends the execution of the current thread. Note: on some platforms this may be a NOP.

**Parameters:**

*exitcode* = Exitcode of the thread. This can be used by other threads to know the exit status of this thread.

**Returns:**

None

**7.232.3.5 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclThread::GetId  
(TOsclThreadId & refThreadId) [static]**

Static routine to retrieve ID of calling thread.

**Parameters:**

*Thread* ID passed by the application

**Returns:**

Error code

**7.232.3.6 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclThread::GetPriority  
(OsclThreadPriority & refThreadPriority)**

GetThreadPriority gets the priority of the thread. It takes reference of the input argument and assigns priority to it from one of the already defined priorities.

**Parameters:**

*int16&* refThreadPriority : Output Priority value

**Returns:**

Error code

**7.232.3.7 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclThread::Resume ()**

ResumeThread resumes the suspended thread and brings it into execution.

**Parameters:**

*None*

**Returns:**

Error code Note: this function may not be supported on all platforms, and may return NOT\_ - IMPLEMENTED.

**7.232.3.8 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclThread::SetPriority  
(OsclThreadPriority ePriority)**

SetThreadPriority sets the priority of the thread. It takes priority as the input argument and assigns it to the thread referred.

**Parameters:**

*ePriorityLevel* : Input Priority value

**Returns:**

Error code Note: this function may not be supported on all platforms, and may return NOT\_ - IMPLEMENTED.

**7.232.3.9 OSCL\_IMPORT\_REF void OsclThread::SleepMillisec (const int32 msec) [static]**

Suspend current thread execution for specified time.

**Parameters:**

*msec*, *t2*: sleep time in milliseconds.

**7.232.3.10 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclThread::Suspend ()**

This API suspends the thread being referred. The thread can later be brought into execution by calling OSCL\_ResumeThread() on it.

**Parameters:**

*None*

**Returns:**

Error code Note: this function may not be supported on all platforms, and may return NOT\_IMPLEMENTED.

**7.232.3.11 OSCL\_IMPORT\_REF OsclProcStatus::eOsclProcError OsclThread::Terminate  
(OsclAny \* *exitcode*)**

Terminate a thread other than the calling thread.

This API may have multiple behaviors. It may do a hard kill, a "join" operation, or a do-nothing. Caller can use CanTerminate option to tell the behavior in advance.

**Parameters:**

*exitcode* = Exitcode of the thread.

**Returns:**

Error code


The documentation for this class was generated from the following file:

- [oscl\\_thread.h](#)

## 7.233 OsclThreadLock Class Reference

```
#include <oscl_mutex.h>
```

Inheritance diagram for OsclThreadLock::



### Public Methods

- OSCL\_IMPORT\_REF OsclThreadLock ()
- virtual OSCL\_IMPORT\_REF ~OsclThreadLock ()
- OSCL\_IMPORT\_REF void Lock ()
- OSCL\_IMPORT\_REF void Unlock ()

#### 7.233.1 Detailed Description

An implementation of [OsclLockBase](#) using a mutex

#### 7.233.2 Constructor & Destructor Documentation

##### 7.233.2.1 OSCL\_IMPORT\_REF OsclThreadLock::OsclThreadLock ()

7.233.2.2 virtual OSCL\_IMPORT\_REF OsclThreadLock::~OsclThreadLock () [virtual]

#### 7.233.3 Member Function Documentation

##### 7.233.3.1 OSCL\_IMPORT\_REF void OsclThreadLock::Lock () [virtual]

Implements [OsclLockBase](#).

##### 7.233.3.2 OSCL\_IMPORT\_REF void OsclThreadLock::Unlock () [virtual]

Implements [OsclLockBase](#).

The documentation for this class was generated from the following file:

- [oscl\\_mutex.h](#)

## 7.234 OsclTickCount Class Reference

```
#include <oscl_tickcount.h>
```

### Static Public Methods

- uint32 [TickCount \(\)](#)
- uint32 [TickCountFrequency \(\)](#)
- uint32 [TickCountPeriod \(\)](#)
- uint32 [TicksToMsec \(uint32 ticks\)](#)
- uint32 [MsecToTicks \(uint32 msec\)](#)

#### 7.234.1 Detailed Description

OsclTickCount class is used to retrieve the system tick count and the tick counter's frequency. The maximum tick count value is equivalent to the maximum uint32 value.

#### 7.234.2 Member Function Documentation

##### 7.234.2.1 uint32 OsclTickCount::MsecToTicks (uint32 *msec*) [static]

This function converts milliseconds to ticks

**Returns:**

ticks

##### 7.234.2.2 uint32 OsclTickCount::TickCount () [static]

This function returns the current system tick count

**Returns:**

returns the tick count

##### 7.234.2.3 uint32 OsclTickCount::TickCountFrequency () [static]

This function returns the tick frequency in ticks per second

**Returns:**

ticks per second

##### 7.234.2.4 uint32 OsclTickCount::TickCountPeriod () [static]

This function returns the tick period in microseconds per tick

**Returns:**

microseconds per tick

**7.234.2.5 uint32 OsclTickCount::TicksToMsec (uint32 *ticks*) [static]**

This function converts ticks to milliseconds

**Returns:**

milliseconds


The documentation for this class was generated from the following file:

- [oscl\\_tickcount.h](#)

## 7.235 OsclTimer< Alloc > Class Template Reference

```
#include <oscl_timer.h>
```

Inheritance diagram for OsclTimer< Alloc >::



### Public Types

- `typedef CallbackTimer< Alloc > callback_timer_type`

### Public Methods

- `OsclTimer (const char *name, uint32 frequency=1, int32 priority=OsclActiveObject::EPriorityNominal)`
- `virtual ~OsclTimer ()`
- `void SetObserver (OsclTimerObserver *obs)`
- `void SetFrequency (uint32 frequency)`
- `void SetExactFrequency (uint32 frequency)`
- `void Request (int32 timerID, int32 timeoutInfo, int32 cycles, OsclTimerObserver *obs=0, bool recurring=0)`
- `void Cancel (int32 timerID, int32 timeoutInfo=-1)`
- `void Clear ()`

### Protected Methods

- `void TimerBaseElapsed ()`

### Friends

- `class CallbackTimer< Alloc >`

template<class Alloc> class OsclTimer< Alloc >

### 7.235.1 Member Typedef Documentation

7.235.1.1 template<class Alloc> typedef CallbackTimer<Alloc> OsclTimer< Alloc >::callback\_timer\_type

### 7.235.2 Constructor & Destructor Documentation

7.235.2.1 template<class Alloc> OsclTimer< Alloc >::OsclTimer (const char \* *name*, uint32 *frequency* = 1, int32 *priority* = OsclActiveObject::EPriorityNominal)

Constructor

**Parameters:**

*frequency* The frequency of the timer in cycles/second. A value of 1 means the timer will cycle in 1 second intervals.

7.235.2.2 template<class Alloc> OsclTimer< Alloc >::~OsclTimer () [virtual]

### 7.235.3 Member Function Documentation

7.235.3.1 template<class Alloc> void OsclTimer< Alloc >::Cancel (int32 *timerID*, int32 *timeoutInfo* = -1)

Cancel a timer

**Parameters:**

*timerID* used to identify the timer to cancel.

*timeoutInfo* if not set to -1, this value will be used as additional matching criteria to cancel a timer.

7.235.3.2 template<class Alloc> void OsclTimer< Alloc >::Clear ()

Cancel all pending timers.

7.235.3.3 template<class Alloc> void OsclTimer< Alloc >::Request (int32 *timerID*, int32 *timeoutInfo*, int32 *cycles*, OsclTimerObserver \* *obs* = 0, bool *recurring* = 0)

Request a timer

**Parameters:**

*timerID* used to identify the timer for cancellation. This value will be returned as part of the timeout event.

*timeoutInfo* for user info. Returned to the observer on a timeout event

*cycles* the number of cycles to wait before a timeout event. If the timer frequency is 1 and the cycles are set to 2, then the timeout event will occur in 2 seconds.

*obs* a local observer object to be called on a timeout event. This observer overrides the global observer if set.

**7.235.3.4 template<class Alloc> void OsclTimer< Alloc >::SetExactFrequency (uint32 *frequency*)**

Set the exact frequency of the timer in microsecond.

**Parameters:**

*frequency* A value of 1 means the timer will cycle in one microsecond intervals, 1000 means millisecond intervals, etc.

**7.235.3.5 template<class Alloc> void OsclTimer< Alloc >::SetFrequency (uint32 *frequency*)**

Set the frequency of the timer in cycles/second.

**Parameters:**

*frequency* A value of 1 means the timer will cycle in one second intervals, 1000 means millisecond intervals, etc.

**7.235.3.6 template<class Alloc> void OsclTimer< Alloc >::SetObserver ([OsclTimerObserver](#) \* *obs*) [inline]**

Set the global observer. Each timer can request a local observer, which if set overrides the global observer.

**Parameters:**

*obs* observer object.

**7.235.3.7 template<class Alloc> void OsclTimer< Alloc >::TimerBaseElapsed () [protected, virtual]**

Implements [CallbackTimerObserver](#).

## 7.235.4 Friends And Related Function Documentation

**7.235.4.1 template<class Alloc> friend class [CallbackTimer](#)< Alloc > [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_timer.h](#)

## 7.236 OsclTimerCompare Class Reference

```
#include <oscl_scheduler_readyq.h>
```

### Static Public Methods

- int [compare \(TOsclReady &a, TOsclReady &b\)](#)

#### 7.236.1 Member Function Documentation

##### 7.236.1.1 int OsclTimerCompare::compare (TOsclReady &*a*, TOsclReady &*b*) [static]


The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_readyq.h](#)

## 7.237 OsclTimerObject Class Reference

```
#include <oscl_scheduler_ao.h>
```

Inheritance diagram for OsclTimerObject::



### Public Methods

- OSCL\_IMPORT\_REF [OsclTimerObject](#) (int32 aPriority, const char name[ ])
- virtual OSCL\_IMPORT\_REF [~OsclTimerObject](#) ()
- OSCL\_IMPORT\_REF void [AddToScheduler](#) ()
- OSCL\_IMPORT\_REF void [RemoveFromScheduler](#) ()
- OSCL\_IMPORT\_REF void [After](#) (int32 aDelayMicrosec)
- OSCL\_IMPORT\_REF void [RunIfNotReady](#) (uint32 aDelayMicrosec=0)
- OSCL\_IMPORT\_REF void [SetBusy](#) ()
- OSCL\_IMPORT\_REF bool [IsBusy](#) () const
- OSCL\_IMPORT\_REF void [Cancel](#) ()
- OSCL\_IMPORT\_REF int32 [Priority](#) () const
- OSCL\_IMPORT\_REF int32 [Status](#) () const
- OSCL\_IMPORT\_REF void [SetStatus](#) (int32)
- OSCL\_IMPORT\_REF [OsclAOStatus](#) & [StatusRef](#) ()

### Protected Methods

- virtual OSCL\_IMPORT\_REF void [DoCancel](#) ()
- virtual OSCL\_IMPORT\_REF int32 [RunError](#) (int32 aError)

### 7.237.1 Detailed Description

User base class for execution objects. OsclTimerObject defines an exec object with a timer.

### 7.237.2 Constructor & Destructor Documentation

#### 7.237.2.1 OSCL\_IMPORT\_REF OsclTimerObject::OsclTimerObject (int32 *aPriority*, const char *name*[ ])

Constructor.

**Parameters:**

*aPriority* (input param): scheduling priority

*name* (input param): optional name for this AO.

#### 7.237.2.2 virtual OSCL\_IMPORT\_REF OsclTimerObject::~OsclTimerObject () [virtual]

Destructor.

### 7.237.3 Member Function Documentation

#### 7.237.3.1 OSCL\_IMPORT\_REF void OsclTimerObject::AddToScheduler ()

Add this AO to the current thread's scheduler.

Reimplemented from [PVActiveBase](#).

#### 7.237.3.2 OSCL\_IMPORT\_REF void OsclTimerObject::After (int32 *aDelayMicrosec*)

'After' sets the request ready, with request status OSCL\_REQUEST\_STATUS\_PENDING, and starts a timer. When the timer expires, the request will complete with status OSCL\_REQUEST\_ERR\_NONE. Must be called from the same thread in which the active object is scheduled. Will leave if the request is already readied, the object is not added to any scheduler, or the calling thread does not match the scheduling thread.

**Parameters:**

*anInterval*: timeout interval in microseconds.

#### 7.237.3.3 OSCL\_IMPORT\_REF void OsclTimerObject::Cancel ()

Cancel any active request. If the request is pending, this will call the DoCancel routine, wait for the request to cancel, then set the request idle. The AO will not run. If the request is not active, it does nothing. Request must be canceled from the same thread in which it is scheduled.

Reimplemented from [PVActiveBase](#).

#### 7.237.3.4 virtual OSCL\_IMPORT\_REF void OsclTimerObject::DoCancel () [protected, virtual]

Cancel request handler. This gets called by scheduler when the request is cancelled. The default routine will cancel the timer. If any additional action is needed, the derived class may override this. If the derived class does override this, it should explicitly call [OsclTimerObject::DoCancel](#) in its own DoCancel routine.

Implements [PVActiveBase](#).

#### 7.237.3.5 OSCL\_IMPORT\_REF bool OsclTimerObject::IsBusy ()

Return true if this AO is active, false otherwise.

#### 7.237.3.6 OSCL\_IMPORT\_REF int32 OsclTimerObject::Priority ()

Return scheduling priority of this exec object.

#### 7.237.3.7 OSCL\_IMPORT\_REF void OsclTimerObject::RemoveFromScheduler ()

Remove this AO from its scheduler. Will leave if the calling thread context does not match the scheduling thread. Cancels any pending request before removing.

Reimplemented from [PVActiveBase](#).

#### 7.237.3.8 virtual OSCL\_IMPORT\_REF int32 OsclTimerObject::RunError (int32 *aError*) [protected, virtual]

Run Leave handler. This gets called by scheduler when the Run routine leaves. The default implementation simply returns the leave code. If the derived class wants to handle errors from Run, it may override this. The ExecError should return OsclErrNone if it handles the error, otherwise it should return the input error code.

**Parameters:**

*aError*: the leave code generated by the Run.

Implements [PVActiveBase](#).

#### 7.237.3.9 OSCL\_IMPORT\_REF void OsclTimerObject::RunIfNotReady (uint32 *aDelayMicrosec* = 0)

Complete the request after a time interval. RunIfNotReady is identical to [After\(\)](#) except that it first checks the request status, and if it is already readied, it does nothing.

**Parameters:**

*aDelayMicrosec* (input param): delay in microseconds.

#### 7.237.3.10 OSCL\_IMPORT\_REF void OsclTimerObject::SetBusy ()

Set request ready for this AO. Will leave if the request is already readied, or the exec object is not added to any scheduler, or the calling thread context does not match the scheduler thread.

**7.237.3.11 OSCL\_IMPORT\_REF void OsclTimerObject::SetStatus (int32)**

**7.237.3.12 OSCL\_IMPORT\_REF int32 OsclTimerObject::Status ()**

Request status access

**7.237.3.13 OSCL\_IMPORT\_REF OsclAOStatus& OsclTimerObject::StatusRef ()**

The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_ao.h](#)

## 7.238 OsclTimerObserver Class Reference

```
#include <oscl_timer.h>
```

### Public Methods

- virtual void [TimeoutOccurred](#) (int32 timerID, int32 timeoutInfo)=0
- virtual [~OsclTimerObserver](#) ()

#### 7.238.1 Detailed Description

The observer class to receive timeout callbacks

#### 7.238.2 Constructor & Destructor Documentation

**7.238.2.1** virtual OsclTimerObserver::[~OsclTimerObserver](#) () [inline, virtual]

#### 7.238.3 Member Function Documentation

**7.238.3.1** virtual void OsclTimerObserver::[TimeoutOccurred](#) (int32 *timerID*, int32 *timeoutInfo*) [pure virtual]

This function will be called when the timer associated with this observer is executed

##### Parameters:

*timerID* The ID given at timer request.

*timeoutInfo* Any extra info given at timer request.


The documentation for this class was generated from the following file:

- [oscl\\_timer.h](#)

## 7.239 OsclTimerQ Class Reference

```
#include <oscl_scheduler_readyq.h>
```

Inheritance diagram for OsclTimerQ::



### Public Methods

- void [Construct](#) (int)
- void [Add](#) ([TOsclReady](#))
- void [Remove](#) ([TOsclReady](#))
- [TOsclReady](#) [PopTop](#) ()
- [TOsclReady](#) [Top](#) ()
- void [Pop](#) ([TOsclReady](#))
- bool [IsIn](#) ([TOsclReady](#))

#### 7.239.1 Member Function Documentation

**7.239.1.1 void OsclTimerQ::Add ([TOsclReady](#))**

**7.239.1.2 void OsclTimerQ::Construct (int)**

**7.239.1.3 bool OsclTimerQ::IsIn ([TOsclReady](#))**

**7.239.1.4 void OsclTimerQ::Pop ([TOsclReady](#))**

**7.239.1.5 [TOsclReady](#) OsclTimerQ::PopTop ()**

**7.239.1.6 void OsclTimerQ::Remove ([TOsclReady](#))**

**7.239.1.7 [TOsclReady](#) OsclTimerQ::Top ()**

The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_readyq.h](#)

## 7.240 OsclTLS< T, ID, Registry > Class Template Reference

```
#include <oscl_tls.h>
```

### Public Methods

- `OsclTLS ()`
- `~OsclTLS ()`
- `T & operator * () const`  
*The indirection operator (\*) accesses a value indirectly, through a pointer.*
- `T * operator -> () const`  
*The indirection operator (->) accesses a value indirectly, through a pointer.*
- `bool set ()`  
*set() method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.*

### Protected Attributes

- `T * _Ptr`

`template<class T, uint32 ID, class Registry = OsclTLSRegistry> class OsclTLS< T, ID, Registry >`

#### 7.240.1 Constructor & Destructor Documentation

**7.240.1.1 `template<class T, uint32 ID, class Registry = OsclTLSRegistry> OsclTLS< T, ID, Registry >::OsclTLS () [inline]`**

**7.240.1.2 `template<class T, uint32 ID, class Registry = OsclTLSRegistry> OsclTLS< T, ID, Registry >::~OsclTLS () [inline]`**

#### 7.240.2 Member Function Documentation

**7.240.2.1 `template<class T, uint32 ID, class Registry = OsclTLSRegistry> T& OsclTLS< T, ID, Registry >::operator * () const [inline]`**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the OsclTLS can be used like the regular pointer that it was initialized with.

**7.240.2.2 `template<class T, uint32 ID, class Registry = OsclTLSRegistry> T* OsclTLS< T, ID, Registry >::operator -> () const [inline]`**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the OsclTLS can be used like the regular pointer that it was initialized with.

**7.240.2.3 template<class T, uint32 ID, class Registry = OsclTLSRegistry> bool OsclTLS< T, ID, Registry >::set () [inline]**

[set\(\)](#) method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.

### 7.240.3 Field Documentation

**7.240.3.1 template<class T, uint32 ID, class Registry = OsclTLSRegistry> T\* OsclTLS< T, ID, Registry >::\_Ptr [protected]**

The documentation for this class was generated from the following file:

- [oscl\\_tls.h](#)

## 7.241 OsclTLSEEx< T, ID, Registry > Class Template Reference

```
#include <oscl_error.h>
```

### Public Methods

- `OsclTLSEEx ()`
- `~OsclTLSEEx ()`
- `T & operator * () const`

*The indirection operator (\*) accesses a value indirectly, through a pointer.*

- `T * operator -> () const`

*The indirection operator (->) accesses a value indirectly, through a pointer.*

- `bool set ()`

*set() method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.*

### Protected Attributes

- `T * _Ptr`

```
template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> class OsclTLSEEx< T, ID, Registry >
```

#### 7.241.1 Constructor & Destructor Documentation

**7.241.1.1 template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> OsclTLSEEx< T, ID, Registry >::OsclTLSEEx () [inline]**

**7.241.1.2 template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> OsclTLSEEx< T, ID, Registry >::~OsclTLSEEx () [inline]**

#### 7.241.2 Member Function Documentation

**7.241.2.1 template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> T& OsclTLSEEx< T, ID, Registry >::operator \* () const [inline]**

The indirection operator (\*) accesses a value indirectly, through a pointer.

This operator ensures that the `OsclTLS` can be used like the regular pointer that it was initialized with.

**7.241.2.2 template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> T\* OsclTLSEEx< T, ID, Registry >::operator -> () const [inline]**

The indirection operator (->) accesses a value indirectly, through a pointer.

This operator ensures that the `OsclTLS` can be used like the regular pointer that it was initialized with.

### 7.241.2.3 template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> bool OsclTLSE< T, ID, Registry >::set () [inline]

[set\(\)](#) method sets ownership to the pointer, passed. This method is needed when the class is created with a default constructor. Returns false in case the class is non-empty.

### 7.241.3 Field Documentation

#### 7.241.3.1 template<class T, uint32 ID, class Registry = OsclTLSRegistryEx> T\* OsclTLSE< T, ID, Registry >::\_Ptr [protected]

The documentation for this class was generated from the following file:

- [oscl\\_error.h](#)

## 7.242 OsclTLSRegistry Class Reference

```
#include <oscl_tls.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF [OsclAny](#) \* getInstance (uint32 ID, int32 &error)
- OSCL\_IMPORT\_REF void [registerInstance](#) ([OsclAny](#) \*ptr, uint32 ID, int32 &error)

### Friends

- class [OsclBase](#)

#### 7.242.1 Member Function Documentation

**7.242.1.1 OSCL\_IMPORT\_REF [OsclAny](#)\* OsclTLSRegistry::getInstance (uint32 *ID*, int32 & *error*) [static]**

**7.242.1.2 OSCL\_IMPORT\_REF void OsclTLSRegistry::registerInstance ([OsclAny](#) \* *ptr*, uint32 *ID*, int32 & *error*) [static]**

#### 7.242.2 Friends And Related Function Documentation

**7.242.2.1 friend class [OsclBase](#) [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_tls.h](#)

## 7.243 OsclTLSRegistryEx Class Reference

```
#include <oscl_error.h>
```

### Static Public Methods

- [OsclAny \\* getInstance \(uint32 ID\)](#)
- [void registerInstance \(OsclAny \\*ptr, uint32 ID\)](#)

#### 7.243.1 Member Function Documentation

**7.243.1.1 [OsclAny\\* OsclTLSRegistryEx::getInstance \(uint32 ID\)](#) [inline, static]**

**7.243.1.2 [void OsclTLSRegistryEx::registerInstance \(OsclAny \\*ptr, uint32 ID\)](#) [inline, static]**

The documentation for this class was generated from the following file:

- [oscl\\_error.h](#)

## 7.244 OsclTrapItem Class Reference

```
#include <oscl_heapbase.h>
```

### Public Methods

- OSCL\_INLINE [OsclTrapItem \(OsclTrapOperation anOperation\)](#)
- OSCL\_INLINE [OsclTrapItem \(OsclTrapOperation anOperation, OsclAny \\*aPtr\)](#)

### Friends

- class [OsclTrapStackItem](#)
- class [OsclTrapStack](#)

#### 7.244.1 Constructor & Destructor Documentation

**7.244.1.1 OSCL\_INLINE OsclTrapItem::OsclTrapItem ([OsclTrapOperation anOperation](#))**

**7.244.1.2 OSCL\_INLINE OsclTrapItem::OsclTrapItem ([OsclTrapOperation anOperation, OsclAny \\* aPtr](#))**

#### 7.244.2 Friends And Related Function Documentation

**7.244.2.1 friend class OsclTrapStack [friend]**

**7.244.2.2 friend class OsclTrapStackItem [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_heapbase.h](#)

## 7.245 OsclTrapStack Class Reference

```
#include <oscl_error_trapcleanup.h>
```

### Friends

- class [OsclError](#)
- class [OsclErrorTrap](#)
- class [OsclErrorTrapImp](#)

### 7.245.1 Detailed Description

A common type for cleanup stack and trap mark stack. for internal use only.

### 7.245.2 Friends And Related Function Documentation

**7.245.2.1 friend class OsclError [friend]**

**7.245.2.2 friend class OsclErrorTrap [friend]**

**7.245.2.3 friend class OsclErrorTrapImp [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_error\\_trapcleanup.h](#)

## 7.246 OsclTrapStackItem Class Reference

```
#include <oscl_error_trapcleanup.h>
```

### Public Methods

- [OsclTrapStackItem \(\)](#)
- [OsclTrapStackItem \(\\_OsclHeapBase \\*aCBase\)](#)
- [OsclTrapStackItem \(OsclAny \\*aTAny\)](#)
- [OsclTrapStackItem \(OsclTrapItem aItem\)](#)

### Data Fields

- [\\_OsclHeapBase \\* iCBase](#)
- [OsclAny \\* iTAny](#)
- [OsclTrapOperation iTrapOperation](#)
- [OsclTrapStackItem \\* iNext](#)

#### 7.246.1 Detailed Description

Internal cleanup stack item type.

#### 7.246.2 Constructor & Destructor Documentation

**7.246.2.1 OsclTrapStackItem::OsclTrapStackItem () [inline]**

**7.246.2.2 OsclTrapStackItem::OsclTrapStackItem (\_OsclHeapBase \* aCBase) [inline]**

**7.246.2.3 OsclTrapStackItem::OsclTrapStackItem (OsclAny \* aTAny) [inline]**

**7.246.2.4 OsclTrapStackItem::OsclTrapStackItem (OsclTrapItem aItem) [inline]**

#### 7.246.3 Field Documentation

**7.246.3.1 \_OsclHeapBase\* OsclTrapStackItem::iCBase**

**7.246.3.2 OsclTrapStackItem\* OsclTrapStackItem::iNext**

**7.246.3.3 OsclAny\* OsclTrapStackItem::iTAny**

**7.246.3.4 OsclTrapOperation OsclTrapStackItem::iTrapOperation**


The documentation for this class was generated from the following file:

- [oscl\\_error\\_trapcleanup.h](#)

## 7.247 OsclUDPSocket Class Reference

```
#include <oscl_socket.h>
```

Inheritance diagram for OsclUDPSocket::



### Public Methods

- OSCL\_IMPORT\_REF ~OsclUDPSocket ()
- OSCL\_IMPORT\_REF TPVSocketEvent ThreadLogoff ()
- OSCL\_IMPORT\_REF TPVSocketEvent ThreadLogon (OsclSocketServ &aServ, OsclSocketObserver \*aObserver)
- OSCL\_IMPORT\_REF int32 Close ()
- OSCL\_IMPORT\_REF int32 Bind (OsclNetworkAddress &aAddress)
- OSCL\_IMPORT\_REF int32 Join (OsclNetworkAddress &aAddress)
- OSCL\_IMPORT\_REF int32 JoinMulticastGroup (OsclIpMReq &aMReq)
- OSCL\_IMPORT\_REF int32 SetMulticastTTL (int32 aTTL)
- OSCL\_IMPORT\_REF int32 SetOptionToReuseAddress ()
- OSCL\_IMPORT\_REF int32 SetTOS (const OsclSocketTOS &aTOS)
- OSCL\_IMPORT\_REF int32 GetPeerName (OsclNetworkAddress &aPeerName)
- OSCL\_IMPORT\_REF TPVSocketEvent BindAsync (OsclNetworkAddress &aAddress, int32 aTimeoutMsec=(-1))
- OSCL\_IMPORT\_REF void CancelBind ()
- OSCL\_IMPORT\_REF uint8 \* GetRecvData (int32 \*aLength)
- OSCL\_IMPORT\_REF uint8 \* GetSendData (int32 \*aLength)
- OSCL\_IMPORT\_REF TPVSocketEvent SendTo (const uint8 \*aPtr, uint32 aLen, OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1)
- OSCL\_IMPORT\_REF void CancelSendTo ()
- OSCL\_IMPORT\_REF TPVSocketEvent RecvFrom (uint8 \*aPtr, uint32 aMaxLen, OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1, uint32 aMultiRecvLimit=0, Oscl\_Vector< uint32, OsclMemAllocator > \*aPacketLen=NULL, Oscl\_Vector< OsclNetworkAddress, OsclMemAllocator > \*aPacketSource=NULL)
- OSCL\_IMPORT\_REF void CancelRecvFrom ()
- OSCL\_IMPORT\_REF int32 SetRecvBufferSize (uint32 size)

### Static Public Methods

- OSCL\_IMPORT\_REF OsclUDPSocket \* NewL (Oscl\_DefAlloc &alloc, OsclSocketServ &aServ, OsclSocketObserver \*aObserver, uint32 aId)

### 7.247.1 Detailed Description

The UDP Socket class

### 7.247.2 Constructor & Destructor Documentation

#### 7.247.2.1 OSCL\_IMPORT\_REF OsclUDPSocket::~OsclUDPSocket ()

Destructor. The object must be deleted using the same allocator used in the NewL call.

### 7.247.3 Member Function Documentation

#### 7.247.3.1 OSCL\_IMPORT\_REF int32 OsclUDPSocket::Bind ([OsclNetworkAddress](#) & *aAddress*)

Bind a UDP socket to an address. This is a synchronous method.

**Parameters:**

*aAddress*: Bind address.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code.

#### 7.247.3.2 OSCL\_IMPORT\_REF [TPVSocketEvent](#) OsclUDPSocket::BindAsync ([OsclNetworkAddress](#) & *aAddress*, int32 *aTimeoutMsec* = (-1))

Bind a UDP socket to an address. This is an asynchronous method.

**Parameters:**

*aAddress*: Bind address.

*aTimeoutMsec*: Optional timeout. Use a negative value for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

#### 7.247.3.3 OSCL\_IMPORT\_REF void OsclUDPSocket::CancelBind ()

Cancel Bind

This method will cancel any pending BindAsync operation on the current socket, causing the BindAsync to complete with error EPVSocketCancel. If there is no pending BindAsync operation, this method will have no effect.

#### 7.247.3.4 OSCL\_IMPORT\_REF void OsclUDPSocket::CancelRecvFrom ()

Cancel RecvFrom

This method will cancel any pending RecvFrom operation on the current socket, causing the RecvFrom to complete with error EPVSocketCancel. If there is no pending RecvFrom operation, this method will have no effect.

**7.247.3.5 OSCL\_IMPORT\_REF void OsclUDPSocket::CancelSendTo ()**

Cancel SendTo

This method will cancel any pending SendTo operation on the current socket, causing the SendTo to complete with error EPVSocketCancel. If there is no pending SendTo operation, this method will have no effect.

**7.247.3.6 OSCL\_IMPORT\_REF int32 OsclUDPSocket::Close ()**

Close a UDP socket. This is a synchronous method.

Once it is closed a socket cannot be re-opened. Sockets are automatically closed when they are deleted. This method may be used to see any error code returned from the platform's socket close call.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code.

**7.247.3.7 OSCL\_IMPORT\_REF int32 OsclUDPSocket::GetPeerName ([OsclNetworkAddress](#) & *aPeerName*)**

Retrieves the peer address of the socket

**Parameters:**

*aPeerName*: This will store the peer address when API returns successfully.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.247.3.8 OSCL\_IMPORT\_REF uint8\* OsclUDPSocket::GetRecvData (int32 \* *aLength*)**

Retrieve the received data after a successful RecvFrom operation. This is a synchronous method.

**Parameters:**

*aLength*: (output) number of bytes of data received.

**Returns:**

Returns pointer to received data, or NULL if none.

**7.247.3.9 OSCL\_IMPORT\_REF uint8\* OsclUDPSocket::GetSendData (int32 \* *aLength*)**

Retrieve the sent data after a successful SendTo operation. This is a synchronous method.

**Parameters:**

*aLength*: (output) number of bytes of data sent.

**Returns:**

Returns pointer to sent data, or NULL if none.

### 7.247.3.10 OSCL\_IMPORT\_REF int32 OsclUDPSocket::Join ([OsclNetworkAddress](#) & *aAddress*)

Bind a UDP socket to an address and Join the multicast group. This is a synchronous method.

**Parameters:**

*aAddress*: Bind address.

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code. May throw an OsclErrNotSupported Exception

### 7.247.3.11 OSCL\_IMPORT\_REF int32 OsclUDPSocket::JoinMulticastGroup ([OsclIpMReq](#) & *aMReq*)

Join the multicast group.

**Parameters:**

*aMReq*: Multicast group information.

**Returns:**

Returns: OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_SUPPORTED, if underlying OS doesn't support joining multicast group PVSOCK\_ERR\_BAD\_PARAM, if config io file is not configured in accordance with underlying OS PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

### 7.247.3.12 OSCL\_IMPORT\_REF OsclUDPSocket\* OsclUDPSocket::NewL ([Oscl\\_DefAlloc](#) & *alloc*, [OsclSocketServ](#) & *aServ*, [OsclSocketObserver](#) \* *aObserver*, uint32 *aId*) [static]

Create a UDP Socket. May leave if failure.

**Parameters:**

*alloc*: Memory allocator.

*aServ*: Socket server. Must be connected.

*aObserver*: Socket observer.

*aId*: Socket ID. The caller must assign an ID to each socket. The ID is used to identify the socket in observer callbacks.

**Returns:**

Returns pointer to socket.

### 7.247.3.13 OSCL\_IMPORT\_REF TPVSocketEvent OsclUDPSocket::RecvFrom (uint8 \* *aPtr*, uint32 *aMaxLen*, [OsclNetworkAddress](#) & *aAddress*, int32 *aTimeoutMsec* = -1, uint32 *aMultiRecvLimit* = 0, [Oscl\\_Vector](#)< uint32, [OsclMemAllocator](#) > \* *aPacketLen* = NULL, [Oscl\\_Vector](#)< [OsclNetworkAddress](#), [OsclMemAllocator](#) > \* *aPacketSource* = NULL)

Receive Data. This is an asynchronous method.

**Parameters:**

**aPtr:** Buffer to receive incoming data

**aMaxLen:** Length of buffer.

**aAddress:** (output) Source address.

**aTimeoutMsec:** Timeout in milliseconds, or (-1) for infinite wait.

**aMultiRecvLimit** (optional input): Configures multiple packet receive mode. As long as there are packets queued at the socket and at least aMultiRecvLimit bytes are available in the buffer, recvfrom operations will continue. A value of zero disabled multiple packet mode. The individual packet lengths can be retrieved in the aPacketLen parameter; and the individual packet source addresses can be retrieved in the aPacketSource parameter.

**aPacketLen:** (optional output) a vector of packet lengths, in case multiple packets were received.

**aPacketSource:** (optional output) a vector of source addresses, in case multiple packets were received.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

#### 7.247.3.14 OSCL\_IMPORT\_REF TPVSocketEvent OsclUDPSocket::SendTo (const uint8 \* aPtr, uint32 aLen, OscINetworkAddress & aAddress, int32 aTimeoutMsec = -1)

Send Data. This is an asynchronous method.

**Parameters:**

**aPtr:** Data to send.

**aLen:** Length of data to send.

**aAddress:** Destination address.

**aTimeoutMsec:** Timeout in milliseconds, or (-1) for infinite wait.

**Returns:**

Will return EPVSocketPending if successful. When the operation is complete, a callback to the observer will occur with the completion status. If the operation cannot be initiated, the call will return EPVSocketFailure and there will be no callback.

#### 7.247.3.15 OSCL\_IMPORT\_REF int32 OsclUDPSocket::SetMulticastTTL (int32 aTTL)

Controls the number of intermediate systems through which a multicast datagram can be forwarded.

**Parameters:**

**aTTL:**Specifies the time-to-live value for multicast datagrams sent through this socket.

**Returns:**

Returns: OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_SUPPORTED, if underlying OS doesn't support joining multicast group PVSOCK\_ERR\_BAD\_PARAM, if config io file is not configured in accordance with underlying OS PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.247.3.16 OSCL\_IMPORT\_REF int32 OsclUDPSocket::SetOptionToReuseAddress ()**

Allows the server to bind to an address which is in a TIME\_WAIT state.

**Returns:**

Returns: OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_SUPPORTED, if underlying OS doesn't support joining multicast group PVSOCK\_ERR\_BAD\_PARAM, if config io file is not configured in accordance with underlying OS PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.247.3.17 OSCL\_IMPORT\_REF int32 OsclUDPSocket::SetRecvBufferSize (uint32 *size*)**

Set the buffer size of the socket This is a synchronous method.

**Parameters:**

*size*: buffer size

**Returns:**

Returns OsclErrNone for success, or a platform-specific error code. May throw an OsclErrNotSupported Exception.

**7.247.3.18 OSCL\_IMPORT\_REF int32 OsclUDPSocket::SetTOS (const OsclSocketTOS & *aTOS*)**

Sets the Type of Service field of each outgoing IP datagram.

**Parameters:**

*aTOS*: Specifies the type of service requested.

**Returns:**

Returns: OsclErrNone for success, or a platform-specific error code. or PVSOCK\_ERR\_NOT\_SUPPORTED, if underlying OS doesn't support joining multicast group PVSOCK\_ERR\_BAD\_PARAM, if config io file is not configured in accordance with underlying OS PVSOCK\_ERR\_NOT\_IMPLEMENTED, if this API is not implemented in OSCL for the underlying OS

**7.247.3.19 OSCL\_IMPORT\_REF TPVSocketEvent OsclUDPSocket::ThreadLogoff ()**

Thread logoff routine. This will prepare for transfer and use of the socket in another thread. All socket requests must be complete prior to calling this routine. If any requests are still active, it will return EPVSocketFailure;

**7.247.3.20 OSCL\_IMPORT\_REF TPVSocketEvent OsclUDPSocket::ThreadLogon  
(OsclSocketServ & *aServ*, OsclSocketObserver \* *aObserver*)**

Thread logon routine. This will complete the transfer of a socket from another thread for use in the current thread. The ThreadLogoff API must be called in the original thread prior to calling ThreadLogon.


The documentation for this class was generated from the following file:

- [oscl\\_socket.h](#)

## 7.248 OsclUDPSocketI Class Reference

```
#include <oscl_udp_socket.h>
```

Inheritance diagram for OsclUDPSocketI::



### Public Methods

- virtual ~OsclUDPSocketI ()
- int32 [Close \(\)](#)
- int32 [JoinMulticastGroup \(OsclIpMReq &aMReq\)](#)
- int32 [SetMulticastTTL \(int32 aTTL\)](#)
- uint8 \* [GetRecvData \(int32 \\*aLength\)](#)
- uint8 \* [GetSendData \(int32 \\*aLength\)](#)
- [TPVSocketEvent ThreadLogoff \(\)](#)
- [TPVSocketEvent ThreadLogon \(OsclSocketServI \\*aServ, OsclSocketObserver \\*aObserver\)](#)
- [TPVSocketEvent BindAsync \(OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1\)](#)
- void [CancelBind \(\)](#)
- [TPVSocketEvent SendTo \(const uint8 \\*&aPtr, uint32 aLen, OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1\)](#)
- void [CancelSendTo \(\)](#)
- [TPVSocketEvent RecvFrom \(uint8 \\*&aPtr, uint32 aMaxLen, OsclNetworkAddress &aAddress, int32 aTimeoutMsec=-1, uint32 aMultiMaxLen=0, Oscl\\_Vector< uint32, OsclMemAllocator > \\*aPacketLen=NULL, Oscl\\_Vector< OsclNetworkAddress, OsclMemAllocator > \\*aPacketSource=NULL\)](#)
- void [CancelRecvFrom \(\)](#)

### Static Public Methods

- OsclUDPSocketI \* [NewL \(Oscl\\_DefAlloc &a, OsclSocketServI \\*aServ, OsclSocketObserver \\*aObserver, uint32 aId\)](#)

#### 7.248.1 Detailed Description

Internal implementation class for [OsclUDPSocket](#)

## 7.248.2 Constructor & Destructor Documentation

**7.248.2.1** `virtual OsclUDPSocketI::~OsclUDPSocketI () [virtual]`

## 7.248.3 Member Function Documentation

**7.248.3.1** `TPVSocketEvent OsclUDPSocketI::BindAsync (OsclNetworkAddress & aAddress, int32 aTimeoutMsec = -1) [inline]`

**7.248.3.2** `void OsclUDPSocketI::CancelBind () [inline]`

**7.248.3.3** `void OsclUDPSocketI::CancelRecvFrom () [inline]`

**7.248.3.4** `void OsclUDPSocketI::CancelSendTo () [inline]`

**7.248.3.5** `int32 OsclUDPSocketI::Close () [virtual]`

Implements [OsclIPSocketI](#).

**7.248.3.6** `uint8 * OsclUDPSocketI::GetRecvData (int32 * aLength) [inline, virtual]`

Implements [OsclIPSocketI](#).

**7.248.3.7** `uint8 * OsclUDPSocketI::GetSendData (int32 * aLength) [inline, virtual]`

Implements [OsclIPSocketI](#).

**7.248.3.8** `int32 OsclUDPSocketI::JoinMulticastGroup (OsclIpMReq & aMReq)`

**7.248.3.9** `OsclUDPSocketI* OsclUDPSocketI::NewL (Oscl_DefAlloc & a, OsclSocketServI * aServ, OsclSocketObserver * aObserver, uint32 aId) [static]`

**7.248.3.10** `TPVSocketEvent OsclUDPSocketI::RecvFrom (uint8 *& aPtr, uint32 aMaxLen, OsclNetworkAddress & aAddress, int32 aTimeoutMsec = -1, uint32 aMultiMaxLen = 0, Oscl_Vector< uint32, OsclMemAllocator > * aPacketLen = NULL, Oscl_Vector< OsclNetworkAddress, OsclMemAllocator > * aPacketSource = NULL) [inline]`

**7.248.3.11** `TPVSocketEvent OsclUDPSocketI::SendTo (const uint8 *& aPtr, uint32 aLen, OsclNetworkAddress & aAddress, int32 aTimeoutMsec = -1) [inline]`

**7.248.3.12** `int32 OsclUDPSocketI::SetMulticastTTL (int32 aTTL)`

**7.248.3.13** `TPVSocketEvent OsclUDPSocketI::ThreadLogoff ()`

Reimplemented from [OsclIPSocketI](#).

**7.248.3.14** `TPVSocketEvent OsclUDPSocketI::ThreadLogon (OsclSocketServI * aServ, OsclSocketObserver * aObserver)`

The documentation for this class was generated from the following file:

- [oscl\\_udp\\_socket.h](#)

## 7.249 OsclUuid Struct Reference

```
#include <oscl_uuid.h>
```

### Public Methods

- [OsclUuid \(\)](#)
- [OsclUuid \(uint32 l, uint16 w1, uint16 w2, uint8 b1, uint8 b2, uint8 b3, uint8 b4, uint8 b5, uint8 b6, uint8 b7, uint8 b8\)](#)
- [OsclUuid \(const OsclUuid &uuid\)](#)
- [OsclUuid & operator= \(const OsclUuid &src\)](#)
- [bool operator== \(const OsclUuid &src\) const](#)
- [bool operator!= \(const OsclUuid &src\) const](#)

### Data Fields

- uint32 [data1](#)
- uint16 [data2](#)
- uint16 [data3](#)
- uint8 [data4 \[BYTES\\_IN\\_UUID\\_ARRAY\]](#)

#### 7.249.1 Detailed Description

OSCL UUID structure used for unique identification of modules and interfaces.

## 7.249.2 Constructor & Destructor Documentation

**7.249.2.1** `OsclUuid::OsclUuid () [inline]`

**7.249.2.2** `OsclUuid::OsclUuid (uint32 l, uint16 w1, uint16 w2, uint8 b1, uint8 b2, uint8 b3, uint8 b4, uint8 b5, uint8 b6, uint8 b7, uint8 b8) [inline]`

**7.249.2.3** `OsclUuid::OsclUuid (const OsclUuid & uuid) [inline]`

## 7.249.3 Member Function Documentation

**7.249.3.1** `bool OsclUuid::operator!= (const OsclUuid & src) const [inline]`

**7.249.3.2** `OsclUuid& OsclUuid::operator= (const OsclUuid & src) [inline]`

**7.249.3.3** `bool OsclUuid::operator== (const OsclUuid & src) const [inline]`

## 7.249.4 Field Documentation

**7.249.4.1** `uint32 OsclUuid::data1`

**7.249.4.2** `uint16 OsclUuid::data2`

**7.249.4.3** `uint16 OsclUuid::data3`

**7.249.4.4** `uint8 OsclUuid::data4[BYTES_IN_UUID_ARRAY]`


The documentation for this struct was generated from the following file:

- [oscl\\_uuid.h](#)

## 7.250 PVActiveBase Class Reference

```
#include <oscl_scheduler_aobase.h>
```

Inheritance diagram for PVActiveBase::



### Public Methods

- [PVActiveBase](#) (const char name[ ], int32 pri)
- virtual [~PVActiveBase](#) ()
- bool [IsInAnyQ](#) ()
- virtual int32 [RunError](#) (int32 aError)=0
- virtual void [Run](#) ()=0
- virtual void [DoCancel](#) ()=0
- void [AddToScheduler](#) ()
- void [RemoveFromScheduler](#) ()
- void [Destroy](#) ()
- void [Activate](#) ()
- OSCL\_IMPORT\_REF bool [IsAdded](#) () const
- void [Cancel](#) ()

### Data Fields

- uint32 [iAddedNum](#)
- [OsclNameString< PVEXECNAMELEN > iName](#)
- [PVThreadContext iThreadContext](#)
- [PVActiveStats \\* iPVAstats](#)
- [TReadyQueLink iPVReadyQLink](#)
- bool [iBusy](#)
- [OsclAOStatus iStatus](#)

### Friends

- class [PVActiveStats](#)
- class [OsclSchedulerCommonBase](#)

- class [OsclActiveObject](#)
- class [OsclTimerObject](#)
- class [OsclReadyQ](#)
- class [OsclReadyCompare](#)
- class [OsclReadySetPosition](#)
- class [OsclExecScheduler](#)

## 7.250.1 Detailed Description

PV Scheduler internal AO base class. Both [OsclActiveObject](#) and [OsclTimerObject](#) derive from this class. For Symbian, this just container has the desired additions to the basic CTimer or OsclActiveObj functionality. For non-Symbian, this class contains the entire AO implementation.

## 7.250.2 Constructor & Destructor Documentation

**7.250.2.1 PVActiveBase::PVActiveBase (const char *name*[ ], int32 *pri*)**

**7.250.2.2 virtual PVActiveBase::~PVActiveBase () [virtual]**

## 7.250.3 Member Function Documentation

**7.250.3.1 void PVActiveBase::Activate ()**

**7.250.3.2 void PVActiveBase::AddToScheduler ()**

Reimplemented in [OsclActiveObject](#), and [OsclTimerObject](#).

**7.250.3.3 void PVActiveBase::Cancel ()**

Reimplemented in [OsclActiveObject](#), and [OsclTimerObject](#).

**7.250.3.4 void PVActiveBase::Destroy ()**

**7.250.3.5 virtual void PVActiveBase::DoCancel () [pure virtual]**

Implements cancellation of an outstanding request.

This function is called as part of the active object's [Cancel\(\)](#).

It must call the appropriate cancel function offered by the active object's asynchronous service provider. The asynchronous service provider's cancel is expected to act immediately.

[DoCancel\(\)](#) must not wait for event completion; this is handled by [Cancel\(\)](#).

Implemented in [OsclDNSRequestAO](#), [OsclSocketRequestAO](#), [OsclActiveObject](#), and [OsclTimerObject](#).

**7.250.3.6 OSCL\_IMPORT\_REF bool PVActiveBase::IsAdded ()**

**7.250.3.7 bool PVActiveBase::IsInAnyQ () [inline]**

**7.250.3.8 void PVActiveBase::RemoveFromScheduler ()**

Reimplemented in [OsclActiveObject](#), and [OsclTimerObject](#).

**7.250.3.9 virtual void PVActiveBase::Run () [pure virtual]**

Handles an active object's request completion event.

A derived class must provide an implementation to handle the completed request. If appropriate, it may issue another request.

The function is called by the active scheduler when a request completion event occurs, i.e. after the active scheduler's `WaitForAnyRequest()` function completes.

Before calling this active object's `Run()` function, the active scheduler has:

1. decided that this is the highest priority active object with a completed request
2. marked this active object's request as complete (i.e. the request is no longer outstanding)

`Run()` runs under a trap harness in the active scheduler. If it leaves, then the active scheduler calls `ExecError()` to handle the leave.

Note that once the active scheduler's `Start()` function has been called, all user code is run under one of the program's active object's `Run()` or `RunError()` functions.

Implemented in [OsclDNSMethod](#), [OsclDNSRequestAO](#), [OsclSocketMethod](#), [OsclSocketRequestAO](#), and [CallbackTimer< Alloc >](#).

**7.250.3.10 virtual int32 PVActiveBase::RunError (int32 *aError*) [pure virtual]**

Virtual routine that gets called if the active object's Run routine leaves.

**Parameters:**

***aError*:** the leave code generated by the Run.

**Returns:**

:returns `OsclErrNone` if the error was handled, or returns the input *aError* value if not handled.

Implemented in [OsclActiveObject](#), and [OsclTimerObject](#).

## 7.250.4 Friends And Related Function Documentation

**7.250.4.1 friend class OsclActiveObject [friend]**

**7.250.4.2 friend class OsclExecScheduler [friend]**

**7.250.4.3 friend class OsclReadyCompare [friend]**

**7.250.4.4 friend class OsclReadyQ [friend]**

**7.250.4.5 friend class OsclReadySetPosition [friend]**

**7.250.4.6 friend class OsclSchedulerCommonBase [friend]**

**7.250.4.7 friend class OsclTimerObject [friend]**

**7.250.4.8 friend class PVActiveStats [friend]**

## 7.250.5 Field Documentation

**7.250.5.1 uint32 PVActiveBase::iAddedNum**

**7.250.5.2 bool PVActiveBase::iBusy**

**7.250.5.3 OsclNameString<PVEXECNAMELEN> PVActiveBase::iName**

**7.250.5.4 PVActiveStats\* PVActiveBase::iPVActiveStats**

**7.250.5.5 TReadyQueLink PVActiveBase::iPVReadyQLink**

**7.250.5.6 OsclAOStatus PVActiveBase::iStatus**

The request status associated with an asynchronous request.

This is passed as a parameter to all asynchronous service providers.

The active scheduler uses this to check whether the active object's request has completed.

The function can use the completion code to judge the success or otherwise of the request.

Request status contains one of the values OSCL\_REQUEST\_ERR\_NONE: request completed with no error, or request is not active. OSCL\_REQUEST\_PENDING: request is active & pending OSCL\_REQUEST\_ERR\_CANCEL: request was canceled before completion. or any user-defined value.

**7.250.5.7 PVThreadContext PVActiveBase::iThreadContext**

The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_aobase.h](#)

## 7.251 PVActiveStats Class Reference

```
#include <oscl_scheduler_aobase.h>
```

### Friends

- class [PVActiveBase](#)
- class [OsclExecScheduler](#)
- class [OsclExecSchedulerCommonBase](#)
- class [OsclActiveObject](#)
- class [OsclTimerObject](#)
- class [OsclReadyQ](#)

### 7.251.1 Detailed Description

PV AO statistics

### 7.251.2 Friends And Related Function Documentation

**7.251.2.1 friend class OsclActiveObject [friend]**

**7.251.2.2 friend class OsclExecScheduler [friend]**

**7.251.2.3 friend class OsclExecSchedulerCommonBase [friend]**

**7.251.2.4 friend class OsclReadyQ [friend]**

**7.251.2.5 friend class OsclTimerObject [friend]**

**7.251.2.6 friend class PVActiveBase [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_aobase.h](#)

## 7.252 PVLogger Class Reference

```
#include <pvlogger.h>
```

### Public Types

- `typedef int32 log_level_type`
- `typedef int32 message_id_type`
- `typedef int32 filter_status_type`
- `typedef _OsclBasicAllocator alloc_type`

### Public Methods

- `void SetLogLevel (log_level_type level)`
- `OSCL_IMPORT_REF void SetLogLevelAndPropagate (log_level_type level)`
- `log_level_type GetLogLevel ()`
- `void DisableAppenderInheritance ()`
- `void AddAppender (OsclSharedPtr< PVLoggerAppender > &appender)`
- `void RemoveAppender (OsclSharedPtr< PVLoggerAppender > &appender)`
- `void AddFilter (OsclSharedPtr< PVLoggerFilter > &filter)`
- `uint32 GetNumAppenders ()`
- `OSCL_IMPORT_REF bool IsActive (log_level_type level)`
- `OSCL_IMPORT_REF void LogMsgStringV (message_id_type msgID, const char *fmt, va_list arguments)`
- `OSCL_IMPORT_REF void LogMsgBuffersV (message_id_type msgID, int32 numPairs, va_list arguments)`
- `OSCL_IMPORT_REF void LogMsgString (message_id_type msgID, const char *fmt,...)`
- `OSCL_IMPORT_REF void LogMsgBuffers (message_id_type msgID, int32 numPairs,...)`
- `OSCL_IMPORT_REF PVLogger (const char *inputTag, log_level_type level, bool oAppenderInheritance)`
- `virtual ~PVLogger ()`

### Static Public Methods

- `OSCL_IMPORT_REF void Init ()`
- `OSCL_IMPORT_REF void Cleanup ()`
- `OSCL_IMPORT_REF PVLogger * GetLoggerObject (const char *inputTag)`

### Protected Methods

- `void SetParent (PVLogger *parentLogger)`
- `PVLogger * GetParent ()`

### Friends

- class `PVLoggerRegistry`

### 7.252.1 Member Typedef Documentation

**7.252.1.1** `typedef _OsclBasicAllocator PVLogger::alloc_type`

**7.252.1.2** `typedef int32 PVLogger::filter_status_type`

**7.252.1.3** `typedef int32 PVLogger::log_level_type`

**7.252.1.4** `typedef int32 PVLogger::message_id_type`

### 7.252.2 Constructor & Destructor Documentation

**7.252.2.1** `OSCL_IMPORT_REF PVLogger::PVLogger (const char * inputTag, log_level_type level, bool oAppenderInheritance)`

Logger Constructor

**Parameters:**

*tag* Logger tag, unique to a logging control point

*level* Active Log level of the logger

*oAppenderInheritance*

**Returns:**

NONE

**7.252.2.2** `virtual PVLogger::~PVLogger () [inline, virtual]`

### 7.252.3 Member Function Documentation

**7.252.3.1** `void PVLogger::AddAppender (OsclSharedPtr< PVLoggerAppender > & appender) [inline]`

This method adds an appender to the logging control point. Each logger maintains a list of appenders. Any msg to a logger if deemed active is logged to all the appenders.

**Parameters:**

*appender* pointer to the appender to add

**Returns:**

NONE

**Exceptions:**

*leaves* if out of memory

**7.252.3.2** `void PVLogger::AddFilter (OsclSharedPtr< PVLoggerFilter > & filter) [inline]`

This method adds a message filter to the logging control point. Each logger maintains a list of filters. Any msg to a logger if deemed active is passed through the msg filters prior to logging.

**Parameters:**

*msgFilter* pointer to the filter to add

**Returns:**

NONE

**Exceptions:**

*leaves* if out of memory

**7.252.3.3 OSCL\_IMPORT\_REF void PVLogger::Cleanup () [static]**

Frees the PVLogger singleton used by the current thread. This must be called before thread exit. No messages can be logged after cleanup.

**Returns:****7.252.3.4 void PVLogger::DisableAppenderInheritance () [inline]**

This method disables appender inheritance for the logging control point

**7.252.3.5 OSCL\_IMPORT\_REF PVLogger\* PVLogger::GetLoggerObject (const char \* *inputTag*) [static]**

This is a factory method to create a log control point, with a certain input tag. There is a central registry of all the loggers, with their corresponding tags, called PV Logger Registry. In case the logger with the specified tag exists in the global registry, it is returned, else a new one is created and a pointer to the same is returned.

**Parameters:**

*inputTag* logger tag, viz. "x.y.z"

*level* log level associated with the logging control point (All messages with log levels less than equal to the log level of the control point would be logged)

*oAppenderInheritance*

**Returns:**

PVLogger\* Pointer to the logging control point

**Exceptions:**

*leaves* if out of memory

**7.252.3.6 log\_level\_type PVLogger::GetLogLevel () [inline]**

This method returns the log level of a control point. This could either have been set explicitly by the user (at the time of creation or later) or could have been inherited from one of its ancestors.

**Returns:**

log level associated with the logging control point

**7.252.3.7 uint32 PVLogger::GetNumAppenders () [inline]**

This method returns the number of appenders attached to the logging control point.

**7.252.3.8 PVLogger\* PVLogger::GetParent () [inline, protected]****7.252.3.9 OSCL\_IMPORT\_REF void PVLogger::Init () [static]**

PVLogger needs to be initialized once per thread. This creates the PVLogger singleton that is used throughout the duration of the thread. Initialization must occur before the first message is logged.

**Exceptions:**

*leaves* if out of memory

**7.252.3.10 OSCL\_IMPORT\_REF bool PVLogger::IsActive ([log\\_level\\_type level](#))**

This method determines if a msg passed to the logging control point is active or not. Only messages that are deemed active are logged. Messages are considered not active if any of the following criteria are met:

- All logging is disabled at this logging control point
- If all the log levels, leading upto the root log point are uninitialized
- If the log level of the incoming message is LESS THAN that of the active log level of the logging control point.

**Returns:**

BOOL

**7.252.3.11 OSCL\_IMPORT\_REF void PVLogger::LogMsgBuffers ([message\\_id\\_type msgID](#), int32 *numPairs*, ...)**

This method logs opaque data buffers to all the appenders, after running through the message filters. After logging the message to the appenders attached to the current control point, the message is passed up to the parent node, only if appender inheritance is enabled.

**Parameters:**

*msgID* Message ID, that is unique to a message

*numPairs* Number of (ptr\_len, ptr) pairs

*arguments* Variable list of arguments

**Returns:**

NONE

**7.252.3.12 OSCL\_IMPORT\_REF void PVLogger::LogMsgBuffersV ([message\\_id\\_type msgID](#), int32 *numPairs*, va\_list *arguments*)**

This method logs opaque data buffers to all the appenders, after running through the message filters. After logging the message to the appenders attached to the current control point, the message is passed up to the parent node, only if appender inheritance is enabled.

**Parameters:**

*msgID* Message ID, that is unique to a message

*numPairs* Number of (ptr\_len, ptr) pairs

*arguments* Variable list of arguments

**Returns:**

NONE

**7.252.3.13 OSCL\_IMPORT\_REF void PVLogger::LogMsgString (*message\_id\_type msgID, const char \*fmt, ...)***

This method logs formatted text msg to all the appenders, after running through the message filters. After logging the message to the appenders attached to the current control point, the message is passed up to the parent node, only if appender inheritance is enabled.

**Parameters:**

*msgID* Message ID, that is unique to a message

*fmt* format string, similar to one taken by printf

*arguments* Variable list of arguments

**Returns:**

NONE

**7.252.3.14 OSCL\_IMPORT\_REF void PVLogger::LogMsgStringV (*message\_id\_type msgID, const char \*fmt, va\_list arguments)***

This method logs formatted text msg to all the appenders, after running through the message filters. After logging the message to the appenders attached to the current control point, the message is passed up to the parent node, only if appender inheritance is enabled.

**Parameters:**

*msgID* Message ID, that is unique to a message

*fmt* format string, similar to one taken by printf

*arguments* Variable list of arguments

**Returns:**

NONE

**7.252.3.15 void PVLogger::RemoveAppender (*OsclSharedPtr< PVLoggerAppender > & appender*) [inline]**

This method removes an appender from the logging control point. Each logger maintains a list of appenders. Any msg to a logger if deemed active is logged to all the appenders.

**Parameters:**

*appender* pointer to the appender to delete

**Returns:**

NONE

**7.252.3.16 void PVLogger::SetLogLevel (*log\_level\_type* *level*) [inline]**

This method is used to set the log level of a control point.

**Parameters:**

*level* log level associated with the logging control point

**Returns:**

NONE

**7.252.3.17 OSCL\_IMPORT\_REF void PVLogger::SetLogLevelAndPropagate (*log\_level\_type* *level*)**

This method is used to set the log level of a control point, as well as to propagate the level to all the descendants of this control point.

**Parameters:**

*level* log level associated with the logging control point

**Returns:**

NONE

**7.252.3.18 void PVLogger::SetParent (PVLogger \**parentLogger*) [inline, protected]****7.252.4 Friends And Related Function Documentation****7.252.4.1 friend class PVLoggerRegistry [friend]**

The documentation for this class was generated from the following file:

- [pvlogger.h](#)

## 7.253 PVLoggerAppender Class Reference

```
#include <pvlogger_accessories.h>
```

### Public Types

- `typedef PVLogger::message_id_type message_id_type`

### Public Methods

- `virtual ~PVLoggerAppender ()`
- `virtual void AppendString (message_id_type msgID, const char *fmt, va_list va)=0`
- `virtual void AppendBuffers (message_id_type msgID, int32 numPairs, va_list va)=0`

#### 7.253.1 Detailed Description

Base class for all message appenders. This class defines the interface to the message appenders. There are two kinds of msg appender APIs, one to append text messages, and other to append opaque message buffers.

#### 7.253.2 Member Typedef Documentation

##### 7.253.2.1 `typedef PVLogger::message_id_type PVLoggerAppender::message_id_type`

#### 7.253.3 Constructor & Destructor Documentation

##### 7.253.3.1 `virtual PVLoggerAppender::~PVLoggerAppender () [inline, virtual]`

#### 7.253.4 Member Function Documentation

##### 7.253.4.1 `virtual void PVLoggerAppender::AppendBuffers (message_id_type msgID, int32 numPairs, va_list va) [pure virtual]`

##### 7.253.4.2 `virtual void PVLoggerAppender::AppendString (message_id_type msgID, const char *fmt, va_list va) [pure virtual]`


The documentation for this class was generated from the following file:

- `pvlogger_accessories.h`

## 7.254 PVLoggerFilter Class Reference

```
#include <pvlogger_accessories.h>
```

Inheritance diagram for PVLoggerFilter::



### Public Types

- `typedef PVLogger::message_id_type message_id_type`
- `typedef PVLogger::log_level_type log_level_type`
- `typedef PVLogger::filter_status_type filter_status_type`

### Public Methods

- `virtual ~PVLoggerFilter ()`
- `virtual filter_status_type FilterString (char *tag, message_id_type msgID, log_level_type level)=0`
- `virtual filter_status_type FilterOpaqueMessge (char *tag, message_id_type msgID, log_level_type level)=0`

#### 7.254.1 Detailed Description

Base class for all message filters. This class defines the interface to the message filters. There are two kinds of msg filtering APIs, one to filter text messages, and other to filter opaque message buffers.

#### 7.254.2 Member Typedef Documentation

##### 7.254.2.1 `typedef PVLogger::filter_status_type PVLoggerFilter::filter_status_type`

Reimplemented in [AllPassFilter](#).

##### 7.254.2.2 `typedef PVLogger::log_level_type PVLoggerFilter::log_level_type`

Reimplemented in [AllPassFilter](#).

##### 7.254.2.3 `typedef PVLogger::message_id_type PVLoggerFilter::message_id_type`

Reimplemented in [AllPassFilter](#).

### 7.254.3 Constructor & Destructor Documentation

7.254.3.1 `virtual PVLoggerFilter::~PVLoggerFilter () [inline, virtual]`

### 7.254.4 Member Function Documentation

7.254.4.1 `virtual filter_status_type PVLoggerFilter::FilterOpaqueMessge (char * tag, message_id_type msgID, log_level_type level) [pure virtual]`

Implemented in [AllPassFilter](#).

7.254.4.2 `virtual filter_status_type PVLoggerFilter::FilterString (char * tag, message_id_type msgID, log_level_type level) [pure virtual]`

Implemented in [AllPassFilter](#).

The documentation for this class was generated from the following file:

- [pvlogger\\_accessories.h](#)

## 7.255 PVLoggerLayout Class Reference

```
#include <pvlogger_accessories.h>
```

### Public Types

- `typedef PVLogger::message_id_type message_id_type`

### Public Methods

- `virtual ~PVLoggerLayout ()`
- `virtual int32 FormatString (char *formatBuf, int32 formatBufSize, message_id_type msgID, const char *fmt, va_list va)=0`
- `virtual int32 FormatOpaqueMessage (char *formatBuf, int32 formatBufSize, message_id_type msgID, int32 numPairs, va_list va)=0`

#### 7.255.1 Detailed Description

Base class for all message formatters. This class defines the interface to the message formatter. There are two kinds of msg formatting APIs, one to format text messages, and other to format opaque message buffers.

#### 7.255.2 Member Typedef Documentation

##### 7.255.2.1 `typedef PVLogger::message_id_type PVLoggerLayout::message_id_type`

#### 7.255.3 Constructor & Destructor Documentation

##### 7.255.3.1 `virtual PVLoggerLayout::~PVLoggerLayout () [inline, virtual]`

#### 7.255.4 Member Function Documentation

##### 7.255.4.1 `virtual int32 PVLoggerLayout::FormatOpaqueMessage (char *formatBuf, int32 formatBufSize, message_id_type msgID, int32 numPairs, va_list va) [pure virtual]`

Formats the data and copies it to the given buffer.

#### Returns:

The length of the buffer used.

##### 7.255.4.2 `virtual int32 PVLoggerLayout::FormatString (char *formatBuf, int32 formatBufSize, message_id_type msgID, const char *fmt, va_list va) [pure virtual]`

Formats the string and copies it to the given buffer.

#### Returns:

The length of the string not including the trailing '\0'

The documentation for this class was generated from the following file:

- [pvlogger\\_accessories.h](#)

## 7.256 PVLoggerRegistry Class Reference

```
#include <pvlogger_registry.h>
```

### Public Types

- `typedef PVLogger::log_level_type log_level_type`
- `typedef PVLogger::alloc_type alloc_type`

### Public Methods

- `OSCL_IMPORT_REF PVLoggerRegistry()`
- `virtual OSCL_IMPORT_REF ~PVLoggerRegistry()`
- `OSCL_IMPORT_REF PVLogger * GetPVLoggerObject (const char *tagIn)`
- `OSCL_IMPORT_REF PVLogger * CreatePVLogger (const char *tagIn, log_level_type level, bool oAppenderInheritance)`
- `OSCL_IMPORT_REF bool SetNodeLogLevelExplicit (char *tagIn, log_level_type level)`
- `OSCL_IMPORT_REF void SetNodeLogLevelExplicit (Oscl_TagTree< PVLogger *, alloc_type >::node_type *node, log_level_type level)`

### Static Public Methods

- `OSCL_IMPORT_REF PVLoggerRegistry * GetPVLoggerRegistry()`

#### 7.256.1 Detailed Description

Class: PVLoggerRegistry

PVLoggerRegistry class, maintains a repository of all the loggers, along with their associated tags, in a tag tree. Any request for a log control point is serviced by this class.

Memory Ownership: Creates log control points for each tag, and holds these pointers in the tag tree. `PVLogger` registry is responsible for calling the destructor on each of these loggers.

#### 7.256.2 Member Typedef Documentation

##### 7.256.2.1 `typedef PVLogger::alloc_type PVLoggerRegistry::alloc_type`

##### 7.256.2.2 `typedef PVLogger::log_level_type PVLoggerRegistry::log_level_type`

#### 7.256.3 Constructor & Destructor Documentation

##### 7.256.3.1 `OSCL_IMPORT_REF PVLoggerRegistry::PVLoggerRegistry()`

PVLoggerRegistry Constructor

##### 7.256.3.2 `virtual OSCL_IMPORT_REF PVLoggerRegistry::~PVLoggerRegistry()` [virtual]

PVLoggerRegistry Destructor

## 7.256.4 Member Function Documentation

### 7.256.4.1 OSCL\_IMPORT\_REF PVLogger\* PVLoggerRegistry::CreatePVLogger (const char \* *tagIn*, log\_level\_type *level*, bool *oAppenderInheritance*)

This method creates a log control point, with specified tag, and level

**Parameters:**

*inputTag* logger tag, viz. "x.y.z"  
*level* log level associated with the logging control point  
*oAppenderInheritance*

**Returns:**

PVLogger<alloc\_type, TheLock>\* Pointer to the logging control point

### 7.256.4.2 OSCL\_IMPORT\_REF PVLogger\* PVLoggerRegistry::GetPVLoggerObject (const char \* *tagIn*)

PVLoggerRegistry method to get access to a logging control point, associated with a tag. In case the logger for this tag does not exist, it is created afresh, else pointer to the existing one is returned.

**Parameters:**

*inputTag* logger tag, viz. "x.y.z"  
*level* log level associated with the logging control point  
*oAppenderInheritance*

**Returns:**

PVLogger<Alloc, TheLock>\* Pointer to the logging control point

### 7.256.4.3 OSCL\_IMPORT\_REF PVLoggerRegistry\* PVLoggerRegistry::GetPVLoggerRegistry () [static]

Get the logger registry. There is only one logger registry instance per thread.

### 7.256.4.4 OSCL\_IMPORT\_REF void PVLoggerRegistry::SetNodeLogLevelExplicit (Oscl\_TagTree< PVLogger \*, alloc\_type >::node\_type \* *node*, log\_level\_type *level*)

This method recursively propagates the log level to all the descendants, of a node.

**Parameters:**

*node* Node ptr, associated with a logger, from the tag tree.  
*level* log level associated with the logging control point

**Returns:**

NONE

#### 7.256.4.5 OSCL\_IMPORT\_REF bool PVLoggerRegistry::SetNodeLogLevelExplicit (char \* *tagIn*, *log\_level\_type level*)

This method propagates the log level to all the descendants of the node, with a specified tag.

**Parameters:**

*tagIn* logger tag, viz. "x.y.z"

*level* log level associated with the logging control point

**Returns:**

true on success, else false.


The documentation for this class was generated from the following file:

- [pvlogger\\_registry.h](#)

## 7.257 PVSchedulerStopper Class Reference

```
#include <oscl_scheduler.h>
```

Inheritance diagram for PVSchedulerStopper::



### Public Methods

- [PVSchedulerStopper \(\)](#)
- [~PVSchedulerStopper \(\)](#)

#### 7.257.1 Detailed Description

Scheduler stopper AO class, for internal use by scheduler.

#### 7.257.2 Constructor & Destructor Documentation

##### 7.257.2.1 PVSchedulerStopper::PVSchedulerStopper ()

##### 7.257.2.2 PVSchedulerStopper::~PVSchedulerStopper ()

The documentation for this class was generated from the following file:

- [oscl\\_scheduler.h](#)

## 7.258 PVSockBufRecv Class Reference

```
#include <oscl_socket_request.h>
```

### Public Methods

- [PVSockBufRecv \(\)](#)
- [PVSockBufRecv \(uint8 \\*aPtr, uint32 aLen, uint32 aMax\)](#)
- [PVSockBufRecv \(const PVSockBufRecv &a\)](#)

### Data Fields

- [uint8 \\* iPtr](#)
- [uint32 iLen](#)
- [uint32 iMaxLen](#)

#### 7.258.1 Constructor & Destructor Documentation

**7.258.1.1 PVSockBufRecv::PVSockBufRecv () [inline]**

**7.258.1.2 PVSockBufRecv::PVSockBufRecv (uint8 \* *aPtr*, uint32 *aLen*, uint32 *aMax*) [inline]**

**7.258.1.3 PVSockBufRecv::PVSockBufRecv (const PVSockBufRecv & *a*) [inline]**

#### 7.258.2 Field Documentation

**7.258.2.1 uint32 PVSockBufRecv::iLen**

**7.258.2.2 uint32 PVSockBufRecv::iMaxLen**

**7.258.2.3 uint8\* PVSockBufRecv::iPtr**

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.259 PVSockBufSend Class Reference

```
#include <oscl_socket_request.h>
```

### Public Methods

- [PVSockBufSend \(\)](#)
- [PVSockBufSend \(const uint8 \\*aPtr, uint32 aLen\)](#)
- [PVSockBufSend \(const PVSockBufSend &a\)](#)

### Data Fields

- const uint8 \* [iPtr](#)
- uint32 [iLen](#)

#### 7.259.1 Constructor & Destructor Documentation

**7.259.1.1 PVSockBufSend::PVSockBufSend () [inline]**

**7.259.1.2 PVSockBufSend::PVSockBufSend (const uint8 \* *aPtr*, uint32 *aLen*) [inline]**

**7.259.1.3 PVSockBufSend::PVSockBufSend (const PVSockBufSend & *a*) [inline]**

#### 7.259.2 Field Documentation

**7.259.2.1 uint32 PVSockBufSend::iLen**

**7.259.2.2 const uint8\* PVSockBufSend::iPtr**

The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.260 PVThreadContext Class Reference

```
#include <oscl_scheduler_threadcontext.h>
```

### Public Methods

- OSCL\_IMPORT\_REF PVThreadContext ()
- OSCL\_IMPORT\_REF ~PVThreadContext ()
- OSCL\_IMPORT\_REF bool IsSameThreadContext ()
- OSCL\_IMPORT\_REF void EnterThreadContext ()
- OSCL\_IMPORT\_REF void ExitThreadContext ()

### Static Public Methods

- OSCL\_IMPORT\_REF uint32 Id ()
- OSCL\_IMPORT\_REF bool ThreadHasScheduler ()

### Friends

- class PVActiveBase
- class OsclActiveObject
- class OsclTimerObject
- class OsclExecScheduler
- class OsclCoeActiveScheduler
- class OsclExecSchedulerCommonBase
- class OsclExecSchedulerBase
- class OsclCoeActiveSchedulerBase

#### 7.260.1 Constructor & Destructor Documentation

##### 7.260.1.1 OSCL\_IMPORT\_REF PVThreadContext::PVThreadContext ()

##### 7.260.1.2 OSCL\_IMPORT\_REF PVThreadContext::~PVThreadContext ()

#### 7.260.2 Member Function Documentation

##### 7.260.2.1 OSCL\_IMPORT\_REF void PVThreadContext::EnterThreadContext ()

enter and exit thread context.

##### 7.260.2.2 OSCL\_IMPORT\_REF void PVThreadContext::ExitThreadContext ()

##### 7.260.2.3 OSCL\_IMPORT\_REF uint32 PVThreadContext::Id () [static]

static routine to get a unique thread ID for caller's thread context.

**7.260.2.4 OSCL\_IMPORT\_REF bool PVThreadContext::IsSameThreadContext ()**

compare caller's thread context to this one.

**7.260.2.5 OSCL\_IMPORT\_REF bool PVThreadContext::ThreadHasScheduler () [static]**

a static utility to tell whether the calling thread has any scheduler— either Oscl scheduler or native scheduler.

**7.260.3 Friends And Related Function Documentation****7.260.3.1 friend class OsclActiveObject [friend]****7.260.3.2 friend class OsclCoeActiveScheduler [friend]****7.260.3.3 friend class OsclCoeActiveSchedulerBase [friend]****7.260.3.4 friend class OsclExecScheduler [friend]****7.260.3.5 friend class OsclExecSchedulerBase [friend]****7.260.3.6 friend class OsclExecSchedulerCommonBase [friend]****7.260.3.7 friend class OsclTimerObject [friend]****7.260.3.8 friend class PVActiveBase [friend]**


The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_threadcontext.h](#)

## 7.261 RecvFromParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for RecvFromParam::



### Public Methods

- [RecvFromParam \(uint8 \\*&aPtr, uint32 aMaxLen, OsclNetworkAddress &aAddress, uint32 flags, uint32 aMultiMax, Oscl\\_Vector< uint32, OsclMemAllocator > \\*aPacketLen, Oscl\\_Vector< OsclNetworkAddress, OsclMemAllocator > \\*aPacketSource\)](#)

### Data Fields

- [PVSockBufRecv iBufRecv](#)
- [uint32 iFlags](#)
- [OsclNetworkAddress & iAddr](#)
- [uint32 iMultiMaxLen](#)
- [Oscl\\_Vector< uint32, OsclMemAllocator > \\* iPacketLen](#)
- [Oscl\\_Vector< OsclNetworkAddress, OsclMemAllocator > \\* iPacketSource](#)

#### 7.261.1 Constructor & Destructor Documentation

[7.261.1.1 RecvFromParam::RecvFromParam \(uint8 \\*& aPtr, uint32 aMaxLen, OsclNetworkAddress & aAddress, uint32 flags, uint32 aMultiMax, Oscl\\_Vector< uint32, OsclMemAllocator > \\* aPacketLen, Oscl\\_Vector< OsclNetworkAddress, OsclMemAllocator > \\* aPacketSource\) \[inline\]](#)

#### 7.261.2 Field Documentation

[7.261.2.1 OsclNetworkAddress& RecvFromParam::iAddr](#)

[7.261.2.2 PVSockBufRecv RecvFromParam::iBufRecv](#)

[7.261.2.3 uint32 RecvFromParam::iFlags](#)

[7.261.2.4 uint32 RecvFromParam::iMultiMaxLen](#)

[7.261.2.5 Oscl\\_Vector<uint32, OsclMemAllocator>\\* RecvFromParam::iPacketLen](#)

[7.261.2.6 Oscl\\_Vector<OsclNetworkAddress, OsclMemAllocator>\\* RecvFromParam::iPacketSource](#)


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.262 RecvParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for RecvParam::



### Public Methods

- [RecvParam \(uint8 \\*&aPtr, uint32 aMaxLen, uint32 flags\)](#)

### Data Fields

- [PVSockBufRecv iBufRecv](#)
- [uint32 iFlags](#)

#### 7.262.1 Constructor & Destructor Documentation

**7.262.1.1 RecvParam::RecvParam (uint8 \*& aPtr, uint32 aMaxLen, uint32 flags) [inline]**

#### 7.262.2 Field Documentation

**7.262.2.1 PVSockBufRecv RecvParam::iBufRecv**

**7.262.2.2 uint32 RecvParam::iFlags**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.263 SendParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for SendParam::



### Public Methods

- [SendParam \(const uint8 \\*&aPtr, uint32 aLen, uint32 aFlags\)](#)

### Data Fields

- [PVSockBufSend iBufSend](#)
- [uint32 iFlags](#)
- [uint32 iXferLen](#)

#### 7.263.1 Detailed Description

Socket method parameter sets

#### 7.263.2 Constructor & Destructor Documentation

**7.263.2.1 SendParam::SendParam (const uint8 \*& aPtr, uint32 aLen, uint32 aFlags) [inline]**

#### 7.263.3 Field Documentation

**7.263.3.1 PVSockBufSend SendParam::iBufSend**

**7.263.3.2 uint32 SendParam::iFlags**

**7.263.3.3 uint32 SendParam::iXferLen**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.264 SendToParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for SendToParam::



### Public Methods

- [SendToParam \(const uint8 \\*&aPtr, uint32 aLen, OsclNetworkAddress &anAddr, uint32 flags\)](#)
- [~SendToParam \(\)](#)

### Data Fields

- [PVSockBufSend iBufSend](#)
- [uint32 iFlags](#)
- [OsclNetworkAddress iAddr](#)
- [uint32 iXferLen](#)

#### 7.264.1 Constructor & Destructor Documentation

**7.264.1.1 SendToParam::SendToParam (const uint8 \*& *aPtr*, uint32 *aLen*, OsclNetworkAddress & *anAddr*, uint32 *flags*) [inline]**

**7.264.1.2 SendToParam::~SendToParam () [inline]**

#### 7.264.2 Field Documentation

**7.264.2.1 OsclNetworkAddress SendToParam::iAddr**

**7.264.2.2 PVSockBufSend SendToParam::iBufSend**

**7.264.2.3 uint32 SendToParam::iFlags**

**7.264.2.4 uint32 SendToParam::iXferLen**


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.265 ShutdownParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for ShutdownParam::



### Public Methods

- [ShutdownParam \(TPVSocketShutdown aHow\)](#)

### Data Fields

- [TPVSocketShutdown iHow](#)

#### 7.265.1 Constructor & Destructor Documentation

**7.265.1.1 ShutdownParam::ShutdownParam ([TPVSocketShutdown aHow](#)) [inline]**

#### 7.265.2 Field Documentation

##### 7.265.2.1 [TPVSocketShutdown ShutdownParam::iHow](#)


The documentation for this class was generated from the following file:

- [oscl\\_socket\\_request.h](#)

## 7.266 SocketRequestParam Class Reference

```
#include <oscl_socket_request.h>
```

Inheritance diagram for SocketRequestParam::



### Public Methods

- [SocketRequestParam \(TPVSocketFxn aFxn\)](#)

### Data Fields

- [TPVSocketFxn iFxn](#)

#### 7.266.1 Detailed Description

Base class for all socket method parameter sets

## 7.266.2 Constructor & Destructor Documentation

7.266.2.1 `SocketRequestParam::SocketRequestParam (TPVSocketFxn aFxn) [inline]`

## 7.266.3 Field Documentation

7.266.3.1 `TPVSocketFxn SocketRequestParam::iFxn`

The documentation for this class was generated from the following file:


- `oscl_socket_request.h`

## 7.267 StrCSumPtrLen Struct Reference

same as [StrPtrLen](#), but includes checksum field and method to speed up querying

```
#include <oscl_str_ptr_len.h>
```

Inheritance diagram for StrCSumPtrLen::



### Public Types

- [typedef int16 CheckSumType](#)

### Public Methods

- [void setPtrLen \(const char \\*newPtr, uint32 newLen\)](#)
- [CheckSumType getCheckSum \(\) const](#)
- [OSCL\\_IMPORT\\_REF void setCheckSum \(\)](#)
- [StrCSumPtrLen \(\)](#)
- [StrCSumPtrLen \(const char \\*newPtr\)](#)
- [StrCSumPtrLen \(const char \\*newPtr, uint32 newLen\)](#)
- [StrCSumPtrLen \(const StrCSumPtrLen &rhs\)](#)
- [StrCSumPtrLen \(const StrPtrLen &rhs\)](#)
- [c\\_bool isCIEquivalentTo \(const StrCSumPtrLen &rhs\) const](#)
- [c\\_bool operator== \(const StrCSumPtrLen &rhs\) const](#)
- [c\\_bool operator!= \(const StrCSumPtrLen &rhs\) const](#)
- [StrCSumPtrLen & operator= \(const StrCSumPtrLen &rhs\)](#)
- [StrCSumPtrLen & operator= \(const StrPtrLen &rhs\)](#)
- [StrCSumPtrLen & operator= \(const char \\*rhs\)](#)

### Protected Attributes

- [CheckSumType checkSum](#)

#### 7.267.1 Detailed Description

same as [StrPtrLen](#), but includes checksum field and method to speed up querying

## 7.267.2 Member Typedef Documentation

**7.267.2.1** `typedef int16 StrCSumPtrLen::CheckSumType`

## 7.267.3 Constructor & Destructor Documentation

**7.267.3.1** `StrCSumPtrLen::StrCSumPtrLen () [inline]`

**7.267.3.2** `StrCSumPtrLen::StrCSumPtrLen (const char * newPtr) [inline]`

**7.267.3.3** `StrCSumPtrLen::StrCSumPtrLen (const char * newPtr, uint32 newLen) [inline]`

**7.267.3.4** `StrCSumPtrLen::StrCSumPtrLen (const StrCSumPtrLen & rhs) [inline]`

**7.267.3.5** `StrCSumPtrLen::StrCSumPtrLen (const StrPtrLen & rhs) [inline]`

## 7.267.4 Member Function Documentation

**7.267.4.1** `CheckSumType StrCSumPtrLen::getCheckSum () const [inline]`

**7.267.4.2** `c_bool StrCSumPtrLen::isCIEquivalentTo (const StrCSumPtrLen & rhs) const [inline]`

**7.267.4.3** `c_bool StrCSumPtrLen::operator!= (const StrCSumPtrLen & rhs) const [inline]`

**7.267.4.4** `StrCSumPtrLen& StrCSumPtrLen::operator= (const char * rhs) [inline]`

Reimplemented from [StrPtrLen](#).

**7.267.4.5** `StrCSumPtrLen& StrCSumPtrLen::operator= (const StrPtrLen & rhs) [inline]`

Reimplemented from [StrPtrLen](#).

**7.267.4.6** `StrCSumPtrLen& StrCSumPtrLen::operator= (const StrCSumPtrLen & rhs) [inline]`

**7.267.4.7** `c_bool StrCSumPtrLen::operator== (const StrCSumPtrLen & rhs) const [inline]`

**7.267.4.8** `OSCL_IMPORT_REF void StrCSumPtrLen::setCheckSum ()`

**7.267.4.9** `void StrCSumPtrLen::setPtrLen (const char * newPtr, uint32 newLen) [inline]`

Reimplemented from [StrPtrLen](#).

## 7.267.5 Field Documentation

**7.267.5.1** `CheckSumType StrCSumPtrLen::checkSum [protected]`

The documentation for this struct was generated from the following file:


- [oscl\\_str\\_ptr\\_len.h](#)

## 7.268 StrPtrLen Struct Reference

This data structure encapsulates a set of functions used to perform.

```
#include <oscl_str_ptr_len.h>
```

Inheritance diagram for StrPtrLen::



### Public Methods

- [StrPtrLen](#) (const char \*newPtr)
- [StrPtrLen](#) (const char \*newPtr, uint32 newLen)
- [StrPtrLen](#) ()
- [StrPtrLen](#) (const StrPtrLen &rhs)
- const char \* [c\\_str](#) () const
- int32 [length](#) () const
- int32 [size](#) () const
- void [setPtrLen](#) (const char \*newPtr, uint32 newLen)
- [c\\_bool](#) [isCIEquivalentTo](#) (const StrPtrLen &rhs) const
- [c\\_bool](#) [isCIPrefixOf](#) (const StrPtrLen &rhs) const
- int32 [operator==](#) (const StrPtrLen &rhs) const
- int32 [operator!=](#) (const StrPtrLen &rhs) const
- StrPtrLen & [operator=](#) (const StrPtrLen &rhs)
- StrPtrLen & [operator=](#) (const char \*rhs)

### Protected Methods

- bool [isLetter](#) (const char c) const

### Protected Attributes

- const char \* [ptr](#)
- int32 [len](#)

#### 7.268.1 Detailed Description

This data structure encapsulates a set of functions used to perform.

standard string operations. It should be used for null-terminated constant (non-modifiable) strings of char type.

## 7.268.2 Constructor & Destructor Documentation

**7.268.2.1** `StrPtrLen::StrPtrLen (const char * newPtr) [inline]`

**7.268.2.2** `StrPtrLen::StrPtrLen (const char * newPtr, uint32 newLen) [inline]`

**7.268.2.3** `StrPtrLen::StrPtrLen () [inline]`

**7.268.2.4** `StrPtrLen::StrPtrLen (const StrPtrLen & rhs) [inline]`

## 7.268.3 Member Function Documentation

**7.268.3.1** `const char* StrPtrLen::c_str () const [inline]`

**7.268.3.2** `c_bool StrPtrLen::isCIEquivalentTo (const StrPtrLen & rhs) const [inline]`

**7.268.3.3** `c_bool StrPtrLen::isCIPrefixOf (const StrPtrLen & rhs) const [inline]`

**7.268.3.4** `bool StrPtrLen::isLetter (const char c) const [inline, protected]`

**7.268.3.5** `int32 StrPtrLen::length () const [inline]`

**7.268.3.6** `int32 StrPtrLen::operator!= (const StrPtrLen & rhs) const [inline]`

**7.268.3.7** `StrPtrLen& StrPtrLen::operator= (const char * rhs) [inline]`

Reimplemented in [StrCSumPtrLen](#).

**7.268.3.8** `StrPtrLen& StrPtrLen::operator= (const StrPtrLen & rhs) [inline]`

Reimplemented in [StrCSumPtrLen](#).

**7.268.3.9** `int32 StrPtrLen::operator== (const StrPtrLen & rhs) const [inline]`

**7.268.3.10** `void StrPtrLen::setPtrLen (const char * newPtr, uint32 newLen) [inline]`

Reimplemented in [StrCSumPtrLen](#).

**7.268.3.11** `int32 StrPtrLen::size () const [inline]`

## 7.268.4 Field Documentation

**7.268.4.1** `int32 StrPtrLen::len [protected]`

**7.268.4.2** `const char* StrPtrLen::ptr [protected]`

The documentation for this struct was generated from the following file:

- [oscl\\_str\\_ptr\\_len.h](#)

## 7.269 TimeValue Class Reference

The TimeValue class represents a time value in a format native to the system.

```
#include <oscl_time.h>
```

### Public Methods

- OSCL\_COND\_IMPORT\_REF [TimeValue](#) ()
 

*Create a TimeValue representing the current time.*
- OSCL\_COND\_IMPORT\_REF [TimeValue](#) (const [TimeValue](#) &Tv)
 

*Copy constructor.*
- OSCL\_COND\_IMPORT\_REF [TimeValue](#) (long tv, [TimeUnits](#) units)
 

*Create a TimeValue representing an interval of tv units.*
- OSCL\_COND\_IMPORT\_REF [TimeValue](#) (const [OsclBasicTimeStruct](#) &in\_tv)
 

*Create a TimeValue representing the absolute time specified by the BasicTimeStruct.*
- OSCL\_COND\_IMPORT\_REF [TimeValue](#) (const [ISO8601timeStrBuf](#) time\_strbuf)
- OSCL\_COND\_IMPORT\_REF [TimeValue](#) (uint16 aYear, uint16 aMonth, uint16 aDay, uint16 aHour, uint16 aMinute, uint16 aSecond, uint16 aMilliseconds)
- OSCL\_COND\_IMPORT\_REF [TimeValue](#) ([OsclBasicDateTimeStruct](#) in\_ts)
 

*Create a TimeValue representing the absolute time specified by the BasicDateTimeStruct.*
- OSCL\_COND\_IMPORT\_REF int32 [get\\_local\\_time](#) ()
 

*Get the local time after having adjusted for daylight saving.*
- OSCL\_COND\_IMPORT\_REF void [set\\_to\\_zero](#) ()
 

*Set the time value to zero (represents a zero interval).*
- OSCL\_COND\_IMPORT\_REF void [set\\_to\\_current\\_time](#) ()
 

*Set the time value to the current system time.*
- OSCL\_COND\_IMPORT\_REF void [set\\_from\\_ntp\\_time](#) (const uint32 ntp\_offset)
 

*This method converts a 32-bit NTP offset to system time.*
- OSCL\_COND\_IMPORT\_REF uint32 [get\\_sec](#) () const
 

*Get a 32 bit value representing the seconds since the (system dependent) epoch.*
- OSCL\_COND\_IMPORT\_REF int32 [to\\_msec](#) () const
- OSCL\_COND\_IMPORT\_REF uint32 [get\\_usec](#) () const
 

*Get a 32 bit value representing the number of microseconds in the time value.*
- OSCL\_COND\_IMPORT\_REF uint64 [get\\_timevalue\\_in\\_usec](#) () const
 

*Get a 64 bit value representing the time value converted to microseconds.*
- OSCL\_IMPORT\_REF char \* [get\\_str\\_ctime](#) ([CtimeStrBuf](#) ctime\_strbuf)
 

*Get a string containing a text representation of this TimeValue object.*

- OSCL\_IMPORT\_REF int [get\\_pv8601\\_str\\_time](#) (PV8601timeStrBuf time\_stdbuf)
 

*Get a PV extended text representation of the Time based on the PV 8601 format.*
- OSCL\_IMPORT\_REF int [get\\_ISO8601\\_str\\_time](#) (ISO8601timeStrBuf time\_stdbuf)
 

*Get a PV extended text representation of the Time based on the ISO 8601 format.*
- OSCL\_IMPORT\_REF char \* [get\\_rfc822\\_gmtime\\_str](#) (int max\_time\_strlen, char \*time\_str)
 

*Get a text representation of the time in the GMT timezone based on the RFC 822 / RFC 1123 (also described in the HTTP spec RFC 2068 and RFC 2616).*
- OSCL\_COND\_IMPORT\_REF bool [is\\_zero](#) ()
 

*Determine if the time value is zero.*
- OSCL\_COND\_IMPORT\_REF bool [is\\_zulu](#) () const
 

*Manipulate internal flags to mark the time value as being in "zulu" (GMT) time.*
- OSCL\_COND\_IMPORT\_REF void [set\\_zulu](#) (bool is\_zulu)
- OSCL\_COND\_IMPORT\_REF TimeValue & [operator=](#) (const TimeValue &a)
 

*Assignment operator.*
- OSCL\_COND\_IMPORT\_REF TimeValue & [operator+=](#) (const TimeValue &a)
 

*+ = operator*
- OSCL\_COND\_IMPORT\_REF TimeValue & [operator-=](#) (const TimeValue &a)
 

*- = operator*
- OSCL\_COND\_IMPORT\_REF TimeValue & [operator \\*=](#) (const int scale)
 

*This operator scales the time value by a constant.*
- OSCL\_COND\_IMPORT\_REF OsclBasicTimeStruct \* [get\\_timeval\\_ptr](#) ()
- OSCL\_COND\_IMPORT\_REF TimeValue & [operator+=](#) (const int32 aSeconds)
- OSCL\_COND\_IMPORT\_REF TimeValue & [operator-=](#) (const int32 aSeconds)

## Friends

- class [NTPTime](#)
- OSCL\_COND\_IMPORT\_REF friend bool [operator==](#) (const TimeValue &a, const TimeValue &b)
- OSCL\_COND\_IMPORT\_REF friend bool [operator!=](#) (const TimeValue &a, const TimeValue &b)
- OSCL\_COND\_IMPORT\_REF friend bool [operator<=](#) (const TimeValue &a, const TimeValue &b)
- OSCL\_COND\_IMPORT\_REF friend bool [operator>=](#) (const TimeValue &a, const TimeValue &b)
- OSCL\_COND\_IMPORT\_REF friend bool [operator<](#) (const TimeValue &a, const TimeValue &b)
- OSCL\_COND\_IMPORT\_REF friend bool [operator>](#) (const TimeValue &a, const TimeValue &b)

## 7.269.1 Detailed Description

The TimeValue class represents a time value in a format native to the system.

This class provides common time functions independent of any OS. The actual representation used is native to the system that the class is compiled on to increase efficiency. Macros used in this class:

- OSCL\_HAS\_ANSI\_STRING\_SUPPORT:

Definitions to determine the type of basic time structure used to store the time

- OSCL\_HAS\_UNIX\_TIME\_FUNCS
- OSCL\_HAS\_SYMBIAN\_SUPPORT
- OSCL\_HAS\_MSWIN\_SUPPORT

## 7.269.2 Constructor & Destructor Documentation

### 7.269.2.1 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue ()

Create a TimeValue representing the current time.

### 7.269.2.2 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue (const TimeValue & *Tv*)

Copy constructor.

### 7.269.2.3 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue (long *tv*, TimeUnits *units*)

Create a TimeValue representing an interval of tv units.

**Parameters:**

- tv* The number of units in the interval to be represented by this TimeValue.
- units* The units of the tv argument. Must be in the enumeration TimeUnits.

### 7.269.2.4 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue (const OsclBasicTimeStruct & *in\_tv*)

Create a TimeValue representing the absolute time specified by the BasicTimeStruct.

**Parameters:**

- in\_tv* OsclBasicTimeStruct as defined for each platform.

### 7.269.2.5 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue (const ISO8601timeStrBuf *time\_strbuf*)

### 7.269.2.6 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue (uint16 *aYear*, uint16 *aMonth*, uint16 *aDay*, uint16 *aHour*, uint16 *aMinute*, uint16 *aSecond*, uint16 *aMilliseconds*)

TimeValue constructor that sets time according to following input parameter for a specific date time. Please note that no argument is check for its validity (range etc) It might assert incase wrong argument are passed by user of this api.

**Parameters:**

*in ] uint16 wYear;*  
*in ] uint16 wMonth; Jan = 1 to Dec = 12*  
*in ] uint16 wDay; 1-28/29/30/31*  
*in ] uint16 wHour; 0 to 23*  
*in ] uint16 wMinute; 0 to 59*  
*in ] uint16 wSecond; 0 to 59*  
*in ] uint16 wMilliseconds; 0 to 999*

**7.269.2.7 OSCL\_COND\_IMPORT\_REF TimeValue::TimeValue ([OsclBasicDateTimeStruct in\\_ts](#))**

Create a TimeValue representing the absolute time specified by the BasicDateTimeStruct.

**Parameters:**

*in\_ts* OsclBasicDateTimeStruct as defined for each platform provides the date in a readable format (i.e. day, date, week etc.) Notes: Implementation incomplete (= not done) on Win32, Wince, Symbian

**7.269.3 Member Function Documentation****7.269.3.1 OSCL\_IMPORT\_REF int TimeValue::get\_ISO8601\_str\_time ([ISO8601timeStrBuf time\\_strbuf](#))**

Get a PV extended text representation of the Time based on the ISO 8601 format.

**Parameters:**

*time\_strbuf* A ISO8601timeStrBuf object to which the text representation will be written,

**Returns:**

The number of characters copied to the buffer, not including the terminating null. The returned string is of the form "1985-04-12 10:15:30Z".

**7.269.3.2 OSCL\_COND\_IMPORT\_REF int32 TimeValue::get\_local\_time ()**

Get the local time after having adjusted for daylight saving.

Notes: Implementation incomplete (= not done) on Win32, Wince, Symbian

**7.269.3.3 OSCL\_IMPORT\_REF int TimeValue::get\_pv8601\_str\_time ([PV8601timeStrBuf time\\_strbuf](#))**

Get a PV extended text representation of the Time based on the PV 8601 format.

**Parameters:**

*time\_strbuf* A PV8601timeStrBuf object to which the text representation will be written,

**Returns:**

The number of characters copied to the buffer, not including the terminating null. The returned string is of the form "19850412T101530.047Z".

**7.269.3.4 OSCL\_IMPORT\_REF char\* TimeValue::get\_rfc822\_gmtime\_str (int max\_time\_strlen, char \* time\_str)**

Get a text representation of the time in the GMT timezone based on the RFC 822 / RFC 1123 (also described in the HTTP spec RFC 2068 and RFC 2616).

**Parameters:**

*max\_time\_strlen* The maximum number of characters that can be written to the buffer.

*time\_str* A pointer to the buffer to which the characters will be written.

**Returns:**

Returns a pointer to the buffer (same as *time\_str*) containing a null terminated (c-style) string of the form "Wed, 30 Jun 1993 21:49:08 GMT".

**7.269.3.5 OSCL\_COND\_IMPORT\_REF uint32 TimeValue::get\_sec ()**

Get a 32 bit value representing the seconds since the (system dependent) epoch.

**Returns:**

This call returns a 32 bit value representing the number of seconds since the epoch. On unix systems this represents the number of seconds since the unix epoch Jan 1 1970. On Win32 this represents the number of seconds since Jan 1, 1601. This is intended to be used for intervals rather than for absolute time. (On Win32 for example, a 32 bit value would be too small to represent the number of seconds from the epoch until the current time.)

**7.269.3.6 OSCL\_IMPORT\_REF char\* TimeValue::get\_str\_ctime (CtimeStrBuf ctime\_strbuf)**

Get a string containing a text representation of this TimeValue object.

**Parameters:**

*ctime\_strbuf* A CtimeStrBuf object to which the text representation will be written,

**Returns:**

A pointer to the input CtimeStrBuf is returned. This string is null terminated of the form "Wed Jun 30 21:49:08 1993".

**7.269.3.7 OSCL\_COND\_IMPORT\_REF OsclBasicTimeStruct\* TimeValue::get\_timeval\_ptr ()****7.269.3.8 OSCL\_COND\_IMPORT\_REF uint64 TimeValue::get\_timevalue\_in\_usec ()**

Get a 64 bit value representing the time value converted to microseconds.

**Returns:**

Returns a uint64 value representing the time value in terms of microseconds. The time origin is dependent on platform for which OSCL is compiled. For example for symbian it is midnight, January 1st, 0 AD for windows it is January 1, 1601 (UTC)

**7.269.3.9 OSCL\_COND\_IMPORT\_REF uint32 TimeValue::get\_usec ()**

Get a 32 bit value representing the number of microseconds in the time value.

**Returns:**

Returns a uint32 value representing the number of microseconds in the time value after subtracting off the whole seconds.

**7.269.3.10 OSCL\_COND\_IMPORT\_REF bool TimeValue::is\_zero ()**

Determine if the time value is zero.

**7.269.3.11 OSCL\_COND\_IMPORT\_REF bool TimeValue::is\_zulu ()**

Manipulate internal flags to mark the time value as being in "zulu" (GMT) time.

**7.269.3.12 OSCL\_COND\_IMPORT\_REF TimeValue& TimeValue::operator \*= (const int scale)**

This operator scales the time value by a constant.

**7.269.3.13 OSCL\_COND\_IMPORT\_REF TimeValue& TimeValue::operator+= (const int32 aSeconds)****7.269.3.14 OSCL\_COND\_IMPORT\_REF TimeValue& TimeValue::operator+= (const TimeValue & a)**

+= operator

**7.269.3.15 OSCL\_COND\_IMPORT\_REF TimeValue& TimeValue::operator-= (const int32 aSeconds)****7.269.3.16 OSCL\_COND\_IMPORT\_REF TimeValue& TimeValue::operator-= (const TimeValue & a)**

-= operator

**7.269.3.17 OSCL\_COND\_IMPORT\_REF TimeValue& TimeValue::operator= (const TimeValue & a)**

Assignment operator.

**7.269.3.18 OSCL\_COND\_IMPORT\_REF void TimeValue::set\_from\_ntp\_time (const uint32 ntp\_offset)**

This method converts a 32-bit NTP offset to system time.

This method takes a 32-bit ntp offset which is the number of seconds from 0 h Jan 1, 1900 and converts it to the system time

**7.269.3.19 OSCL\_COND\_IMPORT\_REF void TimeValue::set\_to\_current\_time ()**

Set the time value to the current system time.

**7.269.3.20 OSCL\_COND\_IMPORT\_REF void TimeValue::set\_to\_zero ()**

Set the time value to zero (represents a zero interval).

**7.269.3.21 OSCL\_COND\_IMPORT\_REF void TimeValue::set\_zulu (bool *is\_zulu*)****7.269.3.22 OSCL\_COND\_IMPORT\_REF int32 TimeValue::to\_msec ()****7.269.4 Friends And Related Function Documentation****7.269.4.1 friend class NTPTime [friend]****7.269.4.2 OSCL\_COND\_IMPORT\_REF friend bool operator!= (const TimeValue & *a*, const TimeValue & *b*) [friend]****7.269.4.3 OSCL\_COND\_IMPORT\_REF friend bool operator< (const TimeValue & *a*, const TimeValue & *b*) [friend]****7.269.4.4 OSCL\_COND\_IMPORT\_REF friend bool operator<= (const TimeValue & *a*, const TimeValue & *b*) [friend]****7.269.4.5 OSCL\_COND\_IMPORT\_REF friend bool operator== (const TimeValue & *a*, const TimeValue & *b*) [friend]****7.269.4.6 OSCL\_COND\_IMPORT\_REF friend bool operator> (const TimeValue & *a*, const TimeValue & *b*) [friend]****7.269.4.7 OSCL\_COND\_IMPORT\_REF friend bool operator>= (const TimeValue & *a*, const TimeValue & *b*) [friend]**

The documentation for this class was generated from the following file:

- [oscl\\_time.h](#)

## 7.270 TLSStorageOps Class Reference

```
#include <oscl_tls.h>
```

### Static Public Methods

- OSCL\_IMPORT\_REF void [save\\_registry \(TOsclTlsKey \\*key, OsclAny \\*ptr, int32 &\)](#)
- OSCL\_IMPORT\_REF [OsclAny \\* get\\_registry \(TOsclTlsKey \\*key\)](#)

#### 7.270.1 Member Function Documentation

**7.270.1.1 OSCL\_IMPORT\_REF OsclAny\* TLSStorageOps::get\_registry (TOsclTlsKey \* *key*)  
[static]**

**7.270.1.2 OSCL\_IMPORT\_REF void TLSStorageOps::save\_registry (TOsclTlsKey \* *key*,  
OsclAny \* *ptr*, int32 &) [static]**

The documentation for this class was generated from the following file:

- [oscl\\_tls.h](#)

## 7.271 TReadyQueLink Class Reference

```
#include <oscl_scheduler_readyq.h>
```

### Public Methods

- [TReadyQueLink \(\)](#)

### Data Fields

- int32 [iAOPriority](#)
- uint32 [iTimeToRunTicks](#)
- uint32 [iTimeQueuedTicks](#)
- uint32 [iSeqNum](#)
- OsclAny \* [iIsIn](#)

#### 7.271.1 Detailed Description

This class defines the queue link, which is common to both ready Q and timer Q. Each AO contains its own queue link object.

#### 7.271.2 Constructor & Destructor Documentation

##### 7.271.2.1 [TReadyQueLink::TReadyQueLink \(\) \[inline\]](#)

#### 7.271.3 Field Documentation

##### 7.271.3.1 [int32 TReadyQueLink::iAOPriority](#)

##### 7.271.3.2 [OsclAny\\* TReadyQueLink::iIsIn](#)

##### 7.271.3.3 [uint32 TReadyQueLink::iSeqNum](#)

##### 7.271.3.4 [uint32 TReadyQueLink::iTimeQueuedTicks](#)

##### 7.271.3.5 [uint32 TReadyQueLink::iTimeToRunTicks](#)

The documentation for this class was generated from the following file:

- [oscl\\_scheduler\\_readyq.h](#)

## 7.272 WStrPtrLen Struct Reference

This data structure encapsulates a set of functions used to perform.

```
#include <oscl_str_ptr_len.h>
```

### Public Methods

- [WStrPtrLen \(const oscl\\_wchar \\*newPtr\)](#)
- [WStrPtrLen \(const oscl\\_wchar \\*newPtr, uint32 newLen\)](#)
- [WStrPtrLen \(\)](#)
- [WStrPtrLen \(const WStrPtrLen &rhs\)](#)
- [const oscl\\_wchar \\* c\\_str \(\) const](#)
- [int32 length \(\) const](#)
- [int32 size \(\) const](#)
- [void setPtrLen \(const oscl\\_wchar \\*newPtr, uint32 newLen\)](#)
- [c\\_bool isCIEquivalentTo \(const WStrPtrLen &rhs\) const](#)
- [int32 operator== \(const WStrPtrLen &rhs\) const](#)
- [int32 operator!= \(const WStrPtrLen &rhs\) const](#)
- [WStrPtrLen & operator= \(const WStrPtrLen &rhs\)](#)
- [WStrPtrLen & operator= \(const oscl\\_wchar \\*rhs\)](#)

### Protected Attributes

- [const oscl\\_wchar \\* ptr](#)
- [int32 len](#)

#### 7.272.1 Detailed Description

This data structure encapsulates a set of functions used to perform.

standard string operations. It should be used for null-terminated constant strings (non-modifiable) of wchar type.

## 7.272.2 Constructor & Destructor Documentation

- 7.272.2.1 `WStrPtrLen::WStrPtrLen (const oscl_wchar * newPtr) [inline]`
- 7.272.2.2 `WStrPtrLen::WStrPtrLen (const oscl_wchar * newPtr, uint32 newLen) [inline]`
- 7.272.2.3 `WStrPtrLen::WStrPtrLen () [inline]`
- 7.272.2.4 `WStrPtrLen::WStrPtrLen (const WStrPtrLen & rhs) [inline]`

## 7.272.3 Member Function Documentation

- 7.272.3.1 `const oscl_wchar* WStrPtrLen::c_str () const [inline]`
- 7.272.3.2 `c_bool WStrPtrLen::isCIEquivalentTo (const WStrPtrLen & rhs) const [inline]`
- 7.272.3.3 `int32 WStrPtrLen::length () const [inline]`
- 7.272.3.4 `int32 WStrPtrLen::operator!= (const WStrPtrLen & rhs) const [inline]`
- 7.272.3.5 `WStrPtrLen& WStrPtrLen::operator= (const oscl_wchar * rhs) [inline]`
- 7.272.3.6 `WStrPtrLen& WStrPtrLen::operator= (const WStrPtrLen & rhs) [inline]`
- 7.272.3.7 `int32 WStrPtrLen::operator== (const WStrPtrLen & rhs) const [inline]`
- 7.272.3.8 `void WStrPtrLen::setPtrLen (const oscl_wchar * newPtr, uint32 newLen) [inline]`
- 7.272.3.9 `int32 WStrPtrLen::size () const [inline]`

## 7.272.4 Field Documentation

- 7.272.4.1 `int32 WStrPtrLen::len [protected]`
- 7.272.4.2 `const oscl_wchar* WStrPtrLen::ptr [protected]`

The documentation for this struct was generated from the following file:

- `oscl_str_ptr_len.h`

# Chapter 8

## oscl File Documentation

### 8.1 oscl\_aostatus.h File Reference

Some basic types used with active objects.

```
#include "osclconfig_proc.h"
#include "oscl_base.h"
#include "oscl_aostatus.inl"
```

#### Data Structures

- class [OsclAOStatus](#)

#### Variables

- const int32 [OSCL\\_REQUEST\\_ERR\\_NONE](#) = 0
- const int32 [OSCL\\_REQUEST\\_PENDING](#) = (-0x7fffffff)
- const int32 [OSCL\\_REQUEST\\_ERR\\_CANCEL](#) = (-1)
- const int32 [OSCL\\_REQUEST\\_ERR\\_GENERAL](#) = (-2)

#### 8.1.1 Detailed Description

Some basic types used with active objects.

## 8.2 oscl\_assert.h File Reference

The file [oscl\\_assert.h](#) provides an OSCL\_ASSERT macro to document assumptions and test them during development.

```
#include "oscl_base.h"  
#include "oscl_assert.inl"
```

### Defines

- #define **OSCL\_ASSERT**(\_expr) ((\_expr)?((void)0):OSCL\_Assert(# \_expr,\_\_FILE\_\_,\_\_LINE\_\_))

### Functions

- OSCL\_COND\_IMPORT\_REF void **\_OSCL\_Abort** ()  
*This function terminates the current process abnormally.*
- OSCL\_IMPORT\_REF void **OSCL\_Assert** (const char \*expr, const char \*filename, int line\_number)  
*OSCL\_ASSERT macro evaluates an expression and when the result is false, prints a diagnostic message and aborts the program.*

### 8.2.1 Detailed Description

The file [oscl\\_assert.h](#) provides an OSCL\_ASSERT macro to document assumptions and test them during development.

## 8.3 oscl\_base.h File Reference

The file [oscl\\_base.h](#) is the public header that should be included to pick up the platform configuration, basic type definitions, and common macros.

```
#include "osclconfig.h"
#include "oscl_base_macros.h"
#include "oscl_types.h"
#include "osclconfig_check.h"
#include "pv_config.h"
```

### Defines

- `#define OSCL_HAS_SINGLETON_SUPPORT 1`

### Functions

- `void PVOsclBase_Init ()`
- `void PVOsclBase_Cleanup ()`

#### 8.3.1 Detailed Description

The file [oscl\\_base.h](#) is the public header that should be included to pick up the platform configuration, basic type definitions, and common macros.

## **8.4 oscl\_base\_alloc.h File Reference**

A basic allocator that does not rely on other modules.

```
#include "osclconfig.h"  
#include "oscl_defalloc.h"  
#include "osclconfig_memory.h"
```

### **Data Structures**

- class [\\_OsclBasicAllocator](#)

#### **8.4.1 Detailed Description**

A basic allocator that does not rely on other modules.

## 8.5 oscl\_base\_macros.h File Reference

This file defines common macros and constants for basic compilation support.

```
#include "osclconfig.h"
```

### Defines

- #define **NULL\_TERM\_CHAR** '\0'  
*The NULL\_TERM\_CHAR is used to terminate c-style strings.*
- #define **NULL** (0)  
*if the NULL macro isn't already defined, then define it as zero.*
- #define **OSCL\_INLINE** inline
- #define **OSCL\_COND\_EXPORT\_REF**
- #define **OSCL\_COND\_IMPORT\_REF**
- #define **OSCL\_CONST\_CAST**(type, exp) ((type)(exp))  
*Type casting macros.*
- #define **OSCL\_STATIC\_CAST**(type, exp) ((type)(exp))
- #define **OSCL\_REINTERPRET\_CAST**(type, exp) ((type)(exp))
- #define **OSCL\_DYNAMIC\_CAST**(type, exp) ((type)(exp))
- #define **OSCL\_VIRTUAL\_BASE**(type) type
- #define **OSCL\_UNUSED\_ARG**(vbl) (void)(vbl)
- #define **OSCL\_UNUSED\_RETURN**(value) return value
- #define **OSCL\_MIN**(a, b) ((a) < (b) ? (a) : (b))
- #define **OSCL\_MAX**(a, b) ((a) > (b) ? (a) : (b))
- #define **OSCL\_ABS**(a) ((a) > (0) ? (a) : -(a))
- #define **OSCL\_TEMPLATED\_DESTRUCTOR\_CALL**(type, simple\_type) type :: ~simple\_type ()
- #define **OSCL\_UNSIGNED\_CONST**(x) x
- #define **OSCL\_PACKED\_VAR** "error"

### 8.5.1 Detailed Description

This file defines common macros and constants for basic compilation support.

## 8.6 oscl\_bin\_stream.h File Reference

Defines a set of binary stream classes which handle portable input / output of binary data regardless of the native byte order.

```
#include "oscl_base.h"  
#include "oscl_bin_stream.inl"
```

### Data Structures

- class [OsclBinIStream](#)
- class [OsclBinIStreamBigEndian](#)
- class [OsclBinIStreamLittleEndian](#)
- class [OsclBinOStream](#)

*Class OsclBinOStream implements the basic stream functions for an output stream.*

- class [OsclBinOStreamBigEndian](#)

*Class OsclBinOStreamBigEndian implements a binary output stream using big endian byte ordering.*

- class [OsclBinOStreamLittleEndian](#)

*Class OsclBinOStreamLittleEndian implements a binary output stream using little endian byte ordering.*

- class [OsclBinStream](#)

### 8.6.1 Detailed Description

Defines a set of binary stream classes which handle portable input / output of binary data regardless of the native byte order.

## 8.7 oscl\_byte\_order.h File Reference

This file defines functions providing byte ordering utility (e.g., switching between big and little endian orders).

```
#include "oscl_base.h"  
#include "oscl_byte_order.inl"
```

### Functions

- void [little\\_endian\\_to\\_host](#) (char \*data, uint32 size)  
*Convert little endian to host format.*
- void [host\\_to\\_little\\_endian](#) (char \*data, unsigned int size)  
*Convert host to little endian format.*
- void [big\\_endian\\_to\\_host](#) (char \*data, unsigned int size)  
*Convert big endian to host format.*
- void [host\\_to\\_big\\_endian](#) (char \*data, unsigned int size)  
*Convert host to big endian format.*

### 8.7.1 Detailed Description

This file defines functions providing byte ordering utility (e.g., switching between big and little endian orders).

## 8.8 oscl\_defalloc.h File Reference

The file defines simple default memory allocator classes. These allocators are used by the [Oscl\\_Vector](#) and [Oscl\\_Map](#) class, etc.

```
#include "oscl_base.h"  
#include "osclconfig_compiler_warnings.h"  
#include "oscl_mem_inst.h"
```

### Data Structures

- class [Oscl\\_Alloc](#)
- class [Oscl\\_Dealloc](#)
- class [Oscl\\_DefAlloc](#)
- class [Oscl\\_TAlloc](#)
- class [OsclAllocDestructDealloc](#)
- class [OsclDestructDealloc](#)
- struct [rebind](#)

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)
- #define [ALLOCATE\(n\)](#) [allocate\\_fl\(n,\\_\\_FILE\\_\\_,\\_\\_LINE\\_\\_\)](#)
- #define [ALLOC\\_AND\\_CONSTRUCT\(n\)](#) [alloc\\_and\\_construct\\_fl\(n,\\_\\_FILE\\_\\_,\\_\\_LINE\\_\\_\)](#)

#### 8.8.1 Detailed Description

The file defines simple default memory allocator classes. These allocators are used by the [Oscl\\_Vector](#) and [Oscl\\_Map](#) class, etc.

## 8.9 oscl\_dll.h File Reference

Defines a DLL entry point.

```
#include "osclconfig.h"
```

### Defines

- #define **OSCL\_DLL\_ENTRY\_POINT()** void oscl\_dll\_entry\_point() {}
- #define **OSCL\_DLL\_ENTRY\_POINT\_DEFAULT()**

#### 8.9.1 Detailed Description

Defines a DLL entry point.

## 8.10 oscl\_dns.h File Reference

The file [oscl\\_socket.h](#) defines the OSCL DNS APIs.

```
#include "osclconfig_io.h"
#include "oscl_socket_types.h"
#include "oscl_defalloc.h"
#include "oscl_socket.h"
```

### Data Structures

- class [OsclIDNS](#)
- class [OsclDNSObserver](#)

### Enumerations

- enum [TPVDNSFxn](#) { [EPVDNSGetHostByName](#) }
- enum [TPVDNSEvent](#) { [EPVDNSSuccess](#), [EPVDNSPending](#), [EPVDNSTimeout](#), [EPVDNSFailure](#), [EPVDNSCancel](#) }

#### 8.10.1 Detailed Description

The file [oscl\\_socket.h](#) defines the OSCL DNS APIs.

## 8.11 oscl\_dns\_gethostbyname.h File Reference

```
#include "oscl_dns_method.h"
#include "oscl_dns.h"
#include "osclconfig_io.h"
```

### Data Structures

- class [OsclGetHostByNameMethod](#)
- class [OsclGetHostByNameRequest](#)

## **8.12 oscl\_dns\_imp.h File Reference**

```
#include "oscl_dns_tuneables.h"  
#include "oscl_dns_imp_pv.h"
```

## 8.13 oscl\_dns\_imp\_base.h File Reference

```
#include "oscl_socket_imp.h"
#include "oscl_dns_request.h"
#include "oscl_dns.h"
```

### Data Structures

- class [OsclDNSIBase](#)

## **8.14 oscl\_dns\_imp\_pv.h File Reference**

```
#include "oscl_socket_imp_base.h"
#include "oscl_dns_request.h"
#include "oscl_dns_imp_base.h"
```

### **Data Structures**

- class [OsclDNSI](#)

## 8.15 oscl\_dns\_method.h File Reference

```
#include "osclconfig_io.h"
#include "oscl_socket_types.h"
#include "oscl_scheduler_ao.h"
#include "oscl_dns.h"
#include "pvlogger.h"
```

### Data Structures

- class [OsclIDNSMethod](#)
- class [OsclDNSRequestAO](#)

## 8.16 oscl\_dns\_param.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_dns_tuneables.h"
#include "oscl_namestring.h"
#include "oscl_dns.h"
#include "oscl_mutex.h"
#include "oscl_semaphore.h"
```

### Data Structures

- class [DNSRequestParam](#)
- class [GetHostByNameParam](#)

### Typedefs

- typedef [OsclMemAllocator TDNSRequestParamAllocator](#)

#### 8.16.1 Typedef Documentation

##### 8.16.1.1 typedef [OsclMemAllocator TDNSRequestParamAllocator](#)

## 8.17 oscl\_dns\_request.h File Reference

```
#include "oscl_dns_tuneables.h"
#include "oscl_namestring.h"
#include "oscl_dns.h"
#include "oscl_socket_types.h"
```

### Data Structures

- class [OsclDNSRequest](#)

## 8.18 oscl\_dns\_tuneables.h File Reference

```
#include "osclconfig_io.h"
#include "osclconfig_proc.h"
```

### Defines

- #define **PV\_DNS\_SERVER** 1
- #define **PV\_DNS\_IS\_THREAD** OSCL\_HAS\_THREAD\_SUPPORT

#### 8.18.1 Define Documentation

##### 8.18.1.1 #define PV\_DNS\_IS\_THREAD OSCL\_HAS\_THREAD\_SUPPORT

PV\_DNS\_IS\_THREAD chooses either the threaded or AO-based implementation of the PV DNS request.  
Note: AO-based option is not good here, since some DNS requests will block the caller until completion.

##### 8.18.1.2 #define PV\_DNS\_SERVER 1

Enable/disable the PV DNS server here.

## 8.19 oscl\_double\_list.h File Reference

Internal use types for scheduler.

```
#include "osclconfig_proc.h"
#include "oscl_base.h"
#include "oscl_assert.h"
#include "oscl_double_list.inl"
```

### Data Structures

- class [OsclDoubleLink](#)
- class [OsclDoubleList](#)
- class [OsclDoubleListBase](#)
- class [OsclDoubleRunner](#)
- class [OsclPriorityLink](#)
- class [OsclPriorityList](#)

### Defines

- #define [QUE\\_ITER\\_BEGIN](#)(\_type, \_qname)
- #define [QUE\\_ITER\\_END](#)(\_qname)

### Functions

- template<class T, class S> T \* [OsclPtrAdd](#) (T \*aPtr, S aVal)
- template<class T, class S> T \* [OsclPtrSub](#) (T \*aPtr, S aVal)

#### 8.19.1 Detailed Description

Internal use types for scheduler.

## 8.20 oscl\_errno.h File Reference

Defines functions to access additional information on errors where supported through an errno or similar service.

```
#include "oscl_base.h"
#include "osclconfig_error.h"
#include "oscl_errno.inl"
```

### Functions

- OSCL\_IMPORT\_REF bool [OSCL\\_IsErrnoSupported \(\)](#)  
*This function determines if a particular system saves the error number that occurs on a system call.*
- OSCL\_IMPORT\_REF int [OSCL\\_GetLastError \(\)](#)  
*This function returns the value of the system's global error number variable.*
- OSCL\_IMPORT\_REF bool [OSCL\\_SetLastError \(int newVal\)](#)  
*This function sets the last error code for the system.*
- OSCL\_IMPORT\_REF char \* [OSCL\\_StrError \(int errnum\)](#)  
*This function maps an error number to an error-message string.*

### 8.20.1 Detailed Description

Defines functions to access additional information on errors where supported through an errno or similar service.

## 8.21 oscl\_error.h File Reference

OSCL Error trap and cleanup include file.

```
#include "oscl_heapbase.h"
#include "oscl_defalloc.h"
#include "oscl_error_codes.h"
#include "oscl_singleton.h"
#include "oscl_assert.h"
#include "oscl_tls.h"
```

### Data Structures

- class [OsclError](#)
- class [OsclErrorTrap](#)
- class [OsclTLSEx](#)
- class [OsclTLSRegistryEx](#)

### Defines

- #define [OSCL\\_TRAPSTACK\\_PUSH\(a\)](#) OsclError::PushL(a)
- #define [OSCL\\_TRAPSTACK\\_POP\(\)](#) OsclError::Pop()
- #define [OSCL\\_TRAPSTACK\\_POPDEALLOC\(\)](#) OsclError::PopDealloc()

### 8.21.1 Detailed Description

OSCL Error trap and cleanup include file.

## 8.22 oscl\_error\_allocator.h File Reference

Defines a memory allocation class used by the oscl error layer.

```
#include "oscl_base.h"  
#include "oscl_base_macros.h"  
#include "osclconfig_error.h"  
#include "oscl_assert.h"  
#include "oscl_defalloc.h"
```

### Data Structures

- class [OsclErrorAllocator](#)

*This class provides static methods to invoke the user defined memory allocation routines.*

#### 8.22.1 Detailed Description

Defines a memory allocation class used by the oscl error layer.

## 8.23 oscl\_error\_codes.h File Reference

Defines basic error and leave codes.

### Defines

- #define `OsclErrNone` 0
- #define `OsclErrGeneral` 100
- #define `OsclErrNoMemory` 101
- #define `OsclErrCancelled` 102
- #define `OsclErrNotSupported` 103
- #define `OsclErrArgument` 104
- #define `OsclErrBadHandle` 105
- #define `OsclErrAlreadyExists` 106
- #define `OsclErrBusy` 107
- #define `OsclErrNotReady` 108
- #define `OsclErrCorrupt` 109
- #define `OsclErrTimeout` 110
- #define `OsclErrOverflow` 111
- #define `OsclErrUnderflow` 112
- #define `OsclErrInvalidState` 113
- #define `OsclErrNoResources` 114
- #define `OsclErrNotInstalled` 115
- #define `OsclErrAlreadyInstalled` 116
- #define `OsclErrSystemCallFailed` 117
- #define `OsclErrNoHandler` 118
- #define `OsclErrThreadContextIncorrect` 119
- #define `OSCL_ERR_NONE` `OsclErrNone`
- #define `OSCL_BAD_ALLOC_EXCEPTION_CODE` `OsclErrNoMemory`
- #define `OsclSuccess` 0
- #define `OsclPending` 1
- #define `OsclFailure` -1

### Typedefs

- typedef int32 `OsclLeaveCode`
- typedef int32 `OsclReturnCode`

### 8.23.1 Detailed Description

Defines basic error and leave codes.

## 8.24 oscl\_error\_imp.h File Reference

Internal error implementation support.

```
#include "osclconfig_error.h"  
#include "oscl_error_imp_jumps.h"
```

### Defines

- #define PVERROR\_IMP\_JUMPS

#### 8.24.1 Detailed Description

Internal error implementation support.

## 8.25 oscl\_error\_imp\_cppexceptions.h File Reference

Implementation File for Leave using C++ exceptions.

```
#include "oscl_error_trapcleanup.h"
```

### Data Structures

- class [internalLeave](#)

### Defines

- #define [PVError\\_DoLeave\(\)](#) [internalLeave](#) \_\_ilv;\_\_ilv.a=0;throw(\_\_ilv)
- #define [\\_PV\\_TRAP](#)(\_\_r, \_\_s)
- #define [\\_PV\\_TRAP\\_NO\\_TLS](#)(\_\_trapimp, \_\_r, \_\_s)

### 8.25.1 Detailed Description

Implementation File for Leave using C++ exceptions.

## 8.26 oscl\_error\_imp\_fatalerror.h File Reference

Implementation File for Leave using system fatal error.

```
#include "oscl_assert.h"
```

### Defines

- #define PVError\_DoLeave() \_OSCL\_Abort()
- #define \_PV\_TRAP(\_\_r, \_\_s)
- #define \_PV\_TRAP\_NO\_TLS(\_\_tr, \_\_r, \_\_s)

#### 8.26.1 Detailed Description

Implementation File for Leave using system fatal error.

#### 8.26.2 Define Documentation

##### 8.26.2.1 #define \_PV\_TRAP(\_\_r, \_\_s)

**Value:**

```
__r=OsclErrNone; \
{__s;}
```

##### 8.26.2.2 #define \_PV\_TRAP\_NO\_TLS(\_\_tr, \_\_r, \_\_s)

**Value:**

```
__r=OsclErrNone; \
{__s;}
```

##### 8.26.2.3 #define PVError\_DoLeave() \_OSCL\_Abort()

## 8.27 oscl\_error\_imp\_jumps.h File Reference

Implementation of using Setjmp / Longjmp.

```
#include "oscl_error_trapcleanup.h"
#include "oscl_assert.h"
#include "osclconfig_error.h"
#include "oscl_defalloc.h"
#include "oscl_error.h"
```

### Data Structures

- class [OsclJump](#)

### Defines

- #define OSCL\_JUMP\_MAX\_JUMP\_MARKS OSCL\_MAX\_TRAP\_LEVELS
- #define internalLeave (-1)
- #define PVError\_DoLeave() OsclJump::StaticJump(internalLeave)
- #define \_PV\_TRAP(\_\_r, \_\_s)
- #define \_PV\_TRAP\_NO\_TLS(\_\_trapimp, \_\_r, \_\_s)

### 8.27.1 Detailed Description

Implementation of using Setjmp / Longjmp.

### 8.27.2 Define Documentation

#### 8.27.2.1 #define \_PV\_TRAP(\_\_r, \_\_s)

**Value:**

```
__r=OsclErrNone; \
{ \
    OsclErrorTrapImp* __trap=OsclErrorTrapImp::Trap(); \
    if(!__trap){__s;}else{ \
        int __tr=setjmp(*(__trap->iJumpData->Top())); \
        if (__tr==0)\ 
            {__s;} \
        else if (__tr==internalLeave)\ 
            {__r=__trap->iLeave;} \
            __trap->UnTrap();} \
}
```

#### 8.27.2.2 #define \_PV\_TRAP\_NO\_TLS(\_\_trapimp, \_\_r, \_\_s)

**Value:**

```
__r=OsclErrNone; \
{ \
    OsclErrorTrapImp* __trap=OsclErrorTrapImp::TrapNoTls(__trapimp); \
    if(!__trap){__s;}else{ \
        int __tr=setjmp(*(__trap->iJumpData->Top())); \
        if (__tr==0)\ 
            {__s;} \
        else if (__tr==internalLeave)\ 
            {__r=__trap->iLeave;} \
        __trap->UnTrap();} \
}
```

#### **8.27.2.3 #define PVError\_DoLeave() OsclJump::StaticJump(internalLeave)**

## 8.28 oscl\_error\_trapcleanup.h File Reference

OSCL Error trap and cleanup implementation include file.

```
#include "osclconfig_error.h"  
#include "oscl_heapbase.h"  
#include "oscl_defalloc.h"  
#include "oscl_assert.h"  
#include "oscl_error.h"  
#include "oscl_base_alloc.h"  
#include "oscl_tls.h"  
#include "oscl_singleton.h"  
#include "oscl_error_imp.h"
```

### Data Structures

- class [OsclErrorTrapImp](#)
- class [OsclTrapStack](#)
- class [OsclTrapStackItem](#)

### Defines

- #define [OSCL\\_MAX\\_TRAP\\_LEVELS](#) 20
- #define [PVERRORTRAP\\_REGISTRY\\_ID](#) [OSCL\\_TLS\\_ID\\_PVERRORTRAP](#)
- #define [PVERRORTRAP\\_REGISTRY](#) OsclTLSRegistry

#### 8.28.1 Detailed Description

OSCL Error trap and cleanup implementation include file.

## 8.29 oscl\_exception.h File Reference

contains all the exception handling macros and classes

```
#include "oscl_error.h"
#include "oscl_error_imp.h"
```

### Data Structures

- class **OsclException**

*oscl\_exception.h contains all the exception handling macros and classes This template class provides the base exception class that all exceptions derive from*

### Defines

- #define **OSCL\_LEAVE(\_leave\_status)** OsclError::Leave(\_leave\_status)  
*Use this macro to cause a Leave. It terminates the execution of the current active function.*
- #define **OSCL\_TRY(\_leave\_status, \_statements)** \_PV\_TRAP(\_leave\_status,\_statements)  
*This macro will be used to set up a try block.*
- #define **OSCL\_TRY\_NO\_TLS(\_trapimp, \_leave\_status, \_statements)** \_PV\_TRAP\_NO\_TLS(\_-  
 $_trapimp, _leave_status, _statements)$   
• #define **OSCL\_FIRST\_CATCH\_ANY(\_leave\_status, \_statements)** if (\_leave\_status!=OsclErrNone){ \_statements; }  
*This section defines the macros to be used in the catch block following the try block Use this macro to call a function that handles all exception types thrown in the preceding try block.*
- #define **OSCL\_FIRST\_CATCH(\_leave\_status, \_catch\_value, \_statements)** if (\_leave\_status!=OsclErrNone && \_leave\_status == \_catch\_value){\_statements;}  
*Use this macro to define a block of code that catches the first exception type thrown in the preceding try block.*
- #define **OSCL\_CATCH(\_leave\_status, \_catch\_value, \_statements)** else if (\_leave\_status!=OsclErrNone && \_leave\_status == \_catch\_value){\_statements;}  
*Use this macro to define a block of code for catching additional exception types.*
- #define **OSCL\_CATCH\_ANY(\_leave\_status, \_statements)** else if (\_leave\_status!=OsclErrNone){ \_-  
 $_statements;$   
*Use this macro to call a function that will catch all remaining exception types.*
- #define **OSCL\_LAST\_CATCH(\_leave\_status)** else if (\_leave\_status!=OsclErrNone){OSCL\_-  
 $LEAVE(_leave_status);$   
*Use this macro if OSCL\_CATCH\_ANY has not been used. It will mark the end of the catch block.*

### 8.29.1 Detailed Description

contains all the exception handling macros and classes

## 8.30 oscl\_exclusive\_ptr.h File Reference

This file defines the [OsclExclusivePtr](#) template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error.

```
#include "oscl_defalloc.h"
```

### Data Structures

- class [OsclExclusiveArrayPtr](#)

*The OsclExclusiveArrayPtr class is a template class that defines an array pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the OsclExclusiveArrayPtr expires, its destructor uses delete to free the memory.*

- class [OsclExclusivePtr](#)

*The OsclExclusivePtr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the OsclExclusivePtr expires, its destructor uses delete to free the memory.*

- class [OsclExclusivePtrA](#)

*The OsclExclusivePtrA class is a template class that defines any pointer like object intended to be assigned an address obtained (directly or or indirectly) through Alloc. When the OsclExclusivePtrA expires, Alloc is used to free the memory.*

### 8.30.1 Detailed Description

This file defines the [OsclExclusivePtr](#) template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error.

## 8.31 oscl\_file\_async\_read.h File Reference

```
#include "oscl_base.h"
#include "osclconfig_io.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
#include "oscl_scheduler_ao.h"
#include "oscl_file_io.h"
#include "oscl_semaphore.h"
```

### Data Structures

- class [OsclAsyncFile](#)
- class [OsclAsyncFileBuffer](#)
- class [OsclBuf](#)
- class [OsclPtr](#)
- class [OsclPtrC](#)

## 8.32 oscl\_file\_cache.h File Reference

The file [oscl\\_file\\_cache.h](#) defines the class [OsclFileCache](#).

```
#include "osclconfig_io.h"  
#include "oscl_base.h"  
#include "oscl_file_io.h"
```

### Data Structures

- class [OsclFileCache](#)
- class [OsclFileCacheBuffer](#)

#### 8.32.1 Detailed Description

The file [oscl\\_file\\_cache.h](#) defines the class [OsclFileCache](#).

## 8.33 oscl\_file\_dir\_utils.h File Reference

The file `oscl_file_dir_utils.h` defines some unix-style directory ops.

```
#include "osclconfig_io.h"
#include "oscl_base.h"
```

### Data Structures

- struct `oscl_fsstat`
- struct `oscl_stat_buf`

### Typedefs

- typedef `oscl_fsstat` `OSCL_FSSTAT`
- typedef `oscl_stat_buf` `OSCL_STAT_BUF`

### Enumerations

- enum `OSCL_FILEMGMT_PERMS` { `OSCL_FILEMGMT_PERMS_READ` = 0x1, `OSCL_FILEMGMT_PERMS_WRITE` = 0x2, `OSCL_FILEMGMT_PERMS_EXECUTE` = 0x4 }
- enum `OSCL_FILEMGMT_MODES` { `OSCL_FILEMGMT_MODE_DIR` = 0x1 }
- enum `OSCL_FILEMGMT_ERR_TYPE` { `OSCL_FILEMGMT_E_OK` = 0, `OSCL_FILEMGMT_E_PATH_TOO_LONG`, `OSCL_FILEMGMT_E_PATH_NOT_FOUND`, `OSCL_FILEMGMT_E_ALREADY_EXISTS`, `OSCL_FILEMGMT_E_NOT_EMPTY`, `OSCL_FILEMGMT_E_PERMISSION_DENIED`, `OSCL_FILEMGMT_E_NO_MATCH`, `OSCL_FILEMGMT_E_UNKNOWN`, `OSCL_FILEMGMT_E_SYS_SPECIFIC`, `OSCL_FILEMGMT_E_NOT_IMPLEMENTED` }

### Functions

- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_getcwd (oscl_wchar *path, uint32 size)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_getcwd (char *path, uint32 size)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_stat (const oscl_wchar *path, OSCL_STAT_BUF *statbuf)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_stat (const char *path, OSCL_STAT_BUF *statbuf)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_mkdir (const oscl_wchar *path)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_mkdir (const char *path)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_rmdir (const oscl_wchar *path)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_rmdir (const char *path)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_chdir (const oscl_wchar *path)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_chdir (const char *path)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_rename (const oscl_wchar *oldpath, const oscl_wchar *newpath)`
- `OSCL_IMPORT_REF OSCL_FILEMGMT_ERR_TYPE oscl_rename (const char *oldpath, const char *newpath)`

- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_statfs (OSCL\_FSSTAT \*stats, const char \*path)
- OSCL\_IMPORT\_REF OSCL\_FILEMGMT\_ERR\_TYPE oscl\_statfs (OSCL\_FSSTAT \*stats, const oscl\_wchar \*path)

### 8.33.1 Detailed Description

The file [oscl\\_file\\_dir\\_utils.h](#) defines some unix-style directory ops.

## 8.34 oscl\_file\_find.h File Reference

The file [oscl\\_file\\_find.h](#) defines the class [Oscl\\_FileFind](#).

```
#include "osclconfig_io.h"  
#include "oscl_base.h"  
#include "oscl_mem.h"  
#include "oscl_vector.h"  
#include "oscl_string_containers.h"  
#include "oscl_file_types.h"
```

### Data Structures

- class [Oscl\\_FileFind](#)

#### 8.34.1 Detailed Description

The file [oscl\\_file\\_find.h](#) defines the class [Oscl\\_FileFind](#).

## 8.35 oscl\_file\_handle.h File Reference

The file [oscl\\_file\\_handle.h](#) defines the class [OsclFileHandle](#).

```
#include "osclconfig_io.h"  
#include "oscl_base.h"
```

### Data Structures

- class [OsclFileHandle](#)

### TypeDefs

- [typedef FILE \\* TOsclFileHandle](#)

#### 8.35.1 Detailed Description

The file [oscl\\_file\\_handle.h](#) defines the class [OsclFileHandle](#).

## 8.36 oscl\_file\_io.h File Reference

The file [oscl\\_file\\_io.h](#) defines the class [Oscl\\_File](#). This is the public API to the basic file I/O operations.

```
#include "osclconfig_io.h"  
#include "oscl_base.h"  
#include "oscl_mem.h"  
#include "oscl_vector.h"  
#include "oscl_file_server.h"  
#include "oscl_file_find.h"  
#include "oscl_file_dir_utils.h"  
#include "oscl_file_handle.h"
```

### Data Structures

- class [Oscl\\_File](#)
- class [OsclFixedCacheParam](#)
- class [OsclCacheObserver](#)

### Defines

- #define [TOsclFileOffsetInt32](#) int32

#### 8.36.1 Detailed Description

The file [oscl\\_file\\_io.h](#) defines the class [Oscl\\_File](#). This is the public API to the basic file I/O operations.

## 8.37 oscl\_file\_manager.h File Reference

File management class.

```
#include "oscl_base.h"
```

### Data Structures

- class [OsclFileManager](#)

#### 8.37.1 Detailed Description

File management class.

## 8.38 oscl\_file\_native.h File Reference

The file [oscl\\_file\\_native.h](#) defines the class [OsclNativeFile](#). This is the porting layer for basic file I/O operations.

```
#include "osclconfig_io.h"
#include "oscl_base.h"
#include "oscl_aostatus.h"
#include "oscl_file_io.h"
```

### Data Structures

- class [OsclNativeFile](#)

#### 8.38.1 Detailed Description

The file [oscl\\_file\\_native.h](#) defines the class [OsclNativeFile](#). This is the porting layer for basic file I/O operations.

## 8.39 oscl\_file\_server.h File Reference

The file [oscl\\_file\\_server.h](#) defines the class [Oscl\\_FileServer](#). This is the porting layer for file server implementations.

```
#include "osclconfig_io.h"  
#include "oscl_base.h"
```

### Data Structures

- class [Oscl\\_FileServer](#)

#### 8.39.1 Detailed Description

The file [oscl\\_file\\_server.h](#) defines the class [Oscl\\_FileServer](#). This is the porting layer for file server implementations.

## 8.40 oscl\_file\_stats.h File Reference

File stats class.

```
#include "oscl_base.h"
#include "osclconfig_io.h"
```

### Data Structures

- class [OsclFileStats](#)
- class [OsclFileStatsItem](#)

### Defines

- #define [OSCL\\_FILE\\_STATS\\_LOGGER\\_NODE](#) "OsclFileStats"

### Enumerations

- enum [TOsclFileOp](#) { [EOsclFileOp\\_Open](#), [EOsclFileOp\\_Close](#), [EOsclFileOp\\_Read](#), [EOsclFileOp\\_Write](#), [EOsclFileOp\\_Seek](#), [EOsclFileOp\\_Tell](#), [EOsclFileOp\\_Size](#), [EOsclFileOp\\_Flush](#), [EOsclFileOp\\_EndOfFile](#), [EOsclFileOp\\_SetSize](#), [EOsclFileOp\\_NativeOpen](#), [EOsclFileOp\\_NativeClose](#), [EOsclFileOp\\_NativeRead](#), [EOsclFileOp\\_NativeWrite](#), [EOsclFileOp\\_NativeSeek](#), [EOsclFileOp\\_NativeTell](#), [EOsclFileOp\\_NativeSize](#), [EOsclFileOp\\_NativeFlush](#), [EOsclFileOp\\_NativeEndOfFile](#), [EOsclFileOp\\_NativeSetSize](#), [EOsclFileOp\\_Last](#) }

### 8.40.1 Detailed Description

File stats class.

## 8.41 oscl\_file\_types.h File Reference

The file [oscl\\_file\\_types.h](#) defines some constants and types for file I/O implementations. Anything that needs to be shared across implementation modules can go here.

### Data Structures

- class [OsclNativeFileParams](#)

### Defines

- #define [OSCL\\_IO\\_FILENAME\\_MAXLEN](#) 512
- #define [OSCL\\_IO\\_EXTENSION\\_MAXLEN](#) 512
- #define [OSCL\\_FILE\\_WCHAR\\_PATH\\_DELIMITER](#) \_STRLIT("/")
- #define [OSCL\\_FILE\\_CHAR\\_PATH\\_DELIMITER](#) \_STRLIT\_CHAR("/")

### 8.41.1 Detailed Description

The file [oscl\\_file\\_types.h](#) defines some constants and types for file I/O implementations. Anything that needs to be shared across implementation modules can go here.

## 8.42 oscl\_heapbase.h File Reference

OSCL Heap Base include file.

```
#include "osclconfig_error.h"
#include "oscl_base.h"
#include "oscl_heapbase.inl"
```

### Data Structures

- class [\\_OsclHeapBase](#)
- class [OsclTrapItem](#)

### TypeDefs

- [typedef void\(\\* OsclTrapOperation \)\(OsclAny \\*\)](#)

#### 8.42.1 Detailed Description

OSCL Heap Base include file.

## 8.43 oscl\_init.h File Reference

Global oscl initialization.

```
#include "oscl_base.h"  
#include <stdio.h>
```

### Data Structures

- class [OsclInit](#)
- class [OsclSelect](#)

#### 8.43.1 Detailed Description

Global oscl initialization.

## 8.44 oscl\_int64\_utils.h File Reference

```
#include "oscl_base.h"
```

### Data Structures

- class [Oscl\\_Int64\\_Utils](#)  
*The Oscl\_Int64\_Utils class provides a wrapper for commonly used int64/uint64 operations.*
- struct [OsclInteger64Transport](#)

### Typedefs

- typedef [OsclInteger64Transport \\_OsclInteger64Transport](#)

#### 8.44.1 Typedef Documentation

##### 8.44.1.1 typedef struct [OsclInteger64Transport \\_OsclInteger64Transport](#)

###### [OsclInteger64Transport](#) Structure

Structure to only transport 64-bit integer values uint64 and int64 could be classes so needed for cases where having a class will not work.

## 8.45 oscl\_ip\_socket.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
```

### Data Structures

- class [OsclIPSocketI](#)

## 8.46 oscl\_linked\_list.h File Reference

The file [oscl\\_linked\\_list.h](#) defines the template class [Oscl\\_Linked\\_List](#) which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.

```
#include "oscl_base.h"
#include "oscl_defalloc.h"
#include "oscl_opaque_type.h"
#include "oscl_assert.h"
```

### Data Structures

- class [LinkedListElement](#)
- class [Oscl\\_Linked\\_List](#)
- class [Oscl\\_Linked\\_List\\_Base](#)
- class [Oscl\\_MTLinked\\_List](#)

#### 8.46.1 Detailed Description

The file [oscl\\_linked\\_list.h](#) defines the template class [Oscl\\_Linked\\_List](#) which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.

## 8.47 oscl\_lock\_base.h File Reference

This file defines an abstract lock class, [OsclLockBase](#), that is used for APIs potentially requiring multi-thread safety. A null-lock implementation, [OsclNullLock](#), is also provided for single-thread configurations (basically a noop for lock/unlock). Also provides the [OsclScopedLock](#) class which is template class takes care of freeing the lock when the class goes out of scope.

### Data Structures

- class [OsclLockBase](#)
- class [OsclNullLock](#)
- class [OsclScopedLock](#)

*The OsclScopedLock class is a template class that handles unlocking an abstract class on destruction. This is very useful for ensuring that the lock is released when the OsclScopedLock goes out of scope.*

### 8.47.1 Detailed Description

This file defines an abstract lock class, [OsclLockBase](#), that is used for APIs potentially requiring multi-thread safety. A null-lock implementation, [OsclNullLock](#), is also provided for single-thread configurations (basically a noop for lock/unlock). Also provides the [OsclScopedLock](#) class which is template class takes care of freeing the lock when the class goes out of scope.

## 8.48 oscl\_map.h File Reference

The file `oscl_map.h` defines the template class `Oscl_Map` which has a very similar API as the STL Map class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.

```
#include "oscl_base.h"
#include "oscl_tree.h"
#include "osclconfig_compiler_warnings.h"
```

### Data Structures

- struct `Oscl_Less`
- class `Oscl_Map`
- struct `Oscl_Select1st`
- class `value_compare`

### Defines

- `#define OSCL_DISABLE_WARNING_TRUNCATE_DEBUG_MESSAGE`

#### 8.48.1 Detailed Description

The file `oscl_map.h` defines the template class `Oscl_Map` which has a very similar API as the STL Map class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.

#### 8.48.2 Define Documentation

##### 8.48.2.1 `#define OSCL_DISABLE_WARNING_TRUNCATE_DEBUG_MESSAGE`

## 8.49 oscl\_math.h File Reference

Provides math functions.

```
#include "osclconfig_util.h"
#include "oscl_base.h"
#include "oscl_math.inl"
```

### Functions

- OSCL\_COND\_IMPORT\_REF double `oscl_log` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_log10` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_sqrt` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_pow` (double x, double y)
- OSCL\_COND\_IMPORT\_REF double `oscl_exp` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_sin` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_cos` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_tan` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_asin` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_atan` (double value)
- OSCL\_COND\_IMPORT\_REF double `oscl_floor` (double value)

### 8.49.1 Detailed Description

Provides math functions.

## 8.50 oscl\_media\_data.h File Reference

Defines a container class for media data made up of a collection of memory fragments.

```
#include "oscl_base.h"  
#include "oscl_mem_basic_functions.h"  
#include "oscl_media_status.h"
```

### Data Structures

- class [BufferFragment](#)
- class [BufferMgr](#)
- class [BufferState](#)
- class [BuffFragGroup](#)
- class [MediaData](#)
- class [MemAllocator](#)

### Typedefs

- typedef void(\* [BufferFreeFuncPtr](#) )(void \*)
- typedef uint32 [MediaTimestamp](#)

#### 8.50.1 Detailed Description

Defines a container class for media data made up of a collection of memory fragments.

## 8.51 oscl\_media\_status.h File Reference

Defines a status values for the [MediaData](#) containers.

### Data Structures

- class [BufFragStatusClass](#)
- class [MediaStatusClass](#)

### Variables

- const int32 [APPEND\\_MEDIA\\_AT\\_END](#) = -1

#### 8.51.1 Detailed Description

Defines a status values for the [MediaData](#) containers.

## 8.52 oscl\_mem.h File Reference

This file contains basic memory definitions for common use across platforms.

```
#include "osclconfig_memory.h"  
#include "oscl_base.h"  
#include "oscl_types.h"  
#include "oscl_assert.h"  
#include "oscl_mem_basic_functions.h"  
#include "oscl_lock_base.h"  
#include "osclconfig_compiler_warnings.h"  
#include "oscl_mem_inst.h"  
#include "oscl_heapbase.h"  
#include "oscl_defalloc.h"  
#include "oscl_refcounter.h"  
#include "oscl_error.h"  
#include "oscl_exception.h"  
#include "oscl_mem.inl"
```

### Data Structures

- class [HeapBase](#)
- class [OsclAuditCB](#)
- class [OsclMem](#)
- class [OsclMemAllocator](#)
- class [OsclMemAllocDestructDealloc](#)
- class [OsclMemBasicAllocator](#)
- class [OsclMemBasicAllocDestructDealloc](#)
- class [OsclMemGlobalAuditObject](#)

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)
- #define [OSCL\\_HAS\\_GLOBAL\\_NEW\\_DELETE](#) 1
- #define [OSCL\\_CLEANUP\\_BASE\\_CLASS\(T\)](#) \_OSCL\_CLEANUP\_BASE\_CLASS(T)
- #define [OSCL\\_ALLOC\\_NEW\(T\\_allocator, T, params\)](#) new(T\_allocator.allocate(1)) T params
- #define [OSCL\\_TRAP\\_ALLOC\\_NEW\(T\\_ptr, T\\_allocator, T, params\)](#) \_OSCL\_TRAP\_NEW(T\_allocator.allocate(1),T\_allocator.deallocate,T\_ptr,T,params)
- #define [OSCL\\_ALLOC\\_DELETE\(ptr, T\\_allocator, T\)](#)
- #define [OSCL\\_MALLOC\(count\)](#) \_oscl\_default\_audit\_malloc(count)
- #define [oscl\\_malloc\(a\)](#) OSCL\_MALLOC(a)
- #define [OSCL\\_DEFAULT\\_MALLOC\(x\)](#) OSCL\_MALLOC(x)
- #define [OSCL\\_AUDIT\\_MALLOC\(auditCB, count\)](#) \_oscl\_audit\_malloc(count, auditCB)
- #define [OSCL\\_CALLOC\(num, size\)](#) \_oscl\_default\_audit\_calloc(num,size)
- #define [oscl\\_calloc\(a, b\)](#) OSCL\_CALLOC(a,b)

- #define **OSCL\_AUDIT\_CALLOC**(auditCB, num, size) \_oscl\_audit\_calloc(num,size, auditCB)
- #define **OSCL\_REALLOC**(ptr, new\_size) \_oscl\_default\_audit\_realloc(ptr,new\_size)
- #define **oscl\_realloc**(a, b) OSCL\_REALLOC(a,b)
- #define **OSCL\_AUDIT\_REALLOC**(auditCB, ptr, new\_size) \_oscl\_audit\_realloc(ptr,new\_size, auditCB)
- #define **OSCL\_FREE**(ptr) \_oscl\_audit\_free(ptr)
- #define **oscl\_free**(x) OSCL\_FREE(x)
- #define **OSCL\_DEFAULT\_FREE**(x) OSCL\_FREE(x)
- #define **OSCL\_NEW**(T, params) new T params
- #define **OSCL\_PLACEMENT\_NEW**(ptr, constructor) new(ptr) constructor
- #define **OSCL\_TRAP\_NEW**(T\_ptr, T, params) \_OSCL\_TRAP\_NEW(\_oscl\_default\_audit\_new(sizeof(T)),\_oscl\_audit\_free,T\_ptr,T,params)
- #define **OSCL\_AUDIT\_NEW**(auditCB, T, params) new(\_oscl\_audit\_new(sizeof(T),auditCB)) T params
- #define **OSCL\_TRAP\_AUDIT\_NEW**(T\_ptr, auditCB, T, params) \_OSCL\_TRAP\_NEW(\_oscl\_audit\_new(sizeof(T),auditCB),\_oscl\_audit\_free,T\_ptr,T,params)
- #define **OSCL\_DELETE**(ptr)
- #define **OSCL\_AUDIT\_ARRAY\_NEW**(auditCB, T, count) new(\_oscl\_audit\_new(sizeof(T)\*(count),auditCB)) T
- #define **OSCL\_ARRAY\_NEW**(T, count) new T[count]
- #define **OSCL\_ARRAY\_DELETE**(ptr) delete [ ] ptr
- #define **OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE**
- #define **\_OSCL\_TRAP\_NEW**(exp, freeFunc, T\_ptr, T, params)
- #define **\_OSCL\_CLEANUP\_BASE\_CLASS**(T) this → T::~T()

## Functions

- **OSCL\_COND\_IMPORT\_REF** **uint** **oscl\_mem\_aligned\_size** (**uint** **size**)
- **OSCL\_IMPORT\_REF** **void** **OsclMemInit** (**OsclAuditCB** &auditCB)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_audit\_malloc** (**size\_t**, **OsclAuditCB** &, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_audit\_calloc** (**size\_t**, **size\_t**, **OsclAuditCB** &, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_audit\_realloc** (**void** \*, **size\_t**, **OsclAuditCB** &, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_audit\_new** (**size\_t**, **OsclAuditCB** &, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_default\_audit\_malloc** (**size\_t**, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_default\_audit\_calloc** (**size\_t**, **size\_t**, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_default\_audit\_realloc** (**void** \*, **size\_t**, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void \*** **\_oscl\_default\_audit\_new** (**size\_t**, **const char** \*f=NULL, **const int** l=0)
- **OSCL\_IMPORT\_REF** **void** **\_oscl\_audit\_free** (**void** \*)
- **void \*** **operator new** (**size\_t** aSize, **const char** \*aFile, **int** aLine)
- **void \*** **operator new** (**size\_t** aSize)
- **void operator delete** (**void** \*aPtr)
- **void \*** **operator new[]** (**size\_t** aSize, **const char** \*aFile, **int** aLine)
- **void \*** **operator new[]** (**size\_t** aSize)
- **void operator delete[]** (**void** \*aPtr)

### 8.52.1 Detailed Description

This file contains basic memory definitions for common use across platforms.

This is the main entry point header file for the OSCL memory library. It should be the only one users directly include. Basic memory copy, compare, and move functions are defined here as well as the allocation functions.

### 8.52.2 Define Documentation

#### 8.52.2.1 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE

Previously this was in oscl\_mem\_imp.h

### 8.52.3 Function Documentation

#### 8.52.3.1 void operator delete (void \* *aPtr*) [inline]

#### 8.52.3.2 void\* operator new (size\_t *aSize*) [inline]

---

**8.53 oscl\_mem\_align.h File Reference**

## 8.54 oscl\_mem\_audit.h File Reference

This file contains the definition and partial implementation of MM\_Audit class.

```
#include "oscl_lock_base.h"
#include "oscl_base_alloc.h"
#include "oscl_tagtree.h"
#include "oscl_mem.h"
#include "oscl_mem_auto_ptr.h"
#include "osclconfig_compiler_warnings.h"
```

### Data Structures

- struct [MM\\_AllocInfo](#)
- struct [MM\\_AllocNode](#)
- struct [MM\\_AllocQueryInfo](#)
- class [MM\\_Audit\\_Imp](#)
- struct [MM\\_AuditOverheadStats](#)
- struct [MM\\_FailInsertParam](#)
- struct [MM\\_Stats\\_CB](#)
- struct [MM\\_Stats\\_t](#)
- class [OsclMemAudit](#)
- class [OsclMemStatsNode](#)

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)
- #define [MM\\_ALLOC\\_MAX\\_QUERY\\_FILENAME\\_LEN](#) 128
- #define [MM\\_ALLOC\\_MAX\\_QUERY\\_TAG\\_LEN](#) 64
- #define [MM\\_AUDIT\\_VALIDATE\\_BLOCK](#) 1
- #define [MM\\_AUDIT\\_PREFILL\\_FLAG](#) 0x1
- #define [MM\\_AUDIT\\_POSTFILL\\_FLAG](#) 0x2
- #define [MM\\_AUDIT\\_VALIDATE\\_ALL\\_HEAP\\_FLAG](#) 0x4
- #define [MM\\_AUDIT\\_VALIDATE\\_ON\\_FREE\\_FLAG](#) 0x8
- #define [MM\\_AUDIT\\_ALLOC\\_NODE\\_ENABLE\\_FLAG](#) 0x10
- #define [MM\\_AUDIT\\_SUPPRESS\\_FILENAME\\_FLAG](#) 0x20
- #define [DEFAULT\\_MM\\_AUDIT\\_MODE](#) 0

### Typedefs

- typedef [OSCLMemAutoPtr< char, Oscl\\_TAlloc< char, OsclMemBasicAllocator > >](#) [MMAudit\\_CharAutoPtr](#)
- typedef [OSCLMemAutoPtr< uint8, Oscl\\_TAlloc< uint8, \\_OscIBasicAllocator > >](#) [MMAudit\\_Uint8AutoPtr](#)
- typedef [OSCLMemAutoPtr< MM\\_AllocNode, Oscl\\_TAlloc< MM\\_AllocNode, OsclMemBasicAllocator > >](#) [MM\\_AllocNodeAutoPtr](#)
- typedef [OSCLMemAutoPtr< OsclMemStatsNode, Oscl\\_TAlloc< OsclMemStatsNode, OsclMemBasicAllocator > >](#) [MM\\_StatsNodeTagTreeType](#)

- `typedef OSCLMemAutoPtr< OsclMemStatsNode, Oscl_TAlloc< OsclMemStatsNode, OsclMemBasicAllocator > > OsclMemStatsNodeAutoPtr`
- `typedef Oscl_TAlloc< MM_StatsNodeTagTreeType, OsclMemBasicAllocator > TagTree_Allocator`
- `typedef Oscl_TagTree< MM_StatsNodeTagTreeType, TagTree_Allocator > OsclTagTreeType`

### **8.54.1 Detailed Description**

This file contains the definition and partial implementation of MM\_Audit class.

### **8.54.2 Define Documentation**

#### **8.54.2.1 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE**

## 8.55 oscl\_mem\_audit\_internals.h File Reference

This file contains the internal definitions for the mem audit library.

```
#include "oscl_base.h"
#include "oscl_mem_audit.h"
#include "oscl_mem_inst.h"
#include "osclconfig_compiler_warnings.h"
```

### Data Structures

- struct [MM\\_AllocBlockFence](#)
- struct [MM\\_AllocBlockHdr](#)

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)
- #define [MM\\_AUDIT\\_ALLOC\\_NODE\\_SUPPORT](#) 1
- #define [MM\\_AUDIT\\_FENCE\\_SUPPORT](#) 0
- #define [MM\\_AUDIT\\_INCLUDE\\_ALL\\_HEAP\\_VALIDATION](#) 1
- #define [MM\\_AUDIT\\_FILL\\_SUPPORT](#) 0
- #define [MM\\_AUDIT\\_FAILURE\\_SIMULATION\\_SUPPORT](#) 1
- #define [FENCE\\_PATTERN](#) 0xAA
- #define [MIN\\_FENCE\\_SIZE](#) 4
- #define [MEM\\_ALIGN\\_SIZE](#) 8
- #define [COMPUTE\\_MEM\\_ALIGN\\_SIZE](#)(x, y, z) (y+(((x+y)%z) ? (z - (x+y)%z) : 0))
- #define [DEFAULT\\_PREFILL\\_PATTERN](#) 0x96
- #define [DEFAULT\\_POSTFILL\\_PATTERN](#) 0x5A

### 8.55.1 Detailed Description

This file contains the internal definitions for the mem audit library.

### 8.55.2 Define Documentation

#### 8.55.2.1 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE

## 8.56 oscl\_mem\_auto\_ptr.h File Reference

This file defines the oscl\_mem\_auto\_ptr template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error.

```
#include "osclconfig_memory.h"  
#include "osclconfig_compiler_warnings.h"  
#include "oscl_mem.h"
```

### Data Structures

- class [OSCLMemAutoPtr](#)

*The oscl\_auto\_ptr class is a template class that defines a pointer like object intended to be assigned an address obtained (directly or or indirectly) by new. When the oscl\_auto\_ptr expires, its destructor uses delete to free the memory.*

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)
- #define [OSCL\\_DISABLE\\_WARNING\\_RETURN\\_TYPE\\_NOT\\_UDT](#)

#### 8.56.1 Detailed Description

This file defines the oscl\_mem\_auto\_ptr template class. This class is used to avoid any potential memory leaks that may arise while returning from methods in case of error.

#### 8.56.2 Define Documentation

##### 8.56.2.1 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE

## 8.57 oscl\_mem\_basic\_functions.h File Reference

This file contains prototypes for the basic memory functions.

```
#include "oscl_base_macros.h"  
#include "oscl_mem_basic_functions.inl"
```

### Functions

- OSCL\_COND\_IMPORT\_REF void \* [\\_oscl\\_malloc](#) (int32 count)
- OSCL\_COND\_IMPORT\_REF void \* [\\_oscl\\_calloc](#) (int32 nelems, int32 size)
- OSCL\_COND\_IMPORT\_REF void \* [\\_oscl\\_realloc](#) (void \*src, int32 count)
- OSCL\_COND\_IMPORT\_REF void [\\_oscl\\_free](#) (void \*src)
- OSCL\_COND\_IMPORT\_REF void \* [oscl\\_memcpy](#) (void \*dest, const void \*src, uint32 count)
- OSCL\_COND\_IMPORT\_REF void \* [oscl\\_memmove](#) (void \*dest, const void \*src, uint32 count)
- OSCL\_COND\_IMPORT\_REF void \* [oscl\\_memmove32](#) (void \*dest, const void \*src, uint32 count)
- OSCL\_COND\_IMPORT\_REF void \* [oscl\\_memset](#) (void \*dest, uint8 val, uint32 count)
- OSCL\_COND\_IMPORT\_REF int [oscl\\_memcmp](#) (const void \*buf1, const void \*buf2, uint32 count)

### 8.57.1 Detailed Description

This file contains prototypes for the basic memory functions.

## **8.58 oscl\_mem\_inst.h File Reference**

The file defines default memory instrumentation level.

```
#include "osclconfig_memory.h"
```

### **Defines**

- #define **PVMEM\_INST\_LEVEL** 1

#### **8.58.1 Detailed Description**

The file defines default memory instrumentation level.

## 8.59 oscl\_mem\_mempool.h File Reference

This file contains the definition of memory pool allocators.

```
#include "oscl_mem.h"  
#include "oscl_defalloc.h"  
#include "oscl_vector.h"
```

### Data Structures

- struct [MemPoolBlockInfo](#)
- struct [MemPoolBufferInfo](#)
- class [OsclMemPoolFixedChunkAllocator](#)
- class [OsclMemPoolFixedChunkAllocatorObserver](#)
- class [OsclMemPoolResizableAllocator](#)
- class [OsclMemPoolResizableAllocatorMemoryObserver](#)
- class [OsclMemPoolResizableAllocatorObserver](#)

#### 8.59.1 Detailed Description

This file contains the definition of memory pool allocators.

## 8.60 oscl\_mutex.h File Reference

This file provides implementation of mutex.

```
#include "osclconfig_proc.h"  
#include "oscl_types.h"  
#include "oscl_base.h"  
#include "oscl_thread.h"  
#include "oscl_lock_base.h"
```

### Data Structures

- class [OsclMutex](#)
- class [OsclThreadLock](#)

### Typedefs

- typedef [OsclMutex OsclNoYieldMutex](#)

#### 8.60.1 Detailed Description

This file provides implementation of mutex.

#### 8.60.2 Typedef Documentation

##### 8.60.2.1 typedef [OsclMutex OsclNoYieldMutex](#)

Class [OsclNoYieldMutex](#) can be used in use cases where there will be no CPU-yielding operation done while the Mutex is locked.

CPU-yielding operations include [OsclMutex::Lock](#), [OsclSemaphore::Wait](#), [OsclThread::Sleep](#), and [OsclBrewThreadUtil::BThreadYield](#).

The behavior of [OsclNoYieldMutex](#) depends on whether the threading model is pre-emptive or not. When threading is pre-emptive, it is identical to [OsclMutex](#). When threading is non-pre-emptive, it is a NO-OP.

An example of this type of use case is for simple data protection.

## 8.61 oscl\_namestring.h File Reference

Name string class include file.

```
#include "oscl_base.h"
```

### Data Structures

- class [OsclNameString](#)

#### 8.61.1 Detailed Description

Name string class include file.

## **8.62 oscl\_opaque\_type.h File Reference**

The file [oscl\\_opaque\\_type.h](#) defines pure virtual classes for working with opaque types.

```
#include "oscl_base.h"
```

### **Data Structures**

- class [Oscl\\_Opaque\\_Type\\_Alloc](#)
- class [Oscl\\_Opaque\\_Type\\_Alloc\\_LL](#)
- class [Oscl\\_Opaque\\_Type\\_Compare](#)

#### **8.62.1 Detailed Description**

The file [oscl\\_opaque\\_type.h](#) defines pure virtual classes for working with opaque types.

## 8.63 oscl\_priqueue.h File Reference

Implements a priority queue data structure similar to STL.

```
#include "oscl_base.h"  
#include "oscl_vector.h"
```

### Data Structures

- class [OsclCompareLess](#)
- class [OsclPriorityQueue](#)
- class [OsclPriorityQueueBase](#)

#### 8.63.1 Detailed Description

Implements a priority queue data structure similar to STL.

Implements a priority queue data structure similar to the STL class. The properties of the class include O(Log\_2(N)) insertion and deletion complexity and O(1) complexity to access the top priority item.

## **8.64 oscl\_procstatus.h File Reference**

### **Data Structures**

- class [OsclProcStatus](#)

## 8.65 oscl\_queue.h File Reference

The file [oscl\\_queue.h](#) defines the template class [Oscl\\_Queue](#). It is similar to the STL::queue class, with some differences: - less complete - based on array rather than a deque - some interfaces modeled on oscl\_vector, for ease of transition Memory allocation is abstracted through the use of an allocator template parameter.

```
#include "oscl_base.h"  
#include "oscl_mem_basic_functions.h"  
#include "oscl_assert.h"  
#include "oscl_opaque_type.h"
```

### Data Structures

- class [Oscl\\_Queue](#)
- class [Oscl\\_Queue\\_Base](#)

#### 8.65.1 Detailed Description

The file [oscl\\_queue.h](#) defines the template class [Oscl\\_Queue](#). It is similar to the STL::queue class, with some differences: - less complete - based on array rather than a deque - some interfaces modeled on oscl\_vector, for ease of transition Memory allocation is abstracted through the use of an allocator template parameter.

## 8.66 oscl\_rand.h File Reference

Provides pseudo-random number generation.

```
#include "osclconfig_util.h"  
#include "oscl_base.h"  
#include "oscl_mem_basic_functions.h"  
#include "oscl_rand.inl"
```

### Data Structures

- class [OsclRand](#)

#### 8.66.1 Detailed Description

Provides pseudo-random number generation.

## 8.67 oscl\_refcounter.h File Reference

A general purpose reference counter to object lifetimes.

```
#include "oscl_assert.h"  
#include "oscl_defalloc.h"
```

### Data Structures

- class [Oscl\\_DefAllocWithRefCounter](#)
- class [OsclRefCounter](#)
- class [OsclRefCounterDA](#)
- class [OsclRefCounterMTDA](#)
- class [OsclRefCounterMTSA](#)
- class [OsclRefCounterSA](#)

#### 8.67.1 Detailed Description

A general purpose reference counter to object lifetimes.

## **8.68 oscl\_refcounter\_memfrag.h File Reference**

This file provides the definition of reference counted memory fragment, which provides access to a buffer and helps manage its lifetime through the refcount.

```
#include "oscl_base.h"  
#include "oscl_refcounter.h"
```

### **Data Structures**

- class [OsclRefCounterMemFrag](#)

#### **8.68.1 Detailed Description**

This file provides the definition of reference counted memory fragment, which provides access to a buffer and helps manage its lifetime through the refcount.

## 8.69 oscl\_registry\_access\_client.h File Reference

Client-side implementation Registry Access implementation.

```
#include "oscl_registry_types.h"
#include "oscl_string_containers.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
```

### Data Structures

- class [OsclRegistryAccessClient](#)

#### 8.69.1 Detailed Description

Client-side implementation Registry Access implementation.

## 8.70 oscl\_registry\_client.h File Reference

Client-side implementation of OsclRegistry.

```
#include "oscl_registry_types.h"
#include "oscl_mem.h"
#include "oscl_string.h"
```

### Data Structures

- class [OsclRegistryClient](#)

#### 8.70.1 Detailed Description

Client-side implementation of OsclRegistry.

## 8.71 oscl\_registry\_client\_impl.h File Reference

Client-side implementation of OsclRegistryInterface.

```
#include "oscl_base.h"
#include "osclconfig_proc.h"
#include "oscl_vector.h"
#include "oscl_string.h"
#include "oscl_registry_types.h"
#include "oscl_registry_serv_impl_tls.h"
```

### Data Structures

- class [OsclRegistryAccessClientImpl](#)
- class [OsclRegistryAccessClientTlsImpl](#)
- class [OsclRegistryClientImpl](#)
- class [OsclRegistryClientTlsImpl](#)

#### 8.71.1 Detailed Description

Client-side implementation of OsclRegistryInterface.

## 8.72 oscl\_registry\_serv\_impl.h File Reference

Server-side implementation of OsclRegistry interfaces.

```
#include "oscl_base.h"
#include "osclconfig_proc.h"
#include "oscl_registry_types.h"
#include "oscl_string.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
#include "oscl_mutex.h"
```

### Data Structures

- class [OsclComponentRegistry](#)
- class [OsclComponentRegistryData](#)
- class [OsclComponentRegistryElement](#)

#### 8.72.1 Detailed Description

Server-side implementation of OsclRegistry interfaces.

## 8.73 oscl\_registry\_serv\_impl\_global.h File Reference

```
#include "osclconfig_proc.h"
#include "oscl_base.h"
```

## 8.74 oscl\_registry\_serv\_impl\_tls.h File Reference

```
#include "osclconfig_proc.h"
#include "oscl_registry_serv_impl.h"
#include "oscl_registry_types.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
```

### Data Structures

- class [OsclRegistryServTlsImpl](#)

## 8.75 oscl\_registry\_types.h File Reference

Common types used in Oscl registry interfaces.

```
#include "oscl_types.h"  
#include "oscl_string_containers.h"
```

### Data Structures

- class [OsclRegistryAccessElement](#)

### TypeDefs

- typedef [OsclAny](#) \* [OsclComponentFactory](#)

#### 8.75.1 Detailed Description

Common types used in Oscl registry interfaces.

## 8.76 oscl\_scheduler.h File Reference

```
#include "oscl_scheduler_types.h"
#include "oscl_scheduler_ao.h"
#include "oscl_scheduler_threadcontext.h"
#include "oscl_defalloc.h"
#include "oscl_mem.h"
```

### Data Structures

- class [OsclExecScheduler](#)
- class [OsclExecSchedulerCommonBase](#)
- class [OsclScheduler](#)
- class [OsclSchedulerObserver](#)
- class [PVSchedulerStopper](#)

### Defines

- #define [PVSCHEDNAMELEN](#) 30

## 8.77 oscl\_scheduler\_ao.h File Reference

Oscl Scheduler user execution object classes.

```
#include "oscl_scheduler_aobase.h"
#include "oscl_mem.h"
#include "oscl_scheduler_types.h"
```

### Data Structures

- class [OsclActiveObject](#)
- class [OsclTimerObject](#)

#### 8.77.1 Detailed Description

Oscl Scheduler user execution object classes.

## 8.78 oscl\_scheduler\_aobase.h File Reference

Oscl Scheduler internal active object classes.

```
#include "oscl_namestring.h"
#include "oscl_scheduler_threadcontext.h"
#include "oscl_scheduler_readyq.h"
#include "oscl_string_containers.h"
#include "oscl_scheduler_types.h"
```

### Data Structures

- class [PVActiveBase](#)
- class [PVActiveStats](#)

### Defines

- #define [OSCL\\_ZEROIZE](#)(ptr, size) oscl\_memset(ptr, 0, size)
- #define [PVEEXECNAMELEN](#) 30

#### 8.78.1 Detailed Description

Oscl Scheduler internal active object classes.

## 8.79 oscl\_scheduler\_readyq.h File Reference

ready q types for oscl scheduler

```
#include "oscl_scheduler_tuneables.h"
#include "oscl_priqueue.h"
#include "oscl_base_alloc.h"
#include "oscl_semaphore.h"
#include "oscl_mem.h"
#include "oscl_string_containers.h"
#include "oscl_scheduler_types.h"
#include "oscl_mutex.h"
```

### Data Structures

- class [OsclReadyAlloc](#)
- class [OsclReadyCompare](#)
- class [OsclReadyQ](#)
- class [OsclTimerCompare](#)
- class [OsclTimerQ](#)
- class [TReadyQueLink](#)

### Typedefs

- typedef [PVActiveBase](#) \* TOsclReady

#### 8.79.1 Detailed Description

ready q types for oscl scheduler

## 8.80 oscl\_scheduler\_threadcontext.h File Reference

Thread context functions needed by oscl scheduler.

```
#include "oscl_double_list.h"  
#include "oscl_mutex.h"  
#include "oscl_aostatus.h"
```

### Data Structures

- class [PVThreadContext](#)

### Enumerations

- enum [TPVThreadContext](#) { [EPVThreadContext\\_InThread](#), [EPVThreadContext\\_OsclThread](#), [EPVThreadContext\\_NonOsclThread](#), [EPVThreadContext\\_Undetermined](#) }

### 8.80.1 Detailed Description

Thread context functions needed by oscl scheduler.

## 8.81 oscl\_scheduler\_tuneables.h File Reference

Tunable settings for Oscl Scheduler.

```
#include "osclconfig_proc.h"
```

### Defines

- #define PV\_SCHED\_ENABLE\_AO\_STATS 1
- #define PV\_SCHED\_ENABLE\_LOOP\_STATS 0
- #define PV\_SCHED\_ENABLE\_PERF\_LOGGING 1
- #define PV\_SCHED\_ENABLE\_THREAD\_CONTEXT\_CHECKS 1
- #define PV\_SCHED\_LOG\_Q 0
- #define PV\_SCHED\_CHECK\_Q 0
- #define PV\_SCHED\_FAIR\_SCHEDULING 1
- #define OSCL\_PERF\_SUMMARY\_LOGGING 0

### 8.81.1 Detailed Description

Tunable settings for Oscl Scheduler.

## 8.82 oscl\_scheduler\_types.h File Reference

Scheduler common types include file.

```
#include "osclconfig_proc.h"  
#include "oscl_aostatus.h"  
#include "oscl_heapbase.h"
```

### Data Structures

- class [OsclExecSchedulerBase](#)

#### 8.82.1 Detailed Description

Scheduler common types include file.

## 8.83 oscl\_semaphore.h File Reference

This file provides implementation of mutex.

```
#include "osclconfig_proc.h"  
#include "oscl_thread.h"
```

### Data Structures

- class [OsclSemaphore](#)

#### 8.83.1 Detailed Description

This file provides implementation of mutex.

## 8.84 oscl\_shared\_ptr.h File Reference

This file defines a template class [OsclSharedPtr](#) which is a "smart pointer" to the parameterized type.

```
#include "oscl_base.h"
#include "oscl_refcounter.h"
#include "osclconfig_compiler_warnings.h"
```

### Data Structures

- class [OsclSharedPtr](#)  
*A parameterized smart pointer class.*

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_RETURN\\_TYPE\\_NOT\\_UDT](#)

#### 8.84.1 Detailed Description

This file defines a template class [OsclSharedPtr](#) which is a "smart pointer" to the parameterized type.

## 8.85 oscl\_singleton.h File Reference

This file defines the [OsclSingleton](#) class. This class provides a container which used to give access to a set of process-level singleton objects. Each object is indexed by an integer ID, listed below. There can only be one instance of each object per process at a given time.

```
#include "oscl_base.h"
#include "oscl_defalloc.h"
```

### Data Structures

- class [OsclSingleton](#)
- class [OsclSingletonRegistry](#)
- class [SingletonTable](#)

### Variables

- const uint32 [OSCL\\_SINGLETON\\_ID\\_TEST](#) = 0
- const uint32 [OSCL\\_SINGLETON\\_ID\\_OSCLMEM](#) = 1
- const uint32 [OSCL\\_SINGLETON\\_ID\\_PVLOGGER](#) = 2
- const uint32 [OSCL\\_SINGLETON\\_ID\\_PVSCHEDULER](#) = 3
- const uint32 [OSCL\\_SINGLETON\\_ID\\_PVERRORTRAP](#) = 4
- const uint32 [OSCL\\_SINGLETON\\_ID\\_SDPMEDIAPARSER](#) = 5
- const uint32 [OSCL\\_SINGLETON\\_ID\\_PAYLOADPARSER](#) = 6
- const uint32 [OSCL\\_SINGLETON\\_ID\\_CPM\\_PLUGIN](#) = 7
- const uint32 [OSCL\\_SINGLETON\\_ID\\_PVMFRECOGNIZER](#) = 8
- const uint32 [OSCL\\_SINGLETON\\_ID\\_OSCLREGISTRY](#) = 9
- const uint32 [OSCL\\_SINGLETON\\_ID\\_OMX](#) = 10
- const uint32 [OSCL\\_SINGLETON\\_ID\\_OMXMASTERCORE](#) = 11
- const uint32 [OSCL\\_SINGLETON\\_ID\\_TICKCOUNT](#) = 12
- const uint32 [OSCL\\_SINGLETON\\_ID\\_WMDRMLOCK](#) = 13
- const uint32 [OSCL\\_SINGLETON\\_ID\\_LAST](#) = 14

### 8.85.1 Detailed Description

This file defines the [OsclSingleton](#) class. This class provides a container which used to give access to a set of process-level singleton objects. Each object is indexed by an integer ID, listed below. There can only be one instance of each object per process at a given time.

[OsclSingleton](#) is initialized in [OsclBase::Init](#).

## 8.85.2 Variable Documentation

- 8.85.2.1 `const uint32 OSCL_SINGLETON_ID_CPM_PLUGIN = 7`
- 8.85.2.2 `const uint32 OSCL_SINGLETON_ID_LAST = 14`
- 8.85.2.3 `const uint32 OSCL_SINGLETON_ID_OMX = 10`
- 8.85.2.4 `const uint32 OSCL_SINGLETON_ID_OMXMASTERCORE = 11`
- 8.85.2.5 `const uint32 OSCL_SINGLETON_ID_OSCLMEM = 1`
- 8.85.2.6 `const uint32 OSCL_SINGLETON_ID_OSCLREGISTRY = 9`
- 8.85.2.7 `const uint32 OSCL_SINGLETON_ID_PAYLOADPARSER = 6`
- 8.85.2.8 `const uint32 OSCL_SINGLETON_ID_PVERRORTRAP = 4`
- 8.85.2.9 `const uint32 OSCL_SINGLETON_ID_PVLOGGER = 2`
- 8.85.2.10 `const uint32 OSCL_SINGLETON_ID_PVMFRECOGNIZER = 8`
- 8.85.2.11 `const uint32 OSCL_SINGLETON_ID_PVSCHEDULER = 3`
- 8.85.2.12 `const uint32 OSCL_SINGLETON_ID_SDPMEDIAPARSER = 5`
- 8.85.2.13 `const uint32 OSCL_SINGLETON_ID_TEST = 0`
- 8.85.2.14 `const uint32 OSCL_SINGLETON_ID_TICKCOUNT = 12`
- 8.85.2.15 `const uint32 OSCL_SINGLETON_ID_WMDRMLOCK = 13`

## 8.86 oscl\_snprintf.h File Reference

Provides a portable implementation of snprintf.

```
#include "oscl_base.h"  
#include "osclconfig_util.h"
```

### Functions

- OSCL\_IMPORT\_REF int32 [oscl\\_snprintf](#) (char \*str, uint32 count, const char \*fmt,...)
- OSCL\_IMPORT\_REF int32 [oscl\\_snprintf](#) ([oscl\\_wchar](#) \*str, uint32 count, const [oscl\\_wchar](#) \*fmt,...)
- OSCL\_IMPORT\_REF int32 [oscl\\_vsnprintf](#) (char \*str, uint32 count, const char \*fmt, va\_list args)
- OSCL\_IMPORT\_REF int32 [oscl\\_vsnprintf](#) ([oscl\\_wchar](#) \*str, uint32 count, const [oscl\\_wchar](#) \*fmt, va\_list args)

### 8.86.1 Detailed Description

Provides a portable implementation of snprintf.

## 8.87 oscl\_socket.h File Reference

The file [oscl\\_socket.h](#) defines the OSCL Socket APIs.

```
#include "osclconfig_io.h"  
#include "oscl_heapbase.h"  
#include "oscl_defalloc.h"  
#include "oscl_vector.h"  
#include "oscl_mem.h"  
#include "oscl_socket_types.h"
```

### Data Structures

- class [OsclSocketServ](#)
- class [OsclTCPSocket](#)
- class [OsclUDPSocket](#)

#### 8.87.1 Detailed Description

The file [oscl\\_socket.h](#) defines the OSCL Socket APIs.

## 8.88 oscl\_socket\_accept.h File Reference

```
#include "oscl_socket_imp.h"
#include "oscl_socket_serv_imp.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclAcceptMethod](#)
- class [OsclAcceptRequest](#)

## 8.89 oscl\_socket\_bind.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_socket_serv_imp.h"
#include "oscl_socket_imp.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclBindMethod](#)
- class [OsclBindRequest](#)

## 8.90 oscl\_socket\_connect.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_socket_serv_imp.h"
#include "oscl_socket_imp.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclConnectMethod](#)
- class [OsclConnectRequest](#)

## **8.91 oscl\_socket\_imp.h File Reference**

```
#include "oscl_socket_tuneables.h"  
#include "oscl_socket_imp_pv.h"
```

## 8.92 oscl\_socket\_imp\_base.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_socket_request.h"
#include "oscl_defalloc.h"
#include "oscl_mutex.h"
#include "oscl_socket_stats.h"
#include "oscl_base.h"
```

### Data Structures

- class [OsclSocketIBase](#)

## 8.93 oscl\_socket\_imp\_pv.h File Reference

```
#include "oscl_socket_imp_base.h"
```

### Data Structures

- class [OsclSocketI](#)

### Defines

- #define [PVSOCK\\_ERR\\_BAD\\_PARAM](#) (-1)
- #define [PVSOCK\\_ERR SOCK\\_NOT\\_OPEN](#) (-2)
- #define [PVSOCK\\_ERR SOCK\\_NO\\_SERV](#) (-3)
- #define [PVSOCK\\_ERR SERV\\_NOT\\_CONNECTED](#) (-4)
- #define [PVSOCK\\_ERR SOCK\\_NOT\\_CONNECTED](#) (-5)
- #define [PVSOCK\\_ERR NOT\\_IMPLEMENTED](#) (-6)
- #define [PVSOCK\\_ERR NOT\\_SUPPORTED](#) (-7)

### 8.93.1 Define Documentation

#### 8.93.1.1 #define PVSOCK\_ERR\_BAD\_PARAM (-1)

some error codes for request completion these are negative so they won't conflict with errors from the OS socket layer.

#### 8.93.1.2 #define PVSOCK\_ERR\_NOT\_IMPLEMENTED (-6)

#### 8.93.1.3 #define PVSOCK\_ERR\_NOT\_SUPPORTED (-7)

#### 8.93.1.4 #define PVSOCK\_ERR\_SERV\_NOT\_CONNECTED (-4)

#### 8.93.1.5 #define PVSOCK\_ERR SOCK\_NO\_SERV (-3)

#### 8.93.1.6 #define PVSOCK\_ERR SOCK\_NOT\_CONNECTED (-5)

#### 8.93.1.7 #define PVSOCK\_ERR SOCK\_NOT\_OPEN (-2)

## 8.94 oscl\_socket\_listen.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_socket_serv_imp.h"
#include "oscl_socket_imp.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclListenMethod](#)
- class [OsclListenRequest](#)

### Defines

- #define [OSCL\\_SOCKET\\_LISTEN\\_H\\_INCLUDEDd](#)

#### 8.94.1 Define Documentation

##### 8.94.1.1 #define OSCL\_SOCKET\_LISTEN\_H\_INCLUDEDd

## 8.95 oscl\_socket\_method.h File Reference

```
#include "osclconfig_io.h"
#include "oscl_socket_types.h"
#include "oscl_scheduler_ao.h"
#include "oscl_socket_request.h"
#include "pvlogger.h"
#include "oscl_socket_tuneables.h"
#include "oscl_ip_socket.h"
#include "oscl_socket_imp.h"
```

### Data Structures

- class [OsclSocketMethod](#)
- class [OsclSocketRequestAO](#)

### Defines

- #define [MSEC\\_TO\\_MICROSEC](#) 1000

#### 8.95.1 Define Documentation

##### 8.95.1.1 #define MSEC\_TO\_MICROSEC 1000

## **8.96 oscl\_socket\_recv.h File Reference**

```
#include "oscl_socket_serv_imp.h"
#include "oscl_socket_imp.h"
#include "oscl_socket_method.h"
```

### **Data Structures**

- class [OsclRecvMethod](#)
- class [OsclRecvRequest](#)

## 8.97 oscl\_socket\_recv\_from.h File Reference

```
#include "oscl_socket_serv_imp.h"
#include "oscl_socket_imp.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclRecvFromMethod](#)
- class [OsclRecvFromRequest](#)

## 8.98 oscl\_socket\_request.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
#include "oscl_socket_tuneables.h"
```

### Data Structures

- class [AcceptParam](#)
- class [BindParam](#)
- class [ConnectParam](#)
- class [ListenParam](#)
- class [OsclSocketRequest](#)
- class [PVSockBufRecv](#)
- class [PVSockBufSend](#)
- class [RecvFromParam](#)
- class [RecvParam](#)
- class [SendParam](#)
- class [SendToParam](#)
- class [ShutdownParam](#)
- class [SocketRequestParam](#)

## 8.99 oscl\_socket\_send.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclSendMethod](#)
- class [OsclSendRequest](#)

## **8.100 oscl\_socket\_send\_to.h File Reference**

```
#include "oscl_socket_types.h"
#include "oscl_socket_imp.h"
#include "oscl_socket_method.h"
```

### **Data Structures**

- class [OsclSendToMethod](#)
- class [OsclSendToRequest](#)

## 8.101 oscl\_socket\_serv\_imp.h File Reference

```
#include "osclconfig_io.h"
#include "oscl_socket_tuneables.h"
#include "oscl_socket_serv_imp_pv.h"
```

## **8.102 oscl\_socket\_serv\_imp\_base.h File Reference**

```
#include "oscl_base.h"
#include "oscl_socket_stats.h"
```

### **Data Structures**

- class [OsclSocketServIBase](#)

## 8.103 oscl\_socket\_serv\_imp\_pv.h File Reference

```
#include "oscl_socket_serv_imp_base.h"
#include "oscl_socket_serv_imp_reqlist.h"
#include "oscl_socket_tuneables.h"
#include "oscl_scheduler_ao.h"
```

### Data Structures

- class [OsclSocketServI](#)

### Defines

- #define [OSCL\\_READSET\\_FLAG](#) 0x04
- #define [OSCL\\_WRITESET\\_FLAG](#) 0x02
- #define [OSCL\\_EXCEPTSET\\_FLAG](#) 0x01

### 8.103.1 Define Documentation

#### 8.103.1.1 #define OSCL\_EXCEPTSET\_FLAG 0x01

#### 8.103.1.2 #define OSCL\_READSET\_FLAG 0x04

A bitmask for socket select operations

#### 8.103.1.3 #define OSCL\_WRITESET\_FLAG 0x02

## 8.104 oscl\_socket\_serv\_imp\_reqlist.h File Reference

```
#include "oscl_socket_tuneables.h"
#include "oscl_defalloc.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
```

### Data Structures

- class [OsclSocketServRequestList](#)
- class [OsclSocketServRequestQElem](#)

## 8.105 oscl\_socket\_shutdown.h File Reference

```
#include "oscl_socket_types.h"
#include "oscl_socket_method.h"
```

### Data Structures

- class [OsclShutdownMethod](#)
- class [OsclShutdownRequest](#)

## 8.106 oscl\_socket\_stats.h File Reference

```
#include "oscl_base.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
#include "oscl_mutex.h"
#include "oscl_socket_tuneables.h"
```

### Enumerations

- enum TOsclSocketStatEvent { EOscSocket\_RequestAO\_Success, EOscSocket\_RequestAO\_Canceled, EOscSocket\_RequestAO\_Error, EOscSocket\_RequestAO\_Timeout, EOscSocket\_ServRequestIssued, EOscSocket\_ServPoll, EOscSocket\_OS, EOscSocket\_Readable, EOscSocket\_Writable, EOscSocket\_Except, EOscSocket\_DataRecv, EOscSocket\_DataSent, EOscSocket\_ServRequestComplete, EOscSocket\_ServRequestCancelIssued, EOscSocketServ\_LoopsockOk, EOscSocketServ\_LoopsockError }
- enum TOsclSocketServStatEvent { EOscSocketServ\_SelectNoActivity = 0, EOscSocketServ\_SelectActivity, EOscSocketServ\_SelectRescheduleAsap, EOscSocketServ\_SelectReschedulePoll, EOscSocketServ\_LastEvent }

#### 8.106.1 Enumeration Type Documentation

##### 8.106.1.1 enum TOsclSocketServStatEvent

###### Enumeration values:

**EOscSocketServ\_SelectNoActivity**  
**EOscSocketServ\_SelectActivity**  
**EOscSocketServ\_SelectRescheduleAsap**  
**EOscSocketServ\_SelectReschedulePoll**  
**EOscSocketServ\_LastEvent**

##### 8.106.1.2 enum TOsclSocketStatEvent

Socket diagnostics.

###### Enumeration values:

**EOscSocket\_RequestAO\_Success**  
**EOscSocket\_RequestAO\_Canceled**  
**EOscSocket\_RequestAO\_Error**  
**EOscSocket\_RequestAO\_Timeout**  
**EOscSocket\_ServRequestIssued**  
**EOscSocket\_ServPoll**  
**EOscSocket\_OS**  
**EOscSocket\_Readable**  
**EOscSocket\_Writable**

---

**EOselSocket\_Except**  
**EOselSocket\_DataRecv**  
**EOselSocket\_DataSent**  
**EOselSocket\_ServRequestComplete**  
**EOselSocket\_ServRequestCancelIssued**  
**EOselSocketServ\_LoopsockOk**  
**EOselSocketServ\_LoopsockError**

## 8.107 oscl\_socket\_tuneables.h File Reference

```
#include "osclconfig_io.h"
#include "osclconfig_proc.h"
```

### Defines

- #define PV\_SOCKET\_REQUEST\_AO\_PRIORITY OsclActiveObject::EPriorityNominal
- #define PV\_OSCL\_SOCKET\_STATS\_LOGGING 0
- #define PV\_SOCKET\_SERVER 1
- #define PV\_SOCKET\_SERVER\_IS\_THREAD OSCL\_HAS\_THREAD\_SUPPORT
- #define PV\_SOCKET\_SERVER\_SELECT 0
- #define PV\_SOCKET\_SERVER\_THREAD\_PRIORITY ThreadPriorityAboveNormal
- #define PV\_SOCKET\_SERVER\_SELECT\_TIMEOUT\_MSEC (-1)
- #define PV\_SOCKET\_SERVER\_SELECT\_LOOPBACK\_SOCKET 0
- #define PV\_SOCKET\_SERVER\_AO\_PRIORITY (OsclActiveObject::EPriorityNominal)
- #define PV\_SOCKET\_SERVER\_AO\_INTERVAL\_MSEC 5
- #define PV\_OSCL\_SOCKET\_SERVER\_LOGGER\_OUTPUT 0
- #define PV\_OSCL\_SOCKET\_1MB\_RECV\_BUF 0
- #define PV\_SOCKET\_SERVI\_STATS 0

### 8.107.1 Define Documentation

#### 8.107.1.1 #define PV\_OSCL\_SOCKET\_1MB\_RECV\_BUF 0

Set this to 0 or 1 to enable/disable setting the socket receive buffer size to 1 MB in the Bind call. This setting only affects PV socket server implementations.

When set to 1, the code will use the OsclSetRecvBufferSize macro to set the buffer size in the Bind call.

This setting was found to improve streaming performance on WinMobile devices, but should not generally be used.

#### 8.107.1.2 #define PV\_OSCL\_SOCKET\_SERVER\_LOGGER\_OUTPUT 0

Set this to 0 or 1 to enable/disable [PVLogger](#) output from PV socket server. Note that socket server logging will appear in a different file when running threaded mode of socket server. This is quite a bit of logging, so it should generally be disabled.

#### 8.107.1.3 #define PV\_OSCL\_SOCKET\_STATS\_LOGGING 0

Set this to 0 or 1 to enable/disable socket stats logging with "OsclSocketStats" node. This feature is fairly costly so should be off in production code.

#### 8.107.1.4 #define PV\_SOCKET\_REQUEST\_AO\_PRIORITY OsclActiveObject::EPriority-Nominal

PV\_SOCKET\_REQUEST\_AO\_PRIORITY sets the priority of the socket request completion AOs.

**8.107.1.5 #define PV\_SOCKET\_SERVER 1**

Enable/disable the PV socket server here.

**8.107.1.6 #define PV\_SOCKET\_SERVER\_AO\_INTERVAL\_MSEC 5**

PV\_SOCKET\_SERVER\_AO\_INTERVAL\_MSEC sets the AO scheduling interval of the PV socket server AO for non-threaded implementations.

**8.107.1.7 #define PV\_SOCKET\_SERVER\_AO\_PRIORITY (OsclActiveObject::EPriority-Nominal)**

PV\_SOCKET\_SERVER\_AO\_PRIORITY sets priority of the PV socket server AO for non-threaded implementations.

**8.107.1.8 #define PV\_SOCKET\_SERVER\_IS\_THREAD OSCL\_HAS\_THREAD\_SUPPORT**

PV\_SOCKET\_SERVER\_IS\_THREAD chooses either the threaded or AO-based implementation of the PV socket server

**8.107.1.9 #define PV\_SOCKET\_SERVER\_SELECT 0**

PV\_SOCKET\_SERVER\_SELECT chooses whether to use "select" call or not. In threaded mode, select call is required and is forced to "1". In AO mode, "select" call is an option that defaults to "0". Avoiding any "select" call was found to greatly reduce CPU usage on WinMobile devices.

**8.107.1.10 #define PV\_SOCKET\_SERVER\_SELECT\_LOOPBACK\_SOCKET 0**

PV\_SOCKET\_SERVER\_SELECT\_LOOPBACK\_SOCKET enables the feature to wakeup the select call by writing to a loopback socket each time a new request comes in. This option is required to support the blocking select option of threaded server mode. This option is forced to "0" in AO mode.

**8.107.1.11 #define PV\_SOCKET\_SERVER\_SELECT\_TIMEOUT\_MSEC (-1)**

PV\_SOCKET\_SERVER\_SELECT\_TIMEOUT\_MSEC sets duration of the select call in the PV socket server thread for the polling select loop implementation. When the timeout is -1, the select call will block forever waiting on a new request and will use a loopback socket to signal a new request. Note: if infinite wait is selected, but loopback socket is not available, the implementation will poll at 10 msec intervals.

**8.107.1.12 #define PV\_SOCKET\_SERVER\_THREAD\_PRIORITY ThreadPriorityAboveNormal**

PV\_SOCKET\_SERVER\_THREAD\_PRIORITY sets the priority of the PV socket server thread.

**8.107.1.13 #define PV\_SOCKET\_SERVI\_STATS 0**

For detailed performance breakdown of time spend in [OsclSocketServI](#) AO. Output is logged under "OsclSchedulerPerfStats" node. Should be off in production code. This option is forced to "0" in threaded mode.

## 8.108 oscl\_socket\_types.h File Reference

```
#include "osclconfig_io.h"
#include "oscl_types.h"
#include "oscl_scheduler_types.h"
#include "oscl_namestring.h"
#include "oscl_stdstring.h"
```

### Data Structures

- class [OsclIpMReq](#)
- class [OsclNetworkAddress](#)
- class [OsclSocketObserver](#)
- class [OsclSocketTOS](#)

### Defines

- #define [PVNETWORKADDRESS\\_LEN](#) 50

### Enumerations

- enum [TPVSocketFxn](#) { EPVSocketSend = 0, EPVSocketSendTo, EPVSocketRecv, EPVSocketRecvFrom, EPVSocketConnect, EPVSocketAccept, EPVSocketShutdown, EPVSocketBind, EPVSocketListen, EPVSocket\_Last }
- enum [TPVSocketEvent](#) { EPVSocketSuccess, EPVSocketPending, EPVSocketTimeout, EPVSocketFailure, EPVSocketCancel, EPVSocketNotImplemented }
- enum [TPVSocketShutdown](#) { EPVSocketSendShutdown, EPVSocketRecvShutdown, EPVSocketBothShutdown }
- enum [TPVSocketOptionName](#) { EPVIMulticastTTL, EPVIPAddMembership, EPVIPTOS, EPVSockReuseAddr }
- enum [TPVSocketOptionLevel](#) { EPVIPProtoIP, EPVIPProtoTCP, EPVSocket }

#### 8.108.1 Define Documentation

##### 8.108.1.1 #define PVNETWORKADDRESS\_LEN 50

#### 8.108.2 Enumeration Type Documentation

##### 8.108.2.1 enum TPVSocketEvent

Return codes for asynchronous APIs

**Enumeration values:**

**EPVSocketSuccess**  
**EPVSocketPending**  
**EPVSocketTimeout**  
**EPVSocketFailure**

**EPVSocketCancel**  
**EPVSocketNotImplemented**

#### **8.108.2.2 enum TPVSocketFxn**

**Enumeration values:**

**EPVSocketSend**  
**EPVSocketSendTo**  
**EPVSocketRecv**  
**EPVSocketRecvFrom**  
**EPVSocketConnect**  
**EPVSocketAccept**  
**EPVSocketShutdown**  
**EPVSocketBind**  
**EPVSocketListen**  
**EPVSocket\_Last**

#### **8.108.2.3 enum TPVSocketOptionLevel**

**Enumeration values:**

**EPVIPProtoIP**  
**EPVIPProtoTCP**  
**EPVSocket**

#### **8.108.2.4 enum TPVSocketOptionName**

**Enumeration values:**

**EPVIMulticastTTL**  
**EPVIAAddMembership**  
**EPVIPTOS**  
**EPVSockReuseAddr**

#### **8.108.2.5 enum TPVSocketShutdown**

**Enumeration values:**

**EPVSocketSendShutdown**  
**EPVSocketRecvShutdown**  
**EPVSocketBothShutdown**

## 8.109 oscl\_stdstring.h File Reference

This file provides standard string operations such as strlen, strncpy, etc. ANSI defines undefined behavior when the destination pointer is null for operations such as strncpy, strncat, etc. But, we chose to define one. In such cases, we return the destination as null.

```
#include "oscl_base.h"
```

### Functions

- OSCL\_IMPORT\_REF uint32 `oscl_strlen` (const char \*str)
- OSCL\_IMPORT\_REF uint32 `oscl_strlen` (const `oscl_wchar` \*str)
- OSCL\_IMPORT\_REF char \* `oscl_strncpy` (char \*dest, const char \*src, uint32 count)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strncpy` (`oscl_wchar` \*dest, const `oscl_wchar` \*src, uint32 count)
- OSCL\_IMPORT\_REF int32 `oscl_strcmp` (const char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF int32 `oscl_stremp` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2)
- OSCL\_IMPORT\_REF int32 `oscl_strncmp` (const char \*str1, const char \*str2, uint32 count)
- OSCL\_IMPORT\_REF int32 `oscl_strncmp` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2, uint32 count)
- OSCL\_IMPORT\_REF char \* `oscl_strncat` (char \*dest, const char \*src, uint32 count)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strncat` (`oscl_wchar` \*dest, const `oscl_wchar` \*src, uint32 count)
- OSCL\_IMPORT\_REF const char \* `oscl_strchr` (const char \*str, int32 c)
- OSCL\_IMPORT\_REF char \* `oscl_strchr` (char \*str, int32 c)
- OSCL\_IMPORT\_REF const `oscl_wchar` \* `oscl_strchr` (const `oscl_wchar` \*str, int32 c)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strchr` (`oscl_wchar` \*str, int32 c)
- OSCL\_IMPORT\_REF const char \* `oscl strrchr` (const char \*str, int32 c)
- OSCL\_IMPORT\_REF char \* `oscl strrchr` (char \*str, int32 c)
- OSCL\_IMPORT\_REF const `oscl_wchar` \* `oscl strrchr` (const `oscl_wchar` \*str, int32 c)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl strrchr` (`oscl_wchar` \*str, int32 c)
- OSCL\_IMPORT\_REF char \* `oscl_strset` (char \*dest, char val, uint32 count)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strset` (`oscl_wchar` \*dest, `oscl_wchar` val, uint32 count)
- OSCL\_IMPORT\_REF int32 `oscl_CIstrcmp` (const char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF int32 `oscl_CIstrcmp` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2)
- OSCL\_IMPORT\_REF int32 `oscl_CIstrncmp` (const char \*str1, const char \*str2, uint32 count)
- OSCL\_IMPORT\_REF int32 `oscl_CIstrncmp` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2, uint32 count)
- OSCL\_IMPORT\_REF char `oscl_tolower` (const char car)
- OSCL\_IMPORT\_REF `oscl_wchar` `oscl_tolower` (const `oscl_wchar` car)
- OSCL\_IMPORT\_REF bool `oscl_isLetter` (const char car)
- OSCL\_IMPORT\_REF const char \* `oscl_strstr` (const char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF char \* `oscl_strstr` (char \*str1, const char \*str2)
- OSCL\_IMPORT\_REF const `oscl_wchar` \* `oscl_strstr` (const `oscl_wchar` \*str1, const `oscl_wchar` \*str2)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_strstr` (`oscl_wchar` \*str1, const `oscl_wchar` \*str2)
- OSCL\_IMPORT\_REF char \* `oscl_streat` (char \*dest, const char \*src)
- OSCL\_IMPORT\_REF `oscl_wchar` \* `oscl_streat` (`oscl_wchar` \*dest, const `oscl_wchar` \*src)

### **8.109.1 Detailed Description**

This file provides standard string operations such as strlen, strncpy, etc. ANSI defines undefined behavior when the destination pointer is null for operations such as strncpy, strncat, etc. But, we chose to define one. In such cases, we return the destination as null.

## 8.110 oscl\_str\_ptr\_len.h File Reference

Defines a data structure for string containment/manipulations where the storage for the string is maintained externally.

```
#include "oscl_base.h"
#include "oscl_stdstring.h"
```

### Data Structures

- struct [StrCSumPtrLen](#)  
*same as [StrPtrLen](#), but includes checksum field and method to speed up querying*
- struct [StrPtrLen](#)  
*This data structure encapsulates a set of functions used to perform.*
- struct [WStrPtrLen](#)  
*This data structure encapsulates a set of functions used to perform.*

### Typedefs

- typedef StrPtrLen [StrPtrLen](#)  
*This data structure encapsulates a set of functions used to perform.*
- typedef WStrPtrLen [WStrPtrLen](#)  
*This data structure encapsulates a set of functions used to perform.*
- typedef StrCSumPtrLen [StrCSumPtrLen](#)  
*same as [StrPtrLen](#), but includes checksum field and method to speed up querying*
- typedef [WStrPtrLen](#) [OSCL\\_TStrPtrLen](#)

### Variables

- const uint8 [OSCL\\_ASCII\\_CASE\\_MAGIC\\_BIT](#) = 0x20

#### 8.110.1 Detailed Description

Defines a data structure for string containment/manipulations where the storage for the string is maintained externally.

## 8.111 oscl\_string.h File Reference

Provides a standardized set of string containers that can be used in place of character arrays.

```
#include "oscl_base.h"  
#include "oscl_mem.h"
```

### Data Structures

- class [OSCL\\_String](#)
- class [OSCL\\_wString](#)

### Enumerations

- enum [TOSCL\\_StringOp](#) { [EOSCL\\_StringOp\\_CompressASCII](#), [EOSCL\\_StringOp\\_UTF16ToUTF8](#) }
- enum [TOSCL\\_wStringOp](#) { [EOSCL\\_wStringOp\\_ExpandASCII](#), [EOSCL\\_wStringOp\\_UTF8ToUTF16](#) }

#### 8.111.1 Detailed Description

Provides a standardized set of string containers that can be used in place of character arrays.

## 8.112 oscl\_string\_containers.h File Reference

Provides a standardized set of string containers that can be used in place of character arrays.

```
#include "oscl_string.h"  
#include "oscl_defalloc.h"  
#include "oscl_refcounter.h"  
#include "oscl_error.h"  
#include "oscl_string_rep.h"  
#include "oscl_stdstring.h"  
#include "oscl_mem.h"
```

### Data Structures

- class [OSCL\\_FastString](#)
- class [OSCL\\_HeapString](#)
- class [OSCL\\_HeapStringA](#)
- class [OSCL\\_StackString](#)
- class [OSCL\\_wFastString](#)
- class [OSCL\\_wHeapString](#)
- class [OSCL\\_wHeapStringA](#)
- class [OSCL\\_wStackString](#)

#### 8.112.1 Detailed Description

Provides a standardized set of string containers that can be used in place of character arrays.

## **8.113 oscl\_string\_rep.h File Reference**

Contains some internal implementation for string containers.

```
#include "oscl_defalloc.h"
```

### **Data Structures**

- class [CFastRep](#)
- class [CHheapRep](#)
- class [CStackRep](#)

#### **8.113.1 Detailed Description**

Contains some internal implementation for string containers.

## 8.114 oscl\_string\_uri.h File Reference

Utilities to unescape URIs.

```
#include "oscl_base.h"  
#include "oscl_string.h"
```

### Functions

- OSCL\_IMPORT\_REF bool [oscl\\_str\\_unescape\\_uri](#) (const char \*str\_buf\_in, char \*str\_buf\_out, uint32 max\_out\_buf\_bytes, uint32 max\_bytes, uint32 &out\_buf\_len)  
*unescape any of the special escape sequence in the uri string*
- OSCL\_IMPORT\_REF bool [oscl\\_str\\_unescape\\_uri](#) (const [OSCL\\_String](#) &oscl\_str\_in, [OSCL\\_String](#) &oscl\_str\_out, uint32 &out\_buf\_len)  
*unescape any of the special escape sequence in the uri string*

### 8.114.1 Detailed Description

Utilities to unescape URIs.

## 8.115 oscl\_string\_utf8.h File Reference

Utilities to validate and truncate UTF-8 encoded strings.

```
#include "oscl_base.h"
```

### Functions

- OSCL\_IMPORT\_REF bool `oscl_str_is_valid_utf8` (const uint8 \*str\_buf, uint32 &num\_valid\_characters, uint32 max\_bytes=0, uint32 max\_char\_2\_valid=0, uint32 \*num\_byte\_4\_char=NULL)

*Check if the input string contains any illegal UTF-8 character. The function scans the string and validate that each character is a valid utf-8. It stops at the first NULL character, invalid character or the max\_byte value. The string is valid if and only if every character is a valid utf-8 character and the scanning stopped on a character boundary.*

- OSCL\_IMPORT\_REF int32 `oscl_str_truncate_utf8` (uint8 \*str\_buf, uint32 max\_char, uint32 max\_bytes=0)

*Truncates the UTF-8 string upto the required size.*

### 8.115.1 Detailed Description

Utilities to validate and truncate UTF-8 encoded strings.

## 8.116 oscl\_string\_utils.h File Reference

Utilities to parse and convert strings.

```
#include "oscl_base.h"
```

### Defines

- #define `oscl_isdigit(c)` ((c) >= '0' && (c) <= '9')

### Functions

- OSCL\_IMPORT\_REF const char \* `skip_whitespace` (const char \*ptr)
- OSCL\_IMPORT\_REF char \* `skip_whitespace` (char \*ptr)
- OSCL\_IMPORT\_REF const char \* `skip_whitespace` (const char \*start, const char \*end)
- OSCL\_IMPORT\_REF const char \* `skip_to_whitespace` (const char \*start, const char \*end)
- OSCL\_IMPORT\_REF const char \* `skip_to_line_term` (const char \*start\_ptr, const char \*end\_ptr)
- OSCL\_IMPORT\_REF const char \* `skip_whitespace_and_line_term` (const char \*start, const char \*end)
- OSCL\_IMPORT\_REF int `extract_string` (const char \*in\_ptr, char \*outstring, int maxsize)
- OSCL\_IMPORT\_REF int `extract_string` (const char \*start, const char \*end, char \*outstring, int maxsize)
- OSCL\_IMPORT\_REF bool `PV_atoi` (const char \*buf, const char new\_format, uint32 &value)
- OSCL\_IMPORT\_REF bool `PV_atoi` (const char \*buf, const char new\_format, int length, uint32 &value)
- OSCL\_IMPORT\_REF bool `PV_atoi` (const char \*buf, const char new\_format, int length, `uint64` &value)
- OSCL\_IMPORT\_REF bool `PV_atof` (const char \*buf, `OsclFloat` &value)
- OSCL\_IMPORT\_REF bool `PV_atof` (const char \*buf, int length, `OsclFloat` &value)
- OSCL\_IMPORT\_REF int `oscl_abs` (int aVal)

### 8.116.1 Detailed Description

Utilities to parse and convert strings.

## 8.117 oscl\_string\_xml.h File Reference

Utilities to escape special characters in XML strings.

```
#include "oscl_base.h"
```

### Functions

- OSCL\_IMPORT\_REF bool [oscl\\_str\\_need\\_escape\\_xml](#) (const char \*str\_buf, uint32 &num\_escape\_bytes, uint32 max\_bytes=0)

*Check if the input string contains any special ASCII character like &, <, >, ', ". The function scans the string and check if each character is a special character. It stops at the first NULL character (if max\_bytes = 0), or the max\_byte value.*

- OSCL\_IMPORT\_REF int32 [oscl\\_str\\_escape\\_xml](#) (const char \*str\_buf\_in, char \*str\_buf\_out, uint32 max\_out\_buf\_bytes, uint32 max\_bytes=0, uint32 \*num\_bytes\_written=NULL)

*Escape any of the following special characters in the string Special ASCII characters: &, <, >, ', ".*

### 8.117.1 Detailed Description

Utilities to escape special characters in XML strings.

## 8.118 oscl\_tagtree.h File Reference

The file [oscl\\_tagtree.h](#) ...

```
#include "oscl_base.h"
#include "oscl_map.h"
#include "oscl_vector.h"
#include "oscl_stdstring.h"
#include "osclconfig_compiler_warnings.h"
```

### Data Structures

- struct [const\\_iterator](#)
- struct [iterator](#)
- struct [Node](#)
- struct [Oscl\\_Tag](#)
- struct [Oscl\\_Tag\\_Base](#)
- class [Oscl\\_TagTree](#)

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)

#### 8.118.1 Detailed Description

The file [oscl\\_tagtree.h](#) ...

#### 8.118.2 Define Documentation

##### 8.118.2.1 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE

## **8.119 oscl\_tcp\_socket.h File Reference**

```
#include "oscl_ip_socket.h"
#include "oscl_defalloc.h"
#include "oscl_vector.h"
#include "oscl_mem.h"
#include "oscl_socket_listen.h"
#include "oscl_socket_recv.h"
#include "oscl_socket_send.h"
#include "oscl_socket_accept.h"
#include "oscl_socket_shutdown.h"
#include "oscl_socket_connect.h"
#include "oscl_socket_bind.h"
```

### **Data Structures**

- class [OsclTCPSocketI](#)

## 8.120 oscl\_thread.h File Reference

```
#include "osclconfig_proc.h"
#include "oscl_procstatus.h"
#include "oscl_base.h"
```

### Data Structures

- class [OsclThread](#)

### Typedefs

- typedef [TOsclThreadFuncRet\(OSCL\\_THREAD\\_DECL \\* TOsclThreadFuncPtr \)\(TOsclThreadFuncArg\)](#)

### Enumerations

- enum [OsclThread\\_State](#) { [Start\\_on\\_creation](#), [Suspend\\_on\\_creation](#) }
- enum [OsclThreadPriority](#) { [ThreadPriorityLowest](#), [ThreadPriorityLow](#), [ThreadPriorityBelowNormal](#), [ThreadPriorityNormal](#), [ThreadPriorityAboveNormal](#), [ThreadPriorityHighest](#), [ThreadPriorityTimeCritical](#) }
- enum [TOsclThreadTerminate](#) { [EOsclThreadTerminate\\_Join](#), [EOsclThreadTerminate\\_Kill](#), [EOsclThreadTerminate\\_NOP](#) }

### 8.120.1 Detailed Description

. This file provides THREAD implementation that can be ported  
to three OS LINUX, SYMBIAN, WIN32

### 8.120.2 Typedef Documentation

#### 8.120.2.1 [typedef TOsclThreadFuncRet\(OSCL\\_THREAD\\_DECL \\* TOsclThreadFuncPtr\)\(TOsclThreadFuncArg\)](#)

### 8.120.3 Enumeration Type Documentation

#### 8.120.3.1 enum [OsclThread\\_State](#)

Enumeration values:

[Start\\_on\\_creation](#)  
[Suspend\\_on\\_creation](#)

#### 8.120.3.2 enum [OsclThreadPriority](#)

Enumeration values:

[ThreadPriorityLowest](#)

**ThreadPriorityLow**  
**ThreadPriorityBelowNormal**  
**ThreadPriorityNormal**  
**ThreadPriorityAboveNormal**  
**ThreadPriorityHighest**  
**ThreadPriorityTimeCritical**

#### 8.120.3.3 enum TOsclThreadTerminate

Enumeration values:

**EOsclThreadTerminate\_Join**  
**EOsclThreadTerminate\_Kill**  
**EOsclThreadTerminate\_NOP**

## 8.121 oscl\_tickcount.h File Reference

Defines a data structure for string containment/manipulations where the storage for the string is maintained externally.

```
#include "oscl_base.h"
#include "oscl_tickcount.inl"
```

### Data Structures

- class [OsclTickCount](#)

### Defines

- #define [OSCLTICKCOUNT\\_MAX\\_TICKS](#) 0xffffffff

### 8.121.1 Detailed Description

Defines a data structure for string containment/manipulations where the storage for the string is maintained externally.

## 8.122 oscl\_time.h File Reference

The file `oscl_time.h` defines two classes `NTPTime` and `TimeValue` for getting, manipulating, and formatting time values. The `TimeValue` class is based on the native system time format while `NTPTime` is used for the standard Network Time Protocol format.

```
#include "oscl_base.h"
#include "osclconfig_time.h"
#include "oscl_int64_utils.h"
#include "oscl_time.inl"
```

### Data Structures

- class `NTPTime`

*The NTPTime class represents a time value as the number of seconds since 0h (UTC) Jan. 1, 1900.*

- class `TimeValue`

*The TimeValue class represents a time value in a format native to the system.*

### Typedefs

- typedef char `CtimeStrBuf` [`CTIME_BUFFER_SIZE`]
- typedef char `PV8601timeStrBuf` [`PV8601TIME_BUFFER_SIZE`]
- typedef char `ISO8601timeStrBuf` [`ISO8601TIME_BUFFER_SIZE`]

### Enumerations

- enum `TimeUnits` { `SECONDS` = 0, `MILLISECONDS` = 1, `MICROSECONDS` = 2 }

*The TimeUnits enum can be used when constructing a `TimeValue` class.*

### Functions

- OSCL\_IMPORT\_REF void `PV8601ToRFC822` (`PV8601timeStrBuf` `pv8601_buffer`, `CtimeStrBuf` `ctime_buffer`)
- OSCL\_IMPORT\_REF void `ISO8601ToRFC822` (`ISO8601timeStrBuf` `iso8601_buffer`, `CtimeStrBuf` `ctime_buffer`)
- OSCL\_IMPORT\_REF void `RFC822ToPV8601` (`CtimeStrBuf` `ctime_buffer`, `PV8601timeStrBuf`)
- OSCL\_COND\_IMPORT\_REF `TimeValue operator-` (const `TimeValue` &`a`, const `TimeValue` &`b`)
- OSCL\_COND\_IMPORT\_REF `TimeValue operator+` (const `TimeValue` &`a`, const int32 `bSeconds`)
- OSCL\_COND\_IMPORT\_REF `TimeValue operator+` (const int32 `aSeconds`, const `TimeValue` &`b`)
- OSCL\_COND\_IMPORT\_REF `TimeValue operator-` (const `TimeValue` &`a`, const int32 `bSeconds`)
- OSCL\_COND\_IMPORT\_REF `TimeValue operator-` (const int32 `aSeconds`, const `TimeValue` &`b`)

## Variables

- const int **CTIME\_BUFFER\_SIZE** = 26
- const int **PV8601TIME\_BUFFER\_SIZE** = 21
- const int **ISO8601TIME\_BUFFER\_SIZE** = 21
- const long **USEC\_PER\_SEC** = 1000000
- const long **MSEC\_PER\_SEC** = 1000
- const uint32 **unix\_ntp\_offset** = 2208988800U

### 8.122.1 Detailed Description

The file **oscl\_time.h** defines two classes **NTPTime** and **TimeValue** for getting, manipulating, and formatting time values. The **TimeValue** class is based on the native system time format while **NTPTime** is used for the standard Network Time Protocol format.

## 8.123 oscl\_timer.h File Reference

```
#include "oscl_base.h"
#include "osclconfig_util.h"
#include "oscl_vector.h"
#include "oscl_tickcount.h"
#include "oscl_rand.h"
#include "oscl_scheduler_ao.h"
```

### Data Structures

- struct [\\_TimerEntry](#)
- class [CallbackTimer](#)
- class [CallbackTimerObserver](#)
- class [OsclTimer](#)
- class [OsclTimerObserver](#)

## 8.124 oscl\_tls.h File Reference

```
#include "oscl_base.h"
#include "oscl_defalloc.h"
```

### Data Structures

- class [OsclTLS](#)
- class [OsclTLSRegistry](#)
- class [TLSStorageOps](#)

### Defines

- #define [OSCL\\_TLS\\_BASE\\_SLOTS](#) OSCL\_TLS\_ID\_BASE\_LAST +1
- #define [OSCL\\_TLS\\_EXTERNAL\\_SLOTS](#) 0
- #define [OSCL\\_TLS\\_MAX\\_SLOTS](#) ( OSCL\_TLS\_BASE\_SLOTS + OSCL\_TLS\_EXTERNAL\_SLOTS)

### Typedefs

- typedef [OsclAny](#) TOsclTlsKey

### Variables

- const uint32 [OSCL\\_TLS\\_ID\\_MAGICNUM](#) = 0
- const uint32 [OSCL\\_TLS\\_ID\\_ERRORHOOK](#) = 1
- const uint32 [OSCL\\_TLS\\_ID\\_PVLOGGER](#) = 2
- const uint32 [OSCL\\_TLS\\_ID\\_TEST](#) = 3
- const uint32 [OSCL\\_TLS\\_ID\\_PVSCHEDULER](#) = 4
- const uint32 [OSCL\\_TLS\\_ID\\_PVERRORTRAP](#) = 5
- const uint32 [OSCL\\_TLS\\_ID\\_SDPMEDIAPARSER](#) = 6
- const uint32 [OSCL\\_TLS\\_ID\\_PAYLOADPARSER](#) = 7
- const uint32 [OSCL\\_TLS\\_ID\\_PVMFRECOGNIZER](#) = 8
- const uint32 [OSCL\\_TLS\\_ID\\_WMDRM](#) = 9
- const uint32 [OSCL\\_TLS\\_ID\\_OSCLREGISTRY](#) = 10
- const uint32 [OSCL\\_TLS\\_ID\\_SQLITE3](#) = 11
- const uint32 [OSCL\\_TLS\\_ID\\_BASE\\_LAST](#) = 11

## 8.125 oscl\_tree.h File Reference

The file [oscl\\_tree.h](#) defines the template class [Oscl\\_Rb\\_Tree](#) which has a very similar API as the STL Tree class. It is an implementation of a Red-Black Tree for use by the [Oscl\\_Map](#) class. Memory allocation is abstracted through the use of an allocator template parameter.

```
#include "oscl_defalloc.h"  
#include "osclconfig_compiler_warnings.h"
```

### Data Structures

- struct [Oscl\\_Pair](#)
- class [Oscl\\_Rb\\_Tree](#)
- class [Oscl\\_Rb\\_Tree\\_Base](#)
- struct [Oscl\\_Rb\\_Tree\\_Const\\_Iterator](#)
- struct [Oscl\\_Rb\\_Tree\\_Iterator](#)
- struct [Oscl\\_Rb\\_Tree\\_Node](#)
- struct [Oscl\\_Rb\\_Tree\\_Node\\_Base](#)

### Defines

- #define [OSCL\\_DISABLE\\_WARNING\\_TRUNCATE\\_DEBUG\\_MESSAGE](#)

### 8.125.1 Detailed Description

The file [oscl\\_tree.h](#) defines the template class [Oscl\\_Rb\\_Tree](#) which has a very similar API as the STL Tree class. It is an implementation of a Red-Black Tree for use by the [Oscl\\_Map](#) class. Memory allocation is abstracted through the use of an allocator template parameter.

### 8.125.2 Define Documentation

#### 8.125.2.1 #define OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE

## 8.126 oscl\_types.h File Reference

This file contains basic type definitions for common use across platforms.

```
#include "osclconfig.h"
```

### Data Structures

- struct [OsclMemoryFragment](#)

### Typedefs

- [typedef int c\\_bool](#)  
*The c\_bool type is mapped to an integer to provide a bool type for C interfaces.*
- [typedef void OsclAny](#)  
*The OsclAny is meant to be used the context of a generic pointer (i.e., no specific type).*
- [typedef char mbchar](#)  
*mbchar is multi-byte char (e.g., UTF-8) with null termination.*
- [typedef unsigned int uint](#)  
*The uint type is a convenient abbreviation for unsigned int.*
- [typedef uint8 octet](#)  
*The octet type is meant to be used for referring to a byte or collection bytes without suggesting anything about the underlying meaning of the bytes.*
- [typedef float OsclFloat](#)  
*The Float type defined as OsclFloat.*
- [typedef OSCL\\_NATIVE\\_INT64\\_TYPE int64](#)
- [typedef OSCL\\_NATIVE\\_UINT64\\_TYPE uint64](#)
- [typedef OSCL\\_NATIVE\\_WCHAR\\_TYPE oscl\\_wchar](#)
- [typedef oscl\\_wchar OSCL\\_TCHAR](#)  
*define OSCL\_TCHAR*

### 8.126.1 Detailed Description

This file contains basic type definitions for common use across platforms.

## 8.127 oscl\_udp\_socket.h File Reference

```
#include "oscl_ip_socket.h"
#include "oscl_defalloc.h"
#include "oscl_socket_recv_from.h"
#include "oscl_socket_send_to.h"
#include "oscl_socket_bind.h"
```

### Data Structures

- class [OsclUDPSocketI](#)

## 8.128 oscl\_utf8conv.h File Reference

Utilities to convert unicode to utf8 and vice versa.

```
#include "oscl_base.h"
```

### Defines

- #define MAX\_NUMBER\_OF\_BYTE\_PER\_UTF8 3

### Functions

- OSCL\_IMPORT\_REF int32 **oscl\_UTF8ToUnicode** (const char \*input, int32 inLength, oscl\_wchar \*output, int32 outLength)  
*Convert UTF8 byte sequence to Unicode string.*
- OSCL\_IMPORT\_REF int32 **oscl\_UnicodeToUTF8** (const oscl\_wchar \*input, int32 inLength, char \*output, int32 outLength)  
*Convert Unicode string to UTF8 byte sequence.*

### 8.128.1 Detailed Description

Utilities to convert unicode to utf8 and vice versa.

## 8.129 oscl\_uuid.h File Reference

This file defines the OSCL UUID structure used for unique identifiers as well as the short (32-bit) identifiers OsclUid32.

```
#include "oscl_base_macros.h"  
#include "oscl_mem_basic_functions.h"
```

### Data Structures

- struct [OsclUuid](#)

### Defines

- #define [EMPTY\\_UUID](#) PVUuid(0,0,0,0,0,0,0,0)
- #define [BYTES\\_IN\\_UUID\\_ARRAY](#) 8

### Typedefs

- typedef uint32 [OsclUid32](#)

#### 8.129.1 Detailed Description

This file defines the OSCL UUID structure used for unique identifiers as well as the short (32-bit) identifiers OsclUid32.

#### 8.129.2 Define Documentation

##### 8.129.2.1 #define [BYTES\\_IN\\_UUID\\_ARRAY](#) 8

##### 8.129.2.2 #define [EMPTY\\_UUID](#) PVUuid(0,0,0,0,0,0,0,0)

#### 8.129.3 Typedef Documentation

##### 8.129.3.1 typedef uint32 [OsclUid32](#)

## 8.130 oscl\_uuid\_utils.h File Reference

```
#include "oscl_string_utils.h"
#include "oscl_stdstring.h"
```

### Variables

- const char **PV\_CHAR\_CLOSE\_BRACKET** = ')
- const char **PV\_CHAR\_COMMA** = ','

#### 8.130.1 Detailed Description

#### 8.130.2 Variable Documentation

8.130.2.1 const char **PV\_CHAR\_CLOSE\_BRACKET** = ')

8.130.2.2 const char **PV\_CHAR\_COMMA** = ','

## 8.131 oscl\_vector.h File Reference

The file `oscl_vector.h` defines the template class `Oscl_Vector` which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.

```
#include "oscl_mem_basic_functions.h"
#include "oscl_assert.h"
#include "oscl_opaque_type.h"
#include "oscl_defalloc.h"
#include "oscl_base.h"
```

### Data Structures

- class `Oscl_Vector`
- class `Oscl_Vector_Base`

#### 8.131.1 Detailed Description

The file `oscl_vector.h` defines the template class `Oscl_Vector` which has a very similar API as the STL Vector class (it basically provides a subset of the STL functionality). Memory allocation is abstracted through the use of an allocator template parameter.

## 8.132 osclconfig.h File Reference

This file contains configuration information for the linux platform.

```
#include <dirent.h>
#include <dlsfcn.h>
#include "osclconfig_limits_typedefs.h"
#include "osclconfig_unix_android.h"
#include "osclconfig_ix86.h"
#include "osclconfig_check.h"
```

### Defines

- #define OSCL\_HAS\_ANDROID\_SUPPORT 1
- #define OSCL\_HAS\_ANDROID\_FILE\_IO\_SUPPORT 1
- #define OSCL\_EXPORT\_REF \_\_attribute\_\_ ((visibility("default")))
- #define OSCL\_IMPORT\_REF \_\_attribute\_\_ ((visibility("default"))))
- #define OSCL\_RELEASE\_BUILD 0
- #define PVLOGGER\_INST\_LEVEL 5
- #define OSCL\_UNSIGNED\_CONST(x) x##u
- #define OSCL\_NATIVE\_UINT64\_TYPE u\_int64\_t
- #define OSCL\_TEMPLATED\_DESTRUCTOR\_CALL(type, simple\_type) ~type ()
- #define \_\_TFS\_\_ <>
- #define OSCL\_HAS\_PRAGMA\_PACK 0
- #define OSCL\_HAS\_PACKED\_STRUCT 1
- #define OSCL\_PACKED\_VAR(x) x \_\_attribute\_\_((packed))
- #define OSCL\_PACKED\_STRUCT\_BEGIN
- #define OSCL\_PACKED\_STRUCT\_END \_\_attribute\_\_((packed))
- #define OSCL\_ASSERT\_ALWAYS 0

### 8.132.1 Detailed Description

This file contains configuration information for the linux platform.

## 8.132.2 Define Documentation

8.132.2.1 `#define __TFS__ <>`

8.132.2.2 `#define OSCL_EXPORT_REF __attribute__ ((visibility("default")))`

8.132.2.3 `#define OSCL_HAS_ANDROID_FILE_IO_SUPPORT 1`

8.132.2.4 `#define OSCL_HAS_ANDROID_SUPPORT 1`

8.132.2.5 `#define OSCL_HAS_PACKED_STRUCT 1`

8.132.2.6 `#define OSCL_IMPORT_REF __attribute__ ((visibility("default")))`

8.132.2.7 `#define OSCL_NATIVE_UINT64_TYPE u_int64_t`

8.132.2.8 `#define OSCL_PACKED_STRUCT_BEGIN`

8.132.2.9 `#define OSCL_PACKED_STRUCT_END __attribute__((packed))`

8.132.2.10 `#define OSCL_PACKED_VAR(x) x __attribute__((packed))`

8.132.2.11 `#define OSCL_RELEASE_BUILD 0`

8.132.2.12 `#define OSCL_TEMPLATED_DESTRUCTOR_CALL(type, simple_type) ~type()`

8.132.2.13 `#define OSCL_UNSIGNED_CONST(x) x##u`

8.132.2.14 `#define PVLOGGER_INST_LEVEL 5`

## 8.133 osclconfig\_ansi\_memory.h File Reference

This file contains common typedefs based on the ANSI C limits.h header.

```
#include <memory.h>
```

### Defines

- #define OSCL\_HAS\_ANSI\_MEMORY\_FUNCS 1

### Typedefs

- typedef size\_t oscl\_memsize\_t

#### 8.133.1 Detailed Description

This file contains common typedefs based on the ANSI C limits.h header.

This header file should work for any ANSI C compiler to determine the proper native C types to use for OSCL integer types.

#### 8.133.2 Define Documentation

8.133.2.1 #define OSCL\_HAS\_ANSI\_MEMORY\_FUNCS 1

#### 8.133.3 Typedef Documentation

8.133.3.1 typedef size\_t oscl\_memsize\_t

## 8.134 osclconfig\_check.h File Reference

### Typedefs

- `typedef int8 __int8__check__`
- `typedef uint8 __uint8__check__`
- `typedef int16 __int16__check__`
- `typedef uint16 __uint16__check__`
- `typedef int32 __int32__check__`
- `typedef uint32 __uint32__check__`

## 8.135 osclconfig\_compiler\_warnings.h File Reference

This file contains the ability to turn off/on compiler warnings.

### Defines

- #define OSCL\_FUNCTION\_PTR(x) (&x)

#### 8.135.1 Detailed Description

This file contains the ability to turn off/on compiler warnings.

#### 8.135.2 Define Documentation

##### 8.135.2.1 #define OSCL\_FUNCTION\_PTR(x) (&x)

## 8.136 osclconfig\_error.h File Reference

This file contains the common typedefs and header files needed to compile osclerror.

```
#include "osclconfig.h"  
#include <setjmp.h>  
#include <errno.h>  
#include "osclconfig_error_check.h"
```

### Defines

- #define OSCL\_HAS\_EXCEPTIONS 1
- #define OSCL\_HAS\_ERRNO\_H 1
- #define OSCL\_HAS\_SYMBIAN\_ERRORTRAP 0
- #define OSCL\_HAS\_SETJMP\_H 1

### 8.136.1 Detailed Description

This file contains the common typedefs and header files needed to compile osclerror.

### 8.136.2 Define Documentation

- 8.136.2.1 #define OSCL\_HAS\_ERRNO\_H 1
- 8.136.2.2 #define OSCL\_HAS\_EXCEPTIONS 1
- 8.136.2.3 #define OSCL\_HAS\_SETJMP\_H 1
- 8.136.2.4 #define OSCL\_HAS\_SYMBIAN\_ERRORTRAP 0

**8.137 osclconfig\_error\_check.h File Reference**

## 8.138 osclconfig\_global\_new\_delete.h File Reference

### Functions

- void \* **operator new** (size\_t)
- void **operator delete** (void \*)

## **8.139 osclconfig\_global\_placement\_new.h File Reference**

### **Functions**

- void \* [operator new](#) (size\_t, void \*ptr)

#### **8.139.1 Function Documentation**

##### **8.139.1.1 void\* operator new (size\_t, void \*ptr) [inline]**

## 8.140 osclconfig\_io.h File Reference

This file contains common typedefs based on the ANSI C limits.h header.

```
#include "osclconfig.h"

#include <stdio.h>
#include <stdlib.h>
#include <stdarg.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <fcntl.h>
#include <signal.h>
#include <netdb.h>
#include <sys/mman.h>
#include <sys/types.h>
#include <errno.h>
#include <sys/vfs.h>
#include <dirent.h>
#include <sys/stat.h>
#include "osclconfig_io_check.h"
```

### Defines

- #define OSCL\_HAS\_GLOB 0
- #define OSCL\_HAS\_ANSI\_FILE\_IO\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_64BIT\_FILE\_IO\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_FILE\_IO\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_COMPATIBLE\_IO\_FUNCTION 0
- #define OSCL\_HAS\_NATIVE\_FILE\_CACHE\_ENABLE 1
- #define OSCL\_FILE\_BUFFER\_MAX\_SIZE 32768
- #define OSCL\_HAS\_PV\_FILE\_CACHE 0
- #define OSCL\_HAS\_LARGE\_FILE\_SUPPORT 1
- #define OSCL\_HAS\_SYMBIAN\_SOCKET\_SERVER 0
- #define OSCL\_HAS\_SYMBIAN\_DNS\_SERVER 0
- #define OSCL\_HAS\_BERKELEY\_SOCKETS 1
- #define OSCL\_HAS\_SOCKET\_SUPPORT 1
- #define OsclValidInetAddr(addr) (inet\_addr(addr)!=INADDR\_NONE)
- #define OsclMakeSockAddr(sockaddr, port, addrstr, ok)
- #define OsclUnMakeSockAddr(sockaddr, addrstr) addrstr=inet\_ntoa(sockaddr.sin\_addr);
- #define OsclMakeInAddr(in\_addr, addrstr, ok)
- #define OsclUnMakeInAddr(in\_addr, addrstr) addrstr=inet\_ntoa(in\_addr);
- #define OsclSetRecvBufferSize(s, val, ok, err)
- #define OsclBind(s, addr, ok, err)

- #define **OsclSetSockOpt**(s, optLevel, optName, optVal, optLen, ok, err)
- #define **OsclJoin**(s, addr, ok, err)
- #define **OsclListen**(s, size, ok, err)
- #define **OsclAccept**(s, accept\_s, ok, err, wouldblock)
- #define **OsclSetNonBlocking**(s, ok, err)
- #define **OsclShutdown**(s, how, ok, err)
- #define **OsclSocket**(s, fam, type, prot, ok, err)
- #define **OsclSendTo**(s, buf, len, addr, ok, err, nbytes, wouldblock)
- #define **OsclSend**(s, buf, len, ok, err, nbytes, wouldblock)
- #define **OsclCloseSocket**(s, ok, err)
- #define **OsclConnect**(s, addr, ok, err, wouldblock)
- #define **OsclGetPeerName**(s, name, namelen, ok, err)
- #define **OsclGetAsyncSockErr**(s, ok, err)
- #define **OsclPipe**(x) pipe(x)
- #define **OsclReadFD**(fd, buf, cnt) read(fd,buf,cnt)
- #define **OsclWriteFD**(fd, buf, cnt) write(fd,buf,cnt)
- #define **OsclConnectComplete**(s, wset, eset, success, fail, ok, err)
- #define **OsclRecv**(s, buf, len, ok, err, nbytes, wouldblock)
- #define **OsclRecvFrom**(s, buf, len, paddr, paddrlen, ok, err, nbytes, wouldblock)
- #define **OsclSocketSelect**(nfds, rd, wr, ex, timeout, ok, err, nhandles)
- #define **OsclSocketStartup**(ok)
- #define **OsclSocketCleanup**(ok)
- #define **OsclGethostbyname**(name, hostent, ok, err)
- #define **OsclGetDottedAddr**(hostent, dottedaddr, ok)
- #define **OsclGetDottedAddrVector**(hostent, dottedaddr, dottedaddrvect, ok)
- #define **OSCL\_SD\_RECEIVE** SHUT\_RD
- #define **OSCL\_SD\_SEND** SHUT\_WR
- #define **OSCL\_SD\_BOTH** SHUT\_RDWR
- #define **OSCL\_AF\_INET** AF\_INET
- #define **OSCL SOCK\_STREAM** SOCK\_STREAM
- #define **OSCL SOCK\_DGRAM** SOCK\_DGRAM
- #define **OSCL IPPROTO\_IP** IPPROTO\_IP
- #define **OSCL IPPROTO\_TCP** IPPROTO\_TCP
- #define **OSCL IPPROTO\_UDP** IPPROTO\_UDP
- #define **OSCL SOL\_SOCKET** SOL\_SOCKET
- #define **OSCL SOL\_IP** IPPROTO\_IP
- #define **OSCL SOL\_TCP** IPPROTO\_TCP
- #define **OSCL SOL\_UDP** IPPROTO\_UDP
- #define **OSCL\_SOCKOPT\_IP\_MULTICAST\_TTL** IP\_MULTICAST\_TTL
- #define **OSCL\_SOCKOPT\_IP\_ADDMEMBERSHIP** IP\_ADD\_MEMBERSHIP
- #define **OSCL\_SOCKOPT\_IP\_TOS** IP\_TOS
- #define **OSCL\_SOCKOPT\_SOL\_REUSEADDR** SO\_REUSEADDR

## Typedefs

- typedef int **TOsclSocket**
- typedef sockaddr\_in **TOsclSockAddr**
- typedef socklen\_t **TOsclSockAddrLen**
- typedef ip\_mreq **TIpMReq**
- typedef hostent **TOsclHostent**
- typedef off64\_t **TOsclFileOffset**

### **8.140.1 Detailed Description**

This file contains common typedefs based on the ANSI C limits.h header.

This header file should work for any ANSI C compiler to determine the proper native C types to use for OSCL integer types.



## 8.140.2 Define Documentation

- 8.140.2.1 `#define OSCL_AF_INET AF_INET`
- 8.140.2.2 `#define OSCL_FILE_BUFFER_MAX_SIZE 32768`
- 8.140.2.3 `#define OSCL_HAS_ANSI_64BIT_FILE_IO_SUPPORT 0`
- 8.140.2.4 `#define OSCL_HAS_ANSI_FILE_IO_SUPPORT 1`
- 8.140.2.5 `#define OSCL_HAS_BERKELEY_SOCKETS 1`
- 8.140.2.6 `#define OSCL_HAS_GLOB 0`
- 8.140.2.7 `#define OSCL_HAS_LARGE_FILE_SUPPORT 1`
- 8.140.2.8 `#define OSCL_HAS_MSWIN_FILE_IO_SUPPORT 0`
- 8.140.2.9 `#define OSCL_HAS_NATIVE_FILE_CACHE_ENABLE 1`
- 8.140.2.10 `#define OSCL_HAS_PV_FILE_CACHE 0`
- 8.140.2.11 `#define OSCL_HAS_SOCKET_SUPPORT 1`
- 8.140.2.12 `#define OSCL_HAS_SYMBIAN_COMPATIBLE_IO_FUNCTION 0`
- 8.140.2.13 `#define OSCL_HAS_SYMBIAN_DNS_SERVER 0`
- 8.140.2.14 `#define OSCL_HAS_SYMBIAN_SOCKET_SERVER 0`
- 8.140.2.15 `#define OSCL IPPROTO_IP IPPROTO_IP`
- 8.140.2.16 `#define OSCL IPPROTO_TCP IPPROTO_TCP`
- 8.140.2.17 `#define OSCL IPPROTO_UDP IPPROTO_UDP`
- 8.140.2.18 `#define OSCL_SD_BOTH SHUT_RDWR`
- 8.140.2.19 `#define OSCL_SD_RECEIVE SHUT_RD`
- 8.140.2.20 `#define OSCL_SD_SEND SHUT_WR`
- 8.140.2.21 `#define OSCL SOCK_DGRAM SOCK_DGRAM`
- 8.140.2.22 `#define OSCL SOCK_STREAM SOCK_STREAM`
- 8.140.2.23 `#define OSCL_SOCKOPT_IP_ADDMEMBERSHIP IP_ADD_MEMBERSHIP`
- 8.140.2.24 `#define OSCL_SOCKOPT_IP_MULTICAST_TTL IP_MULTICAST_TTL`
- 8.140.2.25 `#define OSCL_SOCKOPT_IP_TOS IP_TOS`
- 8.140.2.26 `#define OSCL_SOCKOPT_SOL_REUSEADDR SO_REUSEADDR`
- 8.140.2.27 `#define OSCL_SOL_IP IPPROTO_IP`

```
accept_s=accept(s,NULL,NULL);\
ok=(accept_s!=(-1));\
if (!ok){err=errno;wouldblock=(err==EAGAIN)|err==EWOULDBLOCK);}
```

#### 8.140.2.32 #define OsclBind(s, addr, ok, err)

**Value:**

```
TOsclSockAddr* tmpadr = &addr;\
sockaddr* sadr = OSCL_STATIC_CAST(sockaddr*, tmpadr);\
ok=(bind(s,sadr,sizeof(addr))!=(-1));\
if (!ok)err=errno
```

#### 8.140.2.33 #define OsclCloseSocket(s, ok, err)

**Value:**

```
ok=(close(s)!=(-1));\
if (!ok)err=errno
```

#### 8.140.2.34 #define OsclConnect(s, addr, ok, err, wouldblock)

**Value:**

```
TOsclSockAddr* tmpadr = &addr;\
sockaddr* sadr = OSCL_STATIC_CAST(sockaddr*, tmpadr);\
ok=(connect(s,sadr,sizeof(addr))!=(-1));\
if (!ok){err=errno;wouldblock=(err==EINPROGRESS);}
```

#### 8.140.2.35 #define OsclConnectComplete(s, wset, eset, success, fail, ok, err)

**Value:**

```
success=fail=false;\
if (FD_ISSET(s,&eset))\
{fail=true;OsclGetAsyncSockErr(s,ok,err);}\\
else if (FD_ISSET(s,&wset))\
{OsclGetAsyncSockErr(s,ok,err);if (ok && err==0)success=true;else fail=true;}
```

#### 8.140.2.36 #define OsclGetAsyncSockErr(s, ok, err)

**Value:**

```
int opterr;socklen_t optlen(sizeof(opterr));\
ok=(getsockopt(s,SOL_SOCKET,SO_ERROR,(void *)&opterr,&optlen)!=(-1));\
if(ok)err=opterr;else err=errno;
```

**8.140.2.37 #define OsclGetDottedAddr(hostent, dottedaddr, ok)**
**Value:**

```
long *_hostaddr=(long*)hostent->h_addr_list[0];\
  struct in_addr _inaddr;\
  _inaddr.s_addr=*_hostaddr;\
  dottedaddr/inet_ntoa(_inaddr);\
  ok=(dottedaddr!=NULL);
```

**8.140.2.38 #define OsclGetDottedAddrVector(hostent, dottedaddr, dottedaddrvect, ok)**
**Value:**

```
if(dottedaddrvect)\
{\\
  long **_addrlist=(long**)hostent->h_addr_list;\
  for(int i = 0; _addrlist[i] != NULL; i++){\\
    struct in_addr _inaddr;\
    _inaddr.s_addr=_addrlist[i];\
    OsclNetworkAddress addr(inet_ntoa(_inaddr), 0);\
    dottedaddrvect->push_back(addr);\
  }\\
  if (!dottedaddrvect->empty())\
    {dottedaddr->port = dottedaddrvect->front().port; dottedaddr->ipAddr.Set(dottedaddrvect->front().ipAd\
ok=(!dottedaddrvect->empty() && ((*dottedaddrvect)[0]).ipAddr.Str() != NULL));\
}\\
else\
{\
  char *add;\
  OsclGetDottedAddr(hostent,add,ok);\
  if(ok) dottedaddr->ipAddr.Set(add);\
}
```

**8.140.2.39 #define OsclGethostbyname(name, hostent, ok, err)**
**Value:**

```
hostent=gethostbyname((const char*)name);\
  ok=(hostent!=NULL);\
  if (!ok)err=errno;
```

**8.140.2.40 #define OsclGetPeerName(s, name, namelen, ok, err)**
**Value:**

```
ok=(getpeername(s,(sockaddr*)&name,(socklen_t*)&namelen) != (-1) );\
  if (!ok)err=errno
```

**8.140.2.41 #define OsclJoin(s, addr, ok, err)**
**Value:**

```
{
    struct ip_mreq mreq; \
    void* p = &addr; \
    ok=(bind(s,(sockaddr*)p,sizeof(addr))!=(-1));\
    mreq.imr_multiaddr.s_addr = addr.sin_addr.s_addr ; \
    mreq.imr_interface.s_addr = htonl(INADDR_ANY); \
    ok=(setsockopt(s, IPPROTO_IP, IP_ADD_MEMBERSHIP, &mreq, sizeof(struct ip_mreq))!=(-1)); \
    if (!ok)err=errno; \
}
```

#### 8.140.2.42 #define OsclListen(s, size, ok, err)

**Value:**

```
ok=(listen(iSocket,qSize)!=(-1));\
if (!ok)err=errno
```

#### 8.140.2.43 #define OsclMakeInAddr(in\_addr, addrstr, ok)

**Value:**

```
int32 result = inet_aton((const char*)addrstr, &in_addr);\
ok=(result!=0);
```

#### 8.140.2.44 #define OsclMakeSockAddr(sockaddr, port, addrstr, ok)

**Value:**

```
sockaddr.sin_family=OSCL_AF_INET; \
sockaddr.sin_port=htons(port); \
int32 result=inet_aton((const char*)addrstr,&sockaddr.sin_addr); \
ok=(result!=0);
```

#### 8.140.2.45 #define OsclPipe(x) pipe(x)

#### 8.140.2.46 #define OsclReadFD(fd, buf, cnt) read(fd,buf,cnt)

#### 8.140.2.47 #define OsclRecv(s, buf, len, ok, err, nbytes, wouldblock)

**Value:**

```
nbytes=recv(s,(void *)buf),(size_t)(len),0); \
ok=(nbytes!=(-1)); \
if (!ok){err=errno;wouldblock=(err==EAGAIN);}
```

**8.140.2.48 #define OsclRecvFrom(s, buf, len, paddr, paddrlen, ok, err, nbytes, wouldblock)**
**Value:**

```
\nvoid* p=paddr;\n\nbytes=recvfrom(s,(void*)(buf),(size_t)(len),0,(struct sockaddr*)p,paddrlen);\n  ok=(nbytes!=(-1));\n  if (!ok){err=errno;wouldblock=(err==EAGAIN);}\n}
```

**8.140.2.49 #define OsclSend(s, buf, len, ok, err, nbytes, wouldblock)**
**Value:**

```
nbytes=send(s,(const void*)(buf),(size_t)(len),0);\n  ok=(nbytes!=(-1));\n  if (!ok){err=errno;wouldblock=(err==EAGAIN||err==EWOULDBLOCK);}
```

**8.140.2.50 #define OsclSendTo(s, buf, len, addr, ok, err, nbytes, wouldblock)**
**Value:**

```
TOsclSockAddr* tmpadr = &addr;\nsockaddr* sadr = OSCL_STATIC_CAST(sockaddr*, tmpadr);\nnbytes=sendto(s,(const void*)(buf),(size_t)(len),0,sadr,(socklen_t)sizeof(addr));\n  ok=(nbytes!=(-1));\n  if (!ok){err=errno;wouldblock=(err==EAGAIN||err==EWOULDBLOCK);}
```

**8.140.2.51 #define OsclSetNonBlocking(s, ok, err)**
**Value:**

```
ok=(fcntl(s,F_SETFL,O_NONBLOCK)!=(-1));\n  if (!ok)err=errno
```

**8.140.2.52 #define OsclSetRecvBufferSize(s, val, ok, err)**
**Value:**

```
ok=(setsockopt(s,SOL_SOCKET,SO_RCVBUF,(char*)&val, sizeof(int)) != -1);\n  if (!ok)err=errno
```

**8.140.2.53 #define OsclSetSockOpt(s, optLevel, optName, optVal, optLen, ok, err)**
**Value:**

```
ok=(setsockopt(s,optLevel,optName,OSCL_STATIC_CAST(const char*,optVal),optLen) != (-1));\n  if (!ok)err=errno
```

**8.140.2.54 #define OsclShutdown(s, how, ok, err)****Value:**

```
ok=(shutdown(iSocket,how)!=(-1));\
if (!ok)err=errno
```

**8.140.2.55 #define OsclSocket(s, fam, type, prot, ok, err)****Value:**

```
s=socket(fam,type,prot);\
ok=(s!=(-1));\
if (!ok)err=errno
```

**8.140.2.56 #define OsclSocketCleanup(ok)****Value:**

```
signal(SIGPIPE,SIG_DFL);\
ok=true
```

**8.140.2.57 #define OsclSocketSelect(nfds, rd, wr, ex, timeout, ok, err, nhandles)****Value:**

```
nhandles=select(nfds,&rd,&wr,&ex,&timeout);\
ok=(nhandles!=-1);\
if (!ok)err=errno
```

**8.140.2.58 #define OsclSocketStartup(ok)****Value:**

```
signal(SIGPIPE,SIG_IGN);\
ok=true
```

**8.140.2.59** #define OsclUnMakeInAddr(in\_addr, addrstr) addrstr=inet\_ntoa(in\_addr);

**8.140.2.60** #define OsclUnMakeSockAddr(sockaddr, addrstr) addrstr=inet\_ntoa(sockaddr.sin\_addr);

**8.140.2.61** #define OsclValidInetAddr(addr) (inet\_addr(addr)!=INADDR\_NONE)

**8.140.2.62** #define OsclWriteFD(fd, buf, cnt) write(fd,buf,cnt)

### **8.140.3 Typedef Documentation**

**8.140.3.1** typedef struct ip\_mreq TIpMReq

**8.140.3.2** typedef off64\_t TOsclFileOffset

**8.140.3.3** typedef struct hostent TOsclHostent

**8.140.3.4** typedef struct sockaddr\_in TOsclSockAddr

**8.140.3.5** typedef socklen\_t TOsclSockAddrLen

**8.140.3.6** typedef int TOsclSocket

## 8.141 osclconfig\_io\_check.h File Reference

### Typedefs

- `typedef TOsclFileOffset __verify__TOsclFileOffset__defined__`

#### 8.141.1 Typedef Documentation

##### 8.141.1.1 `typedef TOsclFileOffset __verify__TOsclFileOffset__defined__`

type `TOsclFileOffset` should be defined as the type used for file size and offsets on the target platform.  
Example: `typedef size_t TOsclFileOffset;`

## **8.142 osclconfig\_ix86.h File Reference**

This file contains configuration information for the ix86 processor family.

### **Defines**

- #define OSCL\_INTEGERS\_WORD\_ALIGNED 1
- #define OSCL\_BYTE\_ORDER\_BIG\_ENDIAN 0
- #define OSCL\_BYTE\_ORDER\_LITTLE\_ENDIAN 1

### **8.142.1 Detailed Description**

This file contains configuration information for the ix86 processor family.

## **8.143 osclconfig\_lib.h File Reference**

This file contains configuration information for the ANSI build.

```
#include "osclconfig_lib_check.h"
```

### **Defines**

- #define OSCL\_HAS\_RUNTIME\_LIB\_LOADING\_SUPPORT 1
- #define PV\_RUNTIME\_LIB\_FILENAME\_EXTENSION "so"
- #define OSCL\_LIB\_READ\_DEBUG\_LIBS 1
- #define PV\_DYNAMIC\_LOADING\_CONFIG\_FILE\_PATH "./"

### **8.143.1 Detailed Description**

This file contains configuration information for the ANSI build.

### **8.143.2 Define Documentation**

**8.143.2.1 #define OSCL\_HAS\_RUNTIME\_LIB\_LOADING\_SUPPORT 1**

**8.143.2.2 #define OSCL\_LIB\_READ\_DEBUG\_LIBS 1**

**8.143.2.3 #define PV\_DYNAMIC\_LOADING\_CONFIG\_FILE\_PATH "./"**

**8.143.2.4 #define PV\_RUNTIME\_LIB\_FILENAME\_EXTENSION "so"**

**8.144 osclconfig\_lib\_check.h File Reference**

## **8.145 osclconfig\_limits\_typedefs.h File Reference**

This file contains common typedefs based on the ANSI C limits.h header.

```
#include <limits.h>
```

### **Defines**

- #define OSCL\_CHAR\_IS\_UNSIGNED 1
- #define OSCL\_CHAR\_IS\_SIGNED 0

### **8.145.1 Detailed Description**

This file contains common typedefs based on the ANSI C limits.h header.

This header file should work for any ANSI C compiler to determine the proper native C types to use for OSCL integer types.

### **8.145.2 Define Documentation**

**8.145.2.1 #define OSCL\_CHAR\_IS\_SIGNED 0**

**8.145.2.2 #define OSCL\_CHAR\_IS\_UNSIGNED 1**

## 8.146 osclconfig\_memory.h File Reference

```
#include "osclconfig.h"
#include "osclconfig_ansi_memory.h"
#include "osclconfig_memory_check.h"
```

### Defines

- #define OSCL\_BYPASS\_MEMMGT 1
- #define OSCL\_HAS\_GLOBAL\_NEW\_DELETE 1
- #define PVMEM\_INST\_LEVEL 1
- #define OSCL\_HAS\_HEAP\_BASE\_SUPPORT 1
- #define OSCL\_HAS\_SYMBIAN\_MEMORY\_FUNCS 0

### 8.146.1 Define Documentation

**8.146.1.1 #define OSCL\_BYPASS\_MEMMGT 1**

**8.146.1.2 #define OSCL\_HAS\_GLOBAL\_NEW\_DELETE 1**

**8.146.1.3 #define OSCL\_HAS\_HEAP\_BASE\_SUPPORT 1**

**8.146.1.4 #define OSCL\_HAS\_SYMBIAN\_MEMORY\_FUNCS 0**

**8.146.1.5 #define PVMEM\_INST\_LEVEL 1**

## **8.147 osclconfig\_memory\_check.h File Reference**

## 8.148 osclconfig\_no\_os.h File Reference

### Defines

- #define OSCL\_HAS\_UNIX\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_PARTIAL\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_SUPPORT 0
- #define OSCL\_HAS\_SAVAJE\_SUPPORT 0
- #define OSCL\_HAS\_PV\_C\_OS\_SUPPORT 0
- #define OSCL\_HAS\_ANDROID\_SUPPORT 0
- #define OSCL\_HAS\_IPHONE\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_ERRORTRAP 0
- #define OSCL\_HAS\_SYMBIAN\_MEMORY\_FUNCS 0
- #define OSCL\_HAS\_PV\_C\_OS\_API\_MEMORY\_FUNCS 0
- #define OSCL\_HAS\_PV\_C\_OS\_TIME\_FUNCS 0
- #define OSCL\_HAS\_UNIX\_TIME\_FUNCS 0
- #define OSCL\_HAS\_SYMBIAN\_TIMERS 0
- #define OSCL\_HAS\_SYMBIAN\_MATH 0
- #define OSCL\_HAS\_SYMBIAN\_SCHEDULER 0
- #define OSCL\_HAS\_SEM\_TIMEDWAIT\_SUPPORT 0
- #define OSCL\_HAS\_PTHREAD\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_COMPATIBLE\_IO\_FUNCTION 0
- #define OSCL\_HAS\_SAVAJE\_IO\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_SOCKET\_SERVER 0
- #define OSCL\_HAS\_SYMBIAN\_DNS\_SERVER 0
- #define OSCL\_HAS\_BERKELEY\_SOCKETS 0

## **8.149 osclconfig\_proc.h File Reference**

This file contains configuration information for the linux platform.

```
#include "osclconfig.h"  
#include "osclconfig_proc_unix_android.h"  
#include "osclconfig_proc_check.h"
```

### **8.149.1 Detailed Description**

This file contains configuration information for the linux platform.

## 8.150 osclconfig\_proc\_check.h File Reference

### Typedefs

- `typedef TOsclThreadId __verify__TOsclThreadId_defined__`
- `typedef TOsclThreadFuncRet __verify__TOsclThreadFuncRet_defined__`
- `typedef TOsclThreadFuncArg __verify__TOsclThreadFuncArg_defined__`
- `typedef TOsclThreadObject __verify__TOsclThreadObject_defined__`
- `typedef TOsclMutexObject __verify__TOsclMutexObject_defined__`
- `typedef TOsclSemaphoreObject __verify__TOsclSemaphoreObject_defined__`
- `typedef TOsclConditionObject __verify__TOsclConditionObject_defined__`

#### 8.150.1 Typedef Documentation

##### 8.150.1.1 `typedef TOsclConditionObject __verify__TOsclConditionObject_defined__`

type `TOsclConditionObject` should be defined as the type used as a condition variable on the target platform.  
Example: `typedef pthread_cond_t TOsclConditionObject;`

Note: Condition variables are only used with certain semaphore implementations. If the semaphore implementation does not require a condition variable, then this type can be defined as 'int' as follows: `typedef int TOsclConditionObject; //not used`

##### 8.150.1.2 `typedef TOsclMutexObject __verify__TOsclMutexObject_defined__`

type `TOsclMutexObject` should be defined as the type used as a mutex object or handle on the target platform. Example: `typedef pthread_mutex_t TOsclMutexObject;`

##### 8.150.1.3 `typedef TOsclSemaphoreObject __verify__TOsclSemaphoreObject_defined__`

type `TOsclSemaphoreObject` should be defined as the type used as a mutex object or handle on the target platform. Example: `typedef sem_t TOsclSemaphoreObject;`

##### 8.150.1.4 `typedef TOsclThreadFuncArg __verify__TOsclThreadFuncArg_defined__`

type `TOsclThreadFuncArg` should be defined as the type used as a thread function argument on the target platform. Example: `typedef LPVOID TOsclThreadFuncArg;`

##### 8.150.1.5 `typedef TOsclThreadFuncRet __verify__TOsclThreadFuncRet_defined__`

type `TOsclThreadFuncRet` should be defined as the type used as a thread function return value on the target platform. Example: `typedef DWORD TOsclThreadFuncRet;`

##### 8.150.1.6 `typedef TOsclThreadId __verify__TOsclThreadId_defined__`

type `TOsclThreadId` should be defined as the type used as a thread ID on the target platform. Example: `typedef DWORD TOsclThreadId;`

**8.150.1.7 `typedef TOsclThreadObject __verify__TOsclThreadObject_defined__`**

type TOsclThreadObject should be defined as the type used as a thread object or handle on the target platform. Example: `typedef pthread_t TOsclThreadObject;`

## 8.151 osclconfig\_proc\_unix\_android.h File Reference

```
#include <pthread.h>
#include <errno.h>
#include <signal.h>
```

### Defines

- #define OSCL\_HAS\_SYMBIAN\_SCHEDULER 0
- #define OSCL\_HAS\_THREAD\_SUPPORT 1
- #define OSCL\_HAS\_NON\_PREEMPTIVE\_THREAD\_SUPPORT 0
- #define OSCL\_HAS\_SEM\_TIMEDWAIT\_SUPPORT 0
- #define OSCL\_HAS\_PTHREAD\_SUPPORT 1
- #define OSCL\_THREAD\_DECL

### TypeDefs

- typedef pthread\_t TOsclThreadId
- typedef void \* TOsclThreadFuncArg
- typedef void \* TOsclThreadFuncRet
- typedef pthread\_t TOsclThreadObject
- typedef pthread\_mutex\_t TOsclMutexObject
- typedef int TOsclSemaphoreObject
- typedef pthread\_cond\_t TOsclConditionObject

### 8.151.1 Define Documentation

- 8.151.1.1 `#define OSCL_HAS_NON_PREEMPTIVE_THREAD_SUPPORT 0`
- 8.151.1.2 `#define OSCL_HAS_PTHREAD_SUPPORT 1`
- 8.151.1.3 `#define OSCL_HAS_SEM_TIMEDWAIT_SUPPORT 0`
- 8.151.1.4 `#define OSCL_HAS_SYMBIAN_SCHEDULER 0`
- 8.151.1.5 `#define OSCL_HAS_THREAD_SUPPORT 1`
- 8.151.1.6 `#define OSCL_THREAD_DECL`

### 8.151.2 Typedef Documentation

- 8.151.2.1 `typedef pthread_cond_t TOsclConditionObject`
- 8.151.2.2 `typedef pthread_mutex_t TOsclMutexObject`
- 8.151.2.3 `typedef int TOsclSemaphoreObject`
- 8.151.2.4 `typedef void* TOsclThreadFuncArg`
- 8.151.2.5 `typedef void* TOsclThreadFuncRet`
- 8.151.2.6 `typedef pthread_t TOsclThreadId`
- 8.151.2.7 `typedef pthread_t TOsclThreadObject`

## 8.152 osclconfig\_proc\_unix\_common.h File Reference

```
#include <time.h>
#include <semaphore.h>
#include <pthread.h>
#include <errno.h>
```

### Defines

- #define OSCL\_HAS\_SYMBIAN\_SCHEDULER 0
- #define OSCL\_HAS\_THREAD\_SUPPORT 1
- #define OSCL\_HAS\_NON\_PREEMPTIVE\_THREAD\_SUPPORT 0
- #define OSCL\_HAS\_SEM\_TIMEDWAIT\_SUPPORT 1
- #define OSCL\_HAS\_PTHREAD\_SUPPORT 1
- #define OSCL\_THREAD\_DECL

### Typedefs

- typedef pthread\_t TOsclThreadId
- typedef void \* TOsclThreadFuncArg
- typedef void \* TOsclThreadFuncRet
- typedef pthread\_t TOsclThreadObject
- typedef pthread\_mutex\_t TOsclMutexObject
- typedef sem\_t TOsclSemaphoreObject
- typedef pthread\_cond\_t TOsclConditionObject

### 8.152.1 Define Documentation

- 8.152.1.1 `#define OSCL_HAS_NON_PREEMPTIVE_THREAD_SUPPORT 0`
- 8.152.1.2 `#define OSCL_HAS_PTHREAD_SUPPORT 1`
- 8.152.1.3 `#define OSCL_HAS_SEM_TIMEDWAIT_SUPPORT 1`
- 8.152.1.4 `#define OSCL_HAS_SYMBIAN_SCHEDULER 0`
- 8.152.1.5 `#define OSCL_HAS_THREAD_SUPPORT 1`
- 8.152.1.6 `#define OSCL_THREAD_DECL`

### 8.152.2 Typedef Documentation

- 8.152.2.1 `typedef pthread_cond_t TOsclConditionObject`
- 8.152.2.2 `typedef pthread_mutex_t TOsclMutexObject`
- 8.152.2.3 `typedef sem_t TOsclSemaphoreObject`
- 8.152.2.4 `typedef void* TOsclThreadFuncArg`
- 8.152.2.5 `typedef void* TOsclThreadFuncRet`
- 8.152.2.6 `typedef pthread_t TOsclThreadId`
- 8.152.2.7 `typedef pthread_t TOsclThreadObject`

## 8.153 osclconfig\_time.h File Reference

```
#include "osclconfig.h"
#include <time.h>
#include <sys/time.h>
#include <unistd.h>
#include "osclconfig_time_check.h"
```

### Defines

- #define OSCL\_HAS\_UNIX\_TIME\_FUNCS 1

### TypeDefs

- typedef timeval OsclBasicTimeStruct
- typedef tm OsclBasicDateTimeStruct

#### 8.153.1 Define Documentation

##### 8.153.1.1 #define OSCL\_HAS\_UNIX\_TIME\_FUNCS 1

#### 8.153.2 TypeDef Documentation

##### 8.153.2.1 typedef tm OsclBasicDateTimeStruct

##### 8.153.2.2 typedef struct timeval OsclBasicTimeStruct

## 8.154 osclconfig\_time\_check.h File Reference

### Typedefs

- `typedef OsclBasicTimeStruct __Validate__BasicTimeStruct__`
- `typedef OsclBasicDateTimeStruct __Validate__BasicTimeDateStruct__`

#### 8.154.1 Typedef Documentation

##### 8.154.1.1 `typedef OsclBasicDateTimeStruct __Validate__BasicTimeDateStruct__`

`OsclBasicDateTimeStruct` type should be defined to the platform-specific date + time type.

##### 8.154.1.2 `typedef OsclBasicTimeStruct __Validate__BasicTimeStruct__`

`OsclBasicTimeStruct` type should be defined to the platform-specific time of day type.

## 8.155 osclconfig\_unix\_android.h File Reference

```
#include <stdlib.h>
#include <stdarg.h>
#include <sys/types.h>
#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <pthread.h>
#include <ctype.h>
#include <math.h>
```

### Defines

- #define OSCL\_DISABLE\_INLINES 0
- #define OSCL\_HAS\_ANSI\_STDLIB\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_MATH\_SUPPORT 1
- #define OSCL\_HAS\_GLOBAL\_VARIABLE\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_STRING\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_WIDE\_STRING\_SUPPORT 0
- #define OSCL\_HAS\_ANSI\_STDIO\_SUPPORT 1
- #define OSCL\_MEMFRAG\_PTR\_BEFORE\_LEN 1
- #define OSCL\_HAS\_UNIX\_SUPPORT 1
- #define OSCL\_HAS\_MSWIN\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_PARTIAL\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_SUPPORT 0
- #define OSCL\_HAS\_IPHONE\_SUPPORT 0
- #define OSCL\_NATIVE\_INT64\_TYPE int64\_t
- #define OSCL\_NATIVE\_UINT64\_TYPE uint64\_t
- #define INT64(x) x##LL
- #define UINT64(x) x##ULL
- #define INT64\_HILO(high, low) (((high##LL))<<32)|low)
- #define UINT64\_HILO(high, low) (((high##ULL))<<32)|low)
- #define OSCL\_HAS\_UNICODE\_SUPPORT 1
- #define OSCL\_NATIVE\_WCHAR\_TYPE wchar\_t
- #define \_STRLIT(x) L ## x
- #define \_STRLIT\_CHAR(x) x
- #define \_STRLIT\_WCHAR(x) L ## x
- #define OSCL\_HAS\_TLS\_SUPPORT 1
- #define OSCL\_TLS\_IS\_KEYED 1
- #define OSCL\_TLS\_KEY\_CREATE\_FUNC(key) (pthread\_key\_create(&key,NULL)==0)
- #define OSCL\_TLS\_KEY\_DELETE\_FUNC(key) pthread\_key\_delete(key)
- #define OSCL\_TLS\_STORE\_FUNC(key, ptr) (pthread\_setspecific(key,(const void\*)ptr)==0)
- #define OSCL\_TLS\_GET\_FUNC(key) pthread\_getspecific(key)
- #define OSCL\_HAS\_BASIC\_LOCK 1

## Typedefs

- `typedef pthread_key_t TOsclTlsKey`
- `typedef pthread_mutex_t TOsclBasicLockObject`



### 8.155.1 Define Documentation

8.155.1.1 `#define _STRLIT(x) L ## x`

8.155.1.2 `#define _STRLIT_CHAR(x) x`

8.155.1.3 `#define _STRLIT_WCHAR(x) L ## x`

8.155.1.4 `#define INT64(x) x##LL`

8.155.1.5 `#define INT64_HILO(high, low) (((high##LL))<<32)|low)`

8.155.1.6 `#define OSCL_DISABLE_INLINES 0`

8.155.1.7 `#define OSCL_HAS_ANSI_MATH_SUPPORT 1`

8.155.1.8 `#define OSCL_HAS_ANSI_STDIO_SUPPORT 1`

8.155.1.9 `#define OSCL_HAS_ANSI_STDLIB_SUPPORT 1`

8.155.1.10 `#define OSCL_HAS_ANSI_STRING_SUPPORT 1`

8.155.1.11 `#define OSCL_HAS_ANSI_WIDE_STRING_SUPPORT 0`

8.155.1.12 `#define OSCL_HAS_BASIC_LOCK 1`

8.155.1.13 `#define OSCL_HAS_GLOBAL_VARIABLE_SUPPORT 1`

8.155.1.14 `#define OSCL_HAS_IPHONE_SUPPORT 0`

8.155.1.15 `#define OSCL_HAS_MSWIN_PARTIAL_SUPPORT 0`

8.155.1.16 `#define OSCL_HAS_MSWIN_SUPPORT 0`

8.155.1.17 `#define OSCL_HAS_SYMBIAN_SUPPORT 0`

8.155.1.18 `#define OSCL_HAS_TLS_SUPPORT 1`

8.155.1.19 `#define OSCL_HAS_UNICODE_SUPPORT 1`

8.155.1.20 `#define OSCL_HAS_UNIX_SUPPORT 1`

8.155.1.21 `#define OSCL_MEMFRAG_PTR_BEFORE_LEN 1`

8.155.1.22 `#define OSCL_NATIVE_INT64_TYPE int64_t`

8.155.1.23 `#define OSCL_NATIVE_UINT64_TYPE uint64_t`

8.155.1.24 `#define OSCL_NATIVE_WCHAR_TYPE wchar_t`

8.155.1.25 `#define OSCL_TLS_GET_FUNC(key) pthread_getspecific(key)`

8.155.1.26 `#define OSCL_TLS_IS_KEYED 1`

8.155.1.27 `#define OSCL_TLS_KEY_CREATE_FUNC(key) (pthread_key_create(&key,NULL)==0)`

## 8.156 osclconfig\_unix\_common.h File Reference

```
#include <stdlib.h>
#include <stdarg.h>
#include <sys/types.h>
#include <stdio.h>
#include <wchar.h>
#include <string.h>
#include <unistd.h>
#include <pthread.h>
#include <ctype.h>
#include <math.h>
```

### Defines

- #define OSCL\_DISABLE\_INLINES 0
- #define OSCL\_HAS\_ANSI\_STDLIB\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_MATH\_SUPPORT 1
- #define OSCL\_HAS\_GLOBAL\_VARIABLE\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_STRING\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_WIDE\_STRING\_SUPPORT 1
- #define OSCL\_HAS\_ANSI\_STDIO\_SUPPORT 1
- #define OSCL\_MEMFRAG\_PTR\_BEFORE\_LEN 1
- #define OSCL\_HAS\_UNIX\_SUPPORT 1
- #define OSCL\_HAS\_MSWIN\_SUPPORT 0
- #define OSCL\_HAS\_MSWIN\_PARTIAL\_SUPPORT 0
- #define OSCL\_HAS\_SYMBIAN\_SUPPORT 0
- #define OSCL\_NATIVE\_INT64\_TYPE int64\_t
- #define OSCL\_NATIVE\_UINT64\_TYPE uint64\_t
- #define INT64(x) x##LL
- #define UINT64(x) x##ULL
- #define INT64\_HILO(high, low) (((high##LL))<<32)|low)
- #define UINT64\_HILO(high, low) (((high##ULL))<<32)|low)
- #define OSCL\_HAS\_UNICODE\_SUPPORT 1
- #define OSCL\_NATIVE\_WCHAR\_TYPE wchar\_t
- #define \_STRLIT(x) L ## x
- #define \_STRLIT\_CHAR(x) x
- #define \_STRLIT\_WCHAR(x) L ## x
- #define OSCL\_HAS\_TLS\_SUPPORT 1
- #define OSCL\_TLS\_IS\_KEYED 1
- #define OSCL\_TLS\_KEY\_CREATE\_FUNC(key) (pthread\_key\_create(&key,NULL)==0)
- #define OSCL\_TLS\_KEY\_DELETE\_FUNC(key) pthread\_key\_delete(key)
- #define OSCL\_TLS\_STORE\_FUNC(key, ptr) (pthread\_setspecific(key,(const void\*)ptr)==0)
- #define OSCL\_TLS\_GET\_FUNC(key) pthread\_getspecific(key)
- #define OSCL\_HAS\_BASIC\_LOCK 1

## Typedefs

- `typedef pthread_key_t TOsclTlsKey`
- `typedef pthread_mutex_t TOsclBasicLockObject`



### 8.156.1 Define Documentation

- 8.156.1.1 `#define _STRLIT(x) L ## x`
- 8.156.1.2 `#define _STRLIT_CHAR(x) x`
- 8.156.1.3 `#define _STRLIT_WCHAR(x) L ## x`
- 8.156.1.4 `#define INT64(x) x##LL`
- 8.156.1.5 `#define INT64_HILO(high, low) (((high##LL))<<32)|low)`
- 8.156.1.6 `#define OSCL_DISABLE_INLINES 0`
- 8.156.1.7 `#define OSCL_HAS_ANSI_MATH_SUPPORT 1`
- 8.156.1.8 `#define OSCL_HAS_ANSI_STDIO_SUPPORT 1`
- 8.156.1.9 `#define OSCL_HAS_ANSI_STDLIB_SUPPORT 1`
- 8.156.1.10 `#define OSCL_HAS_ANSI_STRING_SUPPORT 1`
- 8.156.1.11 `#define OSCL_HAS_ANSI_WIDE_STRING_SUPPORT 1`
- 8.156.1.12 `#define OSCL_HAS_BASIC_LOCK 1`
- 8.156.1.13 `#define OSCL_HAS_GLOBAL_VARIABLE_SUPPORT 1`
- 8.156.1.14 `#define OSCL_HAS_MSWIN_PARTIAL_SUPPORT 0`
- 8.156.1.15 `#define OSCL_HAS_MSWIN_SUPPORT 0`
- 8.156.1.16 `#define OSCL_HAS_SYMBIAN_SUPPORT 0`
- 8.156.1.17 `#define OSCL_HAS_TLS_SUPPORT 1`
- 8.156.1.18 `#define OSCL_HAS_UNICODE_SUPPORT 1`
- 8.156.1.19 `#define OSCL_HAS_UNIX_SUPPORT 1`
- 8.156.1.20 `#define OSCL_MEMFRAG_PTR_BEFORE_LEN 1`
- 8.156.1.21 `#define OSCL_NATIVE_INT64_TYPE int64_t`
- 8.156.1.22 `#define OSCL_NATIVE_UINT64_TYPE uint64_t`
- 8.156.1.23 `#define OSCL_NATIVE_WCHAR_TYPE wchar_t`
- 8.156.1.24 `#define OSCL_TLS_GET_FUNC(key) pthread_getspecific(key)`
- 8.156.1.25 `#define OSCL_TLS_IS_KEYED 1`
- 8.156.1.26 `#define OSCL_TLS_KEY_CREATE_FUNC(key) (pthread_key_create(&key,NULL)==0)`

## 8.157 osclconfig\_util.h File Reference

```
#include "osclconfig.h"
#include <stdio.h>
#include <time.h>
#include <sys/time.h>
#include <unistd.h>
#include "osclconfig_util_check.h"
```

### Defines

- #define OSCL\_CLOCK\_HAS\_DRIFT\_CORRECTION 0
- #define OSCL\_HAS\_SYMBIAN\_TIMERS 0
- #define OSCL\_HAS\_SYMBIAN\_MATH 0
- #define OSCL RAND\_MAX RAND\_MAX
- #define SLEEP\_ONE\_SEC sleep(1)

### 8.157.1 Define Documentation

- 8.157.1.1 #define OSCL\_CLOCK\_HAS\_DRIFT\_CORRECTION 0
- 8.157.1.2 #define OSCL\_HAS\_SYMBIAN\_MATH 0
- 8.157.1.3 #define OSCL\_HAS\_SYMBIAN\_TIMERS 0
- 8.157.1.4 #define OSCL RAND\_MAX RAND\_MAX
- 8.157.1.5 #define SLEEP\_ONE\_SEC sleep(1)

## **8.158 osclconfig\_util\_check.h File Reference**

## 8.159 pvlogger.h File Reference

This file contains basic logger interfaces for common use across platforms.

```
#include "oscl_base.h"
#include "oscl_vector.h"
#include "oscl_shared_ptr.h"
#include "oscl_base_alloc.h"
```

### Data Structures

- class [PVLogger](#)

### Defines

- #define [PVLOGMSG\\_INST\\_REL](#) 0
- #define [PVLOGMSG\\_INST\\_PROF](#) 1
- #define [PVLOGMSG\\_INST\\_HLDBG](#) 2
- #define [PVLOGMSG\\_INST\\_MLDBG](#) 3
- #define [PVLOGMSG\\_INST\\_LLDBG](#) 4
- #define [PVLOGGER\\_INST\\_LEVEL](#) 5
- #define [\\_PVLOGGER\\_LOGMSG\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [\\_PVLOGGER\\_LOGMSG\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [\\_PVLOGGER\\_LOGBIN\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [\\_PVLOGGER\\_LOGBIN\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_INST\\_LEVEL\\_SUPPORT](#) 1
- #define [PVLOGGER\\_LOGMSG\\_PVLOGMSG\\_INST\\_REL\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGMSG\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGMSG\\_V\\_PVLOGMSG\\_INST\\_REL\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGMSG\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGBIN\\_PVLOGMSG\\_INST\\_REL\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGBIN\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGBIN\\_V\\_PVLOGMSG\\_INST\\_REL\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGBIN\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGMSG\\_PVLOGMSG\\_INST\\_PROF\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGMSG\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGMSG\\_V\\_PVLOGMSG\\_INST\\_PROF\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGMSG\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGBIN\\_PVLOGMSG\\_INST\\_PROF\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGBIN\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGBIN\\_V\\_PVLOGMSG\\_INST\\_PROF\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGBIN\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGMSG\\_PVLOGMSG\\_INST\\_HLDBG\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGMSG\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGMSG\\_V\\_PVLOGMSG\\_INST\\_HLDBG\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGMSG\\_V\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGBIN\\_PVLOGMSG\\_INST\\_HLDBG\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGBIN\(LOGGER, LEVEL, MESSAGE\)](#)
- #define [PVLOGGER\\_LOGBIN\\_V\\_PVLOGMSG\\_INST\\_HLDBG\(LOGGER, LEVEL, MESSAGE\) \\_- PVLOGGER\\_LOGBIN\\_V\(LOGGER, LEVEL, MESSAGE\)](#)

- #define `PVLOGGER_LOGMSG_PVLOGMSG_INST_MLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGMSG_V_PVLOGMSG_INST_MLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGBIN_PVLOGMSG_INST_MLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGBIN_V_PVLOGMSG_V_INST_MLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGMSG_PVLOGMSG_INST_LLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGMSG_V_PVLOGMSG_INST_LLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGBIN_PVLOGMSG_INST_LLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGBIN_V_PVLOGMSG_INST_LLDBG`(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGMSG(IL, LOGGER, LEVEL, MESSAGE)` PVLOGGER\_LOGMSG\_## IL (LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGMSG_V(IL, LOGGER, LEVEL, MESSAGE)` PVLOGGER\_LOGMSG\_V\_## IL (LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGBIN(IL, LOGGER, LEVEL, MESSAGE)` PVLOGGER\_LOGBIN\_## IL (LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOGBIN_V(IL, LOGGER, LEVEL, MESSAGE)` PVLOGGER\_LOGBIN\_V\_## IL (LOGGER, LEVEL, MESSAGE)
- #define `PVLOGGER_LOG_USE_ONLY(x)` x
- #define `PVLOGGER_ENABLE` 1

## Variables

- const int32 `PVLOGGER_LEVEL_UNINITIALIZED` = -1
- const `PVLogger::log_level_type` `PVLOGMSG_EMERG` = 0
- const `PVLogger::log_level_type` `PVLOGMSG_ALERT` = 1
- const `PVLogger::log_level_type` `PVLOGMSG_CRIT` = 2
- const `PVLogger::log_level_type` `PVLOGMSG_ERR` = 3
- const `PVLogger::log_level_type` `PVLOGMSG_WARNING` = 4
- const `PVLogger::log_level_type` `PVLOGMSG_NOTICE` = 5
- const `PVLogger::log_level_type` `PVLOGMSG_INFO` = 6
- const `PVLogger::log_level_type` `PVLOGMSG_STACK_TRACE` = 7
- const `PVLogger::log_level_type` `PVLOGMSG_DEBUG` = 8
- const `PVLogger::log_level_type` `PVLOGMSG_FATAL_ERROR` = `PVLOGMSG_EMERG`
- const `PVLogger::log_level_type` `PVLOGMSG_NONFATAL_ERROR` = `PVLOGMSG_ERR`
- const `PVLogger::log_level_type` `PVLOGMSG_STATISTIC` = `PVLOGMSG_INFO`
- const `PVLogger::log_level_type` `PVLOGMSG_VERBOSE` = `PVLOGMSG_DEBUG`

### 8.159.1 Detailed Description

This file contains basic logger interfaces for common use across platforms.

This is the main entry point header file for the logger library. It should be the only one users directly include.

## 8.159.2 Define Documentation

### 8.159.2.1 #define \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)

**Value:**

```
{\
  if (LOGGER) \
  {\
    if (LOGGER->IsActive(LEVEL)) \
    {\
      LOGGER->LogMsgBuffers MESSAGE; \
    }\
  }\
}
```

### 8.159.2.2 #define \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)

**Value:**

```
{\
  if (LOGGER) \
  {\
    if (LOGGER->IsActive(LEVEL)) \
    {\
      LOGGER->LogMsgBuffersV MESSAGE; \
    }\
  }\
}
```

### 8.159.2.3 #define \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)

**Value:**

```
{\
  if (LOGGER) \
  {\
    if (LOGGER->IsActive(LEVEL)) \
    {\
      LOGGER->LogMsgString MESSAGE; \
    }\
  }\
}
```

### 8.159.2.4 #define \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)

**Value:**

```
{\
  if (LOGGER) \
  {\
    if (LOGGER->IsActive(LEVEL)) \
    {\
      LOGGER->LogMsgStringV MESSAGE; \
    }\
  }\
}
```

**8.159.2.5 #define PVLOGGER\_ENABLE 1**

In case logging is compiled out, there is no need to compile the logger runtime code either.

**8.159.2.6 #define PVLOGGER\_INST\_LEVEL 5****8.159.2.7 #define PVLOGGER\_INST\_LEVEL\_SUPPORT 1****8.159.2.8 #define PVLOGGER\_LOG\_USE\_ONLY(x) x**

Used to compile in/out lines of code that are used only for **PVLogger** macros.

This code will be removed at compile time when **PVLogger** is disabled, i.e. Release mode. So do not put in any code that is necessary for correct functionality of the module

**8.159.2.9 #define PVLOGGER\_LOGBIN(IL, LOGGER, LEVEL, MESSAGE)  
PVLOGGER\_LOGBIN\_ ## IL (LOGGER, LEVEL, MESSAGE)**

This is a binary API to log messages

**Parameters:**

**IL** Instrumentation level.

**LOGGER** Pointer to the logger object, that acts as the logging control/interface point

**LEVEL** Log level of the message

**MESSAGE** Log Message which includes the message id, and message buffers that need to be logged.

Example Usage: `PVLOGGER_LOGBIN (PVLOGMSG_INST_LLDBG, logger_1, PVLOGMSG_WARNING, (10, 3, msgBuf1Size, msgBuf1, msgBuf2Size, msgBuf2, msgBuf3Size, msgBuf3));`

-This message contains THREE (ptr\_len, ptr) pairs. Log level of this msg is PVLOGMSG\_WARNING, message id is 10.

- 8.159.2.10** #define PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_HLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- 8.159.2.11** #define PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_LLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- 8.159.2.12** #define PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_MLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- 8.159.2.13** #define PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_PROF(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- 8.159.2.14** #define PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_REL(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN(LOGGER, LEVEL, MESSAGE)
- 8.159.2.15** #define PVLOGGER\_LOGBIN\_V(IL, LOGGER, LEVEL, MESSAGE)  
PVLOGGER\_LOGBIN\_V\_## IL (LOGGER, LEVEL, MESSAGE)
- 8.159.2.16** #define PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_HLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.17** #define PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_LLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.18** #define PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_PROF(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.19** #define PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_REL(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.20** #define PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_V\_INST\_MLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGBIN\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.21** #define PVLOGGER\_LOGMSG(IL, LOGGER, LEVEL, MESSAGE)  
PVLOGGER\_LOGMSG\_## IL (LOGGER, LEVEL, MESSAGE)

This is the text based API to log messages

**Parameters:**

**IL** Instrumentation level.

**LOGGER** Pointer to the logger object, that acts as the logging control/interface point

**LEVEL** Log level of the message

**MESSAGE** Log Message which includes the message id, and any kind of formatting information

Example Usage: PVLOGGER\_LOGMSG(PVLOGMSG\_INST\_LLDBG, logger\_1, PVLOGMSG\_-WARNING, (13, "Test Messsage to Node 1

")); -This message of log level PVLOGMSG\_WARNING, and has a message id of 13

- 8.159.2.22 #define PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_HLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- 8.159.2.23 #define PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_LLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- 8.159.2.24 #define PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_MLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- 8.159.2.25 #define PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_PROF(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- 8.159.2.26 #define PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_REL(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG(LOGGER, LEVEL, MESSAGE)
- 8.159.2.27 #define PVLOGGER\_LOGMSG\_V(IL, LOGGER, LEVEL, MESSAGE)  
PVLOGGER\_LOGMSG\_V\_## IL (LOGGER, LEVEL, MESSAGE)
- 8.159.2.28 #define PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_HLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.29 #define PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_LLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.30 #define PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_MLDBG(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.31 #define PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_PROF(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.32 #define PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_REL(LOGGER, LEVEL, MESSAGE) \_PVLOGGER\_LOGMSG\_V(LOGGER, LEVEL, MESSAGE)
- 8.159.2.33 #define PVLOGMSG\_INST\_HLDBG 2

#### High Level Debug Layer

This layer should contain messages that have very minimal impact on performance, but are at lower level (i.e., provide more information) than would be appropriate in a shipping product. The messages are probably used to gather information and validate proper functionality at a high level as might be appropriate for IOT, stress testing, or QA testing.

#### 8.159.2.34 #define PVLOGMSG\_INST\_LLDBG 4

#### Low Level Debug Layer

This layer should contain messages for early functional testing. The messages are typically at a very low-level and allow testing the functionality of individual modules and components. Messages at this layer will typically have a performance impact (sometimes significant) due to the fact that they are at such a low level.

### 8.159.2.35 #define PVLOGMSG\_INST\_MLDBG 3

Mid Level Debug Layer

This layer should contain messages that are useful in the middle stages of the development cycle where major components are being integrated. The components themselves should already be well-tested so the emphasis is on interfaces between these components and integration testing. Messages at this layer may have some performance impact.

### 8.159.2.36 #define PVLOGMSG\_INST\_PROF 1

Profile Layer

The profile layer is used for messages and information related to measuring and reporting performance-related information.

### 8.159.2.37 #define PVLOGMSG\_INST\_REL 0

Release Layer

The release layer should only be used for messages that should remain in the final release. In certain cases all messaging may be disabled depending on customer requirements. However, when allowed the release layer should contain information that will be useful diagnosing problems in a released product (perhaps after entering a diagnostic mode), but with absolutely minimal performance impact when disabled at runtime.

## 8.159.3 Variable Documentation

### 8.159.3.1 const int32 PVLOGGER\_LEVEL\_UNINITIALIZED = -1

### 8.159.3.2 const PVLogger::log\_level\_type PVLOGMSG\_ALERT = 1

action must be taken immediately

### 8.159.3.3 const PVLogger::log\_level\_type PVLOGMSG\_CRIT = 2

critical conditions

### 8.159.3.4 const PVLogger::log\_level\_type PVLOGMSG\_DEBUG = 8

debug-level messages

### 8.159.3.5 const PVLogger::log\_level\_type PVLOGMSG\_EMERG = 0

system is unusable

### 8.159.3.6 const PVLogger::log\_level\_type PVLOGMSG\_ERR = 3

error conditions

**8.159.3.7 const PVLogger::log\_level\_type PVLOGMSG\_FATAL\_ERROR = PVLOGMSG\_EMERG**

**8.159.3.8 const PVLogger::log\_level\_type PVLOGMSG\_INFO = 6**

informational

**8.159.3.9 const PVLogger::log\_level\_type PVLOGMSG\_NONFATAL\_ERROR = PVLOGMSG\_ERR**

**8.159.3.10 const PVLogger::log\_level\_type PVLOGMSG\_NOTICE = 5**

normal but significant condition

**8.159.3.11 const PVLogger::log\_level\_type PVLOGMSG\_STACK\_TRACE = 7**

function enter and exit

**8.159.3.12 const PVLogger::log\_level\_type PVLOGMSG\_STATISTIC = PVLOGMSG\_INFO**

**8.159.3.13 const PVLogger::log\_level\_type PVLOGMSG\_VERBOSE = PVLOGMSG\_DEBUG**

**8.159.3.14 const PVLogger::log\_level\_type PVLOGMSG\_WARNING = 4**

warning conditions

## 8.160 pvlogger\_accessories.h File Reference

```
#include "oscl_base.h"
#include "pvlogger.h"
```

### Data Structures

- class [AllPassFilter](#)
- class [PVLoggerAppender](#)
- class [PVLoggerFilter](#)
- class [PVLoggerLayout](#)

### Variables

- const [PVLoggerFilter::filter\\_status\\_type](#) PVLOGGER\_FILTER\_ACCEPT = 1
- const [PVLoggerFilter::filter\\_status\\_type](#) PVLOGGER\_FILTER\_REJECT = 2
- const [PVLoggerFilter::filter\\_status\\_type](#) PVLOGGER\_FILTER\_NEUTRAL = 3

#### 8.160.1 Variable Documentation

**8.160.1.1 const [PVLoggerFilter::filter\\_status\\_type](#) PVLOGGER\_FILTER\_ACCEPT = 1**

**8.160.1.2 const [PVLoggerFilter::filter\\_status\\_type](#) PVLOGGER\_FILTER\_NEUTRAL = 3**

**8.160.1.3 const [PVLoggerFilter::filter\\_status\\_type](#) PVLOGGER\_FILTER\_REJECT = 2**

## 8.161 pvlogger\_c.h File Reference

This file contains basic logger interfaces for common use across platforms. C-callable version.

```
#include "osclconfig.h"
```

### Defines

- #define PVLOGGER\_C\_INST\_LEVEL 5
- #define PVLOGMSG\_C\_INST\_REL 0
- #define PVLOGMSG\_C\_INST\_PROF 1
- #define PVLOGMSG\_C\_INST\_HLDBG 2
- #define PVLOGMSG\_C\_INST\_MLDBG 3
- #define PVLOGMSG\_C\_INST\_LLDBG 4
- #define PVLOGMSG\_C\_EMERG 0
- #define PVLOGMSG\_C\_ALERT 1
- #define PVLOGMSG\_C\_CRIT 2
- #define PVLOGMSG\_C\_ERR 3
- #define PVLOGMSG\_C\_WARNING 4
- #define PVLOGMSG\_C\_NOTICE 5
- #define PVLOGMSG\_C\_INFO 6
- #define PVLOGMSG\_C\_STACK\_TRACE 7
- #define PVLOGMSG\_C\_STACK\_DEBUG 8

### Functions

- OSCL\_IMPORT\_REF void \* [pvLogger\\_GetLoggerObject](#) (const char \*tag)
- OSCL\_IMPORT\_REF int [pvLogger\\_IsActive](#) (void \*logger, int log\_level)
- OSCL\_IMPORT\_REF void [pvLogger\\_LogMsgString](#) (void \*logger, int msgID, const char \*fmt,...)

### 8.161.1 Detailed Description

This file contains basic logger interfaces for common use across platforms. C-callable version.

This is the main entry point header file for the logger library. It should be the only one users directly include.

## 8.161.2 Define Documentation

- 8.161.2.1 `#define PVLOGGER_C_INST_LEVEL 5`
- 8.161.2.2 `#define PVLOGMSG_C_ALERT 1`
- 8.161.2.3 `#define PVLOGMSG_C_CRIT 2`
- 8.161.2.4 `#define PVLOGMSG_C_EMERG 0`
- 8.161.2.5 `#define PVLOGMSG_C_ERR 3`
- 8.161.2.6 `#define PVLOGMSG_C_INFO 6`
- 8.161.2.7 `#define PVLOGMSG_C_INST_HLDBG 2`
- 8.161.2.8 `#define PVLOGMSG_C_INST_LLDBG 4`
- 8.161.2.9 `#define PVLOGMSG_C_INST_MLDBG 3`
- 8.161.2.10 `#define PVLOGMSG_C_INST_PROF 1`
- 8.161.2.11 `#define PVLOGMSG_C_INST_REL 0`
- 8.161.2.12 `#define PVLOGMSG_C_NOTICE 5`
- 8.161.2.13 `#define PVLOGMSG_C_STACK_DEBUG 8`
- 8.161.2.14 `#define PVLOGMSG_C_STACK_TRACE 7`
- 8.161.2.15 `#define PVLOGMSG_C_WARNING 4`

## 8.161.3 Function Documentation

- 8.161.3.1 `OSCL_IMPORT_REF void* pvLogger_GetLoggerObject (const char * tag)`
- 8.161.3.2 `OSCL_IMPORT_REF int pvLogger_IsActive (void * logger, int log_level)`
- 8.161.3.3 `OSCL_IMPORT_REF void pvLogger_LogMsgString (void * logger, int msgID, const char * fmt, ...)`

## **8.162 pvlogger\_registry.h File Reference**

```
#include "pvlogger.h"
#include "oscl_tagtree.h"
```

### **Data Structures**

- class [PVLoggerRegistry](#)

# Chapter 9

## oscl Page Documentation

### 9.1 Todo List

Global **MAX\_NUMBER\_OF\_BYTE\_PER\_UTF8** Handle 4-byte surrogate pair representation

# Index

~AllPassFilter  
    AllPassFilter, 114  
~BufFragGroup  
    BufFragGroup, 120  
~BufferMgr  
    BufferMgr, 117  
~CallbackTimer  
    CallbackTimer, 123  
~CallbackTimerObserver  
    CallbackTimerObserver, 125  
~DNSRequestParam  
    DNSRequestParam, 132  
~GetHostByNameParam  
    GetHostByNameParam, 135  
~HeapBase  
    HeapBase, 137  
~MM\_AllocInfo  
    MM\_AllocInfo, 149  
~MM\_AllocNode  
    MM\_AllocNode, 150  
~MM\_Audit\_Imp  
    MM\_Audit\_Imp, 153  
~MediaData  
    MediaData, 142  
~MemAllocator  
    MemAllocator, 145  
~OSCLMemAutoPtr  
    OSCLMemAutoPtr, 435  
~OSCL\_FastString  
    OSCL\_FastString, 175  
~OSCL\_HeapString  
    osclutil, 83  
~OSCL\_HeapStringA  
    OSCL\_HeapStringA, 199  
~OSCL\_StackString  
    osclutil, 83  
~OSCL\_String  
    OSCL\_String, 260  
~OSCL\_wFastString  
    OSCL\_wFastString, 294  
~OSCL\_wHeapString  
    osclutil, 83  
~OSCL\_wHeapStringA  
    OSCL\_wHeapStringA, 299  
~OSCL\_wStackString  
    osclutil, 83  
~OSCL\_wString  
    OSCL\_wString, 304  
~OsclAcceptMethod  
    OsclAcceptMethod, 307  
~OsclActiveObject  
    OsclActiveObject, 310  
~OsclAllocDestructDealloc  
    OsclAllocDestructDealloc, 313  
~OsclAsyncFile  
    OsclAsyncFile, 316  
~OsclAsyncFileBuffer  
    OsclAsyncFileBuffer, 319  
~OsclBinIStream  
    OsclBinIStream, 323  
~OsclBinOStream  
    OsclBinOStream, 330  
~OsclBindMethod  
    OsclBindMethod, 321  
~OsclCacheObserver  
    Oscl\_File::OsclCacheObserver, 186  
~OsclComponentRegistry  
    OsclComponentRegistry, 343  
~OsclComponentRegistryElement  
    OsclComponentRegistryElement, 345  
~OsclConnectMethod  
    OsclConnectMethod, 347  
~OsclDNS  
    OsclDNS, 350  
~OsclDNSI  
    OsclDNSI, 352  
~OsclDNSIBase  
    OsclDNSIBase, 355  
~OsclDNSObserver  
    OsclDNSObserver, 360  
~OsclDNSRequest  
    OsclDNSRequest, 361  
~OsclDestructDealloc  
    OsclDestructDealloc, 349  
~OsclExclusiveArrayPtr  
    OsclExclusiveArrayPtr, 380  
~OsclExclusivePtr  
    OsclExclusivePtr, 383  
~OsclExclusivePtrA  
    OsclExclusivePtrA, 386

- ~OsclExecSchedulerCommonBase
  - OsclExecSchedulerCommonBase, 394
- ~OsclFileCache
  - OsclFileCache, 401
- ~OsclGetHostByNameMethod
  - OsclGetHostByNameMethod, 412
- ~OsclIPSocketI
  - OsclIPSocketI, 418
- ~OsclJump
  - OsclJump, 420
- ~OsclListenMethod
  - OsclListenMethod, 421
- ~OsclLockBase
  - OsclLockBase, 423
- ~OsclMemAudit
  - OsclMemAudit, 428
- ~OsclMemPoolFixedChunkAllocator
  - OsclMemPoolFixedChunkAllocator, 443
- ~OsclMemPoolFixedChunkAllocatorObserver
  - OsclMemPoolFixedChunkAllocator-  
Observer, 446
- ~OsclMemPoolResizableAllocator
  - OsclMemPoolResizableAllocator, 448
- ~OsclMemPoolResizableAllocatorMemoryObserver
  - OsclMemPoolResizableAllocatorMemory-  
Observer, 455
- ~OsclMemPoolResizableAllocatorObserver
  - OsclMemPoolResizableAllocatorObserver,  
456
- ~OsclMemStatsNode
  - OsclMemStatsNode, 457
- ~OsclMutex
  - OsclMutex, 458
- ~OsclNativeFile
  - OsclNativeFile, 462
- ~OsclNullLock
  - OsclNullLock, 466
- ~OsclPriorityQueue
  - OsclPriorityQueue, 470
- ~OsclPriorityQueueBase
  - OsclPriorityQueueBase, 473
- ~OsclRecvFromMethod
  - OsclRecvFromMethod, 485
- ~OsclRecvMethod
  - OsclRecvMethod, 489
- ~OsclRefCounter
  - OsclRefCounter, 491
- ~OsclRefCounterDA
  - OsclRefCounterDA, 493
- ~OsclRefCounterMTDA
  - OsclRefCounterMTDA, 497
- ~OsclRefCounterMTSA
  - OsclRefCounterMTSA, 499
- ~OsclRefCounterMemFrag
  - OsclRefCounterMemFrag, 495
- ~OsclRefCounterSA
  - OsclRefCounterSA, 501
- ~OsclRegistryAccessClient
  - OsclRegistryAccessClient, 503
- ~OsclRegistryClient
  - OsclRegistryClient, 508
- ~OsclRegistryServTlsImpl
  - OsclRegistryServTlsImpl, 514
- ~OsclSchedulerObserver
  - OsclSchedulerObserver, 516
- ~OsclScopedLock
  - OsclScopedLock, 517
- ~OsclSemaphore
  - OsclSemaphore, 520
- ~OsclSendMethod
  - OsclSendMethod, 522
- ~OsclSendToMethod
  - OsclSendToMethod, 524
- ~OsclSharedPtr
  - OsclSharedPtr, 527
- ~OsclShutdownMethod
  - OsclShutdownMethod, 529
- ~OsclSingleton
  - OsclSingleton, 531
- ~OsclSocketI
  - OsclSocketI, 535
- ~OsclSocketIBase
  - OsclSocketIBase, 540
- ~OsclSocketMethod
  - OsclSocketMethod, 545
- ~OsclSocketObserver
  - OsclSocketObserver, 547
- ~OsclSocketRequestAO
  - OsclSocketRequestAO, 550
- ~OsclSocketServ
  - OsclSocketServ, 553
- ~OsclSocketServIBase
  - OsclSocketServIBase, 558
- ~OsclTCPSocket
  - OsclTCPSocket, 565
- ~OsclTCPSocketI
  - OsclTCPSocketI, 572
- ~OsclTLS
  - OsclTLS, 591
- ~OsclTLSEx
  - OsclTLSEx, 593
- ~OsclThread
  - OsclThread, 574
- ~OsclThreadLock
  - OsclThreadLock, 578
- ~OsclTimer
  - OsclTimer, 582
- ~OsclTimerObject

OsclTimerObject, 586  
 ~OsclTimerObserver  
   OsclTimerObserver, 589  
 ~OsclUDPSocket  
   OsclUDPSocket, 601  
 ~OsclUDPSocketI  
   OsclUDPSocketI, 607  
 ~Oscl\_Alloc  
   Oscl\_Alloc, 169  
 ~Oscl\_Dealloc  
   Oscl\_Dealloc, 170  
 ~Oscl\_File  
   Oscl\_File, 180  
 ~Oscl\_FileFind  
   Oscl\_FileFind, 189  
 ~Oscl\_FileServer  
   Oscl\_FileServer, 192  
 ~Oscl\_Linked\_List  
   Oscl\_Linked\_List, 205  
 ~Oscl\_Linked\_List\_Base  
   Oscl\_Linked\_List\_Base, 211  
 ~Oscl\_MTLinked\_List  
   Oscl\_MTLinked\_List, 224  
 ~Oscl\_Opaque\_Type\_Alloc  
   Oscl\_Opaque\_Type\_Alloc, 228  
 ~Oscl\_Opaque\_Type\_Alloc\_LL  
   Oscl\_Opaque\_Type\_Alloc\_LL, 230  
 ~Oscl\_Opaque\_Type\_Compare  
   Oscl\_Opaque\_Type\_Compare, 232  
 ~Oscl\_Queue  
   Oscl\_Queue, 236  
 ~Oscl\_Queue\_Base  
   Oscl\_Queue\_Base, 238  
 ~Oscl\_Rb\_Tree  
   Oscl\_Rb\_Tree, 243  
 ~Oscl\_TAlloc  
   Oscl\_TAlloc, 281  
 ~Oscl\_Tag  
   Oscl\_Tag, 264  
 ~Oscl\_TagTree  
   Oscl\_TagTree, 269  
 ~Oscl\_Vector  
   Oscl\_Vector, 285  
 ~Oscl\_Vector\_Base  
   Oscl\_Vector\_Base, 290  
 ~PVActiveBase  
   PVActiveBase, 612  
 ~PVLogger  
   PVLogger, 617  
 ~PVLoggerAppender  
   PVLoggerAppender, 622  
 ~PVLoggerFilter  
   PVLoggerFilter, 624  
 ~PVLoggerLayout  
   PVLoggerLayout, 625  
 ~PVLoggerRegistry  
   PVLoggerRegistry, 627  
 ~PVSchedulerStopper  
   PVSchedulerStopper, 630  
 ~PVThreadContext  
   PVThreadContext, 633  
 ~SendToParam  
   SendToParam, 639  
 ~\_OsclBasicAllocator  
   \_OsclBasicAllocator, 108  
 ~\_OsclHeapBase  
   \_OsclHeapBase, 110  
 \_OSCL\_Abort  
   osclbase, 35  
 \_OSCL\_CLEANUP\_BASE\_CLASS  
   osclmemory, 49  
 \_OSCL\_TRAP\_NEW  
   osclmemory, 49  
 \_OsclBasicAllocator, 107  
 \_OsclBasicAllocator  
   ~\_OsclBasicAllocator, 108  
   allocate, 108  
   deallocate, 108  
 \_OsclHeapBase, 109  
   \_OsclHeapBase, 110  
 \_OsclHeapBase  
   ~\_OsclHeapBase, 110  
   \_OsclHeapBase, 110  
   PVCleanupStack, 110  
 \_OsclInteger64Transport  
   oscl\_int64\_utils.h, 704  
 \_Ownership  
   OSCLMemAutoPtr, 437  
 \_PVLOGGER\_LOGBIN  
   pvlogger.h, 851  
 \_PVLOGGER\_LOGBIN\_V  
   pvlogger.h, 851  
 \_PVLOGGER\_LOGMSG  
   pvlogger.h, 851  
 \_PVLOGGER\_LOGMSG\_V  
   pvlogger.h, 851  
 \_PV\_TRAP  
   oscl\_error\_imp\_fatalerror.h, 684  
   oscl\_error\_imp\_jumps.h, 685  
   osclerror, 87  
 \_PV\_TRAP\_NO\_TLS  
   oscl\_error\_imp\_fatalerror.h, 684  
   oscl\_error\_imp\_jumps.h, 685  
   osclerror, 87  
 \_Ptr  
   OsclExclusiveArrayPtr, 381  
   OsclExclusivePtr, 384  
   OsclExclusivePtrA, 387

OsclSingleton, 532  
 OsclTLS, 592  
 OsclTLSEx, 594  
**\_STRLIT**  
 osclconfig\_unix\_android.h, 842  
 osclconfig\_unix\_common.h, 846  
**\_STRLIT\_CHAR**  
 osclconfig\_unix\_android.h, 842  
 osclconfig\_unix\_common.h, 846  
**\_STRLIT\_WCHAR**  
 osclconfig\_unix\_android.h, 842  
 osclconfig\_unix\_common.h, 846  
**\_TFS\_**  
 osclconfig.h, 803  
**\_Validate\_BasicTimeDateStruct\_**  
 osclconfig\_time\_check.h, 838  
**\_Validate\_BasicTimeStruct\_**  
 osclconfig\_time\_check.h, 838  
**\_int16\_check\_**  
 osclconfig, 24  
**\_int32\_check\_**  
 osclconfig, 24  
**\_int8\_check\_**  
 osclconfig, 24  
**\_uint16\_check\_**  
 osclconfig, 24  
**\_uint32\_check\_**  
 osclconfig, 24  
**\_uint8\_check\_**  
 osclconfig, 24  
**\_verify\_TOsclConditionObject\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_verify\_TOsclFileOffset\_defined\_**  
 osclconfig\_io\_check.h, 822  
**\_verify\_TOsclMutexObject\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_verify\_TOsclSemaphoreObject\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_verify\_TOsclThreadFuncArg\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_verify\_TOsclThreadFuncRet\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_verify\_TOsclThreadId\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_verify\_TOsclThreadObject\_defined\_**  
 osclconfig\_proc\_check.h, 831  
**\_fixedCaches**  
 OsclFileCache, 401  
**\_movableCache**  
 OsclFileCache, 401  
**\_oscl\_audit\_malloc**  
 osclmemory, 58  
**\_oscl\_audit\_free**  
 osclmemory, 58  
**\_oscl\_audit\_new**  
 osclmemory, 58  
**\_oscl\_audit\_realloc**  
 osclmemory, 59  
**\_oscl\_calloc**  
 osclmemory, 59  
**\_oscl\_default\_audit\_malloc**  
 osclmemory, 59  
**\_oscl\_default\_audit\_new**  
 osclmemory, 59  
**\_oscl\_default\_audit\_realloc**  
 osclmemory, 59  
**\_oscl\_free**  
 osclmemory, 59  
**\_oscl\_malloc**  
 osclmemory, 59  
**\_oscl\_realloc**  
 osclmemory, 59  
**a**  
 internalLeave, 138  
**Abort**  
 OsclDNSMethod, 358  
 OsclDNSRequestAO, 363  
 OsclSocketMethod, 545  
 OsclSocketRequestAO, 550  
**AbortAll**  
 OsclDNSMethod, 358  
 OsclSocketMethod, 545  
**Accept**  
 OsclAcceptMethod, 307  
 OsclAcceptRequest, 308  
 OsclSocketI, 535  
 OsclSocketIBase, 540  
 OsclTCPSocket, 565  
 OsclTCPSocketI, 572  
**AcceptParam**, 111  
 AcceptParam, 111  
**AcceptParam**  
 AcceptParam, 111  
 iBlankSocket, 111  
**AcceptRequest**  
 OsclAcceptMethod, 307  
**Activate**  
 OsclDNSRequest, 361  
 OsclSocketRequest, 548  
 PVActiveBase, 612  
**Add**  
 OsclSocketServRequestList, 559  
 OsclTimerQ, 590

add\_element  
     Oscl\_Linked\_List, 206  
     Oscl\_Linked\_List\_Base, 211  
     Oscl\_MTLinked\_List, 225  
 add\_ref  
     CHHeapRep, 129  
 add\_to\_front  
     Oscl\_Linked\_List, 206  
     Oscl\_Linked\_List\_Base, 211  
     Oscl\_MTLinked\_List, 225  
 addAllocNode  
     MM\_Audit\_Imp, 153  
 AddAppender  
     PVLogger, 617  
 AddFilter  
     PVLogger, 617  
 AddFixedCache  
     Oscl\_File, 180  
     OsclFileCache, 401  
 AddFragment  
     BufFragGroup, 120  
 AddLocalFragment  
     MediaData, 142  
 addnewmempoolbuffer  
     OsclMemPoolResizableAllocator, 448  
 addRef  
     Oscl\_DefAllocWithRefCounter, 172  
     OsclMemPoolFixedChunkAllocator, 443  
     OsclMemPoolResizableAllocator, 448  
     OsclRefCount, 491  
     OsclRefCountDA, 494  
     OsclRefCountMTDA, 498  
     OsclRefCountMTSA, 500  
     OsclRefCountSA, 502  
 address  
     Oscl\_TAlloc, 281  
 addressListCapacity  
     GetHostNameParam, 134  
 AddToExecTimerQ  
     OsclExecSchedulerCommonBase, 394  
 AddToScheduler  
     OsclActiveObject, 310  
     OsclTimerObject, 586  
     PVActiveBase, 612  
 After  
     OsclTimerObject, 586  
 Alloc  
     OsclIPSocketI, 418  
     OsclSocketMethod, 545  
     OsclSocketRequestAO, 550  
 ALLOC\_AND\_CONSTRUCT  
     osclbase, 32  
 alloc\_and\_construct  
     Oscl\_TAlloc, 281  
 alloc\_and\_construct\_fi  
     Oscl\_TAlloc, 281  
 ALLOC\_NODE\_FLAG  
     osclmemory, 61  
 alloc\_type  
     PVLogger, 617  
     PVLoggerRegistry, 627  
 ALLOCATE  
     osclbase, 32  
 allocate  
     \_OsclBasicAllocator, 108  
     MemAllocator, 145  
     Oscl\_Alloc, 169  
     Oscl\_DefAlloc, 171  
     Oscl\_Opaque\_Type\_Alloc, 228  
     Oscl\_Opaque\_Type\_Alloc\_LL, 230  
     Oscl\_TAlloc, 281  
     OsclErrorAllocator, 373  
     OsclMemAllocator, 425  
     OsclMemAllocDestructDealloc, 426  
     OSCLMemAutoPtr, 436  
     OsclMemBasicAllocator, 438  
     OsclMemBasicAllocDestructDealloc, 439  
     OsclMemPoolFixedChunkAllocator, 443  
     OsclMemPoolResizableAllocator, 449  
     OsclReadyAlloc, 481  
 allocate\_fi  
     Oscl\_Alloc, 169  
     Oscl\_DefAlloc, 171  
     Oscl\_TAlloc, 281  
     OsclMemAllocator, 425  
     OsclMemAllocDestructDealloc, 426  
     OsclReadyAlloc, 481  
 allocateblock  
     OsclMemPoolResizableAllocator, 449  
 allocator, 112  
 allocNum  
     MM\_AllocInfo, 149  
     MM\_AllocQueryInfo, 151  
 AllPassFilter, 113  
     AllPassFilter, 114  
 AllPassFilter  
     ~AllPassFilter, 114  
     AllPassFilter, 114  
     filter\_status\_type, 113  
     FilterOpaqueMessge, 114  
     FilterString, 114  
     log\_level\_type, 113  
     message\_id\_type, 113  
 ALREADY\_SUSPENDED\_ERROR  
     OsclProcStatus, 474  
 Append  
     OsclPtr, 476  
 append

CFastRep, 127  
 CHheapRep, 129  
 CStackRep, 131  
**APPEND\_MEDIA\_AT\_END**  
 osclutil, 83  
**append\_rep**  
 CHheapRep, 129  
 OSCL\_String, 260  
 OSCL\_wString, 304  
**AppendBuffers**  
 PVLoggerAppender, 622  
**AppendNext**  
 BufFragGroup, 120  
**AppendString**  
 PVLoggerAppender, 622  
**assign**  
 CHheapRep, 129  
**assign\_vector**  
 Oscl\_Vector\_Base, 290  
**asyncfilereadcancel\_test**  
 Oscl\_File, 185  
**asyncfilereadwrite\_test**  
 Oscl\_File, 185  
**Attach**  
 OsclBinStream, 336  
**audit\_type**  
 OsclMemGlobalAuditObject, 440  
**available\_localbuf**  
 MediaData, 143  
  
**back**  
 Oscl\_Queue, 236  
 Oscl\_Vector, 286  
**BAD\_THREADID\_ADDR\_ERROR**  
 OsclProcStatus, 474  
**base\_link\_type**  
 Oscl\_Rb\_Tree\_Base, 245  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_Rb\_Tree\_Iterator, 250  
 Oscl\_Rb\_Tree\_Node\_Base, 253  
**begin**  
 Oscl\_Map, 218  
 Oscl\_Rb\_Tree, 243  
 Oscl\_TagTree, 269  
 Oscl\_Vector, 286  
**BeginScheduling**  
 OsclExecSchedulerCommonBase, 394  
**BeginStats**  
 OsclExecSchedulerCommonBase, 394  
**BFG\_SUCCESS**  
 BufFragStatusClass, 122  
**big\_endian\_to\_host**  
 osclbase, 35  
**Bind**  
 osclbase, 35  
 OsclBindMethod, 321  
 OsclBindRequest, 322  
 OsclIPSocketI, 418  
 OsclSocketI, 535  
 OsclSocketIBase, 540  
 OsclTCPSocket, 565  
 OsclUDPSocket, 601  
**bind**  
 BufferState, 118  
**BindAsync**  
 OsclSocketIBase, 540  
 OsclTCPSocket, 565  
 OsclTCPSocketI, 572  
 OsclUDPSocket, 601  
 OsclUDPSocketI, 607  
**BindParam**, 115  
 BindParam, 115  
**BindParam**  
 BindParam, 115  
 iAddr, 115  
**BindRequest**  
 OsclBindMethod, 321  
**black**  
 Oscl\_Rb\_Tree\_Node\_Base, 253  
**BlockingLoopL**  
 OsclExecSchedulerCommonBase, 394  
**bSetFailure**  
 MM\_AllocInfo, 149  
**Buffer**  
 OsclAsyncFileBuffer, 319  
**buffer**  
 CFastRep, 127  
 CHheapRep, 129  
 CStackRep, 131  
**buffer\_states**  
 BufFragGroup, 121  
**BufferFragment**, 116  
**BufferFreeFuncPtr**  
 osclutil, 68  
**BufferMgr**, 117  
**BufferMgr**  
 ~BufferMgr, 117  
 BufferReleased, 117  
**BufferReleased**  
 BufferMgr, 117  
**BufferState**, 118  
 BufferState, 118  
**BufferState**  
 bind, 118  
 BufferState, 118  
 decrement\_refcnt, 118  
 get\_buf\_mgr, 118  
 get\_free\_function, 118

get\_ptr, 118  
 get\_refcount, 118  
 increment\_refcnt, 118  
 reset, 118  
**BuFragGroup**, 119  
     BuFragGroup, 120  
**BuFragGroup**  
     ~BuFragGroup, 120  
     AddFragment, 120  
     AppendNext, 120  
     buffer\_states, 121  
     BuFragGroup, 120  
     Clear, 120  
     fragments, 121  
     GetLength, 120  
     GetMaxFrags, 121  
     GetNext, 121  
     GetNumFrags, 121  
     length, 121  
     next, 121  
     num\_fragments, 121  
**BuFragStatusClass**, 122  
     BFG\_SUCCESS, 122  
     EMPTY\_FRAGMENT, 122  
     FIXED\_FRAG\_LOC\_FULL, 122  
     INTERNAL\_ERROR, 122  
     INVALID\_ID, 122  
     NOT\_ENOUGH\_SPACE, 122  
     NULL\_INPUT, 122  
     TOO\_MANY\_FRAGS, 122  
**BuFragStatusClass**  
     status\_t, 122  
**bufsize**  
     Oscl\_Queue\_Base, 240  
     Oscl\_Vector\_Base, 292  
**BYTES\_IN\_UUID\_ARRAY**  
     oscl\_uuid.h, 799

**c**  
     OsclPriorityQueue, 472

**c\_bool**  
     osclbase, 34

**c\_str**  
     StrPtrLen, 647  
     WStrPtrLen, 658

**Callback**  
     OsclReadyQ, 484

**callback\_timer\_type**  
     OsclTimer, 582

**CallbackTimer**, 123  
     CallbackTimer, 123

**CallbackTimer**  
     ~CallbackTimer, 123  
     CallbackTimer, 123

**Run**, 123  
**CallbackTimer< Alloc >**  
     OsclTimer, 583

**CallbackTimerObserver**, 125

**CallbackTimerObserver**  
     ~CallbackTimerObserver, 125  
     TimerBaseElapsed, 125

**CallRunExec**  
     OsclExecSchedulerCommonBase, 394

**Cancel**  
     OsclActiveObject, 310  
     OsclTimer, 582  
     OsclTimerObject, 586  
     PVActiveBase, 612

**CancelAccept**  
     OsclSocketIBase, 541  
     OsclTCPSocket, 566  
     OsclTCPSocketI, 572

**CancelBind**  
     OsclSocketIBase, 541  
     OsclTCPSocket, 566  
     OsclTCPSocketI, 572

**CancelConnect**  
     OsclSocketIBase, 541  
     OsclTCPSocket, 566  
     OsclTCPSocketI, 572

**CancelFreeChunkAvailableCallback**  
     OsclMemPoolFixedChunkAllocator, 443  
     OsclMemPoolResizableAllocator, 449

**CancelFreeMemoryAvailableCallback**  
     OsclMemPoolResizableAllocator, 449

**CancelFxn**  
     OsclDNSIBase, 355  
     OsclSocketIBase, 541

**CancelGetHostName**  
     OsclDNS, 350  
     OsclDNSIBase, 355

**Cancelled**  
     OsclDNSRequestAO, 363

**CancelListen**  
     OsclSocketIBase, 541  
     OsclTCPSocket, 566  
     OsclTCPSocketI, 572

**CancelMethod**  
     OsclDNSMethod, 358  
     OsclSocketMethod, 545

**CancelRecv**  
     OsclSocketIBase, 541  
     OsclTCPSocket, 566  
     OsclTCPSocketI, 572

**CancelRecvFrom**  
     OsclSocketIBase, 541

OsclUDPSocket, 601  
 OsclUDPSocketI, 607  
**CancelRequest**  
 OsclIDNSRequest, 361  
 OsclSocketRequest, 548  
**CancelSend**  
 OsclSocketIBase, 541  
 OsclTCPSocket, 566  
 OsclTCPSocketI, 572  
**CancelSendTo**  
 OsclSocketIBase, 541  
 OsclUDPSocket, 601  
 OsclUDPSocketI, 607  
**CancelShutdown**  
 OsclSocketIBase, 541  
 OsclTCPSocket, 566  
 OsclTCPSocketI, 572  
**canPersistMoreHostAddresses**  
 GetHostNameParam, 135  
**CanTerminate**  
 OsclThread, 574  
**capacity**  
 Oscl\_Queue\_Base, 239  
 Oscl\_Vector\_Base, 290  
 OsclFileCacheBuffer, 403  
**CFastRep**, 126  
 CFastRep, 127  
**CFastRep**  
 append, 127  
 buffer, 127  
 CFastRep, 127  
 maxsize, 127  
 overwrite, 127  
 set\_r, 127  
 set\_w, 127  
 size, 127  
 writable, 127  
**chartype**  
 OSCL\_FastString, 175  
 OSCL\_HeapString, 196  
 OSCL\_HeapStringA, 198  
 OSCL\_StackString, 257  
 OSCL\_String, 260  
 OSCL\_wFastString, 293  
 OSCL\_wHeapString, 297  
 OSCL\_wHeapStringA, 299  
 OSCL\_wStackString, 302  
 OSCL\_wString, 304  
**CHeapRep**, 128  
 CHeapRep, 129  
**CHeapRep**  
 add\_ref, 129  
 append, 129  
 append\_rep, 129  
 assign, 129  
 buffer, 129  
 CHeapRep, 129  
 maxsize, 129  
 refcount, 129  
 remove\_ref, 129  
 set, 129  
 set\_rep, 129  
 size, 129  
**check\_fence**  
 MM\_AllocBlockFence, 146  
**check\_list**  
 Oscl\_Linked\_List, 206  
 Oscl\_Linked\_List\_Base, 211  
**checkSum**  
 StrCSumPtrLen, 644  
**CheckSumType**  
 StrCSumPtrLen, 644  
**children**  
 Oscl\_TagTree::Node, 279  
**children\_type**  
 Oscl\_TagTree, 269  
 Oscl\_TagTree::Node, 279  
**ChooseCurCache**  
 Oscl\_File::OsclCacheObserver, 186  
**CleanInUse**  
 OsclAsyncFileBuffer, 319  
**Cleanup**  
 OsclErrorTrap, 375  
 OsclInit, 414  
 OsclMem, 424  
 OsclScheduler, 515  
 PVLogger, 618  
**CleanupExecQ**  
 OsclExecSchedulerCommonBase, 394  
**CleanupParam**  
 OsclSocketRequestAO, 550  
**CleanupStatQ**  
 OsclExecSchedulerCommonBase, 394  
**Clear**  
 BufFragGroup, 120  
 MediaData, 142  
 OsclTimer, 582  
**clear**  
 Oscl\_Linked\_List, 206  
 Oscl\_Map, 218  
 Oscl\_Queue, 236  
 Oscl\_Queue\_Base, 239  
 Oscl\_Rb\_Tree, 243  
 Oscl\_TagTree, 270  
 Oscl\_Vector, 286  
**ClearTOS**  
 OsclSocketTOS, 563  
**Close**

Oscl\_File, 180  
 Oscl\_FileFind, 189  
 Oscl\_FileServer, 192  
 OsclAsyncFile, 316  
 OsclDNSI, 352  
 OsclDNSIBase, 355  
 OsclFileCache, 401  
 OsclIPSocketI, 418  
 OsclMutex, 458  
 OsclNativeFile, 462  
 OsclRegistryAccessClient, 503  
 OsclRegistryClient, 508  
 OsclRegistryClientImpl, 511  
 OsclRegistryServTlsImpl, 514  
 OsclSemaphore, 520  
 OsclSocketI, 535  
 OsclSocketIBase, 541  
 OsclSocketServ, 553  
 OsclSocketServI, 555  
 OsclSocketServIBase, 558  
 OsclSocketServRequestList, 559  
 OsclTCPSocket, 567  
 OsclTCPSocketI, 572  
 OsclUDPSocket, 602  
 OsclUDPSocketI, 607  
**CloseSession**  
 OsclComponentRegistry, 343  
**color**  
 Oscl\_Rb\_Tree\_Node\_Base, 254  
**color\_type**  
 Oscl\_Rb\_Tree\_Node\_Base, 253  
**comp**  
 Oscl\_Map::value\_compare, 222  
 OsclPriorityQueue, 472  
**compare**  
 OsclCompareLess, 341  
 OsclReadyCompare, 482  
 OsclTimerCompare, 584  
**compare\_data**  
 Oscl\_Opaque\_Type\_Alloc\_LL, 230  
**compare\_EQ**  
 Oscl\_Opaque\_Type\_Compare, 232  
 OsclPriorityQueue, 470  
**compare\_LT**  
 Oscl\_Opaque\_Type\_Compare, 232  
 OsclPriorityQueue, 470  
**CompareId**  
 OsclThread, 575  
**Complete**  
 OsclDNSRequest, 361  
 OsclSocketRequest, 548  
**COMPUTE\_MEM\_ALIGN\_SIZE**  
 osclmemory, 50  
**Connect**  
 Oscl\_FileServer, 192  
 OsclConnectMethod, 347  
 OsclConnectRequest, 348  
 OsclRegistryAccessClient, 503  
 OsclRegistryClient, 508  
 OsclRegistryClientImpl, 511  
 OsclRegistryServTlsImpl, 514  
 OsclSocketI, 535  
 OsclSocketIBase, 541  
 OsclSocketServ, 553  
 OsclSocketServI, 555  
 OsclSocketServIBase, 558  
 OsclTCPSocket, 567  
 OsclTCPSocketI, 572  
 ConnectParam, 130  
 ConnectParam, 130  
**ConnectParam**  
 ConnectParam, 130  
 iAddr, 130  
**ConnectRequest**  
 OsclConnectMethod, 347  
**const\_iterator**  
 Oscl\_Map, 217  
 Oscl\_Rb\_Tree, 243  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_TagTree::const\_iterator, 273  
 Oscl\_Vector, 285  
**const\_pointer**  
 Oscl\_Rb\_Tree, 243  
 Oscl\_TAlloc, 281  
**const\_reference**  
 Oscl\_Map, 217  
 Oscl\_Queue, 236  
 Oscl\_Rb\_Tree, 243  
 Oscl\_TAlloc, 281  
 Oscl\_Vector, 285  
 OsclPriorityQueue, 470  
**Construct**  
 OsclReadyQ, 484  
 OsclTimerQ, 590  
**construct**  
 Oscl\_Linked\_List\_Base, 211  
 Oscl\_Opaque\_Type\_Alloc, 228  
 Oscl\_Opaque\_Type\_Alloc\_LL, 230  
 Oscl\_Queue\_Base, 239  
 Oscl\_TAlloc, 281  
 Oscl\_Vector\_Base, 290  
 OsclPriorityQueueBase, 473  
**ConstructL**  
 OsclDNSMethod, 358  
 OsclDNSRequestAO, 363  
 OsclExecSchedulerCommonBase, 394  
 OsclIPSocketI, 418  
 OsclSocketMethod, 545

OsclSocketRequestAO, 550  
 ConstructStatQ  
   OsclExecSchedulerCommonBase, 394  
 container\_type  
   OsclPriorityQueue, 470  
 Contains  
   Oscl\_File::OsclFixedCacheParam, 187  
   OsclFileCacheBuffer, 403  
 count  
   Oscl\_Map, 218  
   Oscl\_Rb\_Tree, 243  
   Oscl\_TagTree, 270  
 CPVInterfaceProxy  
   OsclErrorTrapImp, 377  
 Create  
   GetHostNameParam, 135  
   OsclMutex, 458  
   OsclSemaphore, 520  
   OsclThread, 575  
 createmempool  
   OsclMemPoolFixedChunkAllocator, 443  
 CreatePVLogger  
   PVLoggerRegistry, 628  
 createStatsNode  
   MM\_Audit\_Imp, 153  
 CStackRep, 131  
   CStackRep, 131  
 CStackRep  
   append, 131  
   buffer, 131  
   CStackRep, 131  
   maxsize, 131  
   set, 131  
   size, 131  
 CTIME\_BUFFER\_SIZE  
   osclbase, 45  
 CtimeStrBuf  
   osclbase, 34  
 Current  
   OsclExecScheduler, 388  
 currentPos  
   OsclFileCacheBuffer, 403  
  
 data  
   LinkedListElement, 139  
 data1  
   OsclUuid, 610  
 data2  
   OsclUuid, 610  
 data3  
   OsclUuid, 610  
 data4  
   OsclUuid, 610  
 deallocate  
  
   \_OsclBasicAllocator, 108  
   MemAllocator, 145  
   Oscl\_Dealloc, 170  
   Oscl\_DefAlloc, 171  
   Oscl\_Opaque\_Type\_Alloc, 228  
   Oscl\_Opaque\_Type\_Alloc\_LL, 230  
   Oscl\_TAlloc, 281  
   OsclErrorAllocator, 373  
   OsclMemAllocator, 425  
   OsclMemAllocDestructDealloc, 426  
   OSCLMemAutoPtr, 436  
   OsclMemBasicAllocator, 438  
   OsclMemBasicAllocDestructDealloc, 439  
   OsclMemPoolFixedChunkAllocator, 444  
   OsclMemPoolResizableAllocator, 449  
   OsclReadyAlloc, 481  
 deallocateblock  
   OsclMemPoolResizableAllocator, 449  
 decrement\_refcnt  
   BufferState, 118  
 DEFAULT\_MM\_AUDIT\_MODE  
   osclmemory, 51  
 DEFAULT\_POSTFILL\_PATTERN  
   osclmemory, 51  
 DEFAULT\_PREFILL\_PATTERN  
   osclmemory, 51  
 Delete  
   Oscl\_DefAllocWithRefCounter, 172  
   OsclAsyncFile, 316  
   OsclBuf, 340  
 Depth  
   OsclReadyQ, 484  
 depth  
   Oscl\_TagTree::Node, 279  
 dequeue\_element  
   Oscl\_Linked\_List, 206  
   Oscl\_MTLLinked\_List, 225  
 Des  
   OsclBuf, 340  
 DesC  
   OsclBuf, 340  
 Destroy  
   DNSRequestParam, 132  
   GetHostNameParam, 135  
   PVActiveBase, 612  
 destroy  
   Oscl\_Linked\_List\_Base, 211  
   Oscl\_Opaque\_Type\_Alloc, 228  
   Oscl\_Opaque\_Type\_Alloc\_LL, 231  
   Oscl\_Queue\_Base, 239  
   Oscl\_TAlloc, 281  
   Oscl\_Vector, 286  
   Oscl\_Vector\_Base, 290  
 destroyallmempoolbuffers

OsclMemPoolResizableAllocator, 449  
 destroymempool  
   OsclMemPoolFixedChunkAllocator, 444  
 destruct\_and\_dealloc  
   Oscl\_TAlloc, 281  
   OsclDestructDealloc, 349  
   OsclMemAllocDestructDealloc, 426  
   OsclMemBasicAllocDestructDealloc, 439  
 difference\_type  
   Oscl\_Rb\_Tree, 243  
 DIR\_TYPE  
   Oscl\_FileFind, 188  
 DisableAppenderInheritance  
   PVLogger, 618  
 DiscardAcceptedSocket  
   OsclAcceptMethod, 307  
 DNSRequestParam, 132  
   DNSRequestParam, 132  
   OsclIDNSI, 353  
 DNSRequestParam  
   ~DNSRequestParam, 132  
   Destroy, 132  
   DNSRequestParam, 132  
   iDNSRequest, 133  
   iFxn, 133  
   InThread, 132  
   iRefCount, 133  
   RemoveRef, 133  
 DoCancel  
   OsclActiveObject, 311  
   OsclIDNSRequestAO, 363  
   OsclSocketRequestAO, 550  
   OsclTimerObject, 586  
   PVActiveBase, 612  
  
 E\_BUFFER\_TOO\_SMALL  
   Oscl\_FileFind, 189  
 E\_INVALID\_ARG  
   Oscl\_FileFind, 188  
 E\_INVALID\_STATE  
   Oscl\_FileFind, 188  
 E\_MEMORY\_ERROR  
   Oscl\_FileFind, 189  
 E\_NO\_MATCH  
   Oscl\_FileFind, 189  
 E\_NOT\_IMPLEMENTED  
   Oscl\_FileFind, 189  
 E\_OK  
   Oscl\_FileFind, 188  
 E\_OTHER  
   Oscl\_FileFind, 189  
 E\_PATH\_NOT\_FOUND  
   Oscl\_FileFind, 188  
 E\_PATH\_TOO\_LONG

Oscl\_FileFind, 188  
 element\_type  
   Oscl\_FileFind, 188  
 elems  
   Oscl\_Queue\_Base, 240  
   Oscl\_Vector\_Base, 292  
 empty  
   Oscl\_Map, 218  
   Oscl\_Queue\_Base, 239  
   Oscl\_Rb\_Tree, 243  
   Oscl\_TagTree, 270  
   Oscl\_Vector\_Base, 290  
   OsclPriorityQueue, 471  
 EMPTY\_FRAGMENT  
   BuffFragStatusClass, 122  
 EMPTY\_UUID  
   oscl\_uuid.h, 799  
 enablenullpointerreturn  
   OsclMemPoolFixedChunkAllocator, 444  
   OsclMemPoolResizableAllocator, 449  
 End  
   OsclFileStats, 410  
 end  
   Oscl\_Map, 218  
   Oscl\_Rb\_Tree, 243  
   Oscl\_TagTree, 270  
   Oscl\_Vector, 286  
 EndOfFile  
   Oscl\_File, 180  
   OsclAsyncFile, 316  
   OsclFileCache, 401  
   OsclNativeFile, 462  
 endPos  
   OsclFileCacheBuffer, 403  
 EndScheduling  
   OsclExecSchedulerCommonBase, 394  
 EndStats  
   OsclExecSchedulerCommonBase, 394  
 EnterThreadContext  
   PVThreadContext, 633  
 eof  
   OsclBinStream, 336  
 EOF\_STATE  
   OsclBinStream, 336  
 EOSCL\_StringOp\_CompressASCII  
   osclutil, 69  
 EOSCL\_StringOp\_UTF16ToUTF8  
   osclutil, 69  
 EOSCL\_wStringOp\_ExpandASCII  
   osclutil, 69  
 EOSCL\_wStringOp\_UTF8ToUTF16  
   osclutil, 69  
 EOscFileOp\_Close  
   osclio, 97

EOscIFileOp\_EndOfFile  
     osclio, [97](#)  
 EOscIFileOp\_Flush  
     osclio, [97](#)  
 EOscIFileOp\_Last  
     osclio, [98](#)  
 EOscIFileOp\_NativeClose  
     osclio, [97](#)  
 EOscIFileOp\_NativeEndOfFile  
     osclio, [98](#)  
 EOscIFileOp\_NativeFlush  
     osclio, [98](#)  
 EOscIFileOp\_NativeOpen  
     osclio, [97](#)  
 EOscIFileOp\_NativeRead  
     osclio, [97](#)  
 EOscIFileOp\_NativeSeek  
     osclio, [98](#)  
 EOscIFileOp\_NativeSetSize  
     osclio, [98](#)  
 EOscIFileOp\_NativeSize  
     osclio, [98](#)  
 EOscIFileOp\_NativeTell  
     osclio, [98](#)  
 EOscIFileOp\_NativeWrite  
     osclio, [98](#)  
 EOscIFileOp\_Open  
     osclio, [97](#)  
 EOscIFileOp\_Read  
     osclio, [97](#)  
 EOscIFileOp\_Seek  
     osclio, [97](#)  
 EOscIFileOp\_SetSize  
     osclio, [97](#)  
 EOscIFileOp\_Size  
     osclio, [97](#)  
 EOscIFileOp\_Tell  
     osclio, [97](#)  
 EOscIFileOp\_Write  
     osclio, [97](#)  
 eOsclProcError  
     OsclProcStatus, [474](#)  
 EOscISocket\_DataRecv  
     oscl\_socket\_stats.h, [771](#)  
 EOscISocket\_DataSent  
     oscl\_socket\_stats.h, [771](#)  
 EOscISocket\_Except  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_OS  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_Readable  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_RequestAO\_Canceled  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_RequestAO\_Error  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_RequestAO\_Success  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_RequestAO\_Timeout  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_ServPoll  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_ServRequestCancelIssued  
     oscl\_socket\_stats.h, [771](#)  
 EOscISocket\_ServRequestComplete  
     oscl\_socket\_stats.h, [771](#)  
 EOscISocket\_ServRequestIssued  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocket\_Writable  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocketServ\_LastEvent  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocketServ\_LoopsockError  
     oscl\_socket\_stats.h, [771](#)  
 EOscISocketServ\_LoopsockOk  
     oscl\_socket\_stats.h, [771](#)  
 EOscISocketServ\_SelectActivity  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocketServ\_SelectNoActivity  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocketServ\_SelectRescheduleAsap  
     oscl\_socket\_stats.h, [770](#)  
 EOscISocketServ\_SelectReschedulePoll  
     oscl\_socket\_stats.h, [770](#)  
 EOscIThreadTerminate\_Join  
     oscl\_thread.h, [789](#)  
 EOscIThreadTerminate\_Kill  
     oscl\_thread.h, [789](#)  
 EOscIThreadTerminate\_NOP  
     oscl\_thread.h, [789](#)  
 EOtherExecStats\_Last  
     OsclExecSchedulerCommonBase, [393](#)  
 EOtherExecStats\_NativeOS  
     OsclExecSchedulerCommonBase, [393](#)  
 EOtherExecStats\_QueueTime  
     OsclExecSchedulerCommonBase, [393](#)  
 EOtherExecStats\_ReleaseTime  
     OsclExecSchedulerCommonBase, [393](#)  
 EOtherExecStats\_WaitTime  
     OsclExecSchedulerCommonBase, [393](#)  
 EPriorityHigh  
     OsclActiveObject, [310](#)  
 EPriorityHighest  
     OsclActiveObject, [310](#)  
 EPriorityIdle  
     OsclActiveObject, [310](#)  
 EPriorityLow  
     OsclActiveObject, [310](#)

EPriorityNominal  
     OsclActiveObject, 310  
 EPVCritic\_Ecp  
     OsclSocketTOS, 562  
 EPVDNSCancel  
     osclio, 98  
 EPVDNSFailure  
     osclio, 98  
 EPVDNSGetHostByName  
     osclio, 98  
 EPVDNSPending  
     osclio, 98  
 EPVDNSSuccess  
     osclio, 98  
 EPVDNSTimeout  
     osclio, 98  
 EPVFlash  
     OsclSocketTOS, 562  
 EPVHiRel  
     OsclSocketTOS, 562  
 EPVHiThrpt  
     OsclSocketTOS, 562  
 EPVImmediate  
     OsclSocketTOS, 562  
 EPVInetControl  
     OsclSocketTOS, 562  
 EPVIPAddMembership  
     oscl\_socket\_types.h, 775  
 EPVIMulticastTTL  
     oscl\_socket\_types.h, 775  
 EPVIPProtoIP  
     oscl\_socket\_types.h, 775  
 EPVIPProtoTCP  
     oscl\_socket\_types.h, 775  
 EPVIPTOS  
     oscl\_socket\_types.h, 775  
 EPVLDelay  
     OsclSocketTOS, 562  
 EPVNetControl  
     OsclSocketTOS, 562  
 EPVNoTOS  
     OsclSocketTOS, 562  
 EPVOverrideFlash  
     OsclSocketTOS, 562  
 EPVPriority  
     OsclSocketTOS, 562  
 EPVRoutine  
     OsclSocketTOS, 562  
 EPVSocket  
     oscl\_socket\_types.h, 775  
 EPVSocket\_Last  
     oscl\_socket\_types.h, 775  
 EPVSocketAccept  
     oscl\_socket\_types.h, 775  
 EPVSocketBind  
     oscl\_socket\_types.h, 775  
 EPVSocketBothShutdown  
     oscl\_socket\_types.h, 775  
 EPVSocketCancel  
     oscl\_socket\_types.h, 774  
 EPVSocketConnect  
     oscl\_socket\_types.h, 775  
 EPVSocketFailure  
     oscl\_socket\_types.h, 774  
 EPVSocketListen  
     oscl\_socket\_types.h, 775  
 EPVSocketNotImplemented  
     oscl\_socket\_types.h, 775  
 EPVSocketPending  
     oscl\_socket\_types.h, 774  
 EPVSocketRecv  
     oscl\_socket\_types.h, 775  
 EPVSocketRecvFrom  
     oscl\_socket\_types.h, 775  
 EPVSocketRecvShutdown  
     oscl\_socket\_types.h, 775  
 EPVSocketSend  
     oscl\_socket\_types.h, 775  
 EPVSocketSendShutdown  
     oscl\_socket\_types.h, 775  
 EPVSocketSendTo  
     oscl\_socket\_types.h, 775  
 EPVSocketShutdown  
     oscl\_socket\_types.h, 775  
 EPVSocketSuccess  
     oscl\_socket\_types.h, 774  
 EPVSocketTimeout  
     oscl\_socket\_types.h, 774  
 EPVSockReuseAddr  
     oscl\_socket\_types.h, 775  
 EPVThreadContext\_InThread  
     osclproc, 105  
 EPVThreadContext\_NonOsclThread  
     osclproc, 105  
 EPVThreadContext\_OsclThread  
     osclproc, 105  
 EPVThreadContext\_Undetermined  
     osclproc, 105  
 equal\_range  
     Oscl\_Map, 218  
     Oscl\_Rb\_Tree, 243  
 erase  
     Oscl\_Map, 219  
     Oscl\_Rb\_Tree, 243  
     Oscl\_TagTree, 270  
     Oscl\_Vector, 286  
     Oscl\_Vector\_Base, 290, 291  
 Error

OsclExecSchedulerCommonBase, 394  
 error\_type  
   Oscl\_FileFind, 188  
 ESocketServ\_Connected  
   OsclSocketServIBase, 557  
 ESocketServ\_Error  
   OsclSocketServIBase, 558  
 ESocketServ\_Idle  
   OsclSocketServIBase, 557  
 ESymbianAccessMode\_Rfile  
   Oscl\_File, 179  
 ESymbianAccessMode\_RfileBuf  
   Oscl\_File, 179  
 EXCEED\_MAX\_COUNT\_VARIABLE\_-  
   ERROR  
   OsclProcStatus, 475  
 EXCEED\_MAX\_SEM\_COUNT\_ERROR  
   OsclProcStatus, 475  
 Exit  
   OsclThread, 575  
 ExitThreadContext  
   PVThreadContext, 633  
 extract\_string  
   osclutil, 69  
  
 fail  
   OsclBinStream, 337  
 FAIL\_STATE  
   OsclBinStream, 336  
 Failure  
   OsclDNSRequestAO, 363  
 FENCE\_PATTERN  
   osclmemory, 51  
 FILE\_TYPE  
   Oscl\_FileFind, 188  
 fileName  
   MM\_AllocQueryInfo, 151  
 filePosition  
   OsclFileCacheBuffer, 403  
 FileSize  
   OsclFileCache, 401  
 fill\_fence  
   MM\_AllocBlockFence, 146  
 FillFromFile  
   OsclFileCacheBuffer, 403  
 filter\_status\_type  
   AllPassFilter, 113  
   PVLogger, 617  
   PVLoggerFilter, 623  
 FilterOpaqueMessge  
   AllPassFilter, 114  
   PVLoggerFilter, 624  
 FilterString  
   AllPassFilter, 114  
  
 PVLoggerFilter, 624  
 Find  
   OsclComponentRegistryData, 344  
 find  
   Oscl\_Map, 219  
   Oscl\_Rb\_Tree, 243  
   Oscl\_TagTree, 270  
 find\_heap  
   OsclPriorityQueue, 471  
   OsclPriorityQueueBase, 473  
 FindExact  
   OsclComponentRegistry, 343  
 FindFirst  
   Oscl\_FileFind, 189  
 findfreeblock  
   OsclMemPoolResizableAllocator, 450  
 FindHierarchical  
   OsclComponentRegistry, 343  
 FindNext  
   Oscl\_FileFind, 190  
 FindPVBase  
   OsclExecSchedulerCommonBase, 394  
 first  
   Oscl\_Pair, 234  
 firstFragPtr  
   OsclBinStream, 338  
 FIXED\_FRAG\_LOC\_FULL  
   BuffFragStatusClass, 122  
 Flush  
   Oscl\_File, 181  
   OsclAsyncFile, 316  
   OsclFileCache, 401  
   OsclNativeFile, 462  
 FormatOpaqueMessage  
   PVLoggerLayout, 625  
 FormatString  
   PVLoggerLayout, 625  
 fragments  
   BuffFragGroup, 121  
 fragsLeft  
   OsclBinStream, 338  
 freeblockavailable  
   OsclMemPoolResizableAllocatorObserver,  
     456  
 freebytes  
   oscl\_fsstat, 194  
 freechunkavailable  
   OsclMemPoolFixedChunkAllocator-  
     Observer, 446  
 freememoryavailable  
   OsclMemPoolResizableAllocatorMemory-  
     Observer, 455  
 front  
   Oscl\_Queue, 237

---

Oscl\_Vector, 287  
**Fxn**  
 OsclSocketRequest, 548  
  
**get**  
 OsclBinIStream, 323  
 OsclExclusiveArrayPtr, 380  
 OsclExclusivePtr, 383  
 OsclExclusivePtrA, 386  
 OSCLMemAutoPtr, 436  
 get\_buf\_mgr  
     BufferState, 118  
 get\_count  
     OsclSharedPtr, 527  
 get\_cstr  
     OSCL\_FastString, 176  
     OSCL\_HeapStringA, 199  
     OSCL\_String, 260  
     OSCL\_wFastString, 294  
     OSCL\_wHeapStringA, 299  
     OSCL\_wString, 304  
     osclutil, 69  
 get\_data  
     Oscl\_Opaque\_Type\_Alloc\_LL, 231  
 get\_element  
     Oscl\_Linked\_List, 206  
     Oscl\_Linked\_List\_Base, 211  
     Oscl\_MTLLinked\_List, 225  
 get\_first  
     Oscl\_Linked\_List, 207  
     Oscl\_Linked\_List\_Base, 212  
 get\_free\_function  
     BufferState, 118  
 get\_index  
     Oscl\_Linked\_List, 207  
     Oscl\_Linked\_List\_Base, 212  
     Oscl\_MTLLinked\_List, 225  
 get\_int64\_lower32  
     Oscl\_Int64\_Utils, 203  
 get\_int64\_middle32  
     Oscl\_Int64\_Utils, 203  
 get\_int64\_upper32  
     Oscl\_Int64\_Utils, 203  
 get\_ISO8601\_str\_time  
     TimeValue, 651  
 get\_local\_time  
     TimeValue, 651  
 get\_lower32  
     NTPTime, 167  
 get\_maxsize  
     OSCL\_FastString, 176  
     OSCL\_HeapStringA, 199  
     OSCL\_String, 260  
     OSCL\_wFastString, 294  
  
 OSCL\_wHeapStringA, 299  
 OSCL\_wString, 304  
 osclutil, 70  
 get\_next  
     Oscl\_Linked\_List, 207  
     Oscl\_Linked\_List\_Base, 212  
     Oscl\_Opaque\_Type\_Alloc\_LL, 231  
 get\_num\_elements  
     Oscl\_Linked\_List, 207  
 get\_ptr  
     BufferState, 118  
 get\_pv8601\_str\_time  
     TimeValue, 651  
 get\_refcount  
     BufferState, 118  
 get\_registry  
     TLSStorageOps, 655  
 get\_rfc822\_gmtime\_str  
     TimeValue, 651  
 get\_sec  
     TimeValue, 652  
 get\_size  
     OSCL\_FastString, 176  
     OSCL\_HeapStringA, 200  
     OSCL\_String, 261  
     OSCL\_wFastString, 294  
     OSCL\_wHeapStringA, 299  
     OSCL\_wString, 304  
     osclutil, 70  
 get\_str  
     OSCL\_FastString, 176  
     OSCL\_HeapStringA, 200  
     OSCL\_String, 261  
     OSCL\_wFastString, 294  
     OSCL\_wHeapStringA, 300  
     OSCL\_wString, 304  
     osclutil, 71  
 get\_str\_ctime  
     TimeValue, 652  
 get\_timeval\_ptr  
     TimeValue, 652  
 get\_timevalue\_in\_usec  
     TimeValue, 652  
 get\_uint64\_lower32  
     Oscl\_Int64\_Utils, 203  
 get\_uint64\_middle32  
     Oscl\_Int64\_Utils, 203  
 get\_uint64\_upper32  
     Oscl\_Int64\_Utils, 203  
 get\_upper32  
     NTPTime, 167  
 get\_usec

TimeValue, 652  
 get\_value  
     NTPTime, 167  
 GetAcceptedSocket  
     OsclAcceptMethod, 307  
 GetAcceptedSocketL  
     OsclTCPSocket, 567  
     OsclTCPSocketI, 572  
 getAllocatedSize  
     OsclMemPoolResizableAllocator, 450  
 getAuditRoot  
     MM\_Audit\_Imp, 153  
 GetAvailableBufferSize  
     MediaData, 142  
 getAvailableSize  
     OsclMemPoolResizableAllocator, 450  
 getBufferSize  
     OsclMemPoolResizableAllocator, 450  
 GetBufferState  
     osclutil, 71  
 getCapacity  
     OsclRefCounterMemFrag, 496  
 getCheckSum  
     StrCSumPtrLen, 644  
 getCount  
     Oscl\_DefAllocWithRefCounter, 172  
     OsclRefCounter, 491  
     OsclRefCounterDA, 494  
     OsclRefCounterMemFrag, 496  
     OsclRefCounterMTDA, 498  
     OsclRefCounterMTSA, 500  
     OsclRefCounterSA, 502  
 GetElementType  
     Oscl\_FileFind, 190  
 GetError  
     Oscl\_File, 181  
     OsclNativeFile, 462  
 GetErrorTrapImp  
     OsclErrorTrap, 375  
 GetFactories  
     OsclRegistryAccessClient, 503  
     OsclRegistryClientImpl, 511  
     OsclRegistryServTlsImpl, 514  
 GetFactory  
     OsclRegistryAccessClient, 503  
     OsclRegistryClientImpl, 511  
     OsclRegistryServTlsImpl, 514  
 GetFragment  
     osclutil, 71  
 getGlobalMemAuditObject  
     OsclMemGlobalAuditObject, 440  
 getHead  
     OsclDoubleListBase, 368  
 GetHostName

OsclDNS, 351  
 OsclDNSI, 352  
 OsclDNSIBase, 355  
 OsclGetHostByNameMethod, 412  
 GetHostByNameParam, 134  
     addressListCapacity, 134  
     OsclDNSRequestAO, 364  
 GetHostByNameParam  
     ~GetHostByNameParam, 135  
     canPersistMoreHostAddresses, 135  
     Create, 135  
     Destroy, 135  
     iAddr, 135  
     iAddressList, 135  
     iName, 135  
     PersistHostAddress, 135  
 GetHostByNameResponseContainsAliasInfo  
     OsclDNSI, 353  
     OsclDNSIBase, 355  
 GetHostByNameSuccess  
     OsclDNSI, 353  
     OsclDNSIBase, 355  
 GetId  
     OsclExecSchedulerCommonBase, 394  
     OsclThread, 575  
 getInstance  
     OsclSingletonRegistry, 533  
     OsclTLSRegistry, 595  
     OsclTLSRegistryEx, 596  
 getLargestContiguousFreeBlockSize  
     OsclMemPoolResizableAllocator, 450  
 GetLastError  
     Oscl\_FileFind, 190  
 getLeaveCode  
     OsclException, 378  
 GetLength  
     BufFragGroup, 120  
 GetLocalBufsize  
     MediaData, 143  
 GetLocalFragment  
     MediaData, 143  
 GetLock  
     OsclMemAudit, 429  
 GetLoggerObject  
     PVLogger, 618  
 GetLogLevel  
     PVLogger, 618  
 GetMaxFrags  
     BufFragGroup, 121  
 GetMediaFragment  
     MediaData, 143  
 GetMediaSize  
     MediaData, 143  
 getMemFrag

OsclRefCounterMemFrag, 496  
 getMemFragPtr  
   OsclRefCounterMemFrag, 496  
 getMemFragSize  
   OsclRefCounterMemFrag, 496  
 getMemPoolBufferAllocatedSize  
   OsclMemPoolResizableAllocator, 450  
 getMemPoolBufferSize  
   OsclMemPoolResizableAllocator, 450  
 GetName  
   OsclExecSchedulerCommonBase, 394  
 GetNext  
   BufFragGroup, 121  
 GetNextHost  
   OsclIDNSI, 353  
   OsclIDNSIBase, 355  
 GetNextHostSuccess  
   OsclIDNSI, 353  
   OsclIDNSIBase, 355  
 GetNumAppenders  
   PVLogger, 618  
 GetNumFrags  
   BufFragGroup, 121  
 GetNumMediaFrags  
   MediaData, 143  
 getOffset  
   OsclDoubleListBase, 368  
 GetParent  
   PVLogger, 619  
 GetPeerName  
   OsclIPSocketI, 418  
   OsclSocketI, 535  
   OsclTCPSocket, 567  
   OsclUDPSocket, 602  
 GetPriority  
   OsclThread, 576  
 GetPVLoggerObject  
   PVLoggerRegistry, 628  
 GetPVLoggerRegistry  
   PVLoggerRegistry, 628  
 GetReadAsyncNumElements  
   OsclNativeFile, 462  
 GetRecvData  
   OsclIPSocketI, 418  
   OsclRecvFromMethod, 485  
   OsclRecvFromRequest, 487  
   OsclRecvMethod, 489  
   OsclRecvRequest, 490  
   OsclTCPSocket, 568  
   OsclTCPSocketI, 572  
   OsclUDPSocket, 602  
   OsclUDPSocketI, 607  
 GetRefCounter  
   OsclSharedPtr, 527  
 getRefCounter  
   OsclRefCounterMemFrag, 496  
 GetRep  
   OsclSharedPtr, 527  
 GetScheduler  
   OsclExecSchedulerCommonBase, 394  
 GetSendData  
   OsclIPSocketI, 418  
   OsclSendMethod, 522  
   OsclSendRequest, 523  
   OsclSendToMethod, 524  
   OsclSendToRequest, 525  
   OsclTCPSocket, 568  
   OsclTCPSocketI, 572  
   OsclUDPSocket, 602  
   OsclUDPSocketI, 607  
 GetShutdown  
   OsclSocketIBase, 541  
 getSize  
   MM\_Audit\_Imp, 153  
 GetSocketError  
   OsclDNSRequestAO, 363  
   OsclSocketRequestAO, 550  
 getTagActualSize  
   MM\_Audit\_Imp, 153  
 GetTimestamp  
   MediaData, 143  
 GetTOS  
   OsclSocketTOS, 563  
 good  
   OsclBinStream, 337  
 GOOD\_STATE  
   OsclBinStream, 336  
 Handle  
   Oscl\_File, 181  
   OsclFileHandle, 404  
 HandleDNSEvent  
   OsclDNSObserver, 360  
 HandleSocketEvent  
   OsclSocketObserver, 547  
 HasAsyncBind  
   OsclSocketIBase, 541  
 HasAsyncListen  
   OsclSocketIBase, 541  
 HasAsyncRead  
   OsclNativeFile, 462  
 hash  
   OSCL\_String, 261  
   OSCL\_wString, 304  
 HasThisOffset  
   OsclAsyncFileBuffer, 319  
 HaveRoomInCurrentBlock  
   OsclBinStream, 337

**Head**  
 OsclDoubleList, 366  
 OsclPriorityList, 468

**head**  
 Oscl\_Linked\_List\_Base, 214

**HeapBase**, 136  
 HeapBase, 137

**HeapBase**  
 ~HeapBase, 137  
 HeapBase, 137

**host\_to\_big\_endian**  
 osclbase, 35

**host\_to\_little\_endian**  
 osclbase, 36

**iActive**  
 OsclDNSRequest, 361

**iAddedNum**  
 PVActiveBase, 614

**iAddr**  
 BindParam, 115  
 ConnectParam, 130  
 GetHostNameParam, 135  
 RecvFromParam, 635  
 SendToParam, 639

**iAddress**  
 OsclIPSocketI, 419

**iAddressList**  
 GetHostNameParam, 135

**iAlloc**  
 OsclDNSIBase, 356  
 OsclDNSMethod, 359  
 OsclExecSchedulerCommonBase, 398  
 OsclIPSocketI, 419  
 OsclSocketIBase, 543  
 OsclSocketServIBase, 558

**iAllocatedSz**  
 OsclMemPoolResizableAllocator::MemPoolBufferInfo, 454

**iAOPriority**  
 TReadyQueLink, 656

**iAsyncReadBufferSize**  
 OsclNativeFileParams, 464

**iBlankSocket**  
 AcceptParam, 111

**iBlockBuffer**  
 OsclMemPoolResizableAllocator::MemPoolBlockInfo, 453

**iBlockInfoAlignedSize**  
 OsclMemPoolResizableAllocator, 452

**iBlockingMode**  
 OsclExecSchedulerCommonBase, 398

**iBlockPostFence**

**OsclMemPoolResizableAllocator::MemPoolBlockInfo**, 453

**iBlockPreFence**  
 OsclMemPoolResizableAllocator::MemPoolBlockInfo, 453

**iBlockSize**  
 OsclMemPoolResizableAllocator::MemPoolBlockInfo, 453

**iBuffer**  
 OsclBuf, 340

**iBufferInfoAlignedSize**  
 OsclMemPoolResizableAllocator, 452

**iBufferPostFence**  
 OsclMemPoolResizableAllocator::MemPoolBufferInfo, 454

**iBufferPreFence**  
 OsclMemPoolResizableAllocator::MemPoolBufferInfo, 454

**iBufferSize**  
 OsclMemPoolResizableAllocator::MemPoolBufferInfo, 454

**iBufRecv**  
 RecvFromParam, 635  
 RecvParam, 637

**iBufSend**  
 SendParam, 638  
 SendToParam, 639

**iBusy**  
 PVActiveBase, 614

**iCancel**  
 OsclSocketServRequestQElem, 561

**iCBase**  
 OsclTrapStackItem, 599

**iCheckFreeMemoryAvailable**  
 OsclMemPoolResizableAllocator, 452

**iCheckNextAvailable**  
 OsclMemPoolResizableAllocator, 452

**iCheckNextAvailableFreeChunk**  
 OsclMemPoolFixedChunkAllocator, 445

**iChunkAlignment**  
 OsclMemPoolFixedChunkAllocator, 445

**iChunkSize**  
 OsclMemPoolFixedChunkAllocator, 445

**iChunkSizeMemAligned**  
 OsclMemPoolFixedChunkAllocator, 445

**iComponentId**  
 OsclComponentRegistryElement, 345

**iComponentIdCounter**  
 OsclComponentRegistry, 343

**iContainer**  
 OsclFileCacheBuffer, 403  
 OsclSocketMethod, 546  
 OsclSocketRequestAO, 552

**Id**

OsclAsyncFileBuffer, 319  
 OsclSocketRequestAO, 551  
 PVThreadContext, 633  
**iData**  
 OsclComponentRegistry, 343  
**iDebugLogger**  
 OsclExecSchedulerCommonBase, 398  
**iDefAlloc**  
 OsclExecSchedulerCommonBase, 398  
**iDelta**  
 OsclExecSchedulerCommonBase, 398  
**iDNSFxn**  
 OsclIDNSMethod, 359  
**iDNSI**  
 OsclDNSRequestAO, 364  
**iDNSMethod**  
 OsclDNSRequestAO, 364  
**iDNSObserver**  
 OsclIDNSMethod, 359  
**iDNSRequest**  
 DNSRequestParam, 133  
**iDNSRequestAO**  
 OsclIDNSMethod, 359  
 OsclDNSRequest, 361  
**iDNSRequestParam**  
 OsclDNSRequest, 361  
**iDoStop**  
 OsclExecSchedulerCommonBase, 398  
**iDoSuspend**  
 OsclExecSchedulerCommonBase, 398  
**iEnableNullPtrReturn**  
 OsclMemPoolFixedChunkAllocator, 445  
 OsclMemPoolResizableAllocator, 452  
**iEndAddr**  
 OsclMemPoolResizableAllocator::Mem-  
     PoolBufferInfo, 454  
**iErrAlloc**  
 OsclSelect, 519  
**iErrorTrapImp**  
 OsclExecSchedulerCommonBase, 398  
**iExecTimerQ**  
 OsclExecSchedulerCommonBase, 398  
**iExpectedNumBlocksPerBuffer**  
 OsclMemPoolResizableAllocator, 452  
**iFactory**  
 OsclComponentRegistryElement, 345  
 OsclRegistryAccessElement, 507  
**iFilePosition**  
 Oscl\_File::OsclFixedCacheParam, 187  
**iFlags**  
 RecvFromParam, 635  
 RecvParam, 637  
 SendParam, 638  
 SendToParam, 639  
  
**iFreeMemChunkList**  
 OsclMemPoolFixedChunkAllocator, 445  
**iFreeMemContextData**  
 OsclMemPoolResizableAllocator, 452  
**iFreeMemPoolObserver**  
 OsclMemPoolResizableAllocator, 452  
**ifront**  
 Oscl\_Queue\_Base, 240  
**iFxn**  
 DNSRequestParam, 133  
 SocketRequestParam, 642  
**iGrandTotalTicks**  
 OsclExecSchedulerCommonBase, 398  
**iHead**  
 OsclDoubleListBase, 368  
 OsclDoubleRunner, 369  
**iHeapCheck**  
 OsclSelect, 519  
**iHigh**  
 OsclInteger64Transport, 415  
**iHow**  
 ShutdownParam, 640  
**iId**  
 OsclComponentRegistryElement, 345  
 OsclIDNSMethod, 359  
 OsclIPSocketI, 419  
**iIsIn**  
 TReadyQueLink, 656  
**iJumpData**  
 OsclErrorTrapImp, 377  
**iLeave**  
 OsclErrorTrapImp, 377  
**iLen**  
 PVSockBufRecv, 631  
 PVSockBufSend, 632  
**iLength**  
 OsclBuf, 340  
**iLogger**  
 OsclIDNSMethod, 359  
 OsclDNSRequestAO, 364  
 OsclExecSchedulerCommonBase, 398  
 OsclIPSocketI, 419  
 OsclSocketServIBase, 558  
**iLogPerfIndentStr**  
 OsclExecSchedulerCommonBase, 398  
**iLogPerfIndentStrLen**  
 OsclExecSchedulerCommonBase, 398  
**iLogPerfTotal**  
 OsclExecSchedulerCommonBase, 398  
**iLow**  
 OsclInteger64Transport, 415  
**iMaxLen**  
 PVSockBufRecv, 631  
**iMaxLength**

OsclBuf, 340  
 iMaxNewMemPoolBufferSz  
   OsclMemPoolResizableAllocator, 452  
 iMemPool  
   OsclMemPoolFixedChunkAllocator, 445  
 iMemPoolAligned  
   OsclMemPoolFixedChunkAllocator, 445  
 iMemPoolAllocator  
   OsclMemPoolFixedChunkAllocator, 445  
 iMemPoolBufferAllocator  
   OsclMemPoolResizableAllocator, 452  
 iMemPoolBufferList  
   OsclMemPoolResizableAllocator, 452  
 iMemPoolBufferNumLimit  
   OsclMemPoolResizableAllocator, 452  
 iMemPoolBufferSize  
   OsclMemPoolResizableAllocator, 452  
 iMimeType  
   OsclRegistryAccessElement, 507  
 iMultiMaxLen  
   RecvFromParam, 635  
 iMutex  
   OsclComponentRegistry, 343  
 iName  
   GetHostNameParam, 135  
   OsclExecSchedulerCommonBase, 398  
   PVActiveBase, 614  
 iNativeAccessMode  
   OsclNativeFileParams, 464  
 iNativeBufferSize  
   OsclNativeFileParams, 464  
 iNativeMode  
   OsclExecSchedulerCommonBase, 398  
 IncLogPerf  
   OsclExecSchedulerCommonBase, 395  
 increment\_refcnt  
   BufferState, 118  
 iNext  
   OsclDoubleLink, 365  
   OsclDoubleRunner, 369  
   OsclTrapStackItem, 599  
 iNextAvailableContextData  
   OsclMemPoolFixedChunkAllocator, 445  
   OsclMemPoolResizableAllocator, 452  
 iNextFreeBlock  
   OsclMemPoolResizableAllocator::Mem-  
     PoolBlockInfo, 453  
   OsclMemPoolResizableAllocator::Mem-  
     PoolBufferInfo, 454  
 Init  
   OsclErrorTrap, 375  
   OsclInit, 414  
   OsclMem, 424  
   OsclScheduler, 515  
 PVLogger, 619  
 InitExecQ  
   OsclExecSchedulerCommonBase, 395  
 Insert  
   OsclDoubleListBase, 368  
   OsclPriorityList, 468  
 insert  
   Oscl\_Map, 219  
   Oscl\_TagTree, 271  
   Oscl\_Vector, 287  
   Oscl\_Vector\_Base, 291  
 insert\_element  
   Oscl\_Linked\_List, 207  
   Oscl\_Linked\_List\_Base, 212  
 insert\_unique  
   Oscl\_Rb\_Tree, 243  
 InsertAfter  
   OsclDoubleLink, 365  
 InsertBefore  
   OsclDoubleLink, 365  
 InsertHead  
   OsclDoubleList, 366  
   OsclDoubleListBase, 368  
 InsertTail  
   OsclDoubleList, 366  
   OsclDoubleListBase, 368  
 InstallScheduler  
   OsclExecSchedulerCommonBase, 395  
 INT64  
   osclconfig\_unix\_android.h, 842  
   osclconfig\_unix\_common.h, 846  
 int64  
   osclbase, 34  
 INT64\_HILO  
   osclconfig\_unix\_android.h, 842  
   osclconfig\_unix\_common.h, 846  
 interfaceAddr  
   OsclIpMReq, 416  
 INTERNAL\_ERROR  
   BuffFragStatusClass, 122  
 internalLeave  
   osclerror, 87  
 internalLeave  
   a, 138  
 InThread  
   DNSRequestParam, 132  
 iNumAOAdded  
   OsclExecSchedulerCommonBase, 398  
 iNumChunk  
   OsclMemPoolFixedChunkAllocator, 445  
 iNumOfRun  
   OsclAsyncFile, 317  
 iNumOfRunErr  
   OsclAsyncFile, 317

iNumOutstanding  
     OsclMemPoolResizableAllocator::MemPoolBufferInfo, [454](#)

iNumSessions  
     OsclComponentRegistry, [343](#)

INVALID\_ACCESS\_ERROR  
     OsclProcStatus, [475](#)

INVALID\_ARGUMENT\_ERROR  
     OsclProcStatus, [475](#)

INVALID\_FUNCTION\_ERROR  
     OsclProcStatus, [475](#)

INVALID\_HANDLE\_ERROR  
     OsclProcStatus, [475](#)

INVALID\_ID  
     BufFragStatusClass, [122](#)

INVALID\_OPERATION\_ERROR  
     OsclProcStatus, [475](#)

INVALID\_PARAM\_ERROR  
     OsclProcStatus, [474](#)

INVALID\_POINTER\_ERROR  
     OsclProcStatus, [475](#)

INVALID\_PRIORITY\_ERROR  
     OsclProcStatus, [474](#)

INVALID\_THREAD\_ERROR  
     OsclProcStatus, [474](#)

INVALID\_THREAD\_ID\_ERROR  
     OsclProcStatus, [474](#)

INVALID\_TYPE  
     Oscl\_FileFind, [188](#)

iObserver  
     OsclIPSocketI, [419](#)  
     OsclMemPoolFixedChunkAllocator, [445](#)  
     OsclMemPoolResizableAllocator, [452](#)

iOffset  
     OsclDoubleListBase, [368](#)  
     OsclDoubleRunner, [369](#)

iOpCount  
     OsclFileStatsItem, [411](#)

iOsclBase  
     OsclSelect, [519](#)

iOsclErrorTrap  
     OsclSelect, [519](#)

iOsclLogger  
     OsclSelect, [519](#)

iOsclMemory  
     OsclSelect, [519](#)

iOsclScheduler  
     OsclSelect, [519](#)

iOtherExecStats  
     OsclExecSchedulerCommonBase, [398](#)

iOutputFile  
     OsclSelect, [519](#)

iPacketLen  
     RecvFromParam, [635](#)

iPacketSource  
     RecvFromParam, [635](#)

ipAddr  
     OsclNetworkAddress, [465](#)

iParam  
     OsclFileStatsItem, [411](#)  
     OsclSocketRequest, [548](#)  
     OsclSocketRequestAO, [552](#)

iParam2  
     OsclFileStatsItem, [411](#)

iParamSize  
     OsclSocketRequestAO, [552](#)

iParentBuffer  
     OsclMemPoolResizableAllocator::MemPoolBlockInfo, [453](#)

iPrev  
     OsclDoubleLink, [365](#)

iPrevFreeBlock  
     OsclMemPoolResizableAllocator::MemPoolBlockInfo, [453](#)

iPriority  
     OsclPriorityLink, [467](#)

iPtr  
     PVSockBufRecv, [631](#)  
     PVSockBufSend, [632](#)

iPVActiveStats  
     PVActiveBase, [614](#)

iPVReadyQLink  
     PVActiveBase, [614](#)

iPVStatQ  
     OsclExecSchedulerCommonBase, [398](#)

iPVStats  
     OsclExecSchedulerCommonBase, [398](#)

iQSize  
     ListenParam, [140](#)

iReadyQ  
     OsclExecSchedulerCommonBase, [398](#)

irear  
     Oscl\_Queue\_Base, [240](#)

iRefCount  
     DNSRequestParam, [133](#)  
     OsclMemPoolFixedChunkAllocator, [445](#)  
     OsclMemPoolResizableAllocator, [452](#)

iRequestedAvailableFreeMemSize  
     OsclMemPoolResizableAllocator, [452](#)

iRequestedNextAvailableSize  
     OsclMemPoolResizableAllocator, [452](#)

iResumeSem  
     OsclExecSchedulerCommonBase, [398](#)

is\_writable  
     OSCL\_String, [261](#)  
     OSCL\_wString, [305](#)

is\_zero  
     TimeValue, [653](#)

is\_zulu  
     TimeValue, 653

IsActive  
     PVLogger, 619

IsAdded  
     PVActiveBase, 612

isAllocNodePtr  
     MM\_AllocBlockHdr, 147

IsBusy  
     OsclActiveObject, 311  
     OsclTimerObject, 587

iSchedulerAlloc  
     OsclSelect, 519

iSchedulerName  
     OsclSelect, 519

iSchedulerReserve  
     OsclSelect, 519

isCIEquivalentTo  
     StrCSumPtrLen, 644  
     StrPtrLen, 647  
     WStrPtrLen, 658

isCIPrefixOf  
     StrPtrLen, 647

iSelect  
     OsclSocketServRequestQElem, 561

IsEmpty  
     OsclDoubleListBase, 368

iSeqNum  
     TReadyQueLink, 656

iServerError  
     OsclSocketServIBase, 558

iServerState  
     OsclSocketServIBase, 558

isFixed  
     OsclFileCacheBuffer, 403

IsHead  
     OsclDoubleList, 366  
     OsclPriorityList, 468

IsIn  
     OsclReadyQ, 484  
     OsclTimerQ, 590

IsInAnyQ  
     PVActiveBase, 613

IsInstalled  
     OsclExecSchedulerCommonBase, 395

IsInUse  
     OsclAsyncFileBuffer, 319

iSize  
     Oscl\_File::OsclFixedCacheParam, 187

isLetter  
     StrPtrLen, 647

IsLocalData  
     MediaData, 143

ISO8601TIME\_BUFFER\_SIZE

                osclbase, 45  
 ISO8601timeStrBuf  
     osclbase, 34

ISO8601ToRFC822  
     osclbase, 36

iSocket  
     OsclIPSocketI, 419

iSocketError  
     OsclDNSRequestAO, 364  
     OsclSocketRequestAO, 552

iSocketFxn  
     OsclSocketMethod, 546

iSocketI  
     OsclSocketRequest, 548

iSocketRequest  
     OsclSocketServRequestQElem, 561

iSocketRequestAO  
     OsclSocketMethod, 546  
     OsclSocketRequest, 548

iSocketServ  
     OsclDNSIBase, 356  
     OsclIPSocketI, 419  
     OsclSocketIBase, 543

IsOpen  
     OsclSocketIBase, 541

IsReady  
     OsclDNSIBase, 355

IsSameThreadContext  
     PVThreadContext, 633

IsServConnected  
     OsclSocketServIBase, 558

IsServerThread  
     OsclSocketServI, 556

isSetFailure  
     MM\_Audit\_Imp, 154

IsStarted  
     OsclExecSchedulerCommonBase, 395

IsTail  
     OsclDoubleList, 366  
     OsclPriorityList, 468

iStartAddr  
     OsclMemPoolResizableAllocator::Mem-  
         PoolBufferInfo, 454

iStartTick  
     OsclFileStatsItem, 411

iStatus  
     PVActiveBase, 614

iStopper  
     OsclExecSchedulerCommonBase, 398

iStopperCrit  
     OsclExecSchedulerCommonBase, 398

IsUpdated  
     OsclFileCacheBuffer, 403

iSuspended

OsclExecSchedulerCommonBase, 398  
**IsValid**  
     OsclAsyncFileBuffer, 319  
**iTAny**  
     OsclTrapStackItem, 599  
**iterator**  
     Oscl\_Linked\_List\_Base, 214  
     Oscl\_Map, 217  
     Oscl\_Rb\_Tree, 243  
     Oscl\_Rb\_Tree\_Iterator, 250  
     Oscl\_TagTree::iterator, 276  
     Oscl\_Vector, 285  
     OsclPriorityQueue, 470  
**iThreadContext**  
     OsclExecSchedulerCommonBase, 398  
     PVActiveBase, 614  
**iTime**  
     OsclExecSchedulerCommonBase, 398  
**iTimeCompareThreshold**  
     OsclExecSchedulerCommonBase, 398  
**iTimeQueuedTicks**  
     TReadyQueLink, 656  
**iTimeToRunTicks**  
     TReadyQueLink, 656  
**iTotalPercent**  
     OsclExecSchedulerCommonBase, 398  
**iTotalTicks**  
     OsclFileStatsItem, 411  
**iTotalTicksTemp**  
     OsclExecSchedulerCommonBase, 398  
**iTrapOperation**  
     OsclTrapStackItem, 599  
**iTrapStack**  
     OsclErrorTrapImp, 377  
**iVec**  
     OsclComponentRegistryData, 344  
**iXferLen**  
     SendParam, 638  
     SendToParam, 639  
**Join**  
     OsclIPSocketI, 418  
     OsclSocketI, 536  
     OsclSocketIBase, 541  
     OsclUDPSocket, 602  
**JoinMulticastGroup**  
     OsclUDPSocket, 603  
     OsclUDPSocketI, 607  
**Jump**  
     OsclJump, 420  
**key\_comp**  
     Oscl\_Map, 220  
**key\_compare**

    Oscl\_Map, 217  
**key\_type**  
     Oscl\_Map, 217  
     Oscl\_Rb\_Tree, 243  
**largeasyncfilereadwrite\_test**  
     Oscl\_File, 185  
**Leave**  
     OsclError, 371  
**LeaveIfError**  
     OsclError, 371  
**LeaveIfNull**  
     OsclError, 371  
**Left**  
     OsclPtrC, 479  
**left**  
     Oscl\_Rb\_Tree\_Node\_Base, 254  
**len**  
     OsclMemoryFragment, 441  
     StrPtrLen, 647  
     WStrPtrLen, 658  
**Length**  
     OsclAsyncFileBuffer, 319  
     OsclBuf, 340  
     OsclPtr, 476  
     OsclPtrC, 479  
**length**  
     BuffFragGroup, 121  
     OsclBinStream, 338  
     StrPtrLen, 647  
     WStrPtrLen, 658  
**lineNo**  
     MM\_AllocInfo, 149  
     MM\_AllocQueryInfo, 151  
**link\_type**  
     Oscl\_Rb\_Tree, 243  
     Oscl\_Rb\_Tree\_Const\_Iterator, 247  
     Oscl\_Rb\_Tree\_Iterator, 250  
     Oscl\_Rb\_Tree\_Node, 252  
**LinkedListElement**, 139  
     LinkedListElement, 139  
**LinkedListElement**  
     data, 139  
     LinkedListElement, 139  
     next, 139  
**Listen**  
     OsclListenMethod, 421  
     OsclListenRequest, 422  
     OsclSocketI, 536  
     OsclSocketIBase, 541  
     OsclTCPSocket, 568  
     OsclTCPSocketI, 572  
**ListenAsync**  
     OsclSocketIBase, 541

OsclTCPSocket, 568  
 OsclTCPSocketI, 573  
 ListenParam, 140  
   ListenParam, 140  
 ListenParam  
   iQSize, 140  
   ListenParam, 140  
 ListenRequest  
   OsclListenMethod, 421  
 little\_endian\_to\_host  
   osclbase, 36  
 localbuf  
   MediaData, 143  
 Lock  
   OsclLockBase, 423  
   OsclMutex, 459  
   OsclNullLock, 466  
   OsclThreadLock, 578  
 lockAndGetInstance  
   OsclSingletonRegistry, 533  
 Log  
   OsclFileStats, 410  
 log\_level\_type  
   AllPassFilter, 113  
   PVLogger, 617  
   PVLoggerFilter, 623  
   PVLoggerRegistry, 627  
 LogAll  
   OsclFileStats, 410  
 Logger  
   OsclSocketI, 536  
 LogMsgBuffers  
   PVLogger, 619  
 LogMsgBuffersV  
   PVLogger, 619  
 LogMsgString  
   PVLogger, 620  
 LogMsgStringV  
   PVLogger, 620  
 LoopbackSocket  
   OsclSocketServI, 556  
 lower\_bound  
   Oscl\_Map, 220  
   Oscl\_Rb\_Tree, 243  
 MakeAddr  
   OsclSocketI, 536  
 MakeMulticastGroupInformation  
   OsclSocketI, 536  
 makeValidTag  
   MM\_Audit\_Imp, 154  
 map\_type  
   Oscl\_TagTree, 269  
 mapit  
   Oscl\_TagTree::const\_iterator, 273  
   Oscl\_TagTree::iterator, 276  
 mapiter  
   Oscl\_TagTree::const\_iterator, 273  
   Oscl\_TagTree::iterator, 276  
 Match  
   OsclComponentRegistryElement, 345  
 MAX\_NUMBER\_OF\_BYTE\_PER\_UTF8  
   osclutil, 68  
 max\_size  
   Oscl\_Map, 220  
   Oscl\_Rb\_Tree, 243  
 MAX\_THRDS\_REACHED\_ERROR  
   OsclProcStatus, 474  
 maximum  
   Oscl\_Rb\_Tree\_Node\_Base, 254  
 MaxLen  
   OsclNameString, 460  
 maxsize  
   CFastRep, 127  
   CHeapRep, 129  
   CStackRep, 131  
 mbchar  
   osclbase, 34  
 MediaData, 141  
   MediaData, 142  
 MediaData  
   ~MediaData, 142  
   AddLocalFragment, 142  
   available\_localbuf, 143  
   Clear, 142  
   GetAvailableBufferSize, 142  
   GetLocalBufsize, 143  
   GetLocalFragment, 143  
   GetMediaFragment, 143  
   GetMediaSize, 143  
   GetNumMediaFrags, 143  
   GetTimestamp, 143  
   IsLocalData, 143  
   localbuf, 143  
   MediaData, 142  
   num\_reserved\_fragments, 143  
   SetTimestamp, 143  
   timestamp, 143  
 MediaStatusClass, 144  
 MediaTimestamp  
   osclutil, 68  
 MEM\_ALIGN\_SIZE  
   osclmemory, 51  
 MemAllocator, 145  
 MemAllocator  
   ~MemAllocator, 145  
   allocate, 145  
   deallocate, 145

pointer, 145  
**memoryPoolBufferMgmtOverhead**  
 OsclMemPoolResizableAllocator, 450  
**message\_id\_type**  
 AllPassFilter, 113  
 PVLogger, 617  
 PVLoggerAppender, 622  
 PVLoggerFilter, 623  
 PVLoggerLayout, 625  
**MethodDone**  
 OsclDNSMethod, 358  
 OsclSocketMethod, 545  
**MICROSECONDS**  
 osclbase, 35  
**MILLISECONDS**  
 osclbase, 35  
**MIN\_FENCE\_SIZE**  
 osclmemory, 51  
**minimum**  
 Oscl\_Rb\_Tree\_Node\_Base, 254  
**MM\_AddTag**  
 MM\_Audit\_Imp, 154  
 OsclMemAudit, 429  
**MM\_ALLOC\_MAX\_QUERY\_FILENAME\_LEN**  
 osclmemory, 51  
**MM\_ALLOC\_MAX\_QUERY\_TAG\_LEN**  
 osclmemory, 51  
**MM\_allocate**  
 MM\_Audit\_Imp, 154  
 OsclMemAudit, 429  
**MM\_AllocBlockFence**, 146  
 MM\_AllocBlockFence, 146  
**MM\_AllocBlockFence**  
 check\_fence, 146  
 fill\_fence, 146  
 MM\_AllocBlockFence, 146  
 pad, 146  
**MM\_AllocBlockHdr**, 147  
 MM\_AllocBlockHdr, 147  
**MM\_AllocBlockHdr**  
 isAllocNodePtr, 147  
 MM\_AllocBlockHdr, 147  
 pad, 147  
 pNode, 147  
 pRootNode, 147  
 setAllocNodeFlag, 147  
 size, 147  
**MM\_AllocInfo**, 148  
 MM\_AllocInfo, 149  
**MM\_AllocInfo**  
 ~MM\_AllocInfo, 149  
 allocNum, 149  
 bSetFailure, 149  
 lineNumber, 149  
 MM\_AllocInfo, 149  
 operator delete, 149  
 operator new, 149  
 pFileName, 149  
 pMemBlock, 149  
 pStatsNode, 149  
 size, 149  
**MM\_AllocNode**, 150  
 MM\_AllocNode, 150  
**MM\_AllocNode**  
 ~MM\_AllocNode, 150  
 MM\_AllocNode, 150  
 operator delete, 150  
 operator new, 150  
 pAllocInfo, 150  
 pNext, 150  
 pPrev, 150  
**MM\_AllocNodeAutoPtr**  
 osclmemory, 58  
**MM\_AllocQueryInfo**, 151  
**MM\_AllocQueryInfo**  
 allocNum, 151  
 fileName, 151  
 lineNumber, 151  
 pMemBlock, 151  
 size, 151  
 tag, 151  
**MM\_AUDIT\_ALLOC\_NODE\_ENABLE\_FLAG**  
 osclmemory, 51  
**MM\_AUDIT\_ALLOC\_NODE\_SUPPORT**  
 osclmemory, 51  
**MM\_AUDIT\_FAILURE\_SIMULATION\_SUPPORT**  
 osclmemory, 51  
**MM\_AUDIT\_FENCE\_SUPPORT**  
 osclmemory, 51  
**MM\_AUDIT\_FILL\_SUPPORT**  
 osclmemory, 51  
**MM\_Audit\_Imp**, 152  
 ~MM\_Audit\_Imp, 153  
 addAllocNode, 153  
 createStatsNode, 153  
 getAuditRoot, 153  
 getSize, 153  
 getTagActualSize, 153  
 isSetFailure, 154  
 makeValidTag, 154  
**MM\_AddTag**, 154  
**MM\_allocate**, 154  
**MM\_Audit\_Imp**, 153  
**MM\_CreateAllocNodeInfo**, 154  
**MM\_deallocate**, 154

MM\_GetAllocNo, 154  
 MM\_GetAllocNodeInfo, 155  
 MM\_GetExistingTag, 155  
 MM\_GetMode, 155  
 MM\_GetNumAllocNodes, 155  
 MM\_GetOverheadStats, 155  
 MM\_GetPostfillPattern, 155  
 MM\_GetPrefillPattern, 155  
 MM\_GetRootNode, 156  
 MM\_GetStats, 156  
 MM\_GetStatsInDepth, 156  
 MM\_GetTagName, 156  
 MM\_GetTreeNodes, 156  
 MM\_ReleaseAllocNodeInfo, 156  
 MM\_SetFailurePoint, 157  
 MM\_SetMode, 157  
 MM\_SetPostfillPattern, 157  
 MM\_SetPrefillPattern, 157  
 MM\_SetTagLevel, 157  
 MM\_UnsetFailurePoint, 157  
 MM\_Validate, 157  
 pruneSubtree, 158  
 removeALLAllocNodes, 158  
 removeAllocNode, 158  
 retrieveParentTag, 158  
 retrieveParentTagLength, 158  
 updateStatsNode, 158  
 updateStatsNodeInFailure, 158  
 validate, 158  
 validate\_all\_heap, 158  
**MM\_AUDIT\_INCLUDE\_ALL\_HEAP\_-VALIDATION**  
 osclmemory, 51  
**MM\_AUDIT\_POSTFILL\_FLAG**  
 osclmemory, 51  
**MM\_AUDIT\_PREFILL\_FLAG**  
 osclmemory, 51  
**MM\_AUDIT\_SUPPRESS\_FILENAME\_FLAG**  
 osclmemory, 51  
**MM\_AUDIT\_VALIDATE\_ALL\_HEAP\_FLAG**  
 osclmemory, 51  
**MM\_AUDIT\_VALIDATE\_BLOCK**  
 osclmemory, 51  
**MM\_AUDIT\_VALIDATE\_ON\_FREE\_FLAG**  
 osclmemory, 51  
**MM\_AuditOverheadStats**, 160  
**MM\_AuditOverheadStats**  
 per\_allocation\_overhead, 160  
 stats\_overhead, 160  
**MM\_CreateAllocNodeInfo**  
 MM\_Audit\_Imp, 154  
 OsclMemAudit, 429  
**MM\_deallocate**  
 MM\_Audit\_Imp, 154  
 OsclMemAudit, 429  
**MM\_FailInsertParam**  
 MM\_FailInsertParam, 161  
**MM\_FailInsertParam**  
 MM\_FailInsertParam, 161  
**MM\_FailInsertParam**  
 nAllocNum, 161  
 operator delete, 161  
 operator new, 161  
 reset, 161  
 xsubi, 161  
**MM\_GetAllocNo**  
 MM\_Audit\_Imp, 154  
 OsclMemAudit, 429  
**MM\_GetAllocNodeInfo**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 429  
**MM\_GetExistingTag**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 430  
**MM\_GetMode**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 430  
**MM\_GetNumAllocNodes**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 430  
**MM\_GetOverheadStats**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 430  
**MM\_GetPostfillPattern**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 430  
**MM\_GetPrefillPattern**  
 MM\_Audit\_Imp, 155  
 OsclMemAudit, 430  
**MM\_GetRefCount**  
 OsclMemAudit, 430  
**MM\_GetRootNode**  
 MM\_Audit\_Imp, 156  
 OsclMemAudit, 431  
**MM\_GetStats**  
 MM\_Audit\_Imp, 156  
 OsclMemAudit, 431  
**MM\_GetStatsInDepth**  
 MM\_Audit\_Imp, 156  
 OsclMemAudit, 431  
**MM\_GetTagName**  
 MM\_Audit\_Imp, 156  
 OsclMemAudit, 431  
**MM\_GetTreeNodes**  
 MM\_Audit\_Imp, 156  
 OsclMemAudit, 431  
**MM\_ReleaseAllocNodeInfo**  
 MM\_Audit\_Imp, 156  
 OsclMemAudit, 431

**MM\_SetFailurePoint**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 431

**MM\_SetMode**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 432

**MM\_SetPostfillPattern**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 432

**MM\_SetPrefillPattern**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 432

**MM\_SetTagLevel**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 432

**MM\_Stats\_CB**, 162  
 MM\_Stats\_CB, 162  
 num\_child\_nodes, 162  
 operator delete, 162  
 operator new, 162  
 pStats, 162  
 tag, 162

**MM\_Stats\_t**, 163  
 MM\_Stats\_t, 164  
 numAllocFails, 164  
 numAllocs, 164  
 numBytes, 164  
 operator delete, 164  
 operator new, 164  
 peakNumAllocs, 164  
 peakNumBytes, 164  
 reset, 164  
 totalNumAllocs, 164  
 totalNumBytes, 164  
 update, 164

**MM\_StatsNodeTagTreeType**  
 osclmemory, 58

**MM\_UnsetFailurePoint**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 432

**MM\_Validate**  
 MM\_Audit\_Imp, 157  
 OsclMemAudit, 432

**MMAuditCharAutoPtr**  
 osclmemory, 58

**MMAuditUint8AutoPtr**  
 osclmemory, 58

**Mode**  
 OsclNativeFile, 462

**mode**  
 oscl\_stat\_buf, 258

**MODE\_APPEND**  
 Oscl\_File, 179

**MODE\_BINARY**  
 Oscl\_File, 179

**MODE\_READ**  
 Oscl\_File, 179

**MODE\_READ\_PLUS**  
 Oscl\_File, 179

**MODE\_READWRITE**  
 Oscl\_File, 179

**MODE\_TEXT**  
 Oscl\_File, 179

**mode\_type**  
 Oscl\_File, 179

**move\_to\_end**  
 Oscl\_Linked\_List, 208  
 Oscl\_Linked\_List\_Base, 212  
 Oscl\_MTLinkedList, 225

**move\_to\_front**  
 Oscl\_Linked\_List, 208  
 Oscl\_Linked\_List\_Base, 213  
 Oscl\_MTLinkedList, 226

**MSEC\_PER\_SEC**  
 osclbase, 45

**MSEC\_TO\_MICROSEC**  
 oscl\_socket\_method.h, 759

**MsecToTicks**  
 OsclTickCount, 579

**multicastAddr**  
 OsclIpMReq, 416

**MUTEX\_LOCKED\_ERROR**  
 OsclProcStatus, 475

**nAllocNum**  
 MM\_FailInsertParam, 161

**New**  
 Oscl\_DefAllocWithRefCounter, 173

**NewL**  
 OsclAcceptMethod, 307  
 OsclAsyncFile, 316  
 OsclAsyncFileBuffer, 319  
 OsclBindMethod, 321  
 OsclBuf, 340  
 OsclConnectMethod, 347  
 OsclDNS, 351  
 OsclDNSI, 353  
 OsclGetHostByNameMethod, 412  
 OsclListenMethod, 421  
 OsclRecvFromMethod, 485  
 OsclRecvMethod, 489  
 OsclSendMethod, 522  
 OsclSendToMethod, 524  
 OsclShutdownMethod, 529  
 OsclSocketI, 536  
 OsclSocketServ, 554  
 OsclSocketServI, 556  
 OsclTCPSocket, 568

---

OsclTCPSocketI, [573](#)  
 OsclUDPSocket, [603](#)  
 OsclUDPSocketI, [607](#)  
**NewRequest**  
   OsclIDNSRequestAO, [363](#)  
   OsclSocketRequestAO, [551](#)  
**next**  
   BufFragGroup, [121](#)  
   LinkedListElement, [139](#)  
**nextFragPtr**  
   OsclBinStream, [338](#)  
**NO\_PERMISSION\_ERROR**  
   OsclProcStatus, [474](#)  
**Node**  
   Oscl\_TagTree::Node, [279](#)  
**node**  
   Oscl\_Rb\_Tree\_Const\_Iterator, [247](#)  
   Oscl\_Rb\_Tree\_Iterator, [250](#)  
**node\_ptr**  
   Oscl\_TagTree, [269](#)  
**node\_type**  
   Oscl\_TagTree, [269](#)  
**NOT\_ENOUGH\_MEMORY\_ERROR**  
   OsclProcStatus, [474](#)  
**NOT\_ENOUGH\_RESOURCES\_ERROR**  
   OsclProcStatus, [474](#)  
**NOT\_ENOUGH\_SPACE**  
   BufFragStatusClass, [122](#)  
**NOT\_IMPLEMENTED**  
   OsclProcStatus, [475](#)  
**NOT\_SUSPENDED\_ERROR**  
   OsclProcStatus, [474](#)  
**notifyfreeblockavailable**  
   OsclMemPoolResizableAllocator, [450](#)  
**notifyfreechunkavailable**  
   OsclMemPoolFixedChunkAllocator, [444](#)  
**notifyfreetemoryavailable**  
   OsclMemPoolResizableAllocator, [450](#)  
**NTPTime**, [165](#)  
   get\_lower32, [167](#)  
   get\_middle32, [167](#)  
   get\_upper32, [167](#)  
   get\_value, [167](#)  
   NTPTime, [166](#), [167](#)  
   operator+=, [167](#)  
   operator-, [167](#)  
   operator=, [167](#), [168](#)  
   set\_from\_system\_time, [168](#)  
   set\_to\_current\_time, [168](#)  
   TimeValue, [654](#)  
   to\_system\_time, [168](#)  
**NULL**  
   osclbase, [32](#)  
**NULL\_INPUT**

BufFragStatusClass, [122](#)  
**NULL\_TERM\_CHAR**  
   osclbase, [32](#)  
**num\_child\_nodes**  
   MM\_Stats\_CB, [162](#)  
**num\_elements**  
   Oscl\_Linked\_List\_Base, [214](#)  
**num\_fragments**  
   BufFragGroup, [121](#)  
**num\_reserved.fragments**  
   MediaData, [143](#)  
**numAllocFails**  
   MM\_Stats\_t, [164](#)  
**numAllocs**  
   MM\_Stats\_t, [164](#)  
**numBytes**  
   MM\_Stats\_t, [164](#)  
**numelems**  
   Oscl\_Queue\_Base, [240](#)  
   Oscl\_Vector\_Base, [292](#)  
**numFrags**  
   OsclBinStream, [338](#)  
**octet**  
   osclbase, [34](#)  
**Offset**  
   OsclAsyncFileBuffer, [319](#)  
**Open**  
   Oscl\_File, [181](#)  
   OsclAsyncFile, [316](#), [317](#)  
   OsclDNSI, [353](#)  
   OsclDNSIBase, [355](#)  
   OsclFileCache, [401](#)  
   OsclNativeFile, [462](#)  
   OsclSocketI, [536](#)  
   OsclSocketIBase, [542](#)  
   OsclSocketServRequestList, [559](#)  
**OpenSession**  
   OsclComponentRegistry, [343](#)  
**operator \***  
   Oscl\_Rb\_Tree\_Const\_Iterator, [247](#)  
   Oscl\_Rb\_Tree\_Iterator, [250](#)  
   Oscl\_TagTree::const\_iterator, [273](#)  
   Oscl\_TagTree::iterator, [276](#)  
   OsclExclusiveArrayPtr, [380](#)  
   OsclExclusivePtr, [383](#)  
   OsclExclusivePtrA, [386](#)  
   OSCLMemAutoPtr, [436](#)  
   OsclSharedPtr, [527](#)  
   OsclSingleton, [531](#)  
   OsclTLS, [591](#)  
   OsclTLSEx, [593](#)  
**operator \*=**  
   TimeValue, [653](#)

operator delete  
 MM\_AllocInfo, 149  
 MM\_AllocNode, 150  
 MM\_FailInsertParam, 161  
 MM\_Stats\_CB, 162  
 MM\_Stats\_t, 164  
 oscl\_mem.h, 714  
 OsclErrorAllocator, 374  
 osclmemory, 59  
 OsclMemStatsNode, 457

operator delete[]  
 osclmemory, 59

operator new  
 MM\_AllocInfo, 149  
 MM\_AllocNode, 150  
 MM\_FailInsertParam, 161  
 MM\_Stats\_CB, 162  
 MM\_Stats\_t, 164  
 oscl\_mem.h, 714  
 osclconfig\_global\_placement\_new.h, 810  
 OsclErrorAllocator, 374  
 osclmemory, 59  
 OsclMemStatsNode, 457

operator new[]  
 osclmemory, 59

operator T \*  
 OsclDoubleRunner, 369

operator TheClass \*  
 OsclSharedPtr, 528

operator!=  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_Rb\_Tree\_Iterator, 250  
 OSCL\_String, 261  
 Oscl\_TagTree::const\_iterator, 273  
 Oscl\_TagTree::iterator, 276  
 OSCL\_wString, 305  
 OsclAOStatus, 314  
 OsclUuid, 610  
 StrCSumPtrLen, 644  
 StrPtrLen, 647  
 TimeValue, 654  
 WStrPtrLen, 658

operator()  
 Oscl\_Less, 204  
 Oscl\_Map::value\_compare, 222  
 Oscl\_Select1st, 255  
 Oscl\_Tag\_Base, 267

operator+  
 osclbase, 36, 37

operator++  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_Rb\_Tree\_Iterator, 250  
 Oscl\_TagTree::const\_iterator, 273  
 Oscl\_TagTree::iterator, 276

OsclDoubleRunner, 369

operator+=  
 NTPTTime, 167  
 OSCL\_String, 261  
 OSCL\_wString, 305  
 TimeValue, 653

operator-  
 NTPTTime, 167  
 osclbase, 37

operator-  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_Rb\_Tree\_Iterator, 250  
 Oscl\_TagTree::const\_iterator, 273  
 Oscl\_TagTree::iterator, 276  
 OsclDoubleRunner, 369

operator-=  
 TimeValue, 653

operator->  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_Rb\_Tree\_Iterator, 250  
 Oscl\_TagTree::const\_iterator, 273  
 Oscl\_TagTree::iterator, 276  
 OsclExclusiveArrayPtr, 380  
 OsclExclusivePtr, 383  
 OsclExclusivePtrA, 386  
 OSCLMemAutoPtr, 436  
 OsclSharedPtr, 528  
 OsclSingleton, 531  
 OsclTLS, 591  
 OsclTLSEx, 593

operator<  
 OSCL\_String, 261  
 Oscl\_Tag, 264  
 OSCL\_wString, 305  
 OsclAOStatus, 314  
 TimeValue, 654

operator<<  
 OsclBinOStreamBigEndian, 332  
 OsclBinOStreamLittleEndian, 334

operator<=

operator=

NTPTTime, 167, 168  
 OSCL\_FastString, 176  
 OSCL\_HeapStringA, 200  
 Oscl\_Map, 220  
 Oscl\_Rb\_Tree, 243  
 OSCL\_String, 262  
 Oscl\_TagTree, 271  
 Oscl\_Vector, 287  
 OSCL\_wFastString, 294

OSCL\_wHeapStringA, 300  
 OSCL\_wString, 305  
 OsclAOStatus, 314  
 OsclComponentRegistryElement, 345  
 OsclExclusiveArrayPtr, 380  
 OsclExclusivePtr, 383  
 OsclExclusivePtrA, 386  
 OSCLMemAutoPtr, 436  
 OsclRefCounterMemFrag, 496  
 OsclSharedPtr, 528  
 osclutil, 71–73  
 OsclUuid, 610  
 StrCSumPtrLen, 644  
 StrPtrLen, 647  
 TimeValue, 653  
 WStrPtrLen, 658  
**operator==**  
   Oscl\_Rb\_Tree\_Const\_Iterator, 247  
   Oscl\_Rb\_Tree\_Iterator, 250  
   OSCL\_String, 262  
   Oscl\_TagTree::const\_iterator, 273  
   Oscl\_TagTree::iterator, 276  
   OSCL\_wString, 305  
   OsclAOStatus, 314  
   osclbase, 37  
   OsclNetworkAddress, 465  
   OsclUuid, 610  
   StrCSumPtrLen, 644  
   StrPtrLen, 647  
   TimeValue, 654  
   WStrPtrLen, 658  
**operator>**  
   OSCL\_String, 262  
   OSCL\_wString, 305  
   OsclAOStatus, 314  
   TimeValue, 654  
**operator>=**  
   OSCL\_String, 262  
   OSCL\_wString, 305  
   OsclAOStatus, 314  
   TimeValue, 654  
**operator>>**  
   OsclBinIStreamBigEndian, 326  
   OsclBinIStreamLittleEndian, 329  
**operator[]**  
   Oscl\_Map, 220  
   OSCL\_String, 262  
   Oscl\_TagTree, 271  
   Oscl\_Vector, 287  
   OSCL\_wString, 305  
**optype**  
   OSCL\_FastString, 175  
   OSCL\_HeapString, 196  
   OSCL\_HeapStringA, 198  
 OSCL\_StackString, 257  
 OSCL\_wFastString, 293  
 OSCL\_wHeapString, 297  
 OSCL\_wHeapStringA, 299  
 OSCL\_wStackString, 302  
 OSCL Base, 25  
 OSCL config, 21  
 OSCL Error, 84  
 OSCL Init, 106  
 OSCL IO, 94  
 OSCL Memory, 46  
 OSCL Proc, 102  
 OSCL Util, 62  
 OSCL\_ABS  
   osclbase, 32  
 oscl\_abs  
   osclutil, 73  
 OSCL\_AF\_INET  
   osclconfig\_io.h, 815  
 Oscl\_Alloc, 169  
   ~Oscl\_Alloc, 169  
   allocate, 169  
   allocate\_fl, 169  
 OSCL\_ALLOC\_DELETE  
   osclmemory, 51  
 OSCL\_ALLOC\_NEW  
   osclmemory, 52  
 oscl\_aostatus.h, 659  
 OSCL\_ARRAY\_DELETE  
   osclmemory, 52  
 OSCL\_ARRAY\_NEW  
   osclmemory, 52  
 OSCL\_ASCII\_CASE\_MAGIC\_BIT  
   osclutil, 83  
 oscl\_asin  
   osclutil, 73  
 OSCL\_ASSERT  
   osclbase, 32  
 OSCL\_Assert  
   osclbase, 37  
 oscl\_assert.h, 660  
 OSCL\_ASSERT\_ALWAYS  
   osclconfig, 22  
 oscl\_atan  
   osclutil, 73  
 OSCL\_AUDIT\_ARRAY\_NEW  
   osclmemory, 52  
 OSCL\_AUDIT\_CALLOC  
   osclmemory, 53  
 OSCL\_AUDIT\_MALLOC  
   osclmemory, 53  
 OSCL\_AUDIT\_NEW  
   osclmemory, 53  
 OSCL\_AUDIT\_REALLOC

osclmemory, 54  
**OSCL\_BAD\_ALLOC\_EXCEPTION\_CODE**  
 oscrror, 87  
*oscl\_base.h*, 661  
*oscl\_base\_alloc.h*, 662  
*oscl\_base\_macros.h*, 663  
*oscl\_bin\_stream.h*, 664  
**OSCL\_BYPASS\_MEMMGT**  
*osclconfig\_memory.h*, 827  
*oscl\_byte\_order.h*, 665  
**OSCL\_BYTE\_ORDER\_BIG\_ENDIAN**  
*osclconfig*, 22  
**OSCL\_BYTE\_ORDER\_LITTLE\_ENDIAN**  
*osclconfig*, 22  
**OSCL\_CALLOC**  
*osclmemory*, 54  
*oscl\_calloc*  
*osclmemory*, 54  
**OSCL\_CATCH**  
*oscrror*, 87  
**OSCL\_CATCH\_ANY**  
*oscrror*, 87  
**OSCL\_CHAR\_IS\_SIGNED**  
*osclconfig\_limits\_typedefs.h*, 826  
**OSCL\_CHAR\_IS\_UNSIGNED**  
*osclconfig\_limits\_typedefs.h*, 826  
*oscl\_chdir*  
*osclio*, 98  
*oscl\_CIstrcmp*  
*osclbase*, 37  
*oscl\_CIstrncmp*  
*osclbase*, 38  
**OSCL\_CLEANUP\_BASE\_CLASS**  
*osclmemory*, 54  
**OSCL\_CLOCK\_HAS\_DRIFT\_CORRECTION**  
*osclconfig\_util.h*, 847  
**OSCL\_COND\_EXPORT\_REF**  
*osclbase*, 32  
**OSCL\_COND\_IMPORT\_REF**  
*osclbase*, 32  
**OSCL\_CONST\_CAST**  
*osclbase*, 32  
*oscl\_cos*  
*osclutil*, 73  
*Oscl\_Dalloc*, 170  
*~Oscl\_Dalloc*, 170  
*deallocate*, 170  
*Oscl\_DefAlloc*, 171  
*Oscl\_DefAlloc*  
*allocate*, 171  
*allocate\_fl*, 171  
*deallocate*, 171  
*oscl\_defalloc.h*, 666  
*Oscl\_DefAllocWithRefCounter*, 172  
*Oscl\_DefAllocWithRefCounter*  
*addRef*, 172  
*Delete*, 172  
*getCount*, 172  
*New*, 173  
*removeRef*, 173  
**OSCL\_DEFAULT\_FREE**  
*osclmemory*, 55  
**OSCL\_DEFAULT\_MALLOC**  
*osclmemory*, 55  
**OSCL\_DELETE**  
*osclmemory*, 55  
*Oscl\_DeleteFile*  
*Oscl\_FileServer*, 192, 193  
**OSCL\_DISABLE\_INLINES**  
*osclconfig\_unix\_android.h*, 842  
*osclconfig\_unix\_common.h*, 846  
**OSCL\_DISABLE\_WARNING\_RETURN\_-TYPE\_NOT\_UDT**  
*osclbase*, 32  
*osclmemory*, 55  
**OSCL\_DISABLE\_WARNING\_TRUNCATE\_DEBUG\_MESSAGE**  
*oscl\_map.h*, 708  
*oscl\_mem.h*, 714  
*oscl\_mem\_audit.h*, 717  
*oscl\_mem\_audit\_internals.h*, 718  
*oscl\_mem\_auto\_ptr.h*, 719  
*oscl\_tagtree.h*, 786  
*oscl\_tree.h*, 795  
*osclbase*, 32  
*osclmemory*, 55  
*oscl\_dll.h*, 667  
**OSCL\_DLL\_ENTRY\_POINT**  
*osclbase*, 32  
**OSCL\_DLL\_ENTRY\_POINT\_DEFAULT**  
*osclbase*, 33  
*oscl\_dns.h*, 668  
*oscl\_dns\_gethostbyname.h*, 669  
*oscl\_dns\_imp.h*, 670  
*oscl\_dns\_imp\_base.h*, 671  
*oscl\_dns\_imp\_pv.h*, 672  
*oscl\_dns\_method.h*, 673  
*oscl\_dns\_param.h*, 674  
*TDNSRequestParamAllocator*, 674  
*oscl\_dns\_request.h*, 675  
*oscl\_dns\_tuneables.h*, 676  
*PV\_DNS\_IS\_THREAD*, 676  
*PV\_DNS\_SERVER*, 676  
*oscl\_double\_list.h*, 677  
**OSCL\_DYNAMIC\_CAST**  
*osclbase*, 33  
**OSCL\_ERR\_NONE**  
*oscrror*, 88

oscl\_errno.h, 678  
 oscl\_error.h, 679  
 oscl\_error\_allocator.h, 680  
 oscl\_error\_codes.h, 681  
 oscl\_error\_imp.h, 682  
 oscl\_error\_imp\_cppexceptions.h, 683  
 oscl\_error\_imp\_fatalerror.h, 684  
   \_PV\_TRAP, 684  
   \_PV\_TRAP\_NO\_TLS, 684  
   PVError\_DoLeave, 684  
 oscl\_error\_imp\_jumps.h, 685  
   \_PV\_TRAP, 685  
   \_PV\_TRAP\_NO\_TLS, 685  
   PVError\_DoLeave, 686  
 oscl\_error\_trapcleanup.h, 687  
 oscl\_exception.h, 688  
 OSCL\_EXCEPTSET\_FLAG  
   oscl\_socket\_serv\_imp\_pv.h, 767  
 oscl\_exclusive\_ptr.h, 689  
 oscl\_exp  
   osclutil, 73  
 OSCL\_EXPORT\_REF  
   osclconfig.h, 803  
 OSCL\_FastString, 174  
   OSCL\_FastString, 175  
 OSCL\_FastString  
   ~OSCL\_FastString, 175  
   chartype, 175  
   get\_cstr, 176  
   get\_maxsize, 176  
   get\_size, 176  
   get\_str, 176  
   operator=, 176  
   otype, 175  
   OSCL\_FastString, 175  
   OSCL\_String, 177  
   other\_chartype, 175  
   set, 176, 177  
   set\_length, 177  
 Oscl\_File  
   ESymbianAccessMode\_Rfile, 179  
   ESymbianAccessMode\_RfileBuf, 179  
   MODE\_APPEND, 179  
   MODE\_BINARY, 179  
   MODE\_READ, 179  
   MODE\_READ\_PLUS, 179  
   MODE\_READWRITE, 179  
   MODE\_TEXT, 179  
   SEEKCUR, 179  
   SEEKEND, 179  
   SEEKSET, 179  
 Oscl\_File, 178  
   ~Oscl\_File, 180  
   AddFixedCache, 180  
     asyncfilereadcancel\_test, 185  
     asyncfilereadwrite\_test, 185  
     Close, 180  
     EndOfFile, 180  
     Flush, 181  
     GetError, 181  
     Handle, 181  
     largeasyncfilereadwrite\_test, 185  
     mode\_type, 179  
     Open, 181  
     Oscl\_File, 180  
     Oscl\_FileServer, 193  
     OsclFileCache, 185  
     OsclFileCacheBuffer, 185  
     OsclFileHandle, 404  
     Read, 182  
     RemoveFixedCache, 182  
     Seek, 182  
     seek\_type, 179  
     SetAsyncReadBufferSize, 182  
     SetCacheObserver, 183  
     SetFileHandle, 183  
     SetLoggingEnable, 183  
     SetNativeAccessMode, 183  
     SetNativeBufferSize, 184  
     SetPVCacheSize, 184  
     SetSize, 184  
     SetSummaryStatsLoggingEnable, 184  
     Size, 184  
     Tell, 184  
     TSymbianAccessMode, 179  
     Write, 185  
   Oscl\_File::OsclCacheObserver, 186  
   Oscl\_File::OsclCacheObserver  
     ~OsclCacheObserver, 186  
     ChooseCurCache, 186  
   Oscl\_File::OsclFixedCacheParam, 187  
   Oscl\_File::OsclFixedCacheParam  
     Contains, 187  
     iFilePath, 187  
     iSize, 187  
   oscl\_file\_async\_read.h, 690  
 OSCL\_FILE\_ATTRIBUTE\_ARCHIVE  
   OsclFileManager, 405  
 OSCL\_FILE\_ATTRIBUTE\_DIRECTORY  
   OsclFileManager, 405  
 OSCL\_FILE\_ATTRIBUTE\_HIDDEN  
   OsclFileManager, 405  
 OSCL\_FILE\_ATTRIBUTE\_NORMAL  
   OsclFileManager, 405  
 OSCL\_FILE\_ATTRIBUTE\_READONLY  
   OsclFileManager, 405  
 OSCL\_FILE\_ATTRIBUTE\_SYSTEM  
   OsclFileManager, 405

**OSCL\_FILE\_ATTRIBUTE\_TYPE**  
     osclfilemanager, 405  
**OSCL\_FILE\_BUFFER\_MAX\_SIZE**  
     osclconfig\_io.h, 815  
**oscl\_file\_cache.h**, 691  
**OSCL\_FILE\_CHAR\_PATH\_DELIMITER**  
     osclio, 96  
**oscl\_file\_dir\_utils.h**, 692  
**oscl\_file\_find.h**, 694  
**oscl\_file\_handle.h**, 695  
**oscl\_file\_io.h**, 696  
**oscl\_file\_manager.h**, 697  
**oscl\_file\_native.h**, 698  
**oscl\_file\_server.h**, 699  
**oscl\_file\_stats.h**, 700  
**OSCL\_FILE\_STATS\_LOGGER\_NODE**  
     osclio, 96  
**oscl\_file\_types.h**, 701  
**OSCL\_FILE\_WCHAR\_PATH\_DELIMITER**  
     osclio, 96  
**Oscl\_FileFind**  
     DIR\_TYPE, 188  
     E\_BUFFER\_TOO\_SMALL, 189  
     E\_INVALID\_ARG, 188  
     E\_INVALID\_STATE, 188  
     E\_MEMORY\_ERROR, 189  
     E\_NO\_MATCH, 189  
     E\_NOT\_IMPLEMENTED, 189  
     E\_OK, 188  
     E\_OTHER, 189  
     E\_PATH\_NOT\_FOUND, 188  
     E\_PATH\_TOO\_LONG, 188  
     FILE\_TYPE, 188  
     INVALID\_TYPE, 188  
**Oscl\_FileFind**, 188  
     Oscl\_FileFind, 189  
**Oscl\_FileFind**  
     ~Oscl\_FileFind, 189  
     Close, 189  
     element\_type, 188  
     error\_type, 188  
     FindFirst, 189  
     FindNext, 190  
     GetElementType, 190  
     GetLastError, 190  
     Oscl\_FileFind, 189  
**OSCL\_FILEMGMT\_E\_ALREADY\_EXISTS**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_NO\_MATCH**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_NOT\_EMPTY**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_NOT\_**  
     IMPLEMENTED  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_OK**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_PATH\_NOT\_FOUND**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_PATH\_TOO\_LONG**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_PERMISSION\_-**  
     DENIED  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_SYS\_SPECIFIC**  
     osclio, 97  
**OSCL\_FILEMGMT\_E\_UNKNOWN**  
     osclio, 97  
**OSCL\_FILEMGMT\_ERR\_TYPE**  
     osclio, 97  
**OSCL\_FILEMGMT\_MODE\_DIR**  
     osclio, 97  
**OSCL\_FILEMGMT\_MODES**  
     osclio, 97  
**OSCL\_FILEMGMT\_PERMS**  
     osclio, 97  
**OSCL\_FILEMGMT\_PERMS\_EXECUTE**  
     osclio, 97  
**OSCL\_FILEMGMT\_PERMS\_READ**  
     osclio, 97  
**OSCL\_FILEMGMT\_PERMS\_WRITE**  
     osclio, 97  
**Oscl\_FileServer**, 192  
     Oscl\_FileServer, 192  
**Oscl\_FileServer**  
     ~Oscl\_FileServer, 192  
     Close, 192  
     Connect, 192  
     Oscl\_DeleteFile, 192, 193  
     Oscl\_File, 193  
     Oscl\_FileServer, 192  
     OsclNativeFile, 193  
**OSCL\_FIRST\_CATCH**  
     osclerror, 88  
**OSCL\_FIRST\_CATCH\_ANY**  
     osclerror, 88  
**oscl\_floor**  
     osclutil, 73  
**OSCL\_FREE**  
     osclmemory, 55  
**oscl\_free**  
     osclmemory, 55  
**OSCL\_FSSTAT**  
     osclio, 96  
**oscl\_fsstat**, 194  
     freebytes, 194  
     totalbytes, 194  
**OSCL\_FUNCTION\_PTR**

osclconfig\_compiler\_warnings.h, [806](#)  
 oscl\_getcwd  
     osclio, [98](#), [99](#)  
 OSCL\_GetLastError  
     osclerror, [92](#)  
 OSCL\_HAS\_ANDROID\_FILE\_IO\_SUPPORT  
     osclconfig.h, [803](#)  
 OSCL\_HAS\_ANDROID\_SUPPORT  
     osclconfig, [22](#)  
     osclconfig.h, [803](#)  
 OSCL\_HAS\_ANSI\_64BIT\_FILE\_IO\_-  
     SUPPORT  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_ANSI\_FILE\_IO\_SUPPORT  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_ANSI\_MATH\_SUPPORT  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_ANSI\_MEMORY\_FUNCS  
     osclconfig\_ansi\_memory.h, [804](#)  
 OSCL\_HAS\_ANSI\_STDIO\_SUPPORT  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_ANSI\_STDLIB\_SUPPORT  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_ANSI\_STRING\_SUPPORT  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_ANSI\_WIDE\_STRING\_-  
     SUPPORT  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_BASIC\_LOCK  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_BERKELEY\_SOCKETS  
     osclconfig, [22](#)  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_ERRNO\_H  
     osclconfig\_error.h, [807](#)  
 OSCL\_HAS\_EXCEPTIONS  
     osclconfig\_error.h, [807](#)  
 OSCL\_HAS\_GLOB  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_GLOBAL\_NEW\_DELETE  
     osclconfig\_memory.h, [827](#)  
     osclmemory, [55](#)  
 OSCL\_HAS\_GLOBAL\_VARIABLE\_-  
     SUPPORT  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_HEAP\_BASE\_SUPPORT  
     osclconfig\_memory.h, [827](#)  
  
 OSCL\_HAS\_IPHONE\_SUPPORT  
     osclconfig, [22](#)  
     osclconfig\_unix\_android.h, [842](#)  
 OSCL\_HAS\_LARGE\_FILE\_SUPPORT  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_MSWIN\_FILE\_IO\_SUPPORT  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_MSWIN\_PARTIAL\_SUPPORT  
     osclconfig, [22](#)  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_MSWIN\_SUPPORT  
     osclconfig, [22](#)  
     osclconfig\_unix\_android.h, [842](#)  
     osclconfig\_unix\_common.h, [846](#)  
 OSCL\_HAS\_NATIVE\_FILE\_CACHE\_-  
     ENABLE  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_NON\_PREEMPTIVE\_-  
     THREAD\_SUPPORT  
     osclconfig\_proc\_unix\_android.h, [834](#)  
     osclconfig\_proc\_unix\_common.h, [836](#)  
 OSCL\_HAS\_PACKED\_STRUCT  
     osclconfig.h, [803](#)  
 OSCL\_HAS\_PRAGMA\_PACK  
     osclconfig, [22](#)  
 OSCL\_HAS\_PTHREAD\_SUPPORT  
     osclconfig, [22](#)  
     osclconfig\_proc\_unix\_android.h, [834](#)  
     osclconfig\_proc\_unix\_common.h, [836](#)  
 OSCL\_HAS\_PV\_C\_OS\_API\_MEMORY\_-  
     FUNCS  
     osclconfig, [23](#)  
 OSCL\_HAS\_PV\_C\_OS\_SUPPORT  
     osclconfig, [23](#)  
 OSCL\_HAS\_PV\_C\_OS\_TIME\_FUNCS  
     osclconfig, [23](#)  
 OSCL\_HAS\_PV\_FILE\_CACHE  
     osclconfig\_io.h, [815](#)  
 OSCL\_HAS\_RUNTIME\_LIB\_LOADING\_-  
     SUPPORT  
     osclconfig\_lib.h, [824](#)  
 OSCL\_HAS\_SAVAJE\_IO\_SUPPORT  
     osclconfig, [23](#)  
 OSCL\_HAS\_SAVAJE\_SUPPORT  
     osclconfig, [23](#)  
 OSCL\_HAS\_SEM\_TIMEDWAIT\_SUPPORT  
     osclconfig, [23](#)  
     osclconfig\_proc\_unix\_android.h, [834](#)  
     osclconfig\_proc\_unix\_common.h, [836](#)  
 OSCL\_HAS\_SETJMP\_H  
     osclconfig\_error.h, [807](#)  
 OSCL\_HAS\_SINGLETON\_SUPPORT  
     osclbase, [33](#)

**OSCL\_HAS\_SOCKET\_SUPPORT**  
*osclconfig\_io.h, 815*
  
**OSCL\_HAS\_SYMBIAN\_COMPATIBLE\_IO\_-**  
*FUNCTION*  
*osclconfig, 23*  
*osclconfig\_io.h, 815*
  
**OSCL\_HAS\_SYMBIAN\_DNS\_SERVER**  
*osclconfig, 23*  
*osclconfig\_io.h, 815*
  
**OSCL\_HAS\_SYMBIAN\_ERRORTRAP**  
*osclconfig, 23*  
*osclconfig\_error.h, 807*
  
**OSCL\_HAS\_SYMBIAN\_MATH**  
*osclconfig, 23*  
*osclconfig\_util.h, 847*
  
**OSCL\_HAS\_SYMBIAN\_MEMORY\_FUNCS**  
*osclconfig, 23*  
*osclconfig\_memory.h, 827*
  
**OSCL\_HAS\_SYMBIAN\_SCHEDULER**  
*osclconfig, 23*  
*osclconfig\_proc\_unix\_android.h, 834*  
*osclconfig\_proc\_unix\_common.h, 836*
  
**OSCL\_HAS\_SYMBIAN\_SOCKET\_SERVER**  
*osclconfig, 23*  
*osclconfig\_io.h, 815*
  
**OSCL\_HAS\_SYMBIAN\_SUPPORT**  
*osclconfig, 23*  
*osclconfig\_unix\_android.h, 842*  
*osclconfig\_unix\_common.h, 846*
  
**OSCL\_HAS\_SYMBIAN\_TIMERS**  
*osclconfig, 23*  
*osclconfig\_util.h, 847*
  
**OSCL\_HAS\_THREAD\_SUPPORT**  
*osclconfig\_proc\_unix\_android.h, 834*  
*osclconfig\_proc\_unix\_common.h, 836*
  
**OSCL\_HAS\_TLS\_SUPPORT**  
*osclconfig\_unix\_android.h, 842*  
*osclconfig\_unix\_common.h, 846*
  
**OSCL\_HAS\_UNICODE\_SUPPORT**  
*osclconfig\_unix\_android.h, 842*  
*osclconfig\_unix\_common.h, 846*
  
**OSCL\_HAS\_UNIX\_SUPPORT**  
*osclconfig, 23*  
*osclconfig\_unix\_android.h, 842*  
*osclconfig\_unix\_common.h, 846*
  
**OSCL\_HAS\_UNIX\_TIME\_FUNCS**  
*osclconfig, 23*  
*osclconfig\_time.h, 837*
  
*oscl\_heapbase.h, 702*
  
**OSCL\_HeapString, 195**  
*osclutil, 73, 74*
  
**OSCL\_HeapString**  
*chartype, 196*  
*optype, 196*
  
**OSCL\_String, 196**  
*other\_chartype, 196*
  
**OSCL\_HeapStringA, 197**  
*OSCL\_HeapStringA, 198, 199*
  
**OSCL\_HeapStringA**  
*~OSCL\_HeapStringA, 199*  
*chartype, 198*  
*get\_cstr, 199*  
*get\_maxsize, 199*  
*get\_size, 200*  
*get\_str, 200*  
*operator=, 200*  
*optype, 198*  
*OSCL\_HeapStringA, 198, 199*
  
**OSCL\_String, 201**  
*other\_chartype, 198*  
*set, 200, 201*
  
**OSCL\_IMPORT\_REF**  
*osclconfig.h, 803*
  
*oscl\_init.h, 703*
  
**OSCL\_INLINE**  
*osclbase, 33*
  
**Oscl\_Int64\_Utils, 202**  
*get\_int64\_lower32, 203*  
*get\_int64\_middle32, 203*  
*get\_int64\_upper32, 203*  
*get\_uint64\_lower32, 203*  
*get\_uint64\_middle32, 203*  
*get\_uint64\_upper32, 203*  
*set\_int64, 203*  
*set\_uint64, 203*
  
*oscl\_int64\_utils.h, 704*  
*\_OsclInteger64Transport, 704*
  
**OSCL\_INTEGERS\_WORD\_ALIGNED**  
*osclconfig, 23*
  
**OSCL\_IO\_EXTENSION\_MAXLEN**  
*osclio, 96*
  
**OSCL\_IO\_FILENAME\_MAXLEN**  
*osclio, 96*
  
*oscl\_ip\_socket.h, 705*
  
**OSCL\_IPPROTO\_IP**  
*osclconfig\_io.h, 815*
  
**OSCL\_IPPROTO\_TCP**  
*osclconfig\_io.h, 815*
  
**OSCL\_IPPROTO\_UDP**  
*osclconfig\_io.h, 815*
  
*oscl\_isdigit*  
*osclutil, 68*
  
**OSCL\_IsErrnoSupported**  
*osclerror, 92*
  
**oscl\_isLetter**  
*osclbase, 38*
  
**OSCL\_JUMP\_MAX\_JUMP\_MARKS**  
*osclerror, 88*

OSCL\_LAST\_CATCH  
     osclerror, 88  
 OSCL\_LEAVE  
     osclerror, 88  
 Oscl\_Less, 204  
     operator(), 204  
 OSCL\_LIB\_READ\_DEBUG\_LIBS  
     osclconfig\_lib.h, 824  
 Oscl\_Linked\_List, 205  
     ~Oscl\_Linked\_List, 205  
     add\_element, 206  
     add\_to\_front, 206  
     check\_list, 206  
     clear, 206  
     dequeue\_element, 206  
     get\_element, 206  
     get\_first, 207  
     get\_index, 207  
     get\_next, 207  
     get\_num\_elements, 207  
     insert\_element, 207  
     move\_to\_end, 208  
     move\_to\_front, 208  
     Oscl\_Linked\_List, 205  
     remove\_element, 208  
 oscl\_linked\_list.h, 706  
 Oscl\_Linked\_List\_Base, 210  
     ~Oscl\_Linked\_List\_Base, 211  
     add\_element, 211  
     add\_to\_front, 211  
     check\_list, 211  
     construct, 211  
     destroy, 211  
     get\_element, 211  
     get\_first, 212  
     get\_index, 212  
     get\_next, 212  
     head, 214  
     insert\_element, 212  
     iterator, 214  
     move\_to\_end, 212  
     move\_to\_front, 213  
     num\_elements, 214  
     remove\_element, 213  
     sizeof\_T, 214  
     tail, 214  
 oscl\_lock\_base.h, 707  
 oscl\_log  
     osclutil, 74  
 oscl\_log10  
     osclutil, 74  
 OSCL\_MALLOC  
     osclmemory, 56  
 oscl\_malloc  
 osclmemory, 56  
 Oscl\_Map, 215  
     begin, 218  
     clear, 218  
     const\_iterator, 217  
     const\_reference, 217  
     count, 218  
     empty, 218  
     end, 218  
     equal\_range, 218  
     erase, 219  
     find, 219  
     insert, 219  
     iterator, 217  
     key\_comp, 220  
     key\_compare, 217  
     key\_type, 217  
     lower\_bound, 220  
     max\_size, 220  
     operator=, 220  
     operator[], 220  
     Oscl\_Map, 217  
     pair\_citerator\_citerator, 217  
     pair\_iterator\_bool, 217  
     pair\_iterator\_iterator, 217  
     pointer, 217  
     reference, 217  
     self, 217  
     size, 220  
     size\_type, 217  
     upper\_bound, 220, 221  
     value\_comp, 221  
     value\_type, 217  
 oscl\_map.h, 708  
 OSCL\_DISABLE\_WARNING\_-  
     TRUNCATE\_DEBUG\_MESSAGE,  
     708  
 Oscl\_Map::value\_compare, 222  
     comp, 222  
     operator(), 222  
     Oscl\_Map< Key, T, Alloc, Compare >, 222  
     value\_compare, 222  
 Oscl\_Map< Key, T, Alloc, Compare >  
     Oscl\_Map::value\_compare, 222  
 oscl\_math.h, 709  
 OSCL\_MAX  
     osclbase, 33  
 OSCL\_MAX\_TRAP\_LEVELS  
     osclerror, 89  
 oscl\_media\_data.h, 710  
 oscl\_media\_status.h, 711  
 oscl\_mem.h, 712  
     operator delete, 714  
     operator new, 714

---

```

OSCL_DISABLE_WARNING_-
    TRUNCATE_DEBUG_MESSAGE,
    714
oscl_mem_align.h, 715
oscl_mem_aligned_size
    osclmemory, 59
oscl_mem_audit.h, 716
    OSCL_DISABLE_WARNING_-
        TRUNCATE_DEBUG_MESSAGE,
        717
oscl_mem_audit_internals.h, 718
    OSCL_DISABLE_WARNING_-
        TRUNCATE_DEBUG_MESSAGE,
        718
oscl_mem_auto_ptr.h, 719
    OSCL_DISABLE_WARNING_-
        TRUNCATE_DEBUG_MESSAGE,
        719
oscl_mem_basic_functions.h, 720
oscl_mem_inst.h, 721
oscl_mem_mempool.h, 722
oscl_memcmp
    osclmemory, 60
oscl_memcpy
    osclmemory, 60
OSCL_MEMFRAG_PTR_BEFORE_LEN
    osclconfig_unix_android.h, 842
    osclconfig_unix_common.h, 846
oscl_memmove
    osclmemory, 60
oscl_memmove32
    osclmemory, 60
oscl_memset
    osclmemory, 61
oscl_memsize_t
    osclconfig_ansi_memory.h, 804
OSCL_MIN
    osclbase, 33
oscl_mkdir
    osclio, 99
Oscl_MTLinked_List, 224
    ~Oscl_MTLinked_List, 224
    add_element, 225
    add_to_front, 225
    dequeue_element, 225
    get_element, 225
    get_index, 225
    move_to_end, 225
    move_to_front, 226
    Oscl_MTLinked_List, 224
    remove_element, 226
    the_list, 226
oscl_mutex.h, 723
    OsclNoYieldMutex, 723

oscl_namestring.h, 724
OSCL_NATIVE_INT64_TYPE
    osclconfig_unix_android.h, 842
    osclconfig_unix_common.h, 846
OSCL_NATIVE_UINT64_TYPE
    osclconfig.h, 803
    osclconfig_unix_android.h, 842
    osclconfig_unix_common.h, 846
OSCL_NATIVE_WCHAR_TYPE
    osclconfig_unix_android.h, 842
    osclconfig_unix_common.h, 846
OSCL_NEW
    osclmemory, 56
oscl_opaque_type.h, 725
Oscl_Opaque_Type_Alloc, 228
    ~Oscl_Opaque_Type_Alloc, 228
    allocate, 228
    construct, 228
    deallocate, 228
    destroy, 228
Oscl_Opaque_Type_Alloc_LL, 230
    ~Oscl_Opaque_Type_Alloc_LL, 230
    allocate, 230
    compare_data, 230
    construct, 230
    deallocate, 230
    destroy, 231
    get_data, 231
    get_next, 231
    set_next, 231
Oscl_Opaque_Type_Compare, 232
    ~Oscl_Opaque_Type_Compare, 232
    compare_EQ, 232
    compare_LT, 232
    swap, 232
OSCL_PACKED_STRUCT_BEGIN
    osclconfig.h, 803
OSCL_PACKED_STRUCT_END
    osclconfig.h, 803
OSCL_PACKED_VAR
    osclbase, 33
    osclconfig.h, 803
Oscl_Pair, 234
    first, 234
    Oscl_Pair, 234
    second, 234
OSCL_PERF_SUMMARY_LOGGING
    osclproc, 104
OSCL_PLACEMENT_NEW
    osclmemory, 56
oscl_pow
    osclutil, 74
oscl_pqueue.h, 726
oscl_pqueue_test

```

OsclPriorityQueue, 472  
 oscl\_proctstatus.h, 727  
**Oscl\_Queue**, 235  
 ~Oscl\_Queue, 236  
 back, 236  
 clear, 236  
 const\_reference, 236  
 front, 237  
**Oscl\_Queue**, 236  
 pointer, 236  
 pop, 237  
 push, 237  
 reference, 236  
 size\_type, 236  
 value\_type, 236  
 oscl\_queue.h, 728  
**Oscl\_Queue\_Base**, 238  
 ~Oscl\_Queue\_Base, 238  
 bufsize, 240  
 capacity, 239  
 clear, 239  
 construct, 239  
 destroy, 239  
 elems, 240  
 empty, 239  
 ifront, 240  
 irear, 240  
 numelems, 240  
 pop, 239  
 push, 239  
 reserve, 239  
 size, 239  
 sizeof\_T, 240  
 oscl\_rand.h, 729  
**OSCL\_RAND\_MAX**  
 osclconfig\_util.h, 847  
**Oscl\_Rb\_Tree**, 241  
 ~Oscl\_Rb\_Tree, 243  
 begin, 243  
 clear, 243  
 const\_iterator, 243  
 const\_pointer, 243  
 const\_reference, 243  
 count, 243  
 difference\_type, 243  
 empty, 243  
 end, 243  
 equal\_range, 243  
 erase, 243  
 find, 243  
 insert\_unique, 243  
 iterator, 243  
 key\_type, 243  
 link\_type, 243  
 lower\_bound, 243  
 max\_size, 243  
 operator=, 243  
**Oscl\_Rb\_Tree**, 243  
 pointer, 243  
 reference, 243  
 size, 243  
 size\_type, 243  
 upper\_bound, 243  
 value\_type, 243  
**Oscl\_Rb\_Tree\_Base**, 245  
 base\_link\_type, 245  
 rebalance, 245  
 rebalance\_for\_erase, 245  
 rotate\_left, 245  
 rotate\_right, 245  
**Oscl\_Rb\_Tree\_Const\_Iterator**, 246  
 base\_link\_type, 247  
 const\_iterator, 247  
 link\_type, 247  
 node, 247  
 operator \*, 247  
 operator!=, 247  
 operator++, 247  
 operator-, 247  
 operator->, 247  
 operator==, 247  
**Oscl\_Rb\_Tree\_Const\_Iterator**, 247  
 pointer, 247  
 reference, 247  
 self, 247  
 value\_type, 247  
**Oscl\_Rb\_Tree\_Iterator**, 249  
 base\_link\_type, 250  
 iterator, 250  
 link\_type, 250  
 node, 250  
 operator \*, 250  
 operator!=, 250  
 operator++, 250  
 operator-, 250  
 operator->, 250  
 operator==, 250  
**Oscl\_Rb\_Tree\_Iterator**, 250  
 pointer, 250  
 reference, 250  
 self, 250  
 value\_type, 250  
**Oscl\_Rb\_Tree\_Node**, 252  
 link\_type, 252  
 value, 252  
 value\_type, 252  
**Oscl\_Rb\_Tree\_Node\_Base**  
 black, 253

red, 253  
**Oscl\_Rb\_Tree\_Node\_Base**, 253  
     base\_link\_type, 253  
     color, 254  
     color\_type, 253  
     left, 254  
     maximum, 254  
     minimum, 254  
     parent, 254  
     RedBl, 253  
     right, 254  
**OSCL\_READSET\_FLAG**  
     oscl\_socket\_serv\_imp\_pv.h, 767  
**OSCL\_REALLOC**  
     osclmemory, 56  
**oscl\_realloc**  
     osclmemory, 56  
**oscl\_refcounter.h**, 730  
**oscl\_refcounter\_memfrag.h**, 731  
**oscl\_registry\_access\_client.h**, 732  
**oscl\_registry\_client.h**, 733  
**oscl\_registry\_client\_impl.h**, 734  
**oscl\_registry\_serv\_impl.h**, 735  
**oscl\_registry\_serv\_impl\_global.h**, 736  
**oscl\_registry\_serv\_impl\_tls.h**, 737  
**oscl\_registry\_types.h**, 738  
**OSCL\_REINTERPRET\_CAST**  
     osclbase, 33  
**OSCL\_RELEASE\_BUILD**  
     osclconfig.h, 803  
**oscl\_rename**  
     osclio, 99, 100  
**OSCL\_REQUEST\_ERR\_CANCEL**  
     osclproc, 105  
**OSCL\_REQUEST\_ERR\_GENERAL**  
     osclproc, 105  
**OSCL\_REQUEST\_ERR\_NONE**  
     osclproc, 105  
**OSCL\_REQUEST\_PENDING**  
     osclproc, 105  
**oscl\_rmdir**  
     osclio, 100  
**oscl\_scheduler.h**, 739  
**oscl\_scheduler\_ao.h**, 740  
**oscl\_scheduler\_aobase.h**, 741  
**oscl\_scheduler\_readyq.h**, 742  
**oscl\_scheduler\_threadcontext.h**, 743  
**oscl\_scheduler\_tuneables.h**, 744  
**oscl\_scheduler\_types.h**, 745  
**OSCL\_SD\_BOTH**  
     osclconfig\_io.h, 815  
**OSCL\_SD\_RECEIVE**  
     osclconfig\_io.h, 815  
**OSCL\_SD\_SEND**

    osclconfig\_io.h, 815  
**Oscl\_Select1st**, 255  
     operator(), 255  
**oscl\_semaphore.h**, 746  
**OSCL\_SetLastError**  
     osclerror, 92  
**oscl\_shared\_ptr.h**, 747  
**oscl\_sin**  
     osclutil, 75  
**oscl\_singleton.h**, 748  
     OSCL\_SINGLETON\_ID\_CPM\_PLUGIN, 749  
     OSCL\_SINGLETON\_ID\_LAST, 749  
     OSCL\_SINGLETON\_ID\_OMX, 749  
     OSCL\_SINGLETON\_ID\_-  
         OMXMASTERCORE, 749  
     OSCL\_SINGLETON\_ID\_OSCLMEM, 749  
     OSCL\_SINGLETON\_ID\_-  
         OSCLREGISTRY, 749  
     OSCL\_SINGLETON\_ID\_-  
         PAYLOADPARSER, 749  
     OSCL\_SINGLETON\_ID\_-  
         PVERRORTRAP, 749  
     OSCL\_SINGLETON\_ID\_PVLOGGER, 749  
     OSCL\_SINGLETON\_ID\_-  
         PVMFRECOGNIZER, 749  
     OSCL\_SINGLETON\_ID\_-  
         PVSCEDULER, 749  
     OSCL\_SINGLETON\_ID\_-  
         SDPMEDIAPARSER, 749  
     OSCL\_SINGLETON\_ID\_TEST, 749  
     OSCL\_SINGLETON\_ID\_TICKCOUNT, 749  
     OSCL\_SINGLETON\_ID\_-  
         WMDRMLOCK, 749  
     OSCL\_SINGLETON\_ID\_CPM\_PLUGIN  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_LAST  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_OMX  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_-  
         OMXMASTERCORE  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_OSCLMEM  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_OSCLREGISTRY  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_PAYLOADPARSER  
         oscl\_singleton.h, 749  
     OSCL\_SINGLETON\_ID\_PVERRORTRAP  
         oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_PVLOGGER**  
 oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_-**  
 PVMFRECOGNIZER  
 oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_PVSCHEDULER**  
 oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_-**  
 SDPMEDIAPARSER  
 oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_TEST**  
 oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_TICKCOUNT**  
 oscl\_singleton.h, 749

**OSCL\_SINGLETON\_ID\_WMDRMLOCK**  
 oscl\_singleton.h, 749

**oscl\_snprintf**  
 osclutil, 75  
 oscl\_snprintf.h, 750

**OSCL SOCK\_DGRAM**  
 osclconfig\_io.h, 815

**OSCL SOCK\_STREAM**  
 osclconfig\_io.h, 815

**oscl\_socket.h**, 751

**oscl\_socket\_accept.h**, 752

**oscl\_socket\_bind.h**, 753

**oscl\_socket\_connect.h**, 754

**oscl\_socket\_imp.h**, 755

**oscl\_socket\_imp\_base.h**, 756

**oscl\_socket\_imp\_pv.h**, 757  
 PVSOCK\_ERR\_BAD\_PARAM, 757  
 PVSOCK\_ERR\_NOT\_IMPLEMENTED, 757  
 PVSOCK\_ERR\_NOT\_SUPPORTED, 757  
 PVSOCK\_ERR\_SERV\_NOT\_CONNECTED, 757  
 PVSOCK\_ERR\_SOCK\_NO\_SERV, 757  
 PVSOCK\_ERR\_SOCK\_NOT\_CONNECTED, 757  
 PVSOCK\_ERR\_SOCK\_NOT\_OPEN, 757

**oscl\_socket\_listen.h**, 758  
 OSCL\_SOCKET\_LISTEN\_H\_- INCLUDEDd, 758

**OSCL\_SOCKET\_LISTEN\_H\_INCLUDEDd**  
 oscl\_socket\_listen.h, 758

**oscl\_socket\_method.h**, 759  
 MSEC\_TO\_MICROSEC, 759

**oscl\_socket\_recv.h**, 760

**oscl\_socket\_recv\_from.h**, 761

**oscl\_socket\_request.h**, 762

**oscl\_socket\_send.h**, 763

**oscl\_socket\_send\_to.h**, 764

**oscl\_socket\_serv\_imp.h**, 765

**oscl\_socket\_serv\_imp\_base.h**, 766

**oscl\_socket\_serv\_imp\_pv.h**, 767  
 OSCL\_EXCEPTSET\_FLAG, 767  
 OSCL\_READSET\_FLAG, 767  
 OSCL\_WRITESET\_FLAG, 767

**oscl\_socket\_serv\_imp\_reqlist.h**, 768

**oscl\_socket\_shutdown.h**, 769

**oscl\_socket\_stats.h**  
 EOscSocket\_DataRecv, 771  
 EOscSocket\_DataSent, 771  
 EOscSocket\_Except, 770  
 EOscSocket\_OS, 770  
 EOscSocket\_Readable, 770  
 EOscSocket\_RequestAO\_Canceled, 770  
 EOscSocket\_RequestAO\_Error, 770  
 EOscSocket\_RequestAO\_Success, 770  
 EOscSocket\_RequestAO\_Timeout, 770  
 EOscSocket\_ServPoll, 770  
 EOscSocket\_ServRequestCancelIssued, 771  
 EOscSocket\_ServRequestComplete, 771  
 EOscSocket\_ServRequestIssued, 770  
 EOscSocket\_Writable, 770  
 EOscSocketServ\_LastEvent, 770  
 EOscSocketServ\_LoopsckError, 771  
 EOscSocketServ\_LoopsckOk, 771  
 EOscSocketServ\_SelectActivity, 770  
 EOscSocketServ\_SelectNoActivity, 770  
 EOscSocketServ\_SelectRescheduleAsap, 770  
 EOscSocketServ\_SelectReschedulePoll, 770  
**oscl\_socket\_stats.h**, 770  
 TOscSocketServStatEvent, 770  
 TOscSocketStatEvent, 770

**oscl\_socket\_tuneables.h**, 772  
 PV\_OSCL\_SOCKET\_1MB\_RECV\_BUF, 772  
 PV\_OSCL\_SOCKET\_SERVER\_- LOGGER\_OUTPUT, 772  
 PV\_OSCL\_SOCKET\_STATS\_LOGGING, 772  
 PV\_SOCKET\_REQUEST\_AO\_- PRIORITY, 772  
 PV\_SOCKET\_SERVER, 772  
 PV\_SOCKET\_SERVER\_AO\_- INTERVAL\_MSEC, 773  
 PV\_SOCKET\_SERVER\_AO\_PRIORITY, 773  
 PV\_SOCKET\_SERVER\_IS\_THREAD, 773  
 PV\_SOCKET\_SERVER\_SELECT, 773  
 PV\_SOCKET\_SERVER\_SELECT\_- LOOPBACK\_SOCKET, 773

PV\_SOCKET\_SERVER\_SELECT\_-  
TIMEOUT\_MSEC, 773  
PV\_SOCKET\_SERVER\_THREAD\_-  
PRIORITY, 773  
PV\_SOCKET\_SERVI\_STATS, 773  
oscl\_socket\_types.h  
EPVIPAddMembership, 775  
EPVIMulticastTTL, 775  
EPVIPProtoIP, 775  
EPVIPProtoTCP, 775  
EPVIPTOS, 775  
EPVSocket, 775  
EPVSocket\_Last, 775  
EPVSocketAccept, 775  
EPVSocketBind, 775  
EPVSocketBothShutdown, 775  
EPVSocketCancel, 774  
EPVSocketConnect, 775  
EPVSocketFailure, 774  
EPVSocketListen, 775  
EPVSocketNotImplemented, 775  
EPVSocketPending, 774  
EPVSocketRecv, 775  
EPVSocketRecvFrom, 775  
EPVSocketRecvShutdown, 775  
EPVSocketSend, 775  
EPVSocketSendShutdown, 775  
EPVSocketSendTo, 775  
EPVSocketShutdown, 775  
EPVSocketSuccess, 774  
EPVSocketTimeout, 774  
EPVSockReuseAddr, 775  
oscl\_socket\_types.h, 774  
PVNETWORKADDRESS\_LEN, 774  
TPVSocketEvent, 774  
TPVSocketFxn, 775  
TPVSocketOptionLevel, 775  
TPVSocketOptionName, 775  
TPVSocketShutdown, 775  
OSCL\_SOCKOPT\_IP\_ADDMEMBERSHIP  
osclconfig\_io.h, 815  
OSCL\_SOCKOPT\_IP\_MULTICAST\_TTL  
osclconfig\_io.h, 815  
OSCL\_SOCKOPT\_IP\_TOS  
osclconfig\_io.h, 815  
OSCL\_SOCKOPT\_SOL\_REUSEADDR  
osclconfig\_io.h, 815  
OSCL\_SOL\_IP  
osclconfig\_io.h, 815  
OSCL\_SOL\_SOCKET  
osclconfig\_io.h, 815  
OSCL\_SOL\_TCP  
osclconfig\_io.h, 815  
OSCL\_SOL\_UDP

osclconfig\_io.h, 815  
oscl\_sqrt  
osclutil, 75  
OSCL\_StackString, 256  
osclutil, 75, 76  
OSCL\_StackString  
chartype, 257  
optype, 257  
OSCL\_String, 257  
other\_chartype, 257  
oscl\_stat  
osclo, 100, 101  
OSCL\_STAT\_BUF  
osclo, 96  
oscl\_stat\_buf, 258  
mode, 258  
perms, 258  
oscl\_statsfs  
osclo, 101  
OSCL\_STATIC\_CAST  
osclbase, 33  
oscl\_stdstring.h, 776  
oscl\_str\_escape\_xml  
osclutil, 76  
oscl\_str\_is\_valid\_utf8  
osclutil, 76  
oscl\_str\_need\_escape\_xml  
osclutil, 77  
oscl\_str\_ptr\_len.h, 778  
oscl\_str\_truncate\_utf8  
osclutil, 77  
oscl\_str\_unescape\_uri  
osclutil, 77, 78  
oscl\_strcat  
osclbase, 38, 39  
oscl\_strchr  
osclbase, 39  
oscl\_strcmp  
osclbase, 40  
OSCL\_StrError  
osclerror, 92  
OSCL\_String, 259  
~OSCL\_String, 260  
append\_rep, 260  
chartype, 260  
get\_cstr, 260  
get\_maxsize, 260  
get\_size, 261  
get\_str, 261  
hash, 261  
is\_writable, 261  
operator!=, 261  
operator+=, 261  
operator<, 261

---

operator<=, 262  
 operator=, 262  
 operator==, 262  
 operator>, 262  
 operator>=, 262  
 operator[], 262  
 OSCL\_FastString, 177  
 OSCL\_HeapString, 196  
 OSCL\_HeapStringA, 201  
 OSCL\_StackString, 257  
 OSCL\_String, 260  
 read, 262  
 set\_len, 262  
 set\_rep, 262, 263  
 setrep\_to\_char, 263  
 write, 263  
 oscl\_string.h, 779  
 oscl\_string\_containers.h, 780  
 oscl\_string\_rep.h, 781  
 oscl\_string\_uri.h, 782  
 oscl\_string\_utf8.h, 783  
 oscl\_string\_utils.h, 784  
 oscl\_string\_xml.h, 785  
 oscl\_strlen  
     osclbase, 40  
 oscl\_strncat  
     osclbase, 40, 41  
 oscl\_strcmp  
     osclbase, 41  
 oscl\_strncpy  
     osclbase, 42  
 oscl\_strchr  
     osclbase, 42, 43  
 oscl\_strset  
     osclbase, 43  
 oscl strstr  
     osclbase, 43, 44  
 Oscl\_Tag, 264  
     ~Oscl\_Tag, 264  
     operator<, 264  
     Oscl\_Tag, 264  
     tag, 264  
     tagAllocator, 264  
 Oscl\_Tag\_Base, 266  
     operator(), 267  
     size\_type, 267  
     tag\_ancestor, 267  
     tag\_base\_type, 267  
     tag\_base\_unit, 267  
     tag\_cmp, 267  
     tag\_copy, 267  
     tag\_depth, 267  
     tag\_len, 267  
 Oscl\_TagTree, 268  
     Oscl\_TagTree, 269  
     ~Oscl\_TagTree, 269  
     begin, 269  
     children\_type, 269  
     clear, 270  
     count, 270  
     empty, 270  
     end, 270  
     erase, 270  
     find, 270  
     insert, 271  
     map\_type, 269  
     node\_ptr, 269  
     node\_type, 269  
     operator=, 271  
     operator[], 271  
     Oscl\_TagTree, 269  
     pair\_iterator\_bool, 269  
     size, 271  
     size\_type, 269  
     tag\_base\_type, 269  
     tag\_type, 269  
     value\_type, 269  
 oscl\_tagtree.h, 786  
     OSCL\_DISABLE\_WARNING\_-  
         TRUNCATE\_DEBUG\_MESSAGE,  
         786  
 Oscl\_TagTree::const\_iterator, 272  
 Oscl\_TagTree::const\_iterator  
     const\_iterator, 273  
     mapit, 273  
     mapiter, 273  
     operator \*, 273  
     operator!=, 273  
     operator++, 273  
     operator-, 273  
     operator->, 273  
     operator==, 273  
     pointer, 273  
     reference, 273  
     self, 273  
 Oscl\_TagTree::iterator, 275  
 Oscl\_TagTree::iterator  
     iterator, 276  
     mapit, 276  
     mapiter, 276  
     operator \*, 276  
     operator!=, 276  
     operator++, 276  
     operator-, 276  
     operator->, 276  
     operator==, 276  
     pointer, 276

reference, 276  
 self, 276  
**Oscl\_TagTree::Node**, 278  
**Oscl\_TagTree::Node**  
     children, 279  
     children\_type, 279  
     depth, 279  
     Node, 279  
     parent, 279  
     sort\_children, 279  
     tag, 279  
     value, 279  
**Oscl\_TAlloc**, 280  
     ~Oscl\_TAlloc, 281  
     address, 281  
     alloc\_and\_construct, 281  
     alloc\_and\_construct\_fl, 281  
     allocate, 281  
     allocate\_fl, 281  
     const\_pointer, 281  
     const\_reference, 281  
     construct, 281  
     deallocate, 281  
     destroy, 281  
     destruct\_and\_dealloc, 281  
     pointer, 281  
     reference, 281  
     size\_type, 281  
     value\_type, 281  
**Oscl\_TAlloc::rebind**, 283  
     other, 283  
**oscl\_tan**  
     osclutil, 78  
**OSCL\_TCHAR**  
     osclbase, 34  
**oscl\_tcp\_socket.h**, 787  
**OSCL\_TEMPLATED\_DESTRUCTOR\_CALL**  
     osclbase, 33  
     osclconfig.h, 803  
**oscl\_thread.h**  
     EOscIThreadTerminate\_Join, 789  
     EOscIThreadTerminate\_Kill, 789  
     EOscIThreadTerminate\_NOP, 789  
     Start\_on\_creation, 788  
     Suspend\_on\_creation, 788  
     ThreadPriorityAboveNormal, 789  
     ThreadPriorityBelowNormal, 789  
     ThreadPriorityHighest, 789  
     ThreadPriorityLow, 788  
     ThreadPriorityLowest, 788  
     ThreadPriorityNormal, 789  
     ThreadPriorityTimeCritical, 789  
**oscl\_thread.h**, 788  
     OscIThread\_State, 788  
**OsclThreadPriority**, 788  
**TOscIThreadFuncPtr**, 788  
**TOscIThreadTerminate**, 789  
**OSCL\_THREAD DECL**  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
**oscl\_tickcount.h**, 790  
**oscl\_time.h**, 791  
**oscl\_timer.h**, 793  
**oscl\_tls.h**, 794  
**OSCL\_TLS\_BASE\_SLOTS**  
     osclbase, 33  
**OSCL\_TLS\_EXTERNAL\_SLOTS**  
     osclbase, 33  
**OSCL\_TLS\_GET\_FUNC**  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
**OSCL\_TLS\_ID\_BASE\_LAST**  
     osclbase, 45  
**OSCL\_TLS\_ID\_ERRORHOOK**  
     osclbase, 45  
**OSCL\_TLS\_ID\_MAGICNUM**  
     osclbase, 45  
**OSCL\_TLS\_ID\_OSCLREGISTRY**  
     osclbase, 45  
**OSCL\_TLS\_ID\_PAYLOADPARSER**  
     osclbase, 45  
**OSCL\_TLS\_ID\_PVERRORTRAP**  
     osclbase, 45  
**OSCL\_TLS\_ID\_PVLOGGER**  
     osclbase, 45  
**OSCL\_TLS\_ID\_PVMFRECOGNIZER**  
     osclbase, 45  
**OSCL\_TLS\_ID\_PVSCHEDULER**  
     osclbase, 45  
**OSCL\_TLS\_ID\_SDPMEDIAPARSER**  
     osclbase, 45  
**OSCL\_TLS\_ID\_SQLITE3**  
     osclbase, 45  
**OSCL\_TLS\_ID\_TEST**  
     osclbase, 45  
**OSCL\_TLS\_ID\_WMDRM**  
     osclbase, 45  
**OSCL\_TLS\_IS\_KEYED**  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
**OSCL\_TLS\_KEY\_CREATE\_FUNC**  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
**OSCL\_TLS\_KEY\_DELETE\_FUNC**  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
**OSCL\_TLS\_MAX\_SLOTS**  
     osclbase, 33

**OSCL\_TLS\_STORE\_FUNC**  
 osclconfig\_unix\_android.h, 842  
 osclconfig\_unix\_common.h, 846

**oscl\_tolower**  
 osclbase, 44

**OSCL\_TRAP\_ALLOC\_NEW**  
 osclmemory, 56

**OSCL\_TRAP\_AUDIT\_NEW**  
 osclmemory, 57

**OSCL\_TRAP\_NEW**  
 osclmemory, 57

**OSCL\_TRAPSTACK\_POP**  
 osclerror, 89

**OSCL\_TRAPSTACK\_POPDEALLOC**  
 osclerror, 89

**OSCL\_TRAPSTACK\_PUSH**  
 osclerror, 89

**oscl\_tree.h**, 795
 

- OSCL\_DISABLE\_WARNING\_-  
TRUNCATE\_DEBUG\_MESSAGE, 795

**OSCL\_TRY**  
 osclerror, 89

**OSCL\_TRY\_NO\_TLS**  
 osclerror, 89

**OSCL\_TStrPtrLen**  
 osclutil, 68

**oscl\_types.h**, 796

**oscl\_udp\_socket.h**, 797

**oscl\_UnicodeToUTF8**  
 osclutil, 78

**OSCL\_UNSIGNED\_CONST**  
 osclbase, 33  
 osclconfig.h, 803

**OSCL\_UNUSED\_ARG**  
 osclbase, 33

**OSCL\_UNUSED\_RETURN**  
 osclbase, 34

**oscl\_utf8conv.h**, 798

**oscl\_UTF8ToUnicode**  
 osclutil, 79

**oscl\_uuid.h**, 799
 

- BYTES\_IN\_UUID\_ARRAY, 799
- EMPTY\_UUID, 799
- OsclUid32, 799

**oscl\_uuid\_utils.h**, 800
 

- PV\_CHAR\_CLOSE\_BRACKET, 800
- PV\_CHAR\_COMMA, 800

**Oscl\_Vector**, 284
 

- ~Oscl\_Vector, 285
- back, 286
- begin, 286
- clear, 286
- const\_iterator, 285

const\_reference, 285  
 destroy, 286  
 end, 286  
 erase, 286  
 front, 287  
 insert, 287  
 iterator, 285  
 operator=, 287  
 operator[], 287  
 Oscl\_Vector, 285  
 pointer, 285  
 pop\_back, 287  
 push\_back, 288  
 push\_front, 288  
 reference, 285  
 value\_type, 285

**oscl\_vector.h**, 801

**Oscl\_Vector\_Base**, 289
 

- ~Oscl\_Vector\_Base, 290
- assign\_vector, 290
- bufsize, 292
- capacity, 290
- construct, 290
- destroy, 290
- elems, 292
- empty, 290
- erase, 290, 291
- insert, 291
- numelems, 292
- OsclPriorityQueueBase, 292
- pop\_back, 291
- push\_back, 291
- push\_front, 292
- reserve, 292
- size, 292
- sizeof\_T, 292

**OSCL\_VIRTUAL\_BASE**  
 osclbase, 34

**oscl\_vsnprintf**  
 osclutil, 79, 81

**oscl\_wchar**  
 osclbase, 34

**OSCL\_wFastString**, 293
 

- OSCL\_wFastString, 294

**OSCL\_wFastString**  
 ~OSCL\_wFastString, 294  
 chartype, 293  
 get\_cstr, 294  
 get\_maxsize, 294  
 get\_size, 294  
 get\_str, 294  
 operator=, 294  
 optype, 293  
 OSCL\_wFastString, 294

OSCL\_wString, 295  
 other\_chartype, 294  
 set, 295  
 set\_length, 295  
 OSCL\_wHeapString, 296  
 osclutil, 81  
 OSCL\_wHeapString  
   chartype, 297  
   otype, 297  
   OSCL\_wString, 297  
   other\_chartype, 297  
 OSCL\_wHeapStringA, 298  
   OSCL\_wHeapStringA, 299  
 OSCL\_wHeapStringA  
   ~OSCL\_wHeapStringA, 299  
   chartype, 299  
   get\_cstr, 299  
   get\_maxsize, 299  
   get\_size, 299  
   get\_str, 300  
   operator=, 300  
   otype, 299  
   OSCL\_wHeapStringA, 299  
   OSCL\_wString, 300  
   other\_chartype, 299  
   set, 300  
 OSCL\_WRITESET\_FLAG  
   oscl\_socket\_serv\_imp\_pv.h, 767  
 OSCL\_wStackString, 301  
 osclutil, 81  
 OSCL\_wStackString  
   chartype, 302  
   otype, 302  
   OSCL\_wString, 302  
   other\_chartype, 302  
 OSCL\_wString, 303  
   OSCL\_wFastString, 295  
   OSCL\_wHeapString, 297  
   OSCL\_wHeapStringA, 300  
   OSCL\_wStackString, 302  
   OSCL\_wString, 304  
 OSCL\_wString  
   ~OSCL\_wString, 304  
   append\_rep, 304  
   chartype, 304  
   get\_cstr, 304  
   get\_maxsize, 304  
   get\_size, 304  
   get\_str, 304  
   hash, 304  
   is\_writable, 305  
   operator!=, 305  
   operator+=, 305  
   operator<, 305  
   operator<=, 305  
   operator=, 305  
   operator==, 305  
   operator>, 305  
   operator>=, 305  
   operator[], 305  
   OSCL\_wString, 304  
   read, 305  
   set\_len, 306  
   set\_rep, 306  
   setrep\_to\_wide\_char, 306  
   write, 306  
 OSCL\_ZEROIZE  
   osclproc, 104  
 OsclAccept  
   osclconfig\_io.h, 815  
 OsclAcceptMethod, 307  
 OsclAcceptMethod  
   ~OsclAcceptMethod, 307  
   Accept, 307  
   AcceptRequest, 307  
   DiscardAcceptedSocket, 307  
   GetAcceptedSocket, 307  
   NewL, 307  
 OsclAcceptRequest, 308  
   OsclAcceptRequest, 308  
   OsclSocketI, 538  
 OsclAcceptRequest  
   Accept, 308  
   OsclAcceptRequest, 308  
 OsclActiveObject, 309  
   EPriorityHigh, 310  
   EPriorityHighest, 310  
   EPriorityIdle, 310  
   EPriorityLow, 310  
   EPriorityNominal, 310  
   OsclActiveObject, 310  
   OsclExecSchedulerCommonBase, 396  
   PVActiveBase, 614  
   PVActiveStats, 615  
   PVThreadContext, 634  
 OsclActiveObject  
   ~OsclActiveObject, 310  
   AddToScheduler, 310  
   Cancel, 310  
   DoCancel, 311  
   IsBusy, 311  
   OsclActiveObject, 310  
   OsclActivePriority, 310  
   PendComplete, 311  
   PendForExec, 311  
   Priority, 311  
   RemoveFromScheduler, 311  
   RunError, 311

RunIfNotReady, 312  
 SetBusy, 312  
 SetStatus, 312  
 Status, 312  
 StatusRef, 312  
**OsclActivePriority**  
 OsclActiveObject, 310  
**OsclAllocDestructDealloc**, 313  
**OsclAllocDestructDealloc**  
 ~OsclAllocDestructDealloc, 313  
**OsclAny**  
 osclbase, 34  
**OsclAOStatus**, 314  
 OsclAOStatus, 314  
**OsclAOStatus**  
 operator!=, 314  
 operator<, 314  
 operator<=, 314  
 operator=, 314  
 operator==, 314  
 operator>, 314  
 operator>=, 314  
 OsclAOStatus, 314  
 Value, 314  
**OsclAsyncFile**, 315  
**OsclAsyncFile**  
 ~OsclAsyncFile, 316  
 Close, 316  
 Delete, 316  
 EndOfFile, 316  
 Flush, 316  
 iNumOfRun, 317  
 iNumOfRunErr, 317  
 NewL, 316  
 Open, 316, 317  
 Read, 317  
 Seek, 317  
 Size, 317  
 Tell, 317  
 Write, 317  
**OsclAsyncFileBuffer**, 318  
**OsclAsyncFileBuffer**  
 ~OsclAsyncFileBuffer, 319  
 Buffer, 319  
 CleanInUse, 319  
 HasThisOffset, 319  
 Id, 319  
 IsInUse, 319  
 IsValid, 319  
 Length, 319  
 NewL, 319  
 Offset, 319  
 SetInUse, 319  
 SetOffset, 319  
 StartAsyncRead, 319  
 UpdateData, 319  
**OsclAuditCB**, 320  
**OsclAuditCB**, 320  
**OsclAuditCB**  
 OsclAuditCB, 320  
 pAudit, 320  
 pStatsNode, 320  
**OsclBase**  
 OsclSingletonRegistry, 533  
 OsclTLSRegistry, 595  
**osclbase**  
 \_OSCL\_Abort, 35  
 ALLOC\_AND\_CONSTRUCT, 32  
 ALLOCATE, 32  
 big\_endian\_to\_host, 35  
 Bind, 35  
 c\_bool, 34  
 CTIME\_BUFFER\_SIZE, 45  
 CtimeStrBuf, 34  
 host\_to\_big\_endian, 35  
 host\_to\_little\_endian, 36  
 int64, 34  
 ISO8601TIME\_BUFFER\_SIZE, 45  
 ISO8601timeStrBuf, 34  
 ISO8601ToRFC822, 36  
 little\_endian\_to\_host, 36  
 mbchar, 34  
 MICROSECONDS, 35  
 MILLISECONDS, 35  
 MSEC\_PER\_SEC, 45  
 NULL, 32  
 NULL\_TERM\_CHAR, 32  
 octet, 34  
 operator+, 36, 37  
 operator-, 37  
 operator==, 37  
 OSCL\_ABS, 32  
 OSCL\_ASSERT, 32  
 OSCL\_Assert, 37  
 oscl\_CIstrcmp, 37  
 oscl\_CIstrncmp, 38  
 OSCL\_COND\_EXPORT\_REF, 32  
 OSCL\_COND\_IMPORT\_REF, 32  
 OSCL\_CONST\_CAST, 32  
 OSCL\_DISABLE\_WARNING\_-  
     RETURN\_TYPE\_NOT\_UDT, 32  
 OSCL\_DISABLE\_WARNING\_-  
     TRUNCATE\_DEBUG\_MESSAGE,  
     32  
 OSCL\_DLL\_ENTRY\_POINT, 32  
 OSCL\_DLL\_ENTRY\_POINT\_DEFAULT,  
     33  
 OSCL\_DYNAMIC\_CAST, 33

OSCL\_HAS\_SINGLETON\_SUPPORT, 33  
 OSCL\_INLINE, 33  
 oscl\_isLetter, 38  
 OSCL\_MAX, 33  
 OSCL\_MIN, 33  
 OSCL\_PACKED\_VAR, 33  
 OSCL\_REINTERPRET\_CAST, 33  
 OSCL\_STATIC\_CAST, 33  
 oscl\_streat, 38, 39  
 oscl\_strchr, 39  
 oscl\_strcmp, 40  
 oscl\_strlen, 40  
 oscl\_strncat, 40, 41  
 oscl\_strncmp, 41  
 oscl\_strncpy, 42  
 oscl strrchr, 42, 43  
 oscl\_strset, 43  
 oscl strstr, 43, 44  
 OSCL\_TCHAR, 34  
 OSCL\_TEMPLATED\_DESTRUCTOR\_-  
     CALL, 33  
 OSCL\_TLS\_BASE\_SLOTS, 33  
 OSCL\_TLS\_EXTERNAL\_SLOTS, 33  
 OSCL\_TLS\_ID\_BASE\_LAST, 45  
 OSCL\_TLS\_ID\_ERRORHOOK, 45  
 OSCL\_TLS\_ID\_MAGICNUM, 45  
 OSCL\_TLS\_ID\_OSCLREGISTRY, 45  
 OSCL\_TLS\_ID\_PAYLOADPARSER, 45  
 OSCL\_TLS\_ID\_PVERRORTRAP, 45  
 OSCL\_TLS\_ID\_PVLOGGER, 45  
 OSCL\_TLS\_ID\_PVMFRECOGNIZER, 45  
 OSCL\_TLS\_ID\_PVSCHEDULER, 45  
 OSCL\_TLS\_ID\_SDPMEDIAPARSER, 45  
 OSCL\_TLS\_ID\_SQLITE3, 45  
 OSCL\_TLS\_ID\_TEST, 45  
 OSCL\_TLS\_ID\_WMDRM, 45  
 OSCL\_TLS\_MAX\_SLOTS, 33  
 oscl\_tolower, 44  
 OSCL\_UNSIGNED\_CONST, 33  
 OSCL\_UNUSED\_ARG, 33  
 OSCL\_UNUSED\_RETURN, 34  
 OSCL\_VIRTUAL\_BASE, 34  
 oscl\_wchar, 34  
 OsclAny, 34  
 OsclFloat, 34  
 PV8601TIME\_BUFFER\_SIZE, 45  
 PV8601timeStrBuf, 34  
 PV8601ToRFC822, 44  
 PVMEM\_INST\_LEVEL, 34  
 PVOsclBase\_Cleanup, 44  
 PVOsclBase\_Init, 44  
 RFC822ToPV8601, 45  
 SECONDS, 35  
 TimeUnits, 35  
  
 TOsclTlsKey, 35  
 uint, 35  
 uint64, 35  
 unix\_ntp\_offset, 45  
 USEC\_PER\_SEC, 45  
 OsclBasicDateStruct  
     osclconfig\_time.h, 837  
 OsclBasicTimeStruct  
     osclconfig\_time.h, 837  
 OsclBind  
     osclconfig\_io.h, 816  
 OsclBindMethod, 321  
 OsclBindMethod  
     ~OsclBindMethod, 321  
     Bind, 321  
     BindRequest, 321  
     NewL, 321  
 OsclBindRequest, 322  
     OsclBindRequest, 322  
 OsclBindRequest  
     Bind, 322  
     OsclBindRequest, 322  
 OsclBinIStream, 323  
     OsclBinIStream, 323  
 OsclBinIStream  
     ~OsclBinIStream, 323  
     get, 323  
     OsclBinIStream, 323  
     Read\_uint8, 323  
 OsclBinIStreamBigEndian, 325  
     OsclBinIStreamBigEndian, 326  
 OsclBinIStreamBigEndian  
     operator>>, 326  
     OsclBinIStreamBigEndian, 326  
     Read, 326  
     Read\_uint16, 326  
     Read\_uint32, 326  
 OsclBinIStreamLittleEndian, 328  
     OsclBinIStreamLittleEndian, 329  
 OsclBinIStreamLittleEndian  
     operator>>, 329  
     OsclBinIStreamLittleEndian, 329  
     Read\_uint16, 329  
     Read\_uint32, 329  
 OsclBinOStream, 330  
     OsclBinOStream, 330  
 OsclBinOStream  
     ~OsclBinOStream, 330  
     OsclBinOStream, 330  
     write, 330  
 OsclBinOStreamBigEndian, 331  
     OsclBinOStreamBigEndian, 332  
 OsclBinOStreamBigEndian  
     operator<<, 332

---

OsclBinOStreamBigEndian, 332  
 WriteUnsignedLong, 332  
 WriteUnsignedShort, 332  
 OsclBinOStreamLittleEndian, 333  
 OsclBinOStreamLittleEndian, 334  
 OsclBinOStreamLittleEndian  
     operator<<, 334  
 OsclBinOStreamLittleEndian, 334  
 WriteUnsignedLong, 334  
 WriteUnsignedShort, 334  
 OsclBinStream, 335  
     EOF\_STATE, 336  
     FAIL\_STATE, 336  
     GOOD\_STATE, 336  
     OsclBinStream, 336  
 OsclBinStream  
     Attach, 336  
     eof, 336  
     fail, 337  
     firstFragPtr, 338  
     fragsLeft, 338  
     good, 337  
     HaveRoomInCurrentBlock, 337  
     length, 338  
     nextFragPtr, 338  
     numFrags, 338  
     OsclBinStream, 336  
     pBasePosition, 338  
     PositionInBlock, 337  
     pPosition, 338  
     ReserveSpace, 337  
     Seek, 337  
     seekFromCurrentPosition, 337  
     specialFragBuffer, 338  
     state, 338  
     state\_t, 336  
     tellg, 337  
 OsclBuf, 339  
     OsclBuf, 340  
 OsclBuf  
     Delete, 340  
     Des, 340  
     Desc, 340  
     iBuffer, 340  
     iLength, 340  
     iMaxLength, 340  
     Length, 340  
     NewL, 340  
     OsclBuf, 340  
 OsclCloseSocket  
     osclconfig\_io.h, 816  
 OsclCoeActiveScheduler  
     OsclExecSchedulerBase, 390  
     OsclExecSchedulerCommonBase, 396  
     PVThreadContext, 634  
 OsclCoeActiveSchedulerBase  
     PVThreadContext, 634  
 OsclCompareLess, 341  
 OsclCompareLess  
     compare, 341  
 OsclComponentFactory  
     osclutil, 68  
 OsclComponentRegistry, 342  
     OsclComponentRegistry, 343  
 OsclComponentRegistry  
     ~OsclComponentRegistry, 343  
     CloseSession, 343  
     FindExact, 343  
     FindHierarchical, 343  
     iComponentIdCounter, 343  
     iData, 343  
     iMutex, 343  
     iNumSessions, 343  
     OpenSession, 343  
     OsclComponentRegistry, 343  
     Register, 343  
     Unregister, 343  
 OsclComponentRegistryData, 344  
 OsclComponentRegistryData  
     Find, 344  
     iVec, 344  
 OsclComponentRegistryElement, 345  
     OsclComponentRegistryElement, 345  
 OsclComponentRegistryElement  
     ~OsclComponentRegistryElement, 345  
     iComponentId, 345  
     iFactory, 345  
     iId, 345  
     Match, 345  
     operator=, 345  
     OsclComponentRegistryElement, 345  
 osclconfig  
     \_\_int16\_check\_\_, 24  
     \_\_int32\_check\_\_, 24  
     \_\_int8\_check\_\_, 24  
     \_\_uint16\_check\_\_, 24  
     \_\_uint32\_check\_\_, 24  
     \_\_uint8\_check\_\_, 24  
     OSCL\_ASSERT\_ALWAYS, 22  
     OSCL\_BYTE\_ORDER\_BIG\_ENDIAN,  
         22  
     OSCL\_BYTE\_ORDER\_LITTLE\_-  
         ENDIAN, 22  
     OSCL\_HAS\_ANDROID\_SUPPORT, 22  
     OSCL\_HAS\_BERKELEY\_SOCKETS, 22  
     OSCL\_HAS\_IPHONE\_SUPPORT, 22  
     OSCL\_HAS\_MSWIN\_PARTIAL\_-  
         SUPPORT, 22

OSCL\_HAS\_MSWIN\_SUPPORT, 22  
 OSCL\_HAS\_PRAGMA\_PACK, 22  
 OSCL\_HAS\_PTHREAD\_SUPPORT, 22  
 OSCL\_HAS\_PV\_C\_OS\_API\_-  
     MEMORY\_FUNCS, 23  
 OSCL\_HAS\_PV\_C\_OS\_SUPPORT, 23  
 OSCL\_HAS\_PV\_C\_OS\_TIME\_FUNCS,  
     23  
 OSCL\_HAS\_SAVAJE\_IO\_SUPPORT, 23  
 OSCL\_HAS\_SAVAJE\_SUPPORT, 23  
 OSCL\_HAS\_SEM\_TIMEDWAIT\_-  
     SUPPORT, 23  
 OSCL\_HAS\_SYMBIAN\_-  
     COMPATIBLE\_IO\_FUNCTION,  
     23  
 OSCL\_HAS\_SYMBIAN\_DNS\_SERVER,  
     23  
 OSCL\_HAS\_SYMBIAN\_ERRORTRAP,  
     23  
 OSCL\_HAS\_SYMBIAN\_MATH, 23  
 OSCL\_HAS\_SYMBIAN\_MEMORY\_-  
     FUNCS, 23  
 OSCL\_HAS\_SYMBIAN\_SCHEDULER,  
     23  
 OSCL\_HAS\_SYMBIAN\_SOCKET\_-  
     SERVER, 23  
 OSCL\_HAS\_SYMBIAN\_SUPPORT, 23  
 OSCL\_HAS\_SYMBIAN\_TIMERS, 23  
 OSCL\_HAS\_UNIX\_SUPPORT, 23  
 OSCL\_HAS\_UNIX\_TIME\_FUNCS, 23  
 OSCL\_INTEGERS\_WORD\_ALIGNED,  
     23  
 osclconfig.h, 802  
     \_\_TFS\_\_, 803  
 OSCL\_EXPORT\_REF, 803  
 OSCL\_HAS\_ANDROID\_FILE\_IO\_-  
     SUPPORT, 803  
 OSCL\_HAS\_ANDROID\_SUPPORT, 803  
 OSCL\_HAS\_PACKED\_STRUCT, 803  
 OSCL\_IMPORT\_REF, 803  
 OSCL\_NATIVE\_UINT64\_TYPE, 803  
 OSCL\_PACKED\_STRUCT\_BEGIN, 803  
 OSCL\_PACKED\_STRUCT\_END, 803  
 OSCL\_PACKED\_VAR, 803  
 OSCL\_RELEASE\_BUILD, 803  
 OSCL\_TEMPLATED\_DESTRUCTOR\_-  
     CALL, 803  
 OSCL\_UNSIGNED\_CONST, 803  
 PVLOGGER\_INST\_LEVEL, 803  
 osclconfig\_ansi\_memory.h, 804  
     OSCL\_HAS\_ANSI\_MEMORY\_FUNCS,  
     804  
     oscl\_memsize\_t, 804  
 osclconfig\_check.h, 805  
 osclconfig\_compiler\_warnings.h, 806  
     OSCL\_FUNCTION\_PTR, 806  
 osclconfig\_error.h, 807  
     OSCL\_HAS\_ERRNO\_H, 807  
     OSCL\_HAS\_EXCEPTIONS, 807  
     OSCL\_HAS\_SETJMP\_H, 807  
     OSCL\_HAS\_SYMBIAN\_ERRORTRAP,  
     807  
 osclconfig\_error\_check.h, 808  
 osclconfig\_global\_new\_delete.h, 809  
 osclconfig\_global\_placement\_new.h, 810  
     operator new, 810  
 osclconfig\_io.h, 811  
     OSCL\_AF\_INET, 815  
     OSCL\_FILE\_BUFFER\_MAX\_SIZE, 815  
     OSCL\_HAS\_ANSI\_64BIT\_FILE\_IO\_-  
         SUPPORT, 815  
     OSCL\_HAS\_ANSI\_FILE\_IO\_SUPPORT,  
     815  
     OSCL\_HAS\_BERKELEY\_SOCKETS,  
     815  
     OSCL\_HAS\_GLOB, 815  
     OSCL\_HAS\_LARGE\_FILE\_SUPPORT,  
     815  
     OSCL\_HAS\_MSWIN\_FILE\_IO\_-  
         SUPPORT, 815  
     OSCL\_HAS\_NATIVE\_FILE\_CACHE\_-  
         ENABLE, 815  
     OSCL\_HAS\_PV\_FILE\_CACHE, 815  
     OSCL\_HAS\_SOCKET\_SUPPORT, 815  
     OSCL\_HAS\_SYMBIAN\_-  
         COMPATIBLE\_IO\_FUNCTION,  
         815  
     OSCL\_HAS\_SYMBIAN\_DNS\_SERVER,  
     815  
     OSCL\_HAS\_SYMBIAN\_SOCKET\_-  
         SERVER, 815  
     OSCL\_IPPROTO\_IP, 815  
     OSCL\_IPPROTO\_TCP, 815  
     OSCL\_IPPROTO\_UDP, 815  
     OSCL\_SD\_BOTH, 815  
     OSCL\_SD\_RECEIVE, 815  
     OSCL\_SD\_SEND, 815  
     OSCL SOCK\_DGRAM, 815  
     OSCL SOCK\_STREAM, 815  
     OSCL SOCKOPT\_IP\_-  
         ADDMEMBERSHIP, 815  
     OSCL SOCKOPT\_IP\_MULTICAST\_-  
         TTL, 815  
     OSCL SOCKOPT\_IP\_TOS, 815  
     OSCL SOCKOPT\_SOL\_REUSEADDR,  
     815  
     OSCL SOL\_IP, 815  
     OSCL SOL\_SOCKET, 815

OSCL\_SOL\_TCP, 815  
 OSCL\_SOL\_UDP, 815  
 OsclAccept, 815  
 OsclBind, 816  
 OsclCloseSocket, 816  
 OsclConnect, 816  
 OsclConnectComplete, 816  
 OsclGetAsyncSockErr, 816  
 OsclGetDottedAddr, 816  
 OsclGetDottedAddrVector, 817  
 OsclGethostbyname, 817  
 OsclGetPeerName, 817  
 OsclJoin, 817  
 OsclListen, 818  
 OsclMakeInAddr, 818  
 OsclMakeSockAddr, 818  
 OsclPipe, 818  
 OsclReadFD, 818  
 OsclRecv, 818  
 OsclRecvFrom, 818  
 OsclSend, 819  
 OsclSendTo, 819  
 OsclSetNonBlocking, 819  
 OsclSetRecvBufferSize, 819  
 OsclSetSockOpt, 819  
 OsclShutdown, 819  
 OsclSocket, 820  
 OsclSocketCleanup, 820  
 OsclSocketSelect, 820  
 OsclSocketStartup, 820  
 OsclUnMakeInAddr, 820  
 OsclUnMakeSockAddr, 821  
 OsclValidInetAddr, 821  
 OsclWriteFD, 821  
 TIpMReq, 821  
 TOsclFileOffset, 821  
 TOsclHostent, 821  
 TOsclSockAddr, 821  
 TOsclSockAddrLen, 821  
 TOsclSocket, 821  
 osclconfig\_io\_check.h, 822  
   \_\_verify\_\_TOsclFileOffset\_\_defined\_\_,  
   822  
 osclconfig\_ix86.h, 823  
 osclconfig\_lib.h, 824  
   OSCL\_HAS\_RUNTIME\_LIB\_-  
     LOADING\_SUPPORT, 824  
   OSCL\_LIB\_READ\_DEBUG\_LIBS, 824  
   PV\_DYNAMIC\_LOADING\_CONFIG\_-  
     FILE\_PATH, 824  
   PV\_RUNTIME\_LIB\_FILENAME\_-  
     EXTENSION, 824  
 osclconfig\_lib\_check.h, 825  
 osclconfig\_limits\_typedefs.h, 826  
   OSCL\_CHAR\_IS\_SIGNED, 826  
   OSCL\_CHAR\_IS\_UNSIGNED, 826  
 osclconfig\_memory.h, 827  
   OSCL\_BYPASS\_MEMMGT, 827  
   OSCL\_HAS\_GLOBAL\_NEW\_DELETE,  
     827  
   OSCL\_HAS\_HEAP\_BASE\_SUPPORT,  
     827  
   OSCL\_HAS\_SYMBIAN\_MEMORY\_-  
     FUNCS, 827  
   PVMEM\_INST\_LEVEL, 827  
 osclconfig\_memory\_check.h, 828  
 osclconfig\_no\_os.h, 829  
 osclconfig\_proc.h, 830  
 osclconfig\_proc\_check.h, 831  
   \_\_verify\_\_TOsclConditionObject\_\_-  
     defined\_\_, 831  
   \_\_verify\_\_TOsclMutexObject\_\_defined\_\_,  
     831  
   \_\_verify\_\_TOsclSemaphoreObject\_\_-  
     defined\_\_, 831  
   \_\_verify\_\_TOsclThreadFuncArg\_\_-  
     defined\_\_, 831  
   \_\_verify\_\_TOsclThreadFuncRet\_\_-  
     defined\_\_, 831  
   \_\_verify\_\_TOsclThreadId\_\_defined\_\_, 831  
   \_\_verify\_\_TOsclThreadObject\_\_defined\_\_-  
     , 831  
 osclconfig\_proc\_unix\_android.h, 833  
   OSCL\_HAS\_NON\_PREEMPTIVE\_-  
     THREAD\_SUPPORT, 834  
   OSCL\_HAS\_PTHREAD\_SUPPORT, 834  
   OSCL\_HAS\_SEM\_TIMEDWAIT\_-  
     SUPPORT, 834  
   OSCL\_HAS\_SYMBIAN\_SCHEDULER,  
     834  
   OSCL\_HAS\_THREAD\_SUPPORT, 834  
   OSCL\_THREAD\_DECL, 834  
   TOsclConditionObject, 834  
   TOsclMutexObject, 834  
   TOsclSemaphoreObject, 834  
   TOsclThreadFuncArg, 834  
   TOsclThreadFuncRet, 834  
   TOsclThreadId, 834  
   TOsclThreadObject, 834  
 osclconfig\_proc\_unix\_common.h, 835  
   OSCL\_HAS\_NON\_PREEMPTIVE\_-  
     THREAD\_SUPPORT, 836  
   OSCL\_HAS\_PTHREAD\_SUPPORT, 836  
   OSCL\_HAS\_SEM\_TIMEDWAIT\_-  
     SUPPORT, 836  
   OSCL\_HAS\_SYMBIAN\_SCHEDULER,  
     836  
   OSCL\_HAS\_THREAD\_SUPPORT, 836

OSCL\_THREAD\_DECL, 836  
 TOsclConditionObject, 836  
 TOsclMutexObject, 836  
 TOsclSemaphoreObject, 836  
 TOsclThreadFuncArg, 836  
 TOsclThreadFuncRet, 836  
 TOsclThreadId, 836  
 TOsclThreadObject, 836  
 osclconfig\_time.h, 837  
   OSCL\_HAS\_UNIX\_TIME\_FUNCS, 837  
   OsclBasicDateStruct, 837  
   OsclBasicTimeStruct, 837  
 osclconfig\_time\_check.h, 838  
   \_\_Validate\_\_BasicTimeDateStruct\_\_, 838  
   \_\_Validate\_\_BasicTimeStruct\_\_, 838  
 osclconfig\_unix\_android.h, 839  
   \_\_STRLIT, 842  
   \_\_STRLIT\_CHAR, 842  
   \_\_STRLIT\_WCHAR, 842  
   INT64, 842  
   INT64\_HILO, 842  
   OSCL\_DISABLE\_INLINES, 842  
   OSCL\_HAS\_ANSI\_MATH\_SUPPORT,  
     842  
   OSCL\_HAS\_ANSI\_STDIO\_SUPPORT,  
     842  
   OSCL\_HAS\_ANSI\_STDLIB\_SUPPORT,  
     842  
   OSCL\_HAS\_ANSI\_STRING\_SUPPORT,  
     842  
   OSCL\_HAS\_ANSI\_WIDE\_STRING\_-  
     SUPPORT, 842  
   OSCL\_HAS\_BASIC\_LOCK, 842  
   OSCL\_HAS\_GLOBAL\_VARIABLE\_-  
     SUPPORT, 842  
   OSCL\_HAS\_IPHONE\_SUPPORT, 842  
   OSCL\_HAS\_MSWIN\_PARTIAL\_-  
     SUPPORT, 842  
   OSCL\_HAS\_MSWIN\_SUPPORT, 842  
   OSCL\_HAS\_SYMBIAN\_SUPPORT, 842  
   OSCL\_HAS\_TLS\_SUPPORT, 842  
   OSCL\_HAS\_UNICODE\_SUPPORT, 842  
   OSCL\_HAS\_UNIX\_SUPPORT, 842  
   OSCL\_MEMFRAG\_PTR\_BEFORE\_LEN,  
     842  
   OSCL\_NATIVE\_INT64\_TYPE, 842  
   OSCL\_NATIVE\_UINT64\_TYPE, 842  
   OSCL\_NATIVE\_WCHAR\_TYPE, 842  
   OSCL\_TLS\_GET\_FUNC, 842  
   OSCL\_TLS\_IS\_KEYED, 842  
   OSCL\_TLS\_KEY\_CREATE\_FUNC, 842  
   OSCL\_TLS\_KEY\_DELETE\_FUNC, 842  
   OSCL\_TLS\_STORE\_FUNC, 842  
 TOsclBasicLockObject, 842  
  
 TOsclTlsKey, 842  
 UINT64, 842  
 UINT64\_HILO, 842  
 osclconfig\_unix\_common.h, 843  
   \_\_STRLIT, 846  
   \_\_STRLIT\_CHAR, 846  
   \_\_STRLIT\_WCHAR, 846  
   INT64, 846  
   INT64\_HILO, 846  
   OSCL\_DISABLE\_INLINES, 846  
   OSCL\_HAS\_ANSI\_MATH\_SUPPORT,  
     846  
   OSCL\_HAS\_ANSI\_STDIO\_SUPPORT,  
     846  
   OSCL\_HAS\_ANSI\_STDLIB\_SUPPORT,  
     846  
   OSCL\_HAS\_ANSI\_STRING\_SUPPORT,  
     846  
   OSCL\_HAS\_ANSI\_WIDE\_STRING\_-  
     SUPPORT, 846  
   OSCL\_HAS\_BASIC\_LOCK, 846  
   OSCL\_HAS\_GLOBAL\_VARIABLE\_-  
     SUPPORT, 846  
   OSCL\_HAS\_MSWIN\_PARTIAL\_-  
     SUPPORT, 846  
   OSCL\_HAS\_MSWIN\_SUPPORT, 846  
   OSCL\_HAS\_SYMBIAN\_SUPPORT, 846  
   OSCL\_HAS\_TLS\_SUPPORT, 846  
   OSCL\_HAS\_UNICODE\_SUPPORT, 846  
   OSCL\_HAS\_UNIX\_SUPPORT, 846  
   OSCL\_MEMFRAG\_PTR\_BEFORE\_LEN,  
     846  
   OSCL\_NATIVE\_INT64\_TYPE, 846  
   OSCL\_NATIVE\_UINT64\_TYPE, 846  
   OSCL\_NATIVE\_WCHAR\_TYPE, 846  
   OSCL\_TLS\_GET\_FUNC, 846  
   OSCL\_TLS\_IS\_KEYED, 846  
   OSCL\_TLS\_KEY\_CREATE\_FUNC, 846  
   OSCL\_TLS\_KEY\_DELETE\_FUNC, 846  
   OSCL\_TLS\_STORE\_FUNC, 846  
 TOsclBasicLockObject, 846  
 TOsclTlsKey, 846  
 UINT64, 846  
 UINT64\_HILO, 846  
 osclconfig\_util.h, 847  
   OSCL\_CLOCK\_HAS\_DRIFT\_-  
     CORRECTION, 847  
   OSCL\_HAS\_SYMBIAN\_MATH, 847  
   OSCL\_HAS\_SYMBIAN\_TIMERS, 847  
   OSCL RAND\_MAX, 847  
   SLEEP\_ONE\_SEC, 847  
 osclconfig\_util\_check.h, 848  
 OsclConnect  
 osclconfig\_io.h, 816

OsclConnectComplete  
    osclconfig\_io.h, 816

OsclConnectMethod, 347

OsclConnectMethod  
    ~OsclConnectMethod, 347

    Connect, 347

    ConnectRequest, 347

    NewL, 347

OsclConnectRequest, 348

    OsclConnectRequest, 348

    OsclSocketI, 538

OsclConnectRequest  
    Connect, 348

    OsclConnectRequest, 348

OsclDestructDealloc, 349

OsclDestructDealloc  
    ~OsclDestructDealloc, 349

    destruct\_and\_dealloc, 349

OsclDNS, 350

    OsclSocketServ, 554

OsclDNS  
    ~OsclDNS, 350

    CancelGetHostByName, 350

    GetHostByName, 351

    NewL, 351

    OsclDNSRequestAO, 351

OsclDNSI, 352

    OsclDNSRequestAO, 364

    OsclSocketServI, 556

OsclDNSI  
    ~OsclDNSI, 352

    Close, 352

    DNSRequestParam, 353

    GetHostByName, 352

    GetHostNameResponseContainsAlias-  
        Info, 353

    GetHostNameSuccess, 353

    GetNextHost, 353

    GetNextHostSuccess, 353

    NewL, 353

    Open, 353

    OsclDNSRequest, 353

    OsclGetHostByNameRequest, 353

OsclDNSIBase, 354

    OsclDNSIBase, 355

OsclDNSIBase  
    ~OsclDNSIBase, 355

    CancelFxn, 355

    CancelGetHostByName, 355

    Close, 355

    GetHostByName, 355

    GetHostNameResponseContainsAlias-  
        Info, 355

    GetHostNameSuccess, 355

GetNextHost, 355

GetNextHostSuccess, 355

iAlloc, 356

iSocketServ, 356

IsReady, 355

Open, 355

OsclDNSIBase, 355

OsclDNSRequest, 356

OsclGetHostByNameRequest, 356

OsclDNSMethod, 357

    OsclDNSMethod, 358

    OsclDNSRequestAO, 364

OsclDNSMethod  
    Abort, 358

    AbortAll, 358

    CancelMethod, 358

    ConstructL, 358

    iAlloc, 359

    iDNSFxn, 359

    iDNSObserver, 359

    iDNSRequestAO, 359

    iId, 359

    iLogger, 359

    MethodDone, 358

    OsclDNSMethod, 358

    Run, 358

    StartMethod, 358

OsclDNSObserver, 360

OsclDNSObserver  
    ~OsclDNSObserver, 360

    HandleDNSEvent, 360

OsclDNSRequest, 361

    OsclDNSI, 353

    OsclDNSIBase, 356

    OsclDNSRequest, 361

    OsclDNSRequestAO, 364

OsclDNSRequest  
    ~OsclDNSRequest, 361

    Activate, 361

    CancelRequest, 361

    Complete, 361

    iActive, 361

    iDNSRequestAO, 361

    iDNSRequestParam, 361

    OsclDNSRequest, 361

OsclDNSRequestAO, 362

    OsclDNS, 351

    OsclDNSRequestAO, 363

OsclDNSRequestAO  
    Abort, 363

    Cancelled, 363

    ConstructL, 363

    DoCancel, 363

    Failure, 363

GetHostNameParam, 364  
 GetSocketError, 363  
 iDNSI, 364  
 iDNSMethod, 364  
 iLogger, 364  
 iSocketError, 364  
 NewRequest, 363  
 OsclDNSI, 364  
 OsclDNSMethod, 364  
 OsclDNSRequest, 364  
 OsclDNSRequestAO, 363  
 RequestDone, 363  
 Run, 363  
 Serv, 364  
 Success, 364  
 OsclDoubleLink, 365  
   OsclDoubleLink, 365  
 OsclDoubleLink  
   iNext, 365  
   InsertAfter, 365  
   InsertBefore, 365  
   iPrev, 365  
   OsclDoubleLink, 365  
   Remove, 365  
 OsclDoubleList, 366  
   OsclDoubleList, 366  
 OsclDoubleList  
   Head, 366  
   InsertHead, 366  
   InsertTail, 366  
   IsHead, 366  
   IsTail, 366  
   OsclDoubleList, 366  
   Tail, 366  
 OsclDoubleListBase, 367  
   OsclDoubleListBase, 368  
 OsclDoubleListBase  
   getHead, 368  
   getOffset, 368  
   iHead, 368  
   Insert, 368  
   InsertHead, 368  
   InsertTail, 368  
   iOffset, 368  
   IsEmpty, 368  
   OsclDoubleListBase, 368  
   Reset, 368  
   SetOffset, 368  
 OsclDoubleRunner, 369  
   OsclDoubleRunner, 369  
 OsclDoubleRunner  
   iHead, 369  
   iNext, 369  
   iOffset, 369  
   operator T \*, 369  
   operator++, 369  
   operator--, 369  
   OsclDoubleRunner, 369  
   Set, 369  
   SetToHead, 369  
   SetToTail, 369  
 OsclErrAlreadyExists  
   osclerror, 91  
 OsclErrAlreadyInstalled  
   osclerror, 91  
 OsclErrArgument  
   osclerror, 91  
 OsclErrBadHandle  
   osclerror, 91  
 OsclErrBusy  
   osclerror, 91  
 OsclErrCancelled  
   osclerror, 91  
 OsclErrCorrupt  
   osclerror, 91  
 OsclErrGeneral  
   osclerror, 91  
 OsclErrInvalidState  
   osclerror, 91  
 OsclErrNoHandler  
   osclerror, 91  
 OsclErrNoMemory  
   osclerror, 91  
 OsclErrNone  
   osclerror, 91  
 OsclErrNoResources  
   osclerror, 91  
 OsclErrNotInstalled  
   osclerror, 91  
 OsclErrNotReady  
   osclerror, 91  
 OsclErrNotSupported  
   osclerror, 91  
 OsclError, 371  
   OsclErrorTrapImp, 377  
   OsclExecSchedulerCommonBase, 396  
   OsclTrapStack, 598  
 OsclError  
   Leave, 371  
   LeaveIfError, 371  
   LeaveIfNull, 371  
   Pop, 371  
   PopDealloc, 371, 372  
   PushL, 372  
 osclerror  
   \_PV\_TRAP, 87  
   \_PV\_TRAP\_NO\_TLS, 87  
   internalLeave, 87

**OSCL\_BAD\_ALLOC\_EXCEPTION\_CODE**, [87](#)  
**OSCL\_CATCH**, [87](#)  
**OSCL\_CATCH\_ANY**, [87](#)  
**OSCL\_ERR\_NONE**, [88](#)  
**OSCL\_FIRST\_CATCH**, [88](#)  
**OSCL\_FIRST\_CATCH\_ANY**, [88](#)  
**OSCL\_GetLastError**, [92](#)  
**OSCL\_IsErrnoSupported**, [92](#)  
**OSCL\_JUMP\_MAX\_JUMP\_MARKS**, [88](#)  
**OSCL\_LAST\_CATCH**, [88](#)  
**OSCL\_LEAVE**, [88](#)  
**OSCL\_MAX\_TRAP\_LEVELS**, [89](#)  
**OSCL\_SetLastError**, [92](#)  
**OSCL\_StrError**, [92](#)  
**OSCL\_TRAPSTACK\_POP**, [89](#)  
**OSCL\_TRAPSTACK\_POPDEALLOC**, [89](#)  
**OSCL\_TRAPSTACK\_PUSH**, [89](#)  
**OSCL\_TRY**, [89](#)  
**OSCL\_TRY\_NO\_TLS**, [89](#)  
**OsclErrAlreadyExists**, [91](#)  
**OsclErrAlreadyInstalled**, [91](#)  
**OsclErrArgument**, [91](#)  
**OsclErrBadHandle**, [91](#)  
**OsclErrBusy**, [91](#)  
**OsclErrCancelled**, [91](#)  
**OsclErrCorrupt**, [91](#)  
**OsclErrGeneral**, [91](#)  
**OsclErrInvalidState**, [91](#)  
**OsclErrNoHandler**, [91](#)  
**OsclErrNoMemory**, [91](#)  
**OsclErrNone**, [91](#)  
**OsclErrNoResources**, [91](#)  
**OsclErrNotInstalled**, [91](#)  
**OsclErrNotReady**, [91](#)  
**OsclErrNotSupported**, [91](#)  
**OsclErrOverflow**, [91](#)  
**OsclErrSystemCallFailed**, [91](#)  
**OsclErrThreadContextIncorrect**, [91](#)  
**OsclErrTimeout**, [91](#)  
**OsclErrUnderflow**, [91](#)  
**OsclFailure**, [91](#)  
**OsclLeaveCode**, [92](#)  
**OsclPending**, [91](#)  
**OsclReturnCode**, [92](#)  
**OsclSuccess**, [91](#)  
**OsclTrapOperation**, [92](#)  
**PVError\_DoLeave**, [91](#)  
**PVERRORTRAP\_REGISTRY**, [91](#)  
**PVERRORTRAP\_REGISTRY\_ID**, [92](#)  
**OsclErrorAllocator**, [373](#)  
   **OsclErrorAllocator**, [373](#)  
**OsclErrorAllocator**

**allocate**, [373](#)  
**deallocate**, [373](#)  
**operator delete**, [374](#)  
**operator new**, [374](#)  
**OsclErrorAllocator**, [373](#)  
**OsclErrorTrap**, [375](#)  
   **OsclErrorTrapImp**, [377](#)  
   **OsclTrapStack**, [598](#)  
**OsclErrorTrap**  
   **Cleanup**, [375](#)  
   **GetErrorTrapImp**, [375](#)  
   **Init**, [375](#)  
**OsclErrorTrapImp**, [376](#)  
   **OsclJump**, [420](#)  
   **OsclTrapStack**, [598](#)  
**OsclErrorTrapImp**  
   **CPVInterfaceProxy**, [377](#)  
   **iJumpData**, [377](#)  
   **iLeave**, [377](#)  
   **iTrapStack**, [377](#)  
   **OsclError**, [377](#)  
   **OsclErrorTrap**, [377](#)  
   **OsclExecScheduler**, [377](#)  
   **OsclExecSchedulerCommonBase**, [377](#)  
   **OsclJump**, [377](#)  
   **OsclJumpMark**, [377](#)  
   **OsclScheduler**, [377](#)  
   **OsclTrapStack**, [377](#)  
   **Trap**, [376](#)  
   **TrapNoTls**, [376](#)  
   **UnTrap**, [376](#)  
**OsclErrOverflow**  
   **osclerror**, [91](#)  
**OsclErrSystemCallFailed**  
   **osclerror**, [91](#)  
**OsclErrThreadContextIncorrect**  
   **osclerror**, [91](#)  
**OsclErrTimeout**  
   **osclerror**, [91](#)  
**OsclErrUnderflow**  
   **osclerror**, [91](#)  
**OsclException**, [378](#)  
   **OsclException**, [378](#)  
**OsclException**  
   **getLeaveCode**, [378](#)  
   **OsclException**, [378](#)  
**OsclExclusiveArrayPtr**, [379](#)  
   **OsclExclusiveArrayPtr**, [380](#)  
**OsclExclusiveArrayPtr**  
   **~OsclExclusiveArrayPtr**, [380](#)  
   **\_Ptr**, [381](#)  
   **get**, [380](#)  
   **operator \***, [380](#)  
   **operator->**, [380](#)

operator=, 380  
 OsclExclusiveArrayPtr, 380  
 release, 381  
 set, 381  
 OsclExclusivePtr, 382  
   OsclExclusivePtr, 383  
 OsclExclusivePtr  
   ~OsclExclusivePtr, 383  
   \_Ptr, 384  
   get, 383  
   operator \*, 383  
   operator->, 383  
   operator=, 383  
   OsclExclusivePtr, 383  
   release, 384  
   set, 384  
 OsclExclusivePtrA, 385  
   OsclExclusivePtrA, 386  
 OsclExclusivePtrA  
   ~OsclExclusivePtrA, 386  
   \_Ptr, 387  
   get, 386  
   operator \*, 386  
   operator->, 386  
   operator=, 386  
   OsclExclusivePtrA, 386  
   release, 387  
   set, 387  
 OsclExecScheduler, 388  
   OsclErrorTrapImp, 377  
   OsclExecSchedulerBase, 390  
   OsclExecSchedulerCommonBase, 396  
   PVActiveBase, 614  
   PVActiveStats, 615  
   PVThreadContext, 634  
 OsclExecScheduler  
   Current, 388  
   OsclScheduler, 389  
   RegisterForCallback, 388  
   RunSchedulerNonBlocking, 388  
 OsclExecSchedulerBase, 390  
   PVThreadContext, 634  
 OsclExecSchedulerBase  
   OsclCoeActiveScheduler, 390  
   OsclExecScheduler, 390  
   PVActiveBase, 390  
 OsclExecSchedulerCommonBase, 391  
   EOtherExecStats\_Last, 393  
   EOtherExecStats\_NativeOS, 393  
   EOtherExecStats\_QueueTime, 393  
   EOtherExecStats\_ReleaseTime, 393  
   EOtherExecStats\_WaitTime, 393  
   OsclErrorTrapImp, 377  
   OsclExecSchedulerCommonBase, 394  
     PVActiveStats, 615  
     PVThreadContext, 634  
     OsclExecSchedulerCommonBase  
       ~OsclExecSchedulerCommonBase, 394  
       AddToExecTimerQ, 394  
       BeginScheduling, 394  
       BeginStats, 394  
       BlockingLoopL, 394  
       CallRunExec, 394  
       CleanupExecQ, 394  
       CleanupStatQ, 394  
       ConstructL, 394  
       ConstructStatQ, 394  
       EndScheduling, 394  
       EndStats, 394  
       Error, 394  
       FindPVBase, 394  
       GetId, 394  
       GetName, 394  
       GetScheduler, 394  
       iAlloc, 398  
       iBlockingMode, 398  
       iDebugLogger, 398  
       iDefAlloc, 398  
       iDelta, 398  
       iDoStop, 398  
       iDoSuspend, 398  
       iErrorTrapImp, 398  
       iExecTimerQ, 398  
       iGrandTotalTicks, 398  
       iLogger, 398  
       iLogPerfIndentStr, 398  
       iLogPerfIndentStrLen, 398  
       iLogPerfTotal, 398  
       iName, 398  
       iNativeMode, 398  
       IncLogPerf, 395  
       InitExecQ, 395  
       InstallScheduler, 395  
       iNumAOAdded, 398  
       iOtherExecStats, 398  
       iPVStatQ, 398  
       iPVStats, 398  
       iReadyQ, 398  
       iResumeSem, 398  
       IsInstalled, 395  
       IsStarted, 395  
       iStopper, 398  
       iStopperCrit, 398  
       iSuspended, 398  
       iThreadContext, 398  
       iTime, 398  
       iTimeCompareThreshold, 398  
       iTotalPercent, 398

iTicksTemp, 398  
 OsclActiveObject, 396  
 OsclCoeActiveScheduler, 396  
 OsclError, 396  
 OsclExecScheduler, 396  
 OsclExecSchedulerCommonBase, 394  
 OsclReadyQ, 396  
 OsclScheduler, 396  
 OsclTimerCompare, 396  
 OsclTimerObject, 398  
 PendComplete, 395  
 PVActiveBase, 398  
 PVActiveStats, 398  
 PVSchedulerStopper, 398  
 PVThreadContext, 398  
 RequestCanceled, 395  
 ResetLogPerf, 395  
 ResumeScheduler, 395  
 SetScheduler, 395  
 ShowStats, 395  
 ShowSummaryStats, 395  
 StartNativeScheduler, 395  
 StartScheduler, 395  
 StopScheduler, 395  
 SuspendScheduler, 396  
 TOtherExecStats, 393  
 UninstallScheduler, 396  
 UpdateTimers, 396  
 UpdateTimersMsec, 396  
 WaitForReadyAO, 396  
 OsclExtractFilenameFromFullPath  
   OsclFileManager, 406  
 OsclFailure  
   osclerror, 91  
 OsclFileCache, 400  
   Oscl\_File, 185  
   OsclFileCache, 401  
 OsclFileCache  
   ~OsclFileCache, 401  
   \_fixedCaches, 401  
   \_movableCache, 401  
   AddFixedCache, 401  
   Close, 401  
   EndOfFile, 401  
   FileSize, 401  
   Flush, 401  
   Open, 401  
   OsclFileCache, 401  
   OsclFileCacheBuffer, 401  
   Read, 401  
   Seek, 401  
   Tell, 401  
   Write, 401  
 OsclFileCacheBuffer, 402  
 Oscl\_File, 185  
 OsclFileCache, 401  
 OsclFileCacheBuffer, 403  
 OsclFileCacheBuffer capacity, 403  
 Contains, 403  
 currentPos, 403  
 endPos, 403  
 filePosition, 403  
 FillFromFile, 403  
 iContainer, 403  
 isFixed, 403  
 IsUpdated, 403  
 OsclFileCacheBuffer, 403  
 pBuffer, 403  
 Preceeds, 403  
 PrepRead, 403  
 PrepWrite, 403  
 SetPosition, 403  
 updateEnd, 403  
 updateStart, 403  
 usableSize, 403  
 WriteUpdatesToFile, 403  
 OsclFileHandle, 404  
   OsclFileHandle, 404  
 OsclFileHandle  
   Handle, 404  
   Oscl\_File, 404  
   OsclFileHandle, 404  
 OsclFileManager, 405  
   OSCL\_FILE\_ATTRIBUTE\_ARCHIVE, 405  
   OSCL\_FILE\_ATTRIBUTE\_DIRECTORY, 405  
   OSCL\_FILE\_ATTRIBUTE\_HIDDEN, 405  
   OSCL\_FILE\_ATTRIBUTE\_NORMAL, 405  
   OSCL\_FILE\_ATTRIBUTE\_READONLY, 405  
   OSCL\_FILE\_ATTRIBUTE\_SYSTEM, 405  
 OsclFileManager  
   OSCL\_FILE\_ATTRIBUTE\_TYPE, 405  
   OsclExtractFilenameFromFullPath, 406  
   OsclGetFileAttributes, 406  
   OsclGetFileCreationTime, 406, 407  
   OsclGetFileLastAccessTime, 407  
   OsclGetFileLastWriteTime, 408  
   OsclGetSize, 408  
 OsclFileStats, 410  
   OsclFileStats, 410  
 OsclFileStats  
   End, 410  
   Log, 410

LogAll, 410  
 OsclFileStats, 410  
 Start, 410  
 OsclFileStatsItem, 411  
 OsclFileStatsItem  
   iOpCount, 411  
   iParam, 411  
   iParam2, 411  
   iStartTick, 411  
   iTTotalTicks, 411  
 OsclFloat  
   osclbase, 34  
 OsclGetAsyncSockErr  
   osclconfig\_io.h, 816  
 OsclGetDottedAddr  
   osclconfig\_io.h, 816  
 OsclGetDottedAddrVector  
   osclconfig\_io.h, 817  
 OsclGetFileAttributes  
   OsclFileManager, 406  
 OsclGetFileCreationTime  
   OsclFileManager, 406, 407  
 OsclGetFileLastAccessTime  
   OsclFileManager, 407  
 OsclGetFileLastWriteTime  
   OsclFileManager, 408  
 OsclGetFileSize  
   OsclFileManager, 408  
 OsclGethostbyname  
   osclconfig\_io.h, 817  
 OsclGetHostByNameMethod, 412  
   OsclGetHostByNameRequest, 413  
 OsclGetHostByNameMethod  
   ~OsclGetHostByNameMethod, 412  
   GetHostName, 412  
   NewL, 412  
 OsclGetHostByNameRequest, 413  
   OsclIDNSI, 353  
   OsclIDNSIBase, 356  
 OsclGetHostByNameRequest  
   OsclGetHostByNameMethod, 413  
 OsclGetPeerName  
   osclconfig\_io.h, 817  
 OsclInit, 414  
 OsclInit  
   Cleanup, 414  
   Init, 414  
 OsclInteger64Transport, 415  
 OsclInteger64Transport  
   iHigh, 415  
   iLow, 415  
 osclo  
   EOsclFileOp\_Close, 97  
   EOsclFileOp\_EndOfFile, 97  
     EOsclFileOp\_Flush, 97  
     EOsclFileOp\_Last, 98  
     EOsclFileOp\_NativeClose, 97  
     EOsclFileOp\_NativeEndOfFile, 98  
     EOsclFileOp\_NativeFlush, 98  
     EOsclFileOp\_NativeOpen, 97  
     EOsclFileOp\_NativeRead, 97  
     EOsclFileOp\_NativeSeek, 98  
     EOsclFileOp\_NativeSetSize, 98  
     EOsclFileOp\_NativeSize, 98  
     EOsclFileOp\_NativeTell, 98  
     EOsclFileOp\_NativeWrite, 98  
     EOsclFileOp\_Open, 97  
     EOsclFileOp\_Read, 97  
     EOsclFileOp\_Seek, 97  
     EOsclFileOp\_SetSize, 97  
     EOsclFileOp\_Size, 97  
     EOsclFileOp\_Tell, 97  
     EOsclFileOp\_Write, 97  
     EPVDNSCancel, 98  
     EPVDNSFailure, 98  
     EPVDNSGetHostByName, 98  
     EPVDNSPending, 98  
     EPVDNSSuccess, 98  
     EPVDNSTimeout, 98  
     oscl\_chdir, 98  
     OSCL\_FILE\_CHAR\_PATH\_-  
       DELIMITER, 96  
     OSCL\_FILE\_STATS\_LOGGER\_NODE,  
       96  
     OSCL\_FILE\_WCHAR\_PATH\_-  
       DELIMITER, 96  
     OSCL\_FILEMGMT\_E\_ALREADY\_-  
       EXISTS, 97  
     OSCL\_FILEMGMT\_E\_NO\_MATCH, 97  
     OSCL\_FILEMGMT\_E\_NOT\_EMPTY, 97  
     OSCL\_FILEMGMT\_E\_NOT\_-  
       IMPLEMENTED, 97  
     OSCL\_FILEMGMT\_E\_OK, 97  
     OSCL\_FILEMGMT\_E\_PATH\_NOT\_-  
       FOUND, 97  
     OSCL\_FILEMGMT\_E\_PATH\_TOO\_-  
       LONG, 97  
     OSCL\_FILEMGMT\_E\_PERMISSION\_-  
       DENIED, 97  
     OSCL\_FILEMGMT\_E\_SYS\_SPECIFIC,  
       97  
     OSCL\_FILEMGMT\_E\_UNKNOWN, 97  
     OSCL\_FILEMGMT\_ERR\_TYPE, 97  
     OSCL\_FILEMGMT\_MODE\_DIR, 97  
     OSCL\_FILEMGMT\_MODES, 97  
     OSCL\_FILEMGMT\_PERMS, 97  
     OSCL\_FILEMGMT\_PERMS\_EXECUTE,  
       97

OSCL\_FILEMGMT\_PERMS\_READ, 97  
 OSCL\_FILEMGMT\_PERMS\_WRITE, 97  
 OSCL\_FSSTAT, 96  
 oscl\_getcwd, 98, 99  
 OSCL\_IO\_EXTENSION\_MAXLEN, 96  
 OSCL\_IO\_FILENAME\_MAXLEN, 96  
 oscl\_mkdir, 99  
 oscl\_rename, 99, 100  
 oscl\_rmdir, 100  
 oscl\_stat, 100, 101  
 OSCL\_STAT\_BUFS, 96  
 oscl\_statfs, 101  
 TOsclFileHandle, 96  
 TOsclFileOffsetInt32, 96  
 TOsclFileOp, 97  
 TPVDNSEvent, 98  
 TPVDNSFxN, 98  
 OsclIpMReq, 416  
   OsclIpMReq, 416  
 OsclIpMReq  
   interfaceAddr, 416  
   multicastAddr, 416  
   OsclIpMReq, 416  
 OsclIPSocketI, 417  
   OsclIPSocketI, 418  
 OsclIPSocketI  
   ~OsclIPSocketI, 418  
   Alloc, 418  
   Bind, 418  
   Close, 418  
   ConstructL, 418  
   GetPeerName, 418  
   GetRecvData, 418  
   GetSendData, 418  
   iAddress, 419  
   iAlloc, 419  
   iId, 419  
   iLogger, 419  
   iObserver, 419  
   iSocket, 419  
   iSocketServ, 419  
   Join, 418  
   OsclIPSocketI, 418  
   OsclSocketMethod, 419  
   OsclSocketRequestAO, 419  
   SetOptionToReuseAddress, 418  
   SetRecvBufferSize, 418  
   SetTOS, 418  
   SocketServ, 418  
   ThreadLogoff, 418  
   ThreadLogon, 418  
 OsclJoin  
   osclconfig\_io.h, 817  
 OsclJump, 420  
   OsclErrorTrapImp, 377  
   OsclJump  
     ~OsclJump, 420  
     Jump, 420  
     OsclErrorTrapImp, 420  
     StaticJump, 420  
     Top, 420  
   OsclJumpMark  
     OsclErrorTrapImp, 377  
 OsclLeaveCode  
   osclerror, 92  
 OsclListen  
   osclconfig\_io.h, 818  
 OsclListenMethod, 421  
 OsclListenMethod  
   ~OsclListenMethod, 421  
   Listen, 421  
   ListenRequest, 421  
   NewL, 421  
   OsclListenRequest, 422  
     OsclListenRequest, 422  
 OsclListenRequest  
   Listen, 422  
   OsclListenRequest, 422  
 OsclLockBase, 423  
 OsclLockBase  
   ~OsclLockBase, 423  
   Lock, 423  
   Unlock, 423  
 OsclMakeInAddr  
   osclconfig\_io.h, 818  
 OsclMakeSockAddr  
   osclconfig\_io.h, 818  
 OsclMem, 424  
   OsclMemGlobalAuditObject, 440  
 OsclMem  
   Cleanup, 424  
   Init, 424  
 OsclMemAllocator, 425  
 OsclMemAllocator  
   allocate, 425  
   allocate\_fl, 425  
   deallocate, 425  
 OsclMemAllocDestructDealloc, 426  
 OsclMemAllocDestructDealloc  
   allocate, 426  
   allocate\_fl, 426  
   deallocate, 426  
   destruct\_and\_dealloc, 426  
 OsclMemAudit, 428  
   OsclMemAudit, 428  
 OsclMemAudit  
   ~OsclMemAudit, 428  
   GetLock, 429

MM\_AddTag, 429  
 MM\_allocate, 429  
 MM\_CreateAllocNodeInfo, 429  
 MM\_deallocate, 429  
 MM\_GetAllocNo, 429  
 MM\_GetAllocNodeInfo, 429  
 MM\_GetExistingTag, 430  
 MM\_GetMode, 430  
 MM\_GetNumAllocNodes, 430  
 MM\_GetOverheadStats, 430  
 MM\_GetPostfillPattern, 430  
 MM\_GetPrefillPattern, 430  
 MM\_GetRefCount, 430  
 MM\_GetRootNode, 431  
 MM\_GetStats, 431  
 MM\_GetStatsInDepth, 431  
 MM\_GetTagName, 431  
 MM\_GetTreeNodes, 431  
 MM\_ReleaseAllocNodeInfo, 431  
 MM\_SetFailurePoint, 431  
 MM\_SetMode, 432  
 MM\_SetPostfillPattern, 432  
 MM\_SetPrefillPattern, 432  
 MM\_SetTagLevel, 432  
 MM\_UnsetFailurePoint, 432  
 MM\_Validate, 432  
 OsclMemAudit, 428  
 OsclMemGlobalAuditObject, 433  
**OSCLMemAutoPtr**, 434  
 OSCLMemAutoPtr, 435  
**OSCLMemAutoPtr**  
 ~OSCLMemAutoPtr, 435  
 \_Ownership, 437  
 allocate, 436  
 deallocate, 436  
 get, 436  
 operator \*, 436  
 operator->, 436  
 operator=, 436  
 OSCLMemAutoPtr, 435  
 release, 436  
 setWithoutOwnership, 436  
 takeOwnership, 437  
 OsclMemBasicAllocator, 438  
 OsclMemBasicAllocator  
 allocate, 438  
 deallocate, 438  
 OsclMemBasicAllocDestructDealloc, 439  
 OsclMemBasicAllocDestructDealloc  
 allocate, 439  
 deallocate, 439  
 destruct\_and\_dealloc, 439  
 OsclMemGlobalAuditObject, 440  
 OsclMemAudit, 433

OsclMemGlobalAuditObject  
 audit\_type, 440  
 getGlobalMemAuditObject, 440  
 OsclMem, 440  
**OsclMemInit**  
 osclmemory, 61  
**osclmemory**  
 \_OSCL\_CLEANUP\_BASE\_CLASS, 49  
 \_OSCL\_TRAP\_NEW, 49  
 \_oscl\_audit\_calloc, 58  
 \_oscl\_audit\_free, 58  
 \_oscl\_audit\_malloc, 58  
 \_oscl\_audit\_new, 58  
 \_oscl\_audit\_realloc, 59  
 \_oscl\_calloc, 59  
 \_oscl\_default\_audit\_calloc, 59  
 \_oscl\_default\_audit\_malloc, 59  
 \_oscl\_default\_audit\_new, 59  
 \_oscl\_default\_audit\_realloc, 59  
 \_oscl\_free, 59  
 \_oscl\_malloc, 59  
 \_oscl\_realloc, 59  
 ALLOC\_NODE\_FLAG, 61  
 COMPUTE\_MEM\_ALIGN\_SIZE, 50  
 DEFAULT\_MM\_AUDIT\_MODE, 51  
 DEFAULT\_POSTFILL\_PATTERN, 51  
 DEFAULT\_PREFILL\_PATTERN, 51  
 FENCE\_PATTERN, 51  
 MEM\_ALIGN\_SIZE, 51  
 MIN\_FENCE\_SIZE, 51  
 MM\_ALLOC\_MAX\_QUERY\_-  
 FILENAME\_LEN, 51  
 MM\_ALLOC\_MAX\_QUERY\_TAG\_LEN,  
 51  
 MM\_AllocNodeAutoPtr, 58  
**MM\_AUDIT\_ALLOC\_NODE\_-**  
 ENABLE\_FLAG, 51  
**MM\_AUDIT\_ALLOC\_NODE\_-**  
 SUPPORT, 51  
**MM\_AUDIT\_FAILURE\_SIMULATION\_-**  
 SUPPORT, 51  
 MM\_AUDIT\_FENCE\_SUPPORT, 51  
 MM\_AUDIT\_FILL\_SUPPORT, 51  
**MM\_AUDIT\_INCLUDE\_ALL\_HEAP\_-**  
 VALIDATION, 51  
 MM\_AUDIT\_POSTFILL\_FLAG, 51  
 MM\_AUDIT\_PREFILL\_FLAG, 51  
**MM\_AUDIT\_SUPPRESS\_FILENAME\_-**  
 FLAG, 51  
**MM\_AUDIT\_VALIDATE\_ALL\_HEAP\_-**  
 FLAG, 51  
**MM\_AUDIT\_VALIDATE\_BLOCK**, 51  
**MM\_AUDIT\_VALIDATE\_ON\_FREE\_-**  
 FLAG, 51

MM\_StatsNodeTagTreeType, 58  
 MMAuditCharAutoPtr, 58  
 MMAuditUint8AutoPtr, 58  
 operator delete, 59  
 operator delete[], 59  
 operator new, 59  
 operator new[], 59  
 OSCL\_ALLOC\_DELETE, 51  
 OSCL\_ALLOC\_NEW, 52  
 OSCL\_ARRAY\_DELETE, 52  
 OSCL\_ARRAY\_NEW, 52  
 OSCL\_AUDIT\_ARRAY\_NEW, 52  
 OSCL\_AUDIT\_CALLOC, 53  
 OSCL\_AUDIT\_MALLOC, 53  
 OSCL\_AUDIT\_NEW, 53  
 OSCL\_AUDIT\_REALLOC, 54  
 OSCL\_CALLOC, 54  
 oscl\_calloc, 54  
 OSCL\_CLEANUP\_BASE\_CLASS, 54  
 OSCL\_DEFAULT\_FREE, 55  
 OSCL\_DEFAULT\_MALLOC, 55  
 OSCL\_DELETE, 55  
 OSCL\_DISABLE\_WARNING\_-  
     RETURN\_TYPE\_NOT\_UDT, 55  
 OSCL\_DISABLE\_WARNING\_-  
     TRUNCATE\_DEBUG\_MESSAGE,  
     55  
 OSCL\_FREE, 55  
 oscl\_free, 55  
 OSCL\_HAS\_GLOBAL\_NEW\_DELETE,  
     55  
 OSCL\_MALLOC, 56  
 oscl\_malloc, 56  
 oscl\_mem\_aligned\_size, 59  
 oscl\_memcmp, 60  
 oscl\_memcpy, 60  
 oscl\_memmove, 60  
 oscl\_memmove32, 60  
 oscl\_memset, 61  
 OSCL\_NEW, 56  
 OSCL\_PLACEMENT\_NEW, 56  
 OSCL\_REALLOC, 56  
 oscl\_realloc, 56  
 OSCL\_TRAP\_ALLOC\_NEW, 56  
 OSCL\_TRAP\_AUDIT\_NEW, 57  
 OSCL\_TRAP\_NEW, 57  
 OsclMemInit, 61  
 OsclMemStatsNodeAutoPtr, 58  
 OsclTagTreeType, 58  
 TagTree\_Allocator, 58  
 OsclMemoryFragment, 441  
 OsclMemoryFragment  
     len, 441  
     ptr, 441  
 OsclMemPoolFixedChunkAllocator, 442  
 OsclMemPoolFixedChunkAllocator, 443  
 OsclMemPoolFixedChunkAllocator  
     ~OsclMemPoolFixedChunkAllocator, 443  
     addRef, 443  
     allocate, 443  
     CancelFreeChunkAvailableCallback, 443  
     createmempool, 443  
     deallocate, 444  
     destroymempool, 444  
     enablenullpointerreturn, 444  
     iCheckNextAvailableFreeChunk, 445  
     iChunkAlignment, 445  
     iChunkSize, 445  
     iChunkSizeMemAligned, 445  
     iEnableNullPtrReturn, 445  
     iFreeMemChunkList, 445  
     iMemPool, 445  
     iMemPoolAligned, 445  
     iMemPoolAllocator, 445  
     iNextAvailableContextData, 445  
     iNumChunk, 445  
     iObserver, 445  
     iRefCount, 445  
     notifyfreechunkavailable, 444  
     OsclMemPoolFixedChunkAllocator, 443  
     removeRef, 444  
 OsclMemPoolFixedChunkAllocatorObserver,  
     446  
 OsclMemPoolFixedChunkAllocatorObserver  
     ~OsclMemPoolFixedChunkAllocatorObserver,  
     446  
     freechunkavailable, 446  
 OsclMemPoolResizableAllocator, 447  
 OsclMemPoolResizableAllocator, 448  
 OsclMemPoolResizableAllocator  
     ~OsclMemPoolResizableAllocator, 448  
     addnewmempoolbuffer, 448  
     addRef, 448  
     allocate, 449  
     allocateblock, 449  
     CancelFreeChunkAvailableCallback, 449  
     CancelFreeMemoryAvailableCallback, 449  
     deallocate, 449  
     deallocateblock, 449  
     destroyallmempoolbuffers, 449  
     enablenullpointerreturn, 449  
     findfreeblock, 450  
     getAllocatedSize, 450  
     getAvailableSize, 450  
     getBufferSize, 450  
     getLargestContiguousFreeBlockSize, 450  
     getMemPoolBufferAllocatedSize, 450  
     getMemPoolBufferSize, 450

iBlockInfoAlignedSize, 452  
 iBufferInfoAlignedSize, 452  
 iCheckFreeMemoryAvailable, 452  
 iCheckNextAvailable, 452  
 iEnableNullPtrReturn, 452  
 iExpectedNumBlocksPerBuffer, 452  
 iFreeMemContextData, 452  
 iFreeMemPoolObserver, 452  
 iMaxNewMemPoolBufferSz, 452  
 iMemPoolBufferAllocator, 452  
 iMemPoolBufferList, 452  
 iMemPoolBufferNumLimit, 452  
 iMemPoolBufferSize, 452  
 iNextAvailableContextData, 452  
 iObserver, 452  
 iRefCount, 452  
 iRequestedAvailableFreeMemSize, 452  
 iRequestedNextAvailableSize, 452  
 memoryPoolBufferMgmtOverhead, 450  
 notifyfreeblockavailable, 450  
 notifyfreememoryavailable, 450  
 OsclMemPoolResizableAllocator, 448  
 removeRef, 451  
 setMaxSzForNewMemPoolBuffer, 451  
 trim, 451  
 validateblock, 451  
 OsclMemPoolResizableAllocator::MemPoolBlockInfo, 453  
 OsclMemPoolResizableAllocator::MemPoolBlockInfo  
   iBlockBuffer, 453  
   iBlockPostFence, 453  
   iBlockPreFence, 453  
   iBlockSize, 453  
   iNextFreeBlock, 453  
   iParentBuffer, 453  
   iPrevFreeBlock, 453  
 OsclMemPoolResizableAllocator::MemPoolBufferInfo, 454  
 OsclMemPoolResizableAllocator::MemPoolBufferInfo  
   iAllocatedSz, 454  
   iBufferPostFence, 454  
   iBufferPreFence, 454  
   iBufferSize, 454  
   iEndAddr, 454  
   iNextFreeBlock, 454  
   iNumOutstanding, 454  
   iStartAddr, 454  
 OsclMemPoolResizableAllocatorMemoryObserver, 455  
 OsclMemPoolResizableAllocatorMemoryObserver

~OsclMemPoolResizableAllocatorMemoryObserver, 455  
 freememoryavailable, 455  
 OsclMemPoolResizableAllocatorObserver, 456  
 OsclMemPoolResizableAllocatorObserver  
   ~OsclMemPoolResizableAllocatorObserver, 456  
   freeblockavailable, 456  
 OsclMemStatsNode, 457  
   OsclMemStatsNode, 457  
 OsclMemStatsNode  
   ~OsclMemStatsNode, 457  
   operator delete, 457  
   operator new, 457  
   OsclMemStatsNode, 457  
   pMMFIParam, 457  
   pMMStats, 457  
   reset, 457  
   tag, 457  
 OsclMemStatsNodeAutoPtr  
   osclmemory, 58  
 OsclMutex, 458  
   OsclMutex, 458  
 OsclMutex  
   ~OsclMutex, 458  
   Close, 458  
   Create, 458  
   Lock, 459  
   OsclMutex, 458  
   TryLock, 459  
   Unlock, 459  
 OsclNameString, 460  
   OsclNameString, 460  
 OsclNameString  
   MaxLen, 460  
   OsclNameString, 460  
   Set, 460  
   Str, 460  
 OsclNativeFile, 461  
   Oscl\_FileServer, 193  
   OsclNativeFile, 462  
 OsclNativeFile  
   ~OsclNativeFile, 462  
   Close, 462  
   EndOfFile, 462  
   Flush, 462  
   GetError, 462  
   GetReadAsyncNumElements, 462  
   HasAsyncRead, 462  
   Mode, 462  
   Open, 462  
   OsclNativeFile, 462  
   Read, 462  
   ReadAsync, 462

ReadAsyncCancel, 462  
 Seek, 463  
 SetSize, 463  
 Size, 463  
 Tell, 463  
 Write, 463  
 OsclNativeFileParams, 464  
   OsclNativeFileParams, 464  
 OsclNativeFileParams  
   iAsyncReadBufferSize, 464  
   iNativeAccessMode, 464  
   iNativeBufferSize, 464  
   OsclNativeFileParams, 464  
 OsclNetworkAddress, 465  
   OsclNetworkAddress, 465  
 OsclNetworkAddress  
   ipAddr, 465  
   operator==, 465  
   OsclNetworkAddress, 465  
   port, 465  
 OsclNoYieldMutex  
   oscl\_mutex.h, 723  
 OsclNullLock, 466  
 OsclNullLock  
   ~OsclNullLock, 466  
   Lock, 466  
   Unlock, 466  
 OsclPending  
   osclerror, 91  
 OsclPipe  
   osclconfig\_io.h, 818  
 OsclPriorityLink, 467  
 OsclPriorityLink  
   iPriority, 467  
 OsclPriorityList, 468  
   OsclPriorityList, 468  
 OsclPriorityList  
   Head, 468  
   Insert, 468  
   IsHead, 468  
   IsTail, 468  
   OsclPriorityList, 468  
   Tail, 468  
 OsclPriorityQueue, 469  
   OsclPriorityQueue, 470  
 OsclPriorityQueue  
   ~OsclPriorityQueue, 470  
   c, 472  
   comp, 472  
   compare\_EQ, 470  
   compare\_LT, 470  
   const\_reference, 470  
   container\_type, 470  
   empty, 471  
   find\_heap, 471  
   iterator, 470  
   oscl\_priqueue\_test, 472  
   OsclPriorityQueue, 470  
   pop, 471  
   pop\_heap, 471  
   push, 471  
   push\_heap, 471  
   remove, 471  
   reserve, 471  
   size, 471  
   swap, 471  
   top, 471  
   validate, 472  
   value\_type, 470  
   vec, 472  
 OsclPriorityQueueBase, 473  
   Oscl\_Vector\_Base, 292  
 OsclPriorityQueueBase  
   ~OsclPriorityQueueBase, 473  
   construct, 473  
   find\_heap, 473  
   pop\_heap, 473  
   push\_heap, 473  
   remove, 473  
 osclproc  
   EPVThreadContext\_InThread, 105  
   EPVThreadContext\_NonOsclThread, 105  
   EPVThreadContext\_OsclThread, 105  
   EPVThreadContext\_Undetermined, 105  
   OSCL\_PERF\_SUMMARY\_LOGGING, 104  
   OSCL\_REQUEST\_ERR\_CANCEL, 105  
   OSCL\_REQUEST\_ERR\_GENERAL, 105  
   OSCL\_REQUEST\_ERR\_NONE, 105  
   OSCL\_REQUEST\_PENDING, 105  
   OSCL\_ZEROIZE, 104  
   OsclPtrAdd, 105  
   OsclPtrSub, 105  
   PV\_SCHED\_CHECK\_Q, 104  
   PV\_SCHED\_ENABLE\_AO\_STATS, 104  
   PV\_SCHED\_ENABLE\_LOOP\_STATS, 104  
   PV\_SCHED\_ENABLE\_PERF\_LOGGING, 104  
   PV\_SCHED\_ENABLE\_THREAD\_CONTEXT\_CHECKS, 104  
   PV\_SCHED\_FAIR\_SCHEDULING, 104  
   PV\_SCHED\_LOG\_Q, 104  
   PVEEXECNAMELEN, 104  
   PVSCHEDNAMELEN, 104  
   QUE\_ITER\_BEGIN, 104  
   QUE\_ITER\_END, 104  
   TOsclReady, 105

TPVThreadContext, 105  
**OsclProcStatus**, 474  
   ALREADY\_SUSPENDED\_ERROR, 474  
   BAD\_THREADID\_ADDR\_ERROR, 474  
   EXCEED\_MAX\_COUNT\_VARIABLE\_ERROR, 475  
   EXCEED\_MAX\_SEM\_COUNT\_ERROR, 475  
   INVALID\_ACCESS\_ERROR, 475  
   INVALID\_ARGUMENT\_ERROR, 475  
   INVALID\_FUNCTION\_ERROR, 475  
   INVALID\_HANDLE\_ERROR, 475  
   INVALID\_OPERATION\_ERROR, 475  
   INVALID\_PARAM\_ERROR, 474  
   INVALID\_POINTER\_ERROR, 475  
   INVALID\_PRIORITY\_ERROR, 474  
   INVALID\_THREAD\_ERROR, 474  
   INVALID\_THREAD\_ID\_ERROR, 474  
   MAX\_THRDS\_REACHED\_ERROR, 474  
   MUTEX\_LOCKED\_ERROR, 475  
   NO\_PERMISSION\_ERROR, 474  
   NOT\_ENOUGH\_MEMORY\_ERROR, 474  
   NOT\_ENOUGH\_RESOURCES\_ERROR, 474  
   NOT\_IMPLEMENTED, 475  
   NOT\_SUSPENDED\_ERROR, 474  
   OTHER\_ERROR, 474  
   OUTOFMEMORY\_ERROR, 474  
   PSHARED\_ATTRIBUTE\_SETTING\_ERROR, 475  
   PSHARED\_NOT\_ZERO\_ERROR, 475  
   RELOCK\_MUTEX\_ERROR, 475  
   SEM\_NOT\_SIGNALLED\_ERROR, 475  
   SUCCESS\_ERROR, 474  
   SYSTEM\_RESOURCES\_UNAVAILABLE\_ERROR, 475  
   THREAD\_1\_INACTIVE\_ERROR, 474  
   THREAD\_BLOCK\_ERROR, 475  
   THREAD\_NOT\_OWN\_MUTEX\_ERROR, 475  
   TOO\_MANY\_THREADS\_ERROR, 474  
   WAIT\_ABANDONED\_ERROR, 475  
   WAIT\_TIMEOUT\_ERROR, 475  
**OsclProcStatus**  
   eOsclProcError, 474  
**OsclPtr**, 476  
   OsclPtr, 476  
**OsclPtr**  
   Append, 476  
   Length, 476  
   OsclPtr, 476  
   Ptr, 476  
   Set, 476  
   SetLength, 476  
   Zero, 476  
**OsclPtrAdd**  
   osclproc, 105  
**OsclPtrC**, 478  
   OsclPtrC, 479  
**OsclPtrC**  
   Left, 479  
   Length, 479  
   OsclPtrC, 479  
   Ptr, 479  
   Right, 479  
   Set, 479  
   SetLength, 479  
   Zero, 479  
**OsclPtrSub**  
   osclproc, 105  
**OsclRand**, 480  
**OsclRand**  
   Rand, 480  
   Seed, 480  
**OsclReadFD**  
   osclconfig\_io.h, 818  
**OsclReadyAlloc**, 481  
**OsclReadyAlloc**  
   allocate, 481  
   allocate\_fl, 481  
   deallocate, 481  
**OsclReadyCompare**, 482  
   PVActiveBase, 614  
**OsclReadyCompare**  
   compare, 482  
**OsclReadyQ**, 483  
   OsclExecSchedulerCommonBase, 396  
   PVActiveBase, 614  
   PVActiveStats, 615  
**OsclReadyQ**  
   Callback, 484  
   Construct, 484  
   Depth, 484  
   IsIn, 484  
   PendComplete, 484  
   PopTop, 484  
   RegisterForCallback, 484  
   Remove, 484  
   ThreadLogoff, 484  
   ThreadLogon, 484  
   TimerCallback, 484  
   Top, 484  
   WaitAndPopTop, 484  
   WaitForRequestComplete, 484  
**OsclReadySetPosition**  
   PVActiveBase, 614  
**OsclRecv**  
   osclconfig\_io.h, 818

OsclRecvFrom  
   osclconfig\_io.h, 818  
 OsclRecvFromMethod, 485  
 OsclRecvFromMethod  
   ~OsclRecvFromMethod, 485  
   GetRecvData, 485  
   NewL, 485  
   RecvFrom, 485  
   RecvFromRequest, 485  
 OsclRecvFromRequest, 487  
   OsclRecvFromRequest, 487  
   OsclSocketI, 538  
 OsclRecvFromRequest  
   GetRecvData, 487  
   OsclRecvFromRequest, 487  
   RecvFrom, 487  
   Success, 487  
 OsclRecvMethod, 489  
 OsclRecvMethod  
   ~OsclRecvMethod, 489  
   GetRecvData, 489  
   NewL, 489  
   Recv, 489  
   RecvRequest, 489  
 OsclRecvRequest, 490  
   OsclRecvRequest, 490  
   OsclSocketI, 538  
 OsclRecvRequest  
   GetRecvData, 490  
   OsclRecvRequest, 490  
   Recv, 490  
   Success, 490  
 OsclRefCounter, 491  
 OsclRefCounter  
   ~OsclRefCounter, 491  
   addRef, 491  
   getCount, 491  
   removeRef, 491  
 OsclRefCounterDA, 493  
   OsclRefCounterDA, 493  
 OsclRefCounterDA  
   ~OsclRefCounterDA, 493  
   addRef, 494  
   getCount, 494  
   OsclRefCounterDA, 493  
   removeRef, 494  
 OsclRefCounterMemFrag, 495  
   OsclRefCounterMemFrag, 495  
 OsclRefCounterMemFrag  
   ~OsclRefCounterMemFrag, 495  
   getCapacity, 496  
   getCount, 496  
   getMemFrag, 496  
   getMemFragPtr, 496  
   getMemFragSize, 496  
   getRefCounter, 496  
   operator=, 496  
   OsclRefCounterMemFrag, 495  
 OsclRefCounterMTDA, 497  
   OsclRefCounterMTDA, 497  
 OsclRefCounterMTDA  
   ~OsclRefCounterMTDA, 497  
   addRef, 498  
   getCount, 498  
   OsclRefCounterMTDA, 497  
   removeRef, 498  
 OsclRefCounterMTSA, 499  
   OsclRefCounterMTSA, 499  
 OsclRefCounterMTSA  
   ~OsclRefCounterMTSA, 499  
   addRef, 500  
   getCount, 500  
   OsclRefCounterMTSA, 499  
   removeRef, 500  
 OsclRefCounterSA, 501  
   OsclRefCounterSA, 501  
 OsclRefCounterSA  
   ~OsclRefCounterSA, 501  
   addRef, 502  
   getCount, 502  
   OsclRefCounterSA, 501  
   removeRef, 502  
 OsclRegistryAccessClient, 503  
   OsclRegistryAccessClient, 503  
   OsclRegistryClientImpl, 511  
   OsclRegistryServTlsImpl, 514  
 OsclRegistryAccessClient  
   ~OsclRegistryAccessClient, 503  
   Close, 503  
   Connect, 503  
   GetFactories, 503  
   GetFactory, 503  
   OsclRegistryAccessClient, 503  
 OsclRegistryAccessClientImpl, 505  
   OsclRegistryAccessClientTlsImpl, 506  
 OsclRegistryAccessElement, 507  
 OsclRegistryAccessElement  
   iFactory, 507  
   iMimeType, 507  
 OsclRegistryClient, 508  
   OsclRegistryClient, 508  
   OsclRegistryClientImpl, 511  
   OsclRegistryServTlsImpl, 514  
 OsclRegistryClient  
   ~OsclRegistryClient, 508  
   Close, 508  
   Connect, 508  
   OsclRegistryClient, 508

Register, 508  
 UnRegister, 509  
**OsclRegistryClientImpl**, 510  
**OsclRegistryClientImpl**  
   Close, 511  
   Connect, 511  
   GetFactories, 511  
   GetFactory, 511  
   **OsclRegistryAccessClient**, 511  
   **OsclRegistryClient**, 511  
   Register, 511  
   UnRegister, 511  
**OsclRegistryClientTlsImpl**, 512  
**OsclRegistryServTlsImpl**, 513  
   **OsclRegistryServTlsImpl**, 514  
**OsclRegistryServTlsImpl**  
   ~**OsclRegistryServTlsImpl**, 514  
   Close, 514  
   Connect, 514  
   GetFactories, 514  
   GetFactory, 514  
   **OsclRegistryAccessClient**, 514  
   **OsclRegistryClient**, 514  
   **OsclRegistryServTlsImpl**, 514  
   Register, 514  
   UnRegister, 514  
**OsclReturnCode**  
   osclerror, 92  
**OsclScheduler**, 515  
   **OsclErrorTrapImp**, 377  
   **OsclExecScheduler**, 389  
   **OsclExecSchedulerCommonBase**, 396  
**OsclScheduler**  
   Cleanup, 515  
   Init, 515  
**OsclSchedulerCommonBase**  
   **PVActiveBase**, 614  
**OsclSchedulerObserver**, 516  
**OsclSchedulerObserver**  
   ~**OsclSchedulerObserver**, 516  
   **OsclSchedulerReadyCallback**, 516  
   **OsclSchedulerTimerCallback**, 516  
**OsclSchedulerReadyCallback**  
   **OsclSchedulerObserver**, 516  
**OsclSchedulerTimerCallback**  
   **OsclSchedulerObserver**, 516  
**OsclScopedLock**, 517  
   **OsclScopedLock**, 517  
**OsclScopedLock**  
   ~**OsclScopedLock**, 517  
   **OsclScopedLock**, 517  
**OsclSelect**, 518  
   **OsclSelect**, 519  
**OsclSelect**

iErrAlloc, 519  
 iHeapCheck, 519  
 iOsclBase, 519  
 iOsclErrorTrap, 519  
 iOsclLogger, 519  
 iOsclMemory, 519  
 iOsclScheduler, 519  
 iOutputFile, 519  
 iSchedulerAlloc, 519  
 iSchedulerName, 519  
 iSchedulerReserve, 519  
 OsclSelect, 519  
**OsclSemaphore**, 520  
   **OsclSemaphore**, 520  
**OsclSemaphore**  
   ~**OsclSemaphore**, 520  
   Close, 520  
   Create, 520  
   **OsclSemaphore**, 520  
   Signal, 521  
   TryWait, 521  
   Wait, 521  
**OsclSend**  
   osclconfig\_io.h, 819  
**OsclSendMethod**, 522  
**OsclSendMethod**  
   ~**OsclSendMethod**, 522  
   GetSendData, 522  
   NewL, 522  
   Send, 522  
   SendRequest, 522  
**OsclSendRequest**, 523  
   **OsclSendRequest**, 523  
   **OsclSocketI**, 538  
**OsclSendRequest**  
   GetSendData, 523  
   **OsclSendRequest**, 523  
   Send, 523  
   Success, 523  
**OsclSendTo**  
   osclconfig\_io.h, 819  
**OsclSendToMethod**, 524  
**OsclSendToMethod**  
   ~**OsclSendToMethod**, 524  
   GetSendData, 524  
   NewL, 524  
   SendTo, 524  
   SendToRequest, 524  
**OsclSendToRequest**, 525  
   **OsclSendToRequest**, 525  
   **OsclSocketI**, 538  
**OsclSendToRequest**  
   GetSendData, 525  
   **OsclSendToRequest**, 525

---

SendTo, [525](#)  
 Success, [525](#)  
**OsclSetNonBlocking**  
     osclconfig\_io.h, [819](#)  
**OsclSetRecvBufferSize**  
     osclconfig\_io.h, [819](#)  
**OsclSetSockOpt**  
     osclconfig\_io.h, [819](#)  
**OsclSharedPtr**, [526](#)  
     OsclSharedPtr, [527](#)  
**OsclSharedPtr**  
     ~OsclSharedPtr, [527](#)  
     get\_count, [527](#)  
     GetRefCounter, [527](#)  
     GetRep, [527](#)  
     operator \*, [527](#)  
     operator TheClass \*, [528](#)  
     operator->, [528](#)  
     operator=, [528](#)  
     OsclSharedPtr, [527](#)  
     Unbind, [528](#)  
**OsclShutdown**  
     osclconfig\_io.h, [819](#)  
**OsclShutdownMethod**, [529](#)  
**OsclShutdownMethod**  
     ~OsclShutdownMethod, [529](#)  
     NewL, [529](#)  
     Shutdown, [529](#)  
     ShutdownRequest, [529](#)  
**OsclShutdownRequest**, [530](#)  
     OsclShutdownRequest, [530](#)  
     OsclSocketI, [538](#)  
**OsclShutdownRequest**  
     OsclShutdownRequest, [530](#)  
     Shutdown, [530](#)  
**OsclSingleton**, [531](#)  
     OsclSingleton, [531](#)  
**OsclSingleton**  
     ~OsclSingleton, [531](#)  
     \_Ptr, [532](#)  
     operator \*, [531](#)  
     operator->, [531](#)  
     OsclSingleton, [531](#)  
     set, [531](#)  
**OsclSingletonRegistry**, [533](#)  
**OsclSingletonRegistry**  
     getInstance, [533](#)  
     lockAndGetInstance, [533](#)  
     OsclBase, [533](#)  
     registerInstance, [533](#)  
     registerInstanceAndUnlock, [533](#)  
**OsclSocket**  
     osclconfig\_io.h, [820](#)  
**OsclSocketCleanup**

    osclconfig\_io.h, [820](#)  
**OsclSocketI**, [534](#)  
     OsclSocketRequestAO, [552](#)  
     OsclSocketServI, [556](#)  
**OsclSocketI**  
     ~OsclSocketI, [535](#)  
     Accept, [535](#)  
     Bind, [535](#)  
     Close, [535](#)  
     Connect, [535](#)  
     GetPeerName, [535](#)  
     Join, [536](#)  
     Listen, [536](#)  
     Logger, [536](#)  
     MakeAddr, [536](#)  
     MakeMulticastGroupInformation, [536](#)  
     NewL, [536](#)  
     Open, [536](#)  
     OsclAcceptRequest, [538](#)  
     OsclConnectRequest, [538](#)  
     OsclRecvFromRequest, [538](#)  
     OsclRecvRequest, [538](#)  
     OsclSendRequest, [538](#)  
     OsclSendToRequest, [538](#)  
     OsclShutdownRequest, [538](#)  
     OsclTCPSocket, [538](#)  
     OsclUDPSocket, [538](#)  
     ProcessAccept, [536](#)  
     ProcessConnect, [537](#)  
     ProcessRecv, [537](#)  
     ProcessRecvFrom, [537](#)  
     ProcessSend, [537](#)  
     ProcessSendTo, [537](#)  
     ProcessShutdown, [537](#)  
     Recv, [537](#)  
     RecvFrom, [537](#)  
     RecvFromSuccess, [537](#)  
     RecvSuccess, [537](#)  
     Send, [537](#)  
     SendSuccess, [537](#)  
     SendTo, [537](#)  
     SendToSuccess, [537](#)  
     SetRecvBufferSize, [537](#)  
     SetSockOpt, [538](#)  
     Shutdown, [538](#)  
     Socket, [538](#)  
     ThreadLogoff, [538](#)  
     ThreadLogon, [538](#)  
**OsclSocketIBase**, [539](#)  
     OsclSocketIBase, [540](#)  
**OsclSocketIBase**  
     ~OsclSocketIBase, [540](#)  
     Accept, [540](#)  
     Bind, [540](#)

BindAsync, 540  
 CancelAccept, 541  
 CancelBind, 541  
 CancelConnect, 541  
 CancelFxn, 541  
 CancelListen, 541  
 CancelRecv, 541  
 CancelRecvFrom, 541  
 CancelSend, 541  
 CancelSendTo, 541  
 CancelShutdown, 541  
 Close, 541  
 Connect, 541  
 GetShutdown, 541  
 HasAsyncBind, 541  
 HasAsyncListen, 541  
 iAlloc, 543  
 iSocketServ, 543  
 IsOpen, 541  
 Join, 541  
 Listen, 541  
 ListenAsync, 541  
 Open, 542  
 OsclSocketIBase, 540  
 OsclSocketMethod, 543  
 OsclSocketRequest, 543  
 OsclSocketRequestAO, 543  
 OsclTCPSocket, 543  
 OsclUDPSocket, 543  
 Recv, 542  
 RecvFrom, 542  
 RecvFromSuccess, 542  
 RecvSuccess, 542  
 Send, 542  
 SendSuccess, 542  
 SendTo, 542  
 SendToSuccess, 542  
 Shutdown, 543  
 OsclSocketMethod, 544  
   OsclIPSocketI, 419  
   OsclSocketIBase, 543  
   OsclSocketMethod, 545  
   OsclSocketRequestAO, 552  
 OsclSocketMethod  
   ~OsclSocketMethod, 545  
   Abort, 545  
   AbortAll, 545  
   Alloc, 545  
   CancelMethod, 545  
   ConstructL, 545  
   iContainer, 546  
   iSocketFxn, 546  
   iSocketRequestAO, 546  
   MethodDone, 545  
 OsclSocketMethod, 545  
 Run, 545  
 StartMethod, 546  
 ThreadLogoff, 546  
 ThreadLogon, 546  
 OsclSocketObserver, 547  
 OsclSocketObserver  
   ~OsclSocketObserver, 547  
   HandleSocketEvent, 547  
 OsclSocketRequest, 548  
   OsclSocketIBase, 543  
   OsclSocketRequest, 548  
   OsclSocketRequestAO, 552  
   OsclSocketServI, 556  
 OsclSocketRequest  
   Activate, 548  
   CancelRequest, 548  
   Complete, 548  
   Fxn, 548  
   iParam, 548  
   iSocketI, 548  
   iSocketRequestAO, 548  
   OsclSocketRequest, 548  
 OsclSocketRequestAO, 549  
   OsclIPSocketI, 419  
   OsclSocketIBase, 543  
   OsclSocketRequestAO, 550  
 OsclSocketRequestAO  
   ~OsclSocketRequestAO, 550  
   Abort, 550  
   Alloc, 550  
   CleanupParam, 550  
   ConstructL, 550  
   DoCancel, 550  
   GetSocketError, 550  
   iContainer, 552  
   Id, 551  
   iParam, 552  
   iParamSize, 552  
   iSocketError, 552  
   NewRequest, 551  
   iSocketI, 552  
   OsclSocketMethod, 552  
   OsclSocketRequest, 552  
   OsclSocketRequestAO, 550  
   RequestDone, 551  
   Run, 551  
   SocketI, 551  
   SocketObserver, 551  
   Success, 551  
 OsclSocketSelect  
   osclconfig\_io.h, 820  
 OsclSocketServ, 553  
 OsclSocketServI, 556

**OsclSocketServ**  
 ~OsclSocketServ, [553](#)  
 Close, [553](#)  
 Connect, [553](#)  
 NewL, [554](#)  
 OsclDNS, [554](#)  
 OsclTCPSocket, [554](#)  
 OsclUDPSocket, [554](#)  
**OsclSocketServI**, [555](#)  
 OsclSocketServRequestList, [559](#)  
**OsclSocketServI**  
 Close, [555](#)  
 Connect, [555](#)  
 IsServerThread, [556](#)  
 LoopbackSocket, [556](#)  
 NewL, [556](#)  
 OsclDNSI, [556](#)  
 OsclSocketI, [556](#)  
 OsclSocketRequest, [556](#)  
 OsclSocketServ, [556](#)  
 OsclSocketServRequestList, [556](#)  
 OsclTCPSocketI, [556](#)  
 OsclUDPSocketI, [556](#)  
**OsclSocketServIBase**, [557](#)  
 ESocketServ\_Connected, [557](#)  
 ESocketServ\_Error, [558](#)  
 ESocketServ\_Idle, [557](#)  
 OsclSocketServIBase, [558](#)  
**OsclSocketServIBase**  
 ~OsclSocketServIBase, [558](#)  
 Close, [558](#)  
 Connect, [558](#)  
 iAlloc, [558](#)  
 iLogger, [558](#)  
 iServError, [558](#)  
 iServState, [558](#)  
 IsServConnected, [558](#)  
 OsclSocketServIBase, [558](#)  
 State, [558](#)  
 TSocketServState, [557](#)  
**OsclSocketServRequestList**, [559](#)  
 OsclSocketServI, [556](#)  
 OsclSocketServRequestList, [559](#)  
**OsclSocketServRequestList**  
 Add, [559](#)  
 Close, [559](#)  
 Open, [559](#)  
 OsclSocketServI, [559](#)  
 OsclSocketServRequestList, [559](#)  
 Remove, [559](#)  
 StartCancel, [559](#)  
 WaitOnRequests, [559](#)  
 Wakeup, [559](#)  
**OsclSocketServRequestQElem**, [561](#)  
**OsclSocketServRequestQElem**  
 iCancel, [561](#)  
 iSelect, [561](#)  
 iSocketRequest, [561](#)  
**OsclSocketServRequestQElem**, [561](#)  
**OsclSocketStartup**  
 oscleconfig\_io.h, [820](#)  
**OsclSocketTOS**, [562](#)  
 EPVCritic\_Ecp, [562](#)  
 EPVFlash, [562](#)  
 EPVHiRel, [562](#)  
 EPVHiThrpt, [562](#)  
 EPVImmediate, [562](#)  
 EPVInetControl, [562](#)  
 EPVLDelay, [562](#)  
 EPVNetControl, [562](#)  
 EPVNoTOS, [562](#)  
 EPVOverrideFlash, [562](#)  
 EPVPriority, [562](#)  
 EPVRoutine, [562](#)  
 OsclSocketTOS, [563](#)  
**OsclSocketTOS**  
 ClearTOS, [563](#)  
 GetTOS, [563](#)  
 OsclSocketTOS, [563](#)  
 SetPrecedence, [563](#)  
 SetPriority, [563](#)  
 TPVServicePrecedence, [562](#)  
 TPVServicePriority, [562](#)  
**OsclSuccess**  
 oscrrorror, [91](#)  
**OsclTagTreeType**  
 osclmemory, [58](#)  
**OsclTCPSocket**, [564](#)  
 OsclSocketI, [538](#)  
 OsclSocketIBase, [543](#)  
 OsclSocketServ, [554](#)  
**OsclTCPSocket**  
 ~OsclTCPSocket, [565](#)  
 Accept, [565](#)  
 Bind, [565](#)  
 BindAsync, [565](#)  
 CancelAccept, [566](#)  
 CancelBind, [566](#)  
 CancelConnect, [566](#)  
 CancelListen, [566](#)  
 CancelRecv, [566](#)  
 CancelSend, [566](#)  
 CancelShutdown, [566](#)  
 Close, [567](#)  
 Connect, [567](#)  
 GetAcceptedSocketL, [567](#)  
 GetPeerName, [567](#)

GetRecvData, 568  
 GetSendData, 568  
 Listen, 568  
 ListenAsync, 568  
 NewL, 568  
 Recv, 569  
 Send, 569  
 SetOptionToReuseAddress, 569  
 SetTOS, 570  
 Shutdown, 570  
 ThreadLogoff, 570  
 ThreadLogon, 570  
**OscITCPSocketI**, 571  
   OscSocketServI, 556  
**OscITCPSocketI**  
   ~OscITCPSocketI, 572  
   Accept, 572  
   BindAsync, 572  
   CancelAccept, 572  
   CancelBind, 572  
   CancelConnect, 572  
   CancelListen, 572  
   CancelRecv, 572  
   CancelSend, 572  
   CancelShutdown, 572  
   Close, 572  
   Connect, 572  
   GetAcceptedSocketL, 572  
   GetRecvData, 572  
   GetSendData, 572  
   Listen, 572  
   ListenAsync, 573  
   NewL, 573  
   Recv, 573  
   Send, 573  
   Shutdown, 573  
   ThreadLogoff, 573  
   ThreadLogon, 573  
**OscIThread**, 574  
   OscIThread, 574  
**OscIThread**  
   ~OscIThread, 574  
   CanTerminate, 574  
   CompareId, 575  
   Create, 575  
   Exit, 575  
   GetId, 575  
   GetPriority, 576  
   OscIThread, 574  
   Resume, 576  
   SetPriority, 576  
   SleepMillisec, 576  
   Suspend, 577  
   Terminate, 577  
  
**OscIThread\_State**  
   oscl\_thread.h, 788  
**OscIThreadLock**, 578  
   OscIThreadLock, 578  
**OscIThreadLock**  
   ~OscIThreadLock, 578  
   Lock, 578  
   OscIThreadLock, 578  
   Unlock, 578  
**OscIThreadPriority**  
   oscl\_thread.h, 788  
**OscTickCount**, 579  
**OscTickCount**  
   MsecToTicks, 579  
   TickCount, 579  
   TickCountFrequency, 579  
   TickCountPeriod, 579  
   TicksToMsec, 579  
**OSCLTICKCOUNT\_MAX\_TICKS**  
   osclutil, 68  
**OscITimer**, 581  
   OscITimer, 582  
**OscITimer**  
   ~OscITimer, 582  
   callback\_timer\_type, 582  
   CallbackTimer< Alloc >, 583  
   Cancel, 582  
   Clear, 582  
   OscITimer, 582  
   Request, 582  
   SetExactFrequency, 582  
   SetFrequency, 583  
   SetObserver, 583  
   TimerBaseElapsed, 583  
**OscITimerCompare**, 584  
   OscExecSchedulerCommonBase, 396  
**OscITimerCompare**  
   compare, 584  
**OscITimerObject**, 585  
   OscExecSchedulerCommonBase, 398  
   OscITimerObject, 586  
   PVActiveBase, 614  
   PVActiveStats, 615  
   PVThreadContext, 634  
**OscITimerObject**  
   ~OscITimerObject, 586  
   AddToScheduler, 586  
   After, 586  
   Cancel, 586  
   DoCancel, 586  
   IsBusy, 587  
   OscITimerObject, 586  
   Priority, 587  
   RemoveFromScheduler, 587

RunError, 587  
 RunIfNotReady, 587  
 SetBusy, 587  
 SetStatus, 587  
 Status, 588  
 StatusRef, 588  
 OsclTimerObserver, 589  
 OsclTimerObserver  
   ~OsclTimerObserver, 589  
   TimeoutOccurred, 589  
 OsclTimerQ, 590  
 OsclTimerQ  
   Add, 590  
   Construct, 590  
   IsIn, 590  
   Pop, 590  
   PopTop, 590  
   Remove, 590  
   Top, 590  
 OsclTLS, 591  
   OsclTLS, 591  
 OsclTLS  
   ~OsclTLS, 591  
   \_Ptr, 592  
   operator \*, 591  
   operator->, 591  
   OsclTLS, 591  
   set, 591  
 OsclTLSEx, 593  
   OsclTLSEx, 593  
 OsclTLSEx  
   ~OsclTLSEx, 593  
   \_Ptr, 594  
   operator \*, 593  
   operator->, 593  
   OsclTLSEx, 593  
   set, 593  
 OsclTLSRegistry, 595  
 OsclTLSRegistry  
   getInstance, 595  
   OsclBase, 595  
   registerInstance, 595  
 OsclTLSRegistryEx, 596  
 OsclTLSRegistryEx  
   getInstance, 596  
   registerInstance, 596  
 OsclTrapItem, 597  
   OsclTrapItem, 597  
 OsclTrapItem  
   OsclTrapItem, 597  
   OsclTrapStack, 597  
   OsclTrapStackItem, 597  
 OsclTrapOperation  
   osclerror, 92  
 OsclTrapStack, 598  
   OsclErrorTrapImp, 377  
   OsclTrapItem, 597  
 OsclTrapStack  
   OsclError, 598  
   OsclErrorTrap, 598  
   OsclErrorTrapImp, 598  
 OsclTrapStackItem, 599  
   OsclTrapItem, 597  
   OsclTrapStackItem, 599  
 OsclTrapStackItem  
   iCBase, 599  
   iNext, 599  
   iTAny, 599  
   iTrapOperation, 599  
   OsclTrapStackItem, 599  
 OsclUDPSocket, 600  
   OsclSocketI, 538  
   OsclSocketIBase, 543  
   OsclSocketServ, 554  
 OsclUDPSocket  
   ~OsclUDPSocket, 601  
   Bind, 601  
   BindAsync, 601  
   CancelBind, 601  
   CancelRecvFrom, 601  
   CancelSendTo, 601  
   Close, 602  
   GetPeerName, 602  
   GetRecvData, 602  
   GetSendData, 602  
   Join, 602  
   JoinMulticastGroup, 603  
   NewL, 603  
   RecvFrom, 603  
   SendTo, 604  
   SetMulticastTTL, 604  
   SetOptionToReuseAddress, 604  
   SetRecvBufferSize, 605  
   SetTOS, 605  
   ThreadLogoff, 605  
   ThreadLogon, 605  
 OsclUDPSocketI, 606  
   OsclSocketServI, 556  
 OsclUDPSocketI  
   ~OsclUDPSocketI, 607  
   BindAsync, 607  
   CancelBind, 607  
   CancelRecvFrom, 607  
   CancelSendTo, 607  
   Close, 607  
   GetRecvData, 607  
   GetSendData, 607  
   JoinMulticastGroup, 607

NewL, 607  
 RecvFrom, 607  
 SendTo, 607  
 SetMulticastTTL, 607  
 ThreadLogoff, 607  
 ThreadLogon, 607  
**OsclUid32**  
     oscl\_uuid.h, 799  
**OsclUnMakeInAddr**  
     osclconfig\_io.h, 820  
**OsclUnMakeSockAddr**  
     osclconfig\_io.h, 821  
**osclutil**  
     ~OSCL\_HeapString, 83  
     ~OSCL\_StackString, 83  
     ~OSCL\_wHeapString, 83  
     ~OSCL\_wStackString, 83  
     APPEND\_MEDIA\_AT\_END, 83  
     BufferFreeFuncPtr, 68  
     EOSCL\_StringOp\_CompressASCII, 69  
     EOSCL\_StringOp\_UTF16ToUTF8, 69  
     EOSCL\_wStringOp\_ExpandASCII, 69  
     EOSCL\_wStringOp\_UTF8ToUTF16, 69  
     extract\_string, 69  
     get\_cstr, 69  
     get\_maxsize, 70  
     get\_size, 70  
     get\_str, 71  
     GetBufferState, 71  
     GetFragment, 71  
     MAX\_NUMBER\_OF\_BYTE\_PER\_UTF8,  
         68  
     MediaTimestamp, 68  
     operator=, 71–73  
     oscl\_abs, 73  
     OSCL\_ASCII\_CASE\_MAGIC\_BIT, 83  
     oscl\_asin, 73  
     oscl\_atan, 73  
     oscl\_cos, 73  
     oscl\_exp, 73  
     oscl\_floor, 73  
     OSCL\_HeapString, 73, 74  
     oscl\_isdigit, 68  
     oscl\_log, 74  
     oscl\_log10, 74  
     oscl\_pow, 74  
     oscl\_sin, 75  
     oscl\_snprintf, 75  
     oscl\_sqrt, 75  
     OSCL\_StackString, 75, 76  
     oscl\_str\_escape\_xml, 76  
     oscl\_str\_is\_valid\_utf8, 76  
     oscl\_str\_need\_escape\_xml, 77  
     oscl\_str\_truncate\_utf8, 77  
     oscl\_str\_unescape\_uri, 77, 78  
     oscl\_tan, 78  
     OSCL\_TStrPtrLen, 68  
     oscl\_UncodeToUTF8, 78  
     oscl\_UTF8ToUnicode, 79  
     oscl\_vsnprintf, 79, 81  
     OSCL\_wHeapString, 81  
     OSCL\_wStackString, 81  
     OsclComponentFactory, 68  
     OSCLTICKCOUNT\_MAX\_TICKS, 68  
     PV\_atof, 81  
     PV\_atoi, 81  
     set, 81–83  
     skip\_to\_line\_term, 83  
     skip\_to\_whitespace, 83  
     skip\_whitespace, 83  
     skip\_whitespace\_and\_line\_term, 83  
     StrCSumPtrLen, 68  
     StrPtrLen, 68  
     TOSCL\_StringOp, 69  
     TOSCL\_wStringOp, 69  
     WStrPtrLen, 68  
**OsclUuid**, 609  
     OsclUuid, 610  
**OsclUuid**  
     data1, 610  
     data2, 610  
     data3, 610  
     data4, 610  
     operator!=, 610  
     operator=, 610  
     operator==, 610  
     OsclUuid, 610  
**OsclValidInetAddr**  
     osclconfig\_io.h, 821  
**OsclWriteFD**  
     osclconfig\_io.h, 821  
**other**  
     Oscl\_TAlloc::rebind, 283  
**other\_chartype**  
     OSCL\_FastString, 175  
     OSCL\_HeapString, 196  
     OSCL\_HeapStringA, 198  
     OSCL\_StackString, 257  
     OSCL\_wFastString, 294  
     OSCL\_wHeapString, 297  
     OSCL\_wHeapStringA, 299  
     OSCL\_wStackString, 302  
**OTHER\_ERROR**  
     OsclProcStatus, 474  
**OUTOFMEMORY\_ERROR**  
     OsclProcStatus, 474  
**overwrite**  
     CFastRep, 127

pad  
   MM\_AllocBlockFence, 146  
   MM\_AllocBlockHdr, 147  
 pair\_citerator\_citerator  
   Oscl\_Map, 217  
 pair\_iterator\_bool  
   Oscl\_Map, 217  
   Oscl\_TagTree, 269  
 pair\_iterator\_iterator  
   Oscl\_Map, 217  
 pAllocInfo  
   MM\_AllocNode, 150  
 parent  
   Oscl\_Rb\_Tree\_Node\_Base, 254  
   Oscl\_TagTree::Node, 279  
 pAudit  
   OsclAuditCB, 320  
 pBasePosition  
   OsclBinStream, 338  
 pBuffer  
   OsclFileCacheBuffer, 403  
 peakNumAllocs  
   MM\_Stats\_t, 164  
 peakNumBytes  
   MM\_Stats\_t, 164  
 PendComplete  
   OsclActiveObject, 311  
   OsclExecSchedulerCommonBase, 395  
   OsclReadyQ, 484  
 PendForExec  
   OsclActiveObject, 311  
 per\_allocation\_overhead  
   MM\_AuditOverheadStats, 160  
 perms  
   oscl\_stat\_buf, 258  
 PersistHostAddress  
   GetHostNameParam, 135  
 pFileName  
   MM\_AllocInfo, 149  
 pMemBlock  
   MM\_AllocInfo, 149  
   MM\_AllocQueryInfo, 151  
 pMMFIParam  
   OsclMemStatsNode, 457  
 pMMStats  
   OsclMemStatsNode, 457  
 pNext  
   MM\_AllocNode, 150  
 pNode  
   MM\_AllocBlockHdr, 147  
 pointer  
   MemAllocator, 145  
   Oscl\_Map, 217  
   Oscl\_Queue, 236  
   Oscl\_Rb\_Tree, 243  
   Oscl\_Rb\_Tree\_Const\_Iterator, 247  
   Oscl\_Rb\_Tree\_Iterator, 250  
   Oscl\_TagTree::const\_iterator, 273  
   Oscl\_TagTree::iterator, 276  
   Oscl\_TAlloc, 281  
   Oscl\_Vector, 285  
 Pop  
   OsclError, 371  
   OsclTimerQ, 590  
 pop  
   Oscl\_Queue, 237  
   Oscl\_Queue\_Base, 239  
   OsclPriorityQueue, 471  
 pop\_back  
   Oscl\_Vector, 287  
   Oscl\_Vector\_Base, 291  
 pop\_heap  
   OsclPriorityQueue, 471  
   OsclPriorityQueueBase, 473  
 PopDealloc  
   OsclError, 371, 372  
 PopTop  
   OsclReadyQ, 484  
   OsclTimerQ, 590  
 port  
   OsclNetworkAddress, 465  
 PositionInBlock  
   OsclBinStream, 337  
 Position  
   OsclBinStream, 338  
 pPrev  
   MM\_AllocNode, 150  
 Preceeds  
   OsclFileCacheBuffer, 403  
 PrepRead  
   OsclFileCacheBuffer, 403  
 PrepWrite  
   OsclFileCacheBuffer, 403  
 Priority  
   OsclActiveObject, 311  
   OsclTimerObject, 587  
 ProcessAccept  
   OsclSocketI, 536  
 ProcessConnect  
   OsclSocketI, 537  
 ProcessRecv  
   OsclSocketI, 537  
 ProcessRecvFrom  
   OsclSocketI, 537  
 ProcessSend  
   OsclSocketI, 537  
 ProcessSendTo  
   OsclSocketI, 537

ProcessShutdown  
     OsclSocketI, [537](#)  
 pRootNode  
     MM\_AllocBlockHdr, [147](#)  
 pruneSubtree  
     MM\_Audit\_Imp, [158](#)  
 PSHARED\_ATTRIBUTE\_SETTING\_ERROR  
     OsclProcStatus, [475](#)  
 PSHARED\_NOT\_ZERO\_ERROR  
     OsclProcStatus, [475](#)  
 pStats  
     MM\_Stats\_CB, [162](#)  
 pStatsNode  
     MM\_AllocInfo, [149](#)  
     OsclAuditCB, [320](#)  
 Ptr  
     OsclPtr, [476](#)  
     OsclPtrC, [479](#)  
 ptr  
     OsclMemoryFragment, [441](#)  
     StrPtrLen, [647](#)  
     WStrPtrLen, [658](#)  
 push  
     Oscl\_Queue, [237](#)  
     Oscl\_Queue\_Base, [239](#)  
     OsclPriorityQueue, [471](#)  
 push\_back  
     Oscl\_Vector, [288](#)  
     Oscl\_Vector\_Base, [291](#)  
 push\_front  
     Oscl\_Vector, [288](#)  
     Oscl\_Vector\_Base, [292](#)  
 push\_heap  
     OsclPriorityQueue, [471](#)  
     OsclPriorityQueueBase, [473](#)  
 PushL  
     OsclError, [372](#)  
 PV8601TIME\_BUFFER\_SIZE  
     osclbase, [45](#)  
 PV8601timeStrBuf  
     osclbase, [34](#)  
 PV8601ToRFC822  
     osclbase, [44](#)  
 PV\_atof  
     osclutil, [81](#)  
 PV\_atoi  
     osclutil, [81](#)  
 PV\_CHAR\_CLOSE\_BRACKET  
     oscl\_uuid\_utils.h, [800](#)  
 PV\_CHAR\_COMMA  
     oscl\_uuid\_utils.h, [800](#)  
 PV\_DNS\_IS\_THREAD  
     oscl\_dns\_tuneables.h, [676](#)  
 PV\_DNS\_SERVER  
     oscl\_dns\_tuneables.h, [676](#)  
     PVActiveBase, [611](#)  
     PV\_DYNAMIC\_LOADING\_CONFIG\_FILE\_PATH  
         osclconfig\_lib.h, [824](#)  
     PV\_OSCL\_SOCKET\_1MB\_RECV\_BUF  
         oscl\_socket\_tuneables.h, [772](#)  
     PV\_OSCL\_SOCKET\_SERVER\_LOGGER\_OUTPUT  
         oscl\_socket\_tuneables.h, [772](#)  
     PV\_OSCL\_SOCKET\_STATS\_LOGGING  
         oscl\_socket\_tuneables.h, [772](#)  
     PV\_RUNTIME\_LIB\_FILENAME\_EXTENSION  
         osclconfig\_lib.h, [824](#)  
     PV\_SCHED\_CHECK\_Q  
         osclproc, [104](#)  
     PV\_SCHED\_ENABLE\_AO\_STATS  
         osclproc, [104](#)  
     PV\_SCHED\_ENABLE\_LOOP\_STATS  
         osclproc, [104](#)  
     PV\_SCHED\_ENABLE\_PERF\_LOGGING  
         osclproc, [104](#)  
     PV\_SCHED\_ENABLE\_THREAD\_CONTEXT\_CHECKS  
         osclproc, [104](#)  
     PV\_SCHED\_FAIR\_SCHEDULING  
         osclproc, [104](#)  
     PV\_SCHED\_LOG\_Q  
         osclproc, [104](#)  
     PV\_SOCKET\_REQUEST\_AO\_PRIORITY  
         oscl\_socket\_tuneables.h, [772](#)  
     PV\_SOCKET\_SERVER  
         oscl\_socket\_tuneables.h, [772](#)  
     PV\_SOCKET\_SERVER\_AO\_INTERVAL\_MSEC  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVER\_AO\_PRIORITY  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVER\_IS\_THREAD  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVER\_SELECT  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVER\_SELECT\_LOOPBACK\_SOCKET  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVER\_SELECT\_TIMEOUT\_MSEC  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVER\_THREAD\_PRIORITY  
         oscl\_socket\_tuneables.h, [773](#)  
     PV\_SOCKET\_SERVI\_STATS  
         oscl\_socket\_tuneables.h, [773](#)

OsclExecSchedulerBase, 390  
 OsclExecSchedulerCommonBase, 398  
 PVActiveBase, 612  
 PVActiveStats, 615  
 PVThreadContext, 634  
**PVActiveBase**  
   ~PVActiveBase, 612  
   Activate, 612  
   AddToScheduler, 612  
   Cancel, 612  
   Destroy, 612  
   DoCancel, 612  
   iAddedNum, 614  
   iBusy, 614  
   iName, 614  
   iPVActiveStats, 614  
   iPVReadyQLink, 614  
   IsAdded, 612  
   IsInAnyQ, 613  
   iStatus, 614  
   iThreadContext, 614  
   OsclActiveObject, 614  
   OsclExecScheduler, 614  
   OsclReadyCompare, 614  
   OsclReadyQ, 614  
   OsclReadySetPosition, 614  
   OsclSchedulerCommonBase, 614  
   OsclTimerObject, 614  
   PVActiveBase, 612  
   PVActiveStats, 614  
   RemoveFromScheduler, 613  
   Run, 613  
   RunError, 613  
**PVActiveStats**, 615  
   OsclExecSchedulerCommonBase, 398  
   PVActiveBase, 614  
**PVActiveStats**  
   OsclActiveObject, 615  
   OsclExecScheduler, 615  
   OsclExecSchedulerCommonBase, 615  
   OsclReadyQ, 615  
   OsclTimerObject, 615  
   PVActiveBase, 615  
**PVCleanupStack**  
   \_OsclIHeapBase, 110  
**PVError\_DoLeave**  
   oscl\_error\_imp\_fatalerror.h, 684  
   oscl\_error\_imp\_jumps.h, 686  
   osclerror, 91  
**PVERROR\_IMP\_JUMPS**  
   osclerror, 91  
**PVERRORTRAP\_REGISTRY**  
   osclerror, 91  
**PVERRORTRAP\_REGISTRY\_ID**  
   osclerror, 92  
**PVEXECNAMELEN**  
   osclproc, 104  
**PVLogger**, 616  
   ~PVLogger, 617  
   AddAppender, 617  
   AddFilter, 617  
   alloc\_type, 617  
   Cleanup, 618  
   DisableAppenderInheritance, 618  
   filter\_status\_type, 617  
   GetLoggerObject, 618  
   GetLogLevel, 618  
   GetNumAppenders, 618  
   GetParent, 619  
   Init, 619  
   IsActive, 619  
   log\_level\_type, 617  
   LogMsgBuffers, 619  
   LogMsgBuffersV, 619  
   LogMsgString, 620  
   LogMsgStringV, 620  
   message\_id\_type, 617  
   PVLogger, 617  
   PVLoggerRegistry, 621  
   RemoveAppender, 620  
   SetLogLevel, 620  
   SetLogLevelAndPropagate, 621  
   SetParent, 621  
**pvlogger.h**, 849  
   \_PVLOGGER\_LOGBIN, 851  
   \_PVLOGGER\_LOGBIN\_V, 851  
   \_PVLOGGER\_LOGMSG, 851  
   \_PVLOGGER\_LOGMSG\_V, 851  
   PVLOGGER\_ENABLE, 851  
   PVLOGGER\_INST\_LEVEL, 852  
   PVLOGGER\_INST\_LEVEL\_SUPPORT, 852  
   PVLOGGER\_LEVEL\_UNINITIALIZED, 855  
   PVLOGGER\_LOG\_USE\_ONLY, 852  
   PVLOGGER\_LOGBIN, 852  
   PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_HLDBG, 852  
   PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_LLDBG, 853  
   PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_MLDBG, 853  
   PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_PROF, 853  
   PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_REL, 853  
   PVLOGGER\_LOGBIN\_V, 853

PVLOGGER\_LOGBIN\_V\_-  
   PVLOGMSG\_INST\_HLDBG, 853  
 PVLOGGER\_LOGBIN\_V\_-  
   PVLOGMSG\_INST\_LLDBG, 853  
 PVLOGGER\_LOGBIN\_V\_-  
   PVLOGMSG\_INST\_PROF, 853  
 PVLOGGER\_LOGBIN\_V\_-  
   PVLOGMSG\_INST\_REL, 853  
 PVLOGGER\_LOGBIN\_V\_-  
   PVLOGMSG\_V\_INST\_MLDBG,  
   853  
 PVLOGGER\_LOGMSG, 853  
 PVLOGGER\_LOGMSG\_PVLOGMSG\_-  
   INST\_HLDBG, 853  
 PVLOGGER\_LOGMSG\_PVLOGMSG\_-  
   INST\_LLDBG, 854  
 PVLOGGER\_LOGMSG\_PVLOGMSG\_-  
   INST\_MLDBG, 854  
 PVLOGGER\_LOGMSG\_PVLOGMSG\_-  
   INST\_PROF, 854  
 PVLOGGER\_LOGMSG\_PVLOGMSG\_-  
   INST\_REL, 854  
 PVLOGGER\_LOGMSG\_V, 854  
 PVLOGGER\_LOGMSG\_V\_-  
   PVLOGMSG\_INST\_HLDBG, 854  
 PVLOGGER\_LOGMSG\_V\_-  
   PVLOGMSG\_INST\_LLDBG, 854  
 PVLOGGER\_LOGMSG\_V\_-  
   PVLOGMSG\_INST\_MLDBG,  
   854  
 PVLOGGER\_LOGMSG\_V\_-  
   PVLOGMSG\_INST\_PROF, 854  
 PVLOGGER\_LOGMSG\_V\_-  
   PVLOGMSG\_INST\_REL, 854  
 PVLOGMSG\_ALERT, 855  
 PVLOGMSG\_CRIT, 855  
 PVLOGMSG\_DEBUG, 855  
 PVLOGMSG\_EMERG, 855  
 PVLOGMSG\_ERR, 855  
 PVLOGMSG\_FATAL\_ERROR, 855  
 PVLOGMSG\_INFO, 856  
 PVLOGMSG\_INST\_HLDBG, 854  
 PVLOGMSG\_INST\_LLDBG, 854  
 PVLOGMSG\_INST\_MLDBG, 854  
 PVLOGMSG\_INST\_PROF, 855  
 PVLOGMSG\_INST\_REL, 855  
 PVLOGMSG\_NONFATAL\_ERROR, 856  
 PVLOGMSG\_NOTICE, 856  
 PVLOGMSG\_STACK\_TRACE, 856  
 PVLOGMSG\_STATISTIC, 856  
 PVLOGMSG\_VERBOSE, 856  
 PVLOGMSG\_WARNING, 856  
 pvlogger\_accessories.h, 857  
   PVLOGGER\_FILTER\_ACCEPT, 857  
     PVLOGGER\_FILTER\_NEUTRAL, 857  
     PVLOGGER\_FILTER\_REJECT, 857  
 pvlogger\_c.h, 858  
   PVLOGGER\_C\_INST\_LEVEL, 859  
     pvLogger\_GetLoggerObject, 859  
     pvLogger\_IsActive, 859  
     pvLogger\_LogMsgString, 859  
     PVLOGMSG\_C\_ALERT, 859  
     PVLOGMSG\_C\_CRIT, 859  
     PVLOGMSG\_C\_EMERG, 859  
     PVLOGMSG\_C\_ERR, 859  
     PVLOGMSG\_C\_INFO, 859  
     PVLOGMSG\_C\_INST\_HLDBG, 859  
     PVLOGMSG\_C\_INST\_LLDBG, 859  
     PVLOGMSG\_C\_INST\_MLDBG, 859  
     PVLOGMSG\_C\_INST\_PROF, 859  
     PVLOGMSG\_C\_INST\_REL, 859  
     PVLOGMSG\_C\_NOTICE, 859  
     PVLOGMSG\_C\_STACK\_DEBUG, 859  
     PVLOGMSG\_C\_STACK\_TRACE, 859  
     PVLOGMSG\_C\_WARNING, 859  
 PVLOGGER\_C\_INST\_LEVEL  
   pvlogger\_c.h, 859  
 PVLOGGER\_ENABLE  
   pvlogger.h, 851  
 PVLOGGER\_FILTER\_ACCEPT  
   pvlogger\_accessories.h, 857  
 PVLOGGER\_FILTER\_NEUTRAL  
   pvlogger\_accessories.h, 857  
 PVLOGGER\_FILTER\_REJECT  
   pvlogger\_accessories.h, 857  
 pvLogger\_GetLoggerObject  
   pvlogger\_c.h, 859  
 PVLOGGER\_INST\_LEVEL  
   osclconfig.h, 803  
   pvlogger.h, 852  
 PVLOGGER\_INST\_LEVEL\_SUPPORT  
   pvlogger.h, 852  
 pvLogger\_IsActive  
   pvlogger\_c.h, 859  
 PVLOGGER\_LEVEL\_UNINITIALIZED  
   pvlogger.h, 855  
 PVLOGGER\_LOG\_USE\_ONLY  
   pvlogger.h, 852  
 PVLOGGER\_LOGBIN  
   pvlogger.h, 852  
     PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_-  
       HLDBG  
       pvlogger.h, 852  
     PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_-  
       LLDBG  
       pvlogger.h, 853  
     PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_-  
       MLDBG

pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_PROF**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_PVLOGMSG\_INST\_REL**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_V**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_HLDBG**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_LLDBG**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_PROF**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_INST\_REL**  
 pvlogger.h, 853  
**PVLOGGER\_LOGBIN\_V\_PVLOGMSG\_V\_INST\_MLDBG**  
 pvlogger.h, 853  
**PVLOGGER\_LOGMSG**  
 pvlogger.h, 853  
**PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_HLDBG**  
 pvlogger.h, 853  
**PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_LLDBG**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_MLDBG**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_PROF**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_PVLOGMSG\_INST\_REL**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_V**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_HLDBG**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_LLDBG**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_MLDBG**  
 pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_PROF**

pvlogger.h, 854  
**PVLOGGER\_LOGMSG\_V\_PVLOGMSG\_INST\_REL**  
 pvlogger.h, 854  
**pvLogger\_LogMsgString**  
 pvlogger\_c.h, 859  
**pvlogger\_registry.h**, 860  
**PVLoggerAppender**, 622  
**PVLoggerAppender**  
 ~PVLoggerAppender, 622  
 AppendBuffers, 622  
 AppendString, 622  
 message\_id\_type, 622  
**PVLoggerFilter**, 623  
**PVLoggerFilter**  
 ~PVLoggerFilter, 624  
 filter\_status\_type, 623  
 FilterOpaqueMessge, 624  
 FilterString, 624  
 log\_level\_type, 623  
 message\_id\_type, 623  
**PVLoggerLayout**, 625  
**PVLoggerLayout**  
 ~PVLoggerLayout, 625  
 FormatOpaqueMessage, 625  
 FormatString, 625  
 message\_id\_type, 625  
**PVLoggerRegistry**, 627  
**PVLogger**, 621  
**PVLoggerRegistry**, 627  
**PVLoggerRegistry**  
 ~PVLoggerRegistry, 627  
 alloc\_type, 627  
 CreatePVLogger, 628  
 GetPVLoggerObject, 628  
 GetPVLoggerRegistry, 628  
 log\_level\_type, 627  
 PVLoggerRegistry, 627  
 SetNodeLogLevelExplicit, 628  
**PVLOGMSG\_ALERT**  
 pvlogger.h, 855  
**PVLOGMSG\_C\_ALERT**  
 pvlogger\_c.h, 859  
**PVLOGMSG\_C\_CRIT**  
 pvlogger\_c.h, 859  
**PVLOGMSG\_C\_EMERG**  
 pvlogger\_c.h, 859  
**PVLOGMSG\_C\_ERR**  
 pvlogger\_c.h, 859  
**PVLOGMSG\_C\_INFO**  
 pvlogger\_c.h, 859  
**PVLOGMSG\_C\_INST\_HLDBG**  
 pvlogger\_c.h, 859  
**PVLOGMSG\_C\_INST\_LLDBG**

pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_INST\_MLDBG**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_INST\_PROF**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_INST\_REL**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_NOTICE**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_STACK\_DEBUG**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_STACK\_TRACE**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_C\_WARNING**  
 pvlogger\_c.h, [859](#)  
**PVLOGMSG\_CRIT**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_DEBUG**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_EMERG**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_ERR**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_FATAL\_ERROR**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_INFO**  
 pvlogger.h, [856](#)  
**PVLOGMSG\_INST\_HLDBG**  
 pvlogger.h, [854](#)  
**PVLOGMSG\_INST\_LLDBG**  
 pvlogger.h, [854](#)  
**PVLOGMSG\_INST\_MLDBG**  
 pvlogger.h, [854](#)  
**PVLOGMSG\_INST\_PROF**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_INST\_REL**  
 pvlogger.h, [855](#)  
**PVLOGMSG\_NONFATAL\_ERROR**  
 pvlogger.h, [856](#)  
**PVLOGMSG\_NOTICE**  
 pvlogger.h, [856](#)  
**PVLOGMSG\_STACK\_TRACE**  
 pvlogger.h, [856](#)  
**PVLOGMSG\_STATISTIC**  
 pvlogger.h, [856](#)  
**PVLOGMSG\_VERBOSE**  
 pvlogger.h, [856](#)  
**PVLOGMSG\_WARNING**  
 pvlogger.h, [856](#)  
**PVMEM\_INST\_LEVEL**  
 osclbase, [34](#)  
 osclconfig\_memory.h, [827](#)  
**PVNETWORKADDRESS\_LEN**  
 oscl\_socket\_types.h, [774](#)  
  
**PVOsclBase\_Cleanup**  
 osclbase, [44](#)  
**PVOsclBase\_Init**  
 osclbase, [44](#)  
**PVSCHEDNAMELEN**  
 osclproc, [104](#)  
**PVSchedulerStopper**, [630](#)  
 OsclExecSchedulerCommonBase, [398](#)  
**PVSchedulerStopper**, [630](#)  
**PVSchedulerStopper**  
 ~PVSchedulerStopper, [630](#)  
 PVSchedulerStopper, [630](#)  
**PVSOCK\_ERR\_BAD\_PARAM**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSOCK\_ERR\_NOT\_IMPLEMENTED**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSOCK\_ERR\_NOT\_SUPPORTED**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSOCK\_ERR\_SERV\_NOT\_CONNECTED**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSOCK\_ERR\_SOCK\_NO\_SERV**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSOCK\_ERR\_SOCK\_NOT\_CONNECTED**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSOCK\_ERR\_SOCK\_NOT\_OPEN**  
 oscl\_socket\_imp\_pv.h, [757](#)  
**PVSockBufRecv**, [631](#)  
 PVSockBufRecv, [631](#)  
**PVSockBufRecv**  
 iLen, [631](#)  
 iMaxLen, [631](#)  
 iPtr, [631](#)  
 PVSockBufRecv, [631](#)  
**PVSockBufSend**, [632](#)  
 PVSockBufSend, [632](#)  
**PVSockBufSend**  
 iLen, [632](#)  
 iPtr, [632](#)  
 PVSockBufSend, [632](#)  
**PVThreadContext**, [633](#)  
 OsclExecSchedulerCommonBase, [398](#)  
**PVThreadContext**, [633](#)  
**PVThreadContext**  
 ~PVThreadContext, [633](#)  
 EnterThreadContext, [633](#)  
 ExitThreadContext, [633](#)  
 Id, [633](#)  
 IsSameThreadContext, [633](#)  
 OsclActiveObject, [634](#)  
 OsclCoeActiveScheduler, [634](#)  
 OsclCoeActiveSchedulerBase, [634](#)  
 OsclExecScheduler, [634](#)  
 OsclExecSchedulerBase, [634](#)  
 OsclExecSchedulerCommonBase, [634](#)

OsclTimerObject, 634  
 PVActiveBase, 634  
 PVThreadContext, 633  
 ThreadHasScheduler, 634

**QUE\_ITER\_BEGIN**  
 osclproc, 104

**QUE\_ITER\_END**  
 osclproc, 104

**Rand**  
 OsclRand, 480

**Read**  
 Oscl\_File, 182  
 OsclAsyncFile, 317  
 OsclBinIStreamBigEndian, 326  
 OsclFileCache, 401  
 OsclNativeFile, 462

**read**  
 OSCL\_String, 262  
 OSCL\_wString, 305

**Read\_uint16**  
 OsclBinIStreamBigEndian, 326  
 OsclBinIStreamLittleEndian, 329

**Read\_uint32**  
 OsclBinIStreamBigEndian, 326  
 OsclBinIStreamLittleEndian, 329

**Read\_uint8**  
 OsclBinIStream, 323

**ReadAsync**  
 OsclNativeFile, 462

**ReadAsyncCancel**  
 OsclNativeFile, 462

**rebalance**  
 Oscl\_Rb\_Tree\_Base, 245

**rebalance\_for\_erase**  
 Oscl\_Rb\_Tree\_Base, 245

**Recv**  
 OsclRecvMethod, 489  
 OsclRecvRequest, 490  
 OsclSocketI, 537  
 OsclSocketIBase, 542  
 OsclTCPSocket, 569  
 OsclTCPSocketI, 573

**RecvFrom**  
 OsclRecvFromMethod, 485  
 OsclRecvFromRequest, 487  
 OsclSocketI, 537  
 OsclSocketIBase, 542  
 OsclUDPSocket, 603  
 OsclUDPSocketI, 607

**RecvFromParam**, 635  
 RecvFromParam, 635

**RecvFromParam**

iAddr, 635  
 iBufRecv, 635  
 iFlags, 635  
 iMultiMaxLen, 635  
 iPacketLen, 635  
 iPacketSource, 635  
 RecvFromParam, 635

**RecvFromRequest**  
 OsclRecvFromMethod, 485

**RecvFromSuccess**  
 OsclSocketI, 537  
 OsclSocketIBase, 542

**RecvParam**, 637  
 RecvParam, 637

**RecvParam**  
 iBufRecv, 637  
 iFlags, 637  
 RecvParam, 637

**RecvRequest**  
 OsclRecvMethod, 489

**RecvSuccess**  
 OsclSocketI, 537  
 OsclSocketIBase, 542

**red**  
 Oscl\_Rb\_Tree\_Node\_Base, 253

**RedBl**  
 Oscl\_Rb\_Tree\_Node\_Base, 253

**refcount**  
 CHeapRep, 129

**reference**  
 Oscl\_Map, 217  
 Oscl\_Queue, 236  
 Oscl\_Rb\_Tree, 243  
 Oscl\_Rb\_Tree\_Const\_Iterator, 247  
 Oscl\_Rb\_Tree\_Iterator, 250  
 Oscl\_TagTree::const\_iterator, 273  
 Oscl\_TagTree::iterator, 276  
 Oscl\_TAlloc, 281  
 Oscl\_Vector, 285

**Register**  
 OsclComponentRegistry, 343  
 OsclRegistryClient, 508  
 OsclRegistryClientImpl, 511  
 OsclRegistryServTlsImpl, 514

**RegisterForCallback**  
 OsclExecScheduler, 388  
 OsclReadyQ, 484

**registerInstance**  
 OsclSingletonRegistry, 533  
 OsclTLSRegistry, 595  
 OsclTLSRegistryEx, 596

**registerInstanceAndUnlock**  
 OsclSingletonRegistry, 533

**release**

OsclExclusiveArrayPtr, 381  
 OsclExclusivePtr, 384  
 OsclExclusivePtrA, 387  
 OSCLMemAutoPtr, 436  
**RELOCK\_MUTEX\_ERROR**  
 OsclProcStatus, 475  
**Remove**  
 OsclDoubleLink, 365  
 OsclReadyQ, 484  
 OsclSocketServRequestList, 559  
 OsclTimerQ, 590  
**remove**  
 OsclPriorityQueue, 471  
 OsclPriorityQueueBase, 473  
**remove\_element**  
 Oscl\_Linked\_List, 208  
 Oscl\_Linked\_List\_Base, 213  
 Oscl\_MTLinked\_List, 226  
**remove\_ref**  
 CHeapRep, 129  
**removeALLAllocNodes**  
 MM\_Audit\_Imp, 158  
**removeAllocNode**  
 MM\_Audit\_Imp, 158  
**RemoveAppender**  
 PVLogger, 620  
**RemoveFixedCache**  
 Oscl\_File, 182  
**RemoveFromScheduler**  
 OsclActiveObject, 311  
 OsclTimerObject, 587  
 PVActiveBase, 613  
**RemoveRef**  
 DNSRequestParam, 133  
**removeRef**  
 Oscl\_DefAllocWithRefCounter, 173  
 OsclMemPoolFixedChunkAllocator, 444  
 OsclMemPoolResizableAllocator, 451  
 OsclRefCounter, 491  
 OsclRefCounterDA, 494  
 OsclRefCounterMTDA, 498  
 OsclRefCounterMTSA, 500  
 OsclRefCounterSA, 502  
**Request**  
 OsclTimer, 582  
**RequestCanceled**  
 OsclExecSchedulerCommonBase, 395  
**RequestDone**  
 OsclDNSRequestAO, 363  
 OsclSocketRequestAO, 551  
**reserve**  
 Oscl\_Queue\_Base, 239  
 Oscl\_Vector\_Base, 292  
 OsclPriorityQueue, 471  
**ReserveSpace**  
 OsclBinStream, 337  
**Reset**  
 OsclDoubleListBase, 368  
**reset**  
 BufferState, 118  
 MM\_FailInsertParam, 161  
 MM\_Stats\_t, 164  
 OsclMemStatsNode, 457  
**ResetLogPerf**  
 OsclExecSchedulerCommonBase, 395  
**Resume**  
 OsclThread, 576  
**ResumeScheduler**  
 OsclExecSchedulerCommonBase, 395  
**retrieveParentTag**  
 MM\_Audit\_Imp, 158  
**retrieveParentTagLength**  
 MM\_Audit\_Imp, 158  
**RFC822ToPV8601**  
 osclbase, 45  
**Right**  
 OsclPtrC, 479  
**right**  
 Oscl\_Rb\_Tree\_Node\_Base, 254  
**rotate\_left**  
 Oscl\_Rb\_Tree\_Base, 245  
**rotate\_right**  
 Oscl\_Rb\_Tree\_Base, 245  
**Run**  
 CallbackTimer, 123  
 OsclDNSMethod, 358  
 OsclDNSRequestAO, 363  
 OsclSocketMethod, 545  
 OsclSocketRequestAO, 551  
 PVActiveBase, 613  
**RunError**  
 OsclActiveObject, 311  
 OsclTimerObject, 587  
 PVActiveBase, 613  
**RunIfNotReady**  
 OsclActiveObject, 312  
 OsclTimerObject, 587  
**RunSchedulerNonBlocking**  
 OsclExecScheduler, 388  
**save\_registry**  
 TLSStorageOps, 655  
**second**  
 Oscl\_Pair, 234  
**SECONDS**  
 osclbase, 35  
**Seed**  
 OsclRand, 480

Seek  
   Oscl\_File, 182  
   OsclAsyncFile, 317  
   OsclBinStream, 337  
   OsclFileCache, 401  
   OsclNativeFile, 463

seek\_type  
   Oscl\_File, 179

SEEKCUR  
   Oscl\_File, 179

SEEKEND  
   Oscl\_File, 179

seekFromCurrentPosition  
   OsclBinStream, 337

SEEKSET  
   Oscl\_File, 179

self  
   Oscl\_Map, 217  
   Oscl\_Rb\_Tree\_Const\_Iterator, 247  
   Oscl\_Rb\_Tree\_Iterator, 250  
   Oscl\_TagTree::const\_iterator, 273  
   Oscl\_TagTree::iterator, 276

SEM\_NOT\_SIGNALLED\_ERROR  
   OsclProcStatus, 475

Send  
   OsclSendMethod, 522  
   OsclSendRequest, 523  
   OsclSocketI, 537  
   OsclSocketIBase, 542  
   OsclTCPSocket, 569  
   OsclTCPSocketI, 573

SendParam, 638  
   SendParam, 638

SendParam  
   iBufSend, 638  
   iFlags, 638  
   iXferLen, 638  
   SendParam, 638

SendRequest  
   OsclSendMethod, 522

SendSuccess  
   OsclSocketI, 537  
   OsclSocketIBase, 542

SendTo  
   OsclSendToMethod, 524  
   OsclSendToRequest, 525  
   OsclSocketI, 537  
   OsclSocketIBase, 542  
   OsclUDPSocket, 604  
   OsclUDPSocketI, 607

SendToParam, 639  
   SendToParam, 639

SendToParam  
   ~SendToParam, 639

iAddr, 639  
 iBufSend, 639  
 iFlags, 639  
 iXferLen, 639  
 SendToParam, 639

SendToRequest  
   OsclSendToMethod, 524

SendToSuccess  
   OsclSocketI, 537  
   OsclSocketIBase, 542

Serv  
   OsclDNSRequestAO, 364

Set  
   OsclDoubleRunner, 369  
   OsclNameString, 460  
   OsclPtr, 476  
   OsclPtrC, 479

set  
   CHHeapRep, 129  
   CStackRep, 131  
   OSCL\_FastString, 176, 177  
   OSCL\_HeapStringA, 200, 201  
   OSCL\_wFastString, 295  
   OSCL\_wHeapStringA, 300  
   OsclExclusiveArrayPtr, 381  
   OsclExclusivePtr, 384  
   OsclExclusivePtrA, 387  
   OsclSingleton, 531  
   OsclTLS, 591  
   OsclTLSEx, 593  
   osclutil, 81–83

set\_from\_ntp\_time  
   TimeValue, 653

set\_from\_system\_time  
   NTPTime, 168

set\_int64  
   Oscl\_Int64\_Utils, 203

set\_len  
   OSCL\_String, 262  
   OSCL\_wString, 306

set\_length  
   OSCL\_FastString, 177  
   OSCL\_wFastString, 295

set\_next  
   Oscl\_Opaque\_Type\_Alloc\_LL, 231

set\_r  
   CFastRep, 127

set\_rep  
   CHHeapRep, 129  
   OSCL\_String, 262, 263  
   OSCL\_wString, 306

set\_to\_current\_time  
   NTPTime, 168  
   TimeValue, 653

set\_to\_zero  
     TimeValue, [654](#)  
 set\_uint64  
     Oscl\_Int64\_Utils, [203](#)  
 set\_w  
     CFastRep, [127](#)  
 set\_zulu  
     TimeValue, [654](#)  
 setAllocNodeFlag  
     MM\_AllocBlockHdr, [147](#)  
 SetAsyncReadBufferSize  
     Oscl\_File, [182](#)  
 SetBusy  
     OsclActiveObject, [312](#)  
     OsclTimerObject, [587](#)  
 SetCacheObserver  
     Oscl\_File, [183](#)  
 setCheckSum  
     StrCSumPtrLen, [644](#)  
 SetExactFrequency  
     OsclTimer, [582](#)  
 SetFileHandle  
     Oscl\_File, [183](#)  
 SetFrequency  
     OsclTimer, [583](#)  
 SetInUse  
     OsclAsyncFileBuffer, [319](#)  
 SetLength  
     OsclPtr, [476](#)  
     OsclPtrC, [479](#)  
 SetLoggingEnable  
     Oscl\_File, [183](#)  
 SetLogLevel  
     PVLogger, [620](#)  
 SetLogLevelAndPropagate  
     PVLogger, [621](#)  
 setMaxSzForNewMemPoolBuffer  
     OsclMemPoolResizableAllocator, [451](#)  
 SetMulticastTTL  
     OsclUDPSocket, [604](#)  
     OsclUDPSocketI, [607](#)  
 SetNativeAccessMode  
     Oscl\_File, [183](#)  
 SetNativeBufferSize  
     Oscl\_File, [184](#)  
 SetNodeLogLevelExplicit  
     PVLoggerRegistry, [628](#)  
 SetObserver  
     OsclTimer, [583](#)  
 SetOffset  
     OsclAsyncFileBuffer, [319](#)  
     OsclDoubleListBase, [368](#)  
 SetOptionToReuseAddress  
     OsclIPSocketI, [418](#)  
     OsclTCPSocket, [569](#)  
     OsclUDPSocket, [604](#)  
 SetParent  
     PVLogger, [621](#)  
 SetPosition  
     OsclFileCacheBuffer, [403](#)  
 SetPrecedence  
     OsclSocketTOS, [563](#)  
 SetPriority  
     OsclSocketTOS, [563](#)  
     OsclThread, [576](#)  
 setPtrLen  
     StrCSumPtrLen, [644](#)  
     StrPtrLen, [647](#)  
     WStrPtrLen, [658](#)  
 SetPVCacheSize  
     Oscl\_File, [184](#)  
 SetRecvBufferSize  
     OsclIPSocketI, [418](#)  
     OsclSocketI, [537](#)  
     OsclUDPSocket, [605](#)  
 setrep\_to\_char  
     OSCL\_String, [263](#)  
 setrep\_to\_wide\_char  
     OSCL\_wString, [306](#)  
 SetScheduler  
     OsclExecSchedulerCommonBase, [395](#)  
 SetSize  
     Oscl\_File, [184](#)  
     OsclNativeFile, [463](#)  
 SetSockOpt  
     OsclSocketI, [538](#)  
 SetStatus  
     OsclActiveObject, [312](#)  
     OsclTimerObject, [587](#)  
 SetSummaryStatsLoggingEnable  
     Oscl\_File, [184](#)  
 SetTimestamp  
     MediaData, [143](#)  
 SetToHead  
     OsclDoubleRunner, [369](#)  
 SetTOS  
     OsclIPSocketI, [418](#)  
     OsclTCPSocket, [570](#)  
     OsclUDPSocket, [605](#)  
 SetToTail  
     OsclDoubleRunner, [369](#)  
 setWithoutOwnership  
     OSCLMemAutoPtr, [436](#)  
 ShowStats  
     OsclExecSchedulerCommonBase, [395](#)  
 ShowSummaryStats  
     OsclExecSchedulerCommonBase, [395](#)  
 Shutdown

OsclShutdownMethod, 529  
OsclShutdownRequest, 530  
OsclSocketI, 538  
OsclSocketIBase, 543  
OsclTCPSocket, 570  
OsclTCPSocketI, 573  
ShutdownParam, 640  
    ShutdownParam, 640  
ShutdownParam  
    iHow, 640  
    ShutdownParam, 640  
ShutdownRequest  
    OsclShutdownMethod, 529  
Signal  
    OsclSemaphore, 521  
Size  
    Oscl\_File, 184  
    OsclAsyncFile, 317  
    OsclNativeFile, 463  
size  
    CFastRep, 127  
    CHheapRep, 129  
    CStackRep, 131  
    MM\_AllocBlockHdr, 147  
    MM\_AllocInfo, 149  
    MM\_AllocQueryInfo, 151  
    Oscl\_Map, 220  
    Oscl\_Queue\_Base, 239  
    Oscl\_Rb\_Tree, 243  
    Oscl\_TagTree, 271  
    Oscl\_Vector\_Base, 292  
    OsclPriorityQueue, 471  
    StrPtrLen, 647  
    WStrPtrLen, 658  
size\_type  
    Oscl\_Map, 217  
    Oscl\_Queue, 236  
    Oscl\_Rb\_Tree, 243  
    Oscl\_Tag\_Base, 267  
    Oscl\_TagTree, 269  
    Oscl\_TAlloc, 281  
sizeof\_T  
    Oscl\_Linked\_List\_Base, 214  
    Oscl\_Queue\_Base, 240  
    Oscl\_Vector\_Base, 292  
skip\_to\_line\_term  
    osclutil, 83  
skip\_to\_whitespace  
    osclutil, 83  
skip\_whitespace  
    osclutil, 83  
skip\_whitespace\_and\_line\_term  
    osclutil, 83  
SLEEP ONE SEC  
osclconfig\_util.h, 847  
SleepMillisec  
    OsclThread, 576  
Socket  
    OsclSocketI, 538  
SocketI  
    OsclSocketRequestAO, 551  
SocketObserver  
    OsclSocketRequestAO, 551  
SocketRequestParam, 641  
    SocketRequestParam, 642  
SocketRequestParam  
    iFxn, 642  
    SocketRequestParam, 642  
SocketServ  
    OsclIPSocketI, 418  
sort\_children  
    Oscl\_TagTree::Node, 279  
specialFragBuffer  
    OsclBinStream, 338  
Start  
    OsclFileStats, 410  
Start\_on\_creation  
    oscl\_thread.h, 788  
StartAsyncRead  
    OsclAsyncFileBuffer, 319  
StartCancel  
    OsclSocketServRequestList, 559  
StartMethod  
    OsclDNSMethod, 358  
    OsclSocketMethod, 546  
StartNativeScheduler  
    OsclExecSchedulerCommonBase, 395  
StartScheduler  
    OsclExecSchedulerCommonBase, 395  
State  
    OsclSocketServIBase, 558  
state  
    OsclBinStream, 338  
state\_t  
    OsclBinStream, 336  
StaticJump  
    OsclJump, 420  
stats\_overhead  
    MM\_AuditOverheadStats, 160  
Status  
    OsclActiveObject, 312  
    OsclTimerObject, 588  
status\_t  
    BufFragStatusClass, 122  
StatusRef  
    OsclActiveObject, 312  
    OsclTimerObject, 588  
StopScheduler

OsclExecSchedulerCommonBase, 395  
**Str**  
 OsclNameString, 460  
 StrCSumPtrLen, 643  
   osclutil, 68  
 StrCSumPtrLen, 644  
**StrCSumPtrLen**  
   checkSum, 644  
   CheckSumType, 644  
   getCheckSum, 644  
   isCIEquivalentTo, 644  
   operator!=, 644  
   operator=, 644  
   operator==, 644  
   setCheckSum, 644  
   setPtrLen, 644  
   StrCSumPtrLen, 644  
**StrPtrLen**, 646  
   osclutil, 68  
   StrPtrLen, 647  
**StrPtrLen**  
   c\_str, 647  
   isCIEquivalentTo, 647  
   isCIPrefixOf, 647  
   isLetter, 647  
   len, 647  
   length, 647  
   operator!=, 647  
   operator=, 647  
   operator==, 647  
   ptr, 647  
   setPtrLen, 647  
   size, 647  
   StrPtrLen, 647  
**Success**  
 OsclDNSRequestAO, 364  
 OsclRecvFromRequest, 487  
 OsclRecvRequest, 490  
 OsclSendRequest, 523  
 OsclSendToRequest, 525  
 OsclSocketRequestAO, 551  
**SUCCESS\_ERROR**  
 OsclProcStatus, 474  
**Suspend**  
 OsclThread, 577  
**Suspend\_on\_creation**  
 oscl\_thread.h, 788  
**SuspendScheduler**  
 OsclExecSchedulerCommonBase, 396  
**swap**  
 Oscl\_Opaque\_Type\_Compare, 232  
 OsclPriorityQueue, 471  
**SYSTEM\_RESOURCES\_UNAVAILABLE\_ERROR**  
**OsclProcStatus**, 475  
**MM\_AllocQueryInfo**, 151  
**MM\_Stats\_CB**, 162  
**Oscl\_Tag**, 264  
**Oscl\_TagTree::Node**, 279  
**OsclMemStatsNode**, 457  
**tag\_ancestor**  
 Oscl\_Tag\_Base, 267  
**tag\_base\_type**  
 Oscl\_Tag\_Base, 267  
 Oscl\_TagTree, 269  
**tag\_base\_unit**  
 Oscl\_Tag\_Base, 267  
**tag\_cmp**  
 Oscl\_Tag\_Base, 267  
**tag\_copy**  
 Oscl\_Tag\_Base, 267  
**tag\_depth**  
 Oscl\_Tag\_Base, 267  
**tag\_len**  
 Oscl\_Tag\_Base, 267  
**tag\_type**  
 Oscl\_TagTree, 269  
**tagAllocator**  
 Oscl\_Tag, 264  
**TagTree\_Allocator**  
 osclmemory, 58  
**Tail**  
 OsclDoubleList, 366  
 OsclPriorityList, 468  
**tail**  
 Oscl\_Linked\_List\_Base, 214  
**takeOwnership**  
 OSCLMemAutoPtr, 437  
**TDNSRequestParamAllocator**  
 oscl\_dns\_param.h, 674  
**Tell**  
 Oscl\_File, 184  
 OsclAsyncFile, 317  
 OsclFileCache, 401  
 OsclNativeFile, 463  
**tellg**  
 OsclBinStream, 337  
**Terminate**  
 OsclThread, 577  
**the\_list**  
 Oscl\_MTLLinked\_List, 226  
**THREAD\_1\_INACTIVE\_ERROR**  
 OsclProcStatus, 474  
**THREAD\_BLOCK\_ERROR**  
 OsclProcStatus, 475  
**THREAD\_NOT OWN\_MUTEX\_ERROR**

---

OsclProcStatus, [475](#)  
 ThreadHasScheduler  
   PVThreadContext, [634](#)  
 ThreadLogoff  
   OsclIPSocketI, [418](#)  
   OsclReadyQ, [484](#)  
   OsclSocketI, [538](#)  
   OsclSocketMethod, [546](#)  
   OsclTCPSocket, [570](#)  
   OsclTCPSocketI, [573](#)  
   OsclUDPSocket, [605](#)  
   OsclUDPSocketI, [607](#)  
 ThreadLogon  
   OsclIPSocketI, [418](#)  
   OsclReadyQ, [484](#)  
   OsclSocketI, [538](#)  
   OsclSocketMethod, [546](#)  
   OsclTCPSocket, [570](#)  
   OsclTCPSocketI, [573](#)  
   OsclUDPSocket, [605](#)  
   OsclUDPSocketI, [607](#)  
 ThreadPriorityAboveNormal  
   oscl\_thread.h, [789](#)  
 ThreadPriorityBelowNormal  
   oscl\_thread.h, [789](#)  
 ThreadPriorityHighest  
   oscl\_thread.h, [789](#)  
 ThreadPriorityLow  
   oscl\_thread.h, [788](#)  
 ThreadPriorityLowest  
   oscl\_thread.h, [788](#)  
 ThreadPriorityNormal  
   oscl\_thread.h, [789](#)  
 ThreadPriorityTimeCritical  
   oscl\_thread.h, [789](#)  
 TickCount  
   OsclTickCount, [579](#)  
 TickCountFrequency  
   OsclTickCount, [579](#)  
 TickCountPeriod  
   OsclTickCount, [579](#)  
 TicksToMsec  
   OsclTickCount, [579](#)  
 TimeoutOccurred  
   OsclTimerObserver, [589](#)  
 TimerBaseElapsed  
   CallbackTimerObserver, [125](#)  
   OsclTimer, [583](#)  
 TimerCallback  
   OsclReadyQ, [484](#)  
 timestamp  
   MediaData, [143](#)  
 TimeUnits  
   osclbase, [35](#)  
 TimeValue, [648](#)  
   TimeValue, [650, 651](#)  
 TimeValue  
   get\_ISO8601\_str\_time, [651](#)  
   get\_local\_time, [651](#)  
   get\_pv8601\_str\_time, [651](#)  
   get\_rfc822\_gmtime\_str, [651](#)  
   get\_sec, [652](#)  
   get\_str\_ctime, [652](#)  
   get\_timeval\_ptr, [652](#)  
   get\_timevalue\_in\_usec, [652](#)  
   get\_usec, [652](#)  
   is\_zero, [653](#)  
   is\_zulu, [653](#)  
   NTPTime, [654](#)  
   operator \*=, [653](#)  
   operator!=, [654](#)  
   operator+=, [653](#)  
   operator-=, [653](#)  
   operator<, [654](#)  
   operator<=, [654](#)  
   operator=, [653](#)  
   operator==, [654](#)  
   operator>, [654](#)  
   operator>=, [654](#)  
   set\_from\_ntp\_time, [653](#)  
   set\_to\_current\_time, [653](#)  
   set\_to\_zero, [654](#)  
   set\_zulu, [654](#)  
   TimeValue, [650, 651](#)  
   to\_msec, [654](#)  
 TIpmReq  
   osclconfig\_io.h, [821](#)  
 TLSStorageOps, [655](#)  
 TLSStorageOps  
   get\_registry, [655](#)  
   save\_registry, [655](#)  
 to\_msec  
   TimeValue, [654](#)  
 to\_system\_time  
   NTPTime, [168](#)  
 TOO\_MANY\_FRAGS  
   BuffFragStatusClass, [122](#)  
 TOO\_MANY\_THREADS\_ERROR  
   OsclProcStatus, [474](#)  
 Top  
   OsclJump, [420](#)  
   OsclReadyQ, [484](#)  
   OsclTimerQ, [590](#)  
 top  
   OsclPriorityQueue, [471](#)  
 TOSCL\_StringOp  
   osclutil, [69](#)  
 TOSCL\_wStringOp

osclutil, 69  
**T**  
 OsclBasicLockObject  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
 OsclConditionObject  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclFileHandle  
     osclio, 96  
 OsclFileOffset  
     osclconfig\_io.h, 821  
 OsclFileOffsetInt32  
     osclio, 96  
 OsclFileOp  
     osclio, 97  
 OsclHostent  
     osclconfig\_io.h, 821  
 OsclMutexObject  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclReady  
     osclproc, 105  
 OsclSemaphoreObject  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclSockAddr  
     osclconfig\_io.h, 821  
 OsclSockAddrLen  
     osclconfig\_io.h, 821  
 OsclSocket  
     osclconfig\_io.h, 821  
 OsclSocketServStatEvent  
     oscl\_socket\_stats.h, 770  
 OsclSocketStatEvent  
     oscl\_socket\_stats.h, 770  
 OsclThreadFuncArg  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclThreadFuncPtr  
     oscl\_thread.h, 788  
 OsclThreadFuncRet  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclThreadId  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclThreadObject  
     osclconfig\_proc\_unix\_android.h, 834  
     osclconfig\_proc\_unix\_common.h, 836  
 OsclThreadTerminate  
     oscl\_thread.h, 789  
 OsclTlsKey  
     osclbase, 35  
     osclconfig\_unix\_android.h, 842  
 osclconfig\_unix\_common.h, 846  
 totalbytes  
     oscl\_fsstat, 194  
 totalNumAllocs  
     MM\_Stats\_t, 164  
 totalNumBytes  
     MM\_Stats\_t, 164  
 TOtherExecStats  
     OsclExecSchedulerCommonBase, 393  
 TPVDNSEvent  
     osclio, 98  
 TPVDNSFxn  
     osclio, 98  
 TPVServicePrecedence  
     OsclSocketTOS, 562  
 TPVServicePriority  
     OsclSocketTOS, 562  
 TPVSocketEvent  
     oscl\_socket\_types.h, 774  
 TPVSocketFxn  
     oscl\_socket\_types.h, 775  
 TPVSocketOptionLevel  
     oscl\_socket\_types.h, 775  
 TPVSocketOptionName  
     oscl\_socket\_types.h, 775  
 TPVSocketShutdown  
     oscl\_socket\_types.h, 775  
 TPVThreadContext  
     osclproc, 105  
 Trap  
     OsclErrorTrapImp, 376  
 TrapNoTls  
     OsclErrorTrapImp, 376  
 TReadyQueLink, 656  
     TReadyQueLink, 656  
 TReadyQueLink  
     iAOPriority, 656  
     iIsIn, 656  
     iSeqNum, 656  
     iTimeQueuedTicks, 656  
     iTimeToRunTicks, 656  
     TReadyQueLink, 656  
 trim  
     OsclMemPoolResizableAllocator, 451  
 TryLock  
     OsclMutex, 459  
 TryWait  
     OsclSemaphore, 521  
 TSocketServState  
     OsclSocketServIBase, 557  
 TSymbianAccessMode  
     Oscl\_File, 179  
 uint

osclbase, 35  
**UINT64**  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
**uint64**  
     osclbase, 35  
**UINT64\_HILO**  
     osclconfig\_unix\_android.h, 842  
     osclconfig\_unix\_common.h, 846  
**Unbind**  
     OsclSharedPtr, 528  
**UninstallScheduler**  
     OsclExecSchedulerCommonBase, 396  
**unix\_ntp\_offset**  
     osclbase, 45  
**Unlock**  
     OsclLockBase, 423  
     OsclMutex, 459  
     OsclNullLock, 466  
     OsclThreadLock, 578  
**UnRegister**  
     OsclRegistryClient, 509  
     OsclRegistryClientImpl, 511  
     OsclRegistryServTlsImpl, 514  
**Unregister**  
     OsclComponentRegistry, 343  
**UnTrap**  
     OsclErrorTrapImp, 376  
**update**  
     MM\_Stats\_t, 164  
**UpdateData**  
     OsclAsyncFileBuffer, 319  
**updateEnd**  
     OsclFileCacheBuffer, 403  
**updateStart**  
     OsclFileCacheBuffer, 403  
**updateStatsNode**  
     MM\_Audit\_Imp, 158  
**updateStatsNodeInFailure**  
     MM\_Audit\_Imp, 158  
**UpdateTimers**  
     OsclExecSchedulerCommonBase, 396  
**UpdateTimersMsec**  
     OsclExecSchedulerCommonBase, 396  
**upper\_bound**  
     Oscl\_Map, 220, 221  
     Oscl\_Rb\_Tree, 243  
**usableSize**  
     OsclFileCacheBuffer, 403  
**USEC\_PER\_SEC**  
     osclbase, 45  
**validate**  
     MM\_Audit\_Imp, 158  
     OsclPriorityQueue, 472  
**validate\_all\_heap**  
     MM\_Audit\_Imp, 158  
**validateblock**  
     OsclMemPoolResizableAllocator, 451  
**Value**  
     OsclAOStatus, 314  
**value**  
     Oscl\_Rb\_Tree\_Node, 252  
     Oscl\_TagTree::Node, 279  
**value\_comp**  
     Oscl\_Map, 221  
**value\_compare**  
     Oscl\_Map::value\_compare, 222  
**value\_type**  
     Oscl\_Map, 217  
     Oscl\_Queue, 236  
     Oscl\_Rb\_Tree, 243  
     Oscl\_Rb\_Tree\_Const\_Iterator, 247  
     Oscl\_Rb\_Tree\_Iterator, 250  
     Oscl\_Rb\_Tree\_Node, 252  
     Oscl\_TagTree, 269  
     Oscl\_TAlloc, 281  
     Oscl\_Vector, 285  
     OsclPriorityQueue, 470  
**vec**  
     OsclPriorityQueue, 472  
**Wait**  
     OsclSemaphore, 521  
**WAIT\_ABANDONED\_ERROR**  
     OsclProcStatus, 475  
**WAIT\_TIMEOUT\_ERROR**  
     OsclProcStatus, 475  
**WaitAndPopTop**  
     OsclReadyQ, 484  
**WaitForReadyAO**  
     OsclExecSchedulerCommonBase, 396  
**WaitForRequestComplete**  
     OsclReadyQ, 484  
**WaitOnRequests**  
     OsclSocketServRequestList, 559  
**Wakeup**  
     OsclSocketServRequestList, 559  
**writable**  
     CFastRep, 127  
**Write**  
     Oscl\_File, 185  
     OsclAsyncFile, 317  
     OsclFileCache, 401  
     OsclNativeFile, 463  
**write**  
     OSCL\_String, 263  
     OSCL\_wString, 306

OsclBinOStream, [330](#)  
    WriteUnsignedLong  
        OsclBinOStreamBigEndian, [332](#)  
        OsclBinOStreamLittleEndian, [334](#)  
    WriteUnsignedShort  
        OsclBinOStreamBigEndian, [332](#)  
        OsclBinOStreamLittleEndian, [334](#)  
    WriteUpdatesToFile  
        OsclFileCacheBuffer, [403](#)  
    WStrPtrLen, [657](#)  
        osclutil, [68](#)  
        WStrPtrLen, [658](#)  
    WStrPtrLen  
        c\_str, [658](#)  
        isCIEquivalentTo, [658](#)  
        len, [658](#)  
        length, [658](#)  
        operator!=, [658](#)  
        operator=, [658](#)  
        operator==, [658](#)  
        ptr, [658](#)  
        setPtrLen, [658](#)  
        size, [658](#)  
        WStrPtrLen, [658](#)  
  
    xsubi  
        MM\_FailInsertParam, [161](#)  
  
    Zero  
        OsclPtr, [476](#)  
        OsclPtrC, [479](#)