Institute for System Programming of the Russian Academy of Sciences

MicroTESK User Guide (UNDER DEVELOPMENT)

Contents

1	Ove	Overview									
2	Inst	nstallation									
	2.1	System Requirements	4								
	2.2	Installation Steps	4								
		2.2.1 Setting Environment Variables	4								
		2.2.2 Installing Constraint Solvers	5								
	2.3	Installation Directory Structure	6								
	2.4	Running	6								
	2.5	Command-Line Options	7								
	2.6	Settings File	9								
	2.0	bettings i ne	J								
3	Test	t Templates	10								
	3.1	Introduction	10								
	3.2	Test Template Structure	10								
	3.3	Reusing Test Templates	11								
	3.4	Test Template Settings	12								
	3.5	Text Printing	13								
	3.6	Random Distributions	14								
	3.7	Instruction Calls	15								
		3.7.1 Aliases	16								
		3.7.2 Pseudo Instructions	16								
		3.7.3 Groups	16								
	3.8	Data	17^{-3}								
		3.8.1 Configuration	17								
		3.8.2 Definitions	18								
	3.9	Preparators	19								
		•									
4	Test		2 0								
	4.1	Parameters	20								
	4.2	Description	20								
5	Apr	pendixes	21								
J	Ар г 5.1	References									
	0.1										
		Β ΙΟΠΟ <u>Κ</u> Ιάρπγ	41								

Overview

Installation

2.1 System Requirements

MicroTESK is a set of Java-based utilities that are run from the command line. It can be used on *Windows*, *Linux* and *OS X* machines that have *JDK 1.7 or later* installed. To build MicroTESK from source code or to build the generated Java models, *Apache Ant version 1.8 or later* is required. To generate test data based on constraints, MicroTESK needs the *Microsoft Research Z3* or *CVC4* solver that can work on the corresponding operating system.

2.2 Installation Steps

To install MicroTESK, the following steps should be performed:

- 1. Download from http://forge.ispras.ru/projects/microtesk/files and unpack the MicroTESK installation package (the .tar.gz file, latest release) to your computer. The folder to which it was unpacked will be further referred to as the installation directory (<installation dir>).
- 2. Declare the MICROTESK_HOME environment variable and set its value to the path to the installation directory (see the Setting Environment Variables section).
- 3. Set the <installation dir>/bin folder as the working directory (add the path to the PATH environment variable) to be able to run MicroTESK utilities from any path.
- 4. Note: Required for constraint-based generation. Download and install constraint solver tools to the <installation dir>/tools directory (see the Installing Constraint Solvers section).

2.2.1 Setting Environment Variables

Windows

1. Open the System Properties window.

- 2. Switch to the Advanced tab.
- 3. Click on Environment Variables.
- 4. Click New.. under System Variables.
- 5. In the New System Variable dialog, specify variable name as MICROTESK_HOME and variable value as <installation dir>.
- 6. Click OK on all open windows.
- 7. Reopen the command prompt window.

Linux and OS X

Add the command below to the $\tilde{\ }$.bash_profile file (Linux) or the $\tilde{\ }$ /.profile file ($OS\ X$):

```
export MICROTESK_HOME=<installation dir>
```

To start editing the file, type vi ~/.bash_profile (or vi ~/.profile). Changes will be applied after restarting the command-line terminal or reboot. You can also run the command in your command-line terminal to make temporary changes.

2.2.2 Installing Constraint Solvers

To generate test data based on constraints, MicroTESK requires external constraint solvers. The current version supports the Z3 and CVC4 constraint solvers. Constraint executables should be downloaded and placed to the <installation dir>/tools directory.

Using Environment Variables

If solvers are already installed in another directory, to let MicroTESK find them, the following environment variables can be used: Z3_PATH and CVC4_PATH. They specify the paths to the Z3 and CVC4 excutables correspondingly.

Installing Z3

- Windows users should download Z3 (32 or 64-bit version) from the following page:http://z3.codeplex.com/releases and unpack the archive to the <installation dir>/tools/z3/windows directory. Note: the executable file path is <windows>/z3/bin/z3.exe.
- *UNIX* and *Linux* users should use one of the links below and and unpack the archive to the <installation dir>/tools/z3/unix directory. Note: the executable file path is <unix>/z3/bin/z3.

Debian x64	http://z3.codeplex.com/releases/view/101916
Ubuntu x86	http://z3.codeplex.com/releases/view/101913
Ubuntu x64	http://z3.codeplex.com/releases/view/101911
FreeBSD x64	http://z3.codeplex.com/releases/view/101907

• OS X users should download Z3 from http://z3.codeplex.com/releases/view/101918 and unpack the archive to the <installation dir>/z3/osx directory. Note: the executable file path is <osx>/z3/bin/z3.

Installing CVC4

- Windows users should download the latest version of CVC4 binary from http://cvc4.cs.nyu.edu/builds/win32-opt/ and save it to the <installation dir>/tools/cvc4/windows directory as cvc4.exe.
- Linux users download the latest version of CVC4 binary from http://cvc4.cs.nyu.edu/builds/i386-linux-opt/unstable/ (32-bit version) or http://cvc4.cs.nyu.edu/builds/x86_64-linux-opt/unstable/ (64-bit version) and save it to the <installation dir>/tools/cvc4/unix directory as cvc4.
- OS X users should download the latest version of CVC4 distribution package from http://cvc4.cs.nyu.edu/builds/macos/ and install it. The CVC4 binary should be copied to <installation dir>/tools/cvc4/osx as cvc4 or linked to this file name via a symbolic link.

2.3 Installation Directory Structure

The MicroTESK installation directory contains the following subdirectories:

arch	Microprocessor specifications and test templates		
bin	Scripts to run modeling and test generation tasks		
\mathbf{doc}	c Documentation		
etc	tc Configuration files		
gen	Generated code of microprocessor models		
lib	ib JAR files and Ruby scripts to perform modeling and		
	test generation tasks		
src	Source code of MicroTESK		

2.4 Running

To generate a Java model of a microprocessor from its nML specification, a user needs to run the compile.sh script (Unix, Linux, OS X) or the compile.bat script (Windows). For example, the following command generates a model for the miniMIPS specification:

sh bin/compile.sh arch/minimips/model/minimips.nml

NOTE: Models for all demo specifications are already built and included in the MicroTESK distribution package. So a user can start working with MicroTESK from generating test programs for these models.

To generate a test program, a user needs to use the generate.sh script (Unix, Linux, OS X) or the generate.bat script (Windows). The scripts require the following parameters:

- model name;
- test template file;
- target test program source code file.

For example, the command below runs the euclid.rb test template for the miniMIPS model generated by the command from the previous example and saves the generated test program to an assembler file. The file name is based on values of the -code-file-prefix and -code-file-extension options.

```
sh bin/generate.sh minimips arch/minimips/templates/euclid.rb
```

To specify whether Z3 or CVC4 should be used to solve constraints, a user needs to specify the -s or -solver command-line option as z3 or cvc4 respectively. By default, Z3 will be used. Here is an example:

```
sh bin/generate.sh -s cvc4 minimips arch/minimips/templates/constraint.rb
```

More information on command-line options can be found on the Command-Line Options section.

2.5 Command-Line Options

MicroTESK works in two modes: specification translation and test generation, which are enabled with the -translate (used by default) and -generate keys correspondingly. In addition, the -help key prints information on the command-line format.

The -translate and -generate keys are inserted into the command-line by compile.sh/compile.bat and generate.sh/generate.bat scripts correspondingly. Other options should be specified explicitly to customize the behavior of MicroTESK. Here is the list of options:

Full name	Short	Description	Requires
	name		_
-help	-h	Shows help message	
-verbose	-V	Enables printing diagnostic	
		messages	
-translate	-t	Translates formal specifica-	
		tions	
-generate	-g	Generates test programs	
-output-dir <arg></arg>	-od	Sets where to place gener-	
		ated files	
-include <arg></arg>	-i	Sets include files directories	-translate
-extension-dir <arg></arg>	-ed	Sets directory that stores	-translate
		user-defined Java code	
-random-seed <arg></arg>	-rs	Sets seed for randomizer	-generate
-solver <arg></arg>	-S	Sets constraint solver engine	-generate
		to be used	
-branch-exec-limit	-bel	Sets the limit on control	-generate
<arg></arg>		transfers to detect endless	
		loops	
-solver-debug	-sd	Enables debug mode for	-generate
		SMT solvers	
-tarmac-log	-tl	Saves simulator log in Tar-	-generate
		mac format	
-self-checks	-sc	Inserts self-checking code	-generate
		into test programs	
-arch-dirs <arg></arg>	-ad	Home directories for tested	-generate
		architectures	
-rate-limit <arg></arg>	-rl	Generation rate limit,	-generate
		causes error when broken	
-code-file-extension	-cfe	The output file extension	-generate
<arg></arg>			

-code-file-prefix	-cfp	The output file prefix (file	-generate
<arg></arg>		names are as follows pre-	
		fix_xxxx.ext, where xxxx is	
		a 4-digit decimal number)	
-data-file-extension	-dfe	The data file extension	-generate
<arg></arg>			
-data-file-prefix	-dfp	The data file prefix	-generate
<arg></arg>			
-exception-file-prefix	-efp	The exception handler file	-generate
<arg></arg>		prefix	
-program-length-limit	-pll	The maximum number of	-generate
<arg></arg>		instructions in output pro-	
		grams	
-trace-length-limit	-tll	The maximum length of	-generate
<arg></arg>		execution traces of output	
		programs	
-comments-enabled	-ce	Enables printing comments;	-generate
		if not specified no comments	
		are printed	
-comments-debug	-cd	Enables printing detailed	-generate
		comments; must be used	
		together with –comments-	
		enabled	

2.6 Settings File

Default values of options are stored in the <MICROTESK_HOME>/etc/settings.xml configururation file that has the following format:

```
<?xml version="1.0" encoding="utf-8"?>
<settings>
 <setting name="random-seed" value="0"/>
 <setting name="branch-exec-limit" value="1000"/>
 <setting name="code-file-extension" value="asm"/>
 <setting name="code-file-prefix" value="test"/>
 <setting name="data-file-extension" value="dat"/>
 <setting name="data-file-prefix" value="test"/>
 <setting name="exception-file-prefix" value="test_except"/>
 <setting name="program-length-limit" value="1000"/>
 <setting name="trace-length-limit" value="1000"/>
 <setting name="comments-enabled" value=""/>
 <setting name="comments-debug" value=""/>
 <setting
   name="arch-dirs"
   value="cpu=arch/demo/cpu/settings.xml:minimips=arch/minimips/settings.xml"
</settings>
```

Test Templates

3.1 Introduction

MicroTESK generates test programs on the basis of *test templates* that describe test programs to be generated in an abstract way. Test templates are created using special Ruby-based test template description language. The language is implemented as a library that includes provides facilities for describing test cases.

MicroTESK uses the JRuby interpreter to process test templates. This allows Ruby libraries to interact with other components of MicroTESK written in Java.

Test templates are processed in two stages:

- 1. Ruby code is executed to build the internal representation (a hierarchy of Java objects) of the test template.
- 2. The internal representation is processed with various engines to generate test cases which are then simulated on the reference model and printed to files.

This chapter describes facilities of the test template description language and supported test generation engines.

3.2 Test Template Structure

A test template is implemented as a class inherited from the Template library class that provides access to all features of the library. Information on the location of the Template class is stored in the TEMPLATE environment variable. Thus, the definition of a test template class looks like this:

```
require ENV['TEMPLATE']
class MyTemplate < Template</pre>
```

Test template classes should contain implementations of the following methods:

- 1. initialize (optional) specifies settings for the given test template;
- 2. pre (optional) specifies the initialization code for test programs;

- 3. post (optional) specifies the finalization code for test programs;
- 4. run specifies the main code of test programs (test cases).

The definitions of optional methods can be skipped. In this case, the default implementations provided by the parent class will be used. The default implementation of the initialize method initializes the settings with default values. The default implementations of the pre and post methods do nothing.

The full interface of a test template looks as follows:

```
require ENV['TEMPLATE']

class MyTemplate < Template

def initialize
    super
    # Initialize settings here
end

def pre
    # Place your initialization code here
end

def post
    # Place your finalization code here
end

def run
    # Place your test problem description here
end

end</pre>
```

3.3 Reusing Test Templates

It is possible to reuse code of existing test templates in other test templates. To do this, you need to subclass the template you want to reuse instead of the Template class. For example, the MyTemplate class below reuses code from the MyPrepost class that provides initialization and finalization code for similar test templates.

```
require ENV['TEMPLATE']
require_relative 'MyPrepost'

class MyTemplate < MyPrepost

def run
    ...
end
end</pre>
```

Another way to reuse code is creating code libraries with methods that can be called by test templates. A code library is defined as a Ruby module file and has the following structure:

```
module MyLibrary

def method1
   ...
  end

def method2(arg1, arg2)
   ...
  end

def method3(arg1, arg2, arg3)
   ...
  end

end
```

To be able to use utility methods method1, method2 and method3 in a test template, the MyLibrary module must be included in that test template as a mixin. Once this is done, all methods of the library are available in the test template. Here is an example:

```
require ENV['TEMPLATE']
require_relative 'my_library'

class MyTemplate < Template
  include MyLibrary

def run
  method1
  method2 arg1, arg2
  method3 arg1, arg2, arg3
  end

end</pre>
```

3.4 Test Template Settings

Test templates use the following settings that set up the format of generated test programs:

- sl_comment_starts_with starting characters for single-line comments;
- ml_comment_starts_with starting characters for multi-line comments;
- ml_comment_ends_with terminating characters for multi-line comments;
- indent_token indentation token;
- separator_token token used in separator lines.

Here is how these settings are initialized with default values in the Template class:

```
@sl_comment_starts_with = "//"
@ml_comment_starts_with = "/*"
@ml_comment_ends_with = "*/"

@indent_token = "\t"
@separator_token = "="
```

The settings can be overridden in the initialize method of a test template. For example:

```
class MyTemplate < Template

def initialize
    super

    @sl_comment_starts_with = ";"
    @ml_comment_starts_with = "/="
    @ml_comment_ends_with = "=/"

    @indent_token = " "
    @separator_token = "*"
    end
    ...
end</pre>
```

3.5 Text Printing

The test template description language provides facilities for printing text messages. Text messages are printed either into the generated source code or into the simulator log. Here is the list of functions that print text:

- newline adds the new line character into the test program;
- text(format, *args) adds text into the test program;
- trace(format, *args) prints text into the simulator execution log;
- comment(format, *args) adds a comment into the test program;
- start_comment starts a multi-line comment;
- end_comment ends a multi-line comment.

Formatted Printing

Functions text, trace and comment print formatted text. They take a format string and a variable list of arguments that provide data to be printed.

Supported argument types:

- constants;
- locations.

To specify locations to be printed (registers, memory), the location(name, index) function should be used. It takes the name of the memory array and the index of the selected element.

Supported format characters:

- d decimal format;
- x or X hexadecimal format (lowercase or uppercase letters);
- s decimal format for constants and binary format for locations.

For example, the code below prints the OxDEADBEEF value as a constant and as a value stored in a register using different format characters:

```
prepare reg(1), OxDEADBEEF
reg1 = location('GPR', 1)
text 'Constants: dec=%d, hex=0x%X, str=%s', OxDEADBEEF, OxDEADBEEF
text 'Locations: dec=%d, hex=0x%X, str=%s', reg1, reg1, reg1
```

Here is how it will be printed:

3.6 Random Distributions

Many tasks involve selection based on *random distribution*. The test template language includes constructs to describe ranges of possible values and their weights. To accomplish this task, the following functions are provided:

- range(attrs) creates a range of values and its weight, which are described by the :value and :bias attribures. Values can be one of the following types:
 - Single value;
 - Range of values;
 - Array of values;
 - Distribution of values.

The :bias attribute can be skipped which means default weight. Default weight is used to describe an even distribution based on ranges with equal weights.

• dist(*ranges) - creates a random distribution from a collection of ranges.

The code below illustrates how to create weighted distributions for integer numbers:

Distributions are used in a number of test template features that will be described further in this chapter.

3.7 Instruction Calls

The pre, post and run methods of a test template contain descriptions of instruction call sequences. Instructions are operations defined in ISA specifications which represent target assembler instructions. Operations can have arguments of three kinds:

- immediate value;
- addressing mode;
- operation.

Addressing modes encapsulate logic of reading or writing values to memory resources. For example, an addressing mode can refer to a register, a memory location or hold an immediate value. Operations are used to describe complex instructions that are composed of several operations (e.g. VLIW instructions). What arguments are suitable for specific instructions is specified in ISA specifications.

Arguments are passed to instructions and addressing modes in two ways:

- As arrays. This format is based on methods with a variable number of arguments. Values are expected to come in the same order as corresponding parameter definitions in specifications.
- As hash maps. This format implies that operations and addressing modes are parameterized with hash tables where the key is in the name of the parameter and the value is the value to be assigned to this parameter.

The first way is more preferable as it is simpler and closer to the assembly code syntax. The code below demonstrates both ways (miniMIPS):

```
# Arrays
add reg(11), reg(9), reg(0)
# Hash maps
add :rd=>reg(:i=>11), :rs=>reg(:i=>9), :rt=>reg(:i=>0)
```

3.7.1 Aliases

Sometimes it is required to define *aliases* for addressing modes or operations invoked with certain arguments. This is needed to make a test template more human-readable. This can be done by defining in a test template Ruby functions that create instances with specific arguments. For example, the following code makes it possible to address registers reg(0) and reg(1) as zero and at:

```
def zero
    reg(0)
end

def at
    reg(1)
end
```

3.7.2 Pseudo Instructions

It is possible to specifify *pseudo instructions* that do not have correspondent operation in specifications. Such instructions print user-specified text and do not change the state of the reference model. The can be described using the following function: pseudo(text). For example:

```
pseudo 'syscall'
```

3.7.3 Groups

Addressing modes and operations can be organized into *groups*. Groups are used when it is required to randomly select an addressing mode or an operation from the specified set.

Groups can be defined in specifications or in test templates. To define them in test templates, the following functions are used:

- define_mode_group(name, distribution) defines an addressing mode group;
- define_op_group(name, distribution) defined an operation group.

Both function take the name and distribution arguments that specify the group name and the distribution used to select its items. *Note*: it is not allowed to redefine existing groups.

For example, the code below creates an instruction group called alu that contains instructions add, sub, and, or, nor, and xor selected randomly according to the specified distribution. More information on distributions is in the Random Distribution section.

```
define_op_group('alu', alu_dist)
```

The following code specifies three calls that use instructions randomly selected from the alu group:

```
alu t0, t1, t2
alu t3, t4, t5
alu t6, t7, t8
```

3.8 Data

3.8.1 Configuration

Defining data requires the use of assembler-specific directives. Information on these directives is not included in ISA specifications and should be provided in test templates. It includes textual format of data directives and mappings between nML and assembler data types used by these directives. Configuration information on data directives is specified in the data_config block, which is usually placed in the pre method. Only one such block per a test template is allowed. Here is an example:

```
data_config(:text => '.data', :target => 'M') {
  define_type :id => :byte, :text => '.byte', :type => type('card', 8)
  define_type :id => :half, :text => '.half', :type => type('card', 16)
  define_type :id => :word, :text => '.word', :type => type('card', 32)

define_space :id => :space, :text => '.space', :fillWith => 0
  define_ascii_string :id => :ascii, :text => '.ascii', :zeroTerm => false
  define_ascii_string :id => :asciiz, :text => '.asciiz', :zeroTerm => true
}
```

The block takes the following parameters:

- text (compulsory) specifies the keyword that marks the beginning of the data section in the generated test program;
- target (compulsory) specifies the memory array defined in the nML specification to which data will be placed during simulation;
- base_virtual_address (optional) specifies the base virtual address where data allocation starts. Default value is 0;
- item_size (optional) specifies the size of a memory location unit pointed by address. Default value is 8 bits (or 1 byte).

To set up particular directives, the language provides special methods that must be called inside the block. All the methods share two common parameters: id and text. The first specifies the keyword to be used in a test template to address the directive and the second specifies how it will be printed in the test program. The current version of MicroTESK provides the following methods:

- 1. define_type defines a directive to allocate memory for a data element of an nML data type specified by the type parameter;
- 2. define_space defines a directive to allocate memory (one or more addressable locations) filled with a default value specified by the fillWith parameter;
- define_ascii_string defines a directive to allocate memory for an ASCII string terminated or not terminated with zero depending on the zeroTerm parameter.

The above example defines the directives byte, half, word, ascii (non-zero terminated string) and asciiz (zero terminated string) that place data in the memory array M (specified in nML using the mem keyword). The size of an addressable memory location is 1 byte.

3.8.2 Definitions

Data are defined using the data construct. Data definitions can be added to the test program source code file or placed into a separate source code file. There are two types of data definitions:

- Global defined in the beginning of a test template and can be used by all test cases generated by the test template. Global data definitions can be placed in the root of the pre or run methods or methods called from these methods. Memory allocation is performed during inital processing of a test template (see stage 1 of template processing).
- **Test case level** defined and used by specific test cases. Such definitions can be applied multiple times (e.g. when defined in preparators). Memory allocation is performed when a test case is generated (see stage 2 of template processing).

The data construct has two optional parameters:

- global a boolean value that states that the data definition should be treated as global regardless of where it is defined.
- separate_file a boolean value that states that the generated data definitions should be placed into a separate source code file.

Here is the list of methods that can be used in data sections:

- align
- org
- space

Here is an example:

```
data {
  org 0x00001000

label :data1
  byte 1, 2, 3, 4

label :data2
  half 0xDEAD, 0xBEEF

label :data3
  word 0xDEADBEEF

label :hello
  ascii 'Hello'

label :world
  asciiz 'World'

space 6
}
```

In this example, data is placed into memory. Data items are aligned by their size (1 byte, 2 bytes, 4 bytes). Strings are allocated at the byte border (addressable unit). For simplicity, in the current version of MicroTESK, memory is allocated starting from the address 0 (in the memory array of the executable model).

3.9 Preparators

Test Engine Branch

4.1 Parameters

- branch_exec_limit is an upper bound for the number of executions of a single branch instruction;
- trace_count_limit is an upper bound for the number of execution traces to be returned.

More information on the parameters is given in the "Execution Traces Enumeration" section.

4.2 Description

Functioning of the *branch* test engine includes the following steps:

- 1. construction of a branch structure of an abstract test sequence;
- 2. enumeration of execution traces of the branch structure;
- 3. concretization of the test sequence for each execution trace:
 - (a) construction of a *control* code;
 - (b) construction of an *initialization* code.

Let D be the size of the delay slot for an architecture under scrutiny (e.g., D=1 for MIPS, and D=0 for ARM).

Appendixes

5.1 References

Bibliography

[1] M. Freericks. *The nML Machine Description Formalism*. Technical Report TR SM-IMP/DIST/08, TU Berlin CS Department, 1993.