

API Documentation

Guide and Best Practices

Revision history

Document version	Revision date	Updated by	Reviewed by	Changes Implemented
1.0.	12 th August, 2018	Sonu Kumar	Yogesh Kumar	Initial APIs details included
1.1.	4 th October, 2020	Miraj Sen Gupta	Rupam Saxena	New APIs details added
2.0.	10 th October, 2023	Sabhyata Gurung and Navya Mahadevi	Manpreet Singh and Prabhat Ranjan	New APIs details added
2.1	8 th July, 2025	Navya Mahadevi	Manpreet Singh	Details on Jio TPS and license_hold scenario included. Update on Modify API JSON
2.2	4 th July, 2026	Navya Mahadevi	Manpreet Singh	Redundant APIs removed. Verified no broken references across doc

Copyright Information

©2026-2027, Telenity, Inc. ("Telenity"), All Rights Reserved. This Telenity document, as well as the software described in it ("Software"), are only furnished under a license agreement and/ or confidentiality agreement and may be used only in full accordance with the terms of such agreements. The content of this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Telenity. Telenity assumes no responsibility or liability for any errors or inaccuracies that may appear in this manual.

No part of this document may be copied, reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Telenity, except as permitted by such license agreement stated above.

In no event shall Telenity, or the authors or the distributors be liable to any party for any damage including but not limited to direct, indirect, special, incidental, or consequential damages arising out of the use of this documentation, or the Software, or any derivatives thereof, even if Telenity, or the authors or the distributors have been advised of the possibility of such damage.

Telenity, the authors and the distributors specifically disclaim any warranties, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement. This document and the Software are provided on an "as is" basis, and Telenity and the authors and distributors have no obligation to provide maintenance, support, updates, enhancements, or modifications.

Canvas and Telenity are registered trademarks of Telenity İletişim Sistemleri A.Ş. All other product or service names mentioned herein are trademarks of their respective owners.

At any time, you may reach Telenity through our Online Customer Support Center (<http://jira.telenity.com>) via which you will be able to submit web-based issues (technical request, question, documentation, enhancement request, and professional services) to let us know any product related issues you may have or product enhancement requests. To report an Issue, please go to our Online Customer Support Center and complete all the required information on the form. All received issues are reviewed, prioritized as they are received and are responded back to you in a timely manner.

All incoming customer inquiries will be given an Issue id by our Customer Support Center. All follow ups regarding the submitted incidents should go through the Telenity Customer Support Center and include the issue id whenever possible. Below, please find the contact information for Telenity's worldwide Customer` Support Center.

Below, please find the contact information for Telenity India office location.

APAC Headquarters
 1st Floor, A-17, Sector-4,
 Noida, Uttar Pradesh,
 India
 Pin Code: 201301
 Phone: +91 (120) 4311157 /58 /62 /69

Below, please find the contact information for Telenity's office locations.

Corporate Headquarters Telenity Incorporated 755 Main Street, Building 7 Monroe, CT 06468, USA Phone: +1 203 445 2000 Fax: +1 203 268 1860	EMEA Headquarters Telenity Europe AHL Serbest Bolgesi, Plaza No. 501 Yesilkoy 34149, Istanbul, Turkey Phone: +90 212 468 2100 Fax: +90 212 465 0910
APAC Headquarters 2nd Floor, Mindmill Corporate Tower 24 A, Film City, Sector 16A Noida, Uttar Pradesh 201301	Telenity MEA Dubai Internet City Building1, Ground Floor, FS- Office#4 POBox 73030 Dubai-UAE Phone: +971 4 4298734

Contents

Contents

Overview	6
Scope of Document	6
Audience	6
Acronyms	6
Introduction	7
Smart Trail API Service Flow.....	7
1. Tenant Creation.....	7
2. API Key Generation	7
3. Using API Key & Resource Addition	7
4. Smart Trail API's Offering.....	8
4.1 Authentication API.....	9
4.1.1 Requests:.....	9
4.1.2 Responses:	9
4.2 Import API	10
4.2.1 Requests:.....	10
4.2.2 Parameters:	11
4.2.3 Responses:	11
4.3 Entity Search API.....	11
4.3.1. Requests:.....	12
4.3.2 Parameters:	12
4.3.3 Responses:	12
4.4 Consent API	13
4.4.1 Consent Auth API Request.....	13
4.4.1 (i) Requests:	13
4.4.1 (ii) Responses:	14
4.4.2 Consent Check API	14
4.4.2 (i) Requests:	14
4.4.2 (ii) Parameters:.....	15
4.4.2 (iii) Responses:	15
4.5 Location API.....	16
4.5.1 Requests:.....	17
4.5.2 Parameters:	17

4.5.3	Responses:	18
4.5.4	Response Error Codes Description:.....	19
4.6	Delete API.....	19
4.6.1	Requests:.....	20
4.6.2	Parameters:	20
4.6.3	Responses:	20
4.7	License check API	21
4.7.1	Requests:.....	21
4.7.2	Parameters:	21
4.7.3	Responses:	22
4.8	Bulk Location API	22
4.8.1	Requests:.....	23
4.8.2	Parameters:	23
4.8.3	Responses:	24
4.9	Modify API	25
4.9.1	Requests:.....	25
4.9.2	Parameters:	26
4.9.3	Responses:	26
4.10	Jio Consent Re- Initiate API.....	27
4.10.1	Requests:.....	27
4.10.2	Parameters:	28
4.10.3	Responses:	28
4.11	General HTTP Response Codes	29

Overview

The purpose of this document is to provide an overview of the features of Telenity Smarttrail API's. This serves as a guide to develop business applications, that need this API for Sim Based Location tracking.

Scope of Document

The purpose of this document is to provide an overview of the features of Smart trail API's. This serves as a guide to develop business applications, that need this API for Location tracking and Cell base tracking.

Audience

The audience of the document shall be the users of the API provided by the Telenity Smarttrail APIs for the enterprise customers to have a complete end-to-end solution for tracking the live status of numbers.

Acronyms

Acronym	Description
API	Application Programming Interface
TPA	Third Party Application

Introduction

This solution provides service to enterprises having mobile devices that are connected to one of several mobile operator networks (Airtel, V! and JIO) in a transparent manner without having to worry about which network the mobile device is connected to.

Telenity's SmartTrail API Service is deployed on Cloud Infrastructure on Telenity's SmartTrail product. Telenity's Smart Trail product is a member of the Canvas® enterprise location-based service portfolio. It is a powerful location-based employee, resource and vehicle tracking application that runs with network provided location information to help SMEs and enterprises to achieve efficiency in managing resources in the field. Telenity's SmartTrail Service offers customer **APIs**.

Telenity's SmartTrail Service provides **Application Protocol Interfaces (APIs)** It is an innovative solution for enterprise business to offer Telenity's Smart Trail Service to provide flexibility. Also, through these APIs it can send consent SMS, check consent status and locate number's location on a real time basis. Enterprise's 3rd Party Applications (TPAs) need to integrate these APIs with their application to avail this service.

Smart Trail API Service Flow

To utilize Telenity's Smart Trail API Service, customer must integrate Telenity's APIs with their system.

Once APIs are integrated then detailed service flow will be as mentioned below

1. Tenant Creation

Telenity Admin creates a customer account, details like tenant name, description, license, contact details etc. to be provided by customer account Manager.

2. API Key Generation

Customer's application will call Authentication API to get auth token using account credential shared by Telenity. Once Authentication API request is received, Telenity will authenticate it, generate Auth key and send Auth key in API response.

3. Using API Key & Resource Addition

The customer's application will call Import-API (using Auth key) to provision resource. information (driver's mobile numbers and details) into Telenity's Smart Trail system.

This API will add resource information like Mobile number, First name and Last name.

When Import API request gets received at Telenity's Smart Trail system, application will add the resource details (Mobile number, First name and Last name) into SmartTrail's database.

- a. After addition of resource details, Telenity application also triggers the location consent SMS to resource's mobile number.
- b. Once resource gives reply 'Y' to short code on SMS or Presses '1' After Calling IVR number, (Only consent SMS mode is available in case of JIO), immediately Telenity application start location tracking of mobile number in backend. Based on the current location of mobile number, application start checking the current lat-long of mobile.

4. Smart Trail API's Offering

Telenity's Smart Trail API Service offers to enterprise customers by which they can have full access of provisioning mobile numbers of resources in their account, send consent SMS to mobile numbers, check consent status and can check the updated location through **APIs**.

This service provides below APIs:

1. Authentication API
2. Import API
3. Entity Search API
4. Consent API
5. Location API
6. Delete API
7. Modify API
8. License check API
9. Bulk Location API
10. Jio Consent Re-Initiate API

4.1 Authentication API

To authenticate API requests, a token needs to be passed. For this purpose, Authentication-API is used for generating a token.

Third party applications (TPA) need to call Authentication-API to generate token by passing authentication key. This token value needs to be used in Import-API and Location-API, Deleted-API. **(This Token is valid for 6 hours. TPA needs to re-generate a new Token in case Auth API returns error code 401 Unauthorized)**

4.1.1 Requests:

API Description	This API provides User the ability to generate access token
HTTP Method	GET
Payload Schema	N/A
Headers	Content -Type: application/json
	Host: smarttrail.telenity.com
	Token: {{Token}}
URI	https://smarttrail.telenity.com/trail-rest/login

4.1.2 Responses:

Status Code	Description	Response
200	Success Response	{ "username": "Customer", "userRole": "Customer_TRACKER_ADMIN", "token": "f*****" }
401	Failure Response	{ "errorCode": 19840201, "explanation": "Username and/or password is invalid.", "customExplanation": "Username and/or password is invalid." }

4.2 Import API

Import-API allows third party applications (TPA) to add/provision the driver's MSISDN, First Name and Last Name by calling Import-API from customer's application. It also triggers an SMS to mobile number which is known as 'location consent SMS'.

To enable location of any mobile number, resource must reply with Y on SMS as his consent or Call IVR number and press '1' (Only consent SMS mode is available in case of JIO).

Import API response will provide you with the additional attributes (isTracked, entityID) while adding a number.

isTracked:- It defines the tracking status of the number as true (or) false.

"isTracked" flag will be set according to the consent status of that particular number you import.

If the consent API response shows as "allowed"(for non-Jio numbers) and "consent_approved"(for Jio numbers), the "isTracked" flag in Import API response will be set as 'true'; else it will set as 'false' after adding the number.

If "isTracked" flag in Import API response is false, it indicates that the consent is not received for the added number due to which Consent API response is PENDING. Once the consent gets 'ALLOWED' after taking the consent, you need to change the "isTracked" parameter as 'true' for that number using Modify Entity API.

entityID: Earlier you needed to call the Entity Search API to get the "entityID" for any number. But now you can get "entityID" in the Import API response as well upon adding the number.

Note: TPA needs to pass token value (which was generated through Authentication-API) in Import-API to authenticate this API at Telenity SmartTrail application.

Resource import API is accessible via a REST API by the following:

4.2.1 Requests:

API Description	used to add the number as well as trigger the SMS consent to the numbers
HTTP Method	POST
Payload Schema	<pre> { "entityImportList": [{ "firstName": "user", </pre>

	<pre> "lastName": "user", "msisdn": "91*****" }] } </pre>
Headers	Content -Type: application/json
	Host: smarttrail.telenity.com
	Token: {{Token}}
URI	https://smarttrail.telenity.com/trail-rest/entities/import

4.2.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
firstName	Body parameter	string	Y	Test
lastName	Body parameter	string	Y	User
Msisdn	Body parameter	integer	Y	91*****

***Please note that special characters (e.g ,!@#\$\$%^&*()) should not be included in request parameters, data, or any part of your API requests.

4.2.3 Responses:

Status Code	Description	Response
200	Success Response	<pre> { "successList": [{ "firstName": "user", "lastName": "user", "msisdn": "91*****", "isTracked": true, "entityId": 22401979 }], "failureList": [] } </pre>
500	Failure Response	<pre> { "errorMessage": "invalid msisdn: 91****" } </pre>

4.3 Entity Search API

This API of Smart Trail provides TPA to have all the details of a numbers present in the account. *Note: TPA needs to pass token value (which was generated through Authentication-API) in Entity Search-API to authenticate this API at Telenity application.*

4.3.1. Requests:

API Description	Gives the overall details of the given msisdn
HTTP Method	GET
Payload Schema	N/A
Headers	Content -Type: application/json
	Host: smarttrail.telenity.com
	Token: {{Token}}
URI	https://smarttrail.telenity.com/trail-rest/entities?search=91*****

4.3.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
search	URI parameter	integer	Y	91*****

***Please note that special characters (e.g., !@#\$%^&*()) should not be included in request parameters, data, or any part of your API requests.

4.3.3 Responses:

Status Code	Description	Response
200	Success Response	<pre>{ "limit": 5, "offset": 0, "total": 1, "data": [{ "id": 17282343, "name": "Test User", "operator": "unknown", "msisdn": "91*****", "active": true, "suspended": false, "charged": false, "tracked": true, "customerName": "test company", "consentStatus": "ACTIVE" }] }</pre>

4.4 Consent API

After addition of resource details, Telenity application triggers the location consent SMS to subscriber's mobile number.

The Consent API allows an MSISDN to be queried to get user consent over SMS/IVR, which enables TPA to get consent of a subscriber.

We always recommend to rely on Consent API for retrieving real-time and accurate consent status for your numbers (not the Entity Search API).

IVR Consent process:

- Applicable on Airtel, Vi & Bsnl operators only
- The driver needs to call the IVR number. A voice prompt in Hindi language would be heard; driver needs to give his consent by pressing 1. Consent will get registered in the system in 15 minutes.
- IVR consent works as an advanced Consent model also wherein, driver can call & press 1. And once trip gets created, our system will map received consent with number to allow tracking thus on IVR, no need to wait to receive Consent SMS

JIO Consent process:

- Reliance Jio numbers consent is applicable on SMS and Missed call number.
- Once the number has been added/imported on service by the client, consent SMS will be initiated to driver mobile number from short code 51712032 wherein driver needs to reply to Y to register his consent.
- OR driver may open URL web link on SMS to approve his consent.
- Any one method can be opted to register consent.

TPA needs to generate authentication bearer token before calling the consent API, using Consent Auth API.

4.4.1 Consent Auth API Request

To authenticate API requests, a token needs to be passed. For this purpose, Consent Authentication-API is used for generating a token.

Third party applications (TPA) need to call Authentication-API to generate token by passing authentication key. This token value needs to be used in Consent API, Jio Consent Validity Check API and Jio Consent Re-Initiate API (*This Token is valid for 1 hour. TPA needs to re-generate a new Token in case Auth API returns error code 401 Unauthorized*)

4.4.1 (i) Requests:

API Description	This API provides user the ability to generate the Bearer token which is used in Consent API calling
------------------------	--

HTTP Method	POST
Payload Schema	N/A
Headers	Content-Type: application/json
	Accept: */*
	Host: india-agw.telenity.com
	Authorization: Basic {{Token}} (which would be defined already in the API collection shared)
URI	https://india-agw.telenity.com/oauth/token?grant_type=client_credentials

4.4.1 (ii) Responses:

Status Code	Description	Response
200	Success Response	<code>{"access_token":"8e72feeab2469d*****ce2aa9", "token_type":"BEARER","expires_in":3600}</code>
400	Failure Response	<code>{"error_description":"invalid_request, Bad request content type. Expecting: application/x-www-form-urlencoded","error":"invalid_request"}</code>

Note: TPA needs to pass this Bearer token (which is valid for 60min/ 1 Hour) on Consent API to get the consent status of the subscriber.

4.4.2 Consent Check API

This API allows the TPA to check the consent of the subscriber. *TPA needs to pass token value (which was generated through Consent Authentication-API) in Consent-API to authenticate this API at Telenity application and the Bearer token validity is 1 Hour.*

4.4.2 (i) Requests:

API Description	This API retrieves the consent status of the subscriber
HTTP Method	GET

Payload Schema	N/A
Headers	Content-Type: application/json
	Cache-Control: no-cache
	Accept: */*
	Host: india-agw.telenity.com
	Authorization: Bearer {{Token}} (which is generated using Consent Auth API)
URI	<u>https://india-agw.telenity.com/apigw/NOFBconsent/v1/NOFBconsent?address=tel:+91*****</u>

4.4.2 (ii) Parameters:

Field	Field type	Data type	Is Mandatory	Description
address	URI parameter	integer	Y	=tel:+91*****

***Please note that special characters (e.g., !@#%&^*()) should not be included in request parameters, data, or any part of your API requests.

4.4.2 (iii) Responses:

Status Code	Description	Response
200	Consent status ALLOWED for the subscriber.	{"Consent":{"status":"ALLOWED"}}
200	Consent status PENDING for the subscriber.	{"Consent":{"status":"PENDING"}}
400	Consent status reflecting as "Invalid Msisdn" as the number passed in the API calling is Invalid.	{"errorCode": 8001001, "errorDescription": "Invalid Msisdn"}
200	Consent Received But Tracking is not enabled	{ "Consent": { "status": "consent_approved", "registeredDate": "2024-04-05 16:17:36", "consentExpiresOn": "2024-10-02 16:17:36", "trackingStart": "2024-05-07 16:16:55", "trackingPause": "2024-05-10 09:23:42", "message": "" } }

200	When Device tracking is stopped within 24 hours, Licenses will be kept on hold until 24 hours is completed. License will be released automatically after 24 hours of last activation time.	<pre> { "Consent": { "status": "license_hold", "2024-04-05 16:17:36", "consentExpiresOn": "2024-10-02 16:17:36", "trackingStart": "2024-05-07 16:16:55", "trackingPause": "2024-05-10 09:23:42", "message": "" } } </pre>
200	Provides the message info if there is any TPS error incase of Jio numbers	<pre> {"errorCode":8001001 ,"errorDescription":"exceeded the maximum request limit"} </pre>

Additional attributes description for Jio numbers consent status:

registeredDate	Date of the number registered on Jio platform
consentExpiresOn	Date of consent expiry as of 180 days logic
trackingStart	Date & time of tracking initiated for the Jio number
trackingPause	Date & time of tracking paused/disabled for the Jio number
message	Provides the message info if there is any TPS error

4.5 Location API

To retrieve the location of driver's number, TPA needs to ping this location API by passing driver's mobile number as a variable and store the location data in their system which can be used as per their requirement.

If the consent status is 'ALLOWED' and the tracking status is 'true', clients will be able to retrieve the first location trace within 2 to 3 minutes for their resources. Post that, location traces would be retrieved as per the tracking frequency set for their SmartTrail API account.

Note: TPA needs to pass token value (which was generated through Authentication-API) in Location-API to authenticate this API at Telenity SmartTrail application.

4.5.1 Requests:

API Description	This API helps to retrieve the location details of the subscriber
HTTP Method	GET
Payload Schema	N/A
Headers	Content -Type: application/json
	Host: smarttrail.telenity.com
	Token: {{Token}}
URI	https://smarttrail.telenity.com/trail-rest/location/msisdnList/91*****?lastResult=True

4.5.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
msisdnList	URI parameter	integer	Y	91*****
lastResult	URI parameter	string	Y	True

***Please note that special characters (e.g., !@#\$%^&*()) should not be included in request parameters, data, or any part of your API requests.

4.5.3 Responses:

Status Code	Description	Response
200	Location API response depicting a subscriber's location capture	<pre>{ "terminalLocation": [{ "address": "tel:+91*****", "locationRetrievalStatus": "Retrieved", "currentLocation": { "latitude": 12.383911, "longitude": 77.0478, "timestamp": "2024-06-02 16:59:02.152 +0530", "detailedAddress": "in Malavalli, Mandya, Karnataka" }, "locationResultStatusText": "Success", "locationResultStatus": 0, "entityId": 23006639, "tracked": true }], "errorMessageList": [] }</pre>
200	Location status could not be retrieved as the number itself does not present in the TPA account	<pre>{ "terminalLocation": [], "errorMessageList": ["Not Found MSISDN 91*****"] }</pre>
200	Location could not be retrieved due to generic error	<pre>{ "terminalLocation": [{ "address": "tel:+91*****", "locationRetrievalStatus": "Not Retrieved", "currentLocation": { "timestamp": "2024-05-07 15:49:12.813 +0530" }, "locationResultStatusText": "Location could not be obtained: NETWORK_ERROR", "locationResultStatus": 50, "entityId": 22443073, "tracked": true }], "errorMessageList": [] }</pre>

Note:

- If you set the “lastResult” parameter in Location API URI as ‘false’, it will provide you with the last recorded success location response for that number
- If you set the “lastResult” parameter in Location API URI as ‘true’, it will provide you with the latest updated location response for that number. It could be a network error from the operator end (or) a successfully retrieved location trace

4.5.4 Response Error Codes Description:

Response Error Codes	Description
location_result_status:"Server busy and service unavailable; Please retry the request 26"	Out of Coverage
location_result_status:"48"	Phone switched off
location_result_status:"50"	Generic problem
location_result_status:"5044"	CALL_BARRED
location_result_status:"53"	Address Not Mapped
location_result_status:"6044"	TELESERVICE_NOT_PROVISIONED
location_result_status:"7"	Subscription Not found
location_result_status:"19840102"	Number not added in the account

4.6 Delete API

Delete API of Smart Trail allows to delete numbers of resource through API.

Delete API provides flexibility to enterprises to manage provisioning part for their account.

Numbers of resources from a unified and easy-to-use through APIs as they have privileges to add and delete numbers at any time by maintaining a quota limit of total resources to be tracked for which customer has taken subscription pack for his account. *Note: TPA needs to pass token value (which was generated through Authentication-API) in Delete-API to authenticate this API at Telenity application.*

4.6.1 Requests:

API Description	Delete numbers at any time
HTTP Method	POST
Payload Schema	{"msisdnList": ["91*****"]}
Headers	Content -Type: application/json
	Host: smarttrail.telenity.com
	x-access-token: enter token here
URI	https://smarttrail.telenity.com/trail-rest/tracking/remove

4.6.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
msisdnList	Body parameter	integer	Y	91*****

****Please note that special characters (e.g., !@#%&*()) should not be included in request parameters, data, or any part of your API requests.*

4.6.3 Responses:

Status Code	Description	Response
200	Success	{ "status": 200, "success": true, "msisdnSuccessSet": ["91*****"] }
400	Failure Response	{ "status": 400,

		<pre>"success": false, "errorMessage": "couldn't delete resources for any msisdn", "msisdnErrorMessageMap": {} }</pre>
--	--	--

4.7 License check API

License check API allows the TPA to capture the details such as total count of license, total count of occupied numbers, utilized license count and the left license count.

****TPA needs to pass the {Customer-id} or "id" (generated in the Auth API), to retrieve the license details using this License API.**

Note: TPA needs to pass token value (which was generated through Authentication-API) in License check-API to authenticate this API at Telenity application.

4.7.1 Requests:

API Description	This API provides user the ability to retrieve the License Utilization details of their account
HTTP Method	GET
Payload Schema	N/A
Headers	Content -Type: application/json
	Host: smartrail.telenity.com
	Token: {{Token}}
URI	https://smartrail.telenity.com/trail-rest/entities/licence-information/{Customer-id}

4.7.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
{Customer-id} or "id" entry	URI parameter	integer	Y	123

*****Please note that special characters (e.g., !@#%&*()) should not be included in request parameters, data, or any part of your API requests.**

Short description of each field of license API response depicted below for your kind reference,

- Total License: total number of licenses
- Total occupied Number: total count of numbers added in the account.
- utilized License: active and pending tracked numbers.
- Left License: left license count would reflect.

4.7.3 Responses:

Status Code	Description	Response
200	Licence details check API response body depicting the licence utilization of an account	<pre>{ "totalLicence": 100, "totalOccupiedNumber": 5, "utilizedLicence": 5, "leftLicence": 95 }</pre>
404	404 Not Found!	Customer licence information could not be found

4.8 Bulk Location API

With the Bulk Location Api one can get the location report of all the numbers present in the account or the specific number

Note: TPA needs to pass token value (which was generated through Authentication-API) in Bulk Location-API to authenticate this API at Telenity application.

Below are the key highlights to be known on upgraded Bulk Location API.

Change in logic to improve API performance s efficiency:- Earlier this API used to retrieve the location traces for all the MSISDN values present in your SmartTrail API a/c at code level; and then it used to throw the API response as per the limit defined. Now the API retrieves the bulk location traces, based only on the limit value defined. As a result of this, API response time is also improvised.

Validation on 'limit' and 'offset' value:- The 'offset' C 'limit' value in API URI are now validated. You'll have to define them in URI for retrieving the bulk location traces.

Max s Min range value of 'limit':- The max and min value of 'limit' is 200 and 1 respectively.

i.e., Standardized max limit value defined to fetch the bulk location traces is 200 in one API call. If you try to pass the 'limit' value less than 1 and greater than 200, you'd receive the error message.

4.8.1 Requests:

API Description	Bulk Location history of the multiple numbers
HTTP Method	GET
Payload Schema	N/A
Headers	Content -Type: application/json
	Host: smarttrail.telenity.com
	Token: {{Token}}
URI	https://smarttrail.telenity.com/trail-rest/location/msisdnList/?limit=200&offset=0&lastResult=true

4.8.2 Parameters:

***Please note that special characters (e.g., !@#\$%^&*()) should not be included in request parameters, data, or any part of your API requests.

Field	Field type	Data type	Is Mandatory	Description
lastResult	URI parameter	string	Y	true
tracked	URI parameter	string	N	True/false
limit	URI parameter	integer	Y	100
Offset	URI parameter	integer	Y	0

If you add “tracked” parameter as true, it will show you resources whose tr_entity.tracked (tracked) value is 1.

If you add “tracked” parameter as false, it will show you resources whose tr_entity.tracked (not tracked) value is 0.

It is not obligatory. You don't have to write this parameter. If you do not enter “tracked” parameters, API will work like before; API will show you all the results in JSON response.

4.8.3 Responses:

Status Code	Description	Response
200	Success Response	<pre> { "locationAdditionalInfoList": [{ "terminalLocation": { "address": "tel:+919575*****", "locationRetrievalStatus": "Retrieved", "currentLocation": { "latitude": 18.537018, "longitude": 73.85293, "timestamp": "2023-09-11 12:33:03.182+0530", "detailedAddress": "Shivaji Nagar, Maharashtra" }, "locationResultStatusText": "Success", "locationResultStatus": 0 }, "deviceName": "Arpit", "lastTrackingTime": "12:33:03", "lastTrackingDate": "11-09-2023", "trackingLinkMap": "No active trips.", "tripStatus": "ACTIVE", "averageSpeed": 0.0, "traveledDistance": 0.0 }], }</pre>
404	Failure Response	RESTEASY003210: Could not find resource for full path:

4.9 Modify API

This API Start or pauses the tracking of the numbers.

Note:

- TPA needs to pass token value (which was generated through Authentication-API) in Modify-API to authenticate this API at Telenity application.
- *The entities passed in the parameter is unique and is basically the entity ID which can be obtained by calling entity search API for the given msisdn.*
- *isTracked:true -Tracking is ON for the number and isTracked:false - Tracking is Off for the number.*
- *400 error code Response - Consent date is expired OR/ You can reactivate tracking for this number after 15 Min OR/ Device is already active. (Jio Operator)*
- *429 Error Code Response- You have exceeded the maximum request limit per second. (Jio Operator)*

Note: Client will be able to enable the tracking (isTracked=true) for their numbers via Modify Entity API only if the consent status reflects as 'ALLOWED' for their numbers. If consent is not received and it is reflecting as 'Pending', clients won't be able to enable tracking (isTracked=true) in Modify Entity API. If tried to do so, they will encounter 403 error.

4.9.1 Requests:

API Description	Start and pause the tracking of the number
HTTP Method	PUT
Payload Schema	<pre>{ "isActive": true, "isTracked": true }</pre>
Headers	Content-Type: application/json
	User-Agent: curl/7.50.3
	Cache-Control: no-cache
	Host: smarttrail.telenity.com
	Token: {{Token}}
URI	https://smarttrail.telenity.com/trail-rest/entities/5804409

4.9.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
isActive	Body parameter	string	Y	true
istracked	Body parameter	string	Y	true/false
entities	URI parameter	integer	Y	5804409

***Please note that special characters (e.g., !@#%\$%^&*()) should not be included in request parameters, data, or any part of your API requests.

4.9.3 Responses:

Status Code	Description	Response
200	Success Response	<pre>{ "id": 5804409, "firstName": "user", "lastName": "user", "isActive": true, "isSuspended": false, "isCharged": false, "isTracked": true, "isTrackedTripWise": false, "isDeleted": false, "canChangeGpsTrackingPeriod": false, "gpsPushFailureNotificationThreshold": 0, "isNotified": false, "isOpaque": false, "deleteDate": "", "customerId": 2, "customerName": "test company", "devices": [{ "id": 5804409, "type": "msisdn", "value": "91*****", "operatorId": "unknown", "opaqueId": "MdoFMu73+33vd7vc7iJpwJL4", "subscriptionStatus": 0 }], "groups": [], "properties": [{ "name": "LS0", "text": "LSI" }] }</pre>

401	Failure Response	RESTEASY003210: Could not find resource for full path
403	Failure Response as API didn't enable tracking due to consent pending status	{"errorCode":403,"explanation":"Consent Status is not in allow state","customExplanation":"Consent Status is not in allow state"}

4.10 Jio Consent Re- Initiate API

Jio Consent Re - Initiate API allows TPA to re -initiate the consent SMS to the jio numbers that are pending state or the sms not triggered while importing the number.

Note:

- TPA needs to pass token value (which was generated through Consent Authentication-API) in Jio Consent Re-Initiate API to authenticate this API at Telenity application.
- Jio numbers need to be registered in the jio platform and the consent should be pending to trigger the reinitiate the consent SMS.
- Request to hit this API only when needed because from the operator end numbers get locked for 24 hours when multiple hit received.

4.10.1 Requests:

API Description	Re-initiate the SMS to the pending jio numbers
HTTP Method	GET
Payload Schema	N/A
Headers	Content-Type: application/json
	Cache-Control: no-cache
	User-Agent: curl/7.50.3
	Host: india-agw.telenity.com
	Token: Bearer{{Token}} (which is generated using Consent Auth API)
URI	https://india-agw.telenity.com/apigw/NOFBconsent/v1/JIOReinitiate?address=tel:+919*****

4.10.2 Parameters:

Field	Field type	Data type	Is Mandatory	Description
address	URI parameter	integer	Y	Msisdn with 91*****

***Please note that special characters (e.g., !@\$%^&*()) should not be included in request parameters, data, or any part of your API requests.

4.10.3 Responses:

Status Code	Description	Response
200	Success Response	<i>{"data": "Requested initiated successfully"}</i>
404	Failure Response	<i>{"data": "Number not registered in the Jio platform"}</i>
404	Failure Response	<i>{"data": "Consent received and tracking is not active"}</i>
404	Failure Response	<i>{"data": "Consent received and tracking is active"}</i>

4.11 General HTTP Response Codes

HTTP response codes are used to indicate:

Status Code	Description
200	Success!
400	Bad request; check the error message for details. Generally returned for service exceptions.
401	Authentication failure, check your authentication details
403	Forbidden; please provide authentication credentials. Generally returned for policy exceptions.
404	Not found mistake in the host or path of the service URI, including a problem with the MSISDN supplied within the path.
405	Method not supported: for example, you mistakenly used a HTTP GET instead of a POST.
500	The server encountered an unexpected condition. This could be incorrect authentication details or limited user permission.
503	Server busy and service unavailable. Please retry the request.