

# MAPPING INVESTIGATIONS AND CASES IN MISP

E.205

CIRCL COMPUTER INCIDENT RESPONSE CENTER LUXEMBOURG

MISP PROJECT

<https://www.misp-project.org/>

MARCH 29, 2022 - VO.7



# OBJECTIVES OF THIS MODULE

- Recap on MISP data model and distribution levels
- Data from cases to be structured and encoded:
  - ▶ **Network indicators:** ip, domain, url, ...
  - ▶ **Files and binaries:** non-malicious / malicious payload
  - ▶ **Emails:** content, header, attachment, ...
  - ▶ **Web:** URL, cookies, x509
  - ▶ **Cryptographic materials:** public / private key, certificate
  - ▶ **Infrastructure and devices**
  - ▶ **Financial fraud:** bank-account, phone-number, btc
  - ▶ **Person:** name, online accounts, passport, visa
  - ▶ **Support tools:** yara, detection/remediation scripts
  - ▶ **Vulnerabilities:** cve
  - ▶ **External analysis:** Reports, blogpost, ransome notes
- Relationships and timeliness
- Enrichments via module and correlation
- Preparing data for sharing with other LE partners, CSIRT, SOC

# **MISP DATA MODEL AND DISTRIBUTION LEVELS**

## Event



*Encapsulations for contextually linked information.*

**Purpose:** Group datapoints and context together. Acting as an envelop, it allows setting distribution and sharing rules for itself and its children.

**Usecase:** Encode incidents/events/reports/...

- ▶ events can contain other elements such as attributes, objects and eventreports.
- ▶ The distribution level and any context added on an event (such as taxonomies) are propagated to its underlying data.



## Attribute



*Basic building block to share information.*

**Purpose:** Individual data point. Can be an indicator or supporting data.

**Usecase:** Domain, IP, link, sha1, attachment, ...

- ▶ attributes cannot be duplicated inside the same event and can have sightings.
- ▶ The difference between an indicator or supporting data is usually indicated by the state of the attribute's `to_ids` flag.



## MISP Object



*Advanced building block providing attribute compositions via templates.*

**Purpose:** Groups attributes that are intrinsically linked together.

**Usecase:** File, person, credit-card, x509, device, ...

- ▶ objects have their attribute compositions described in their respective template. They are instantiated with attributes and can reference other attributes or objects.
- ▶ MISP is not required to know the template to save and display the object. However, *edits* will not be possible as the template to validate against is unknown.

## ↗ Object Reference



*Relationships between individual building blocks.*

**Purpose:** Allows to create relationships between entities, thus creating a graph where they are the edges and entities are the nodes.

**Usecase:** Represent behaviours, similarities, affiliation, ...

► references can have a textual relationship which can come from MISP or be set freely.

## Event Report



*Advanced building block containing formatted text.*

**Purpose:** Supporting data point to describe events or processes.

**Usecase:** Encode reports, provide more information about the event, ...

► Event reports are markdown-aware and include a special syntax to reference data points or context.



Which structure should be used when encoding data?

## ■ **Attribute vs Object**

- ▶ If the value is contextually linked to another element or is a subpart of a higher concept, an **object** should be used
- ▶ If the value is part of a large list of atomic data, an **attribute** should be used

## ■ **Annotation Object vs Event Report**

- ▶ If it is possible to encode the text (raw text or markdown), an **event report** is preferred
- ▶ If the text is written in a specific format (e.g pdf, docx), an **annotation object** should be used

# **CASE STUDY 1: SCAM CALL**

# CASE STUDY 1: SCAM CALL

**Case:** A victim was asked to transfer money to a novice scammer

## **Chronology - 2022-03-24**

**11:42:43 UTC+0:** Scammer called the victim pretending to be a microsoft employee

**11:47:27 UTC+0:** Scammer convinced the victim to be helped via remote desktop assistance

**12:06:32 UTC+0:** Scammer downloaded the binary on the victim's computer

**12:08:18 UTC+0:** Scammer installed the binary on the victim's computer

**12:17:51 UTC+0:** Scammer asked the victim to transfer money on a bank account for the help he provided

**12:25:04 UTC+0:** Victim executed the money transfer

**2022-03-25 08:39:21 UTC+0:** Victim contacted police

## Collected evidences

- ▶ RDP Log file
- ▶ Installed binary
- ▶ Victim's browser history
- ▶ Bank account statement
- ▶ Victim's phone call log

## Data extracted from evidences

- ▶ Scammer's **ip address**
- ▶ Potentially **malicious binary**
- ▶ **URL** (and **domain**) from which the binary was downloaded
- ▶ Scammer's **bank account** and **phone number**
- ▶ Scammer's full name and nationality

## Extracted values

- ▶ 194.78.89.250
  - ip-address from log file
- ▶ bin.exe
  - downloaded binary
- ▶ <https://zdgyot.ugicok.ru/assets/bin.exe>
  - download URL
- ▶ GB 29 NWBK 601613 31926819
  - IBAN number
  - Swift: NWBK, Account number: 31926819, Currency: GBP
- ▶ +12243359185
  - phone number
- ▶ Wallace Breen is from GB
  - name and nationality

# CASE STUDY 1: SCAM CALL

## Tasks


- ▶ Create an new *event* to be shared with **all**
- ▶ Encode binary to be shared with **CSIRT**
- ▶ Encode ip address to be shared with both **ISP** and **CSIRT**
- ▶ Encode domain and url to be shared with both **ISP** and **CSIRT**
- ▶ Encode bank account to be shared with **Financial sector**
- ▶ Encode phone number to be shared with **Telecommunication sector**
- ▶ Encode full name and nationality to be shared with **LEA only**
- ▶ Add relationships to recreate the events
- ▶ Add time component to recreate the chronology
- ▶ Perform enrichments on the binary, and other attribute
- ▶ Add contextualization
- ▶ Create a small write-up as an *event report*
- ▶ Review the distribution level and publish

# CASE STUDY 1: SCAM CALL

## ■ Creating the *event* in MISP

Date

2022-03-24

Distribution 

All communities



Threat Level 

Low



Analysis 

Completed



Event Info

Successful Scam call involving money transfer

Extends Event

Event UUID or ID. Leave blank if not applicable.

Submit

# CASE STUDY 1: SCAM CALL

- Adding the binary as attachment
- Pick the Payload Delivery category
- Check *Is a malware sample*

### Add Attachment(s)

Category ⓘ

Payload delivery ▾

Distribution ⓘ

Inherit event ▾

Contextual Comment

Browse...

 bin.exe

☒ Is a malware sample (encrypt and hash)

☐ Advanced extraction

Upload



# CASE STUDY 1: SCAM CALL

- Encode the IP address of the scammer with an *attribute*
- Pick the Payload Installation category and ip-src type
- Check the For Intrusion Detection System
- Add a contextual comment such as
  - ▶ IP address of the scammer collected from the RDP log file

Category	Type
<input type="text" value="Payload delivery"/>	<input type="text" value="ip-src"/>
Distribution	
<input type="text" value="Inherit event"/>	
Value	
<input type="text" value="194.78.89.250"/>	
Contextual Comment	
<input type="text"/>	

- Encode the domain and the URL from which the binary was downloaded
- As these two attributes are contextually linked between each others, we should use an URL *object*
- Add a contextual comment such as
  - ▶ URL used by the scammer to download the binary
- Include at least: url, domain and ressource\_path

# CASE STUDY 1: SCAM CALL

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	url
Template version	9
Meta-category	network
Distribution	Inherit event
Comment	URL used by the scammer to download the binary
First seen	2022-03-24T12:06:32.000000+00:00
Last seen	

Attribute	Category	Type	Value	To IDS
url	Network activity	url	https://zdgyot.ugic0k.ru/assets/bin.exe	Yes
domain	Network activity	domain	zdgyot.ugic0k.ru	Yes
domain_without_tid	Other	text	zdgyot.ugic0k	No
resource_path	Other	text	/assets/bin.exe	No
scheme	Other	text	https	No
tid	Other	text	ru	No

Update object

Back to review

Cancel

## CASE STUDY 1: SCAM CALL

- Encode the bank account
- As these 4 attributes are contextually linked between each others, we should use an bank-account *object*
- Add a contextual comment such as
  - ▶ Bank account that received the money.  
Supposed to belong to the scammer
- Include at least: iban, swift, account and currency\_code

# CASE STUDY 1: SCAM CALL

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	bank-account
Template version	3
Meta-category	financial
Distribution	Inherit event
Comment	Bank account that received the money. Supposed to belong to the scammer
First seen	
Last seen	

Attribute	Category	Type	Value	To IDS
iban	Financial fraud	iban	GB29NWBK60161331926819	Yes
swift	Financial fraud	bic	NWBK	Yes
account	Financial fraud	bank-account-nr	31926819	Yes
currency-code	Other	text	GBP	No

[Update object](#)[Back to review](#)[Cancel](#)

# CASE STUDY 1: SCAM CALL

- Encode the phone number
- Pick the Financial Fraud category and phone-number type
- Add a contextual comment such as
  - ▶ Phone number used by the scammer to call the victim
- Check *For Intrusion Detection System*

Category	Type
<input type="text" value="Financial fraud"/>	<input type="text" value="phone-number"/>
Distribution	
<input type="text" value="Inherit event"/>	
Value	
<input type="text" value="+12243359185"/>	

- Encode the full name and nationality
- As these attributes are contextually linked between each others, we should use a person *object*
- Add a contextual comment such as
  - ▶ Name of the scammer given to the victim
- Include at least: full-name, nationality and role

# CASE STUDY 1: SCAM CALL

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	person
Template version	16
Meta-category	misc
Distribution	Inherit event
Comment	Name of the scammer given to the victim. Name confirmed to be the owner of the bank account and phone number
First seen	
Last seen	

Attribute	Category	Type	Value	To IDS
last-name	Person	last-name	Breen	No
full-name	Person	full-name	Wallace Breen	No
first-name	Person	first-name	Wallace	No
role	Other	text	Accused	No
gender	Person	gender	Male	No
nationality	Person	nationality	British	No

Update object


Back to review

Cancel




## CASE STUDY 1: SCAM CALL

Add (at least) these relationships to recreate the story



# CASE STUDY 1: SCAM CALL


## Add relationships to recreate the story



# CASE STUDY 1: SCAM CALL

Add time component to recreate the chronology

- Main focus is the Cyber Threat Intelligence (CTI) aspect



# CASE STUDY 1: SCAM CALL

## Perform enrichments

- Scammer IP address to get its location
- Binary to check if it's an existing (and malicious) application

### Mmdb Lookup:



Object: geolocation

country	Belgium
countrycode	BE
latitude	50.8333
longitude	4
text	db_source: GeoOpen-Country. build_db: 2022-02-05 10:37:33. Latitude and longitude are country average.

Object: geolocation

country	Belgium
countrycode	BE
latitude	50.8333
longitude	4
text	db_source: GeoOpen-Country-ASN. build_db: 2022-02-06 09:30:25. Latitude and longitude are country average.

Object: asn

# CASE STUDY 1: SCAM CALL

## ■ Contextualizing the data: Taxonomies


- ▶ Note: Different country / sectors might use different nomenclature

## ■ Suggestions for tagging with taxonomies:

- ▶ `circl:incident-classification="scam"`
- ▶ `social-engineering-attack-vectors:non-technical="technical-expert"`
- ▶ `social-engineering-attack-vectors:technical="vishing"`
- ▶ `veris:action:hacking:vector="Desktop sharing"`
- ▶ `veris:action:malware:vector="Direct install"`
- ▶ `veris:action:social:variety="Scam"`
- ▶ `veris:action:social:vector="Phone"`
- ▶ `veris:actor:external:motive="Financial"`
- ▶ `veris:impact:loss:rating="Minor"`
- ▶ `veris:impact:loss:variety="Asset and fraud"`
- ▶ `workflow:state="complete"`
- ▶ `tlp:green`

# CASE STUDY 1: SCAM CALL


## Tags

 workflow:state="complete" x  tlp:green x

 veris:action:hacking:vector="Desktop sharing" x

 veris:action:social:variety="Scam" x

 veris:action:social:vector="Phone" x

 veris:actor:external:motive="Financial" x

 veris:impact:loss:rating="Minor" x

 veris:impact:loss:variety="Asset and fraud" x

 social-engineering-attack-vectors:non-technical="technical-expert" x

 social-engineering-attack-vectors:technical="vishing" x

# CASE STUDY 1: SCAM CALL

- Contextualizing the data: Galaxy Clusters
  - ▶ Note: Different country / sectors might use different nomenclature
- Suggestions for tagging with Galaxies:
  - ▶ MITRE Attack Pattern

## Galaxies

### Attack Pattern 🔍

🌐 Phishing - T1566 🔍 ☰ 🗑️

🌐 User Execution - T1204 🔍 ☰ 🗑️

Create a small write-up as an *event report*

- Create the *event report* with a concise name
- Example: Executive summary of the case
  - ▶ Leave its content empty as it can be edited with more ease in the editor afterward
- Write a summary with
  - ▶ Quick chronology
  - ▶ Written explanation of the steps tooks by the scammer
  - ▶ Reference to existing *attributes* or *objects* whenever possible
    - The special syntax is: @[scope]{uuid}



# CASE STUDY 1: SCAM CALL

## Create a small write-up as an event report

### Executive summary of the case

A victim was called by the suspected scammer **person Wallace Breen** using the following number: **phone-number +12243359185**. The scammer pretended to be a microsoft employee, managed to convince the victim that he could help by using remote desktop assistance.

Once he had access, the scammer downloaded a binary **file bin.exe** from the following url **url https://zdyot.ugic0k.ru/assets/bin.exe**. He then proceed to install the binary, probably to use it a backdoor for future access.

After the installation, he asked the victim to transfer money to the scammer bank account: **bank-account iban GB29NWBK60161331926819**

The day after, the victim suspecting a scam contacted the police.

### Technique used

Social vector	<b>veris.action:social-vector="Phone"</b>
Potential hacking vector	<b>veris.action:hacking-vector="Desktop sharing"</b>
Actor motive	<b>veris.actor:external-motive="Financial"</b>
Impacted loss	<b>veris.impact:loss-variety="Asset and fraud"</b>
Loss rating	<b>veris.impact:loss-rating="Minor"</b>

### Information collected after analysis

- According to the phone number, IP address and bank account, the scammer **person Wallace Breen** is very likely based in **geolocation country Belgium**.

### Timeline

- 2022-03-25 11:42:43 UTC+0: Scammer called the victim pretending to be a microsoft employee
- 2022-03-25 11:47:27 UTC+0: Scammer convinced the victim to be helped via remote desktop assistance
- 2022-03-25 12:06:32 UTC+0: Scammer downloaded the binary on the victim's computer
- 2022-03-25 12:08:18 UTC+0: Scammer installed the binary on the victim's computer
- 2022-03-25 12:17:51 UTC+0: Scammer asked the victim to transfer money on a bank account for the help he provided
- 2022-03-25 12:25:04 UTC+0: Victim executed the money transfer

Review the distribution level and publish

- In our case, we consider the following MISP network topology
- The current instance is owned and managed by a LEA
- The current instance is connected to a central MISP instance acting as a "hub"
- The "hub" is connected to various other MISP instances such as other LEAs, CSIRTs, Financial and telecom institutions

**include diagram**

# CASE STUDY 1: SCAM CALL

Review the distribution level and publish

- binary file: **All communities**
- person: **LEA Sharing group**
- geolocation: **LEA Sharing group**
- ip: **LEA Sharing group**
  - ▶ The IP might be reassigned
- phone
  - ▶ If part of a telco sharing group **Telco Sharing group**
  - ▶ **Connected communities** otherwise
- bank account
  - ▶ If part of a financial sharing group **Financial Sharing group**
  - ▶ **Connected communities** otherwise

→ **Publish the event!**

# **CASE STUDY 2: RANSOMWARE**

## CASE STUDY 2: RANSOMWARE

**Case:** Ransomware infection via e-mail

### **Chronology - 2022-03-24**

**11:42:43 UTC+0:** Email containing the ransomware from supposedly Andrew Ryan

**11:47:27 UTC+0:** Email was read and its attachment opened and executed

**11:47:28 UTC+0:** Malware add persistence

**12:08:18 UTC+0:** Malware successfully contacted the C2 to get the PK

**12:08:19 UTC+0:** Malware saved the PK in the registry

**12:25:04 UTC+0:** Malware began the encryption process

**2022-03-25 08:39:21 UTC+0:** Victim contacted the police

# CASE STUDY 2: RANSOMWARE

## Splash message from the Ransomware



# CASE STUDY 2: RANSOMWARE

## Collected evidences

- ▶ E-mail received by the victim
- ▶ E-mail attachment of the ransomware as an .exe payload
- ▶ Windows registry
- ▶ Ransomware's public key (PK)
- ▶ Captured network traffic
- ▶ Message displayed by the ransomware

## Data extracted from evidences

- ▶ Original **e-mail**
- ▶ The actual ransomware **binary**
- ▶ **Registry Keys** for persistence and configuration
- ▶ **Public Key** used for encryption
- ▶ C&C server **ip address** used to generate the Private Key (SK)
- ▶ The **bitcoin address** on which the ransom should be paid
- ▶ The **person**, impersonated or fake that sent the email

# CASE STUDY 2: RANSOMWARE

Subject: 4829—2375  
From: "Andrew\_Ryan" <Andrew\_Ryan@rindustries rp>

Please see the attached lolta report for 4829—2375.

We received a check request in the amount of \$19,637.28 for the above referenced file .  
However, the attached report reflects a \$0 balance. At your earliest convenience, please advise how this request is to be funded.

Thanks.

Andrew\_Ryan \*  
Accounts Payable

Ryan Industries  
42, Central Control Hephaestus — Rapture  
www.rindustries rp

\*Not licensed to practise law.

This communication contains information that is intended only for the recipient named and may be privileged, confidential, subject to the attorney—client privilege, and/or exempt from disclosure under applicable law. If you are not the intended recipient or agent responsible for delivering this communication to the intended recipient, you are hereby notified that you have received this communication in error, and that any review, disclosure, dissemination, distribution, use, or copying of this communication is STRICTLY PROHIBITED. If you have received this communication in error, please notify us immediately by telephone at 1—800—766—7751 or 1—972—643—6600 and destroy the material in its entirety, whether in electronic or hard copy format.



# CASE STUDY 2: RANSOMWARE

## Extracted values

- ▶ e-mail from previous slide
- ▶ cryptolocker.exe
  - Ransomware attached to the mail
- ▶ 81.177.170.166
  - ip-address of a C2 server used to generate the SK
- ▶ HKCU\SOFTWARE\Microsoft\Windows\CurrentVersion\Run "CryptoLocker"
  - The registry key used for persistence
- ▶ HKCU\SOFTWARE\CryptoLocker VersionInfo
  - The registry key containing configuration data
- ▶ HKCU\SOFTWARE\CryptoLocker PublicKey
  - The registry key containing the RSA public key received from the C2 server
- ▶ 0x819C33AE
  - XOR key used to encode the configuration data

## CASE STUDY 2: RANSOMWARE

```
-----BEGIN PUBLIC KEY-----  
MIGfMA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQDaogllvHPytDAdUWZPk9aWXJ5G  
Lk9F+HzDaJ5qGXou8XmISwChbia/NC84QmBHTiyg4B1tqVjqk5X6yh6pcZuVw+GX  
oCrH505o2QoXVYZYYsEZQB36VHxwm7xTx21y0y2rSOQy0upQ6e7HMGtu7p7+RlWO  
D5UfPkv337plrEiUuwIDAQAB  
-----END PUBLIC KEY-----
```

- ▶ The public key received from the C2 used to encrypt files
- 1KP72fBmh3XBRfuJDMn53APaqM6iMRspCh
  - ▶ Bitcoin address on which to transfer the ransom
- Andrew Ryan, Andrew\_Ryan@rindustries.rp
  - ▶ Accountant, Suspect & Victim & Originator
  - ▶ Person, e-mail, occupation and role

### Tasks

- ▶ Create a new *event* to be shared with **all**
- ▶ Encode data to be shared
- ▶ Add relationships to recreate the events
- ▶ Add time component to recreate the chronology
- ▶ Perform enrichments on the binary, and other attributes
- ▶ Add contextualization
- ▶ Create a small write-up as an *event report*
- ▶ Review the distribution level and publish

## CASE STUDY 2: RANSOMWARE

### ■ Creating the *event* in MISP

Date

2022-03-24

Distribution ⓘ

All communities

Threat Level ⓘ

Medium

Analysis ⓘ

Completed

Event Info

CryptoLocker ransomware infection via e-mail

Extends Event

Event UUID or ID. Leave blank if not applicable.

Submit

- Add the original e-mail
- As the email contains multiple contextually linked data points, we should use an Email *object*
- Add contextual comment such as:
  - ▶ Email received by the victim containing the ransomware
- Include at least: from, subject and body

# CASE STUDY 2: RANSOMWARE

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	email
Template version	18
Meta-category	network
Distribution	Inherit event
Comment	
First seen	2022-03-24T11:42:43
Last seen	

Attribute	Category	Type	Value	To IDS
subject	Payload delivery	email-subject	4829-2375	No
from	Payload delivery	email-src	Andrew_Ryan@rindustries.rp	Yes
email-body	Payload delivery	email-body	Please see the attached Iolta report for 4829-2375. We received a check request in the amount of \$19,637.28 for the above referenced file. However, the attached report reflects a \$0 balance. At your earliest convenience, please advise how this request is to be funded. Thanks. Andrew_Ryan * Accounts Payable Ryan Industries 42, Central Control Hephaestus - Rapture www.rindustries.rp *Not licensed to practise law. This communication contains information that is intended only for the recipient named and may be privileged, confidential, subject to the attorney-client privilege, and/or exempt from disclosure under applicable law. If you are not the intended recipient or agent responsible for delivering this communication to the intended recipient, you are hereby notified that you have received this communication in error, and that any review, disclosure, dissemination, distribution, use, or copying of this communication is STRICTLY PROHIBITED. If you have received this communication in error, please notify us immediately by telephone at 1-800-766-7751 or 1-972-643-6600 and destroy the material in its entirety, whether in electronic or hard copy format.	No

[Create new object](#)[Back to review](#)[Cancel](#)

## CASE STUDY 2: RANSOMWARE

- Add the ransomware binary as attachment
- Pick the Payload Delivery category
- Add contextual comment such as:
  - ▶ CryptoLocker ransomware delivered by email
- Check *Is a malware sample*

### Add Attachment(s)

Category ⓘ

Payload installation ▼

Distribution ⓘ

Inherit event ▼

Contextual Comment

CryptoLocker ransomware delivered by email

Browse...

 cryptolocker.exe

☒ Is a malware sample (encrypt and hash)

☐ Advanced extraction

Upload

# CASE STUDY 2: RANSOMWARE

- Encode the IP address of the C2 server with an *attribute*
- Pick the Payload Installation category and ip-src type
- Check the For Intrusion Detection System
- Add a contextual comment such as
  - ▶ IP address of the scammer collected from the RDP log file

## Add Attribute

Category ⓘ

Payload delivery ▼

Type ⓘ

ip-src ▼

Distribution ⓘ

Inherit event ▼

Value

81.177.170.166

Contextual Comment

IP of the C2 phoned-home by the ransomware

☒ For Intrusion Detection System



# CASE STUDY 2: RANSOMWARE

- Encode the registry keys used for persistence by the ransomware
- As the registry keys contains multiple contextually linked data points, we should use an *registry-key object*
- Add a contextual comment such as
  - ▶ The registry key used for persistence, making sure it gets run again after an OS reboot

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	registry-key				
Template version	4				
Meta-category	file				
Distribution	Inherit event				
Comment					
First seen	2022-03-24T11:47:28				
Last seen					
Attribute	Category	Type	Value	To IDS	
data	Persistence mechanism	text	"CryptoLocker"	No	
key	Persistence mechanism	regkey	SOFTWARE\Microsoft\Windows\CurrentVersion\Run "CryptoLocker"	Yes	
root-keys	Other	text	HKCU	No	
<div>Create new objectBack to reviewCancel</div>					

# CASE STUDY 2: RANSOMWARE

- Encode the registry keys used for storing the ransomware's configuration
- As the registry keys contains multiple contextually linked data points, we should use an *registry-key object*
- Add a contextual comment such as
  - ▶ Containing configuration data (C2 address, malware version and installation timestamp)

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	registry-key			
Template version	4			
Meta-category	file			
Distribution	Inherit event			
Comment				
First seen	2022-03-24T12:08:18.000000+00:00			
Last seen				

Attribute	Category	Type	Value	To IDS
name	Persistence mechanism	text	VersionInfo	No
key	Persistence mechanism	regkey	HKCU\SOFTWARE\CryptoLocker VersionInfo	Yes
root-keys	Other	text	HKCU	No

Update objectBack to reviewCancel

# CASE STUDY 2: RANSOMWARE

- Encode the registry keys used for ransomware PK
- As the registry keys contains multiple contextually linked data points, we should use an *registry-key object*
- Add a contextual comment such as
  - ▶ Contains the RSA public key received from the C2 used for encryption

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	registry-key		
Template version	4		
Meta-category	file		
Distribution	Inherit event		
Comment			
First seen	2022-03-24T12:08:19.000000+00:00		
Last seen			

Attribute	Category	Type	Value	To IDS
data	Persistence mechanism	text	-----BEGIN PUBLIC KEY-----	No
			MIGMA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQDaogIvHPyIDAdUWZP9aWXJ5G Lk9F+HzDaj5qXou8xmISwChbia/Nc84QmBHTjg4B1tqVjpk5X8yh6pcZuVw+GX OCiH5O5o2Q0XVYzYY6EZQB36VHxwm7Xt21yOy2rSOQyOupO6e7HMG3u7p7+RiWO D5UIPkV337prEiUwIDAGAB -----END PUBLIC KEY-----	
name	Persistence mechanism	text	PublicKey	No
key	Persistence mechanism	regkey	HKCU\SOFTWARE\CryptoLocker PublicKey	Yes
root-keys	Other	text	HKCU	No

[Update object](#)[Back to review](#)[Cancel](#)

## CASE STUDY 2: RANSOMWARE

- Encode the bitcoin address used to receive the ransom
- Pick the Financial Fraud category and btc type
- Check the For Intrusion Detection System
- Add a contextual comment such as
  - ▶ Hardcoded address on which the ransom is asked to be transferred

### Add Attribute

Category ⓘ

Type ⓘ

Financial fraud ▼

btc ▼

Distribution ⓘ

Inherit event ▼

Value

1KP72fBmh3XBRfuJDMn53APaqM6iMRspCh

Contextual Comment

☒ For Intrusion Detection System

# CASE STUDY 2: RANSOMWARE

- Encode the name and roles of the person
- As these attributes are contextually linked between each others, we should use a person *object*
- Add a contextual comment such as
  - ▶ Person from which the mail seems to originate
- Include at least: full-name, e-mail and roles

## Object pre-save review

Make sure that the below Object reflects your expectation before submitting it.

Name	person
Template version	16
Meta-category	misc
Distribution	Inherit event
Comment	Person from which the mail seems to originate
First seen	
Last seen	

Attribute	Category	Type	Value	To IDS
last-name	Person	last-name	Ryan	No
full-name	Person	full-name	Andrew Ryan	No
first-name	Person	first-name	Andrew	No
e-mail	Payload delivery	email-src	andrew_ryan@rindustries.rp	Yes
role	Other	text	Suspect	No
role	Other	text	Victim	No
role	Other	text	Originator	No
nationality	Person	nationality	Belarus	No

[Update object](#)[Back to review](#)[Cancel](#)


# CASE STUDY 2: RANSOMWARE

- use crypto material
  - ▶ XOR key used to encode the malware's configuration in the registry

Category	Type
Artifacts dropped ▼	hex ▼
Distribution	
Inherit event ▼	
Value	
<div>819C33AE</div>	
Contextual Comment	
<div>XOR key used to encode the malware's configuration in the registry</div>	
<input checked="" type="checkbox"/> For Intrusion Detection System	


## CASE STUDY 2: RANSOMWARE

Add (at least) these relationships to recreate the story



# CASE STUDY 2: RANSOMWARE

## Add relationships to recreate the story






# CASE STUDY 2: RANSOMWARE

Add time component to recreate the chronology

- Main focus is the Cyber Threat Intelligence (CTI) aspect



# CASE STUDY 2: RANSOMWARE

## Perform enrichments

### ■ IP address to get its location

#### Mmdb Lookup:



##### Object: geolocation

country	Russia
countrycode	RU
latitude	60
longitude	100
text	db_source: GeoOpen-Country. build_db: 2022-02-05 10:37:33. Latitude and longitude are country average.

##### Object: geolocation

country	Russia
countrycode	RU
latitude	60
longitude	100
text	db_source: GeoOpen-Country-ASN. build_db: 2022-02-06 09:30:25. Latitude and longitude are country average.

##### Object: asn

asn	8342
-----	------

# CASE STUDY 2: RANSOMWARE

## Perform enrichments

### ■ Bitcoin wallet to view the transactions

#### Btc Steroids:

Address: 1KP72fBmh3XBRfuJDMn53APaqM6iMRspCh

Balance: 0.000000000 BTC (+54.9083000000 BTC / -54.9083000000 BTC)

Transactions: 40

```
=====
#40 19 Nov 2013 12:03:48 UTC -0.00020000 BTC   0.13 USD    0.10 EUR
#39 15 Oct 2013 15:16:44 UTC -2.00000000 BTC  316.18 USD   227.78 EUR
#39 15 Oct 2013 15:16:44 UTC -1.99950000 BTC  316.10 USD   227.72 EUR
-----
#39          Sum: -3.99950000 BTC   632.28 USD   455.50 EUR

#38 15 Oct 2013 02:12:02 UTC -2.00000000 BTC  316.18 USD   227.78 EUR
#37 13 Oct 2013 21:03:42 UTC -2.00000000 BTC  295.06 USD   211.26 EUR
#36 11 Oct 2013 21:23:33 UTC -2.00000000 BTC  280.20 USD   204.02 EUR
#36 11 Oct 2013 21:23:33 UTC -2.00000000 BTC  280.20 USD   204.02 EUR
-----
#36          Sum: -4.00000000 BTC   560.40 USD   408.04 EUR

#35 08 Oct 2013 23:24:22 UTC -2.00000000 BTC  272.98 USD   199.28 EUR
#35 08 Oct 2013 23:24:22 UTC -2.00000000 BTC  272.98 USD   199.28 EUR
-----
#35          Sum: -4.00000000 BTC   545.96 USD   398.56 EUR

#34 07 Oct 2013 08:26:25 UTC -2.00000000 BTC  271.60 USD   198.90 EUR
#34 07 Oct 2013 08:26:25 UTC -2.00000000 BTC  271.60 USD   198.90 EUR
#34 07 Oct 2013 08:26:25 UTC -2.00000000 BTC  271.60 USD   198.90 EUR
#34 07 Oct 2013 08:26:25 UTC -2.00000000 BTC  271.60 USD   198.90 EUR
-----
#34          Sum: -8.00000000 BTC  1086.40 USD   795.60 EUR
```

## CASE STUDY 2: RANSOMWARE

- Contextualizing the data
  - ▶ Different country / sectors might use different nomenclature
- Suggestions of taxonomies for tagging:
  - ▶ adversary: adversary infrastructure
  - ▶ circl: Classification in Incident Response
  - ▶ enisa: ENISA structuring aid for information and threats
  - ▶ europol-\*: Describe the type of events or incidents
  - ▶ maec-\*: Malware Attribute Enumeration and Characterization
  - ▶ malware\_classification: Based on SANS malware 101
  - ▶ ms-caro-malware: Microsoft's Malware Type and Platform
  - ▶ ransomware: ransomware types and the elements
  - ▶ veris: Vocabulary for Event Recording and Incident Sharing
  - ▶ collaborative-intelligence: Support analysts
  - ▶ workflow: Support analysts
  - ▶ tlp: Traffic Light Protocol

# CASE STUDY 2: RANSOMWARE

## ■ Incident type

- ▶ `circl:incident-classification="ransomware"`
- ▶ `enisa:nefarious-activity-abuse="ransomware"`
- ▶ `europol-incident:malware="infection"`
- ▶ `europol-incident:malware="c&c"`
- ▶ `ms-caro-malware:malware-type="Ransom"`

## ■ Malware type

- ▶ `malware_classification:malware-category="Ransomware"`
- ▶ `ransomware:type="crypto-ransomware"`

## ■ Collaration and Sharing

- ▶ `collaborative-intelligence:request="extracted-malware-config"`
- ▶ `workflow:state="complete"`
- ▶ `tlp:green`

# CASE STUDY 2: RANSOMWARE

## ■ Infection vector

- ▶ `europol-event:dissemination-malware-email`
- ▶ `maec-delivery-vectors:maec-delivery-vector="email-attachment"`
- ▶ `ransomware:infection="phishing-e-mails"`

## ■ Adversary infrastructure

- ▶ `adversary:infrastructure-type="c2"`
- ▶ `veris:action:malware:variety="C2"`

# CASE STUDY 2: RANSOMWARE

## Malware-specific information

- `maec-malware-capabilities:maec-malware-capability="fraud"`
- `maec-malware-capabilities:maec-malware-capability="persistence"`
- `maec-malware-capabilities:maec-malware-capability="communicate-with-c2-server"`
- `maec-malware-capabilities:maec-malware-capability="compromise-data-availability"`
- `ransomware:element="ransomnote"`
- `ransomware:element="dropper"`
- `ransomware:complexity-level="file-restoration-possible-using-shadow-volume-copies"`
- `ransomware:complexity-level="file-restoration-possible-using-backups"`
- `ransomware:complexity-level="decryption-key-recovered-from-a-C&C-server-or-network-communications"`
- `ransomware:complexity-level="encryption-model-is-seemingly-flawless"`
- `ransomware:purpose="deployed-as-ransomware-extortion"`
- `ransomware:target="pc-workstation"`
- `ransomware:communication="dga-based"`
- `ransomware:malicious-action="asymmetric-key-encryption"`

# CASE STUDY 2: RANSOMWARE

## Tags



tlp:green x    circl:incident-classification="ransomware" x  
enisa:nefarious-activity-abuse="ransomware" x  
europol-incident:malware="infection" x  
europol-incident:malware="c&c" x  
ms-caro-malware:malware-type="Ransom" x  
malware\_classification:malware-category="Ransomware" x  
ransomware:type="crypto-ransomware" x  
workflow:state="complete" x  
europol-event:dissemination-malware-email x  
maec-delivery-vectors:maec-delivery-vector="email-attachment" x  
ransomware:infection="phishing-e-mails" x

## ■ Danger of over-classification


- ▶ Make things cluttered and unreadable
- ▶ Mixing classification scheme
- ▶ Introduce a non-negligible overhead when using *LIKE* filters (e.g. tlp:%)





# CASE STUDY 2: RANSOMWARE

- Adding tags on attribute level make the role of the data clearer
- Make searches and exports easier

<input type="checkbox"/>	2022-03-29	Payload delivery	ip-src	81.177.170.166 🔍	<span>adversary:infrastructure-types="c2" x</span> <span>veris:action.malware:variety="C2" x</span>
<input type="checkbox"/>	2022-03-29	Artifacts dropped	attachment		<span>ransomware:element="ransomnote" x</span> <span>+ +</span>
2022-03-29    Object name: email 📄 References: 1 📄 📄 Referenced by: 2 📄 📄					
<input type="checkbox"/>	2022-03-28	Payload delivery	<b>subject:</b> email-subject	4829-2375	<span>+ +</span>
<input type="checkbox"/>	2022-03-28	Payload delivery	<b>from:</b> email-src	andrew_ryan@rindustries.rp 🔍	<span>+ +</span>
<input type="checkbox"/>	2022-03-29	Payload delivery	<b>email-body:</b> email-body	<p>Please see the attached Iolta report for 4829-2375.</p> <p>We received a check request in the amount of \$19,637.28 for the above referenced file. However, the attached report reflects a \$0 balance. At your earliest convenience, please advise how this request is to be funded.</p> <p>Thanks.</p> <p>Andrew_Ryan * Accounts Payable</p>	<span>ransomware:element="dropper" x</span>

- Contextualizing the data: Galaxy Clusters
  - ▶ Note: Different country / sectors might use different nomenclature
- Suggestions for tagging with Galaxies:
  - ▶ Malpedia
  - ▶ Ransomware
  - ▶ MITRE Attack Pattern
  - ▶ Preventive Measure

# CASE STUDY 2: RANSOMWARE

## Galaxies

### Malpedia 🔍

🔗 CryptoLocker 🔍 ☰ 🗑

### Ransomware 🔍

🔗 CryptoLocker 🔍 ☰ 🗑

### Attack Pattern 🔍

🔗 Modify Registry - T1112 🔍 ☰ 🗑

🔗 Registry Run Keys / Startup Folder - T1547.001 🔍 ☰ 🗑

🔗 File and Directory Discovery - T1083 🔍 ☰ 🗑

🔗 Domains - T1583.001 🔍 ☰ 🗑

🔗 Peripheral Device Discovery - T1120 🔍 ☰ 🗑

🔗 Web Protocols - T1071.001 🔍 ☰ 🗑

🔗 Bidirectional Communication - T1102.002 🔍 ☰ 🗑

🔗 Standard Encoding - T1132.001 🔍 ☰ 🗑

🔗 Malicious File - T1204.002 🔍 ☰ 🗑

🔗 Spear phishing messages with malicious attachments - T1367 🔍 ☰ 🗑

🔗 Data Encrypted for Impact - T1486 🔍 ☰ 🗑

🔗 Credentials in Registry - T1552.002 🔍 ☰ 🗑

🔗 Asymmetric Cryptography - T1573.002 🔍 ☰ 🗑

🔗 Virtual Private Server - T1583.003 🔍 ☰ 🗑

🔗 Botnet - T1583.005 🔍 ☰ 🗑

Preventive measures

TODO: Include PM

# CASE STUDY 2: RANSOMWARE

## MITRE ATT&CK Matrix





Initial access (19 items)	Malicious File Execution (29 items)	Persistence (114 items)	Privilege escalation (101 items)	Defense evasion (163 items)	Credential access (35 items)	Discovery (42 items)	Lateral movement (23 items)	Collection (36 items)	Command and control (40 items)	Exfiltration (17 items)	Impact (26 items)
Cloud Accounts	Malicious File	Registry Run Keys / Startup Folder	Registry Run Keys / Startup Folder	Modify Registry	Credentials in Registry	File and Directory Discovery	Application Access Token	ARP Cache Poisoning	Asymmetric Cryptography	Automated Exfiltration	Data Encrypted for Impact
Compromise Hardware Supply Chain	AppleScript	bash_profile and bashrc	bash_profile and bashrc	Abuse Elevation Control Mechanism	icljavaword and icljshadow	Peripheral Device Discovery	Component Object Model and Distributed COM	Adversary-in-the-Middle	Bi-directional Communication	Data Transfer Size Limits	Account Access Removal
Compromise Software Dependencies and Development Tools	AI (Linux)	Accessibility Features	Abuse Elevation Control Mechanism	Access Token Manipulation	ARP Cache Poisoning	Account Discovery	Distributed Component Object Model	Archive Collected Data	Standard Encoding	Exfiltration Over Alternative Protocol	Application Exhaustion Flood
Compromise Software Supply Chain	AI (Windows)	Account Manipulation	Access Token Manipulation	Application Access Token	AS-REP Roasting	Application Window Discovery	Exploitation of Remote Services	Archive via Custom Method	Web Protocols	Exfiltration Over Asymmetric Encrypted Non-C2 Protocol	Application or System Exploitation
Default Accounts	Command and Scripting Interpreter	Active Setup	Accessibility Features	Asynchronous Procedure Call	Adversary-in-the-Middle	Browser Bookmark Discovery	Internal Spearphishing	Archive via Library	Application Layer Protocol	Exfiltration Over Bluetooth	Data Destruction
Domain Accounts	Component Object Model	Add Office 365 Global Administrator Role	Active Setup	BITS Jobs	Bash History	Cloud Account	Lateral Tool Transfer	Archive via Utility	Commonly Used Port	Exfiltration Over C2 Channel	Data Manipulation
Drive-by Compromise	Component Object Model and Distributed COM	Add-ins	AppCert DLLs	Binary Padding	Brute Force	Cloud Groups	Pass the Hash	Audio Capture	Communication Through Removable Media	Exfiltration Over Other Network Medium	Defacement
Exploit Public-Facing Application	Container Administration Command	Additional Cloud Credentials	AppInit DLLs	Bootkit	Cached Domain Credentials	Cloud Infrastructure Discovery	Pass the Ticket	Automated Collection	DNS	Exfiltration Over Physical Medium	Direct Network Flood
External Remote Services	Container Orchestration Job	AppCert DLLs	Application Shimming	Build Image on Host	Cloud Instance Metadata API	Cloud Service Dashboard	RDP Hijacking	Browser Session Hijacking	DNS Calculation	Exfiltration Over Symmetric Encrypted Non-C2 Protocol	Disk Content Wipe
Hardware Additions	Cron	AppInit DLLs	Asynchronous Procedure Call	Bypass User Account Control	Container API	Cloud Service Discovery	Remote Desktop Protocol	Clipboard Data	Data Encoding	Exfiltration Over Unencrypted/Obfuscated Non-C2 Protocol	Disk Structure Wipe

Create a small write-up as an *event report*

- Create the *event report* with a concise name
- Example: Executive summary of the case
  - ▶ Leave its content empty as it can be edited with more ease in the editor afterward
- Write a summary with
  - ▶ Quick chronology
  - ▶ Written explanation of the steps tooks by the ransomware
  - ▶ Reference to existing *attributes* or *objects* whenever possible
    - The special syntax is: @[scope]{uuid}

# CASE STUDY 2: RANSOMWARE

- Create a small write-up as an *event report*
- We could have a technical report and another one for the incident

Event Reports				
<a href="#">+ Add Event Report</a> <a href="#">Import from URL</a> <a href="#">Generate report from Event</a> <span>All</span> <span>Default</span> <span>Deleted</span>				
ID	Name	Last update	Distribution	Actions
73	Executive summary of the incident	2022-03-29 14:02:53	This community only	 
72	Technical details about the ransomware	2022-03-29 13:57:13	Inherit event	 



# CASE STUDY 2: RANSOMWARE

## Technical details about the ransomware

The ransomware in question seems to be an early version of the [ransomware - CryptoLocker](#) ransomware, or at least an extremely close version.

### Infection vector

Distributed through spam or spearphishing emails. In this case, the mail [email: Please see the attached kolla report for 4829-2375...](#) was sent to lure the victim to read it and get infected. The ransomware payload [file: cryptolocker.exe](#) was attached to the mail with a PDF icon and relied on the fact that Windows hides the extensions of known file to get the user to execute it once it's opened.

### Execution and persistence

Cryptolocker hides its presence from the victims until it has successfully contacted the command and control (C2) server [ip: 61.177.170.166](#). Prior to this action, the malware ensures its persistence by copying itself and adding an autorun registry key [registry-key: "Cryptolocker"](#). It also store additional configuration data such as the C2 address [ip: 61.177.170.166](#), the malware version and installation timestamp in another registry key [registry-key: VersionInfo](#). This registry key is encoded with the key [crypto-material: 819C33AE](#).

### Network

The malware try to contacts the C2 server and once successful recover the RSA public-key (generated by the C2 used to encrypt the files on the victim's computer).

### Encryption

Once the malware has its public-key, it begins the encryption process by enumerating files and encrypting it. A small amount of metadata and the encrypted file contents are then written back to disk, replacing the original files. Encrypted files can only be recovered by obtaining the RSA private key held exclusively by the threat actors. After finishing the file encryption process, Cryptolocker displays a window containing instructions on how to decrypt the file by paying the ransom as seen in the picture below



## CASE STUDY 2: RANSOMWARE

### Payment

The ransom amount is set to 2 BTC to be transferred on the bitcoin address `1KP728mh3XB9uJ0Mn53APqMNMRRspCh` before the countdown timer expires. According to the ransomware, the private key associated to the public key is destroyed if the payment is not done, rendering the decryption of the files impossible.

### Ransomware details

Delivery	mac-delivery-vectors:mac-delivery-vectors.'email-attachment'
Complexity Level	ransomware:complexity-level.'file-restoration-possible-using-shadow-volume-copies'
	ransomware:complexity-level.'file-restoration-possible-using-backups'
	ransomware:complexity-level.'decryption-key-recovered-from-a-C&C-server-or-network-communications'
	ransomware:complexity-level.'encryption-model-is-seemingly-flawless'
Purpose	ransomware:purpose.'deployed-as-ransomware-extortion'
Malicious Action	ransomware:malicious-action.'asymmetric-key-encryption'
Capability	mac-malware-capabilities:mac-malware-capability.'persistence'
	mac-malware-capabilities:mac-malware-capability.'fraud'
	mac-malware-capabilities:mac-malware-capability.'communicate-with-c2-server'
	mac-malware-capabilities:mac-malware-capability.'compromise-data-availability'

### Mitigation

## Techniques and MITRE ATT&CK

- **mitre-attack-pattern** = **Botnet** - T1603.001
- **mitre-attack-pattern** = **Domainss** - T1603.001
- **mitre-attack-pattern** = **Visual Privateer Server** - T1503.003
- **mitre-attack-pattern** = **Spam phishing messages with malicious attachments** - T1591.001
- **mitre-attack-pattern** = **Malicious File** - T1204.002
- **mitre-attack-pattern** = **Registry Run Keys Startup Folder** - T1547.001
- **mitre-attack-pattern** = **Data Encrypted for Impact** - T1486
- **mitre-attack-pattern** = **File and Directory Discovery** - T1603
- **mitre-attack-pattern** = **Asymmetric Cryptography** - T1573.001
- **mitre-attack-pattern** = **System File Manipulation** - T1102.002
- **mitre-attack-pattern** = **Service Enumeration** - T1059.001
- **mitre-attack-pattern** = **Web Protocols** - T1071.001
- **mitre-attack-pattern** = **Commandss in Registry** - T1552.001
- **mitre-attack-pattern** = **Modify Registry** - T1112
- **mitre-attack-pattern** = **Peripheral Device Discovery** - T1210

<a href="#">mitre-attack-pattern</a> - <a href="#">Peripheral Device - Attack</a> - T1120											
mitre-attack-attack		mitre-attack-technique		mitre-attack-tool		mitre-attack-impact		mitre-attack-credential		mitre-attack-asset	
Initial access (14 items)	Execution (20 items)	Persistence (14 items)	Privilege escalation (14 items)	Defense evasion (14 items)	Credential access (24 items)	Discovery (42 items)	lateral movement (38 items)	Collection (38 items)	Command and control (46 items)	Exfiltration (17 items)	Impact (26 items)
Cloud Accounts	Malicious File	Registry Run Keys / Startup Folder	Registry Run Keys / Startup Folder	Modify Registry	Credentials in Registry	File and Directory Discovery	Application Access Token	APP Cache Poisoning	Asymmetric Cryptography	Automated Exfiltration	Data Encrypted for Impact
Compromise	AppleScript	bash	bash	Abuse Elevation	Abuse Elevation	Peripheral	Component	Adversary-in	Bi-directional	Data Transfer	Account Access

Review the distribution level and publish

- In our case, we consider the following MISP network topology
- The current instance is owned and managed by a LEA
- The current instance is connected to a central MISP instance acting as a "hub"
- The "hub" is connected to various other MISP instances such as other LEAs, CSIRTs, Financial and telecom institutions

**include diagram**

Review the distribution level and publish

- binary file: **All communities**
- person: **LEA Sharing group**
- geolocation: **LEA Sharing group**
- ip: **All communities**
  - ▶ The IP is clearly used for delivering malware: It's an IoC

→ **Publish the event!**