

MISP Objects

MISP Objects

Introduction	8
Funding and Support	9
MISP objects	10
ail-leak	10
ais-info	11
android-app	12
android-permission	13
annotation	15
anonymisation	16
apivoid-email-verification	20
artifact	23
asn	25
attack-pattern	27
authentication-failure-report	27
authenticode-signerinfo	28
av-signature	29
bank-account	30
bgp-hijack	34
bgp-ranking	35
blog	35
boleto	37
btc-transaction	38
btc-wallet	39
cap-alert	40
cap-info	44
cap-resource	48
cloth	49
coin-address	51
command	53
command-line	53
concordia-mtmf-intrusion-set	54
cookie	54
cortex	56
cortex-taxonomy	56
course-of-action	57
covid19-csse-daily-report	59

covid19-dxy-live-city	61
covid19-dxy-live-province	62
cowrie	63
cpe-asset	65
credential	75
credit-card	77
crypto-material	78
cytomic-orion-file	81
cytomic-orion-machine	82
dark-pattern-item	82
ddos	83
device	86
diameter-attack	89
dkim	90
dns-record	91
domain-crawled	93
domain-ip	93
edr-report	94
elf	95
elf-section	99
email	102
employee	105
error-message	106
exploit-poc	106
facebook-account	107
facebook-group	108
facebook-page	110
facebook-post	112
facial-composite	114
fail2ban	115
favicon	116
file	116
forensic-case	121
forensic-evidence	122
forged-document	123
ftm-Airplane	125
ftm-Assessment	127
ftm-Asset	129
ftm-Associate	130
ftm-Audio	131
ftm-BankAccount	134

ftm-Call	136
ftm-Company	137
ftm-Contract	142
ftm-ContractAward	145
ftm-CourtCase	146
ftm-CourtCaseParty	148
ftm-Debt	149
ftm-Directorship	150
ftm-Document	151
ftm-Documentation	154
ftm-EconomicActivity	155
ftm-Email	157
ftm-Event	161
ftm-Family	163
ftm-Folder	164
ftm-HyperText	167
ftm-Image	170
ftm-Land	173
ftm-LegalEntity	175
ftm-License	178
ftm-Membership	181
ftm-Message	182
ftm-Organization	185
ftm-Ownership	188
ftm-Package	189
ftm-Page	192
ftm-Pages	193
ftm-Passport	196
ftm-Payment	197
ftm-Person	198
ftm-PlainText	202
ftm-PublicBody	205
ftm-RealEstate	208
ftm-Representation	210
ftm-Row	211
ftm-Sanction	212
ftm-Succession	213
ftm-Table	214
ftm-TaxRoll	217
ftm-UnknownLink	218
ftm-UserAccount	219

ftm-Vehicle	221
ftm-Vessel	222
ftm-Video	225
ftm-Workbook	228
game-cheat	231
geolocation	234
git-vuln-finder	236
github-user	238
gitlab-user	239
gtp-attack	240
hashlookup	241
http-request	243
identity	245
ilr-impact	248
ilr-notification-incident	248
image	251
impersonation	252
imsi-catcher	253
infrastructure	255
instant-message	257
instant-message-group	259
intel471-vulnerability-intelligence	261
intelmq_event	264
intelmq_report	282
internal-reference	284
interpol-notice	285
iot-device	286
iot-firmware	289
ip-api-address	290
ip-port	292
irc	293
ja3	294
ja3s	295
jarm	296
keybase-account	296
language-content	297
leaked-document	300
legal-entity	301
lnk	302
macho	306
macho-section	306

mactime-timeline-analysis	308
malware-config	309
meme-image	310
microblog	312
mutex	314
narrative	315
netflow	316
network-connection	318
network-profile	319
network-socket	322
news-agency	327
news-media	328
open-data-security	330
organization	332
original-imported-file	334
paloalto-threat-event	334
parler-account	336
parler-comment	337
parler-post	339
passive-dns	342
passive-dns-dnsdbflex	345
passive-ssh	345
paste	346
pcap-metadata	348
pe	350
pe-section	352
person	353
personification	358
pgp-meta	362
phishing	363
phishing-kit	365
phone	366
postal-address	369
probabilistic-data-structure	369
process	371
publication	373
python-etvx-event-log	375
r2graphity	378
ransom-negotiation	381
reddit-account	383
reddit-comment	384

reddit-post	386
reddit-subreddit	388
regexp	390
registry-key	391
regripper-NTUser	393
regripper-sam-hive-single-user	395
regripper-sam-hive-user-group	396
regripper-software-hive-BHO	397
regripper-software-hive-appInit-DLLS	398
regripper-software-hive-application-paths	399
regripper-software-hive-applications-installed	400
regripper-software-hive-command-shell	401
regripper-software-hive-software-run	402
regripper-software-hive-userprofile-winlogon	402
regripper-software-hive-windows-general-info	406
regripper-system-hive-firewall-configuration	408
regripper-system-hive-general-configuration	409
regripper-system-hive-network-information	411
regripper-system-hive-services-drivers	412
report	414
research-scanner	415
rogue-dns	416
rtir	417
sandbox-report	417
sb-signature	419
scheduled-event	419
scrippsco2-c13-daily	422
scrippsco2-c13-monthly	423
scrippsco2-co2-daily	424
scrippsco2-co2-monthly	425
scrippsco2-o18-daily	427
scrippsco2-o18-monthly	427
script	429
security-playbook	430
shell-commands	434
shodan-report	435
short-message-service	436
shortened-link	437
social-media-group	438
software	440
splunk	441

ss7-attack	442
ssh-authorized-keys	449
stix2-pattern	450
submarine	451
suricata	453
target-system	454
tattoo	455
telegram-account	456
temporal-event	457
threatgrid-report	457
timecode	458
timesketch-timeline	459
timesketch_message	459
timestamp	460
tor-hiddenservice	461
tor-node	461
tracking-id	463
transaction	464
translation	466
trustar_report	471
tsk-chats	475
tsk-web-bookmark	476
tsk-web-cookie	477
tsk-web-downloads	478
tsk-web-history	479
tsk-web-search-query	480
twitter-account	481
twitter-list	484
twitter-post	485
url	488
user-account	489
vehicle	492
victim	493
virustotal-graph	496
virustotal-report	496
virustotal-submission	497
vulnerability	498
weakness	500
whois	500
windows-service	501
x509	503

yabin.....	505
yara.....	506
youtube-channel	507
youtube-comment	508
youtube-playlist	510
youtube-video.....	511
Relationships.....	512

Introduction



The MISP threat sharing platform is a free and open source software helping information sharing of threat intelligence including cyber security indicators, financial fraud or counter-terrorism information. The MISP project includes multiple sub-projects to support the operational requirements of analysts and improve the overall quality of information shared.

MISP objects are used in MISP (starting from version 2.4.80) system and can be used by other information sharing tool. MISP objects are in addition to MISP attributes to allow advanced combinations of attributes. The creation of these objects and their associated attributes are based on real cyber security use-cases and existing practices in information sharing. The objects are just shared like any other attributes in MISP even if the other MISP instances don't have the template of the object. The following document is generated from the machine-readable JSON describing the [MISP objects](#).

Funding and Support

The MISP project is financially and resource supported by [CIRCL Computer Incident Response Center Luxembourg](#).



A CEF (Connecting Europe Facility) funding under CEF-TC-2016-3 - Cyber Security has been granted from 1st September 2017 until 31th August 2019 as **Improving MISP as building blocks for next-generation information sharing**.



Co-financed by the European Union
Connecting Europe Facility

If you are interested to co-fund projects around MISP, feel free to get in touch with us.

MISP objects

ail-leak

An information leak as defined by the AIL Analysis Information Leak framework.



ail-leak is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
duplicate	text	Duplicate of the existing leaks.	—	✓
duplicate_number	counter	Number of known duplicates.	✓	—
first-seen	datetime	When the leak has been accessible or seen for the first time.	✓	—
last-seen	datetime	When the leak has been accessible or seen for the last time.	✓	—
origin	text	The link where the leak is (or was) accessible at first-seen.	—	—
original-date	datetime	When the information available in the leak was created. It's usually before the first-seen.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
raw-data	attachment	Raw data as received by the AIL sensor compressed and encoded in Base64.	✓	—
sensor	text	The AIL sensor uuid where the leak was processed and analysed.	✓	—
text	text	A description of the leak which could include the potential victim(s) or description of the leak.	✓	—

ais-info

Automated Indicator Sharing (AIS) Information Source Markings.



ais-info is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
administrative-area	text	AIS Administrative Area represented using ISO-3166-2.	—	—
country	text	AIS Country represented using ISO-3166-1_alpha-2.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
industry	text	AIS IndustryType. ['Chemical Sector', 'Commercial Facilities Sector', 'Communications Sector', 'Critical Manufacturing Sector', 'Dams Sector', 'Defense Industrial Base Sector', 'Emergency Services Sector', 'Energy Sector', 'Financial Services Sector', 'Food and Agriculture Sector', 'Government Facilities Sector', 'Healthcare and Public Health Sector', 'Information Technology Sector', 'Nuclear Reactors, Materials, and Waste Sector', 'Transportation Systems Sector', 'Water and Wastewater Systems Sector', 'Other']	—	✓
organisation	text	AIS Organisation Name.	—	—

android-app

Indicators related to an Android app.



android-app is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
appid	text	Application ID	—	✓
certificate	sha1	Android certificate	—	✓
domain	domain	Domain used by the app	—	✓
name	text	Generic name of the application	—	—
sha256	sha256	SHA256 of the APK.	—	✓

android-permission

A set of android permissions - one or more permission(s) which can be linked to other objects (e.g. malware, app).



android-permission is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	Comment about the set of android permission(s)	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
permission	text	Android permission ['ACCESS_CHECKIN_PROPERTIES', 'ACCESS_COARSE_LOCATION', 'ACCESS_FINE_LOCATION', 'ACCESS_LOCATION_EXTRA_COMMANDS', 'ACCESS_NETWORK_STATE', 'ACCESS_NOTIFICATION_POLICY', 'ACCESS_WIFI_STATE', 'ACCOUNT_MANAGER', 'ADD_VOICEMAIL', 'ANSWER_PHONE_CALLS', 'BATTERY_STATS', 'BIND_ACCESSIBILITY_SERVICE', 'BIND_APPWIDGET', 'BIND_AUTOFILL_SERVICE', 'BIND_CARRIER_MESSAGING_SERVICE', 'BIND_CHOOSER_TARGET_SERVICE', 'BIND_CONDITION_PROVIDER_SERVICE', 'BIND_DEVICE_ADMIN', 'BIND_DREAM_SERVICE', 'BIND_INCALL_SERVICE', 'BIND_INPUT_METHOD', 'BIND_MIDI_DEVICE_SERVICE', 'BIND_NFC_SERVICE'	—	✓
14				

annotation

An annotation object allowing analysts to add annotations, comments, executive summary to a MISP event, objects or attributes.

'BIND_NOTIFICATIONS
ON_LISTENER_SE



annotation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

'VICE',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	An attachment to support the annotation	—	✓
creation-date	datetime	Initial creation of the annotation	—	—
format	text	Format of the annotation ['text', 'markdown', 'asciidoc', 'MultiMarkdown', 'GFM', 'pandoc', 'Fountain', 'CommonWork', 'kramdown-rfc2629', 'rfc7328', 'Extra']	✓	—
modification-date	datetime	Last update of the annotation	—	—
ref	link	Reference(s) to the annotation	—	✓
text	text	Raw text of the annotation	—	—

,
'BROADCAST_STICKY',
'BROADCAST_WAPUSH',
'CALL_PHONE',
'CALL_PRIVILEGE',
'CAMERA',
'CAPTURE_AUDIO_OUTPUT',
'CAPTURE_SECURE'

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	Type of the annotation ['Annotation', 'Executive Summary', 'Introduction', 'Conclusion', 'Disclaimer', 'Keywords', 'Acknowledgement', 'Other', 'Copyright', 'Authors', 'Logo', 'Full Report']	✓	—

anonymisation

Anonymisation object describing an anonymisation technique used to encode MISP attribute values. Reference: <https://www.caida.org/tools/taxonomy/anonymization.xml>.



anonymisation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description of the anonymisation technique or tool used	✓	—

ZE', 'GET_TASKS',
'GLOBAL_SEARCH'

,

'INSTALL_LOCATION_PROVIDER',
'INSTALL_PACKAGES',
'INSTALL_SHORTCUT',
'INSTANT_APP_FOREGROUND_SERVICE',
'INTERNET',
'KILL_BACKGROUND_PROCESSES',
'LOCATION_HARDWARE',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
encryption-function	text	Encryption function or algorithm used to anonymise the attribute ['aes128', 'aes-128-cbc', 'aes-128-cfb', 'aes-128-cfb1', 'aes-128-cfb8', 'aes-128-ctr', 'aes-128-ecb', 'aes-128-ofb', 'aes192', 'aes-192-cbc', 'aes-192-cfb', 'aes-192-cfb1', 'aes-192-cfb8', 'aes-192-ctr', 'aes-192-ecb', 'aes-192-ofb', 'aes-256-cfb', 'aes-256-cfb1', 'aes-256-cfb8', 'aes-256-ctr', 'aes-256-ecb', 'aes-256-ofb', 'bf', 'bf-cbc', 'bf-cfb', 'bf-ecb', 'bf-ofb', 'blowfish', 'camellia128', 'camellia-128-cbc', 'camellia-128-cfb', 'camellia-128-cfb1', 'camellia-128-cfb8', 'camellia-128-ctr', 'camellia-128-ecb', 'camellia-128-ofb', 'camellia192', 'camellia-192-cbc', 'camellia-192-cfb', 'camellia-192-cfb1', 'camellia-192-cfb8', 'camellia-192-ctr', 'camellia-192-ecb', 'camellia-192-ofb', 'camellia256', 'camellia-256-cbc', 'camellia-256-cfb', 'camellia-256-cfb1', 'camellia-256-cfb8',	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
iv	text	Initialisation vector for the encryption function used to anonymise the attribute	✓	—
key	text	Key (such as a PSK in a keyed-hash-function) used to anonymise the attribute	✓	—
keyed-hash-function	text	Keyed-hash function used to anonymise the attribute ['hmac-sha1', 'hmac-md5', 'hmac-sha256', 'hmac-sha384', 'hmac-sha512']	✓	—
level-of-knowledge	text	Level of knowledge of the organisation who created this object ['Only the anonymised data is known', 'Deanonymised data is known'] 'SET_CLOCK', 'SET_TIMEZONE', 'SET_WALLPAPER' , 'SET_WALLPAPER_HINTS', 'SIGNAL_PERSISTENT_PROCESSES', 'STATUS_BAR', 'SYSTEM_ALERT_WINDOW', 'TRANSMIT_IR', 'UNINSTALL_SHORTCUT', 'UPDATE_DEVICE_STATS',	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
method	text	Anonymisation (or pseudo-anonymisation) method(s) used ["hiding - Attribute is replaced with a constant value (typically 0) of the same size. Sometimes called 'black marker'.", 'hash - A hash function maps each attribute to a new (not necessarily unique) attribute.', 'permutation - Maps each original value to a unique new value.', "prefix-preserving - Any two values that had the same n-bit prefix before anonymisation will still have the same n-bit prefix as each other after anonymization. (Would be more accurately called 'prefix-relationship-preserving', because the actual prefix values are not preserved.)", 'shift - Adds a fixed offset to each value/attribute.', 'enumeration - Map each original value to a new value such that	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
regexp	text	Regular expression to perform the anonymisation (reversible or not)	✓	—

apivoid-email-verification

Apivoid email verification API result. Reference: <https://www.apivoid.com/api/email-verify/>.



apivoid-email-verification is a MISP object available in JSON format at **this location**. The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
china_free_email	boolean	True if email is a free China email, i.e 163.com.	✓	—
comment	text	Field for comments or correlating text	✓	—
dirty_words_domain	boolean	True if domain contains dirty/bad words.	✓	—
dirty_words_username	boolean	True if username contains dirty/bad words.	✓	—
disposable	boolean	True if email is disposable, i.e yopmail.com.	✓	—
dmarc_configured	boolean	True if domain has DMARC records configured.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
dmarc_enforced	boolean	True if domain is configured for DMARC and set to an enforcement policy.	✓	—
domain	domain	Email domain.	✓	—
domain_popular	boolean	True if domain is a known popular domain.	✓	—
educational_domain	boolean	True if domain is an educational domain, i.e .edu	✓	—
email	email	The email address that was queried.	—	—
free_email	boolean	True if email is a free email, i.e gmail.com.	✓	—
government_domain	boolean	True if domain is a government domain, i.e .gov	✓	—
has_a_records	boolean	True if domain has A records configured.	✓	—
has_mx_records	boolean	True if domain has MX records configured.	✓	—
has_spf_records	boolean	True if domain has SPF records configured.	✓	—
is_spoofable	boolean	True if domain does not have SPF records or if ~all is not configured.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
police_domain	boolean	True if domain is a police domain (such as polizei , police , etc).	✓	—
risky_tld	boolean	True if domain TLD is risky, i.e .top or .pro.	✓	—
role_address	boolean	True if email is a role address, i.e admin@website.com	✓	—
russian_free_email	boolean	True if email is a free Russian email, i.e mail.ru.	✓	—
score	float	A number between 0 (bad) and 100 (good).	✓	—
should_block	boolean	True if the score is bad (≤ 70) and thus it should be blocked.	✓	—
suspicious_domain	boolean	True if domain is suspicious, i.e known spam or parked.	✓	—
suspicious_email	boolean	True if email is considered suspicious.	✓	—
suspicious_username	boolean	True if username is suspicious, i.e only numbers.	✓	—
username	text	Username part of the email address (email prefix)	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
valid_format	boolean	True if email has a valid format.	✓	—
valid_tld	boolean	True if domain TLD is valid, i.e .com or .co.uk	✓	—

artifact

The Artifact object permits capturing an array of bytes (8-bits), as a base64-encoded string, or linking to a file-like payload. from STIX 2.1 (6.1).



artifact is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
decryption_key	text	Specifies the decryption key for the encrypted binary data (either via payload_bin or url). For example, this may be useful in cases of sharing malware samples, which are often encoded in an encrypted archive.	—	—
encryption_algorithm	text	If the artifact is encrypted, specifies the type of encryption algorithm the binary data (either via payload_bin or url) is encoded in.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hashes	text	Specifies a dictionary of hashes for the contents of the url or the payload_bin. This property MUST be present when the url property is present. (should be file with relationships?)	—	✓
mime_type	mime-type	Whenever feasible, this value SHOULD be one of the values defined in the Template column in the IANA media type registry [Media Types]. Maintaining a comprehensive universal catalog of all extant file types is obviously not possible. When specifying a MIME Type not included in the IANA registry, implementers should use their best judgement so as to facilitate interoperability.	✓	—
payload_bin	text	Specifies the binary data contained in the artifact as a base64-encoded string.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	The value of this property MUST be a valid URL that resolves to the unencoded content.	—	—

asn

Autonomous system object describing an autonomous system which can include one or more network operators management an entity (e.g. ISP) along with their routing policy, routing prefixes or alike.



asn is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
asn	AS	Autonomous System Number	—	—
country	text	Country code of the main location of the autonomous system	—	—
description	text	Description of the autonomous system	—	—
export	text	The outbound routing policy of the AS in RFC 2622 – Routing Policy Specification Language (RPSL) format	—	✓
first-seen	datetime	First time the ASN was seen	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
import	text	The inbound IPv4 routing policy of the AS in RFC 2622 – Routing Policy Specification Language (RPSL) format	—	✓
last-seen	datetime	Last time the ASN was seen	✓	—
mp-export	text	This attribute performs the same function as the export attribute above. The difference is that mp-export allows both IPv4 and IPv6 address families to be specified. The export is described in RFC 4012 – Routing Policy Specification Language next generation (RPSLng), section 4.5. format	—	✓
mp-import	text	The inbound IPv4 or IPv6 routing policy of the AS in RFC 4012 – Routing Policy Specification Language next generation (RPSLng), section 4.5. format	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
subnet-announced	ip-src	Subnet announced	—	✓

attack-pattern

Attack pattern describing a common attack pattern enumeration and classification.



attack-pattern is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
id	text	CAPEC ID.	✓	—
name	text	Name of the attack pattern.	—	—
prerequisites	text	Prerequisites for the attack pattern to succeed.	—	—
references	link	External references	—	✓
related-weakness	weakness	Weakness related to the attack pattern.	—	✓
solutions	text	Solutions for the attack pattern to be countered.	—	—
summary	text	Summary description of the attack pattern.	—	—

authentication-failure-report

Authentication Failure Report.



authentication-failure-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ip-dst	ip-dst	Destination IP.	—	—
ip-src	ip-src	IP address originating the authentication failure.	—	—
total	counter	the number of authentication failures reported.	✓	—
type	text	the type of authentication failure. ['ssh']	✓	—
username	text	the username used.	✓	—

authenticode-signerinfo

Authenticode Signer Info.



authenticode-signerinfo is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
content-type	text	Content type	—	—
digest-base64	text	Signature created by the signing certificate's private key	✓	—
digest_algorithm	text	Algorithm used to hash the file.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
encryption_algorithm	text	Algorithm used to encrypt the digest	✓	—
issuer	text	Issuer of the certificate	✓	—
program-name	text	Program name	—	—
serial-number	text	Serial number of the certificate	✓	—
signature_algorithm	text	Signature algorithm ['SHA1_WITH_RSA_ENCRYPTION', 'SHA256_WITH_RS_A_ENCRYPTION']	✓	—
text	text	Free text description of the signer info	—	—
url	url	Url	—	✓
version	text	Version of the certificate	✓	—

av-signature

Antivirus detection signature.



av-signature is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
datetime	datetime	Datetime	✓	—
signature	text	Name of detection signature	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
software	text	Name of antivirus software	✓	—
text	text	Free text value to attach to the file	✓	—

bank-account

An object describing bank account information based on account description from goAML 4.0.



bank-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
aba-rtn	aba-rtn	ABA routing transit number	—	—
account	bank-account-nr	Account number	—	—
account-name	text	A field to freely describe the bank account details.	—	—
balance	text	The balance of the account after the suspicious transaction was processed.	✓	—
beneficiary	text	Final beneficiary of the bank account.	✓	—
beneficiary-comment	text	Comment about the final beneficiary.	✓	—
branch	text	Branch code or name	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
client-number	text	Client number as seen by the bank.	—	—
closed	datetime	When the account was closed.	✓	—
comments	text	Comments about the bank account.	✓	—
currency-code	text	Currency of the account. ['USD', 'EUR']	✓	—
date-balance	datetime	When the balance was reported.	✓	—
iban	iban	IBAN of the bank account.	—	—
institution-code	text	Institution code of the bank.	✓	—
institution-name	text	Name of the bank or financial organisation.	✓	—
non-banking-institution	boolean	A flag to define if this account belong to a non-banking organisation. If set to true, it's a non-banking organisation. ['True', 'False']	✓	—
opened	datetime	When the account was opened.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
personal-account-type	text	Account type. ['A - Business', 'B - Personal Current', 'C - Savings', 'D - Trust Account', 'E - Trading Account', 'O - Other']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
report-code	text	Report code of the bank account. ['CTR Cash Transaction Report', 'STR Suspicious Transaction Report', 'EFT Electronic Funds Transfer', 'IFT International Funds Transfer', 'TFR Terror Financing Report', 'BCR Border Cash Report', 'UTR Unusual Transaction Report', 'AIF Additional Information File – Can be used for example to get full disclosure of transactions of an account for a period of time without reporting it as a CTR.', 'IRI Incoming Request for Information – International', 'ORI Outgoing Request for Information – International', 'IRD Incoming Request for Information – Domestic', 'ORD Outgoing Request for Information – Domestic']	✓	–

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
status-code	text	Account status at the time of the transaction processed. ['A - Active', 'B - Inactive', 'C - Dormant']	✓	—
swift	bic	SWIFT or BIC as defined in ISO 9362.	✓	—
text	text	A description of the bank account.	✓	—

bgp-hijack

Object encapsulating BGP Hijack description as specified, for example, by [bgpstream.com](#).



bgp-hijack is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
country	text	Country code of the main location of the attacking autonomous system	—	—
description	text	BGP Hijack details	—	—
detected-asn	AS	Detected Autonomous System Number	—	—
end	datetime	Last time the Prefix hijack was seen	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
expected-asn	AS	Expected Autonomous System Number	—	—
start	datetime	First time the Prefix hijack was seen	✓	—
subnet-announced	ip-src	Subnet announced	—	✓

bgp-ranking

BGP Ranking object describing the ranking of an ASN for a given day, along with its position, 1 being the most malicious ASN of the day, with the highest ranking. This object is meant to have a relationship with the corresponding ASN object and represents its ranking for a specific date.



bgp-ranking is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address-family	text	The IP address family concerned by the ranking. ['v4', 'v6']	✓	—
date	datetime	Date for the ranking.	✓	—
position	float	Position of the ASN for a given day.	✓	—
ranking	float	Ranking of the Autonomous System number.	✓	—

blog

Blog post like Medium or WordPress.



blog is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
creation-date	datetime	Initial creation of the blog post.	—	—
embedded-link	url	Site linked by the blog post.	—	✓
embedded-safe-link	link	Safe site linked by the blog post.	—	✓
link	link	Original link into the blog post (Supposed harmless).	—	—
modification-date	datetime	Last update of the blog post.	—	—
post	text	Raw post.	—	—
removal-date	datetime	When the blog post was removed.	—	—
title	text	Title of blog post.	—	—
type	text	Type of blog post. ['Medium', 'WordPress', 'Blogger', 'Tumbler', 'LiveJournal', 'Forum', 'Other']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	Original URL location of the blog post (potentially malicious).	—	—
username	text	Username who posted the blog post.	—	—
username-quoted	text	Username who are quoted into the blog post.	—	✓
verified-username	text	Is the username account verified by the operator of the blog platform. ['Verified', 'Unverified', 'Unknown']	✓	—

boleto

A common form of payment used in Brazil.



boleto is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
beneficiary	text	Final beneficiary of the boleto.	—	—
beneficiary-bank-account	bank-account-nr	Recipient bank account number	—	—
beneficiary-bank-agency	bank-account-nr	Recipient bank agency number	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
boleto-number	text	Boleto code numbers	—	—
creation-date	datetime	Date the boleto was created	✓	—
febraban-code	text	Financial institution code in Brazil that created the boleto.	✓	—
generator-financial-institution	text	Name of the bank or financial organisation that created the boleto.	✓	—
payment-due-date	datetime	Boleto payment date	✓	—
payment-status	text	Inform if boleto was as paid or not ['Not Paid', 'Paid']	✓	—
payment-value	float	The payment boleto value in Brazilian Reais	✓	—
requester	text	Organisation, service or affiliated person that requested creation of the boleto.	—	—

btc-transaction

An object to describe a Bitcoin transaction. Best to be used with bitcoin-wallet.



btc-transaction is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
btc-address	btc	A Bitcoin transactional address	✓	—
time	datetime	Date and time of transaction	✓	—
transaction-number	text	A Bitcoin transaction number in a sequence of transactions	✓	✓
value_BTC	float	Value in BTC at date/time displayed in field 'time'	✓	—
value_EUR	float	Value in EUR with conversion rate as of date/time displayed in field 'time'	✓	—
value_USD	float	Value in USD with conversion rate as of date/time displayed in field 'time'	✓	—

btc-wallet

An object to describe a Bitcoin wallet. Best to be used with bitcoin-transactions.



btc-wallet is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
BTC_received	float	Value of received BTC	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
BTC_sent	float	Value of sent BTC	✓	—
balance_BTC	float	Value in BTC at date/time displayed in field 'time'	✓	—
time	datetime	Date and time of lookup/conversion	✓	—
wallet-address	btc	A Bitcoin wallet address	—	—

cap-alert

Common Alerting Protocol Version (CAP) alert object.



cap-alert is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
addresses	text	<p>The group listing of intended recipients of the alert message. (1) Required when <scope> is “Private”, optional when <scope> is “Public” or “Restricted”. (2) Each recipient SHALL be identified by an identifier or an address. (3) Multiple space-delimited addresses MAY be included. Addresses including whitespace MUST be enclosed in double-quotes.</p>	✓	—
code	text	The code denoting the special handling of the alert message.	✓	—
identifier	text	The identifier of the alert message in a number or string uniquely identifying this message, assigned by the sender.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
incident	text	<p>The group listing naming the referent incident(s) of the alert message. (1) Used to collate multiple messages referring to different aspects of the same incident. (2) If multiple incident identifiers are referenced, they SHALL be separated by whitespace.</p> <p>Incident names including whitespace SHALL be surrounded by double-quotes.</p>	✓	—
msgType	text	<p>The code denoting the nature of the alert message.</p> <ul style="list-style-type: none"> 'Alert', 'Update', 'Cancel', 'Ack', 'Error' 	✓	—
note	text	<p>The text describing the purpose or significance of the alert message.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
references	text	The group listing identifying earlier message(s) referenced by the alert message. (1) The extended message identifier(s) (in the form sender,identifier,s ent) of an earlier CAP message or messages referenced by this one. (2) If multiple messages are referenced, they SHALL be separated by whitespace.	✓	—
restriction	text	The text describing the rule for limiting distribution of the restricted alert message.	✓	—
scope	text	The code denoting the intended distribution of the alert message. ['Public', 'Restricted', 'Private']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sender	text	The identifier of the sender of the alert message which identifies the originator of this alert. Guaranteed by assigner to be unique globally; e.g., may be based on an Internet domain name.	✓	—
sent	datetime	The time and date of the origination of the alert message.	✓	—
source	text	The text identifying the source of the alert message. The particular source of this alert; e.g., an operator or a specific device.	✓	—
status	text	The code denoting the appropriate handling of the alert message. ['Actual', 'Exercise', 'System', 'Test', 'Draft']	—	—

cap-info

Common Alerting Protocol Version (CAP) info object.



cap-info is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
audience	text	The text describing the intended audience of the alert message.	✓	—
category	text	The code denoting the category of the subject event of the alert message. ['Geo', 'Met', 'Safety', 'Security', 'Rescue', 'Fire', 'Health', 'Env', 'Transport', 'Infra', 'CBRNE', 'Other']	✓	—
certainty	text	The code denoting the certainty of the subject event of the alert message. For backward compatibility with CAP 1.0, the deprecated value of “Very Likely” SHOULD be treated as equivalent to “Likely”. ['Likely', 'Possible', 'Unlikely', 'Unknown']	✓	—
contact	text	The text describing the contact for follow-up and confirmation of the alert message.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	The text describing the subject event of the alert message.	✓	—
effective	datetime	The effective time of the information of the alert message.	✓	—
event	text	The text denoting the type of the subject event of the alert message.	✓	—
eventCode	text	A system-specific code identifying the event type of the alert message.	✓	—
expires	datetime	The expiry time of the information of the alert message.	✓	—
headline	text	The text headline of the alert message.	✓	—
instruction	text	The text describing the recommended action to be taken by recipients of the alert message.	✓	—
language	text	The code denoting the language of the info sub-element of the alert message.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
onset	datetime	The expected time of the beginning of the subject event of the alert message.	✓	—
parameter	text	A system-specific additional parameter associated with the alert message.	✓	—
responseType	text	The code denoting the type of action recommended for the target audience. ['Shelter', 'Evacuate', 'Prepare', 'Execute', 'Avoid', 'Monitor', 'Assess', 'AllClear', 'None']	✓	—
senderName	text	The text naming the originator of the alert message.	✓	—
severity	text	The code denoting the severity of the subject event of the alert message. ['Extreme', 'Severe', 'Moderate', 'Minor', 'Unknown']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
urgency	text	The code denoting the urgency of the subject event of the alert message. ['Immediate', 'Expected', 'Future', 'Past', 'Unknown']	✓	—
web	link	The identifier of the hyperlink associating additional information with the alert message.	✓	—

cap-resource

Common Alerting Protocol Version (CAP) resource object.



cap-resource is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
derefUri	attachment	The base-64 encoded data content of the resource file.	✓	—
digest	sha1	The code representing the digital digest (“hash”) computed from the resource file (OPTIONAL).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
mimeType	mime-type	The identifier of the MIME content type and sub-type describing the resource file.	✓	—
resourceDesc	text	The text describing the type and content of the resource file.	✓	—
size	text	The integer indicating the size of the resource file.	✓	—
uri	link	The identifier of the hyperlink for the resource file.	—	—

cloth

Describes clothes a natural person wears.



cloth is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bottom-accessories	text	Cloth and accessories on the bottom part of the body ['trousers', 'skirt', 'underpants / panties', 'shorts', 'boxer shorts', 'body stocking', 'sock', 'shoe', 'boot', 'sandal', 'slipper', 'sneaker', 'hiking boot', 'high tops']	—	✓
cloth-color	text	Cloth's colors ['black', 'white', 'red', 'green', 'blue', 'cyan', 'orange', 'violet', 'pink', 'yellow', 'brown', 'grey']	—	✓
cloth-picture	attachment	Cloth's pictures	—	✓
description	text	Cloth's Description of a natural person	—	—
head-accessories	text	Cloth and accessories on the head ['hat', 'cap', 'bonnet', 'glasses', 'bandeau']	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
top-accessories	text	Cloth and accessories on the top part of the body ['jacket', 'coat', 'dress', 'shirt', 'top', 'pullover', 'sweatshirt', 'suit', 'tie', 'bow tie', "lady's suit", 'waistcoat', 'cardigan', 'undershirt', 't-shirt', 'bra', 'scarf', 'glove']	—	✓

coin-address

An address used in a cryptocurrency.



coin-address is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	btc	Bitcoin address used as a payment destination in a cryptocurrency	—	—
address-xmr	xmr	Monero address used as a payment destination in a cryptocurrency	—	—
current-balance	float	Current balance of address	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
first-seen	datetime	First time this payment destination address has been seen	✓	—
last-seen	datetime	Last time this payment destination address has been seen	✓	—
last-updated	datetime	Last time the balances and totals have been updated	✓	—
symbol	text	The (uppercase) symbol of the cryptocurrency used. Symbol should be from https://coinmarketcap.com/all/views/all/ ['BTC', 'ETH', 'BCH', 'XRP', 'MIOTA', 'DASH', 'BTG', 'LTC', 'ADA', 'XMR', 'ETC', 'NEO', 'NEM', 'EOS', 'XLM', 'BCC', 'LSK', 'OMG', 'QTUM', 'ZEC', 'USDT', 'HSR', 'STRAT', 'WAVES', 'PPT', 'ETN']	✓	—
text	text	Free text value	✓	—
total-received	float	Total balance received	✓	—
total-sent	float	Total balance sent	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
total-transactions	text	Total transactions performed	✓	—

command

Command functionalities related to specific commands executed by a program, whether it is malicious or not. Command-line are attached to this object for the related commands.



command is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description of the command functionalities	—	—
location	text	Location of the command functionality ['Bundled', 'Module', 'Libraries', 'Unknown']	✓	—
trigger	text	How the commands are triggered ['Local', 'Network', 'Unknown']	✓	—

command-line

Command line and options related to a specific command executed by a program, whether it is malicious or not.



command-line is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	description of the command	—	—
value	text	command code	—	✓

concordia-mtmf-intrusion-set

Intrusion Set - Phase Description.



concordia-mtmf-intrusion-set is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
AttackName	text	Name of the Attack	—	—
CMTMF_ATCKID	counter	Identifier of the Attack	—	—
FeedbackLoop	counter	Feedback Loop Sequence	—	—
PhName	text	Name of the Phase (Tactic)	✓	—
PhSequence	counter	Phase Sequence	✓	—
description	text	Description of the phase	✓	—

cookie

An HTTP cookie (web cookie, browser cookie) is a small piece of data that a server sends to the user's web browser. The browser may store it and send it back with the next request to the same server. Typically, it's used to tell if two requests came from the same browser — keeping a user logged-in, for example. It remembers stateful information for the stateless HTTP protocol. (as defined by the Mozilla foundation).



cookie is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cookie	cookie	Full cookie	—	—
cookie-name	text	Name of the cookie (if splitted)	—	—
cookie-value	text	Value of the cookie (if splitted)	—	—
expires	datetime	Expiration date/time of the cookie	✓	—
http-only	boolean	True if send only through HTTP ['True', 'False']	✓	—
path	text	Path defined in the cookie	✓	—
secure	boolean	True if cookie is sent over TLS ['True', 'False']	✓	—
text	text	A description of the cookie.	✓	—
type	text	Type of cookie and how it's used in this specific object. ['Session management', 'Personalization', 'Tracking', 'Exfiltration', 'Malicious Payload', 'Beaconing']	—	—

cortex

Cortex object describing a complete cortex analysis. Observables would be attribute with a relationship from this object.



cortex is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
full	text	Cortex report object (full report) in JSON	✓	—
name	text	Cortex analyser/worker name	✓	—
server-name	text	Name of the cortex server	✓	—
start-date	datetime	When the Cortex analyser was started	✓	—
success	boolean	Result of the cortex job ['True', 'False']	✓	—
summary	text	Cortex summary object (summary) in JSON	—	—

cortex-taxonomy

Cortex object describing an Cortex Taxonomy (or mini report).



cortex-taxonomy is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cortex_url	link	URL to the Cortex job	✓	—
level	text	Cortex Taxonomy Level ['info', 'safe', 'suspicious', 'malicious']	✓	—
namespace	text	Cortex Taxonomy Namespace	✓	—
predicate	text	Cortex Taxonomy Predicate	✓	—
value	text	Cortex Taxonomy Value	✓	—

course-of-action

An object describing a specific measure taken to prevent or respond to an attack.



course-of-action is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cost	text	The estimated cost of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓	—
description	text	A description of the course of action.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
efficacy	text	The estimated efficacy of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓	—
impact	text	The estimated impact of applying the course of action. ['High', 'Medium', 'Low', 'None', 'Unknown']	✓	—
name	text	The name used to identify the course of action.	✓	—
objective	text	The objective of the course of action.	✓	—
stage	text	The stage of the threat management lifecycle that the course of action is applicable to. ['Remedy', 'Response', 'Further Analysis Required']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	The type of the course of action. ['Perimeter Blocking', 'Internal Blocking', 'Redirection', 'Redirection (Honey Pot)', 'Hardening', 'Patching', 'Eradication', 'Rebuilding', 'Training', 'Monitoring', 'Physical Access Restrictions', 'Logical Access Restrictions', 'Public Disclosure', 'Diplomatic Actions', 'Policy Actions', 'Other']	✓	—

covid19-csse-daily-report

CSSE COVID-19 Daily report.



covid19-csse-daily-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
active	counter	the number of active cases.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
confirmed	counter	the number of confirmed cases. For Hubei Province: from Feb 13 (GMT +8), we report both clinically diagnosed and lab-confirmed cases. For lab-confirmed cases only (Before Feb 17), please refer to https://github.com/CSSEGISandData/COVID-19/tree/master/who_covid_19_situation_reports .	✓	—
country-region	text	country/region name conforming to WHO (will be updated).	✓	—
county	counter	US County (US Only)	✓	—
death	counter	the number of deaths.	✓	—
fips	counter	Federal Information Processing Standard county code (US Only)	✓	—
latitude	float	Approximate latitude of the entry	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
longitude	float	Approximate longitude of the entry	✓	—
province-state	text	province name; US/Canada/Australia/ - city name, state/province name; Others - name of the event (e.g., "Diamond Princess" cruise ship); other countries - blank.	✓	—
recovered	counter	the number of recovered cases.	✓	—
update	datetime	Time of the last update that day (UTC)	✓	—

covid19-dxy-live-city

COVID 19 from dxy.cn - Aggregation by city.



covid19-dxy-live-city is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
city	text	Name of the Chinese city, in Chinese.	✓	—
current-confirmed	counter	Current number of confirmed cases	✓	—
total-confirmed	counter	Total number of confirmed cases.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
total-cured	counter	Total number of cured cases.	✓	—
total-death	counter	Total number of deaths.	✓	—
update	datetime	Approximate time of the update (~hour)	✓	—

covid19-dxy-live-province

COVID 19 from dxy.cn - Aggregation by province.



covid19-dxy-live-province is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Comment, in chinese	✓	—
current-confirmed	counter	Current number of confirmed cases	✓	—
province	text	Name of the Chinese province, in Chinese.	✓	—
total-confirmed	counter	Total number of confirmed cases.	✓	—
total-cured	counter	Total number of cured cases.	✓	—
total-death	counter	Total number of deaths.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
update	datetime	Approximate time of the update (~hour)	✓	—

cowrie

Cowrie honeypot object template.



cowrie is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
compCS	text	SSH compression algorithm supported in the session	✓	✓
dst_ip	ip-dst	Destination IP address of the session	✓	—
dst_port	port	Destination port of the session	✓	—
encCS	text	SSH symmetric encryption algorithm supported in the session	✓	✓
eventid	text	Eventid of the session in the cowrie honeypot	✓	—
hassh	hassh-md5	HASSH of the client SSH session following Salesforce algorithm	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
input	text	Input of the session	—	—
isError	text	isError	✓	—
keyAlgs	text	SSH public-key algorithm supported in the session	✓	✓
macCS	text	SSH MAC supported in the session	✓	✓
message	text	Message of the cowrie honeypot	✓	—
password	text	Password	—	✓
protocol	text	Protocol used in the cowrie honeypot	✓	—
sensor	text	Cowrie sensor name	✓	—
session	text	Session id	—	—
src_ip	ip-src	Source IP address of the session	—	—
src_port	port	Source port of the session	✓	—
system	text	System origin in cowrie honeypot	✓	—
timestamp	datetime	When the event happened	✓	—
username	text	Username related to the password(s)	—	—

cpe-asset

An asset which can be defined by a CPE. This can be a generic asset. CPE is a structured naming scheme for information technology systems, software, and packages.



cpe-asset is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cpe	cpe	CPE—the well-formed CPE name(WFN). WFNs can be used to describe a set of products or to identify an individual product.	—	—
description	text	Complementary description of the asset	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
edition	text	<p>The edition attribute is considered deprecated in this specification, and it SHOULD be assigned the logical value ANY except where required for backward compatibility with version 2.2 of the CPE specification. This attribute is referred to as the “legacyedition” attribute. If this attribute is used, values for this attribute SHOULD capture edition-related terms applied by the vendor to the product. Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAY be defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs (cf. 5.3.2) MAY be specified as the value of the attribute.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
language	text	<p>Values for this attribute SHALL be valid language tags as defined by [RFC5646], and SHOULD be used to define the language supported in the user interface of the product being described. Although any valid language tag MAY be used, only tags containing language and region codes SHOULD be used.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
other	text	<p>Values for this attribute SHOULD capture any other general descriptive or identifying information which is vendor- or product-specific and which does not logically fit in any other attribute value.</p> <p>Values SHOULD NOT be used for storing instance-specific data (e.g., globally-unique identifiers or Internet Protocol addresses). Values for this attribute SHOULD be selected from a valid-values list that is refined over time; this list MAYbe defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs (cf. 5.3.2) MAYbe specified as the value of the attribute.</p>	✓	—
part	text	Part - application, operating systems or hardware devices ['a', 'o', 'h']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
product	text	<p>Values for this attribute SHOULD describe or identify the most common and recognizable title or name of the product. Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAY be defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs(cf. 5.3.2) MAY be specified as the value of the attribute.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sw_edition	text	<p>Values for this attribute SHOULD characterize how the product is tailored to a particular market or class of end users. Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAYbe defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs(cf. 5.3.2) MAYbe specified as the value of the attribute.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
target_hw	text	<p>Values for this attribute SHOULD characterize the instruction set architecture (e.g., x86) on which the product being described or identified by the WFN operates.</p> <p>Bytecode-intermediate languages, such as Java bytecode for the Java Virtual Machine or Microsoft Common Intermediate Language for the Common Language Runtime virtual machine, SHALL be considered instruction set architectures.</p> <p>Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAYbe defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs(cf. 5.3.2) MAYbe specified as the value of the attribute.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
target_sw	text	<p>Values for this attribute SHOULD characterize the software computing environment within which the product operates. Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAY be defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs(cf. 5.3.2) MAY be specified as the value of the attribute.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
update	text	<p>Values for this attribute SHOULD be vendor-specific alphanumeric strings characterizing the particular update, service pack, or point release of the product. Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAYbe defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs (cf. 5.3.2) MAYbe specified as the value of the attribute.</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
vendor	text	<p>Values for this attribute SHOULD describe or identify the person or organization that manufactured or created the product. Values for this attribute SHOULD be selected from an attribute-specific valid-values list, which MAY be defined by other specifications that utilize this specification. Any character string meeting the requirements for WFNs (cf. 5.3.2) MAY be specified as the value of the attribute</p>	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
version	text	Values for this attribute SHOULD be vendor-specific alphanumeric strings characterizing the particular release version of the product. Version information SHOULD be copied directly (with escaping of printable non-alphanumeric characters as required) from discoverable data and SHOULD NOT be truncated or otherwise modified. Any character string meeting the requirements for WFNs (cf. 5.3.2) MAY be specified as the value of the attribute.	✓	—

credential

Credential describes one or more credential(s) including password(s), api key(s) or decryption key(s).



credential is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
format	text	Format of the password(s) ['clear-text', 'hashed', 'encrypted', 'unknown']	✓	—
notification	text	Mention of any notification(s) towards the potential owner(s) of the credential(s) ['victim-notified', 'service-notified', 'none']	✓	✓
origin	text	Origin of the credential(s) ['bruteforce-scanning', 'malware-analysis', 'memory-analysis', 'network-analysis', 'leak', 'unknown']	✓	—
password	text	Password	—	✓
text	text	A description of the credential(s)	✓	—
type	text	Type of password(s) ['password', 'api-key', 'encryption-key', 'unknown']	✓	—
username	text	Username related to the password(s)	—	—

credit-card

A payment card like credit card, debit card or any similar cards which can be used for financial transactions.



credit-card is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bank_name	text	Name of the bank which have issued the card	—	—
card-security-code	text	Card security code (CSC, CVD, CVV, CVC and SPC) as embossed or printed on the card.	—	—
cc-number	cc-number	credit-card number as encoded on the card.	—	—
comment	comment	A description of the card.	—	—
expiration	datetime	Maximum date of validity	—	—
iin	text	International Issuer Number (First eight digits of the credit card number)	—	—
issued	datetime	Initial date of validity or issued date.	—	—
name	text	Name of the card owner.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
version	text	Version of the card.	—	—

crypto-material

Cryptographic materials such as public or/and private keys.



crypto-material is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Gx	text	Curve Parameter - Gx in decimal	✓	—
Gy	text	Curve Parameter - Gy in decimal	✓	—
b	text	Curve Parameter - B in decimal	✓	—
curve-length	text	Length of the Curve in bits	✓	—
e	text	RSA public exponent	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ecdsa-type	text	Curve type of the ECDSA cryptographic materials ['Anomalous', 'M-221', 'E-222', 'NIST P-224', 'Curve1174', 'Curve25519', 'BN(2,254)', 'brainpoolP256t1', 'ANSSI FRP256v1', 'NIST P-256', 'secp256k1', 'E-382', 'M-383', 'Curve383187', 'brainpoolP384t1', 'NIST P-384', 'Curve41417', 'Ed448-Goldilocks', 'M-511', 'E-521']	✓	—
g	text	Curve Parameter - G in decimal	✓	—
generic-symmetric-key	text	Generic symmetric key (please precise the type)	—	—
modulus	text	Modulus Parameter - in hexadecimal - no 0x, no :	—	—
n	text	Curve Parameter - N in decimal	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
origin	text	Origin of the cryptographic materials ['mathematical-attack', 'exhaustive-search', 'bruteforce-attack', 'malware-extraction', 'memory-interception', 'network-interception', 'leak', 'unknown']	✓	—
p	text	Prime Parameter - P in decimal	—	—
private	text	Private part of the cryptographic materials in PEM format	—	—
public	text	Public part of the cryptographic materials in PEM format	—	—
q	text	Prime Parameter - Q in decimal	—	—
rsa-modulus-size	text	RSA modulus size in bits	✓	—
text	text	A description of the cryptographic materials.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	Type of cryptographic materials ['RSA', 'DSA', 'ECDSA', 'RC4', 'XOR', 'unknown']	✓	—
x	text	Curve Parameter - X in decimal	✓	—
y	text	Curve Parameter - Y in decimal	✓	—

cytomic-orion-file

Cytomic Orion File Detection.



cytomic-orion-file is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
classification	text	File classification - number	—	—
classificationName	text	File classification	—	—
fileName	filename	Original filename	—	—
fileSize	size-in-bytes	Size of the file	—	—
first-seen	datetime	First seen timestamp of the file	—	—
last-seen	datetime	Last seen timestamp of the file	—	—

cytomic-orion-machine

Cytomic Orion File at Machine Detection.



cytomic-orion-machine is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
clientCreationDate UTC	datetime	Client creation date UTC	—	—
clientId	text	Client id	—	—
clientName	target-org	Client name	—	—
creationDate	datetime	Client creation date	—	—
first-seen	datetime	First seen on machine	—	—
last-seen	datetime	Last seen on machine	—	—
lastSeenUtc	datetime	Client last seen UTC	—	—
machineMuid	text	Machine UID	—	—
machineName	target-machine	Machine name	—	—
machinePath	text	Path of observable	—	—

dark-pattern-item

An Item whose User Interface implements a dark pattern.



dark-pattern-item is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	textual comment about the item	✓	—
gain	text	What is the implementer is gaining by deceiving the user ['registration', 'personal data', 'money', 'contacts', 'audience']	✓	—
implementer	text	Who is the vendor / holder of the item	✓	—
location	text	Location where to find the item	✓	✓
screenshot	attachment	A screencapture or a screengrab of the item at work	✓	—
time	datetime	Date and time when first-seen	✓	—
user	text	who are the user of the item	✓	—

ddos

DDoS object describes a current DDoS activity from a specific or/and to a specific target. Type of DDoS can be attached to the object as a taxonomy or using the type field.



ddos is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
backscatter-threshold	counter	The minimum amount of backscatter received in 5 minutes / day. This field is only used when the capture origin is indirect network capture such as backscatter.	✓	—
capture-origin	text	Origin of the (D)DoS evidences ['Direct network capture', 'Logs', 'Indirect network capture (e.g. backscatter)', 'Unknown']	✓	—
domain-dst	domain	Destination domain (victim)	—	—
dst-port	port	Destination port of the attack	—	✓
first-seen	datetime	Beginning of the attack	✓	—
ip-dst	ip-dst	Destination IP (victim)	—	—
ip-src	ip-src	IP address originating the attack	—	✓
last-seen	datetime	End of the attack	✓	—
protocol	text	Protocol used for the attack ['TCP', 'UDP', 'ICMP', 'IP']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
src-port	port	Port originating the attack	—	✓
text	text	Description of the DDoS	✓	—
total-bps	counter	Bits per second (maximum rate of bits per second measured)	✓	—
total-bytes-sent	counter	Total number of bytes sent by the sources mentioned	✓	—
total-packets-sent	counter	Total number of packets sent by the source mentioned	✓	—
total-pps	counter	Packets per second (maximum rate of packets per second measured)	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	Type(s) or Technique(s) of Denial of Service ['amplification-attack', 'reflected-spoofed-attack', 'slow-read-attack', 'flooding-attack', 'post-attack', 'chargen-amplification', 'dns', 'dns-amplification', 'ip-fragmentation', 'ip-private', 'icmp', 'memcached-amplification', 'ms-sql-rs-amplification', 'ntp-amplification', 'snmp-amplification', 'ssdp-amplification', 'tcp-null', 'tcp-rst', 'tcp-syn', 'udp']	✓	✓

device

An object to define a device.



device is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
MAC-address	mac-address	Device MAC address	—	—
OS	text	OS of the device	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alias	text	Alias of the Device	—	✓
analysis-date	datetime	Date of device analysis	—	—
attachment	attachment	An attachment	—	✓
description	text	Description of the Device	✓	—
device-type	text	Type of the device ['PC', 'Mobile', 'Laptop', 'HID', 'TV', 'IoT', 'Hardware', 'Other']	✓	—
dns-name	text	Device DNS Name	—	✓
hits	counter	Number of hits for the device	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
infection_type	text	Type of infection if the device is in Infected status ['android_spams', 'android.bakdoor.prizmes', 'android.bankbot', 'android.banker.anubis', 'android.bankspy', 'android.cliaid', 'android.darksilent', 'android.fakeav', 'android.fakebank', 'android.fakedoc', 'android.fakeinst', 'android.fakemart', 'android.faketoken', 'android.fobus', 'android.fungram', 'android.geost', 'android.gopl', 'android.hiddad', 'android.hqwar', 'android.hummer', 'android.infosteal', 'android.iop', 'android.lockdroid', 'android.milipnot', 'android.nitmo', 'android.opfake', 'android.premiumtext', 'android.provar', 'android.pwstealer', 'android.rootnik', 'android.skyfin', 'android.smsbot', 'android.smssilence', 'android.smsspy', 'android.smsspy.be24', 'android.trojan', 'android.virus', 'android.worm']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ip-address	ip-src	Device IP address	—	✓
name	text	Name of the Device	—	—
status	text	Status of the device ['Infected', 'Exposed', 'Unknown', 'Clean']	✓	—
version	text	Version of the device/ OS	✓	—

diameter-attack

Attack as seen on the diameter signaling [phonelock](#) targeting LTE networks.
 'untrap',
 'caphaw',
 'carberp', 'chafer',
 'changeup',
 'cobint',



diameter-attack is a MISP [object](#) available in JSON format at [this location](#). The JSON format can be freely [modified](#) in your application or automatically enabled in MISP.
 'cryptowall',
 'cutwail', 'cycbot',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ApplicationId	text	Application-ID is used to identify for which Diameter application the message is applicable. Application-ID is a decimal representation.	—	—
CmdCode	text	A decimal representation of the diameter Command Code.	✓	—
Destination-Host	text	Destination-Host.	—	✓

'flux-double', 'fast-flux;fast-flux-double',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Destination-Realm	text	Destination-Realm.	—	✓
IdrFlags	text	IDR-Flags.	✓	—
Origin-Host	text	Origin-Host.	—	✓
Origin-Realm	text	Origin-Realm.	—	✓
SessionId	text	Session-ID.	—	—
Username	text	Username (in this case, usually the IMSI).	—	✓
category	text	Category. ['Cat0', 'Cat1', 'Cat2', 'Cat3', 'CatSMS']	✓	—
first-seen	datetime	When the attack has been seen for the first time.	✓	—
text	text	A description of the attack seen.	✓	—

dkim

DomainKeys Identified Mail - DKIM.



dkim is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
d	domain	DKIM domain used for the selector record	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
dkim	dkim	DomainKeys Identified Mail - DKIM full DNS TXT record	—	—
h	text	DKIM hash type ['sha1', 'md5']	✓	—
k	text	DKIM key type ['rsa']	✓	—
n	text	DKIM administrator note	✓	—
public-key	text	DKIM public key	—	—
s	text	DKIM service record	✓	—
t	text	DKIM domain testing ['y', 's']	✓	—
version	text	DKIM version ['DKIM1']	✓	—

dns-record

A set of DNS records observed for a specific domain.



dns-record is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
a-record	ip-dst	IPv4 address associated with A record	—	✓

e', 'rat.vermin',
 'renocide', 'revil',
 'rodecap', 'sality',
 'sality-p2p',
 'servhelper',
 'sgminer', 'shifu',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
aaaa-record	ip-dst	IPv6 address associated with AAAA record	—	✓
cname-record	domain	Domain associated with CNAME record	—	✓
mx-record	domain	Domain associated with MX record	—	✓
ns-record	domain	Domain associated with NS record	—	✓
ptr-record	domain	Domain associated with PTR record	—	✓
queried-domain	domain	Domain name	—	—
soa-record	domain	Domain associated with SOA record	—	✓
spf-record	ip-dst	IP addresses associated with SPF record	—	✓
srv-record	domain	Domain associated with SRV record	—	✓
text	text	A description of the records	—	—
txt-record	text	Content associated with TXT record zeus_gameover, 'zeus_panda', 'zloader']	—	✓

domain-crawled

A domain crawled over time.



domain-crawled is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
domain	domain	Domain name	—	—
text	text	A description of the tuple	✓	—
url	url	domain url	—	✓

domain-ip

A domain/hostname and IP address seen as a tuple in a specific time frame.



domain-ip is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
domain	domain	Domain name	—	✓
first-seen	datetime	First time the tuple has been seen	✓	—
hostname	hostname	Hostname related to the IP	—	—
ip	ip-dst	IP Address	—	✓
last-seen	datetime	Last time the tuple has been seen	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
port	port	Associated TCP port with the domain	—	—
registration-date	datetime	Registration date of domain	—	—
text	text	A description of the tuple	✓	—

edr-report

An Object Template to encode an EDR detection report.



edr-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
additional-file	attachment	Additional file involved in detection	✓	✓
command	attachment	JSON file containing the output of a command ran at report generation	✓	✓
comment	text	Any valuable comment about the report	✓	—
drivers	attachment	JSON file containing metadata about drivers loaded on the system	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
endpoint-id	text	Unique identifier of the endpoint concerned by the report	—	—
event	attachment	Raw EDR event which triggered reporting	✓	—
executable	attachment	Executable file involved in detection	✓	✓
hostname	text	Endpoint hostname	—	—
id	text	Report unique identifier	—	—
ip	ip-src	Endpoint IP address	✓	—
modules	attachment	JSON file containing metadata about modules loaded on the system	✓	—
processes	attachment	JSON file containing metadata about running processes at the time of detection	✓	—
product	text	EDR product name	✓	—

elf

Object describing a Executable and Linkable Format.



elf is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
arch	text	Architecture of the ELF file ['None', 'M32', 'SPARC', 'i386', 'ARCH_68K', 'ARCH_88K', 'IAMCU', 'ARCH_860', 'MIPS', 'S370', 'MIPS_RS3_LE', 'PARISC', 'VPP500', 'SPARC32PLUS', 'ARCH_960', 'PPC', 'PPC64', 'S390', 'SPU', 'V800', 'FR20', 'RH32', 'RCE', 'ARM', 'ALPHA', 'SH', 'SPARCV9', 'TRICORE', 'ARC', 'H8_300', 'H8_300H', 'H8S', 'H8_500', 'IA_64', 'MIPS_X', 'COLDFIRE', 'ARCH_68HC12', 'MMA', 'PCP', 'NCPU', 'NDR1', 'STARCORE', 'ME16', 'ST100', 'TINYJ', 'x86_64', 'PDSP', 'PDP10', 'PDP11', 'FX66', 'ST9PLUS', 'ST7', 'ARCH_68HC16', 'ARCH_68HC11', 'ARCH_68HC08', 'ARCH_68HC05', 'SVX', 'ST19', 'VAX', 'CRIS', 'JAVELIN', 'FIREPATH', 'ZSP', 'MMIX', 'HUANY', 'PRISM', 'AVR', 'FR30', 'D10V', 'D30V', 'V850', 'M32R', 'MN10300', 'MN10200', 'PJ', 'OPENRISC',	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
entrypoint-address	text	Address of the entry point	✓	—
number-sections	counter	Number of sections	✓	—
os_abi	text	Header operating system application binary interface (ABI) ['AIX', 'ARM', 'AROS', 'C6000_ELFABI', 'C6000_LINUX', 'CLOUDABI', 'FENIXOS', 'FREEBSD', 'GNU', 'HPUX', 'HURD', 'IRIX', 'MODESTO', 'NETBSD', 'NSK', 'OPENBSD', 'OPENVMS', 'SOLARIS', 'STANDALONE', 'SYSTEMV', 'TRU64']	✓	—
text	text	Free text value to attach to the ELF	✓	—
type	text	Type of ELF ['CORE', 'DYNAMIC', 'EXECUTABLE', 'HIPROC', 'LOPROC', 'NONE', 'RELOCATABLE']	✓	—

elf-section

Object describing a section of an Executable and Linkable Format.



elf-section is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

'AVR32', 'STM8',
'TILE64',
'TILEPRO', 'CUDA',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
entropy	float	Entropy of the whole section	✓	—
flag	text	Flag of the section ['ALLOC', 'EXCLUDE', 'EXECINSTR', 'GROUP', 'HEX_GPREL', 'INFO_LINK', 'LINK_ORDER', 'MASKOS', 'MASKPROC', 'MERGE', 'MIPS_ADDR', 'MIPS_LOCAL', 'MIPS_MERGE', 'MIPS_NAMES', 'MIPS_NODUPES', 'MIPS_NOSTrip', 'NONE', 'OS_NONCONFORMING', 'STRINGS', 'TLS', 'WRITE', 'XCORE_SHF_CP_SELECTION']	✓	✓
md5	md5	[Insecure] MD5 hash (128 bits)	—	—
name	text	Name of the section	✓	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓	—
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—	—
text	text	Free text value to attach to the section	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	Type of the section ['NULL', 'PROGBITS', 'SYMTAB', 'STRTAB', 'RELA', 'HASH', 'DYNAMIC', 'NOTE', 'NOBITS', 'REL', 'SHLIB', 'DYNSYM', 'INIT_ARRAY', 'FINI_ARRAY', 'PREINIT_ARRAY', 'GROUP', 'SYMTAB_SHNDX', 'LOOS', 'GNU_ATTRIBUTE S', 'GNU_HASH', 'GNU_VERDEF', 'GNU_VERNEED', 'GNU_VERSYM', 'HIOS', 'LOPROC', 'ARM_EXIDX', 'ARM_PREEMPTM AP', 'HEX_ORDERED', 'X86_64_UNWIND', 'MIPS_REGINFO', 'MIPS_OPTIONS', 'MIPS_ABIFLAGS', 'HIPROC', 'LOUSER', 'HIUSER']	✓	—

email

Email object describing an email with meta-information.



email is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	email-attachment	Attachment	—	✓
bcc	email-dst	Blind carbon copy	✓	✓
bcc-display-name	email-dst-display-name	Display name of the blind carbon copy	—	✓
cc	email-dst	Carbon copy	✓	✓
cc-display-name	email-dst-display-name	Display name of the carbon copy	—	✓
email-body	email-body	Body of the email	✓	✓
eml	attachment	Full EML	✓	—
from	email-src	Sender email address	—	✓
from-display-name	email-src-display-name	Display name of the sender	—	✓
from-domain	domain	Sender domain address (when only the source domain is known)	—	✓
header	email-header	Full headers	✓	✓
ip-src	ip-src	Source IP address of the email sender	—	✓
message-id	email-message-id	Message ID	✓	—
mime-boundary	email-mime-boundary	MIME Boundary	✓	—
msg	attachment	Full MSG	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
received-header-hostname	hostname	Extracted hostname from parsed headers	—	✓
received-header-ip	ip-src	Extracted IP address from parsed headers	—	✓
reply-to	email-reply-to	Email address the reply will be sent to	—	✓
reply-to-display-name	email-dst-display-name	Display name of the email address the reply will be sent to	—	✓
return-path	email-src	Message return path	—	—
screenshot	attachment	Screenshot of email	✓	—
send-date	datetime	Date the email has been sent	✓	—
subject	email-subject	Subject	—	✓
thread-index	email-thread-index	Identifies a particular conversation thread	✓	—
to	email-dst	Destination email address	✓	✓
to-display-name	email-dst-display-name	Display name of the receiver	—	✓
user-agent	text	User Agent of the sender	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
x-mailer	email-x-mailer	X-Mailer generally tells the program that was used to draft and send the original email	✓	—

employee

An employee and related data points.



employee is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
business-unit	target-org	the organizational business unit associated with the employee	✓	—
email-address	target-email	Employee Email Address	—	—
employee-type	text	type of employee ['Mid-Level Manager', 'Senior Manager', 'Non-Manager', 'Supervisor', 'First-Line Manager', 'Director']	✓	—
first-name	first-name	Employee's first name	✓	—
full-name	full-name	Employee's full name	✓	—
last-name	last-name	Employee's last name	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
primary-asset	target-machine	Asset tag of the primary asset assigned to employee	—	—
text	text	A description of the person or identity.	✓	—
userid	target-user	EMployee user identification	✓	—

error-message

An error message which can be related to the processing of data such as import, export scripts from the original MISP instance.



error-message is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
message	text	Content of the error message.	—	—
source	text	Source of the error message. ['misp-stix', 'lief', 'other']	✓	—

exploit-poc

Exploit-poc object describing a proof of concept or exploit of a vulnerability. This object has often a relationship with a vulnerability object.



exploit-poc is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
author	text	Author of the exploit - proof of concept	✓	✓
description	text	Description of the exploit - proof of concept	—	—
poc	attachment	Proof of Concept or exploit (as a script, binary or described process)	✓	✓
references	link	External references	—	✓
vulnerable_configuration	text	The vulnerable configuration described in CPE format where the exploit/proof of concept is valid	—	✓

facebook-account

Facebook account.



facebook-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
account-id	text	Account id.	—	—
account-name	text	Account name.	—	—
archive	link	Archive of the account (Internet Archive, Archive.is, etc).	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	A screen capture or exported list of contacts etc.	—	✓
description	text	A description of the user.	—	—
link	link	Original link to the page (supposed harmless).	—	—
url	url	Original URL location of the page (potentially malicious).	—	—
user-avatar	attachment	A user profile picture or avatar.	—	✓

facebook-group

Public or private facebook group.



facebook-group is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
administrator	text	A user account who is an owner or admin of the group.	—	✓
archive	link	Archive of the original group (Internet Archive, Archive.is, etc).	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	A screen capture or exported list of contacts, group members, etc.	—	✓
creator	text	The user account that created the group.	—	—
description	text	A description of the group, channel or community.	—	—
embedded-link	url	Link embedded in the group description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the group description (supposed safe).	—	✓
group-alias	text	Aliases or previous names of group.	—	✓
group-name	text	The name of the group, channel or community.	—	—
group-type	text	Facebook group type, e.g. general, buy and sell etc.	—	—
hashtag	text	Hashtag used to identify or promote the group.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link to the group (supposed harmless).	—	—
privacy	text	Group privacy: public, closed, secret. ['Public', 'Closed', 'Secret']	—	—
url	url	Original URL location of the group (potentially malicious).	—	—

facebook-page

Facebook page.



facebook-page is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original page (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts, page members, etc.	—	✓
contact-detail	url	Contact url listed on about page.	—	✓
creator	text	The user account that created the page.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	A description of the page.	—	—
embedded-link	url	Link embedded in the page description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the page description (supposed safe).	—	✓
event	text	Event announcement on page.	—	✓
hashtag	text	Hashtag used to identify or promote the page.	—	✓
link	link	Original link to the page (supposed harmless).	—	—
page-alias	text	Aliases or previous names of page.	—	✓
page-id	text	Page id (without the @).	—	—
page-name	text	The name of the page.	—	—
page-type	text	Facebook page type, e.g. community, product etc.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
related-page-id	text	id of a page listed as related to this one (without the @).	—	✓
related-page-name	text	name of a page listed as related to this one.	—	✓
team-member	text	A user account who is a member of the page.	—	✓
url	url	Original URL location of the page (potentially malicious).	—	—

facebook-post

Post on a Facebook wall.



facebook-post is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The facebook post file or screen capture.	—	✓
embedded-link	url	Link in the facebook post	—	✓
embedded-safe-link	link	Safe link in the facebook post	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hashtag	text	Hashtag embedded in the facebook post	—	✓
in-reply-to-display-name	text	The user display name of the facebook this post shares.	—	✓
in-reply-to-status-id	text	The facebook ID of the post that this post shares.	—	✓
in-reply-to-user-id	text	The user ID of the facebook this post shares.	—	✓
language	text	The language of the post.	✓	✓
link	link	Original link to the facebook post (supposed harmless).	—	✓
post	text	Raw text of the post.	—	—
post-id	text	The facebook post id.	—	—
post-location	text	id of the group, page or wall the post was posted to.	—	—
removal-date	datetime	When the facebook post was removed.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	Original URL of the facebook post, e.g. link shortener (potentially malicious).	—	✓
user-id	text	Id of the account who posted.	—	—
user-name	text	Display name of the account who posted.	—	—
username	text	Username who posted the facebook post	—	—
username-quoted	text	Username who is quoted in the facebook post.	—	✓

facial-composite

An object which describes a facial composite.



facial-composite is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
facial-composite	attachment	Facial composite image.	—	✓
technique	text	Construction technique of the facial composite. ['E-FIT', 'PROfit', 'Sketch', 'Photofit', 'EvoFIT', 'PortraitPad']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
text	text	A description of the facial composite.	✓	—

fail2ban

Fail2ban event.



fail2ban is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attack-type	text	Type of the attack	✓	—
banned-ip	ip-src	IP Address banned by fail2ban	—	—
failures	counter	Amount of failures that lead to the ban.	✓	—
logfile	attachment	Full logfile related to the attack.	✓	—
logline	text	Example log line that caused the ban.	✓	—
processing-timestamp	datetime	Timestamp of the report	✓	—
sensor	text	Identifier of the sensor	✓	—
victim	text	Identifier of the victim	✓	—

favicon

A favicon, also known as a shortcut icon, website icon, tab icon, URL icon, or bookmark icon, is a file containing one or more small icons, associated with a particular website or web page. The object template can include the murmur3 hash of the favicon to facilitate correlation.



favicon is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
favicon	attachment	The raw favicon file.	—	—
favicon-mmh3	favicon-mmh3	favicon-mmh3 is the murmur3 hash of a favicon as used in Shodan.	—	—
link	link	The original link where the favicon was seen.	—	✓

file

File object describing a file with meta-information.



file is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	A non-malicious file.	—	—
authentihash	authentihash	Authenticode executable signature hash	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
certificate	x509-fingerprint-sha1	Certificate value if the binary is signed with another authentication scheme than authenticode	—	—
compilation-timestamp	datetime	Compilation timestamp	—	—
entropy	float	Entropy of the whole file	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
file-encoding	text	Encoding format of the file ['Adobe-Standard-Encoding', 'Adobe-Symbol-Encoding', 'Amiga-1251', 'ANSI_X3.110-1983', 'ASMO_449', 'Big5', 'Big5-HKSCS', 'BOCU-1', 'BRF', 'BS_4730', 'BS_viewdata', 'CESU-8', 'CP50220', 'CP51932', 'CSA_Z243.4-1985-1', 'CSA_Z243.4-1985-2', 'CSA_Z243.4-1985-gr', 'CSN_369103', 'DEC-MCS', 'DIN_66003', 'dk-us', 'DS_2089', 'EBCDIC-AT-DE', 'EBCDIC-AT-DE-A', 'EBCDIC-CA-FR', 'EBCDIC-DK-NO', 'EBCDIC-DK-NO-A', 'EBCDIC-ES', 'EBCDIC-ES-A', 'EBCDIC-ES-S', 'EBCDIC-FI-SE', 'EBCDIC-FI-SE-A', 'EBCDIC-FR', 'EBCDIC-IT', 'EBCDIC-PT', 'EBCDIC-UK', 'EBCDIC-US', 'ECMA-cyrillic', 'ES', 'ES2', 'EUC-KR', 'Extended_UNIX_Code_Fixed_Width_for_Japanese', 'Extended_UNIX_Code_Packed_Format_for_Japanese', 'GB18030',	✓	—
118				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
filename	filename	Filename on disk	✓	✓
fullpath	text	Complete path of the filename including the filename	—	✓
imphash	imphash	Hash (md5) calculated from the PE import table	—	—
malware-sample	malware-sample	The file itself (binary)	—	—
md5	md5	[Insecure] MD5 hash (128 bits)	—	—
mimetype	mime-type	Mime type	✓	—
path	text	Path of the filename complete or partial	✓	✓
pattern-in-file	pattern-in-file	Pattern that can be found in the file	—	✓
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—	—

'IBM869', 'IBM870',
 'IBM871', 'IBM880',
 'IBM891', 'IBM903',
 'IBM904', 'IBM905',
 'IBM918', 'IBM-Symbols', 'IBM-Thai', 'IEC_P27-1',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sha3-224	sha3-224	Secure Hash Algorithm 3 (224 bits)	—	—
sha3-256	sha3-256	Secure Hash Algorithm 3 (256 bits)	—	—
sha3-384	sha3-384	Secure Hash Algorithm 3 (384 bits)	—	—
sha3-512	sha3-512	Secure Hash Algorithm 3 (512 bits)	—	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—	—
size-in-bytes	size-in-bytes	Size of the file, in bytes	✓	—
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH) 'ISO_8859-5:1988', 'ISO_8859-6:1987', 'ISO_8859-6-E', 'ISO_8859-6-I', 'ISO_8859-7:1987', 'ISO_8859-8:1988', 'ISO_8859-8-E',	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
state	text	State of the file ['Malicious', 'Harmless', 'Signed', 'Revoked', 'Expired', 'Trusted']	✓	✓
telfhash	telfhash	telfhash - Symbol hash for ELF files.	—	—
text	text	Free text value to attach to the file	✓	✓
tlsh	tlsh	Fuzzy hash by Trend Micro: Locality Sensitive Hash	—	—
vhash	vhash	vhash by VirusTotal JIS_C6229-1984-a, 'JIS_C6229-1984-b', 'JIS_C6229-1984-b-add', 'JIS_C6229-1984-hand', 'JIS_C6229-1984-kana', 'Latin-greek-1', 'latin-lap', 'macintosh', 'Microsoft-Publishing', 'MNEM', 'MNEMONIC',	—	—

forensic-case

An object template to describe a digital forensic case.



forensic-case is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
additional-comments	text	Comments.	✓	—
analysis-start-date	datetime	Date when the analysis began.	✓	—
case-name	text	Name to address the case.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
case-number	text	Any unique number assigned to the case for unique identification.	—	—
name-of-the-analyst	text	Name(s) of the analyst assigned to the case.	✓	✓
references	link	External references	—	✓

forensic-evidence

An object template to describe a digital forensic-evidence-



forensic-evidence is a MISP object available in JSON format at [this location](#). The JSON format can be freely parsed in [MISP4](#) application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
acquisition-method	text	Method used for acquisition of the evidence. ['Live acquisition', 'Dead/Offline acquisition', 'Physical collection', 'Logical collection', 'File system extraction', 'Chip-off', 'Other']	✓	—

ventura-
 International',
 'Ventura-Math',
 'Ventura-US',
 'videotex-suppl',
 'VIQR', 'VISCII',
 'windows-1250',
 'windows-1251',
 'windows-1252',
 'windows-1253',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
acquisition-tools	text	Tools used for acquisition of the evidence. ['dd', 'dc3dd', 'dcfldd', 'EnCase', 'FTK Imager', 'FDAS', 'TrueBack', 'Guymager', 'IXimager', 'Other']	✓	✓
additional-comments	text	Comments.	✓	—
case-number	text	A unique number assigned to the case for unique identification.	—	—
evidence-number	text	A unique number assigned to the evidence for unique identification.	—	—
name	text	Name of the evidence acquired.	—	—
references	link	External references	—	✓
type	text	Evidence type. ['Computer', 'Network', 'Mobile Device', 'Multimedia', 'Cloud', 'IoT', 'Other']	✓	✓

forged-document

Object describing a forged document.



forged-document is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The forged document file.	—	—
document-name	text	Title of the document.	—	—
document-text	text	Raw text of document	—	—
document-type	text	The type of document (not the file type). ['email', 'letterhead', 'speech', 'literature', 'blog', 'microblog', 'photo', 'audio', 'invoice', 'receipt', 'other']	✓	✓
first-seen	datetime	When the document has been accessible or seen for the first time.	✓	—
last-seen	datetime	When the document has been accessible or seen for the last time.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link into the document (Supposed harmless)	—	—
objective	text	Objective of the forged document. ['Disinformation', 'Advertising', 'Parody', 'Other']	✓	✓
purpose-of-document	text	What the document is used for. ['Identification', 'Travel', 'Health', 'Legal', 'Financial', 'Government', 'Military', 'Media', 'Communication', 'Other']	✓	✓
url	url	Original URL location of the document (potentially malicious)	—	—

ftm-Airplane



ftm-Airplane is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
buildDate	text	Build Date	—	✓
country	text	Country	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
icaoCode	text	ICAO aircraft type designator	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
manufacturer	text	Manufacturer	✓	✓
model	text	Model	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
publisherUrl	url	Publishing source URL	—	✓
registrationDate	text	Registration Date	—	✓
registrationNumber	text	Registration Number	—	✓
retrievedAt	text	Retrieved on	—	✓
serialNumber	text	Serial Number	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
type	text	Type	✓	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Assessment



ftm-Assessment is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alias	text	Other name	—	✓
assessmentId	text	Assessment ID	✓	✓
country	text	Country	—	✓
description	text	Description	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publishDate	text	Date of publishing	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Asset



ftm-Asset is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
country	text	Country	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Associate

Non-family association between two people.



ftm-Associate is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
relationship	text	Nature of the association	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓

ftm-Audio



ftm-Audio is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
duration	float	Duration of the audio in ms	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
samplingRate	float	Sampling rate of the audio in Hz	✓	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-BankAccount



ftm-BankAccount is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
accountNumber	text	Account Number	—	✓
accountType	text	Account Type	✓	✓
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
balance	float	Balance	✓	✓
bankAddress	text	Bank Address	✓	✓
bankName	text	Bank Name	✓	✓
bic	text	Bank Identifier Code	✓	✓
country	text	Country	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
iban	iban	IBAN	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
modifiedAt	text	Modified on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
name	text	Name	—	✓
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Call



ftm-Call is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
callerNumber	phone-number	Caller's Number	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date	text	Date	—	✓
description	text	Description	✓	✓
duration	float	Call Duration in seconds	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
receiverNumber	phone-number	Receiver's Number	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓

ftm-Company

A legal entity representing an association of people, whether natural, legal or a mixture of both, with a specific objective.



ftm-Company is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
bikCode	text	Russian bank account code	✓	✓
bvdId	text	Bureau van Dijk ID	—	✓
caemCode	text	(RO) What kind of activity a legal entity is allowed to develop	✓	✓
capital	text	Capital	✓	✓
cikCode	text	US SEC Central Index Key	—	✓
classification	text	Classification	✓	✓
coatoCode	text	COATO / SOATO / OKATO	—	✓
country	text	Country	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
dissolutionDate	text	The date the legal entity was dissolved, if applicable	—	✓
dunsCode	text	Dun & Bradstreet identifier	—	✓
email	email-src	Email address	—	✓
fnsCode	text	(RU, ΦHC) Federal Tax Service related info	—	✓
fssCode	text	(RU, ΦCC) Social Security	✓	✓
ibcRuc	text	ibcRUC	—	✓
icijId	text	ID according to International Consortium for Investigative Journalists	✓	✓
idNumber	text	ID number of any applicable ID	—	✓
incorporationDate	text	The date the legal entity was incorporated	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
innCode	text	Russian company ID	—	✓
ipoCode	text	IPO	—	✓
irsCode	text	US tax ID	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
jibCode	text	Yugoslavia company ID	—	✓
jurisdiction	text	Jurisdiction	—	✓
keywords	text	Keywords	✓	✓
kppCode	text	(RU, КПП) in addition to INN for orgs; reason for registration at FNS	—	✓
legalForm	text	Legal form	✓	✓
mainCountry	text	Primary country of this entity	—	✓
mbsCode	text	MBS	—	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
ogrnCode	text	Major State Registration Number	—	✓
okopfCode	text	(RU, ОКОПФ) What kind of business entity	✓	✓
okpoCode	text	Russian industry classifier	—	✓
oksmCode	text	Russian (OKCM) countries classifier	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
okvedCode	text	(RU, ОКВЭД) Economical activity classifier. OKVED2 is the same but newer	✓	✓
opencorporatesUrl	url	OpenCorporates URL	—	✓
pfrNumber	text	(RU, ПФП) Pension Fund Registration number. AAA-BBB-CCCCC, where AAA is organisation region, BBB is district, CCCCCC number at a specific branch	—	✓
phone	phone-number	Phone number	—	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
sector	text	Sector	✓	✓
sourceUrl	url	Source link	—	✓
status	text	Status	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
summary	text	Summary	✓	✓
swiftBic	text	Bank identifier code	—	✓
taxNumber	text	Tax identification number	—	✓
taxStatus	text	Tax status	✓	✓
topics	text	Topics	—	✓
vatCode	text	(EU) VAT number	—	✓
voenCode	text	Azerbaijan taxpayer ID	—	✓
weakAlias	text	Weak alias	✓	✓
website	url	Website address	—	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Contract

An contract or contract lot issued by an authority. Multiple lots may be awarded to different suppliers (see ContractAward).



ftm-Contract is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
cancelled	text	Cancelled?	✓	✓
classification	text	Classification	✓	✓
contractDate	text	Contract date	—	✓
country	text	Country	—	✓
criteria	text	Contract award criteria	✓	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
method	text	Procurement method	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Contract name	✓	✓
notes	text	Notes	✓	✓
noticeId	text	Contract Award Notice ID	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
numberAwards	text	Number of awards	✓	✓
previousName	text	Previous name	—	✓
procedure	text	Contract procedure	✓	✓
procedureNumber	text	Procedure number	✓	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
status	text	Procurement status	✓	✓
summary	text	Summary	✓	✓
title	text	Contract title	✓	✓
topics	text	Topics	—	✓
type	text	Type of contract. Potentially W (Works), U (Supplies), S (Services).	✓	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-ContractAward

A contract or contract lot as awarded to a supplier.



ftm-ContractAward is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
amended	text	Was this award amended, modified or updated by a subsequent document?	✓	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
cpvCode	text	Contract Procurement Vocabulary (what type of goods/services, EU)	✓	✓
currency	text	Currency	✓	✓
date	text	Date	—	✓
decisionReason	text	Decision reason	✓	✓
description	text	Description	✓	✓
documentNumber	text	Document number	✓	✓
documentType	text	Document type	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
lotNumber	text	Lot number	✓	✓
modifiedAt	text	Modified on	—	✓
nutsCode	text	Nomenclature of Territorial Units for Statistics (NUTS)	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-CourtCase



ftm-CourtCase is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
caseNumber	text	Case number	—	✓
category	text	Category	✓	✓
closeDate	text	Close date	—	✓
country	text	Country	—	✓
court	text	Court	✓	✓
description	text	Description	✓	✓
fileDate	text	File date	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
type	text	Type	✓	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-CourtCaseParty



ftm-CourtCaseParty is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Debt

A monetary debt between two parties.



ftm-Debt is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
currency	text	Currency	✓	✓
date	text	Date	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓

ftm-Directorship



ftm-Directorship is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
secretary	text	Secretary	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Document



ftm-Document is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
MimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Documentation



ftm-Documentation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-EconomicActivity

A foreign economic activity.



ftm-EconomicActivity is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
ccdNumber	text	Customs Cargo Declaration Number	—	✓
ccdValue	text	Declaration Value	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
customsAmount	text	Customs Value of goods	✓	✓
customsProcedure	text	Customs Procedure — type of customs clearance	✓	✓
date	text	Date	—	✓
departureCountry	text	Country out of which the goods are transported	—	✓
description	text	Description	✓	✓
destinationCountry	text	Final destination for the goods	—	✓
directionOfTransportation	text	Direction of transportation (import/export)	✓	✓
dollarExchRate	text	USD Exchange Rate for the activity	✓	✓
endDate	text	End date	—	✓
goodsDescription	text	Description of goods	✓	✓
indexText	text	Index text	✓	✓
invoiceAmount	text	Invoice Value of goods	✓	✓
modifiedAt	text	Modified on	—	✓
originCountry	text	Country of origin of goods	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓
tradingCountry	text	Trading Country of the company which transports the goods via Russian border	—	✓
vedCode	text	(Код ТН ВЭД) Foreign Economic Activity Commodity Code	—	✓
vedCodeDescription	text	(Описание кода ТН ВЭД) Foreign Economic Activity Commodity Code description	✓	✓

ftm-Email



ftm-Email is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
bcc	text	Blind carbon copy	✓	✓
bodyHtml	text	HTML	✓	✓
bodyText	text	Text	✓	✓
cc	text	Carbon copy	✓	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
from	text	From	✓	✓
generator	text	The program used to generate this file	✓	✓
headers	text	Raw headers	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
inReplyTo	text	Message ID of the preceding email in the thread	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
MimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sender	text	Sender	✓	✓
sourceUrl	url	Source link	—	✓
subject	text	Subject	✓	✓
summary	text	Summary	✓	✓
threadTopic	text	Thread topic	✓	✓
title	text	Title	✓	✓
to	text	To	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Event



ftm-Event is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
companiesMentioned	text	Detected companies	—	✓
country	text	Country	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
endDate	text	End date	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ibanMentioned	iban	Detected IBANs	—	✓
important	text	Important	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
location	text	Location	—	✓
locationMentioned	text	Detected locations	—	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sourceUrl	url	Source link	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Family

Family relationship between two people.



ftm-Family is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
recordId	text	Record ID	✓	✓
relationship	text	Nature of the relationship, from the person's perspective eg. 'mother', where 'relative' is mother of 'person'.	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓

ftm-Folder



ftm-Folder is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-HyperText



ftm-HyperText is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
bodyHtml	text	HTML	✓	✓
bodyText	text	Text	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Image



ftm-Image is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
bodyText	text	Text	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Land



ftm-Land is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
area	float	Area	✓	✓
cadastralCode	text	Cadastral code	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
censusBlock	text	Census block	✓	✓
country	text	Country	—	✓
createDate	text	Record date	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
encumbrance	text	An encumbrance is a right to, interest in, or legal liability on real property that does not prohibit passing title to the property but that diminishes its value.	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
landType	text	Land type	✓	✓
latitude	float	Latitude	✓	✓
longitude	float	Longitude	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
propertyType	text	Property type	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
tenure	text	Tenure	✓	✓
titleNumber	text	Title number	—	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-LegalEntity

A legal entity may be a person or a company.



ftm-LegalEntity is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
bvdId	text	Bureau van Dijk ID	—	✓
classification	text	Classification	✓	✓
country	text	Country	—	✓
description	text	Description	✓	✓
dissolutionDate	text	The date the legal entity was dissolved, if applicable	—	✓
dunsCode	text	Dun & Bradstreet identifier	—	✓
email	email-src	Email address	—	✓
icijId	text	ID according to International Consortium for Investigative Journalists	✓	✓
idNumber	text	ID number of any applicable ID	—	✓
incorporationDate	text	The date the legal entity was incorporated	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
innCode	text	Russian company ID	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
jurisdiction	text	Country or region in which this entity operates	—	✓
keywords	text	Keywords	✓	✓
legalForm	text	Legal form	✓	✓
mainCountry	text	Primary country of this entity	—	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
okpoCode	text	Russian industry classifier	—	✓
opencorporatesUrl	url	OpenCorporates URL	—	✓
phone	phone-number	Phone number	—	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Company registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
sector	text	Sector	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sourceUrl	url	Source link	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓
swiftBic	text	Bank identifier code	—	✓
taxNumber	text	Tax identification number	—	✓
taxStatus	text	Tax status	✓	✓
topics	text	Topics	—	✓
vatCode	text	(EU) VAT number	—	✓
weakAlias	text	Weak alias	✓	✓
website	url	Website address	—	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-License

A grant of land, rights or property. A type of Contract.



ftm-License is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
area	text	Area	✓	✓
cancelled	text	Cancelled?	✓	✓
classification	text	Classification	✓	✓
commodities	text	Commodities	✓	✓
contractDate	text	Contract date	—	✓
country	text	Country	—	✓
criteria	text	Contract award criteria	✓	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
method	text	Procurement method	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Contract name	✓	✓
notes	text	Notes	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
noticeId	text	Contract Award Notice ID	✓	✓
numberAwards	text	Number of awards	✓	✓
previousName	text	Previous name	—	✓
procedure	text	Contract procedure	✓	✓
procedureNumber	text	Procedure number	✓	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
reviewDate	text	License review date	✓	✓
sourceUrl	url	Source link	—	✓
status	text	Procurement status	✓	✓
summary	text	Summary	✓	✓
title	text	Contract title	✓	✓
topics	text	Topics	—	✓
type	text	Type of contract. Potentially W (Works), U (Supplies), S (Services).	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Membership



ftm-Membership is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Message



ftm-Message is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
bodyHtml	text	HTML	✓	✓
bodyText	text	Text	✓	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
endDate	text	End date	—	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
inReplyTo	text	Message ID of the preceding message in the thread	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
metadata	text	Metadata	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
startDate	text	Start date	—	✓
subject	text	Subject	✓	✓
summary	text	Summary	✓	✓
threadTopic	text	Thread topic	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Organization



ftm-Organization is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bvdId	text	Bureau van Dijk ID	—	✓
classification	text	Classification	✓	✓
country	text	Country	—	✓
description	text	Description	✓	✓
dissolutionDate	text	The date the legal entity was dissolved, if applicable	—	✓
dunsCode	text	Dun & Bradstreet identifier	—	✓
email	email-src	Email address	—	✓
icijId	text	ID according to International Consortium for Investigative Journalists	✓	✓
idNumber	text	ID number of any applicable ID	—	✓
incorporationDate	text	The date the legal entity was incorporated	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
innCode	text	Russian company ID	—	✓
jurisdiction	text	Country or region in which this entity operates	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
keywords	text	Keywords	✓	✓
legalForm	text	Legal form	✓	✓
mainCountry	text	Primary country of this entity	—	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
okpoCode	text	Russian industry classifier	—	✓
opencorporatesUrl	url	OpenCorporates URL	—	✓
phone	phone-number	Phone number	—	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Company registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
sector	text	Sector	✓	✓
sourceUrl	url	Source link	—	✓
status	text	Status	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
summary	text	Summary	✓	✓
swiftBic	text	Bank identifier code	—	✓
taxNumber	text	Tax identification number	—	✓
taxStatus	text	Tax status	✓	✓
topics	text	Topics	—	✓
vatCode	text	(EU) VAT number	—	✓
weakAlias	text	Weak alias	✓	✓
website	url	Website address	—	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Ownership



ftm-Ownership is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
legalBasis	text	Legal basis	✓	✓
modifiedAt	text	Modified on	—	✓
ownershipType	text	Type of ownership	✓	✓
percentage	text	Percentage held	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sharesCount	text	Number of shares	✓	✓
sharesCurrency	text	Currency of shares	✓	✓
sharesType	text	Type of shares	✓	✓
sharesValue	text	Value of shares	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Package



itm-Package is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
MimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Page



ftm-Page is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bodyText	text	Text	✓	✓
detectedLanguage	text	Auto-detected language	✓	✓
index	float	Index	✓	✓
indexText	text	Index text	✓	✓

ftm-Pages



ftm-Pages is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
pdfHash	sha1	PDF alternative version checksum	—	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Passport

Passport.



ftm-Passport is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
authority	text	Authority	✓	✓
birthDate	text	Date of birth	—	✓
birthPlace	text	Place of birth	✓	✓
country	text	Country	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
gender	text	Gender	✓	✓
givenName	text	Given name	✓	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
passportNumber	text	Passport number	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
personalNumber	text	Personal number	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓
surname	text	Surname	✓	✓
type	text	Document type	✓	✓

ftm-Payment

A monetary payment between two parties.



ftm-Payment is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
currency	text	Currency	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
programme	text	Programme name, funding code, category identifier, etc.	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
purpose	text	Payment purpose	✓	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sequenceNumber	text	Sequence number	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓
transactionNumber	text	Transaction number	✓	✓

ftm-Person

An individual.



ftm-Person is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
birthDate	text	Birth date	—	✓
birthPlace	text	Place of birth	✓	✓
bvdId	text	Bureau van Dijk ID	—	✓
classification	text	Classification	✓	✓
country	text	Country	—	✓
deathDate	text	Death date	—	✓
description	text	Description	✓	✓
dissolutionDate	text	The date the legal entity was dissolved, if applicable	—	✓
dunsCode	text	Dun & Bradstreet identifier	—	✓
email	email-src	Email address	—	✓
fatherName	text	Patronymic	✓	✓
firstName	text	First name	✓	✓
gender	text	Gender	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
icijId	text	ID according to International Consortium for Investigative Journalists	✓	✓
idNumber	text	ID number of any applicable ID	—	✓
incorporationDate	text	The date the legal entity was incorporated	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
innCode	text	Russian company ID	—	✓
jurisdiction	text	Country or region in which this entity operates	—	✓
keywords	text	Keywords	✓	✓
lastName	text	Last name	✓	✓
legalForm	text	Legal form	✓	✓
mainCountry	text	Primary country of this entity	—	✓
middleName	text	Middle name	✓	✓
modifiedAt	text	Modified on	—	✓
motherName	text	Matronymic	✓	✓
name	text	Name	—	✓
nationality	text	Nationality	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
notes	text	Notes	✓	✓
okpoCode	text	Russian industry classifier	—	✓
opencorporatesUrl	url	OpenCorporates URL	—	✓
passportNumber	text	Passport	—	✓
phone	phone-number	Phone number	—	✓
position	text	Position	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Company registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
secondName	text	Second name	✓	✓
sector	text	Sector	✓	✓
sourceUrl	url	Source link	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓
swiftBic	text	Bank identifier code	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
taxNumber	text	Tax identification number	—	✓
taxStatus	text	Tax status	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
vatCode	text	(EU) VAT number	—	✓
weakAlias	text	Weak alias	✓	✓
website	url	Website address	—	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-PlainText



ftm-PlainText is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bodyText	text	Text	✓	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-PublicBody

A public body, such as a ministry, department or state company.



ftm-PublicBody is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
bvdId	text	Bureau van Dijk ID	—	✓
classification	text	Classification	✓	✓
country	text	Country	—	✓
description	text	Description	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
dissolutionDate	text	The date the legal entity was dissolved, if applicable	—	✓
dunsCode	text	Dun & Bradstreet identifier	—	✓
email	email-src	Email address	—	✓
icijId	text	ID according to International Consortium for Investigative Journalists	✓	✓
idNumber	text	ID number of any applicable ID	—	✓
incorporationDate	text	The date the legal entity was incorporated	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
innCode	text	Russian company ID	—	✓
jurisdiction	text	Country or region in which this entity operates	—	✓
keywords	text	Keywords	✓	✓
legalForm	text	Legal form	✓	✓
mainCountry	text	Primary country of this entity	—	✓
modifiedAt	text	Modified on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
name	text	Name	—	✓
notes	text	Notes	✓	✓
okpoCode	text	Russian industry classifier	—	✓
opencorporatesUrl	url	OpenCorporates URL	—	✓
phone	phone-number	Phone number	—	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Company registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
sector	text	Sector	✓	✓
sourceUrl	url	Source link	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓
swiftBic	text	Bank identifier code	—	✓
taxNumber	text	Tax identification number	—	✓
taxStatus	text	Tax status	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
topics	text	Topics	—	✓
vatCode	text	(EU) VAT number	—	✓
weakAlias	text	Weak alias	✓	✓
website	url	Website address	—	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-RealEstate

A piece of land or property.



ftm-RealEstate is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
area	float	Area	✓	✓
cadastralCode	text	Cadastral code	—	✓
censusBlock	text	Census block	✓	✓
country	text	Country	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
createDate	text	Record date	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
encumbrance	text	An encumbrance is a right to, interest in, or legal liability on real property that does not prohibit passing title to the property but that diminishes its value.	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
landType	text	Land type	✓	✓
latitude	float	Latitude	✓	✓
longitude	float	Longitude	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
propertyType	text	Property type	✓	✓
publisher	text	Publishing source	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
publisherUrl	url	Publishing source URL	—	✓
registrationNumber	text	Registration number	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
tenure	text	Tenure	✓	✓
titleNumber	text	Title number	—	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Representation

A mediatory, intermediary, middleman, or broker acting on behalf of a legal entity.



ftm-Representation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Row



ftm-Row is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cells	text	Cells	✓	✓
index	float	Index	✓	✓
indexText	text	Index text	✓	✓

ftm-Sanction

A sanction designation.



ftm-Sanction is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
authority	text	Authority	✓	✓
country	text	Country	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
duration	text	Duration	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
reason	text	Reason	✓	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Succession

Two entities that legally succeed each other.



ftm-Succession is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-Table



ftm-Table is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
columns	text	Column headings	✓	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓
csvHash	sha1	CSV alternative version checksum	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
rowCount	float	Number of rows	✓	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-TaxRoll

A tax declaration of an individual.



ftm-TaxRoll is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
birthDate	text	Date of birth	—	✓
country	text	Country	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
givenName	text	Given name	✓	✓
income	text	Registered income	✓	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
summary	text	Summary	✓	✓
surname	text	Surname	✓	✓
taxPaid	text	Amount of tax paid	✓	✓
wealth	text	Registered wealth	✓	✓

ftm-UnknownLink



ftm-UnknownLink is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
date	text	Date	—	✓
description	text	Description	✓	✓
endDate	text	End date	—	✓
indexText	text	Index text	✓	✓
modifiedAt	text	Modified on	—	✓
publisher	text	Publishing source	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
publisherUrl	url	Publishing source URL	—	✓
recordId	text	Record ID	✓	✓
retrievedAt	text	Retrieved on	—	✓
role	text	Role	✓	✓
sourceUrl	url	Source URL	—	✓
startDate	text	Start date	—	✓
status	text	Status	✓	✓
summary	text	Summary	✓	✓

ftm-UserAccount



ftm-UserAccount is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
country	text	Country	—	✓
description	text	Description	✓	✓
email	email-src	E-mail	—	✓
indexText	text	Index text	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓
number	phone-number	Phone Number	—	✓
password	text	Password	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
service	text	Service	✓	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
username	text	Username	✓	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Vehicle



ftm-Vehicle is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
buildDate	text	Build Date	—	✓
country	text	Country	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
model	text	Model	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
notes	text	Notes	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationDate	text	Registration Date	—	✓
registrationNumber	text	Registration Number	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
topics	text	Topics	—	✓
type	text	Type	✓	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Vessel

A boat or ship.



ftm-Vessel is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
amount	float	Amount	✓	✓
amountEur	float	Amount in EUR	✓	✓
amountUsd	float	Amount in USD	✓	✓
buildDate	text	Build Date	—	✓
callSign	text	Call Sign	—	✓
country	text	Country	—	✓
crsNumber	text	CRS Number	—	✓
currency	text	Currency	✓	✓
description	text	Description	✓	✓
flag	text	Flag	—	✓
grossRegisteredTonnage	float	Gross Registered Tonnage	✓	✓
imoNumber	text	IMO Number	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
keywords	text	Keywords	✓	✓
mmsi	text	MMSI	—	✓
model	text	Model	✓	✓
modifiedAt	text	Modified on	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
name	text	Name	—	✓
nameChangeDate	text	Date of Name Change	—	✓
navigationArea	text	Navigation Area	✓	✓
notes	text	Notes	✓	✓
pastFlags	text	Past Flags	✓	✓
pastNames	text	Past Names	—	✓
pastTypes	text	Past Types	✓	✓
previousName	text	Previous name	—	✓
program	text	Program	✓	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
registrationDate	text	Registration Date	—	✓
registrationNumber	text	Registration Number	—	✓
registrationPort	text	Port of Registration	✓	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
tonnage	text	Tonnage	✓	✓
topics	text	Topics	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	Type	✓	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Video



ftm-Video is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
duration	float	Duration of the video in ms	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
messageId	text	Message ID of a document; unique in most cases	✓	✓
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

ftm-Workbook



ftm-Workbook is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Address	—	✓
alephUrl	url	Aleph URL	—	✓
alias	text	Other name	—	✓
author	text	The original author, not the uploader	✓	✓
authoredAt	text	Authored on	—	✓
companiesMentioned	text	Detected companies	—	✓
contentHash	sha1	SHA1 hash of the data	—	✓
country	text	Country	—	✓
crawler	text	The crawler used to acquire this file	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date	text	If not otherwise specified	—	✓
description	text	Description	✓	✓
detectedCountry	text	Detected country	—	✓
detectedLanguage	text	Detected language	✓	✓
emailMentioned	email-src	Detected e-mail addresses	—	✓
encoding	text	File encoding	✓	✓
extension	text	File extension	✓	✓
fileName	text	File name	✓	✓
fileSize	float	File size	✓	✓
generator	text	The program used to generate this file	✓	✓
ibanMentioned	iban	Detected IBANs	—	✓
indexText	text	Index text	✓	✓
indexUpdatedAt	text	Index updated at	—	✓
ipMentioned	ip-src	Detected IP addresses	—	✓
keywords	text	Keywords	✓	✓
language	text	Language	✓	✓
locationMentioned	text	Detected locations	—	✓
messageId	text	Message ID of a document; unique in most cases	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
mimeType	mime-type	MIME type	✓	✓
modifiedAt	text	Modified on	—	✓
name	text	Name	—	✓
namesMentioned	text	Detected names	—	✓
notes	text	Notes	✓	✓
peopleMentioned	text	Detected people	—	✓
phoneMentioned	phone-number	Detected phones	—	✓
previousName	text	Previous name	—	✓
processingError	text	Processing error	✓	✓
processingStatus	text	Processing status	✓	✓
program	text	Program	✓	✓
publishedAt	text	Published on	—	✓
publisher	text	Publishing source	✓	✓
publisherUrl	url	Publishing source URL	—	✓
retrievedAt	text	Retrieved on	—	✓
sourceUrl	url	Source link	—	✓
summary	text	Summary	✓	✓
title	text	Title	✓	✓
topics	text	Topics	—	✓
weakAlias	text	Weak alias	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
wikidataId	text	Wikidata ID	—	✓
wikipediaUrl	url	Wikipedia Article	—	✓

game-cheat

Describes a game cheat or a cheatware.



game-cheat is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
affected-game	text	Name of the game that is targeted by the cheatware.	—	—
cheat-name	text	Known name of the game cheat, if given.	✓	—
cheat-screenshot	attachment	Screenshot of the cheat at work.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cheat-type	text	Select a type of cheat. ['Aimbot', 'Artificial lag', 'Auto farmer', 'DDoS', 'Disconnecting', 'Exploit', 'Fly', 'Force field', 'Full brightness', 'Ghosting', 'God mode', 'Invincibility', 'Macros', 'No clip', 'No fog', 'RapidFire', 'Scripting', 'Show Hitboxes', 'Wallhack', 'Others']	—	✓
cheat-version	text	Any information about the cheatware version.	✓	—
compilation-date	datetime	Compilation date of the game cheat, if known.	✓	—
creator	threat-actor	Individual and/or Group and/or Organization that created the cheat.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ig-cheat-behaviour	comment	Describe the in-game behaviour of the cheat (e.g. You selected 'Aim Bot', here you can add details like 'Activate by pressing F7, Deactivate by pressing F8. Not detected be Easy Anti-Cheat.')	✓	—
implementation	text	How cheatware is implemented ['Game code modification', 'In-memory data manipulation', 'System software modification', 'Packet interception and manipulation']	✓	—
implementation-details	text	Additionnal informations about the implementation of the cheatware. (e.g. Requires to swap a dll file.)	✓	—
operating-system	text	Operating system required and its version.	✓	✓
pricing	text	Cheatware price, 0 if free.	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
webpage	url	Place where the cheat is promoted. Website, Forum, Download page, ...	—	—

geolocation

An object to describe a geographic location.



geolocation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
accuracy-radius	float	The approximate accuracy radius, in kilometers, around the latitude and longitude for the geographical entity (country, subdivision, city or postal code) associated with the related object. (based on geoip2 accuracy of maxmind)	✓	—
address	text	Address.	—	—
altitude	float	The altitude is the decimal value of the altitude in the World Geodetic System 84 (WGS84) reference.	✓	—
city	text	City.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
country	text	Country.	—	—
countrycode	text	Country code in ISO 3166-1 alpha-2	—	—
epsg	text	EPSG Geodetic Parameter value. This is an integer value of the EPSG.	✓	—
first-seen	datetime	When the location was seen for the first time.	✓	—
last-seen	datetime	When the location was seen for the last time.	✓	—
latitude	float	The latitude is the decimal value of the latitude in the World Geodetic System 84 (WGS84) reference.	✓	—
longitude	float	The longitude is the decimal value of the longitude in the World Geodetic System 84 (WGS84) reference	✓	—
neighborhood	text	Neighborhood.	—	—
region	text	Region.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
spacial-reference	text	Default spacial or projection reference for this object. ['WGS84', 'EPSG:4326', 'Mercator' 'EPSG:3857']	✓	—
text	text	A generic description of the location.	✓	—
zipcode	text	Zip Code.	—	—

git-vuln-finder

Export from git-vuln-finder.



git-vuln-finder is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
author	text	Commit author	—	—
author-email	email-src	Commit authors email	—	—
authored_date	datetime	Date the commit was originally made	—	—
branches	text	Branches the commit is on	✓	✓
commit-id	git-commit-id	Commit ID where the vulnerability is fixed.	—	—
committed_date	datetime	Date the commit was modified last	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cve	vulnerability	CVE associated to the vulnerability	—	—
language	text	Language of the commit (ISO 639-1 codes)	✓	✓
message	text	Commit message	✓	—
origin	text	Origin of the repository	—	—
origin-github-api	url	Full path to the commit on github	✓	—
pattern-matches	text	Pattern matching for the vulnerability	✓	✓
pattern-selected	text	Pattern used to find the vulnerability	✓	—
state	text	State of the vulnerability ['under-review', 'cve-assigned']	✓	—
stats.deletions	counter	Number of deletions in the commit	✓	—
stats.files	counter	Number of files changed in the commit	✓	—
stats.insertions	counter	Number of insertions in the commit	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
stats.lines	counter	Number of line changes in the commit	✓	—
summary	text	Commit summary	✓	—
tags	text	User defined tags	✓	✓

github-user

GitHub user.



github-user is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
avatar_url	link	Avatar URL	—	—
bio	text	Biography of the GitHub user.	—	—
blog	text	Blog - often used as website field of the user	—	—
company	text	Company	—	—
follower	github-username	GitHub user is followed by.	—	✓
following	github-username	Followed GitHub users by the GitHub user.	—	✓
id	text	User id	—	—
link	link	Original Link to the GitHub account.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
location	text	Location given by the GitHub user	✓	—
node_id	text	GitHub GraphQL node_id	—	—
organisation	github-organisation	Organisation affiliation of the GitHub user (it can be multiple).	—	✓
profile-image	attachment	Profile image of the GitHub user (it can be multiple).	—	✓
public_gists	text		✓	—
public_repos	text		✓	—
repository	github-repository	GitHub repository under the GitHub user.	—	✓
ssh-public-key	text	SSH public key associated to the GitHub user.	—	✓
twitter_username	text	Associated twitter account	—	—
user-fullname	text	Fullname of the GitHub user.	—	—
username	github-username	GitHub username.	—	✓
verified	text	User verified. ['True', 'False']	✓	—

gitlab-user

GitLab user. Gitlab.com user or self-hosted GitLab instance.



gitlab-user is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
avatar_url	link	Avatar url of the GitLab User	—	—
id	text	GitLab User id	—	—
name	text	Complete Name of the GitLab User Id	—	—
state	text	State of the GitLab User ['active', 'inactive', 'blocked']	✓	—
username	text	Username of the GitLab User	—	—
web_url	link	Profile url of the GitLab User	—	✓

gtp-attack

GTP attack object as attack as seen on the GTP signaling protocol supporting GPRS/LTE networks.



gtp-attack is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
GtpImei	text	GTP IMEI (International Mobile Equipment Identity).	—	—
GtpImsi	text	GTP IMSI (International mobile subscriber identity).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
GtpInterface	text	GTP interface. ['S5', 'S11', 'S10', 'S8', 'Gn', 'Gp']	✓	✓
GtpMessageType	text	GTP defines a set of messages between two associated GSNs or an SGSN and an RNC. Message type is described as a decimal value.	✓	—
GtpMsisdn	text	GTP MSISDN.	—	—
GtpServingNetwork	text	GTP Serving Network.	✓	—
GtpVersion	text	GTP version ['0', '1', '2']	✓	—
PortDest	text	Destination port.	✓	—
PortSrc	port	Source port.	✓	—
first-seen	datetime	When the attack has been seen for the first time.	✓	—
ipDest	ip-dst	IP destination address.	—	—
ipSrc	ip-src	IP source address.	—	—
text	text	A description of the GTP attack.	✓	—

hashlookup

hashlookup object as described on hashlookup services from circl.lu - <https://www.circl.lu/services/hashlookup>.



hashlookup is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
FileName	filename	Complete path of the filename including the filename	✓	—
FileSize	size-in-bytes	Size of the file, in bytes	✓	—
KnownMalicious	text	Source of the hashlookup record if it's a known malicious file	✓	—
MD5	md5	MD5 hash (128 bits) in hex representation	—	—
PackageArch	text	Package architecture	✓	—
PackageDescription	text	Package description and information	✓	—
PackageMaintainer	text	Package Maintainer(s)	—	—
PackageName	text	Package Name	✓	—
PackageRelease	text	Package Release	✓	—
PackageVersion	text	Package Version	✓	—
SHA-1	sha1	Secure Hash Algorithm 1 (160 bits) in hex representation	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
SHA-256	sha256	Secure Hash Algorithm 2 (256 bits) in hex representation	—	—
SSDEEP	ssdeep	SSDEEP - Fuzzy hashing	—	—
TLSH	tlsh	TLSH - Trend Micro Locality Sensitive Hash	—	—
source	text	Source of the hashlookup record	✓	—

http-request

A single HTTP request header.



http-request is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
basicauth-password	text	HTTP Basic Authentication Password	—	—
basicauth-user	text	HTTP Basic Authentication Username	—	—
content-type	other	The MIME type of the body of the request	—	—
cookie	text	An HTTP cookie previously sent by the server with Set-Cookie	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
header	text	An HTTP header sent during HTTP request	—	✓
host	hostname	The domain name of the server	—	—
ip-dst	ip-dst	The IP address of the server	—	—
ip-src	ip-src	The IP address of the client	—	—
method	http-method	HTTP Method invoked (one of GET, POST, PUT, HEAD, DELETE, OPTIONS, CONNECT)	✓	—
proxy-password	text	HTTP Proxy Password	—	—
proxy-user	text	HTTP Proxy Username	—	—
referer	other	This is the address of the previous web page from which a link to the currently requested page was followed	—	—
text	text	HTTP Request comment	✓	—
uri	uri	Request URI	—	—
url	url	Full HTTP Request URL	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
user-agent	user-agent	The user agent string of the user agent	—	—

identity

Identities can represent actual individuals, organizations, or groups (e.g., ACME, Inc.) as well as classes of individuals, organizations, systems or groups (e.g., the finance sector). The Identity SDO can capture basic identifying information, contact information, and the sectors that the Identity belongs to. Identity is used in STIX to represent, among other things, targets of attacks, information sources, object creators, and threat actor identities. (ref. STIX 2.1 - 4.5).



identity is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
contact_information	text	The contact information (email, phone number, etc.) for this Identity. No format for this information is currently defined by this specification.	—	—
description	text	A description that provides more details and context about the Identity, potentially including its purpose and its key characteristics.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
identity_class	text	The type of entity that this Identity describes, e.g., an individual or organization. ['individual', 'group', 'system', 'organization', 'class', 'unknown']	—	—
name	text	The name of this Identity. When referring to a specific entity (e.g., an individual or organization), this property SHOULD contain the canonical name of the specific entity.	—	✓
roles	text	The list of roles that this Identity performs (e.g., CEO, Domain Administrators, Doctors, Hospital, or Retailer).	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sectors	text	Description of the organization ['agriculture', 'aerospace', 'automotive', 'chemical', 'commercial', 'communication', 'construction', 'defense', 'education', 'energy', 'entertainment', 'financial- services', 'government', 'government emergency- services', 'government government-local', 'government- national', 'government- public-services', 'government- regional', 'healthcare', 'hospitality- leisure', 'infrastructure', 'infrastructure dams', 'infrastructure nuclear', 'infrastructure water', 'insurance', 'manufacturing', 'mining', 'non- profit', 'pharmaceuticals', 'retail', 'technology', 'telecommunicatio n', 'transportation', 'utilities']	—	✓

ilr-impact

Institut Luxembourgeois de Regulation - Impact.



ilr-impact is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
duree	text	Duree de l'incident en hh : mm	✓	—
nombre-utilisateurs-touches	text	Nombre d'utilisateurs touches par l'incident	✓	—
pourcentage-utilisateurs-touches	text	Pourcentage d'utilisateurs du service touches par l'incident	✓	—
service	text	Service impacte par l'incident ['Telephonie fixe', 'Acces Internet fixe', 'Telephonie mobile', 'Acces Internet mobile']	✓	✓

ilr-notification-incident

Institut Luxembourgeois de Regulation - Notification d'incident.



ilr-notification-incident is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
actions-corrective	text	Actions correctives a long terme	✓	-
actions-posterieur	text	Actions posterieures de l'incident pour minimiser le risque	✓	-
autres-information	text	Autres informations concernant la nature de l'incident notamment la liste des actifs affectes et les causes subsequentes eventuelles, declenches par la cause initiale	✓	-
cause-initiale-incident	text	Cause initiale de l'incident ['erreur humaine', "Defaut systeme 'hardware', 'software', 'procedures'", 'Attaque malveillante', 'Defaut d'une partie tierce ou externe', 'Catastrophe naturelle']	✓	-
date-incident	datetime	Date/heure de la detection de l'incident:	✓	-

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date-pre-notification	text	Date de la pre-notification	✓	—
delimitation-geographique	text	Delimitation geographique ['Nationale', 'Regionale']	✓	—
description-incident	text	Description generale de l'incident	✓	—
description-probleme-services-urgence	text	Description du probleme sur les services d'urgences impactes	✓	—
details-service	text	Details relatifs au service concerne et a l'impact de l'incident	✓	—
email-contact-incident	text	Email de la personne de contact en rapport avec l'incident	✓	—
impact-servicesw-urgence	text	Services d'urgences impactes ? ['Oui', 'Non']	✓	—
interconnections-affectees	text	Interconnections nationales et/ou internationales affectees	✓	—
nom-contact-incident	text	Nom de la personne de contact en rapport avec l'incident	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
nom-entreprise	text	Nom de l'entreprise notifiée	✓	—
remarques	text	Remarque(s), notamment les expériences gagnées et les leçons tirées de l'incident	✓	—
telephone-contact-incident	text	Telephone de la personne de contact en rapport avec l'incident	✓	—
traitement-incident	text	Traitements de l'incident et actions effectuées en ordre chronologique	✓	—
zone-impactee	text	zones/communes/villes impactées	✓	✓

image

Object describing an image file.



image is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the image (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The image file.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
filename	filename	The image filename.	—	—
image-text	text	Raw text of image	—	—
link	link	Original link into the image (Supposed harmless)	—	—
url	url	Original URL location of the image (potentially malicious)	—	—
username	text	Username who posted the image.	—	—

impersonation

Represent an impersonating account.



Impersonation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
account-name	text	Name of the impersonating account	—	—
account-url	url	url of the impersonating account	—	—
impersonated-account-name	text	Name of the impersonated account	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
impersonated-account-url	link	url of the impersonated account	—	—
objective	text	Objective of the impersonation ['Information stealing', 'Disinformation', 'Distrusting', 'Advertising', 'Parody', 'Other']	✓	✓
real-name	text	Real name of the impersonated person or entity	—	—
type	text	Type of the account ['Person', 'Association', 'Enterprise', 'Other']	✓	—
type-of-account	text	Type of the impersonated account ['Twitter', 'Facebook', 'LinkedIn', 'Reddit', 'Google+', 'Instagram', 'Forum', 'Other']	✓	—

imsi-catcher

IMSI Catcher entry object based on the open source IMSI catcher.



imsi-catcher is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
brand	text	Brand associated with the IMSI registration.	✓	—
cellid	text	CellID	✓	—
country	text	Country where the IMSI is registered.	✓	—
first-seen	datetime	When the IMSI has been accessible or seen for the first time.	✓	—
imsi	text	A usually unique International Mobile Subscriber Identity (IMSI) is allocated to each mobile subscriber in the GSM/UMTS/EPS system. IMSI can also refer to International Mobile Station Identity in the ITU nomenclature.	—	—
lac	text	LAC - Location Area Code	✓	—
mcc	text	MCC - Mobile Country Code	✓	—
mnc	text	MNC - Mobile Network Code	✓	—
operator	text	Operator associated with the IMSI registration.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
seq	counter	A sequence number for the collection	✓	—
text	text	A description of the IMSI record.	✓	—
tmsi-1	text	Temporary Mobile Subscriber Identities (TMSI) to visiting mobile subscribers can be allocated.	—	—
tmsi-2	text	Temporary Mobile Subscriber Identities (TMSI) to visiting mobile subscribers can be allocated.	—	—

infrastructure

The Infrastructure object represents a type of TTP and describes any systems, software services and any associated physical or virtual resources intended to support some purpose (e.g., C2 servers used as part of an attack, device or server that are part of defense, database servers targeted by an attack, etc.). While elements of an attack can be represented by other objects, the Infrastructure object represents a named group of related data that constitutes the infrastructure. STIX 2.1 - 4.8.



infrastructure is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alias	text	Alternative names used to identify this Infrastructure.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	A description that provides more details and context about the Infrastructure, potentially including its purpose, how it is being used, how it relates to other intelligence activities captured in related objects, and its key characteristics.	—	—
infrastructure_type	text	The type of infrastructure being described. The values for this property SHOULD come from the infrastructure-type-ov open vocabulary. ['amplification', 'anonymization', 'botnet', 'command-and-control', 'exfiltration', 'hosting-malware', 'hosting-target-lists', 'phishing', 'reconnaissance', 'staging', 'unknown']	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
kill_chain_phases	text	The list of Kill Chain Phases for which this Infrastructure is used. ['(1) Reconnaissance', '(2) Weaponization', '(3) Deliver', '(4) Exploitation', '(5) Installation', '(6) Command and Control', '(7) Actions on objectives']	✓	—
name	text	A name or characterizing text used to identify the Infrastructure.	—	—

instant-message

Instant Message (IM) object template describing one or more IM message.



instant-message is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
app-used	text	The IM application used to send the message. ['WhatsApp', 'Google Hangouts', 'Facebook Messenger', 'Telegram', 'Signal', 'WeChat', 'BlackBerry Messenger', 'TeamSpeak', 'TorChat', 'Tox', 'RetroShare', 'Slack', 'Wire', 'Threema', 'Discord', 'Mumble', 'Jabber', 'Twitter']	✓	—
archive	link	Archive of the original message (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The message file or screen capture.	—	✓
body	text	Message body of the IM.	—	—
from-name	text	Name of the person that sent the message.	—	✓
from-number	phone-number	Phone number used to send the message.	—	✓
from-user	text	User account that sent the message.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link into the message (Supposed harmless).	—	—
received-date	datetime	Received date of the message.	✓	—
sent-date	datetime	Initial sent date of the message.	✓	—
subject	text	Subject of the message if any.	—	—
to-name	text	Name of the person that received the message.	—	✓
to-number	phone-number	Phone number receiving the message.	—	✓
to-user	text	User account that received the message.	—	✓
url	url	Original URL location of the message (potentially malicious).	—	—

instant-message-group

Instant Message (IM) group object template describing a public or private IM group, channel or conversation.



instant-message-group is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
app-used	text	The IM application used to send the message. ['WhatsApp', 'Google Hangouts', 'Facebook Messenger', 'Telegram', 'Signal', 'WeChat', 'BlackBerry Messenger', 'TeamSpeak', 'TorChat', 'Tox', 'RetroShare', 'Slack']	✓	✓
archive	link	Archive of the original group (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	A screen capture or exported list of contacts, group members, etc.	—	✓
group-alias	text	Aliases of group, channel or community.	—	✓
group-name	text	The name of the group, channel or community.	—	—
link	link	Original link into the group (Supposed harmless).	—	—
person-name	text	A person who is a member of the group.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	Original URL location of the group (potentially malicious).	—	—
username	text	A user account who is a member of the group.	—	✓

intel471-vulnerability-intelligence

Intel 471 vulnerability intelligence object.



intel471-vulnerability-intelligence is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
activity-location-open-source	boolean	The vulnerability is being discussed in open source. ['True', 'False']	✓	—
activity-location-private	boolean	The vulnerability is being discussed in private/direct communications. ['True', 'False']	✓	—
activity-location-underground	boolean	The vulnerability is being discussed in the underground. ['True', 'False']	✓	—
countermeasures	text	Summary of countermeasures to protect against the vulnerability.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cve-id	text	The vulnerability's CVE ID.	—	—
cvss-score-v2	float	CVSS score (version 2).	✓	—
cvss-score-v3	float	CVSS score (version 3).	✓	—
detection	text	Detection signatures/definitions exist for the vulnerability.	✓	—
exploit-status-available	boolean	Exploit code for the vulnerability is available. ['True', 'False']	✓	—
exploit-status-not-observed	boolean	Exploit code or usage has not been observed for the vulnerability. ['True', 'False']	✓	—
exploit-status-productized	boolean	There is a module for the vulnerability in commercial exploit kits or network security tools. ['True', 'False']	✓	—
exploit-status-weaponized	boolean	The vulnerability has been used in an attack or has been included in an exploit kit. ['True', 'False']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
interest-level-disclosed-publicly	boolean	The vulnerability has been disclosed publicly. ['True', 'False']	✓	—
interest-level-exploit-sought	boolean	An exploit for the vulnerability is being sought. ['True', 'False']	✓	—
interest-level-researched-publicly	boolean	The vulnerability has been researched or documented publicly. ['True', 'False']	✓	—
modified	datetime	Last modification date.	✓	—
patch-status	text	Availability of a patch for the vulnerability.	✓	—
product-name	text	Product name.	✓	—
proof-of-concept	text	Proof of concept code or demonstration exists.	✓	—
published	datetime	Initial publication date.	✓	—
references	link	External references.	—	✓
risk-level	text	Risk level of the vulnerability.	✓	—
summary	text	Summary of the vulnerability.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
underground-activity-status	text	Indicates if underground activity has been observed for the vulnerability.	✓	—
underground-activity-summary	text	Description of underground activity related to the vulnerability.	✓	—
vendor-name	text	Vendor name.	✓	—
vulnerability-status	text	The status of vulnerability.	✓	—
vulnerability-type	text	The type of vulnerability.	✓	—
vulnerable-configuration	text	Vulnerable configuration in CPE format.	—	✓

intelmq_event

IntelMQ Event.



intelmq_event is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
classification.identifier	text	The lowercase identifier defines the actual software or service (e.g. 'heartbleed' or 'ntp_version') or standardized malware name (e.g. 'zeus'). Note that you MAY overwrite this field during processing for your individual setup. This field is not standardized across IntelMQ setups/users.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
classification.taxonomy	text	<p>We recognize the need for the CSIRT teams to apply a static (incident) taxonomy to abuse data. With this goal in mind the type IOC will serve as a basis for this activity. Each value of the dynamic type mapping translates to a element in the static taxonomy. The European CSIRT teams for example have decided to apply the eCSIRT.net incident classification. The value of the taxonomy key is thus a derivative of the dynamic type above. For more information about check [ENISA taxonomies](http://www.enisa.europa.eu/activities/cert/support/incident-management/browsable/incident-handling-process/incident-taxonomy/existing-taxonomies).</p>	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
classification.type	text	<p>The abuse type IOC is one of the most crucial pieces of information for any given abuse event. The main idea of dynamic typing is to keep our ontology flexible, since we need to evolve with the evolving threatscape of abuse data. In contrast with the static taxonomy below, the dynamic typing is used to perform business decisions in the abuse handling pipeline. Furthermore, the value data set should be kept as minimal as possible to avoid 'type explosion', which in turn dilutes the business value of the dynamic typing. In general, we normally have two types of abuse type IOC: ones referring to a compromised resource or ones referring to pieces of the criminal infrastructure, such as a command and control servers for example.</p>	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Free text commentary about the abuse event inserted by an analyst.	—	—
destination.abuse_contact	text	Abuse contact for destination address. A comma separated list.	—	—
destination.account	text	An account name or email address, which has been identified to relate to the destination of an abuse event.	—	—
destination.allocated	datetime	Allocation date corresponding to BGP prefix.	—	—
destination.as_name	text	The autonomous system name to which the connection headed.	—	—
destination.asn	AS	The autonomous system number to which the connection headed.	—	—
destination.domain_suffix	text	The suffix of the domain from the public suffix list.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
destination.fqdn	domain	A DNS name related to the host from which the connection originated. DNS allows even binary data in DNS, so we have to allow everything. A final point is stripped, string is converted to lower case characters.	—	—
destination.geolocation.cc	text	Country-Code according to ISO3166-1 alpha-2 for the destination IP.	—	—
destination.geolocation.city	text	Some geolocation services refer to city-level geolocation.	—	—
destination.geolocation.country	text	The country name derived from the ISO3166 country code (assigned to cc field).	—	—
destination.geolocation.latitude	float	Latitude coordinates derived from a geolocation service, such as MaxMind geoip db.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
destination.geolocation.longitude	float	Longitude coordinates derived from a geolocation service, such as MaxMind geoip db.	—	—
destination.geolocation.region	text	Some geolocation services refer to region-level geolocation.	—	—
destination.geolocation.state	text	Some geolocation services refer to state-level geolocation.	—	—
destination.ip	ip-dst	The IP which is the target of the observed connections.	—	—
destination.local_hostname	hostname	Some sources report a internal hostname within a NAT related to the name configured for a compromized system	—	—
destination.local_ip	ip-dst	Some sources report a internal (NATed) IP address related a compromized system. N.B. RFC1918 IPs are OK here.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
destination.network	ip-dst	CIDR for an autonomous system. Also known as BGP prefix. If multiple values are possible, select the most specific.	—	—
destination.port	counter	The port to which the connection headed.	—	—
destination.registry	text	The IP registry a given ip address is allocated by.	—	—
destination.reverse_dns	text	Reverse DNS name acquired through a reverse DNS query on an IP address. N.B. Record types other than PTR records may also appear in the reverse DNS tree. Furthermore, unfortunately, there is no rule prohibiting people from writing anything in a PTR record. Even JavaScript will work. A final point is stripped, string is converted to lower case characters.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
destination.tor_node	boolean	If the destination IP was a known tor node. ['True', 'False']	—	—
destination.url	url	A URL denotes on IOC, which refers to a malicious resource, whose interpretation is defined by the abuse type. A URL with the abuse type phishing refers to a phishing resource.	—	—
destination.urlpath	text	The path portion of an HTTP or related network request.	—	—
event_description.target	text	Some sources denominate the target (organization) of a an attack.	—	—
event_description.text	text	A free-form textual description of an abuse event.	—	—
event_description.url	url	A description URL is a link to a further description of the the abuse event in question.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
event_hash	text	Computed event hash with specific keys and values that identify a unique event. At present, the hash should default to using the SHA1 function. Please note that for an event hash to be able to match more than one event (deduplication) the receiver of an event should calculate it based on a minimal set of keys and values present in the event. Using for example the observation time in the calculation will most likely render the checksum useless for deduplication purposes.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
extra	text	All anecdotal information, which cannot be parsed into the data harmonization elements. E.g. os.name, os.version, etc. Note: this is only intended for mapping any fields which can not map naturally into the data harmonization. It is not intended for extending the data harmonization with your own fields.	—	—
feed.accuracy	float	A float between 0 and 100 that represents how accurate the data in the feed is	—	—
feed.code	text	Code name for the feed, e.g. DFGS, HSDAG etc.	—	—
feed.documentation	text	A URL or hint where to find the documentation of this feed.	—	—
feed.name	text	Name for the feed, usually found in collector bot configuration.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
feed.provider	text	Name for the provider of the feed, usually found in collector bot configuration.	—	—
feed.url	url	The URL of a given abuse feed, where applicable	—	—
malware.hash.md5	md5	A string depicting an MD5 checksum for a file, be it a malware sample for example.	—	—
malware.hash.sha1	sha1	A string depicting a SHA1 checksum for a file, be it a malware sample for example.	—	—
malware.hash.sha256	sha256	A string depicting a SHA256 checksum for a file, be it a malware sample for example.	—	—
malware.name	text	The malware name in lower case.	—	—
malware.version	text	A version string for an identified artifact generation, e.g. a crime-ware kit.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
misp.attribute_uuid	text	MISP - Malware Information Sharing Platform & Threat Sharing UUID of an attribute.	—	—
misp.event_uuid	text	MISP - Malware Information Sharing Platform & Threat Sharing UUID.	—	—
output	text	Event data converted into foreign format, intended to be exported by output plugin.	—	—
protocol.application	text	e.g. vnc, ssh, sip, irc, http or smtp.	—	—
protocol.transport	text	e.g. tcp, udp, icmp.	—	—
raw	text	The original line of the event from encoded in base64.	—	—
rtir_id	counter	Request Tracker Incident Response ticket id.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
screenshot_url	url	Some source may report URLs related to a an image generated of a resource without any metadata. Or an URL pointing to resource, which has been rendered into a webshot, e.g. a PNG image and the relevant metadata related to its retrieval/generation.	—	—
source.abuse_contact	text	Abuse contact for source address. A comma separated list.	—	—
source.account	text	An account name or email address, which has been identified to relate to the source of an abuse event.	—	—
source.allocated	datetime	Allocation date corresponding to BGP prefix.	—	—
source.as_name	text	The autonomous system name from which the connection originated.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
source.asn	AS	The autonomous system number from which originated the connection.	—	—
source.domain_suf fix	text	The suffix of the domain from the public suffix list.	—	—
source.fqdn	domain	A DNS name related to the host from which the connection originated. DNS allows even binary data in DNS, so we have to allow everything. A final point is stripped, string is converted to lower case characters.	—	—
source.geolocation .cc	text	Country-Code according to ISO3166-1 alpha-2 for the source IP.	—	—
source.geolocation .city	text	Some geolocation services refer to city-level geolocation.	—	—
source.geolocation .country	text	The country name derived from the ISO3166 country code (assigned to cc field).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
source.geolocation.cymru_cc	text	The country code denoted for the ip by the Team Cymru asn to ip mapping service.	—	—
source.geolocation.geoip_cc	text	MaxMind Country Code (ISO3166-1 alpha-2).	—	—
source.geolocation.latitude	float	Latitude coordinates derived from a geolocation service, such as MaxMind geoip db.	—	—
source.geolocation.longitude	float	Longitude coordinates derived from a geolocation service, such as MaxMind geoip db.	—	—
source.geolocation.region	text	Some geolocation services refer to region-level geolocation.	—	—
source.geolocation.state	text	Some geolocation services refer to state-level geolocation.	—	—
source.ip	ip-src	The ip observed to initiate the connection	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
source.local_hostname	hostname	Some sources report a internal hostname within a NAT related to the name configured for a compromised system	—	—
source.local_ip	ip-src	Some sources report a internal (NATed) IP address related a compromised system. N.B. RFC1918 IPs are OK here.	—	—
source.network	ip-src	CIDR for an autonomous system. Also known as BGP prefix. If multiple values are possible, select the most specific.	—	—
source.port	counter	The port from which the connection originated.	—	—
source.registry	text	The IP registry a given ip address is allocated by.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
source.reverse_dns	text	Reverse DNS name acquired through a reverse DNS query on an IP address. N.B. Record types other than PTR records may also appear in the reverse DNS tree. Furthermore, unfortunately, there is no rule prohibiting people from writing anything in a PTR record. Even JavaScript will work. A final point is stripped, string is converted to lower case characters.	—	—
source.tor_node	boolean	If the source IP was a known tor node. ['True', 'False']	—	—
source.url	url	A URL denotes an IOC, which refers to a malicious resource, whose interpretation is defined by the abuse type. A URL with the abuse type phishing refers to a phishing resource.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
source.urlpath	text	The path portion of an HTTP or related network request.	—	—
status	text	Status of the malicious resource (phishing, dropzone, etc), e.g. online, offline.	—	—
time.observation	datetime	The time the collector of the local instance processed (observed) the event.	—	—
time.source	datetime	The time of occurrence of the event as reported by the feed (source).	—	—
tlp	text	Traffic Light Protocol level of the event.	—	—

intelmq_report

IntelMQ Report.



intelmq_report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
extra	text	All anecdotal information of the report, which cannot be parsed into the data harmonization elements. E.g. subject of mails, etc. This is data is not automatically propagated to the events.	—	—
feed.accuracy	float	A float between 0 and 100 that represents how accurate the data in the feed is	—	—
feed.code	text	Code name for the feed, e.g. DFGS, HSDAG etc.	—	—
feed.documentation	text	A URL or hint where to find the documentation of this feed.	—	—
feed.name	text	Name for the feed, usually found in collector bot configuration.	—	—
feed.provider	text	Name for the provider of the feed, usually found in collector bot configuration.	—	—
feed.url	url	The URL of a given abuse feed, where applicable	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
raw	text	The original raw and unparsed data encoded in base64.	—	—
rtir_id	counter	Request Tracker Incident Response ticket id.	—	—
time.observation	datetime	The time the collector of the local instance processed (observed) the event.	—	—

internal-reference

Internal reference.



internal-reference is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	Comment associated to the identifier.	—	—
identifier	text	Identifier of the reference. Should be unique in your system.	—	—
link	link	Link associated to the identifier.	—	—
type	text	Type of internal reference.	—	—

interpol-notice

An object which describes a Interpol notice.



interpol-notice is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
alias	text	Alias name or known as.	—	✓
charges	text	Charges published as provided by requesting entity	✓	✓
colour-of-eyes	text	Description of a person's colour of eyes.	✓	—
colour-of-hair	text	Description of a person's colour of hair.	✓	—
date-of-birth	date-of-birth	Date of birth of a natural person (in YYYY-MM-DD format).	—	—
date-of-disappearance	text	Date of disappearance of a missing person.	—	—
distinguishing-marks-and-characteristics	text	Distinguishing marks and characteristics of a person.	✓	—
father-s-family-name-&-forename	text	Father's family name & forename.	—	—
forename	first-name	First name of a natural person.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
height	text	Height of a person.	✓	—
language-spoken	text	Languages spoken by a person.	✓	✓
mother-s-family-name-&-forename	text	Mother's family name & forename.	—	—
nationality	nationality	The nationality of a natural person.	✓	✓
notice-color	text	The color/type of the notice ['Red', 'Yellow', 'Blue', 'Black', 'Green', 'Orange', 'Purple']	—	—
place-of-birth	place-of-birth	Place of birth of a natural person.	✓	—
place-of-disappearance	text	Place of birth of a natural person.	—	—
portrait	attachment	Portrait of the person.	—	✓
present-family-name	last-name	Last name of a natural person.	—	—
sex	gender	The gender of a natural person. ['Male', 'Female', 'Other', 'Prefer not to say']	✓	—
weight	text	weight of a person.	✓	—

iot-device

An IoT device.



iot-device is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
architecture	text	architecture of the IoT device ['ARC', 'ARM', 'M68000', 'MicroBlaze', 'MIPS', 'NSD32', 'Nios II', 'PowerPC', 'RISC-V', 'Sandbox', 'SH', 'x86', 'Xtensa']	—	—
boot-log	attachment	Boot log of the IoT device	—	✓
fcc-id	text	FCC-ID of the IoT device	—	✓
jtag-interface	text	JTAG interface of the IoT device ['Yes', 'No', 'Unknown', 'Disabled']	✓	—
model	text	Model of the IoT device	—	✓
picture-device	attachment	Picture of the IoT device	—	✓
picture-pcb	attachment	Picture of the IoT device PCB	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
platform	text	Platform of of the IoT device ['mach-aspeed', 'mach-at91', 'mach-bcm283x', 'mach-bcmstb', 'mach-cortina', 'mach-davinci', 'mach-exynos', 'mach-highbank', 'mach-imx', 'mach-integrator', 'mach-k3', 'mach-keystone', 'mach-kirkwood', 'machmediatek', 'mach-meson', 'mach-mvebu', 'mach-omap2', 'mach-orion5x', 'mach-owl', 'mach-qemu', 'mach-rmobile', 'mach-rockchip', 'mach-s5pc1xx', 'mach-snapdragon', 'mach-socfpga', 'mach-sti', 'mach-stm32', 'mach-stm32mp', 'mach-sunxi', 'mach-tegra', 'mach-u8500', 'mach-uniphier', 'mach-versal', 'mach-versatile', 'mach-zynq', 'mach-zynqmp', 'mach-zynqmp-r5', 'mcf5227x', 'mcf523x', 'mcf52x2', 'mcf530x', 'mcf532x', 'mcf5445x', 'mcf547x_8x', 'mach-ath79', 'mach-bmips',	—	—
288				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
reference	link	Reference of the IoT device	—	✓
serial-interface	text	Serial interface of the IoT device ['Yes', 'No', 'Unknown', 'Disabled']	✓	—
spi-interface	text	SPI interface of the IoT device ['Yes', 'No', 'Unknown', 'Disabled']	✓	—
vendor	text	Vendor of the IoT device	—	—

iot-firmware

A firmware for an IoT device.



iot-firmware is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
binwalk-entropy-graph	attachment	Entropy graph of the firmware	✓	—
binwalk-output	attachment	Binwalk output of the firmware image	—	—
boot-log	attachment	Boot log of the IoT device for this firmware	—	✓
filename	text	Filename of the firmware	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
firmware	attachment	Firmware of the IoT device	—	✓
format	text	Format of the firmware ['raw', 'Intel hex', 'Motorola S-Record', 'Unknown']	—	—
md5	md5	[Insecure] MD5 hash (128 bits)	—	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—	—
size-in-bytes	size-in-bytes	Size of the file, in bytes	✓	—
version	text	Version of the firmware	—	✓

ip-api-address

IP Address information. Useful if you are pulling your ip information from ip-api.com.



ip-api-address is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ISP	text	ISP.	✓	—
asn	AS	Autonomous System Number	✓	—
city	text	City.	✓	—
country	text	Country name	✓	—
country-code	text	Country code	✓	—
first-seen	datetime	First time the ASN was seen	✓	—
ip-src	ip-src	Source IP address of the network connection.	—	—
last-seen	datetime	Last time the ASN was seen	✓	—
latitude	float	The latitude is the decimal value of the latitude in the World Geodetic System 84 (WGS84) reference.	✓	—
longitude	float	The longitude is the decimal value of the longitude in the World Geodetic System 84 (WGS84) reference	✓	—
organization	text	organization	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
region	text	Region. example: California.	✓	—
region-code	text	Region code. example: CA	✓	—
state	text	State.	✓	—
zipcode	text	Zip Code.	✓	—

ip-port

An IP address (or domain or hostname) and a port seen as a tuple (or as a triple) in a specific time frame.



ip-port is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
AS	AS	Autonomous system	✓	✓
country-code	text	Country Code	✓	—
domain	domain	Domain	—	✓
dst-port	port	Destination port	✓	✓
first-seen	datetime	First time the tuple has been seen	✓	—
hostname	hostname	Hostname	—	✓
ip	ip-dst	IP Address	—	✓
ip-dst	ip-dst	destination IP address	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ip-src	ip-src	source IP address	—	✓
last-seen	datetime	Last time the tuple has been seen	✓	—
protocol	text	Protocol	✓	—
src-port	port	Source port	✓	✓
text	text	Description of the tuple	✓	—

irc

An IRC object to describe an IRC server and the associated channels.



irc is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
channel	text	IRC channel associated to the IRC server	—	✓
dst-port	port	Destination port to reach the IRC server	✓	✓
first-seen	datetime	First time the IRC server with the associated channels has been seen	✓	—
hostname	hostname	Hostname of the IRC server	—	✓
ip	ip-dst	IP address of the IRC server	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
last-seen	datetime	Last time the IRC server with the associated channels has been seen	✓	—
nickname	text	IRC nickname used to connect to the associated IRC server and channels	—	✓
text	text	Description of the IRC server	✓	—

ja3

JA3 is a new technique for creating SSL client fingerprints that are easy to produce and can be easily shared for threat intelligence. Fingerprints are composed of Client Hello packet; SSL Version, Accepted Ciphers, List of Extensions, Elliptic Curves, and Elliptic Curve Formats. <https://github.com/salesforce/ja3>.



ja3 is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Type of detected software ie software, malware	—	—
first-seen	datetime	First seen of the SSL/TLS handshake	✓	—
ip-dst	ip-dst	Destination IP address	—	—
ip-src	ip-src	Source IP Address	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ja3-fingerprint-md5	ja3-fingerprint-md5	Hash identifying source	—	—
last-seen	datetime	Last seen of the SSL/TLS handshake	✓	—

ja3s

JA3S is JA3 for the Server side of the SSL/TLS communication and fingerprints how servers respond to particular clients. JA3S fingerprints are composed of Server Hello packet; SSL Version, Cipher, SSLExtensions. <https://github.com/salesforce/ja3>.



ja3s is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Type of detected software ie software, malware, c&c	—	—
first-seen	datetime	First seen of the SSL/TLS handshake	✓	—
ip-dst	ip-dst	Destination IP address	—	—
ip-src	ip-src	Source IP Address	—	—
ja3-fingerprint-md5	ja3-fingerprint-md5	Hash identifying client	—	—
ja3s-fingerprint-md5	ja3-fingerprint-md5	Hash identifying server	—	—
last-seen	datetime	Last seen of the SSL/TLS handshake	✓	—

jarm

Jarm object to describe an TLS/SSL implementation used for malicious or legitimate use-case.



jarm is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
jarm	jarm-fingerprint	JARM Hash of this implementation	—	—
reference	link	Reference to the tool matching this fingerprint	✓	—
scope	text	Scope of the tool ['Malicious - C2', 'Malicious - Client', 'Malicious - Unknown', 'Legitimate', 'Undefined']	✓	—
tls-implementation	text	SSL/TLS implementation matching this object	✓	—
tool	text	Tool having this jarm fingerprint	✓	—

keybase-account

Information related to a keybase account, from API Users Object.



keybase-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bio	text	Bio of the keybase user	—	—
cryptocurrency_adresses	btc	Associated cryptocurrency address with the keybase user	—	✓
emails	text	Emails associated with the keybase user	—	✓
full_name	text	Full name	—	—
id	text	Keybase user identifier	—	—
location	text	Location	—	—
private_keys	text	OpenPGP private keys associated with the keybase user	—	✓
public_keys	text	OpenPGP public keys associated with the keybase user	—	✓
username	text	Keybase username	—	—

language-content

The Language Content object represents text content for objects represented in languages other than that of the original object. Language content may be a translation of the original object by a third-party, a first-source translation by the original publisher, or additional official language content provided at the time of creation. STIX 2.1 ref 7.1.



language-content is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
content	text	The contents property contains the actual Language Content (translation).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
language	text	RFC 5646 language codes for which language content is being provided. ['af', 'af-ZA', 'ar', 'ar-AE', 'ar-BH', 'ar-DZ', 'ar-EG', 'ar-IQ', 'ar-JO', 'ar-KW', 'ar-LB', 'ar-LY', 'ar-MA', 'ar-OM', 'ar-QA', 'ar-SA', 'ar-SY', 'ar-TN', 'ar-YE', 'az', 'az-AZ', 'az-Cyrl-AZ', 'be', 'be-BY', 'bg', 'bg-BG', 'bs-BA', 'ca', 'ca-ES', 'cs', 'cs-CZ', 'cy', 'cy-GB', 'da', 'da-DK', 'de', 'de-AT', 'de-CH', 'de-DE', 'de-LI', 'de-LU', 'dv', 'dv-MV', 'el', 'el-GR', 'en', 'en-AU', 'en-BZ', 'en-CA', 'en-CB', 'en-GB', 'en-IE', 'en-JM', 'en-NZ', 'en-PH', 'en-TT', 'en-US', 'en-ZA', 'en-ZW', 'eo', 'es', 'es-AR', 'es-BO', 'es-CL', 'es-CO', 'es-CR', 'es-DO', 'es-EC', 'es-ES', 'es-GT', 'es-HN', 'es-MX', 'es-NI', 'es-PA', 'es-PE', 'es-PR', 'es-PY', 'es-SV', 'es-UY', 'es-VE', 'et', 'et-EE', 'eu', 'eu-ES', 'fa', 'fa-IR', 'fi', 'fi-FI', 'fo', 'fo-FO', 'fr', 'fr-BE', 'fr-CA', 'fr-CH', 'fr-FR', 'fr-LU', 'fr-MC', 'gl', 'gl-ES', 'gu', 'gu-IN', 'he', 'he-IL', 'hi', 'hi-IN', 'hr', 'hr-BA', 'hr-HR', 'hu', 'hu-']	✓	—

leaked-document

Object describing a leaked document. HU', 'hy', 'hy-AM',
'id', 'id-ID', 'is', 'is-



leaked-document is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

'ka-GE', 'kk', 'kk-KZ', 'kn', 'kn-IN',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	-	✓
attachment	attachment	The leaked document file.	-	-
document-name	text	Title of the document.	-	-
document-text	text	Raw text of document	-	-
document-type	text	The type of document (not the file type). ['email', 'letterhead', 'speech', 'literature', 'photo', 'audio', 'invoice', 'receipt', 'other']	✓	✓
first-seen	datetime	When the document has been accessible or seen for the first time.	✓	-
last-seen	datetime	When the document has been accessible or seen for the last time.	✓	-

ZH-SG, ZH-TW,
'zu', 'zu-ZA']

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link into the document (Supposed harmless)	—	—
objective	text	Reason for leaking the document. ['Disinformation', 'Influence', 'Whistleblowing', 'Extortion', 'Other']	✓	✓
origin	text	Original source of leaked document.	—	—
purpose-of-document	text	What the document is used for. ['Identification', 'Travel', 'Health', 'Legal', 'Financial', 'Government', 'Military', 'Media', 'Communication', 'Other']	✓	✓
url	url	Original URL location of the document (potentially malicious)	—	—

legal-entity

An object to describe a legal entity.



legal-entity is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
business	text	Business area of the entity.	—	—
commercial-name	text	Commercial name of the entity.	—	—
legal-form	text	Legal form of the entity.	—	—
logo	attachment	Logo of the entity.	—	—
name	text	Name of the entity.	—	—
phone-number	phone-number	Phone number of the entity.	—	—
registration-number	text	Registration number of the entity in the relevant authority.	—	—
text	text	A description of the entity.	✓	—
website	link	Website of the entity.	—	—

lnk

LNK object describing a Windows LNK binary file (aka Windows shortcut).



Lnk is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
birth-droid-file-identifier	text	Birth droid volume identifier (UUIDv1 where MAC can be extracted)	—	—
birth-droid-volume-identifier	text	Droid volume identifier	—	—
droid-file-identifier	text	Droid file identifier (UUIDv1 where MAC can be extracted)	—	—
droid-volume-identifier	text	Droid volume identifier	—	—
entropy	float	Entropy of the whole file	✓	—
filename	filename	Filename on disk	✓	✓
fullpath	text	Complete path of the LNK filename including the filename	—	✓
lnk-access-time	datetime	Access time of the LNK	✓	—
lnk-command-line-arguments	text	LNK command line arguments	✓	—
lnk-creation-time	datetime	Creation time of the LNK	✓	—
lnk-description	text	LNK description	✓	—
lnk-drive-serial-number	text	Drive serial number	—	—
lnk-drive-type	text	Drive type	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
lnk-file-attribute-flags	text	File attribute flags	✓	—
lnk-file-size	size-in-bytes	Size of the target file, in bytes	✓	—
lnk-hot-key-value	text	Hot Key value	✓	—
lnk-icon-index	text	Icon index	✓	—
lnk-local-path	text	Local path	✓	—
lnk-modification-time	datetime	Modification time of the LNK	✓	—
lnk-relative-path	text	Relative path	✓	—
lnk-show-window-value	text	Show Window value	✓	—
lnk-volume-label	text	Volume label	✓	—
lnk-working-directory	text	LNK working path	✓	—
machine-identifier	text	Machine identifier	—	—
malware-sample	malware-sample	The LNK file itself (binary)	—	—
md5	md5	[Insecure] MD5 hash (128 bits)	—	—
path	text	Path of the LNK filename complete or partial	✓	✓
pattern-in-file	pattern-in-file	Pattern that can be found in the file	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—	—
size-in-bytes	size-in-bytes	Size of the LNK file, in bytes	✓	—
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—	—
state	text	State of the LNK file ['Malicious', 'Harmless', 'Trusted']	✓	✓
text	text	Free text value to attach to the file	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
tlsh	tlsh	Fuzzy hash by Trend Micro: Locality Sensitive Hash	—	—

macho

Object describing a file in Mach-O format.



macho is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
entrypoint-address	text	Address of the entry point	✓	—
name	text	Binary's name	—	—
number-sections	counter	Number of sections	✓	—
text	text	Free text value to attach to the Mach-O file	✓	—
type	text	Type of Mach-O ['BUNDLE', 'CORE', 'DSYM', 'DYLIB', 'DYLIB_STUB', 'DYLINKER', 'EXECUTE', 'FVMLIB', 'KEXT_BUNDLE', 'OBJECT', 'PRELOAD']	—	—

macho-section

Object describing a section of a file in Mach-O format.



macho-section is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
entropy	float	Entropy of the whole section	✓	—
md5	md5	[Insecure] MD5 hash (128 bits)	—	—
name	text	Name of the section	✓	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—	—
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—	—
text	text	Free text value to attach to the section	✓	—

mactime-timeline-analysis

Mactime template, used in forensic investigations to describe the timeline of a file activity.



mactime-timeline-analysis is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
activityType	text	Determines the type of activity conducted on the file at a given time ['Accessed', 'Created', 'Changed', 'Modified', 'Other']	✓	—
datetime	datetime	Date and time when the operation was conducted on the file	✓	—
file	attachment	Mactime output file	✓	—
file-path	text	Location of the file on the disc	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
filePermissions	text	Describes permissions assigned the file	✓	—
file_size	text	Determines the file size in bytes	✓	—

malware-config

Malware configuration recovered or extracted from a malicious binary.



malware-config is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
config	text	Raw (decrypted, decoded) text of the malware configuration.	—	—
encrypted	text	Encrypted or encoded text of the malware configuration in base64.	—	—
first-seen	datetime	When the malware configuration has been seen for the first time.	✓	—
format	text	Original format of the malware configuration. ['JSON', 'yaml', 'INI', 'other']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
last-seen	datetime	When the malware configuration has been seen for the last time.	✓	—
password	text	Password or encryption key used to encrypt the malware configuration.	—	—

meme-image

Object describing a meme (image).



meme-image is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
5Ds-of-propaganda	text	5 D's of propaganda are tactics of rebuttal used to defend against criticism and adversarial narratives. ['dismiss', 'distort', 'distract', 'dismay', 'divide']	✓	✓
a/b-test	boolean	A flag to define if this meme is part of an a/b test. If set to true, it is part of an a/b test set. ['True', 'False']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The image file.	—	—
crosspost	link	Safe site where the meme has been posted.	—	✓
crosspost-unsafe	url	Unsafe site where the meme has been posted.	—	✓
document-text	text	Raw text of meme	—	—
first-seen	datetime	When the meme has been accessible or seen for the first time.	✓	—
last-seen	datetime	When the meme has been accessible or seen for the last time.	✓	—
link	link	Original link into the meme (Supposed harmless)	—	—
meme-reference	link	A link to know-your-meme or similar reference material.	—	—
objective	text	Objective of the meme. ['Disinformation', 'Advertising', 'Parody', 'Other']	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	Original URL location of the meme (potentially malicious)	—	—
username	text	Username who posted the meme.	—	—

microblog

Microblog post like a Twitter tweet or a post on a Facebook wall.



microblog is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The microblog post file or screen capture.	—	✓
creation-date	datetime	Initial creation of the microblog post	—	—
display-name	text	Display name of the account who posted the microblog.	—	—
embedded-link	url	Link into the microblog post	—	✓
embedded-safe-link	link	Safe link into the microblog post	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hashtag	text	Hashtag embedded in the microblog post	—	✓
in-reply-to-display-name	text	The user display name of the microblog this post replies to.	—	✓
in-reply-to-status-id	text	The microblog ID of the microblog this post replies to.	—	✓
in-reply-to-user-id	text	The user ID of the microblog this post replies to.	—	✓
language	text	The language of the post.	—	✓
link	link	Original link to the microblog post (supposed harmless).	—	✓
modification-date	datetime	Last update of the microblog post	—	—
post	text	Raw text of the post.	—	—
removal-date	datetime	When the microblog post was removed.	—	—
state	text	State of the microblog post ['Informative', 'Malicious', 'Misinformation', 'Disinformation', 'Unknown']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
title	text	Title of the post.	—	—
twitter-id	twitter-id	The microblog post id.	—	✓
type	text	Type of the microblog post ['Twitter', 'Facebook', 'LinkedIn', 'Reddit', 'Google+', 'Instagram', 'Forum', 'Other']	✓	—
url	url	Original URL of the microblog post (potentially malicious).	—	✓
username	text	Username who posted the microblog post (without the @ prefix)	—	—
username-quoted	text	Username who are quoted in the microblog post.	—	✓
verified-username	text	Is the username account verified by the operator of the microblog platform ['Verified', 'Unverified', 'Unknown']	✓	—

mutex

Object to describe mutual exclusion locks (mutex) as seen in memory or computer program.



mutex is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description	—	—
name	text	name of the mutex	—	—
operating-system	text	Operating system where the mutex has been seen ['Windows', 'Unix']	—	—

narrative

Object describing a narrative.



narrative is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
5Ds-of-propaganda	text	5 D's of propaganda are tactics of rebuttal used to defend against criticism and adversarial narratives. ['dismiss', 'distort', 'distract', 'dismay', 'divide']	✓	✓
archive	link	Archive of the original narrative source (Internet Archive, Archive.is, etc).	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	Documents related to the narrative.	—	—
external-references	link	Link to external references.	✓	—
link	link	Original link to the narrative source (Supposed harmless)	—	—
narrative-disproof	text	Disproof or evidence against the narrative.	✓	—
narrative-summary	text	A summary of the narrative.	—	—
objective	text	Objective of the narrative. ['Disinformation', 'Advertising', 'Parody', 'Other']	✓	✓
url	url	Original link to the narrative source (Supposed malicious)	—	—

netflow

Netflow object describes an network object based on the Netflowv5/v9 minimal definition.



netflow is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
byte-count	counter	Bytes counted in this flow	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
community-id	community-id	Community id of the represented flow	—	—
direction	text	Direction of this flow ['Ingress', 'Egress']	✓	—
dst-as	AS	Destination AS number for this flow	—	—
dst-port	port	Destination port of the netflow	—	—
first-packet-seen	datetime	First packet seen in this flow	✓	—
flow-count	counter	Flows counted in this flow	✓	—
icmp-type	text	ICMP type of the flow (if the traffic is ICMP)	✓	—
ip-dst	ip-dst	IP address destination of the netflow	—	—
ip-protocol-number	size-in-bytes	IP protocol number of this flow	✓	—
ip-src	ip-src	IP address source of the netflow	—	—
ip_version	counter	IP version of this flow	✓	—
last-packet-seen	datetime	Last packet seen in this flow	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
packet-count	counter	Packets counted in this flow	✓	—
protocol	text	Protocol used for this flow ['TCP', 'UDP', 'ICMP', 'IP']	✓	—
src-as	AS	Source AS number for this flow	—	—
src-port	port	Source port of the netflow	—	—
tcp-flags	text	TCP flags of the flow	✓	—

network-connection

A local or remote network connection.



network-connection is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
community-id	community-id	Flow description as a community ID hash value	—	—
dst-port	port	Destination port of the nework connection.	—	—
first-packet-seen	datetime	Datetime of the first packet seen.	✓	—
hostname-dst	hostname	Destination hostname of the network connection.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hostname-src	hostname	Source hostname of the network connection.	—	—
ip-dst	ip-dst	Destination IP address of the nework connection.	—	—
ip-src	ip-src	Source IP address of the nework connection.	—	—
layer3-protocol	text	Layer 3 protocol of the network connection. ['IP', 'ICMP', 'ARP']	✓	—
layer4-protocol	text	Layer 4 protocol of the network connection. ['TCP', 'UDP']	✓	—
layer7-protocol	text	Layer 7 protocol of the network connection. ['HTTP', 'HTTPS', 'FTP']	✓	—
src-port	port	Source port of the nework connection.	—	—

network-profile

Elements that can be used to profile, pivot or identify a network infrastructure, including domains, ip and urls.



network-profile is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
asn	AS	ASN where the content is hosted	—	—
certificate-common-name	text	Certificate common name	—	—
certificate-country	text	Certificate country name	—	—
certificate-creation-date	datetime	Certificate date it was created	—	—
certificate-expiry-date	datetime	Certificate date it will expire	—	—
certificate-issuer	text	Certificate Issuer	—	—
certificate-organization	text	Certificate organization	—	—
certificate-organization-locality	text	Certificate locality	—	—
certificate-organization-state	text	Certificate state or provincy name	—	—
certificate-organization-unit	text	Certificate organization unit	—	—
dns-server	hostname	DNS server	—	✓
domain	domain	Domain of the whois entry	—	✓
evidences	attachment	Screenshot of the network resources.	✓	✓
google-analytics-id	text	Google analytics IDS	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hosting-provider	text	The hosting provider/ISP where the resources are.	—	—
ip-address	ip-src	IP address of the whois entry	—	✓
jarm	jarm-fingerprint	JARM Footprint string	—	—
port	port	Port number	✓	—
query_string	text	Query (after path, preceded by '?')	—	✓
resource_path	text	Path (between hostname:port and query)	—	✓
service-abuse	text	Service abused by threat actors as part of their infrastructure. ['OneDrive', 'Google Drive', 'Dropbox', 'Microsoft', 'Google', 'DuckDNS', 'Cloudflare', 'AWS']	—	✓
subdomain	text	Subdomain	✓	—
text	text	Full whois entry	✓	—
threat-actor-infrastructure-pattern	text	Patterns found on threat actor infrastructure that can correlate with other analysis.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
threat-actor-infrastructure-value	text	Unique value found on threat actor infrastructure identified through an investigation.	—	✓
tld	text	Top-Level Domain	✓	—
url	url	Full URL	—	—
whois-creation-date	datetime	Initial creation of the whois entry	✓	—
whois-expiration-date	datetime	Expiration of the whois entry	✓	—
whois-registrant-email	whois-registrant-email	Registrant email address	—	—
whois-registrant-name	whois-registrant-name	Registrant name	—	—
whois-registrant-org	whois-registrant-org	Registrant organisation	—	—
whois-registrant-phone	whois-registrant-phone	Registrant phone number	—	—
whois-registrar	whois-registrar	Registrar of the whois entry	—	—

network-socket

Network socket object describes a local or remote network connections based on the socket data structure.



network-socket is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address-family	text	Address family who specifies the address family type (AF_*) of the socket connection. ['AF_UNSPEC', 'AF_LOCAL', 'AF_UNIX', 'AF_FILE', 'AF_INET', 'AF_AX25', 'AF_IPX', 'AF_APPLETALK', 'AF_NETROM', 'AF_BRIDGE', 'AF_ATMPVC', 'AF_X25', 'AF_INET6', 'AF_ROSE', 'AF_DECnet', 'AF_NETBEUI', 'AF_SECURITY', 'AF_KEY', 'AF_NETLINK', 'AF_ROUTE', 'AF_PACKET', 'AF_ASH', 'AF_ECONET', 'AF_ATMSVC', 'AF_RDS', 'AF_SNA', 'AF_IRDA', 'AF_PPPOX', 'AF_WANPIPE', 'AF_LLC', 'AF_IB', 'AF MPLS', 'AF_CAN', 'AF_TIPC', 'AF_BLUETOOTH', 'AF_IUCV', 'AF_RXRPC', 'AF_ISDN', 'AF_PHONET', 'AF_IEEE802154', 'AF_CAIF', 'AF_ALG', 'AF_NFC', 'AF_VSOCK', 'AF_KCM',	—	—
324				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
domain-family	text	Domain family who specifies the communication domain (PF_*) of the socket connection. ['PF_UNSPEC', 'PF_LOCAL', 'PF_UNIX', 'PF_FILE', 'PF_INET', 'PF_AX25', 'PF_IPX', 'PF_APPLETALK', 'PF_NETROM', 'PF_BRIDGE', 'PF_ATMPVC', 'PF_X25', 'PF_INET6', 'PF_ROSE', 'PF_DECnet', 'PF_NETBEUI', 'PF_SECURITY', 'PF_KEY', 'PF_NETLINK', 'PF_ROUTE', 'PF_PACKET', 'PF_ASH', 'PF_ECONET', 'PF_ATMSVC', 'PF_RDS', 'PF_SNA', 'PF_IRDA', 'PF_PPPOX', 'PF_WANPIPE', 'PF_LLC', 'PF_IB', 'PF_MPLS', 'PF_CAN', 'PF_TIPC', 'PF_BLUETOOTH', 'PF_IUCV', 'PF_RXRPC', 'PF_ISDN', 'PF_PHONET', 'PF_IEEE802154', 'PF_CAIF', 'PF_ALG', 'PF_NFC', 'PF_VSOCK',	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
dst-port	port	Destination port of the network socket connection.	—	—
filename	filename	Socket using filename	—	—
hostname-dst	hostname	Destination hostname of the network socket connection.	—	—
hostname-src	hostname	Source (local) hostname of the network socket connection.	—	—
ip-dst	ip-dst	Destination IP address of the network socket connection.	—	—
ip-src	ip-src	Source (local) IP address of the network socket connection.	—	—
option	text	Option on the socket connection.	—	✓
protocol	text	Protocol used by the network socket. ['TCP', 'UDP', 'ICMP', 'IP']	—	—
socket-type	text	Type of the socket. ['SOCK_STREAM', 'SOCK_DGRAM', 'SOCK_RAW', 'SOCK_RDM', 'SOCK_SEQPACKET']	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
src-port	port	Source (local) port of the network socket connection.	—	—
state	text	State of the socket connection. ['blocking', 'listening']	—	✓

news-agency

News agencies compile news and disseminate news in bulk.



news-agency is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Postal address of the news agency.	—	✓
alias	text	Alias of the news agency.	✓	✓
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The news file, screen capture, audio, etc.	—	✓
e-mail	email-src	Email address of the organization.	—	✓
fax-number	phone-number	Fax number of the news agency.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link to the news agency (Supposed harmless).	—	✓
name	text	Name of the news agency.	✓	—
phone-number	phone-number	Phone number of the news agency.	—	✓
url	url	Original URL location of the news agency (potentially malicious).	—	✓

news-media

News media are forms of mass media delivering news to the general public.



news-media is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Postal address of the news source.	—	✓
alias	text	Alias of the news source.	✓	✓
archive	link	Archive of the news (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The news file, screen capture, audio, etc.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
content	text	Raw content of the news.	—	—
e-mail	email-src	Email address of the news source.	—	✓
embedded-link	url	Site linked by the blog post.	—	✓
embedded-safe-link	link	Safe site linked by the blog post.	—	✓
fax-number	phone-number	Fax number of the news source.	—	✓
link	link	Original link to news (Supposed harmless).	—	✓
phone-number	phone-number	Phone number of the news source.	—	✓
source	text	Name of the news source.	✓	—
sub-type	text	Format of the news post (business daily, local news, metasite, etc). ['Business Daily', 'Local News', 'State News', 'National News', 'Metasite', 'Political Commentary', 'Clipper', 'Pressure Group', 'Staging', 'Trade Site', 'Other']	✓	—
title	text	Title of the post.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
transcription	text	Transcribed audio/visual content.	—	—
type	text	Type of news media (newspaper, TV, podcast, etc). ['Newspaper', 'Newspaper (Online)', 'Magazine', 'Magazine (Online)', 'TV', 'Tube', 'Radio', 'Radio (Online)', 'Podcast', 'Alternative Media', 'Other']	✓	✓
url	url	Original URL location of news (potentially malicious).	—	✓
username	text	Username who posted the blog post.	—	—

open-data-security

An object describing an open dataset available and described under the open data security model.
ref. <https://github.com/CIRCL/open-data-security>.



open-data-security is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	comment	an exhaustive description of the dataset including methods of collection, extraction or analysis	✓	—
frequency	text	frequency of the dataset generation which MUST be expressed in yearly, monthly, daily, hourly ['yearly', 'monthly', 'daily', 'hourly']	✓	—
human-validated	text	human-validated describes if the dataset has been manually validated ['true', 'false', 'unknown']	✓	—
license	text	license MUST be expressed in SPDX format to describe under which license the dataset is distributed	✓	—
link	link	link to open dataset	—	—
machine-validated	text	machine-validated describes if the dataset has been automatically validated ['true', 'false', 'unknown']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
producer	link	producer MUST be expressed as an URI to reference the original producer of the dataset	—	—
source	text	original source of the dataset	✓	✓
subtitle	text	an extended title of the dataset	✓	—
time-precision	text	time-precision MUST be expressed in years, months, days, hours, minutes or seconds to describe the precision of the time expressed ['years', 'months', 'days', 'hours', 'minutes', 'seconds']	✓	—
title	text	a comprehensive and concise title of the dataset	✓	—

organization

An object which describes an organization.



organization is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
VAT	text	VAT or TAX-ID of the organization	—	✓
address	text	Postal address of the organization.	—	✓
alias	text	Alias of the organization	—	✓
date-of-inception	datetime	Date of inception of the organization	—	—
description	text	Description of the organization	—	—
e-mail	email-src	Email address of the organization.	—	✓
fax-number	phone-number	Fax number of the organization.	—	✓
name	text	Name of the organization	—	—
phone-number	phone-number	Phone number of the organization.	—	✓
registration-number	text	Registration number of the organization	—	—
role	text	The role of the organization. ['Suspect', 'Victim', 'Defendant', 'Accused', 'Culprit', 'Accomplice', 'Target', 'Source', 'Originator', 'Informant', 'Emitter']	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type-of-organization	text	Type of the organization	—	—

original-imported-file

Object describing the original file used to import data in MISP.



original-imported-file is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
format	text	Format of data imported. ['STIX 1.0', 'STIX 1.1', 'STIX 1.2', 'STIX 2.0', 'OpenIOC']	✓	—
imported-sample	attachment	The original imported file itself (binary).	✓	—
uri	uri	URI related to the imported file.	—	—

paloalto-threat-event

Palo Alto Threat Log Event.



paloalto-threat-event is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
app	text	The application identified (e.g. vnc, ssh, sip, irc, http or smtp).	✓	—
direction	text	The Direction of the Event.	✓	—
dport	counter	The port to which the connection headed.	✓	—
dst	ip-dst	The Destination IP which is the target of the observed connections.	—	—
dstloc	text	The Destination Location of the event.	✓	—
proto	text	The transport protocol (e.g. tcp, udp, icmp).	✓	—
sport	counter	The port from which the connection originated.	✓	—
src	ip-src	The ip observed to initiate the connection	—	—
srcloc	text	The Source Location of the event.	✓	—
subtype	text	The subtype of the Log Event.	✓	—
thr_category	text	The Threat Category.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
threatid	text	The Threat ID.	✓	—
time_generated	datetime	The datetime of the event.	✓	—
type	text	The type of the Log Event	✓	—

parler-account

Parler account.



parler-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
account-id	text	Numeric id of the account.	—	—
account-name	text	Name of the account.	—	—
archive	link	Archive of the original parley (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The parley file or screen capture.	—	✓
badge	float	Post badge.	✓	✓
bio	text	The account bio.	—	—
comments	text	The number of user comments.	✓	—
cover-photo	attachment	Comment controversy.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
followers	text	Number of followers.	✓	—
following	text	Number user is following.	✓	—
human	boolean	Account 'human' bool. ['True', 'False']	✓	—
interactions	float	Account interactions.	✓	—
likes	text	Number user likes.	✓	—
link	link	Original URL of the parley (supposed harmless).	—	✓
posts	text	Number user posts.	✓	—
profile-photo	attachment	Comment controversy.	—	—
score	text	User score.	✓	—
url	url	Original URL of the parley, e.g. link shortener (potentially malicious).	—	✓
verified	boolean	Account 'verified' bool. ['True', 'False']	✓	—

parler-comment

Parler comment.



parler-comment is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original parley (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The parley file or screen capture.	—	✓
badge	float	Comment badge.	✓	—
body	text	Raw text of the post.	—	—
comment-depth	float	Comment nesting depth.	✓	—
comments	text	Comments on this object.	✓	—
controversy	float	Comment controversy.	✓	—
creator	text	Name of the account that posted this parley.	—	—
creator-id	text	ID of the account that posted this parley.	—	—
downvotes	text	Comment downvotes.	✓	—
embedded-link	url	Link in the parley	—	✓
embedded-safe-link	link	Safe link in the parley	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hashtag	text	Hashtag embedded in the parley.	—	✓
in-reply-to-display-name	text	The user display name of the parley this post shares.	—	✓
in-reply-to-parley-id	text	The Parler ID of the parley that this post shares.	—	✓
in-reply-to-user-id	text	The user ID of the parley this post shares.	—	✓
link	link	Original link to the post (supposed harmless).	—	✓
post-id	text	Numeric id of the parley.	—	—
score	text	Comment score.	✓	—
upvotes	text	Comment upvotes.	✓	—
url	url	Original URL of the parley, e.g. link shortener (potentially malicious).	—	✓
username-quoted	text	Username who is quoted in the parley.	—	✓

parler-post

Parler post (parley).



parler-post is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original parley (Internet Archive, Archive.is, etc).	—	✓
article	boolean	Indicates if the post is an article. ['True', 'False']	✓	—
attachment	attachment	The parley file or screen capture.	—	✓
badge	float	Post badge.	✓	—
body	text	Raw text of the post.	—	—
comments	text	Number of comments on this object.	✓	—
creator	text	Name of the account that posted this parley.	—	—
creator-id	text	ID of the account that posted this parley.	—	—
depth	float	Post nesting depth.	✓	—
embedded-link	url	Link in the parley	—	✓
embedded-safe-link	link	Safe link in the parley	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hashtag	text	Hashtag embedded in the parley.	—	✓
impressions	text	Number of impressions.	✓	—
in-reply-to-display-name	text	The user display name of the parley this post shares.	—	✓
in-reply-to-parley-id	text	The Parler ID of the parley that this post shares.	—	✓
in-reply-to-user-id	text	The user ID of the parley this post shares.	—	✓
link	link	Original link to the post (supposed harmless).	—	✓
post-id	text	Numeric id of the parley.	—	—
share-link	link	Sharable link generated by Parler (supposed harmless).	—	✓
upvotes	text	Comment upvotes.	✓	—
url	url	Original URL of the parley, e.g. link shortener (potentially malicious).	—	✓
username-quoted	text	Username who is quoted in the parley.	—	✓

passive-dns

Passive DNS records as expressed in draft-dulaunoy-dnsop-passive-dns-cof-07. See <https://tools.ietf.org/id/draft-dulaunoy-dnsop-passive-dns-cof-07.html>.



passive-dns is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
bailiwick	domain	Best estimate of the apex of the zone where this data is authoritative	✓	—
count	counter	How many authoritative DNS answers were received at the Passive DNS Server's collectors with exactly the given set of values as answers.	✓	—
origin	text	Origin of the Passive DNS response. This field is represented as a Uniform Resource Identifier (URI)	✓	—
raw_rdata	text	Resource records of the queried resource, in hexadecimal. All rdata entries at once.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
rdata	text	Resource records of the queried resource. Note that this field is added for each rdata entry in the rrset.	—	—
rrname	text	Resource Record name of the queried resource.	—	—
rrtype	text	Resource Record type as seen by the passive DNS. ['A', 'AAAA', 'CNAME', 'PTR', 'SOA', 'TXT', 'DNAME', 'NS', 'SRV', 'RP', 'NAPTR', 'HINFO', 'A6']	✓	—
sensor_id	text	Sensor information where the record was seen	✓	—
text	text	Description of the passive DNS record.	✓	—
time_first	datetime	First time that the unique tuple (rrname, rrtype, rdata) has been seen by the passive DNS	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
time_first_ms	datetime	Same meaning as the field 'time_first', with the only difference, that the resolution is in milliseconds since 1st of January 1970 (UTC)	✓	—
time_last	datetime	Last time that the unique tuple (rrname, rrtype, rdata) record has been seen by the passive DNS	✓	—
time_last_ms	datetime	Same meaning as the field 'time_last', with the only difference, that the resolution is in milliseconds since 1st of January 1970 (UTC)	✓	—
zone_time_first	datetime	First time that the unique tuple (rrname, rrtype, rdata) record has been seen via master file import	✓	—
zone_time_last	datetime	Last time that the unique tuple (rrname, rrtype, rdata) record has been seen via master file import.	✓	—

passive-dns-dnsdbflex

DNSDBFLEX object. This object is used at farsight security. Roughly based on Passive DNS records as expressed in [draft-dulaunoy-dnsop-passive-dns-cof-07](https://tools.ietf.org/id/draft-dulaunoy-dnsop-passive-dns-cof-07.html). See <https://tools.ietf.org/id/draft-dulaunoy-dnsop-passive-dns-cof-07.html>.



passive-dns-dnsdbflex is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
rrname	text	Resource Record name of the queried resource.	—	—
rrtype	text	Resource Record type as seen by the passive DNS. ['A', 'AAAA', 'CNAME', 'PTR', 'SOA', 'TXT', 'DNAME', 'NS', 'SRV', 'RP', 'NAPTR', 'HINFO', 'A6']	✓	—

passive-ssh

Passive-ssh object as described on [passive-ssh services from circl.lu](#) - <https://github.com/D4-project/passive-ssh>.



passive-ssh is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
banner	text	SSH banner	—	✓
base64	text	Base64 representation of the ssh-key	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
fingerprint	ssh-fingerprint	Fingerprint of the SSH key	✓	✓
first_seen	datetime	First time that the passive-ssh object has been seen by the passive SSH	✓	—
hassh	hassh-md5	Hassh fingerprint	—	—
host	ip-dst	IP Address of the host(s) that exposed this SSH key	—	✓
last_seen	datetime	Last time that the passive-ssh object has been seen by the passive SSH	✓	—
port	port	Port of the connection	—	—

paste

Paste or similar post from a website allowing to share privately or publicly posts.



paste is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
first-seen	datetime	When the paste has been accessible or seen for the first time.	✓	—
last-seen	datetime	When the paste has been accessible or seen for the last time.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Link to the original source of the source or post (when used legitimately for OSINT source or alike).	—	—
origin	text	Original source of the paste or post. ['pastebin.com', 'pastebin.com_pro' , 'pastebin.fr', 'pastie.org', 'slexy.org', 'gist.github.com', 'codepad.org', 'safebin.net', 'hastebin.com', 'ghostbin.com', 'paste.ee', '0bin.net']	✓	—
paste	text	Raw text of the paste or post	—	—
paste-file	attachment	Content of the paste in file	—	—
title	text	Title of the paste or post.	—	—
url	url	Link to the original source of the paste or post (when used maliciously).	—	—
username	text	User who posted the post.	—	—

pcap-metadata

Network packet capture metadata.



pcap-metadata is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
capture-interface	text	Interface name where the packet capture was running.	✓	—
capture-length	text	Capture length set on the captured interface.	✓	—
first-packet-seen	datetime	When the first packet has been seen.	✓	—
last-packet-seen	datetime	When the last packet has been seen.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
protocol	text	Capture protocol (linktype name). ['PER_PACKET', 'UNKNOWN', 'ETHERNET', 'TOKEN_RING', 'SLIP', 'PPP', 'FDDI', 'FDDI_BITSWAPPE D', 'RAW_IP', 'ARCNET', 'ARCNET_LINUX', 'ATM RFC1483', 'LINUX_ATM_CLIP ', 'LAPB', 'ATM_PDUS', 'ATM_PDUS_UNTR UNCATED', 'NULL', 'ASCEND', 'ISDN', 'IP_OVER_FC', 'PPP_WITH_PHDR' , 'IEEE_802_11', 'IEEE_802_11_PRIS M', 'IEEE_802_11_WIT H_RADIO', 'IEEE_802_11_RAD IOTAP', 'IEEE_802_11_AV S', 'SLL', 'FRELAY', 'FRELAY_WITH_P HDR', 'CHDLC', 'CISCO_IOS', 'LOCALTALK', 'OLD_PFLOG', 'HHDLC', 'DOCSIS', 'COSINE', 'WFLEET_HDLC', 'SDLC', 'TZSP', 'ENC', 'PFLOG', 'CHDLC_WITH_PH DR', 'BLUETOOTH_H4', 'MTP2', 'MTP3', 'IRDA', 'USER0', 'USER1', 'USER2', 'USER3', 'USER4', 'USER5', 'USER6',	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
text	text	A description of the packet capture.	✓	—

pe

Object describing a Portable Executable.

'USER13',
 'USER14',
 'USER15',
 'SYMANTEC',
 'APPLE_IP_OVER_I
 EEE1394',
 'BACNET_MS_TP',
 'NETTL_RAW_ICM'



pe is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

p'

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
authentihash	authentihash	Authenticode executable signature hash (sha256)	—	—
company-name	text	CompanyName in the resources	✓	—
compilation-timestamp	datetime	Compilation timestamp defined in the PE header	—	—
entrypoint-address	text	Address of the entry point	✓	—
entrypoint-section-at-position	text	Name of the section and position of the section in the PE	✓	—
file-description	text	FileDescription in the resources	✓	—
file-version	text	FileVersion in the resources	✓	—

'JUNIPER_VP',
 'USB_FREEBSD',
 'IEEE802_16_MAC_CPS',
 'NETTL_RAW_TEL'

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
impfuzzy	impfuzzy	Fuzzy Hash (ssdeep) calculated from the import table	—	—
imphash	imphash	Hash (md5) calculated from the import table	—	—
internal-filename	filename	InternalFilename in the resources	✓	—
lang-id	text	Lang ID in the resources	✓	—
legal-copyright	text	LegalCopyright in the resources	✓	—
number-sections	counter	Number of sections	✓	—
original-filename	filename	OriginalFilename in the resources	✓	—
pehash	pehash	Hash of the structural information about a sample. See https://www.usenix.org/legacy/event/leet09/tech/full_papers/wicherski/wicherski_html/	—	—
product-name	text	ProductName in the resources	✓	—
product-version	text	ProductVersion in the resources	✓	—
richpe	md5	RichPE metadata hash	—	✓

'PPP_EETHER',
 'NFC_LLCP',
 'NFLOG', 'V5_EF',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
text	text	Free text value to attach to the PE	✓	—
type	text	Type of PE ['exe', 'dll', 'driver', 'unknown']	✓	—

pe-section

Object describing a section of a Portable Executable.

'JUNIPER_SVCS',
 'USBPCAP',
 'RTAC_SERIAL',
 'BLUETOOTH_LE_

'WIRESHARK_UPP'



pe-section is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

'STANAG_5066_D'

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
characteristic	text	Characteristic of the section ['read', 'write', 'executable']	—	—
entropy	float	Entropy of the whole section	✓	—
md5	md5	[Insecure] MD5 hash (128 bits)	—	—
name	text	Name of the section ['.rsrc', '.reloc', '.rdata', '.data', '.text']	✓	—
offset	hex	Section's offset	✓	—
sha1	sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
sha224	sha224	Secure Hash Algorithm 2 (224 bits)	—	—

'NORDIC_BLE',

'NETMON_NET_N'

'EVEVENT',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sha256	sha256	Secure Hash Algorithm 2 (256 bits)	—	—
sha384	sha384	Secure Hash Algorithm 2 (384 bits)	—	—
sha512	sha512	Secure Hash Algorithm 2 (512 bits)	—	—
sha512/224	sha512/224	Secure Hash Algorithm 2 (224 bits)	—	—
sha512/256	sha512/256	Secure Hash Algorithm 2 (256 bits)	—	—
size-in-bytes	size-in-bytes	Size of the section, in bytes	✓	—
ssdeep	ssdeep	Fuzzy hash using context triggered piecewise hashes (CTPH)	—	—
text	text	Free text value to attach to the section	✓	—
virtual_address	hex	Section's virtual address	✓	—
virtual_size	size-in-bytes	Section's virtual size	✓	—

person

An object which describes a person or an identity.



person is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Postal address of the person.	—	✓
alias	text	Alias name or known as.	—	✓
birth-certificate-number	text	Birth Certificate Number	—	—
date-of-birth	date-of-birth	Date of birth of a natural person (in YYYY-MM-DD format).	—	—
dni	text	Spanish National ID	—	✓
e-mail	email-src	Email address of the person.	—	✓
fax-number	phone-number	Fax number of the person.	—	✓
first-name	first-name	First name of a natural person.	✓	—
full-name	full-name	Full name of a natural person usually composed of first-name, middle-name and last-name.	—	—
function	text	Function of the natural person such as analyst, cyber operator, lawyer.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
gender	gender	The gender of a natural person. ['Male', 'Female', 'Other', 'Prefer not to say', 'Unknown']	✓	—
handle	text	Handle used by the user in application.	—	✓
identity-card-number	identity-card-number	The identity card number of a natural person.	—	—
instant-messaging-used	text	The IM application used by this person. ['WhatsApp', 'Google Hangouts', 'Facebook Messenger', 'Telegram', 'Signal', 'WeChat', 'BlackBerry Messenger', 'TeamSpeak', 'TorChat', 'Tox', 'RetroShare', 'Slack', 'Wire', 'Threema', 'Discord', 'Mumble', 'Jabber', 'Twitter']	✓	✓
last-name	last-name	Last name of a natural person.	—	—
middle-name	middle-name	Middle name of a natural person.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
mothers-name	text	Mother name, father, second name or other names following country's regulation.	—	—
nationality	nationality	The nationality of a natural person.	✓	✓
nic-hdl	text	NIC Handle (Network Information Centre handle) of the person.	—	✓
nie	text	Foreign National ID (Spain)	—	✓
nif	text	Tax ID Number (Spain)	—	✓
occupation	text	Work or occupation of the person or identity.	✓	—
ofac-identification-number	text	ofac-identification Number	—	—
passport-country	passport-country	The country in which the passport was issued.	✓	—
passport-expiration	passport-expiration	The expiration date of a passport.	✓	—
passport-number	passport-number	The passport number of a natural person.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
phone-number	phone-number	Phone number of the person.	—	✓
place-of-birth	place-of-birth	Place of birth of a natural person.	✓	—
portrait	attachment	Portrait of the person.	—	✓
redress-number	redress-number	The Redress Control Number is the record identifier for people who apply for redress through the DHS Travel Redress Inquiry Program (DHS TRIP). DHS TRIP is for travelers who have been repeatedly identified for additional screening and who want to file an inquiry to have erroneous information corrected in DHS systems.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
role	text	The role of a person. ['Suspect', 'Victim', 'Defendant', 'Accused', 'Culprit', 'Accomplice', 'Witness', 'Target', 'Source', 'Originator', 'Informant', 'Emitter']	✓	✓
social-security-number	text	Social security number.	—	—
text	text	A description of the person or identity.	✓	—
title	text	Title of the natural person such as Dr. or equivalent.	✓	—

personification

An object which describes a person or an identity.



personification is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
age-range	float	Age range that the person appears to be	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
beard	text	Description of the characteristics of someones beard. ['Beardless', 'Stubble Short', 'Stubble Medium', 'Stubble Long', 'Full Beard', 'French Fork', 'Ducktail', 'Goatee', 'Imperial', 'Van Dyke', 'Anchor', 'Balbo', 'Mutton Chops', 'Verdi', 'Garibaldi', 'Dutch', 'Winter Beard', 'Mustache', 'Unknown']	-	✓
birthmark	text	Position(s) of birthmarks. ['Head', 'Arms', 'Back', 'Torso', 'Legs', 'Foot', 'Backside', 'Unknown']	-	✓
body-type	text	Body type of a person. ['Slim', 'Tone', 'Muscular', 'Stocky', 'Large', 'Unknown']	✓	-
color-of-eyes	text	Description of a person's colour of eyes. ['Amber', 'Blue', 'Brown', 'Gray', 'Green', 'Hazel', 'Red', 'Unknown']	-	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hair-characteristics	text	Description of the characteristics of someones hairs. ['Straight', 'Wavy', 'Curly', 'Coily', 'Unknown']	-	✓
hair-color	text	Description of a person's colour of hair. ['Black', 'Brown', 'Auburn', 'Red', 'Blond', 'Gray', 'White', 'Blue', 'Pink', 'Green', 'Violet', 'Unknown']	-	✓
haircut	text	Description of the characteristics of someones hairs. ['Crew Cut', 'Shaved', 'Bald', 'Long', 'Spiky', 'Dreadlocks', 'Cornrow', 'Bob', 'Layered', 'Flat-top', 'Chignon', 'Bun', 'French Twist', 'Medium', 'Braid', 'Pigtails', 'Ponytail', 'Unknown']	-	✓
height	float	Height of a person in cm.	-	✓
other-facial-features	text	Description of other facial features such as nose, cheeks, lips etc...	-	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
portrait	attachment	Portrait of the person.	—	✓
shape-of-eyes	text	Description of a person's eye shape. ['Monolids', 'Hooded', 'Upturned', 'Downturned', 'Round', 'Almond', 'Unknown']	—	✓
shoe-size	float	Shoe size of a person. ['US', 'UK', 'EU', 'Asia', 'CM', 'Inches']	—	✓
skin-characteristics	text	Traits or features of a person's skin ['Normal', 'Irritated', 'Dry', 'Oily', 'Scaly', 'Red spots', 'Skin moles']	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
skin-complexion	text	Skin tone and complexion of a person. Type I: Extremely fair skin, always burns, never tans. Type II: Fair skin, always burns, sometimes tans. Dry: Medium skin, sometimes burns, always tans. Type IV: Olive skin, rarely burns, always tans. Type V: Moderately pigmented brown skin, never burns, always tans. Type VI: Markedly pigmented black skin, never burns, always tans. ['Type I', 'Type II', 'Type III', 'Type IV', 'Type V', 'Type VI', 'Unknown']	-	✓
weight	float	Weight of a person in Kg.	-	✓

pgp-meta

Metadata extracted from a PGP keyblock, message or signature.



pgp-meta is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
key-id	text	Key ID in hexadecimal	-	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
user-id-email	text	User ID packet, email address of the key holder (UTF-8 text)	—	✓
user-id-name	text	User ID packet, name of the key holder	—	✓

phishing

Phishing template to describe a phishing website and its analysis.



phishing is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hostname	hostname	host of the phishing website	—	✓
internal-reference	text	Internal reference such as ticket ID	—	—
online	text	If the phishing is online and operational, by default is yes ['Yes', 'No']	✓	—
phishtank-detail-url	link	Phishtank detail URL to the reported phishing	—	—
phishtank-id	text	Phishtank ID of the reported phishing	—	—
screenshot	attachment	Screenshot of phishing site	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
submission-time	datetime	When the phishing was submitted and/or reported	—	—
takedown-request	datetime	When the phishing was requested to be taken down	✓	—
takedown-request-to	text	Destination email address for take-down request	✓	✓
takedown-time	datetime	When the phishing was taken down	✓	—
target	text	Targeted organisation by the phishing	—	✓
url	url	Original URL of the phishing website	—	—
url-redirect	url	Redirect URL of the phishing website	—	✓
verification-time	datetime	When the phishing was verified	✓	—
verified	text	The phishing has been verified by the team handling the phishing ['No', 'Yes']	✓	—

phishing-kit

Object to describe a phishing-kit.



phishing-kit is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date-found	datetime	Date when the phishing kit was found	✓	✓
email-type	text	Type of the Email	✓	—
internal-reference	text	Internal reference such as ticket ID	—	—
kit-mailer	text	Mailer Kit Used	✓	✓
kit-name	text	Name of the Phishing Kit	—	—
kit-url	url	URL of Phishing Kit	—	—
online	text	If the phishing kit is online and operational, by default is yes ['Yes', 'No']	✓	—
phishing-domain	url	Domain used for Phishing	—	✓
reference-link	link	Link where the Phishing Kit was observed	—	✓
target	text	What was targeted using this phishing kit	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
threat-actor	text	Identified threat actor	—	✓
threat-actor-email	email-src	Email of the Threat Actor	—	✓

phone

A phone or mobile phone object which describe a phone.



phone is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
brand	text	Brand of the phone.	✓	—
first-seen	datetime	When the phone has been accessible or seen for the first time.	✓	—
gummei	text	Globally Unique MME Identifier (GUMMEI) is composed from MCC, MNC and MME Identifier (MMEI).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
guti	text	Globally Unique Temporary UE Identity (GUTI) is a temporary identification to not reveal the phone (user equipment in 3GPP jargon) composed of GUMMEI and the M-TMSI.	—	—
imei	text	International Mobile Equipment Identity (IMEI) is a number, usually unique, to identify 3GPP and iDEN mobile phones, as well as some satellite phones.	—	—
imsi	text	A usually unique International Mobile Subscriber Identity (IMSI) is allocated to each mobile subscriber in the GSM/UMTS/EPS system. IMSI can also refer to International Mobile Station Identity in the ITU nomenclature.	—	—
last-seen	datetime	When the phone has been accessible or seen for the last time.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
model	text	Model of the phone.	✓	—
msisdn	text	MSISDN (pronounced as /'em es ai es di en/ or misden) is a number uniquely identifying a subscription in a GSM or a UMTS mobile network. Simply put, it is the mapping of the telephone number to the SIM card in a mobile/cellular phone. This abbreviation has a several interpretations, the most common one being Mobile Station International Subscriber Directory Number.	—	—
serial-number	text	Serial Number.	—	—
text	text	A description of the phone.	✓	—
tmsi	text	Temporary Mobile Subscriber Identities (TMSI) to visiting mobile subscribers can be allocated.	—	—

postal-address

A postal address.



postal-address is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
apartment	text	Apartment / suite number	✓	—
city	text	City or town name	✓	—
country	text	Country	✓	—
description	text	Description of the address	✓	—
number	text	House number	✓	—
postal-code	text	ZIP / postal code	✓	—
province	text	Province	✓	—
state	text	State	✓	—
street	text	Street name	—	—

probabilistic-data-structure

Probabilistic data structure object describe a space-efficient data structure such as Bloom filter or similar structure.



probabilistic-data-structure is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Source of the probabilistic data structure.	✓	—
probability	float	The false positive rate of the probabilistic data structure. ['0.1', '0.01', '0.001', '0.0001']	✓	—
total-bits	counter	The number of bits used by this probabilistic data structure.	✓	—
total-capacity	counter	The total capacity of the total set represented in this probabilistic data structure.	✓	—
type	text	Type of the probabilistic data structure. ['Bloom filter', 'Ribbon filter', 'Cuckoo filter', 'Quotient filter', 'Xor filter', 'Taffy filter', 'HyperLogLog filter', 'Count-min sketch filter']	✓	—
updatable	boolean	Is the probabilistic data structure updatable? ['False', 'True']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
used-capacity	counter	The used capacity (and cardinality) of the set represented in this probabilistic data structure.	✓	—
vendor-implementation-ref	link	Details about the implementation of the probabilistic data structure.	✓	—

process

Object describing a system process.



process is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
args	text	Arguments of the process	✓	—
child-pid	text	Process ID of the child(ren) process	✓	✓
command-line	text	Command line of the process	—	—
creation-time	datetime	Local date/time at which the process was created	✓	—
current-directory	text	Current working directory of the process	✓	—
fake-process-name	boolean	Is the process spawned under a false name. ['1', '0']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
guid	text	The globally unique identifier assigned by the vendor product	—	—
hidden	boolean	Specifies whether the process is hidden ['True', 'False']	✓	—
image	filename	Path of process image	—	—
integrity-level	text	Integrity level of the process ['system', 'high', 'medium', 'low', 'untrusted']	✓	—
name	text	Name of the process	—	—
parent-command-line	text	Command line of the parent process	—	—
parent-guid	text	The globally unique identifier of the parent process assigned by the vendor product	—	—
parent-image	filename	Path of parent process image	—	—
parent-pid	text	Process ID of the parent process	✓	—
parent-process-name	text	Process name of the parent	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
parent-process-path	text	Parent process path of the parent	—	—
pgid	text	Identifier of the group of processes the process belongs to	✓	—
pid	text	Process ID of the process	✓	—
port	port	Port(s) owned by the process	✓	✓
process-state	process-state	State of process. ['D', 'R', 'S', 'T', 't', 'W', 'X', 'Z', '<', 'N', 'L', 's', 'I', '+']	✓	—
start-time	datetime	Local date/time at which the process was started	✓	—
user-creator	text	User who created the process	✓	—
user-process	text	User who is running the process at the time of the analysis	✓	—

publication

An object to describe a book, journal, or academic publication.



publication is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
DOI	text	DOI System is used to identify digital resources.	—	✓
ISBN	text	International Standard Book Number.	—	✓
academic-institution	text	Academic institution associated with the publisher or authors.	—	✓
archive	link	Archive of the original document (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The publication file or screen capture.	—	✓
author	text	Author of the publication.	—	✓
content	text	Content of the publication.	—	—
contributor	text	Contributors include editors, compilers, and translators.	—	✓
description	text	A description of the publication.	✓	—
edition	text	Edition of the publication.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
embedded-link	url	Link contained in the publication (possibly malicious).	—	✓
embedded-safe-link	link	Link contained in the publication (assumed safe).	—	✓
link	link	Original link to the publication (supposed harmless).	—	✓
publisher	text	Publisher of the document.	—	—
series	text	Series of the publication.	✓	—
title	text	Content of the publication.	—	—
url	url	Original link to the publication (possibly malicious).	—	✓
volume	text	Volume of the publication.	✓	—
website	link	Website of the publisher.	✓	—
year	text	Year of publication.	✓	—

python-etvx-event-log

Event log object template to share information of the activities conducted on a system..



python-etvx-event-log is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Computer	text	Computer name on which the event occurred	✓	—
Correlation-ID	text	Unique activity identity which relates the event to a process.	—	—
Event-data	text	Event data description.	✓	—
Keywords	text	Tags used for the event for the purpose of filtering or searching. ['Network', 'Security', 'Resource not found', 'other']	—	—
Operational-code	text	The opcode (numeric value or name) associated with the activity carried out by the event.	✓	—
Processor-ID	text	ID of the processor that processed the event.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Relative-Correlation-ID	text	Related activity ID which identity similar activities which occurred as a part of the event.	✓	—
Session-ID	text	Terminal server session ID.	✓	—
Thread-ID	text	Thread id that generated the event.	✓	—
User	text	Name or the User ID the event is associated with.	✓	—
comment	text	Additional comments.	✓	—
event-channel	text	Channel through which the event occurred ['Application', 'System', 'Security', 'Setup', 'other']	✓	—
event-date-time	datetime	Date and time when the event was logged.	✓	—
event-id	text	A unique number which identifies the event.	✓	—
event-type	text	Event-type assigned to the event ['Admin', 'Operational', 'Audit', 'Analytic', 'Debug', 'other']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
kernel-time	datetime	Execution time of the kernel mode instruction.	✓	—
level	text	Determines the event severity. ['Information', 'Warning', 'Error', 'Critical', 'Success Audit', 'Failure Audit']	—	—
log	text	Log file where the event was recorded.	✓	—
name	text	Name of the event.	✓	—
source	text	The source of the event log - application/software that logged the event.	—	—
task-category	text	Activity by the event publisher	✓	—
user-time	datetime	Date and time when the user instruction was executed.	✓	—

r2graphity

Indicators extracted from files using radare2 and graphml.



r2graphity is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
callback-average	counter	Average size of a callback	✓	—
callback-largest	counter	Largest callback	✓	—
callbacks	counter	Amount of callbacks (functions started as thread)	✓	—
create-thread	counter	Amount of calls to CreateThread	✓	—
dangling-strings	counter	Amount of dangling strings (string with a code cross reference, that is not within a function. Radare2 failed to detect that function.)	✓	—
get-proc-address	counter	Amount of calls to GetProcAddress	✓	—
gml	attachment	Graph export in G>raph Modelling Language format	✓	—
local-references	counter	Amount of API calls inside a code section	✓	—
memory-allocations	counter	Amount of memory allocations	✓	—
miss-api	counter	Amount of API call reference that does not resolve to a function offset	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
not-referenced-strings	counter	Amount of not referenced strings	✓	—
r2-commit-version	text	Radare2 commit ID used to generate this object	✓	—
ratio-api	float	Ratio: amount of API calls per kilobyte of code section	✓	—
ratio-functions	float	Ratio: amount of functions per kilobyte of code section	✓	—
ratio-string	float	Ratio: amount of referenced strings per kilobyte of code section	✓	—
referenced-strings	counter	Amount of referenced strings	✓	—
refsglobalvar	counter	Amount of API calls outside of code section (glob var, dynamic API)	✓	—
shortest-path-to-create-thread	counter	Shortest path to the first time the binary calls CreateThread	✓	—
text	text	Description of the r2graphity object	✓	—
total-api	counter	Total amount of API calls	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
total-functions	counter	Total amount of functions in the file.	✓	—
unknown-references	counter	Amount of API calls not ending in a function (Radare2 bug, probalby)	✓	—

ransom-negotiation

An object to describe ransom negotiations, as seen in ransomware incidents.



ransom-negotiation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Remarks	text	Remarks	✓	—
annual_revenue_EUR	float	Annual revenue of the targeted organisation in EUR	✓	—
currency	text	The currency of the initial demand. Often USD or BTC.	✓	—
data_leaked	boolean	Was data leaked in this incident? ['True', 'False']	✓	—
data_stolen	boolean	Was data exfiltrated in this incident? ['True', 'False']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
discount	float	Discount after negotiations	✓	—
email_address	text	Contact address, if any	—	—
final_ransom	float	Final ransom amount after negotiations, in the currency as displayed in field 'currency'	✓	—
initial_ransom	float	Initial ransom demand in the currency as displayed in field 'currency'	✓	—
negotiations_screenshot	attachment	Screenshot of the negotiations	✓	—
negotiations_transcript	text	Transcript of the negotiations	✓	—
pay_for_deletion	boolean	Does the target need/want to pay for data deletion ['True', 'False']	✓	—
pay_for_encryptor	boolean	Does the target need/want to pay for the decryptor ['True', 'False']	✓	—
percentage_of_revenue	float	Percentage of the annual revenue that the ransom demand amounts to	✓	—
time	datetime	Date and time of transaction	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url_leaksite	url	URL of the leaksite	—	—
value_EUR	float	Value in EUR of the final ransom amount, with conversion rate as of date/time displayed in field 'time'	✓	—
wallet-address	btc	A cryptocoins wallet address	—	—

reddit-account

Reddit account.



reddit-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
account-avatar	attachment	A screen capture or exported account avatar.	—	✓
account-avatar-url	url	A user profile picture or avatar.	—	✓
account-id	text	Account id.	—	—
account-name	text	Account name (do not include u/).	—	—
archive	link	Archive of the account (Internet Archive, Archive.is, etc).	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	A screen capture or exported list of contacts etc.	—	✓
description	text	A description of the user.	✓	—
link	link	Original link to the account page (supposed harmless).	—	—
moderator-of	text	Subreddits of which this account is a moderator (exclude the r/).	—	✓
trophies	text	Trophies listed in the account Trophy Case.	—	✓
url	url	Original URL location of the page (potentially malicious).	—	—

reddit-comment

A Reddit post comment.



reddit-comment is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original comment (Internet Archive, Archive.is, etc).	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
attachment	attachment	A screen capture or exported file from the comment.	—	✓
author	text	The user account that created the post (do not include u/).	—	—
body	text	The raw text of the comment.	—	—
description	text	A description of the comment.	✓	—
embedded-link	url	Link embedded in the subreddit description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the subreddit description (supposed safe).	—	✓
hashtag	text	Hashtag used to identify or promote the comment.	—	✓
link	link	Original link to the comment (supposed harmless).	—	—
subreddit-name	text	The name of the subreddit where it was posted (exclude the r/).	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	Original URL location of the comment (potentially malicious).	—	—
username-quoted	text	Username who are quoted in the comment (do not include u/).	—	✓

reddit-post

A Reddit post.



reddit-post is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original Reddit post (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported file from the Reddit post.	—	✓
author	text	The user account that created the post (do not include u/).	—	—
description	text	A description of the post.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
edited	text	Has the post been edited? ['True', 'False']	✓	—
embedded-link	url	Link embedded in the subreddit description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the subreddit description (supposed safe).	—	✓
hashtag	text	Hashtag used to identify or promote the Reddit post.	—	✓
link	link	Original link to the Reddit post (supposed harmless).	—	—
post-content	text	The raw text of the Reddit post.	—	—
post-title	text	The title of the Reddit post.	—	—
subreddit-name	text	The name of the subreddit where it was posted (exclude the r/).	—	✓
thumbnail	attachment	Screen capture or exported post thumbnail.	—	—
thumbnail-url	url	Link to post thumbnail.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
url	url	Original URL location of the Reddit post (potentially malicious).	—	—
username-quoted	text	Username who are quoted in the Reddit post (do not include u/).	—	✓

reddit-subreddit

Public or private subreddit.



reddit-subreddit is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
active-user-count	text	Number of active accounts in the subreddit.	✓	—
archive	link	Archive of the original subreddit (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts, subreddit members, etc.	—	✓
banner-background-image	attachment	A screen capture or exported subreddit header.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
banner-background-url	url	A link to the subreddit header.	—	✓
creator	text	The user account that created the subreddit (do not include u/).	—	—
description	text	A description of the subreddit.	—	—
display-name	text	The name of the subreddit (exclude the r/).	—	—
embedded-link	url	Link embedded in the subreddit description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the subreddit description (supposed safe).	—	✓
hashtag	text	Hashtag used to identify or promote the subreddit.	—	✓
header-title	text	A title of the subreddit.	—	✓
icon-img	attachment	A screen capture or exported subreddit community icon.	—	✓
icon-img-url	url	A link to the subreddit community icon.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link to the subreddit (supposed harmless).	—	—
moderator	text	A user account who is a moderator of the subreddit (do not include u/).	—	✓
privacy	text	Subreddit privacy. ['Public', 'Private']	—	—
rules	text	Raw text of the rules of the subreddit.	—	✓
submit-text	text	The submission form raw text when posting to the subreddit.	—	—
subreddit-alias	text	Aliases or previous names of subreddit.	—	✓
subreddit-type	text	Subreddit type, e.g. general, buy and sell etc.	✓	✓
url	url	Original URL location of the subreddit (potentially malicious).	—	—

regexp

An object describing a regular expression (regex or regexp). The object can be linked via a relationship to other attributes or objects to describe how it can be represented as a regular expression.



regexp is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	A description of the regular expression.	—	—
regexp	text	regexp	—	—
regexp-type	text	Type of the regular expression syntax. ['PCRE', 'PCRE2', 'POSIX BRE', 'POSIX ERE', 'FCRE (Farsight Compatible Regular Expressions)']	✓	—
type	text	Specify which type corresponds to this regex. ['hostname', 'domain', 'email-src', 'email-dst', 'email-subject', 'url', 'user-agent', 'regkey', 'cookie', 'uri', 'filename', 'windows-service-name', 'windows-scheduled-task']	✓	—

registry-key

Registry key object describing a Windows registry key with value and last-modified timestamp.



registry-key is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
data	text	Data stored in the registry key	—	—
data-type	text	Registry value type ['REG_NONE', 'REG_SZ', 'REG_EXPAND_SZ', 'REG_BINARY', 'REG_DWORD', 'REG_DWORD_LITTLE_ENDIAN', 'REG_DWORD_BIG_ENDIAN', 'REG_LINK', 'REG_MULTI_SZ', 'REG_RESOURCE_LIST', 'REG_FULL_RESOURCE_DESCRIPTOR', 'REG_RESOURCE_REQUIREMENTS_LIST', 'REG_QWORD', 'REG_QWORD_LITTLE_ENDIAN']	✓	—
hive	text	Hive used to store the registry key (file on disk)	✓	—
key	regkey	Full key path	—	—
last-modified	datetime	Last time the registry key has been modified	—	—
name	text	Name of the registry key	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
root-keys	text	Root key of the Windows registry (extracted from the key) ['HKCC', 'HKCR', 'HKCU', 'HKDD', 'HKEY_CLASSES_ROOT', 'HKEY_CURRENT_CONFIG', 'HKEY_CURRENT_USER', 'HKEY_DYN_DATA ', 'HKEY_LOCAL_MACHINE', 'HKEY_PERFORMANCE_DATA', 'HKEY_USERS', 'HKLM', 'HKPD', 'HKU']	✓	—

regripper-NTUser

Regripper Object template designed to present user specific configuration details extracted from the NTUSER.dat hive.



regripper-NTUser is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
applications-installed	text	List of applications installed.	—	✓
applications-run	text	List of applications set to run on the system.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comments	text	Additional information related to the user profile	✓	—
external-devices	text	List of external devices connected to the system by the user.	—	✓
key	text	Registry key where the information is retrieved from.	—	—
key-last-write-time	datetime	Date and time when the key was last updated.	✓	—
logon-user-name	text	Name assigned to the user profile.	—	—
mount-points	text	Details of the mount points created on the system.	✓	✓
network-connected-to	text	List of networks the user connected the system to.	—	✓
nukeOnDelete	boolean	Determines if the Recycle bin option has been disabled. ['True', 'False']	✓	—
recent-files-accessed	text	List of recent files accessed by the user.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
recent-folders-accessed	text	List of recent folders accessed by the user.	—	✓
typed-urls	text	Urls typed by the user in internet explorer	—	✓
user-init	text	Applications or processes set to run when the user logs onto the windows system.	—	✓

regripper-sam-hive-single-user

Regripper Object template designed to present user profile details extracted from the SAM hive.



regripper-sam-hive-single-user is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comments	text	Full name assigned to the user profile.	✓	—
full-user-name	text	Full name assigned to the user profile.	—	—
key	text	Registry key where the information is retrieved from.	—	—
key-last-write-time	datetime	Date and time when the key was last updated.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
last-login-time	datetime	Date and time when the user last logged onto the system.	✓	—
login-count	counter	Number of times the user logged-in onto the system.	✓	—
pwd-fail-date	datetime	Date and time when a password last failed for this user profile.	✓	—
pwd-reset-time	datetime	Date and time when the password was last reset.	✓	—
user-name	text	User name assigned to the user profile.	—	—

regripper-sam-hive-user-group

Regripper Object template designed to present group profile details extracted from the SAM hive.



regripper-sam-hive-user-group is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
full-name	text	Full name assigned to the profile.	—	—
group-comment	text	Any group comment added.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
group-name	text	Name assigned to the profile.	—	—
group-users	text	Users belonging to the group	—	✓
key	text	Registry key where the information is retrieved from.	—	—
key-last-write-time	datetime	Date and time when the key was last updated.	✓	—
last-write-date-time	datetime	Date and time when the group key was updated.	✓	—

regripper-software-hive-BHO

Regripper Object template designed to gather information of the browser helper objects installed on the system.



regripper-software-hive-BHO is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
BHO-key-last-write-time	datetime	Date and time when the BHO key was last updated.	✓	—
BHO-name	text	Name of the browser helper object.	—	—
class	text	Class to which the BHO belongs to.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comments	text	Additional comments.	✓	—
key	text	Software hive key where the information is retrieved from.	—	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
module	text	DLL module the BHO belongs to.	✓	—
references	link	References to the BHO.	—	✓

regripper-software-hive-appInit-DLLS

Regripper Object template designed to gather information of the DLL files installed on the system.



regripper-software-hive-appInit-DLLS is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
DLL-last-write-time	datetime	Date and time when the DLL file was last updated.	✓	—
DLL-name	text	Name of the DLL file.	—	—
DLL-path	text	Path where the DLL file is stored.	—	—
comments	text	Additional comments.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
key	text	Software hive key where the information is retrieved from.	—	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
references	link	References to the DLL file.	—	✓

regripper-software-hive-application-paths

Regripper Object template designed to gather information of the application paths.



regripper-software-hive-application-paths is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comments	text	Additional comments.	✓	—
executable-file-name	text	Name of the executable file.	—	✓
key	text	Software hive key where the information is retrieved from.	—	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
path	text	Path of the executable file.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
references	link	References to the application installed.	—	✓

regripper-software-hive-applications-installed

Regripper Object template designed to gather information of the applications installed on the system.



regripper-software-hive-applications-installed is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
app-last-write-time	datetime	Date and time when the application key was last updated.	✓	—
app-name	text	Name of the application.	—	—
comments	text	Additional comments.	✓	—
key	text	Software hive key where the information is retrieved from.	—	—
key-path	text	Path of the key.	—	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
references	link	References to the application installed.	—	✓
version	text	Version of the application.	—	—

regripper-software-hive-command-shell

Regripper Object template designed to gather information of the shell commands executed on the system.



regripper-software-hive-command-shell is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
command	text	Command executed.	—	—
comments	text	Additional comments.	✓	—
key	text	Software hive key where the information is retrieved from.	—	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
shell	text	Type of shell used to execute the command. ['exe', 'cmd', 'bat', 'hta', 'pif', 'Other']	✓	—
shell-path	text	Path of the shell.	—	—

regripper-software-hive-software-run

Regripper Object template designed to gather information of the applications set to run on the system.



regripper-software-hive-software-run is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
application-name	text	Name of the application run.	—	✓
application-path	text	Path where the application is installed.	—	✓
comments	text	Additional comments.	✓	—
key	text	Software hive key where the information is retrieved from. ['Run', 'RunOnce', 'Runservices', 'Terminal', 'Other']	✓	—
key-path	text	Path of the key.	✓	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
references	link	References to the applications.	—	✓

regripper-software-hive-userprofile-winlogon

Regripper Object template designed to gather user profile information when the user logs onto the system, gathered from the software hive.



regripper-software-hive-userprofile-winlogon is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
AutoAdminLogon	boolean	Flag value to determine if autologon is enabled for a user without entering the password. ['True', 'False']	✓	—
AutoRestartShell	boolean	Value of the flag set to auto restart the shell if it crashes or shuts down automatically. ['True', 'False']	✓	—
CachedLogonCount	counter	Number of times the user has logged into the system.	✓	—
Comments	text	Additional comments.	✓	—
DefaultUserName	text	user-name of the default user.	✓	—
DisableCAD	boolean	Flag to determine if user login is enabled by pressing Ctrl+ALT+Delete. ['True', 'False']	✓	—
Legal-notice-caption	text	Message title set to display when the user logs-in.	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Legal-notice-text	text	Message set to display when the user logs-in.	✓	✓
PasswordExpiryWarning	counter	Number of times the password expiry warning appeared.	✓	—
PowerdownAfterShutdown	boolean	Flag value- if the system is set to power down after it is shutdown. ['True', 'False']	✓	—
PreCreateKnownFolders	text	create known folders key	✓	—
ReportBootOk	boolean	Flag to check if the reboot was successful. ['True', 'False']	✓	—
SID	text	Security identifier assigned to the user profile.	✓	—
Shell	text	Shell set to run when the user logs onto the system.	✓	✓
ShutdownFlags	counter	Number of times shutdown is initiated from a process when the user is logged-in.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ShutdownWithoutLogon	boolean	Value of the flag set to enable shutdown without requiring a user to login. ['True', 'False']	✓	—
UserInit	text	Applications and files set to run when the user logs onto the system (User logon activity).	—	✓
WinStationsDisabled	boolean	Flag value set to enable/disable logons to the system. ['True', 'False']	✓	—
user-profile-key-last-write-time	datetime	Date and time when the key was last updated.	✓	—
user-profile-key-path	text	key where the user-profile information is retrieved from.	✓	—
user-profile-last-write-time	datetime	Date and time when the user profile was last updated.	✓	—
user-profile-path	text	Path of the user profile on the system	✓	—
winlogon-key-last-write-time	datetime	Date and time when the winlogon key was last updated.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
winlogon-key-path	text	winlogon key referred in order to retrieve default user information	✓	—

regripper-software-hive-windows-general-info

Regripper Object template designed to gather general windows information extracted from the software-hive.



regripper-software-hive-windows-general-info is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
BuildGUID	text	Build ID.	—	—
BuildLab	text	Windows BuildLab string.	—	—
BuildLabEx	text	Windows BuildLabEx string.	—	—
CSDVersion	text	Version of the service pack installed.	—	—
CurrentBuild	text	Build number of the windows OS.	—	—
CurrentBuildType	text	Current build type of the OS.	—	—
CurrentVersion	text	Current version of windows	✓	—
EditionID	text	Windows edition.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
InstallDate	datetime	Date when windows was installed.	✓	—
InstallationType	text	Type of windows installation.	✓	—
PathName	text	Path to the root directory.	✓	—
ProductID	text	ID of the product version.	—	—
ProductName	text	Name of the windows version.	—	—
RegisteredOrganization	text	Name of the registered organization.	—	—
RegisteredOwner	text	Name of the registered owner.	—	—
SoftwareType	text	Software type of windows. ['System', 'Application', 'other']	✓	—
SystemRoot	text	Root directory.	✓	—
comment	comment	Additional comments.	✓	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
win-cv-path	text	key where the windows information is retrieved from	—	—

regripper-system-hive-firewall-configuration

Regripper Object template designed to present firewall configuration information extracted from the system-hive.



regripper-system-hive-firewall-configuration is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Additional comments.	✓	—
disable-notification	boolean	Boolean flag to determine if firewall notifications are enabled. ['True', 'False']	✓	—
enabled-firewall	boolean	Boolean flag to determine if the firewall is enabled. ['True', 'False']	✓	—
last-write-time	datetime	Date and time when the firewall profile policy was last updated.	✓	—
profile	text	Firewall Profile type ['Domain Profile', 'Standard Profile', 'Network Profile', 'Public Profile', 'Private Profile', 'other']	✓	—

regripper-system-hive-general-configuration

Regripper Object template designed to present general system properties extracted from the system-hive.



regripper-system-hive-general-configuration is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Additional comments.	✓	—
computer-name	text	name of the computer under analysis	—	—
fDenyTSConnections:	boolean	Specifies whether remote connections are enabled or disabled on the system. ['True', 'False']	✓	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
shutdown-time	datetime	Date and time when the system was shutdown.	✓	—
timezone-bias	text	Offset in minutes from UTC. Offset added to the local time to get a UTC value.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
timezone-daylight-bias	text	value in minutes to be added to the value of timezone-bias to generate the bias used during daylight time.	✓	—
timezone-daylight-date	datetime	Daylight date - daylight saving months	✓	—
timezone-daylight-name	text	Timezone name used during daylight saving months.	✓	—
timezone-last-write-time	datetime	Date and time when the timezone key was last updated.	✓	—
timezone-standard-bias	text	value in minutes to be added to the value of timezone-bias to generate the bias used during standard time.	✓	—
timezone-standard-date	datetime	Standard date - non daylight saving months	✓	—
timezone-standard-name	text	Timezone standard name used during non-daylight saving months.	✓	—

regripper-system-hive-network-information

Regripper object template designed to gather network information from the system-hive.



regripper-system-hive-network-information is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
DHCP-IP-address	ip-dst	DHCP service - IP address	—	—
DHCP-domain	text	Name of the DHCP domain service	—	—
DHCP-name-server	ip-dst	DHCP server - Name IP address.	—	—
DHCP-server	ip-dst	DHCP server - IP address.	—	—
DHCP-subnet-mask	ip-dst	DHCP subnet mask - IP address.	—	—
TCPIP-key	text	TCPIP key	—	—
TCPIP-key-last-write-time	datetime	Datetime when the key was last updated.	✓	—
additional-comments	text	Comments.	✓	—
interface-GUID	text	GUID value assigned to the interface.	✓	—
interface-IPcheckingEnabled	boolean		✓	—
interface-MediaSubType	text	—	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
interface-PnpInstanceID	text	Plug and Play instance ID assigned to the interface.	✓	—
interface-last-write-time	datetime	Last date and time when the interface key was updated.	✓	—
interface-name	text	Name of the interface.	—	—
network-key	text	Registry key assigned to the network	—	—
network-key-last-write-time	datetime	Date and time when the network key was last updated.	✓	—
network-key-path	text	Path of the key where the information is retrieved from.	✓	—

regripper-system-hive-services-drivers

Regripper Object template designed to gather information regarding the services/drivers from the system-hive.



regripper-system-hive-services-drivers is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Additional comments.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
display	text	Display name/information of the service or the driver.	—	—
group	text	Group to which the system/driver belong to. ['Base', 'Boot Bus Extender', 'Boot File System', 'Cryptography', 'Extended base', 'Event Log', 'Filter', 'FSFilter Bottom', 'FSFilter Infrastructure', 'File System', 'FSFilter Virtualization', 'Keyboard Port', 'Network', 'NDIS', 'Parallel arbitrator', 'Pointer Port', 'PnP Filter', 'ProfSvc_Group', 'PNP_TDI', 'SCSI Miniport', 'SCSI CDROM Class', 'System Bus Extender', 'Video Save', 'other']	✓	—
image-path	text	Path of the service/drive	—	—
last-write-time	datetime	Date and time when the key was last updated.	✓	—
name	text	name of the key	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
start	text	When the service/driver starts or executes. ['Boot start', 'System start', 'Auto start', 'Manual', 'Disabled']	✓	—
type	text	Service/driver type. ['Kernel driver', 'File system driver', 'Own process', 'Share process', 'Interactive', 'Other']	✓	—

report

Metadata used to generate an executive level report.



report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
case-number	text	Case number	—	—
link	link	Link to the report mentioned	—	✓
report-file	attachment	Attachment(s) that is related to the report	—	✓
summary	text	Free text summary of the report	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
type	text	Type of report ['Report', 'Alert', 'Incident', 'Operation', 'Press Article', 'Press Release', 'Online Article', 'Blog post']	✓	—

research-scanner

Information related to known scanning activity (e.g. from research projects).



research-scanner is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
asn	AS	Autonomous System Number related to project	✓	—
contact_email	email-dst	Project contact information	✓	✓
contact_phone	phone-number	Phone number related to project	✓	✓
domain	domain	Domain related to project	—	✓
project	text	Description of scanning project	✓	—
project_url	link	URL related to project	✓	✓
scanning_ip	ip-src	IP address used by project	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
scheduled_end	datetime	Scheduled end of scanning activity	✓	✓
scheduled_start	datetime	Scheduled start of scanning activity	✓	✓

rogue-dns

Rogue DNS as defined by CERT.br.



rogue-dns is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
hijacked-domain	hostname	Domain/hostname hijacked by the rogue DNS	—	—
phishing-ip	ip-dst	Resource records returns by the rogue DNS	—	—
rogue-dns	ip-dst	IP address of the rogue DNS	—	—
status	text	How many authoritative DNS answers were received at the Passive DNS Server's collectors with exactly the given set of values as answers. ['ROGUE DNS', 'Unknown']	✓	—
timestamp	datetime	Last time that the rogue DNS value was seen.	✓	—

rtir

RTIR - Request Tracker for Incident Response.



rtir is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
classification	text	Classification of the RTIR ticket	—	✓
constituency	text	Constituency of the RTIR ticket	—	—
ip	ip-dst	IPs automatically extracted from the RTIR ticket	—	✓
queue	text	Queue of the RTIR ticket ['incident', 'investigations', 'blocks', 'incident reports']	—	—
status	text	Status of the RTIR ticket ['new', 'open', 'stalled', 'resolved', 'rejected', 'deleted']	✓	—
subject	text	Subject of the RTIR ticket	—	—
ticket-number	text	ticket-number of the RTIR ticket	—	—

sandbox-report

Sandbox report.



sandbox-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
on-premise-sandbox	text	The on-premise sandbox used ['cuckoo', 'symantec-cas-on-premise', 'bluecoat-maa', 'trendmicro-deep-discovery-analyzer', 'fireeye-ax', 'vmray', 'joe-sandbox-on-premise']	✓	—
permalink	link	Permalink reference	—	—
raw-report	text	Raw report from sandbox	✓	—
results	text	Freetext result values	✓	✓
saas-sandbox	text	A non-on-premise sandbox, also results are not publicly available ['forticloud-sandbox', 'joe-sandbox-cloud', 'symantec-cas-cloud']	✓	—
sandbox-file	attachment	File related to sandbox run	✓	✓
sandbox-type	text	The type of sandbox used ['on-premise', 'web', 'saas']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
score	text	Score	✓	—
web-sandbox	text	A web sandbox where results are publicly available via an URL ['malwr', 'hybrid-analysis']	✓	—

sb-signature

Sandbox detection signature.



sb-signature is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
datetime	datetime	Datetime	✓	—
signature	text	Name of detection signature - set the description of the detection signature as a comment	—	✓
software	text	Name of Sandbox software	✓	—
text	text	Additional signature description	✓	—

scheduled-event

Event object template describing a gathering of individuals in meatspace.



scheduled-event is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	Postal address of the event.	—	✓
administrator	text	A user account who is an owner or admin of the event.	—	✓
archive	link	Archive of the original event (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	A screen capture or other attachment relevant to the event.	—	✓
e-mail	email-src	Email address of the event contact.	—	✓
embedded-link	url	Link embedded in the event description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the event description (supposed safe).	—	✓
event-alias	text	Aliases of event.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
event-listing	text	Social media and other platforms on which the event is advertised. ['Twitter', 'Facebook', 'Meetup', 'Eventbrite', 'Other']	✓	✓
event-name	text	The name of the event.	—	—
fax-number	phone-number	Fax number of the event contact.	—	✓
hashtag	text	Hashtag used to identify or promote the event.	—	✓
link	link	Original link into the event (supposed harmless).	—	—
person-name	text	A person who is going to the event.	—	✓
phone-number	phone-number	Phone number of the event contact.	—	✓
scheduled-date	datetime	Initial creation of the microblog post	—	✓
url	url	Original URL location of the event (potentially malicious).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
username	text	A user account who is going to the event.	—	✓

scrippsco2-c13-daily

Daily average C13 concentrations (ppm) derived from flask air samples.



scrippsco2-c13-daily is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
c13-value	float	C13 value (ppm) - C13 concentrations are measured on the '08A' Calibration Scale	✓	—
flag	counter	Flag (see taxonomy for details).	✓	—
number-flask	counter	Number of flasks used in daily average.	✓	—
sample-date-excel	float	M\$Excel spreadsheet date format.	✓	—
sample-date-fractional	float	Decimal year and fractional year.	✓	—
sample-datetime	datetime	Datetime the sample has been taken	✓	—

scrippsco2-c13-monthly

Monthly average C13 concentrations (ppm) derived from flask air samples.



scrippsco2-c13-monthly is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
monthly-c13	float	Monthly C13 concentrations in micro-mol C13 per mole (ppm) reported on the 2008A SIO manometric mole fraction scale. This is the standard version of the data most often sought.	✓	—
monthly-c13-seasonal-adjustment	float	Same data after a seasonal adjustment to remove the quasi-regular seasonal cycle. The adjustment involves subtracting from the data a 4-harmonic fit with a linear gain factor.	✓	—
monthly-c13-smoothed	float	Smoothed version of the data generated from a stiff cubic spline function plus 4-harmonic functions with linear gain.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
monthly-c13-smoothed-seasonal-adjustment	float	Same smoothed version with the seasonal cycle removed.	✓	—
sample-date-excel	float	M\$Excel spreadsheet date format.	✓	—
sample-date-fractional	float	Decimal year and fractional year.	✓	—
sample-datetime	datetime	The monthly values have been adjusted to 24:00 hours on the 15th of each month.	✓	—

scrippsco2-co2-daily

Daily average CO2 concentrations (ppm) derived from flask air samples.



scrippsco2-co2-daily is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
co2-value	float	CO2 value (ppm) - CO2 concentrations are measured on the '08A' Calibration Scale	✓	—
flag	counter	Flag taxonomy (see for details).	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
number-flask	counter	Number of flasks used in daily average.	✓	—
sample-date-excel	float	M\$Excel spreadsheet date format.	✓	—
sample-date-fractional	float	Decimal year and fractional year.	✓	—
sample-datetime	datetime	Datetime the sample has been taken	✓	—

scrippsc02-co2-monthly

Monthly average CO2 concentrations (ppm) derived from flask air samples.



scrippsc02-co2-monthly is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
monthly-co2	float	Monthly CO2 concentrations in micro-mol CO2 per mole (ppm) reported on the 2008A SIO manometric mole fraction scale. This is the standard version of the data most often sought.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
monthly-co2-seasonal-adjustment	float	Same data after a seasonal adjustment to remove the quasi-regular seasonal cycle. The adjustment involves subtracting from the data a 4-harmonic fit with a linear gain factor.	✓	—
monthly-co2-smoothed	float	Smoothed version of the data generated from a stiff cubic spline function plus 4-harmonic functions with linear gain.	✓	—
monthly-co2-smoothed-seasonal-adjustment	float	Same smoothed version with the seasonal cycle removed.	✓	—
sample-date-excel	float	M\$Excel spreadsheet date format.	✓	—
sample-date-fractional	float	Decimal year and fractional year.	✓	—
sample-datetime	datetime	The monthly values have been adjusted to 24:00 hours on the 15th of each month.	✓	—

scrippsco2-o18-daily

Daily average O18 concentrations (ppm) derived from flask air samples.



scrippsco2-o18-daily is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
flag	counter	Flag (see taxonomy for details).	✓	—
number-flask	counter	Number of flasks used in daily average.	✓	—
o18-value	float	O18 value (ppm) - O18 concentrations are measured on the '08A' Calibration Scale	✓	—
sample-date-excel	float	M\$Excel spreadsheet date format.	✓	—
sample-date-fractional	float	Decimal year and fractional year.	✓	—
sample-datetime	datetime	Datetime the sample has been taken	✓	—

scrippsco2-o18-monthly

Monthly average O18 concentrations (ppm) derived from flask air samples.



scrippsco2-o18-monthly is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
monthly-o18	float	Monthly O18 concentrations in micro-mol O18 per mole (ppm) reported on the 2008A SIO manometric mole fraction scale. This is the standard version of the data most often sought.	✓	—
monthly-o18-seasonal-adjustment	float	Same data after a seasonal adjustment to remove the quasi-regular seasonal cycle. The adjustment involves subtracting from the data a 4-harmonic fit with a linear gain factor.	✓	—
monthly-o18-smoothed	float	Smoothed version of the data generated from a stiff cubic spline function plus 4-harmonic functions with linear gain.	✓	—
monthly-o18-smoothed-seasonal-adjustment	float	Same smoothed version with the seasonal cycle removed.	✓	—
sample-date-excel	float	M\$Excel spreadsheet date format.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
sample-date-fractional	float	Decimal year and fractional year.	✓	—
sample-datetime	datetime	The monthly values have been adjusted to 24:00 hours on the 15th of each month.	✓	—

script

Object describing a computer program written to be run in a special run-time environment. The script or shell script can be used for malicious activities but also as support tools for threat analysts.



script is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Comment associated to the script.	—	—
filename	filename	Filename used for the script.	✓	✓
language	text	Scripting language used for the script. ['PowerShell', 'VBScript', 'Bash', 'Lua', 'JavaScript', 'AppleScript', 'AWK', 'Python', 'Perl', 'Ruby', 'Winbatch', 'AutoIt', 'PHP', 'Nim']	✓	—
script	text	Free text of the script.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
script-as-attachment	attachment	Attachment of the script.	—	—
state	text	Known state of the script. ['Malicious', 'Unknown', 'Harmless', 'Trusted']	✓	✓

security-playbook

An object to manage, represent, and share course of action playbooks (security playbooks) for cyberspace defense.



security-playbook is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
created	datetime	The time at which the playbook was originally created.	✓	—
creator	text	The entity that created this playbook. It can be a natural person or an organization. It may be represented using an id that identifies the creator.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	More details, context, and possibly an explanation about what this playbook does and tries to accomplish.	✓	—
id	text	A value that uniquely identifies the playbook.	—	—
impact	counter	An integer that represents the impact the playbook has on the organization from 0 to 100. A value of 0 means specifically undefined. Values range from 1, the lowest impact, to a value of 100, the highest. For example, a purely investigative playbook that is non-invasive would have a low impact value of 1, whereas a playbook that performs changes such as adding rules into a firewall would have a higher impact value.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
label	text	An optional set of terms, labels or tags associated with this playbook (e.g., aliases of adversary groups or operations that this playbook is related to).	✓	✓
modified	datetime	The time that this particular version of the playbook was last modified.	✓	—
organization-type	text	Type of an organization, that the playbook is intended for. This can be an industry sector.	✓	—
playbook	attachment	The whole playbook in its native format (e.g., CACAO JSON). Producers and consumers of playbooks use this property to share and retrieve playbooks.	—	—
playbook-abstraction	text	Identifies the level of completeness of the playbook. ['guideline', 'playbook template', 'playbook', 'partial workflow', 'full workflow', 'fully scripted']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
playbook-standard	text	Identification of the playbook standard.	✓	—
playbook-type	text	The security operational functions the playbook addresses. A playbook may account for multiple types (e.g., detection, investigation). ['notification playbook', 'detection playbook', 'investigation playbook', 'prevention playbook', 'mitigation playbook', 'remediation playbook', 'attack playbook']	✓	✓
priority	counter	An integer that represents the priority of this playbook relative to other defined playbooks. A value of 0 means undefined. Values range from 1, the highest priority, to a value of 100, the lowest.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
revoked	boolean	A boolean that identifies if the playbook creator deems that this playbook is no longer valid. ['True', 'False']	✓	—
severity	counter	A positive integer that represents the seriousness of the conditions that this playbook addresses. A value of 0 means specifically undefined. Values range from 1, the lowest severity, to a value of 100, the highest.	✓	—
valid-from	datetime	The time from which the playbook is considered valid and the steps that it contains can be executed.	✓	—
valid-until	datetime	The time at which this playbook should no longer be considered a valid playbook to be executed.	✓	—

shell-commands

Object describing a series of shell commands executed. This object can be linked with malicious files in order to describe a specific execution of shell commands.



shell-commands is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Comment associated to the shell commands executed.	—	—
language	text	Scripting language used for the shell commands executed. ['PowerShell', 'VBScript', 'Bash', 'Lua', 'JavaScript', 'AppleScript', 'AWK', 'Python', 'Perl', 'Ruby', 'Winbatch', 'AutoIt', 'PHP']	✓	—
script	text	Free text of the script if available which executed the shell commands.	—	—
shell-command	text	—	—	✓
state	text	Known state of the script. ['Malicious', 'Unknown', 'Harmless', 'Trusted']	✓	✓

shodan-report

Shodan Report for a given IP.



shodan-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
banner	text	server banner reported	—	—
hostname	domain	Hostnames found	—	✓
ip	ip-dst	IP Address Queried	—	—
org	text	Associated Organization	—	—
port	port	Listening Port	—	—
text	text	A description of the report	—	—

short-message-service

Short Message Service (SMS) object template describing one or more SMS message. Restriction of the initial format 3GPP 23.038 GSM character set doesn't apply.



short-message-service is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
body	text	Message body of the SMS	—	—
from	phone-number	Phone number used to send the SMS	—	✓
name	text	Sender name	—	—
phone-company	text	Phone company of the number used to send the SMS	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
received-date	datetime	Received date of the SMS	✓	—
sent-date	datetime	Initial sent date of the SMS	✓	—
smsc	phone-number	SMS Message Center	—	—
to	phone-number	Phone number receiving the SMS	—	✓
url-rfc5724	url	url representing SMS using RFC 5724 (not url contained in the SMS which should use an url object)	—	—

shortened-link

Shortened link and its redirect target.



shortened-link is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
credential	text	Credential (username, password)	—	—
domain	domain	Full domain	—	—
first-seen	datetime	First time this shortened URL has been seen	✓	—
redirect-url	url	Redirected to URL	—	—
shortened-url	url	Shortened URL	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
text	text	Description and context of the shortened URL	—	—

social-media-group

Social media group object template describing a public or private group or channel.



social-media-group is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
administrator	text	A user account who is an owner or admin of the group.	—	✓
archive	link	Archive of the original group (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts, group members, etc.	—	✓
description	text	A description of the group, channel or community.	—	—
embedded-link	url	Link embedded in the group description (potentially malicious).	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
embedded-safe-link	link	Link embedded in the group description (supposed safe).	—	✓
group-alias	text	Aliases of group, channel or community.	—	✓
group-name	text	The name of the group, channel or community.	—	—
hashtag	text	Hashtag used to identify or promote the group.	—	✓
link	link	Original link into the group (supposed harmless).	—	—
person-name	text	A person who is a member of the group.	—	✓
platform	text	The social media platform used. ['Facebook', 'Twitter']	✓	✓
url	url	Original URL location of the group (potentially malicious).	—	—
username	text	A user account who is a member of the group.	—	✓

software

The Software object represents high-level properties associated with software, including software products. STIX 2.1 - 6.14.



software is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
cpe	cpe	Specifies the Common Platform Enumeration (CPE) entry for the software, if available. The value for this property MUST be a CPE v2.3 entry from the official NVD CPE Dictionary [NVD]. While the CPE dictionary does not contain entries for all software, whenever it does contain an identifier for a given instance of software, this property SHOULD be present.	-	✓
language	text	Specifies the languages supported by the software. The value of each list member MUST be a language code conformant to [RFC5646].	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
name	text	Specifies the name of the software.	—	—
swid	text	Specifies the Software Identification (SWID) Tags [SWID] entry for the software, if available. The tag attribute, tagId, a globally unique identifier, SHOULD be used as a proxy identifier of the tagged product.	—	✓
vendor	text	Specifies the name of the vendor of the software.	✓	—
version	text	Specifies the version of the software.	✓	—

splunk

Splunk / Splunk ES object.



splunk is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	comment	Description	✓	—
drill-down	text	Drilldown	✓	✓
earliest	text	Earliest time	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
latest	text	Latest time	✓	—
response-action	text	Response action ['notable', 'risk']	✓	✓
schedule	other	Schedule	✓	—
search	text	Search / Correlation search	✓	✓

ss7-attack

SS7 object of an attack as seen on the SS7 signaling protocol supporting GSM/GPRS/UMTS networks.



ss7-attack is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Category	text	Category ['Cat0', 'Cat1', 'Cat2.1', 'Cat2.2', 'Cat3.1', 'Cat3.2', 'Cat3.3', 'CatSMS', 'CatSpoofing']	✓	✓
GtAssignee	text	GT Assignee this is the party that got the GT range assigned by their Regulator.	—	✓
GtLessee	text	GT Lessee is a third party who will use a leased global title from a GT Lessor.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
GtLessor	text	GT Lessor is a GT Assignee that has decided to lease one or more of their GTs to a third party, the GT Lessee, typically on a commercial basis.	—	✓
GtSubLessee	text	GT Sub-Lessee – this is an additional third party who has entered into an agreement with the GT Lessee to sub-lease a GT from them.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
MapApplicationContext	text	MAP application context in OID format. ['4.0.0.1.0.1. - networkLocUp', '4.0.0.1.0.2. - locationCancel', '4.0.0.1.0.3. - roamingNbEnquiry', '4.0.0.1.0.22. - subscriberDataModificationNotification', '4.0.0.1.0.6. - callControlTransfer', '4.0.0.1.0.16. - subscriberDataMngt', '4.0.0.1.0.46. - vcsgLcationUpdate', '4.0.0.1.0.15. - interVlrInfoRetrieval', '4.0.0.1.0.18. - networkFunctionals', '4.0.0.1.0.39. - authenticationFailureReport', '4.0.0.1.0.44. - resourceMngt', '4.0.0.1.0.41. - shortMsgMT_VGCS_Relay', '4.0.0.1.0.5. - locInfoRetrieval', '4.0.0.1.0.32. - gprsLocationUpdate', '4.0.0.1.0.33. - gprsLocationInfoRetrieval', '4.0.0.1.0.34. - failureReport', '4.0.0.1.0.35. - gprsNotify', '4.0.0.1.0.11. - handoverControl', '4.0.0.1.0.12. - siWFSAllocation', '4.0.0.1.0.47. - vcsgLcationCancel', '4.0.0.1.0.10. -	✓	-
444				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
MapGmlc	text	MAP GMLC. Phone number.	—	—
MapGsmScfGT	text	MAP GSMSCF GT. Phone number.	—	—
MapImsi	text	MAP IMSI. Phone number starting with MCC/MNC.	—	✓
MapMscGT	text	MAP MSC GT. Phone number.	—	—
MapMsisdn	text	MAP MSISDN. Phone number. tracing, '4.0.0.1.0.14. - infoRetrieval', '4.0.0.1.0.26. - imsiRetrieval', '4.0.0.1.0.19. - networkUnstructuredSs', '4.0.0.1.0.43. - anyTimeInfoHandling', '4.0.0.1.0.4. - istAlerting', '4.0.0.1.0.27. - msPurging', '4.0.0.1.0.28. - subscriberInfoEnquiry', '4.0.0.1.0.29. - anyTimeEnquiry', '4.0.0.1.0.36. - ss_InvocationNotification', '4.0.0.1.0.7. - reporting', '4.0.0.1.0.8. - callCompletion', '4.0.0.1.0.38. - locationSvcEnquiry', '4.0.0.1.0.45. - groupCallInfoRetrieval', '4.0.0.1.0.37. - locationSvcGateways', '4.0.0.1.0.9. -	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
MapOpCode	text	MAP operation codes - Decimal value between 0-99. ['updateLocation - 2', 'cancelLocation - 3', 'provideRoamingNumber - 4', 'noteSubscriberDataModified - 5', 'resumeCallHandling - 6', 'insertSubscriberData - 7', 'deleteSubscriberData - 8', 'sendParameters - 9', 'registerSS - 10', 'eraseSS - 11', 'activateSS - 12', 'deactivateSS - 13', 'interrogateSS - 14', 'authenticationFailureReport - 15', 'registerPassword - 17', 'getPassword - 18', 'processUnstructuredSS_Data - 19', 'releaseResources - 20', 'mtForwardSM_VGCS - 21', 'sendRoutingInfo - 22', 'updateGprsLocation - 23', 'sendRoutingInfoForGprs - 24', 'failureReport - 25', 'noteMsPresentForGprs - 26', 'performHandover - 28', 'sendEndSignal - 29']	✓	-
446				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
MapSmsTP-DCS	text	MAP SMS TP-DCS.	✓	—
MapSmsTP-OA	text	MAP SMS TP-OA. Phone number.	—	—
MapSmsTP-PID	text	MAP SMS TP-PID.	✓	—
MapSmsText	text	MAP SMS Text. Important indicators in SMS text.	—	—
MapSmsTypeNumber	text	MAP SMS TypeNumber.	✓	—
MapSmScGT	text	MAP SMSC. Phone number.	—	✓
MapUssdCoding	text	MAP USSD Content.	✓	—
MapUssdContent	text	MAP USSD Content.	—	—
MapVersion	text	Map version. [1', '2', '3']	✓	—
MapVlrGT	text	MAP VLR GT. Phone number.	—	—
SccpCdGT	text	Signaling Connection Control Part (SCCP) CdGT - Phone number.	—	✓
SccpCdGT-Country	text	Country in which SCCP CDGT is registered.	—	—

'deactivateTraceMode - 51',
'traceSubscriberActivity - 52',
'updateVcsgLocation - 53',

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
SccpCdGT-CountryISO2	text	Code ISO 3166-1 alpha-2 from which the SCCP CDTG is allocated.	—	—
SccpCdGT-OperatorName	text	Operator Name under which the SCCP CDTG is registered.	—	—
SccpCdGT-TADIG	text	TADIG under which the SCCP CDTG is registered.	—	—
SccpCdPC	text	Signaling Connection Control Part (SCCP) CdPC - Phone number.	—	—
SccpCdSSN	text	Signaling Connection Control Part (SCCP) - Decimal value between 0-255.	✓	—
SccpCgGT	text	Signaling Connection Control Part (SCCP) CgGT - Phone number.	—	✓
SccpCgGT-Country	text	Country in which SCCP CGGT is registered.	—	—
SccpCgGT-CountryISO2	text	Allocated Code ISO 3166-1 alpha-2 for the SCCP CGGT.	—	—

'eraseCC_Entry - 77',
 'provideSubscribe rLocation - 83',
 'sendGroupCallInf'

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
SccpCgGT-OperatorName	text	Operator Name under which the SCCP CGGT is registered.	—	—
SccpCgGT-TADIG	text	TADIG under which the SCCP CGGT is registered.	—	—
SccpCgPC	text	Signaling Connection Control Part (SCCP) CgPC - Phone number.	—	✓
SccpCgSSN	text	Signaling Connection Control Part (SCCP) - Decimal value between 0-255.	✓	—
first-seen	datetime	When the attack has been seen for the first time.	✓	—
text	text	A description of the attack seen via SS7 logging.	✓	✓

ssh-authorized-keys

An object to store ssh authorized keys file.



ssh-authorized-keys is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
first-seen	datetime	First time the ssh authorized keys file has been seen	✓	—
full-line	text	One full-line of the authorized key file	—	✓
hostname	hostname	hostname	—	✓
ip	ip-dst	IP Address	—	✓
key	text	Public key in base64 as found in the authorized key file	—	✓
key-id	text	Key-id and option part of the public key line	—	✓
last-seen	datetime	Last time the ssh authorized keys file has been seen	✓	—
text	text	A description of the ssh authorized keys	✓	—

stix2-pattern

An object describing a STIX pattern. The object can be linked via a relationship to other attributes or objects to describe how it can be represented as a STIX pattern.



stix2-pattern is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	A description of the stix2-pattern.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
stix2-pattern	stix2-pattern	STIX 2 pattern	—	—
version	text	Version of STIX 2 pattern. ['stix 2.0', 'stix 2.1']	✓	—

submarine

Submarine description.



submarine is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
active	counter	The number of submarines of this class in active service	—	—
armament	text	Armaments carried by the submarine	—	✓
beam	float	The beam measurement of the submarine in meters	—	—
builders	text	The organisation building this class of submarines	—	✓
cancelled	counter	The number of submarines of this class cancelled	—	—
class	text	Submarine class	—	—
complement	counter	Crew size	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
completed	counter	The number of submarines of this class built	—	—
displacement	counter	Displacement in tons	—	—
draught	float	The draught measurement of the submarine in meters	—	—
endurance	counter	Expected submerged endurance in days	—	—
in_service_from	counter	The year the submarine entered service	—	—
in_service_until	counter	The year the submarine left service	—	—
length	float	The length measurement of the submarine in meters	—	—
operator	text	The countries operating such vessels (can be multiple)	—	✓
planned	counter	The number of submarines of this class planned to be built	—	—
predecessor	text	Predecessor class	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
propulsion	text	The propulsion of the submarine, add multiple if applicable	—	✓
retired	counter	The number of submarines of this class that has been retired	—	—
speed_submerged	float	Surfaced top speed in knots	—	—
speed_surfaced	float	Surfaced top speed in knots	—	—
successor	text	Successor class	—	—
type	text	Submarine type ['Ballistic missile submarine', 'Cruise missile submarine', 'Nuclear-powered attack submarine', 'Non-nuclear attack submarine with air-independent propulsion', 'Diesel-electric attack submarine', 'Midget submarine', 'Special mission submarine']	✓	—

suricata

An object describing one or more Suricata rule(s) along with version and contextual information.



suricata is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	A description of the Suricata rule(s).	—	—
ref	link	Reference to the Suricata rule such as origin of the rule or alike.	—	—
suricata	snort	Suricata rule.	—	✓
version	text	Version of the Suricata rule depending where the suricata rule is known to work as expected.	—	—

target-system

Description about an targeted system, this could potentially be a compromised internal system.



target-system is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
targeted_ip_of_system	ip-src	Targeted system IP address	✓	—
targeted_machine	target-machine	Targeted system	✓	—
timestamp_seen	datetime	Registered date and time	✓	—

tattoo

Describes tattoos on a natural person's body.



tattoo is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
tattoo-body-part	text	Describe the body part where the tattoo is located. ['head', 'forehead', 'face', 'ear', 'eye', 'mouth/lips', 'neck', 'shoulder', 'chest', 'elbow', 'arm', 'forearm', 'hand', 'finger', 'thigh', 'knee', 'calf', 'heel', 'foot', 'toe']	-	-
tattoo-color	text	Colors of the tattoo ['black', 'white', 'red', 'green', 'blue', 'cyan', 'orange', 'violet', 'pink', 'yellow', 'brown', 'grey']	-	✓
tattoo-description	text	Description of the tattoo, its composition.	✓	-
tattoo-picture	attachment	Picture of the tattoo	-	✓
tattoo-size	text	Size of the tattoo ['tiny', 'small', 'medium', 'large']	-	-

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
tattoo-style	text	Style of the tattoo ['traditional', 'realism', 'watercolor', 'tribal', 'new school', 'japanese', 'blackwork', 'lettering', 'dotwork', 'abstract', 'celtic', 'geometric', 'mandala', 'minimalist', 'neo- traditional', 'portrait', 'sketch']	—	✓

telegram-account

Information related to a telegram account.



telegram-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
first_name	text	First name	—	—
id	text	Telegram user identifier	—	—
last_name	text	Last name	—	—
phone	text	Phone associated with the telegram user	—	✓
username	text	Telegram username	—	—
verified	text	Verified	—	—

temporal-event

A temporal event consists of some temporal and spacial boundaries. Spacial boundaries can be physical, virtual or hybrid.



temporal-event is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Free text description of the temporal event.	—	✓
link	link	Link or reference to the temporal event mentioned.	—	✓
summary	text	One line summary of the temporal event.	—	—
type	text	Type of temporal event. ['Physical Event', 'Virtual Event', 'Hybrid Event', 'Unknown']	✓	—

threatgrid-report

ThreatGrid report.



threatgrid-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
analysis_submitted_at	text	Submission date	—	—
heuristic_raw_score	text	heuristic_raw_score	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
heuristic_score	text	heuristic_score	—	—
id	text	ThreatGrid ID	—	—
iocs	text	iocs	—	✓
original_filename	text	Original filename	—	—
permalink	text	permalink	—	—
threat_score	text	threat_score	✓	—

timecode

Timecode object to describe a start of video sequence (e.g. CCTV evidence) and the end of the video sequence.



timecode is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description of the video sequence	—	—
end-marker-timecode	text	End marker timecode in the format hh:mm:ss;ff	—	✓
end-timecode	text	End marker timecode in the format hh:mm:ss.mms	—	✓
recording-date	datetime	Date of recording of the video sequence	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
start-marker-timecode	text	Start marker timecode in the format hh:mm:ss;ff	—	✓
start-timecode	text	Start marker timecode in the format hh:mm:ss.mms	—	✓

timesketch-timeline

A timesketch timeline object based on mandatory field in timesketch to describe a log entry.



timesketch-timeline is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
datetime	datetime	When the log entry was seen	—	—
message	text	Informative message of the event	—	—
timestamp	text	When the log entry was seen in microseconds since Unix epoch	—	—
timestamp_desc	text	Text explaining what type of timestamp is it	—	—

timesketch_message

A timesketch message entry.



timesketch_message is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
datetime	datetime	datetime of the message	✓	—
message	text	message	✓	—

timestamp

A generic timestamp object to represent time including first time and last time seen. Relationship will then define the kind of time relationship.



timestamp is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
first-seen	datetime	First time that the linked object or attribute has been seen.	✓	—
last-seen	datetime	First time that the linked object or attribute has been seen.	✓	—
precision	text	Timestamp precision represents the precision given to first_seen and/or last_seen in this object. ['year', 'month', 'day', 'hour', 'minute', 'full']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
text	text	Description of the time object.	✓	—

tor-hiddenservice

Tor hidden service (onion service) object.



tor-hiddenservice is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	text	onion address of the Tor node seen.	—	—
description	text	Tor onion service comment.	✓	—
first-seen	datetime	When the Tor hidden service was been seen for the first time.	✓	—
last-seen	datetime	When the Tor hidden service was seen for the last time.	✓	—

tor-node

Tor node (which protects your privacy on the internet by hiding the connection between users Internet address and the services used by the users) description which are part of the Tor network at a time.



tor-node is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
address	ip-src	IP address of the Tor node seen.	—	—
description	text	Tor node description.	✓	—
document	text	Raw document from the consensus.	✓	—
fingerprint	text	router's fingerprint.	—	—
first-seen	datetime	When the Tor node designed by the IP address has been seen for the first time.	✓	—
flags	text	list of flag associated with the node.	—	—
last-seen	datetime	When the Tor node designed by the IP address has been seen for the last time.	✓	—
nickname	text	router's nickname.	—	—
published	datetime	router's publication time. This can be different from first-seen and last-seen.	✓	—
text	text	Tor node comment.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
version	text	parsed version of tor, this is None if the relay's using a new versioning scheme.	—	—
version_line	text	versioning information reported by the node.	—	—

tracking-id

Analytics and tracking ID such as used in Google Analytics or other analytic platform.



tracking-id is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description of the tracking id.	✓	—
first-seen	datetime	First time the tracking code was seen.	✓	—
hostname	hostname	Hostname where the tracking id was found (assumed safe).	—	✓
id	text	Tracking code.	—	—
last-seen	datetime	Last time the tracking code was seen.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
tracker	text	Name of the tracker organisation doing the tracking and/or analytics. ['Google Analytics', 'Piwik', 'Kissmetrics', 'Woopra', 'Chartbeat']	—	—
url	url	URL where the tracking id was found (potentially malicious).	—	✓

transaction

An object to describe a financial transaction.



transaction is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
amount	text	The value of the transaction in local currency.	—	—
authorized	text	Person who authorized the transaction.	—	—
date	datetime	Date and time of the transaction.	—	—
date-posting	datetime	Date of posting, if different from date of transaction.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
from-country	text	Origin country of a transaction.	—	—
from-funds-code	text	Type of funds used to initiate a transaction. ['A Deposit', 'C Currency exchange', 'D Casino chips', 'E Bank draft', 'F Money order', 'G Traveler's cheques', 'H Life insurance policy', 'I Real estate', 'J Securities', 'K Cash', 'O Other', 'P Cheque']	✓	—
location	text	Location where the transaction took place.	—	—
teller	text	Person who conducted the transaction.	—	—
text	text	A description of the transaction.	✓	—
to-country	text	Target country of a transaction.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
to-funds-code	text	Type of funds used to finalize a transaction. ['A Deposit', 'C Currency exchange', 'D Casino chips', 'E Bank draft', 'F Money order', 'G Traveler's cheques', 'H Life insurance policy', 'I Real estate', 'J Securities', 'K Cash', 'O Other', 'P Cheque']	✓	—
transaction-number	text	A unique number identifying a transaction.	—	—
transmode-code	text	How the transaction was conducted.	—	—
transmode-comment	text	Comment describing transmode-code, if needed.	—	—

translation

Used to keep a text and its translation.



translation is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
original-language	text	Language of the original text ['Mandarin (language family)', 'Spanish', 'English', 'Hindi', 'Bengali', 'Portuguese', 'Russian', 'Japanese', 'Western Punjabi', 'Marathi', 'Telugu', 'Wu (language family)', 'Turkish', 'Korean', 'French', 'German', 'Vietnamese', 'Tamil', 'Yue (language family)', 'Urdu', 'Javanese', 'Italian', 'Egyptian Arabic', 'Gujarati', 'Iranian Persian', 'Bhojpuri', 'Min Nan (language family)', 'Hakka', 'Jinyu', 'Hausa', 'Kannada', 'Indonesian (Indonesian Malay)', 'Polish', 'Yoruba', 'Xiang Chinese (language family)', 'Malayalam', 'Odia', 'Maithili', 'Burmese', 'Eastern Punjabi', 'Sunda', 'Sudanese Arabic', 'Algerian Arabic', 'Moroccan Arabic', 'Ukrainian', 'Igbo', 'Northern Uzbek', 'Sindhi', 'North Levantine Arabic', 'Romanian', 'Tagalog', 'Dutch', 'Sāidi Arabic',	—	—
468				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
original-text	text	Original text	—	—
translated-text	text	Text after translation	—	—

'Somali', 'Malay (Malaysian Malay)', 'Cebuano', 'Nepali', 'Mesopotamian Arabic', 'Assamese', 'Sinhala', 'Northern Kurdish', 'Hejazi Arabic', 'Nigerian Fulfulde', 'South Azerbaijani', 'Greek', 'Chittagonian', 'Kazakh', 'Deccan', 'Hungarian', 'Kinyarwanda', 'Zulu', 'South Levantine Arabic', 'Tunisian Arabic', 'Sanaani Spoken Arabic', 'Min Bei Chinese (language family)', 'Southern Pashto', 'Rundi', 'Czech', 'Taizzi-Adeni Arabic', 'Uyghur', 'Min Dong Chinese (language family)', 'Sylheti']

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
translation-language	text	Language of translation ['Mandarin (language family)', 'Spanish', 'English', 'Hindi', 'Bengali', 'Portuguese', 'Russian', 'Japanese', 'Western Punjabi', 'Marathi', 'Telugu', 'Wu (language family)', 'Turkish', 'Korean', 'French', 'German', 'Vietnamese', 'Tamil', 'Yue (language family)', 'Urdu', 'Javanese', 'Italian', 'Egyptian Arabic', 'Gujarati', 'Iranian Persian', 'Bhojpuri', 'Min Nan (language family)', 'Hakka', 'Jinyu', 'Hausa', 'Kannada', 'Indonesian (Indonesian Malay)', 'Polish', 'Yoruba', 'Xiang Chinese (language family)', 'Malayalam', 'Odia', 'Maithili', 'Burmese', 'Eastern Punjabi', 'Sunda', 'Sudanese Arabic', 'Algerian Arabic', 'Moroccan Arabic', 'Ukrainian', 'Igbo', 'Northern Uzbek', 'Sindhi', 'North Levantine Arabic', 'Romanian', 'Tagalog', 'Dutch', 'Sāidi Arabic',	—	—
470				

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
translation-service	text	translation service used for the translation ['Google Translate', 'Microsoft Translator', 'Babelfish', 'Reverso', 'Dict.cc', 'Linguee', 'unknown']	—	—
translation-type	text	type of translation ['Automated translation', 'Manual translation']	—	—

trustar_report

TruStar Report.



trustar_report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
BITCOIN_ADDRESSES	btc	A bitcoin address is an identifier of 26-35 alphanumeric characters, beginning with the number 1 or 3, that represents a possible destination for a bitcoin payment.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
CIDR_BLOCK	ip-src	CIDR (Classless Inter-Domain Routing) identifies a range of IP addresses, and was introduced as a way to allow more flexible allocation of Internet Protocol (IP) addresses than was possible with the original system of IP address classes.	—	✓
COMMENTS	text	A space for additional comments.	—	✓
CVE	vulnerability	The Common Vulnerabilities and Exposures (CVE) system provides a reference-method for publicly known information-security vulnerabilities and exposures.	—	✓
EMAIL_ADDRESS	email-src	An email address is a unique identifier for an email account.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
INDICATOR_SUMMARY	text	Free text summary data related to an indicator. This should include a normalized score if one exists.	—	✓
IP	ip-dst	An Internet Protocol address (IP address) is a numerical label assigned to each device participating in a computer network that uses the Internet Protocol for communication.	—	✓
MALWARE	malware-type	Names of software that are intended to damage or disable computers and computer systems.	—	✓
MD5	md5	The MD5 algorithm is a widely used hash function producing a 128-bit hash value.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
REGISTRY_KEY	regkey	The registry is a hierarchical database that contains data that is critical for the operation of Windows and the applications and services that run on Windows.	—	✓
REPORT_LINK	link	A link to the TruSTAR report. Access may be restricted depending on user permissions.	—	✓
SHA1	sha1	SHA-1 (Secure Hash Algorithm 1) is a cryptographic hash function which takes an input and produces a 160-bit (20-byte) hash value known as a message digest - typically rendered as a hexadecimal number, 40 digits long. SHA-1 is prone to length extension attacks.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
SHA256	sha256	SHA-256 is a member of the SHA-2 cryptographic hash functions designed by the NSA, which are the successors to SHA-1. It is represented as a 64-character hexadecimal string.	—	✓
SOFTWARE	filename	The name of a file on a filesystem.	—	✓
THREAT_ACTOR	threat-actor	A string identifying the threat actor.	—	✓
URL	url	A Uniform Resource Locator (URL) is a reference to a web resource that specifies its location on a computer network and a mechanism for retrieving it.	—	✓

tsk-chats

An Object Template to gather information from evidential or interesting exchange of messages identified during a digital forensic investigation.



tsk-chats is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
Source	text	Source of the message.(Contact details)	✓	—
additional-comments	text	Comments.	✓	—
app-used	text	Application used to send the message.	✓	—
attachments	link	External references	—	✓
datetime-received	datetime	date and time when the message was received.	✓	✓
datetime-sent	datetime	date and the time when the message was sent.	✓	—
destination	text	Destination of the message.(Contact details)	✓	—
message	text	Message exchanged.	—	—
message-type	text	the type of message extracted from the forensic-evidence. ['SMS', 'MMS', 'Instant Message (IM)', 'Voice Message']	✓	—
subject	text	Subject of the message if any.	—	—

tsk-web-bookmark

An Object Template to add evidential bookmarks identified during a digital forensic investigation.



tsk-web-bookmark is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
URL	link	The URL saved as bookmark.	—	—
additional-comments	text	Comments.	✓	—
browser	text	Browser used to access the URL. ['IE', 'Safari', 'Chrome', 'Firefox', 'Opera mini', 'Chromium']	✓	—
datetime-bookmarked	datetime	date and time when the URL was added to favorites.	✓	—
domain-ip	ip-src	IP of the URL domain.	—	—
domain-name	text	Domain of the URL.	—	—
name	text	Book mark name.	✓	—
title	text	Title of the web page	—	—

tsk-web-cookie

An TSK-Autopsy Object Template to represent cookies identified during a forensic investigation.



tsk-web-cookie is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
URL	link	The website URL that created the cookie.	—	—
additional-comments	text	Comments.	✓	—
browser	text	Browser on which the cookie was created. ['IE', 'Safari', 'Chrome', 'Firefox', 'Opera mini', 'Chromium']	—	—
datetime-created	datetime	date and time when the cookie was created.	✓	—
domain-ip	ip-src	IP of the domain that created the URL.	—	—
domain-name	text	Domain of the URL that created the cookie.	—	—
name	text	Name of the cookie	—	—
value	text	Value assigned to the cookie.	—	—

tsk-web-downloads

An Object Template to add web-downloads.



tsk-web-downloads is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
additional-comments	text	Comments.	✓	—
attachment	attachment	The downloaded file itself.	✓	—
datetime-accessed	datetime	date and time when the file was downloaded.	✓	—
name	text	Name of the file downloaded.	—	—
path-downloadedTo	text	Location the file was downloaded to.	—	—
pathID	text	Id of the attribute file where the information is gathered from.	✓	—
url	url	The URL used to download the file.	—	—

tsk-web-history

An Object Template to share web history information.



tsk-web-history is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
URL	link	The URL accessed.	—	—
additional-comments	text	Comments.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
browser	text	Browser used to access the URL. ['IE', 'Safari', 'Chrome', 'Firefox', 'Opera mini', 'Chromium']	✓	—
datetime-accessed	datetime	date and the time when the URL was accessed.	✓	—
domain-ip	ip-src	IP of the URL domain.	—	—
domain-name	text	Domain of the URL.	—	—
referrer	text	where the URL was referred from	✓	—
title	text	Title of the web page	—	—

tsk-web-search-query

An Object Template to share web search query information.



tsk-web-search-query is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
additional-comments	text	Comments.	✓	—
browser	text	Browser used. ['IE', 'Safari', 'Chrome', 'Firefox', 'Opera mini', 'Chromium']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
datetime-searched	datetime	date and time when the search was conducted.	✓	—
domain	text	The domain of the search engine. ['Google', 'Yahoo', 'Bing', 'Alta Vista', 'MSN']	✓	—
text	text	the search word or sentence.	—	—
username	text	User name or ID associated with the search.	✓	—

twitter-account

Twitter account.



twitter-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the account (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts etc.	—	✓
bio	text	Displayed biography of the user.	—	—
description	text	A description of the user.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
displayed-name	text	Displayed name.	—	—
embedded-link	url	Link embedded in the user description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the user description (supposed safe).	—	✓
followers	text	Number of followers.	✓	—
following	text	Number of accounts this accounts is following.	✓	—
hashtag	text	Hashtag embedded in the user description.	—	✓
id	text	Numeric account id.	—	—
joined-date	datetime	When the account was created	✓	—
likes	text	Number of likes this account has.	✓	—
link	link	Original link to the user (supposed harmless).	—	—
listed	text	Number of lists the user is on.	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
location	text	User description of location.	✓	—
media	text	Number of images and videos posted.	✓	—
name	text	User's screen name (without the @).	—	—
private	text	User verified. ['True', 'False']	✓	—
profile-banner	attachment	A screenshot or exported user avatar.	—	—
profile-banner-url	url	A link to the user's background image.	—	—
profile-image	attachment	A screenshot or exported user avatar.	—	—
profile-image-url	url	A link to the user's avatar.	—	—
tweets	text	Number of tweets posted.	✓	—
twitter-followers	text	followers accounts of interest	—	✓
twitter-following	text	following accounts of interest	—	✓
url	url	Original URL location of the user (potentially malicious).	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
verified	text	User verified. ['True', 'False']	✓	—

twitter-list

Twitter list.



twitter-list is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the account (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts etc.	—	✓
description	text	A description of the list.	—	—
embedded-link	url	Link embedded in the description (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the description (supposed safe).	—	✓
hashtag	text	Hashtag embedded in the description.	—	✓
id	text	Numeric list id.	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link to the list (supposed harmless).	—	—
member-count	text	Number of accounts following this list.	✓	—
name	text	List's screen name (without the @).	—	—
subscriber-count	text	Number of accounts subscribing to this list.	✓	—
url	url	Original URL location of the list (potentially malicious).	—	—
user-id	text	Id of the account that manages this list.	—	—
user-name	text	Name of the account that manages this list (without the @).	—	—

twitter-post

Twitter post (tweet).



twitter-post is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original tweet (Internet Archive, Archive.is, etc).	—	✓
attachment	attachment	The tweet file or screen capture.	—	✓
created-at	datetime	Datetime of Tweet publication	—	—
embedded-link	url	Link in the tweet	—	✓
embedded-safe-link	link	Safe link in the tweet	—	✓
favorite-count	text	Number of favorites.	✓	—
geo	text	Geolocation data.	✓	—
hashtag	text	Hashtag embedded in the tweet	—	✓
in-reply-to-display-name	text	The user display name of the tweet this post shares.	—	✓
in-reply-to-status-id	text	The twitter ID of the tweet that this post shares.	—	✓
in-reply-to-user-id	text	The user ID of the tweet this post shares.	—	✓
language	text	The language of the post.	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
link	link	Original link to the post (supposed harmless).	—	✓
media	attachment	Media (Photos, videos) present in tweet	—	✓
name	text	Name of the account that posted this tweet.	—	—
possibly-sensitive	text	Does this post contain sensitive content?	✓	—
possibly-sensitive-appealable	text	Is the sensitive content of this post appealable?	✓	—
post	text	Raw text of the post.	—	—
post-id	text	Numeric id of the tweet.	—	—
removal-date	datetime	When the tweet was removed.	✓	—
retweet-count	text	Number of retweets.	✓	—
source	text	Source of tweet (android, web etc).	✓	—
url	url	Original URL of the tweet, e.g. link shortener (potentially malicious).	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
user-id	text	Id of the account that posted this tweet.	—	—
username-quoted	text	Username who is quoted in the tweet.	—	✓

url

url object describes an url along with its normalized field (like extracted using faup parsing library) and its metadata.



url is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
credential	text	Credential (username, password)	—	—
domain	domain	Full domain	—	—
domain_without_td	text	Domain without Top-Level Domain	—	—
first-seen	datetime	First time this URL has been seen	✓	—
fragment	text	Fragment identifier is a short string of characters that refers to a resource that is subordinate to another, primary resource.	—	✓
host	hostname	Full hostname	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
ip	ip-dst	Better type when the host is an IP.	—	✓
last-seen	datetime	Last time this URL has been seen	✓	—
port	port	Port number	✓	—
query_string	text	Query (after path, preceded by '?')	—	✓
resource_path	text	Path (between hostname:port and query)	—	✓
scheme	text	Scheme ['http', 'https', 'ftp', 'gopher', 'sip']	✓	—
subdomain	text	Subdomain	✓	—
text	text	Description of the URL	—	—
tld	text	Top-Level Domain	✓	—
url	url	Full URL	—	—

user-account

User-account object, defining aspects of user identification, authentication, privileges and other relevant data points.



user-account is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
account-type	text	Type of the account. ['facebook', 'ldap', 'nis', 'openid', 'radius', 'skype', 'tacacs', 'twitter', 'unix', 'windows-local', 'windows-domain']	—	—
can_escalate_privs	boolean	Specifies if the account has the ability to escalate privileges. ['True', 'False']	✓	—
created	datetime	Creation time of the account.	✓	—
description	text	A description of the user account.	✓	—
disabled	boolean	Specifies if the account is desabled. ['True', 'False']	✓	—
display-name	text	Display name of the account.	—	—
expires	datetime	Expiration time of the account	✓	—
first_login	datetime	First time someone logged in to the account.	✓	—
group	text	UNIX group(s) the account is member of.	✓	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
group-id	text	Identifier of the primary group of the account, in case of a UNIX account.	✓	—
home_dir	text	Home directory of the UNIX account.	✓	—
is_service_account	boolean	Specifies if the account is associated with a network service. ['True', 'False']	✓	—
last_login	datetime	Last time someone logged in to the account.	✓	—
link	link	Original link into the account page (Supposed harmless)	—	—
password	text	Password related to the username.	—	—
password_last_changed	datetime	Last time the password has been changed.	✓	—
privileged	boolean	Specifies if the account has privileges such as root rights. ['True', 'False']	✓	—
shell	text	UNIX command shell of the account.	✓	—
user-avatar	attachment	A user profile picture or avatar.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
user-id	text	Identifier of the account.	—	—
username	text	Username related to the password.	—	—

vehicle

Vehicle object template to describe a vehicle information and registration.



vehicle is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
date-first-registration	text	Date of first registration	—	✓
description	text	Description of the vehicle	✓	—
dyno-power	text	Dyno power output	—	✓
exterior-color	text	Exterior color of the vehicle	✓	—
gearbox	text	Gearbox	—	✓
image	attachment	Image of the vehicle.	—	✓
image-url	text	Image URL	—	✓
indicative-value	text	Indicative value	—	✓
interior-color	text	Interior color of the vehicle	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
license-plate-number	text	License plate number	—	✓
make	text	Manufacturer of the vehicle	✓	—
model	text	Model of the vehicle	✓	—
state	text	State of the vehicule (stolen or recovered)	✓	—
type	text	Type of the vehicule ['car', 'bus', 'caravan', 'bicycle', 'boat', 'taxi', 'camper van', 'motorcycle', 'truck', 'scooter', 'tractor', 'trailer', 'van']	✓	—
vin	text	Vehicle identification number (VIN)	—	—

victim

Victim object describes the target of an attack or abuse.



victim is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
classification	text	The type of entity being targeted. ['individual', 'group', 'organization', 'class', 'unknown']	✓	—
description	text	Description of the victim	—	—
domain	domain	Domain name of the organisation targeted.	—	✓
email	target-email	The email address(es) of the user targeted.	—	✓
external	target-external	External target organisations affected by this attack.	—	✓
ip-address	ip-dst	IP address(es) of the node targeted.	—	✓
name	target-org	The name of the department(s) or organisation(s) targeted.	—	✓
node	target-machine	Name(s) of node that was targeted.	—	✓
reference	text	External reference to the victim/case.	—	✓
regions	target-location	The list of regions or locations from the victim targeted. ISO 3166 should be used.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
roles	text	The list of roles targeted within the victim.	—	✓
sectors	text	The list of sectors that the victim belong to ['agriculture', 'aerospace', 'automotive', 'communications', 'construction', 'defence', 'education', 'energy', 'engineering', 'entertainment', 'financial services', 'government national', 'government regional', 'government local', 'government public services', 'healthcare', 'hospitality leisure', 'infrastructure', 'insurance', 'manufacturing', 'mining', 'non profit', 'pharmaceuticals', 'retail', 'technology', 'telecommunications', 'transportation', 'utilities']	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
user	target-user	The username(s) of the user targeted.	—	✓

virustotal-graph

VirusTotal graph.



virustotal-graph is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
access	text	Access to the VirusTotal graph ['Private', 'Public']	✓	—
comment	text	Comment related to this VirusTotal graph	✓	✓
permalink	link	Permalink Reference to the VirusTotal graph	—	—
screenshot	attachment	Screenshot of the VirusTotal graph	✓	—

virustotal-report

VirusTotal report.



virustotal-report is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Comment related to this hash	✓	✓
community-score	text	Community Score	✓	—
detection-ratio	text	Detection Ratio	✓	—
first-submission	datetime	First Submission	✓	—
last-submission	datetime	Last Submission	✓	—
permalink	link	Permalink Reference	✓	—

virustotal-submission

VirusTotal Submission.



virustotal-submission is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
city	text	The city a file was uploaded from.	✓	—
country	text	The country a file was uploaded from.	✓	—
date	datetime	The upload date.	✓	—
filename	filename	The filename used to submit a file.	—	—
interface	text	The interface used to upload a file. ['web', 'api', 'email']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
submitter-id	text	Submitter ID, given as source_key via the VT API.	—	—

vulnerability

Vulnerability object describing a common vulnerability enumeration which can describe published, unpublished, under review or embargo vulnerability for software, equipments or hardware.



vulnerability is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
created	datetime	First time when the vulnerability was discovered	✓	—
credit	text	Who reported/found the vulnerability such as an organisation, person or nickname.	✓	✓
cvss-score	float	Score of the Common Vulnerability Scoring System (version 3).	✓	—
cvss-string	text	String of the Common Vulnerability Scoring System (version 3).	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description of the vulnerability	—	—
id	vulnerability	Vulnerability ID (generally CVE, but not necessarily). The id is not required as the object itself has an UUID and the CVE id can be update or assigned later.	—	✓
modified	datetime	Last modification date	✓	—
published	datetime	Initial publication date	✓	—
references	link	External references	—	✓
state	text	State of the vulnerability. A vulnerability can have multiple states depending of the current actions performed. ['Published', 'Embargo', 'Reviewed', 'Vulnerability ID Assigned', 'Reported', 'Fixed']	✓	✓
summary	text	Summary of the vulnerability	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
vulnerable-configuration	cpe	The vulnerable configuration is described in CPE format	—	✓

weakness

Weakness object describing a common weakness enumeration which can describe usable, incomplete, draft or deprecated weakness for software, equipment of hardware.



weakness is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
description	text	Description of the weakness.	—	—
id	weakness	Weakness ID (generally CWE).	—	—
name	text	Name of the weakness.	—	—
status	text	Status of the weakness. ['Incomplete', 'Deprecated', 'Draft', 'Usable']	✓	—
weakness-abs	text	Abstraction of the weakness. ['Class', 'Base', 'Variant']	✓	—

whois

Whois records information for a domain name or an IP address.



whois is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Comment of the whois entry	—	—
creation-date	datetime	Initial creation of the whois entry	✓	—
domain	domain	Domain of the whois entry	—	✓
expiration-date	datetime	Expiration of the whois entry	✓	—
ip-address	ip-src	IP address of the whois entry	—	✓
modification-date	datetime	Last update of the whois entry	✓	—
nameserver	hostname	Nameserver	✓	✓
registrant-email	whois-registrant-email	Registrant email address	—	—
registrant-name	whois-registrant-name	Registrant name	—	—
registrant-org	whois-registrant-org	Registrant organisation	—	—
registrant-phone	whois-registrant-phone	Registrant phone number	—	—
registrar	whois-registrar	Registrar of the whois entry	—	—
text	text	Full whois entry	✓	—

windows-service

Windows service and detailed about a service running a Windows operating system.



windows-service is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	text	Additional comments.	✓	—
display	windows-service-displayname	Display name/information of the service.	—	—
group	text	Group to which the system/driver belong to. ['Base', 'Boot Bus Extender', 'Boot File System', 'Cryptography', 'Extended base', 'Event Log', 'Filter', 'FSFilter Bottom', 'FSFilter Infrastructure', 'File System', 'FSFilter Virtualization', 'Keyboard Port', 'Network', 'NDIS', 'Parallel arbitrator', 'Pointer Port', 'PnP Filter', 'ProfSvc_Group', 'PNP_TDI', 'SCSI Miniport', 'SCSI CDROM Class', 'System Bus Extender', 'Video Save', 'other']	✓	—
image-path	text	Path of the service/drive	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
name	windows-service-name	name of the service	—	—
start	text	When the service/driver starts or executes. ['Boot start', 'System start', 'Auto start', 'Manual', 'Disabled']	✓	—
type	text	Service/driver type. ['Kernel driver', 'File system driver', 'Own process', 'Share process', 'Interactive', 'Other']	✓	—

x509

x509 object describing a X.509 certificate.



x509 is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
dns_names	hostname	Subject Alternative Name - DNS names	—	✓
email	email-dst	Subject Alternative Name - emails	—	✓
ip	ip-dst	Subject Alternative Name - IP	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
is_ca	boolean	CA certificate ['True', 'False']	✓	—
issuer	text	Issuer of the certificate	✓	—
pem	text	Raw certificate in PEM format (Unix-like newlines)	—	—
pubkey-info-algorithm	text	Algorithm of the public key	✓	—
pubkey-info-exponent	text	Exponent of the public key - in decimal	—	—
pubkey-info-modulus	text	Modulus of the public key - in Hexadecimal - no 0x, no :	—	—
pubkey-info-size	text	Length of the public key (in bits expressed in decimal: eg. 256 bits)	✓	—
raw-base64	text	Raw certificate base64 encoded (DER format)	—	—
rid	text	Subject Alternative Name - RID	—	✓
self_signed	boolean	Self-signed certificate ['True', 'False']	✓	—
serial-number	text	Serial number of the certificate	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
signature_algorithm	text	Signature algorithm ['SHA1_WITH_RSA_ENCRYPTION', 'SHA256_WITH_RSA_ENCRYPTION']	✓	—
subject	text	Subject of the certificate	—	—
text	text	Free text description of the certificate	—	—
uri	uri	Subject Alternative Name - URI	—	✓
validity-not-after	datetime	Certificate invalid after that date	✓	—
validity-not-before	datetime	Certificate invalid before that date	✓	—
version	text	Version of the certificate	✓	—
x509-fingerprint-md5	x509-fingerprint-md5	[Insecure] MD5 hash (128 bits)	—	—
x509-fingerprint-sha1	x509-fingerprint-sha1	[Insecure] Secure Hash Algorithm 1 (160 bits)	—	—
x509-fingerprint-sha256	x509-fingerprint-sha256	Secure Hash Algorithm 2 (256 bits)	—	—

yabin

yabin.py generates Yara rules from function prologs, for matching and hunting binaries. ref: <https://github.com/AlienVault-OTX/yabin>.



yabin is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	A description of Yara rule generated.	—	—
version	comment	yabin.py and regex.txt version used for the generation of the yara rules.	—	—
whitelist	comment	Whitelist name used to generate the rules.	—	—
yara	yara	Yara rule generated from -y.	✓	—
yara-hunt	yara	Wide yara rule generated from -yh.	✓	—

yara

An object describing a YARA rule (or a YARA rule name) along with its version.



yara is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
comment	comment	A description of the YARA rule.	—	—
context	text	Context where the YARA rule can be applied ['all', 'disk', 'memory', 'network']	✓	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
version	text	Version of the YARA rule depending where the yara rule is known to work as expected. ['3.7.1']	✓	—
yara	yara	YARA rule.	—	—
yara-rule-name	text	YARA rule name.	—	—

youtube-channel

A YouTube channel.



youtube-channel is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in MISP.

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
about	text	About page of the channel.	—	—
archive	link	Archive of the channel (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts etc.	—	✓
channel-avatar	attachment	A screen capture or exported channel avatar.	—	✓
channel-banner	attachment	A screen capture or exported channel header.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
channel-id	text	Channel id.	—	—
channel-name	text	Channel name.	—	—
description	text	A description of the channel.	✓	—
featured-channel	text	Featured channel names.	—	✓
link	link	Original link to the channel page (supposed harmless).	—	—
url	url	Original URL location of the page (potentially malicious).	—	—

youtube-comment

A YouTube video comment.



youtube-comment is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original comment (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported comment.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
channel-name	text	The name of the channel where it was posted.	—	✓
comment	text	The raw text of the YouTube video comment.	—	—
description	text	A description of the comment.	✓	—
embedded-link	url	Link embedded in the comment (potentially malicious).	—	✓
embedded-safe-link	link	Link embedded in the comment (supposed safe).	—	✓
hashtag	text	Hashtag used in the comment.	—	✓
link	link	Original link to the comment (supposed harmless).	—	—
url	url	Original URL location of the comment (potentially malicious).	—	—
user-account	text	The user account that commented on the YouTube video.	—	—
username-quoted	text	Username who are quoted in the comment.	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
video-title	text	The title of the YouTube video.	—	—

youtube-playlist

A YouTube playlist.



youtube-playlist is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the playlist (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported list of contacts etc.	—	✓
description	text	A description of the playlist.	✓	—
link	link	Original link to the playlist page (supposed harmless).	—	—
playlist-id	text	Playlist id.	—	—
playlist-name	text	Playlist name.	—	—
url	url	Original URL location of the page (potentially malicious).	—	—

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
video-link	link	Link to the video in playlist (supposed harmless).	—	—

youtube-video

A YouTube video.



youtube-video is a MISP object available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
archive	link	Archive of the original YouTube video (Internet Archive, Archive.is, etc).	✓	✓
attachment	attachment	A screen capture or exported YouTube video.	—	✓
channel-name	text	The name of the channel where it was posted.	—	✓
creator	text	The user account that created the YouTube video.	—	—
description	text	A description of the YouTube video.	✓	—
embedded-link	url	Link embedded in the YouTube video description (potentially malicious).	—	✓

Object attribute	MISP attribute type	Description	Disable correlation	Multiple
embedded-safe-link	link	Link embedded in the YouTube video description (supposed safe).	—	✓
hashtag	text	Hashtag used to identify or promote the YouTube video.	—	✓
link	link	Original link to the YouTube video (supposed harmless).	—	—
url	url	Original URL location of the YouTube video (potentially malicious).	—	—
username-quoted	text	Username who are quoted in the YouTube video or description.	—	✓
video-title	text	The title of the YouTube video.	—	—
video-transcript	text	The YouTube video transcript (closed captions).	—	—

Relationships

Default type of relationships in MISP objects.

Relationships are part of MISP object and available in JSON format at [this location](#). The JSON format can be freely reused in your application or automatically enabled in [MISP](#).

Name of relationship	Description	Format
derived-from	The information in the target object is based on information from the source object.	['misp', 'stix-2.0', 'alfred']
executes	This relationship describes an object which executes another object	['misp']
duplicate-of	The referenced source and target objects are semantically duplicates of each other.	['misp', 'stix-2.0']
related-to	The referenced source is related to the target object.	['alfred', 'followthemoney', 'misp', 'stix-2.0']
connected-to	The referenced source is connected to the target object.	['misp', 'stix-1.1']
connected-from	The referenced source is connected from the target object.	['misp', 'stix-1.1']
contains	The referenced source is containing the target object.	['misp', 'stix-1.1', 'alfred']
contained-by	The referenced source is contained by the target object.	['misp', 'stix-1.1']
contained-within	The referenced source is contained within the target object.	['misp', 'stix-1.1']
characterized-by	The referenced source is characterized by the target object.	['misp', 'stix-1.1']
characterizes	The referenced source is characterizing the target object.	['misp', 'stix-1.1']
properties-queried	The referenced source has queried the target object.	['misp', 'stix-1.1']
properties-queried-by	The referenced source is queried by the target object.	['misp', 'stix-1.1']
extracted-from	The referenced source is extracted from the target object.	['misp', 'stix-1.1']
supra-domain-of	The referenced source is a supra domain of the target object.	['misp', 'stix-1.1']
sub-domain-of	The referenced source is a sub domain of the target object.	['misp', 'stix-1.1']

Name of relationship	Description	Format
dropped	The referenced source has dropped the target object.	['misp', 'stix-1.1']
dropped-by	The referenced source is dropped by the target object.	['misp', 'stix-1.1']
downloaded	The referenced source has downloaded the target object.	['misp', 'stix-1.1']
downloaded-from	The referenced source has been downloaded from the target object.	['misp', 'stix-1.1']
resolved-to	The referenced source is resolved to the target object.	['misp', 'stix-1.1']
attributed-to	This referenced source is attributed to the target object.	['misp', 'stix-2.0']
targets	This relationship describes that the source object targets the target object.	['misp', 'stix-2.0']
uses	This relationship describes the use by the source object of the target object.	['misp', 'stix-2.0', 'alfred']
indicates	This relationship describes that the source object indicates the target object.	['misp', 'stix-2.0']
mentions	This relationship describes that the source object mentions the target object.	['misp']
mitigates	This relationship describes a source object which mitigates the target object.	['misp', 'stix-2.0']
variant-of	This relationship describes a source object which is a variant of the target object	['misp', 'stix-2.0', 'alfred']
impersonates	This relationship describes a source object which impersonates the target object	['misp', 'stix-2.0']
retrieved-from	This relationship describes an object retrieved from the target object.	['misp']
authored-by	This relationship describes the author of a specific object.	['misp']

Name of relationship	Description	Format
is-author-of	This relationship describes an object being author by someone.	['misp']
located	This relationship describes the location (of any type) of a specific object.	['misp']
included-in	This relationship describes an object included in another object.	['misp']
includes	This relationship describes an object that includes an other object.	['misp']
analysed-with	This relationship describes an object analysed by another object.	['misp']
claimed-by	This relationship describes an object claimed by another object.	['misp']
communicates-with	This relationship describes an object communicating with another object.	['misp']
drops	This relationship describes an object which drops another object	['misp']
executed-by	This relationship describes an object executed by another object.	['misp']
affects	This relationship describes an object affected by another object.	['misp', 'alfred']
beacons-to	This relationship describes an object beaconing to another object.	['misp', 'alfred']
abuses	This relationship describes an object which abuses another object.	['misp']
exfiltrates-to	This relationship describes an object exfiltrating to another object.	['misp', 'alfred']

Name of relationship	Description	Format
identifies	This relationship describes an object which identifies another object.	['misp', 'alfred']
intercepts	This relationship describes an object which intercepts another object.	['misp', 'alfred']
calls	This relationship describes an object which calls another objects.	['misp']
detected-as	This relationship describes an object which is detected as another object.	['misp']
followed-by	This relationship describes an object which is followed by another object. This can be used when a time reference is missing but a sequence is known.	['misp']
preceding-by	This relationship describes an object which is preceded by another object. This can be used when a time reference is missing but a sequence is known.	['misp']
triggers	This relationship describes an object which triggers another object.	['misp']
vulnerability-of	This relationship describes an object which is a vulnerability of another object.	['cert-eu']
works-like	This relationship describes an object which works like another object.	['cert-eu']
seller-of	This relationship describes an object which is selling another object.	['cert-eu']
seller-on	This relationship describes an object which is selling on another object.	['cert-eu']

Name of relationship	Description	Format
trying-to-obtain-the-exploit	This relationship describes an object which is trying to obtain the exploit described by another object	['cert-eu']
used-by	This relationship describes an object which is used by another object.	['cert-eu', 'stix-2.1']
hosts	This relationship describes an object which hosts another object.	['stix-2.1']
hosted-by	This relationship describes an object hosted by another object.	['stix-2.1']
consists	This relationship describes an object which consists of one or more object(s).	['stix-2.1']
delivers	This relationship describes an object which delivers to one or more object(s).	['stix-2.1']
affiliated	This relationship describes an object which is affiliated with another object.	['cert-eu']
alleged-founder-of	This relationship describes an object which is the alleged founder of another object.	['cert-eu']
attacking-other-group	This relationship describes an object which attacks another object.	['cert-eu']
belongs-to	This relationship describes an object which belongs to another object.	['cert-eu', 'followthemoney']
business-relations	This relationship describes an object which has business relations with another object.	['cert-eu']
claims-to-be-the-founder-of	This relationship describes an object which claims to be the founder of another object.	['cert-eu']
cooperates-with	This relationship describes an object which cooperates with another object.	['cert-eu']

Name of relationship	Description	Format
former-member-of	This relationship describes an object which is a former member of another object.	['cert-eu']
successor-of	This relationship describes an object which is a successor of another object.	['cert-eu']
has-joined	This relationship describes an object which has joined another object.	['cert-eu']
member-of	This relationship describes an object which is a member of another object.	['cert-eu']
primary-member-of	This relationship describes an object which is a primary member of another object.	['cert-eu']
administrator-of	This relationship describes an object which is an administrator of another object.	['cert-eu']
is-in-relation-with	This relationship describes an object which is in relation with another object,	['cert-eu']
provide-support-to	This relationship describes an object which provides support to another object.	['cert-eu']
regional-branch	This relationship describes an object which is a regional branch of another object.	['cert-eu']
similar	This relationship describes an object which is similar to another object.	['cert-eu']
subgroup	This relationship describes an object which is a subgroup of another object.	['cert-eu']
suspected-link	This relationship describes an object which is suspected to be linked with another object.	['misp']
same-as	This relationship describes an object which is the same as another object.	['misp']

Name of relationship	Description	Format
creator-of	This relationship describes an object which is the creator of another object.	['cert-eu']
developer-of	This relationship describes an object which is a developer of another object.	['cert-eu']
uses-for-recon	This relationship describes an object which uses another object for recon.	['cert-eu']
operator-of	This relationship describes an object which is an operator of another object.	['cert-eu']
overlaps	This relationship describes an object which overlaps another object.	['cert-eu']
owner-of	This relationship describes an object which owns another object.	['cert-eu', 'alfred']
publishes-method-for	This relationship describes an object which publishes method for another object.	['cert-eu']
recommends-use-of	This relationship describes an object which recommends the use of another object.	['cert-eu']
released-source-code	This relationship describes an object which released source code of another object.	['cert-eu']
released	This relationship describes an object which release another object.	['cert-eu']
exploits	This relationship describes an object (like a PoC/exploit) which exploits another object (such as a vulnerability object).	['misp']
signed-by	This relationship describes an object signed by another object.	['misp']
delivered-by	This relationship describes an object by another object (such as exploit kit, dropper).	['misp']

Name of relationship	Description	Format
controls	This relationship describes an object which controls another object.	['misp']
annotates	This relationships describes an object which annotates another object.	['misp']
references	This relationships describes an object which references another object or attribute.	['misp']
child-of	A child semantic link to a parent.	['alfred']
parent-of	A parent semantic link to a child.	['alfred', 'misp']
compromised	Represents the semantic link of having compromised something.	['alfred']
connects	The initiator of a connection.	['alfred']
connects-to	The destination or target of a connection.	['alfred']
cover-term-for	Represents the semantic link of one thing being the cover term for another.	['alfred']
disclosed-to	Semantic link indicating where information is disclosed to.	['alfred']
downloads	Represents the semantic link of one thing downloading another.	['alfred']
downloads-from	Represents the semantic link of malware being downloaded from a location.	['alfred']
generated	Represents the semantic link of an alert generated from a signature.	['alfred']
implements	One data object implements another.	['alfred']
initiates	Represents the semantic link of a communication initiating an event.	['alfred']
instance-of	Represents the semantic link between a FILE and FILE_BINARY.	['alfred']

Name of relationship	Description	Format
issuer-of	Represents the semantic link of being the issuer of something.	['alfred']
linked-to	Represents the semantic link of being associated with something.	['alfred', 'followthemoney']
not-relevant-to	Represents the semantic link of a comm that is not relevant to an EVENT.	['alfred']
part-of	Represents the semantic link that defines one thing to be part of another in a hierachial structure from the child to the parent.	['alfred']
processed-by	Represents the semantic link of something has been processed by another program.	['alfred']
produced	Represents the semantic link of something having produced something else.	['alfred']
queried-for	The IP Address or domain being queried for.	['alfred']
query-returned	The IP Address or domain returned as the result of a query.	['alfred']
registered	Represents the semantic link of someone registered some thing.	['alfred']
registered-to	Represents the semantic link of something being registered to.	['alfred']
relates	Represents the semantic link between HBS Comms and communication addresses.	['alfred']
relevant-to	Represents the semantic link of a comm that is relevant to an EVENT.	['alfred']
resolves-to	Represents the semantic link of resolving to something.	['alfred']
responsible-for	Represents the semantic link of some entity being responsible for something.	['alfred']

Name of relationship	Description	Format
seeded	Represents the semantic link of a seeded domain redirecting to another site.	['alfred']
sends	A sends semantic link meaning 'who sends what'.	['alfred']
sends-as-bcc-to	A sends to as BCC semantic link meaning 'what sends to who as BCC'.	['alfred']
sends-as-cc-to	A sends to as CC semantic link meaning 'what sends to who as CC'.	['alfred']
sends-to	A sends to semantic link meaning 'what sends to who'.	['alfred']
spoofed-of	The represents the semantic link of having spoofed something.	['alfred']
subdomain-of	Represents a domain being a subdomain of another.	['alfred']
supersedes	One data object supersedes another.	['alfred']
triggered-on	Represents the semantic link of an alert triggered on an event.	['alfred']
uploads	Represents the semantic link of one thing uploading another.	['alfred']
user-of	The represents the semantic link of being the user of something.	['alfred']
works-for	Represents the semantic link of working for something.	['alfred']
works-with	Represents an object working with another one.	['misp']
witness-of	Represents an object being a witness of something.	['misp']
injects-into	Represents an object injecting something into something	['misp']
injected-into	Represents an object which is injected something into something	['misp']
creates	Represents an object that creates something.	['misp', 'haxpak']

Name of relationship	Description	Format
screenshot-of	Represents an object being the screenshot of something.	['misp']
knows	Represents an object having the knowledge of another object.	['misp']
describes	Represents the semantic link of describing another object.	['misp']
extends	Represents the semantic link of extending another object.	['misp']
writes	Represents an object which writes towards another object or attribute	['misp']
ranked-with	Represents the semantic link of an ASN object being ranked with a BGP-ranking object	['misp']
owns	owns	['followthemoney']
awarded-to	awarded-to	['followthemoney']
directs	directs	['followthemoney']
involved-in	involved-in	['followthemoney']
associated-with	associated-with	['followthemoney']
represents	represents	['followthemoney']
owes	owes	['followthemoney']
preceeds	preceeds	['followthemoney']
documents	documents	['followthemoney']
paid	paid	['followthemoney']
leaks	leaks	['misp']
leaked-by	leaked-by	['misp']
doxed-by	doxed-by	['misp']
alerts	alerts about a specific object	['misp']
legal-address-of	The referenced source object is the legal address of the target.	['misp']
shipping-address-of	The referenced source object is a shipping address of the target.	['misp']
visited	The referenced source object visited the target (for example an address).	['misp']
office-of	The referenced source object is an office of the target.	['misp']

Name of relationship	Description	Format
picture-of	The referenced source object is a picture (photo/image) of the target.	['misp']
pictured-by	The referenced source object is pictured by the target (photo/image).	['misp']
found-on	The referenced source object has been found on the target (device, server).	['misp']
found-in	The referenced source object has been found in the target (document).	['misp']
drives	The referenced source object drives the target described (often a vehicle).	['misp']
friend-of	The referenced source object is a friend of the target object.	['foaf']
acquaintance-of	The referenced source object is an acquaintance of the target object.	['foaf']
sibling-of	The referenced source object is a sibling of the target object.	['foaf']
grandchild-of	The referenced source object is a grandchild of the target object.	['foaf']
spouse-of	The referenced source object is a spouse of the target object.	['foaf']
ennemy-of	The referenced source object is an ennemy of the target object.	['foaf']
antagonist-of	The referenced source object is an antagonist of the target object.	['foaf']
ambivalent-of	The referenced source object is an ambivalent of the target object.	['foaf']
is-a-translation-of	The referenced source object is a translation of the target object.	['misp']
has-met	The referenced source object has met with the target object.	['misp']

Name of relationship	Description	Format
submitted	The referenced source object submitted the referenced target object (to an online anti virus scanner).	['misp']
submitted-by	The referenced source object was submitted (to an online anti virus scanner) by the referenced target object.	['misp']